
REFERENCE [RADIO] id0903e3830000

1. Multipath Noise


Signals from an FM transmitter are a high frequency and similar to beams of light because they do not bend around corners, but they do reflect. Since FM signals can be reflected by obstructions, it is possible to receive both the direct signal and the reflected signal at the same time. This causes a slight delay in reception and may be heard as a broken sound or a distortion.



ac5wzw00003046

2. Flutter/Skip Noise

Signals become weak in valleys between mountains, tall building, and other obstacles. When the vehicle passes through such an area, the reception conditions may change suddenly, resulting in annoying noise.



ac5wzw00003047

3. Stereo and Monaural Receptions

 As signals become weak, noise may appear more in stereo reception. Comparing to stereo reception, noise in monaural receptions is relatively less striking.

Measures in Audio System

Separation control

· Utilizing the characteristic of monaural reception that noise is relatively less striking than stereo reception, the audio system automatically changes the reception from stereo to monaural and lessens annoying noise when signals become weak or a multipath phenomenon occurs.

High tone control

When signals become weak or a multipath phenomenon occurs, the audio system restrains volume level in high frequency band and lessens annoying noise.

Effect Setting of Separation Control and High Tone Control


The separation and high tone controls influence sound quality, Therefore they are specifically tuned for individual model. (Comparison of characteristic must be done on the same models)

High tone setting	Less effective range	\Rightarrow	Noise is conspicuous
Noise restraint setting	Wider effective range	\Rightarrow	
			20011111100001036

acxuuw00001936

Remarks

Signals tend to reach longer distances at night. It is conspicuous in AM signals, several audio functions may stop
due to foreign broadcasting station or noise. Though the audio system restrains sensitivity of SEEK and SCAN
functions at night, the audio system may select other than desired broadcasting station when signals are
considerably strong. This function is linked to the parking light. When the parking light or headlight is turned on,
SEEK and SCAN may not function for weak signals.



acxuuw00001937