

DEBUGGING REPORT

FAILURE SIMULATION

1) Element not Found

Steps Used:

1. Open Selectors.ts
2. Change the Full Name locator
FullName: '#userName'
to
FullName: '#user'
3. Run : npx cucumber-js

Error Log:

```
Failed scenarios:
  1) Submit form with multiple fields # features\form.feature:6
    when user fills the form with following data: # step-definitions\form.steps.ts:13
      | field | value |
      | name  | John  |
      | email | john@test.com |
      | address | newYork |
      locator.fill: Timeout 30000ms exceeded.
      Call log:
        - waiting for locator('#user')
          at FormPage.fillForm (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_38DD\pages\FormPage.ts:37:29)
          at CustomWorld.<anonymous> (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_38DD\step-definitions\form.steps.ts:28:24)
```

Root Cause:

The locator did not match any element on the page because of incorrect CSS Locator.
Since Playwright could not find the element, it waited until the timeout period expired.

Resolution:

Identify the actual locator using DevTools and correct the locator

2) Assertion mismatch

Steps used:

1. Open Form.ts
2. Change :

```
await expect(this.outputName).toContainText(data.name);
```

to

```
await expect(this.outputName).toContainText("Peter");
```

3. Run : npx cucumber-js

Error Log:

```
Failed scenarios:
  1) Submit form with multiple fields # features\form.feature:6
    Then form should be submitted successfully # step-definitions\form.steps.ts:33
      Error: expect(locator).toContainText(expected) failed

      locator: locator('#name')
      Expected substring: "Peter"
      Received string:   "Name:John"
      Timeout: 5000ms

      Call log:
        - Expect "to.have.text" with timeout 5000ms
        - waiting for locator('#name')
          13 x locator resolved to <p id="name" class="mb-1">Name:John</p>
            - unexpected value "Name:John"

      at captureRawStack (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\node_modules\playwright-core\lib\coreBundle.js:3172:17)
      at callMatcherAsStep (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\node_modules\playwright\lib\matchers\expect.js:12875:57)
      at Object.toContainText (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\node_modules\playwright\lib\matchers\expect.js:12865:23)
      at FormPage.verifySubmission (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\pages\FormPage.ts:0:39)
      at CustomWorld.<anonymous> (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\step-definitions\form.steps.ts:37:24)

8 scenarios (7 passed, 1 failed)
44 steps (43 passed, 1 failed)
0m 54.57s (0m 53.965s executing your code)
```

Root Cause:

The expected Value in the assertion did not match the actual value displayed by the application.

Resolution:

Do not verify directly by a text and instead create an object and store it directly and then verify it using data.name

3) Incorrect Locator

Steps used:

1. Open Selectors.ts
2. Modify '#submit' to '#sumbit'
3. Run: npx cucumber-js

Error log:

```
..F-.....
Failed scenarios:
  1) Submit form with multiple fields # features\form.feature:6
     when user fills the form with following data: # step-definitions\form.steps.ts:13
       | field | value |
       | name  | John  |
       | email | john@test.com |
       | address | newYork |
       locator.click: Timeout 30000ms exceeded.
       Call log:
         - waiting for locator('#sumbit')
           at FormPage.submit (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\pages\FormPage.ts:43:33)
           at CustomWorld.<anonymous> (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\step-definitions\form.steps.ts:29:24)

8 scenarios (7 passed, 1 failed)
44 steps (42 passed, 1 skipped, 1 failed)
```

Root Cause:

The locator pointed to a non-existent element, preventing Playwright from performing the click action.

Resolution:

Carefully identify the correct locator using pick locator or DevTools and correct the locator.

4) Navigation Failure

Steps Used:

1. Open routes.ts
2. Change the demo link
3. Run : npx cucumber-js

Error Log:

```
..F-.....
Failed scenarios:
  1) Submit form with multiple fields # features\form.feature:6
    When user fills the form with following data: # step-definitions\form.steps.ts:13
      | field | value |
      | name  | John  |
      | email | john@test.com |
      | address | newYork |
      locator.fill: Timeout 30000ms exceeded.
      Call log:
        - waiting for locator('#userName')
          at FormPage.fillForm (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\pages\FormPage.ts:37:29)
          at CustomWorld.<anonymous> (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\step-definitions\form.steps.ts:28:24)
8 scenarios (7 passed, 1 failed)
44 steps (42 passed, 1 skipped, 1 failed)
```

Root Cause:

The automation attempted to navigate to an invalid URL, causing the application page to not load.

Resolution:

Restore the original URL

5) Undefined Step Definition

Steps Used:

1. Open form.feature
2. Change : Then form should be submitted successfully to Then form submission should be successful.

3. Run: npx cucumber-js

Error Log:

```
...U.....

Undefined scenarios:
  1) Submit form with multiple fields # features\form.feature:6
    Then form submission should be Successful

8 scenarios (7 passed, 1 undefined)
44 steps (43 passed, 1 undefined)
0m 40.448s (0m 40.398s executing your code)

You can implement missing steps with the snippets below:

Then('form submission should be Successful', function () {
  // Write code here that turns the phrase above into concrete actions
  return 'pending';
});
```

Root Cause:

The step text no longer matched any existing step definition. Cucumber performs an exact match between file steps and step definition patterns.

Resolution:

Implement a matching step definition

TIMEOUT SIMULATION

1) Page Load Timeout

Steps Used:

1. Open FormPage.ts
2. Modify the goto() method as:

```
await this.page.goto(routes.form,{timeout:1});
```

3. Run: npx cucumber-js

Error log:

```
.F-----
Failed scenarios:
  1) Submit form with multiple fields # features\form.feature:6
    Given user is on form page # step-definitions\form.steps.ts:5
      page.goto: Timeout 1ms exceeded.
      Call log:
        - navigating to "https://demoqa.com/text-box", waiting until "load"

        at FormPage.goto (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\pages\FormPage.ts:29:25)
        at CustomWorld.<anonymous> (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\step-definitions\form.steps.ts:9:24)

8 scenarios (7 passed, 1 failed)
44 steps (41 passed, 2 skipped, 1 failed)
1m 6.919s (1m 6.888s executing your code)
```

Root Cause:

The page did not finish loading within the specified timeout. Since the timeout value was intentionally set too low, Playwright aborted the navigation.

Resolution:

Increase the timeout or remove the custom timeout.

2) Element Timeout

Steps Used:

1. Open selectors.ts
2. Change the submit button locator
3. Run: npx cucumber-js

Error Log:

```

..F-.....
Failed scenarios:
  1) Submit form with multiple fields # features\form.feature:6
    when user fills the form with following data: # step-definitions\form.steps.ts:13
      | field | value |
      | name  | John  |
      | email | john@test.com |
      | address | newYork |
      locator.click: Timeout 30000ms exceeded.
      Call log:
        - waiting for locator('#submit')
          at FormPage.submit (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\pages\FormPage.ts:43:33)
          at CustomWorld.<anonymous> (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\step-definitions\form.steps.ts:29:24)

8 scenarios (7 passed, 1 failed)
44 steps (42 passed, 1 skipped, 1 failed)

```

Root Cause:

Playwright waited for the element to become available, but the locator never matched any element on the page, causing an element timeout

Resolution:

Carefully identify the correct locator using pick locator or DevTools and correct the locator or restore the correct locator.

3) Step Timeout

Steps Used:

1. Open form.step.ts
2. Inside any step add:
 Await new Promise(resolve=>setTimeout(resolve,70000));
3. Run : npx cucumber-js

Error Log:

```

PS C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD> npx cucumber-js
..F-.....

Failed scenarios:
  1) Submit form with multiple fields # features\form.feature:6
    when user fills the form with following data: # step-definitions\form.steps.ts:13
      | field | value |
      | name  | John  |
      | email | john@test.com |
      | address | newYork |
      Error: function timed out, ensure the promise resolves within 60000 milliseconds
        at Timeout.<anonymous> (C:\Users\dnyanesh.panchal\Desktop\AutomationTask_3BDD\node_modules\@cucumber\cu
cumber\src\time.ts:50:14)
        at listOnTimeout (node:internal/timers:605:17)
        at processTimers (node:internal/timers:541:7)

8 scenarios (7 passed, 1 failed)
44 steps (42 passed, 1 skipped, 1 failed)
1m 45.265s (1m 45.208s executing your code)

```

Root Cause:

The step execution exceeded the default Cucumber timeout of 60 seconds. Since the promise intentionally delayed execution for 70 seconds, Cucumber terminated the step.

Resolution:

Remove the artificial delay or increase the timeout if the step legitimately requires more timeout