

Experiment No. 7

Output:

The image shows a Cisco Packet Tracer network diagram and a PC1 command prompt window. The network diagram features a central 2950 Switch connected to a Server-PT (Server0) and two PC-PTs (PC0 and PC1). The PC1 window displays the following output:

```
Command Prompt
C:\>ipconfig
Connection-specific DNS Suffix...: 
Link-local IPv6 Address . . . . .: 
IPv6 Address. . . . .: 
IPv4 Address. . . . .: 0.0.0.0
Subnet Mask . . . . .: 0.0.0.0
Default Gateway. . . . .: 
C:\>ftp 192.168.1.3
Trying to connect...192.168.1.3
Connected to 192.168.1.3
220- Welcome to Ft Pp server
Username: Cisco
331- Username ok, need password
Password:
230- Logged in
(passive mode On)
ftp>dir

Listing /ftp directory from 192.168.1.3:
 0 : asa442-k8.bin                    5571584
 1 : asa553-k8.bin                    30468096
 2 : c1841-advipservicesk9-mz.124-15.T1.bin 33591768
 3 : c1841-ipbase-mz.123-14.T7.bin    13832032
 4 : c1841-ipbasek9-mz.124-12.bin    16599160
 5 : c1800-universalk9-mz.SPA.155-3.M4a.bin 33591768
 6 : c2600-advipservicesk9-mz.124-15.T1.bin 33591768
 7 : c2600-i-mz.122-28.bin           5571584
 8 : c2600-ipbasek9-mz.124-8.bin     13169700
 9 : c2800nm-advipservicesk9-mz.124-15.T1.bin 50938004
10 : c2800nm-advipservicesk9-mz.151-4.M4a.bin 33591768
11 : c2800nm-ipbase-mz.123-14.T7.bin  5571584
12 : c2800nm-ipbasek9-mz.124-8.bin    15522644
13 : c2900-universalk9-mz.SPA.155-3.M4a.bin 33591768
14 : c2950-16q12-mz.121-22.EAa.bin  3058048
15 : c2950-16q12-mz.121-22.EAa.bin  3117390
16 : c2960-lanbase-mz.122-25.FXa.bin  4414921
17 : c2960-lanbase-mz.122-25.SR1a.bin  4670455
18 : c2960-lanbasek9-mz.150-2.SF4a.bin 4670455
19 : c3560-advipservicesk9-mz.122-37.SF1a.bin 8662192
20 : c3560-advipservicesk9-mz.122-46.SF1a.bin 10712379
21 : c800-universalk9-mz.SPA.152-4.M4a.bin 33591768
22 : c800-universalk9-mz.SPA.152-4.M4a.bin 33028436
```

The image shows a Cisco Packet Tracer network diagram and a Realtime Simulation packet capture table. The network diagram is identical to the one above. The Realtime Simulation packet capture table shows the following data:

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
PC0	Successful	PC0	PC1	ICMP		0.000	N	0	(edit)	(delete)
PC0	Successful	PC0	Server0	ICMP		0.000	N	1	(edit)	(delete)
PC0	Successful	PC0	PC1	ICMP		0.000	N	2	(edit)	(delete)
PC0	Successful	PC0	Server0	ICMP		0.000	N	3	(edit)	(delete)

Cisco Packet Tracer
File Edit Options View Tools Extensions Window Help

Logical Physical x: 330, y: 205

```

graph TD
    Switch[2901-KT Switch] --- Server0[Server-PT Server0]
    Switch --- PC0[PC-PT PC0]
    Switch --- PC1[PC-PT PC1]
  
```

Simulation Panel

Event List

Vis	Time(sec)	Last Device
0.002	--	--
0.003	--	PC0
0.003	--	Switch0
0.003	--	PC1
0.003	--	--
0.004	--	PC0
0.004	--	Switch0
0.004	--	Server0
0.004	--	Switch0
Visible 0.005	--	Switch0
Visible 0.005	--	PC1
Visible 0.005	--	Switch0

Reset Simulation Constant Delay Captured to 0.005 s

Play Controls

Event List Filters - Visible Events

ACL Filter, ARP, BGP, Bluetooth, CAPWAP, CDP, DHCP, DHCPv6, DNS, DTP, EAPOL, EIGRP, EIGRPv6, FTP, H.323, HSRP, HSRPv6, HTTP, HTTPS, ICMP, ICMPv6, IEC, IPsec, ISAKMP, IoT, IoT TCP, LACP, LLDP, MODBUS, Meraki, NDP, NETFLOW, NTP, OSPF, OSPFv6, PAP, POP3, PPP, PPPoE, PTP, Profinet, RADIUS, REP, RIP, RIPng, RTP, SCCP, SMTP, SNMP, SSH, STP, SYSLOG, TACACS, TCP, TFTP, Telnet, UDP, USB, VTP

Edit Filters Show All/None

Time: 00:14:07.618 PLAY CONTROLS

Scenario 0

New Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
●	Successful	PC0	PC1	ICMP		0.000	N	0	(edit)	(delete)
●	Successful	PC0	Server0	ICMP		0.000	N	1	(edit)	(delete)
●	In Progress	PC0	PC1	ICMP		0.000	N	2	(edit)	(delete)
●	In Progress	PC0	Server0	ICMP		0.000	N	3	(edit)	(delete)