

Magnet Project API Documentation

Authentication & User Management APIs

Auth Routes

1. Register User

- **POST** /api/auth/register
 - **Description:** Register a new customer user.
 - **Body:**
 - **firstname** (string, required)
 - **lastname** (string, required)
 - **email** (string, required)
 - **phone** (string, optional)
 - **password** (string, required)
 - **country** (string, required)
 - **language** (string, optional, default: 'en')
 - **Response:**
 - **201 Created:** User info + JWT token
-

2. Register Business

- **POST** /api/auth/business-register
 - **Description:** Register a new business user (requires approval).
 - **Body:**
 - **firstname, lastname, email, password, crNumber, vatNumber, companyName, companyType, country, city, district, streetName, phone** (all required)
 - **Response:**
 - **201 Created:** Business info (under review)
-

3. Send Email OTP

- **POST** /api/auth/send-email-otp
 - **Description:** Send an OTP to a new email (fails if email already exists).
 - **Body:**
 - **email** (string, required)
 - **Response:**
 - **200 OK:** Success message
-

4. Send Phone OTP

- **POST** /api/auth/send-phone-otp

- **Description:** Send an OTP to a new phone (fails if phone already exists).
 - **Body:**
 - `phone` (string, required)
 - **Response:**
 - `200 OK`: Success message
-

5. Confirm OTP

- **POST** `/api/auth/confirm-otp`
 - **Description:** Confirm an OTP for email or phone verification.
 - **Body:**
 - `identifier` (string, required)
 - `otp` (string, required)
 - **Response:**
 - `200 OK`: Email/Phone verified
-

6. Login

- **POST** `/api/auth/login`
 - **Description:** Login with email/phone and password.
 - **Body:**
 - `identifier` (email or phone, required)
 - `password` (string, required)
 - **Response:**
 - `200 OK`: User info + JWT token
-

7. Login with OTP

- **POST** `/api/auth/login-with-otp`
 - **Description:** Request an OTP for login (email or phone).
 - **Body:**
 - `identifier` (email or phone, required)
 - **Response:**
 - `200 OK`: OTP sent
-

8. Forgot Password

- **POST** `/api/auth/forgot-password`
 - **Description:** Change password for authenticated user.
 - **Headers:** `Authorization: Bearer <token>`
 - **Body:**
 - `newPassword` (string, required)
 - **Response:**
 - `200 OK`: Password updated
-

User Routes

1. Get Current User Profile

- **GET** /api/user/profile
 - **Description:** Get the profile of the authenticated user (**customer only**).
 - **Headers:** Authorization: Bearer <token>
 - **Role:** customer (requires 'customer' role)
 - **Response:**
 - 200 OK: User info
-

2. Update User Profile

- **PUT** /api/user/profile
 - **Description:** Update the profile of the authenticated user (**customer only**).
 - **Headers:** Authorization: Bearer <token>
 - **Role:** customer (requires 'customer' role)
 - **Body:**
 - firstname, lastname, email, phone, country, language (all optional)
 - **Response:**
 - 200 OK: Updated user info
-

3. Get All Business Registration Requests

- **GET** /api/user/business-requests?status=pending&page=1&limit=10
 - **Description:** Get paginated business registration requests (admin/employee only).
 - **Headers:** Authorization: Bearer <token>
 - **Query Params:**
 - status (optional, default: 'pending')
 - page (optional, default: 1)
 - limit (optional, default: 10)
 - **Response:**
 - 200 OK: List of businesses (paginated)
-

4. Approve/Reject Business Registration

- **POST** /api/user/business-approval
 - **Description:** Approve or reject a business registration (admin/employee only).
 - **Headers:** Authorization: Bearer <token>
 - **Body:**
 - businessId (string, required)
 - status (string, required: 'approved' or 'rejected')
 - reason (string, optional, required if status is 'rejected')
 - **Response:**
 - 200 OK: Business approval status
-

5. Get Business Details by ID

- **GET** `/api/user/business/:businessId`
 - **Description:** Get details of a business user by ID (admin/employee only).
 - **Headers:** `Authorization: Bearer <token>`
 - **Params:**
 - `businessId` (string, required)
 - **Response:**
 - `200 OK`: Business info
-

6. Get Business Profile (for Business Users)

- **GET** `/api/user/business-profile`
 - **Description:** Get the profile of the authenticated business user.
 - **Headers:** `Authorization: Bearer <token>`
 - **Response:**
 - `200 OK`: Business user info
-

7. Favourites APIs (Customer Only)

- **POST** `/api/user/favourites/:productId`
 - **Description:** Add a product to the customer's favourites.
 - **DELETE** `/api/user/favourites/:productId`
 - **Description:** Remove a product from the customer's favourites.
 - **GET** `/api/user/favourites`
 - **Description:** Get all favourite products for the customer.
 - **Headers:** `Authorization: Bearer <token>`
-

8. Cart APIs (Customer Only)

- **POST** `/api/user/cart`
 - **Description:** Add a product to the customer's cart or increase its quantity.
 - **Body:** `{ productId, quantity }`
 - **DELETE** `/api/user/cart/:productId`
 - **Description:** Remove a product from the customer's cart.
 - **PUT** `/api/user/cart/:productId`
 - **Description:** Update the quantity of a product in the customer's cart.
 - **Body:** `{ quantity }`
 - **GET** `/api/user/cart`
 - **Description:** Get all products in the customer's cart.
 - **Headers:** `Authorization: Bearer <token>`
-

Product Routes

1. Get Products

- **GET** /api/products
 - **Description:** Get all approved products (public, any user can call).
 - **Response:**
 - **200 OK:** List of products
-

2. Add Product

- **POST** /api/products
 - **Description:** Business user adds a new product (pending approval).
 - **Headers:** **Authorization:** Bearer <token>
 - **Body:**
 - **title, description, image, price, rate, amount, inStock** (all required except image and rate)
 - **Response:**
 - **201 Created:** Product info (pending approval)
-

3. Update Product

- **PUT** /api/products/:productId
 - **Description:** Business user updates their own product (pending approval).
 - **Headers:** **Authorization:** Bearer <token>
 - **Body:**
 - **title, description, image, price, rate, amount, inStock** (all optional)
 - **Response:**
 - **200 OK:** Updated product info (pending approval)
-

4. Product Approval

- **POST** /api/products/product-approval
 - **Description:** Admin/employee approves or rejects a product.
 - **Headers:** **Authorization:** Bearer <token>
 - **Body:**
 - **productId** (string, required)
 - **status** (string, required: 'approved' or 'rejected')
 - **Response:**
 - **200 OK:** Product approval status
-

5. Delete Product

- **DELETE** /api/products/:productId
 - **Description:** Business user deletes their own product, or admin/employee deletes any product (sends email to business user on delete).
 - **Headers:** **Authorization:** Bearer <token>
 - **Response:**
 - **200 OK:** Product deleted
-

Notes

- All endpoints require authentication unless stated otherwise.
 - Role-based access is enforced for some endpoints (Admin, Employee, Business, Customer).
 - For endpoints that update or approve/reject, validation middleware is used.
 - **The GET and PUT `/api/user/profile` endpoints are protected by the `requireCustomer` middleware, allowing only users with the 'customer' role to access them.**
-

For more details or example requests, refer to the code or request further examples.