

Magnet Project API Documentation

Route Authentication & Role Protection Summary

| Module | Route/Action | Public | Auth Required | Role(s) Required |
|------------|---|--------|---------------|--|
| Products | GET /api/products | No | Yes | Any authenticated user |
| | GET /api/products/:id | No | Yes | Any authenticated user |
| | POST /api/products/addProductsByBusiness | No | Yes | business |
| | POST /api/products/addProductsByMagnet_employee | No | Yes | magnet_employee, admin |
| | PUT /api/products/:id | No | Yes | business (own), admin, magnet_employee |
| | DELETE /api/products/:id | No | Yes | business (own), admin, magnet_employee |
| | PUT /api/products/:id/approve | No | Yes | admin, magnet_employee |
| | PUT /api/products/:id/decline | No | Yes | admin, magnet_employee |
| Categories | GET /api/categories | Yes | No | None |
| | POST /api/categories | No | Yes | business, admin, magnet_employee |
| | PUT /api/categories/:id | No | Yes | business (own), admin, magnet_employee |
| | DELETE /api/categories/:id | No | Yes | business (own), admin, magnet_employee |
| Orders | GET /api/orders/status-options | Yes | No | None |
| | POST /api/orders | No | Yes | customer |
| | GET /api/orders/my | No | Yes | customer |
| | GET /api/orders/business-products | No | Yes | business |

| Module | Route/Action | Public | Auth Required | Role(s) Required |
|----------|--|--------|---------------|--|
| | GET /api/orders/:id | No | Yes | admin, magnet_employee, customer (own) |
| | GET /api/orders | No | Yes | admin, magnet_employee |
| | PUT /api/orders/:id/status | No | Yes | admin, magnet_employee |
| Reviews | POST /api/reviews/products/:id/reviews | No | Yes | customer |
| | GET /api/reviews/products/:id/reviews | Yes | No | None |
| | GET /api/reviews/business-products-reviews | No | Yes | business |
| | DELETE /api/reviews/:id | No | Yes | admin, magnet_employee |
| Wishlist | GET /api/wishlist | No | Yes | customer |
| | POST /api/wishlist | No | Yes | customer |
| | DELETE /api/wishlist/:productId | No | Yes | customer |
| Address | GET /api/addresses | No | Yes | customer |
| | POST /api/addresses | No | Yes | customer |
| | PUT /api/addresses/:id | No | Yes | customer |
| | DELETE /api/addresses/:id | No | Yes | customer |
| User | GET /api/user/profile | No | Yes | customer |
| | PUT /api/user/profile | No | Yes | customer |
| | GET /api/user/business-requests | No | Yes | admin, magnet_employee |
| | POST /api/user/business-approval | No | Yes | admin, magnet_employee |
| | GET /api/user/business/:businessId | No | Yes | admin, magnet_employee |
| | GET /api/user/business-profile | No | Yes | business, admin, magnet_employee |
| Admin | POST /api/admin/users | No | Yes | admin |
| | GET /api/admin/users | No | Yes | admin |
| | GET /api/admin/users/stats | No | Yes | admin |

| Module | Route/Action | Public | Auth Required | Role(s) Required |
|--------|---|--------|---------------|---------------------------|
| | GET /api/admin/users/:id | No | Yes | admin |
| | PUT /api/admin/users/:id | No | Yes | admin |
| | DELETE /api/admin/users/:id | No | Yes | admin |
| | PUT /api/admin/users/:id/disallow | No | Yes | admin |
| | PUT /api/admin/users/:id/allow | No | Yes | admin |
| | PUT /api/admin/users/:id/verify-email | No | Yes | admin, magnet_employee |
| | PUT /api/admin/users/:id/unverify-email | No | Yes | admin, magnet_employee |
| | PUT /api/admin/users/:id/verify-phone | No | Yes | admin, magnet_employee |
| | PUT /api/admin/users/:id/unverify-phone | No | Yes | admin, magnet_employee |
| | GET /api/admin/wishlists | No | Yes | admin |
| | GET /api/admin/wishlists/:id | No | Yes | admin |
| | POST /api/admin/wishlists | No | Yes | admin |
| | PUT /api/admin/wishlists/:id | No | Yes | admin |
| | DELETE /api/admin/wishlists/:id | No | Yes | admin |
| | GET /api/admin/reviews | No | Yes | admin |
| | GET /api/admin/reviews/:id | No | Yes | admin |
| | POST /api/admin/reviews | No | Yes | admin |
| | PUT /api/admin/reviews/:id | No | Yes | admin |
| | PUT /api/admin/reviews/:id/reject | No | Yes | admin |

|| DELETE /api/admin/reviews/:id | No | Yes | admin || | GET /api/admin/addresses | No | Yes | admin || | GET /api/admin/addresses/:id | No | Yes | admin || | POST /api/admin/addresses | No | Yes | admin || | PUT /api/admin/addresses/:id | No | Yes | admin || | DELETE /api/admin/addresses/:id | No | Yes | admin || | GET /api/admin/orders | No | Yes | admin || | GET /api/admin/orders/:id | No | Yes | admin || | POST /api/admin/orders | No | Yes | admin || | PUT /api/admin/orders/:id | No | Yes | admin || | DELETE /api/admin/orders/:id | No | Yes | admin || Auth | Registration/Login/OTP | Yes | No | None || | Forgot Password | No | Yes | Any authenticated user |

Notes

- **Auth Required:** Requires a valid JWT token in the **Authorization** header.
 - **Role(s) Required:** Requires the user to have one of the listed roles. If "(own)" is specified, the user must own the resource (e.g., their own product or order).
 - **Public:** Anyone can access, no authentication required.
 - **All:** All HTTP methods (GET, POST, PUT, DELETE) for that endpoint.
 - **Business (if owns product in order):** Business user can access if any product in the order is owned by them (see order tracking section).
 - **Enhanced Data Population:** All APIs now return complete user information instead of just IDs for related fields (owner, approvedBy, createdBy, customer, user, etc.).
-

Message Format

All API responses return bilingual messages in both English and Arabic for every endpoint, including all errors and successes. The system uses a centralized messages.js file to ensure consistency across all modules (auth, user, product, order, address, category, review, wishlist, etc.).

Example:

```
{
  "status": "success",
  "message": {
    "en": "User registered successfully",
    "ar": "تم تسجيل المستخدم بنجاح"
  },
  "data": { ... }
}
```

Enhanced User Data Population

All APIs now return complete user information instead of just IDs for related fields. This includes:

User Object Format

When user data is populated, it returns:

```
{
  "id": "user_id",
  "firstname": "John",
  "lastname": "Doe",
  "email": "john@example.com",
  "role": "customer"
}
```

Business User Object Format

For business users, additional company information is included:

```
{
  "id": "user_id",
  "firstname": "Business",
  "lastname": "Owner",
  "email": "business@example.com",
  "role": "business",
  "companyName": "ABC Company"
}
```

Admin User Object Format

For admin users who approved content:

```
{
  "id": "admin_id",
  "firstname": "Admin",
  "lastname": "User",
  "email": "admin@example.com",
  "role": "admin"
}
```

Populated Fields

The following fields are now populated with complete user objects instead of IDs:

- **Product Owner:** `product.owner` - Returns business user details
- **Product Approved By:** `product.approvedBy` - Returns admin/employee details
- **Category Created By:** `category.createdBy` - Returns creator details
- **Review User:** `review.user` - Returns reviewer details
- **Order Customer:** `order.customer` - Returns customer details
- **Address User:** `address.user` - Returns address owner details
- **Wishlist User:** `wishlist.user` - Returns wishlist owner details
- **Business Approved By:** `business.businessInfo.approvedBy` - Returns approver details

Example Enhanced Responses

Product Response

```
{
  "status": "success",
  "data": {
    "product": {
      "id": "product_id",
      "name": "Product Name",

```

```
    "code": "PROD001",
    "owner": {
      "id": "owner_id",
      "firstname": "Business",
      "lastname": "Owner",
      "email": "business@example.com",
      "companyName": "ABC Company"
    },
    "approvedBy": {
      "id": "admin_id",
      "firstname": "Admin",
      "lastname": "User",
      "email": "admin@example.com",
      "role": "admin"
    }
  }
}
```

Review Response

```
{
  "status": "success",
  "data": {
    "review": {
      "id": "review_id",
      "rating": 5,
      "comment": "Great product!",
      "user": {
        "id": "user_id",
        "firstname": "John",
        "lastname": "Doe",
        "email": "john@example.com",
        "role": "customer"
      },
    },
    "product": {
      "id": "product_id",
      "name": "Product Name",
      "owner": {
        "id": "owner_id",
        "firstname": "Business",
        "lastname": "Owner",
        "email": "business@example.com",
        "companyName": "ABC Company"
      }
    }
  }
}
```

Order Response

```
{
  "status": "success",
  "data": {
    "order": {
      "id": "order_id",
      "status": "pending",
      "customer": {
        "id": "customer_id",
        "firstname": "John",
        "lastname": "Doe",
        "email": "john@example.com",
        "role": "customer"
      },
      "items": [
        {
          "product": {
            "id": "product_id",
            "name": "Product Name",
            "owner": {
              "id": "owner_id",
              "firstname": "Business",
              "lastname": "Owner",
              "email": "business@example.com",
              "companyName": "ABC Company"
            }
          },
          "quantity": 2
        }
      ]
    }
  }
}
```

Verification Rules

Phone Number Verification

- **If phone number is provided:** Only the phone is verified (`isPhoneVerified = true`, `isEmailVerified = false`)
- **If no phone number is provided:** Only the email is verified (`isEmailVerified = true`, `isPhoneVerified = false`)

This applies to both customer and business registration.

Validation Rules

Email Validation

- **Format:** Must match email format: `^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}$`
- **Required:** Email is required for all user registrations
- **Unique:** Email must be unique across all users

Phone Validation

- **Format:** Must match phone format: `^\+?[1-9]\d{1,14}$`
- **Optional:** Phone number is optional for customer registration
- **Unique:** If provided, phone must be unique across all users
- **Saudi Numbers:** Saudi phone numbers are automatically verified

Password Requirements

- **Minimum Length:** 8 characters
- **Complexity:** Must contain at least:
 - One uppercase letter (A-Z)
 - One lowercase letter (a-z)
 - One number (0-9)
- **Pattern:** `^(?=.*[a-z])(?=.*[A-Z])(?=.*\d)`

Name Validation

- **First Name:** 2-50 characters, required
- **Last Name:** 2-50 characters, required
- **Trim:** Leading and trailing whitespace is automatically removed

Business Registration Validation

- **CR Number:** 1-50 characters, required
- **VAT Number:** 1-50 characters, required
- **Company Name:** 2-100 characters, required
- **Company Type:** 2-100 characters, required
- **Country:** 2-50 characters, required
- **City:** 2-50 characters, required
- **District:** 2-50 characters, required
- **Street Name:** 2-100 characters, required

Product Validation

- **Category:** Required bilingual object { en: "English Category", ar: "Arabic Category" }
- **Name:** Required bilingual object { en: "English Name", ar: "Arabic Name" }
- **Description:** Optional bilingual object { en: "English Description", ar: "Arabic Description" }
- **Unit:** Optional bilingual object { en: "English Unit", ar: "Arabic Unit" }
- **Custom Fields:** Array of objects, minimum 3, maximum 10
 - Each object must have **key** and **value** properties
 - Both key and value must be bilingual objects: { en: "English", ar: "Arabic" }

- **Code:** Optional, auto-generated if not provided
- **Images:** Optional array of strings (URLs)
- **Attachments:** Optional array of product IDs
- **Min Order:** Optional number
- **Price Per Unit:** Optional string
- **Stock:** Optional number

Address Validation

- **Address Line 1:** Required string
- **Address Line 2:** Optional string
- **City:** Required string
- **State:** Required string
- **Postal Code:** Required string
- **Country:** Required string

Category Validation

- **Name:** Required bilingual object { en: "English", ar: "Arabic" }
- **Description:** Optional bilingual object { en: "English", ar: "Arabic" }

Review Validation

- **Rating:** Required number, min: 1, max: 5
- **Comment:** Optional string

Admin User Management Validation

- **Role:** Must be one of: 'admin', 'magnet_employee', 'business', 'customer'
- **Business Info:** Required for business users
 - **CR Number:** 1-50 characters, required for business users
 - **VAT Number:** 1-50 characters, required for business users
 - **Company Name:** 2-100 characters, required for business users
 - **Company Type:** 2-100 characters, required for business users
 - **City:** 2-50 characters, required for business users
 - **District:** 2-50 characters, required for business users
 - **Street Name:** 2-100 characters, required for business users
- **Disallow Reason:** Required when disallowing a user
- **Self-Protection:** Admins cannot disallow or delete their own accounts
- **Admin Protection:** Admin users cannot be disallowed by other admins

Order Validation

- **Customer:** Required user ID
- **Items:** Required array of order items
 - Each item must have **product** (product ID) and **quantity** (number)
- **Shipping Address:** Required address ID
- **Status:** Optional, defaults to 'pending', enum: 'pending', 'confirmed', 'shipped', 'delivered', 'cancelled' (English values only, backend converts to bilingual)

- **Valid English Statuses:** ['pending', 'confirmed', 'shipped', 'delivered', 'cancelled']
 - **Valid Arabic Statuses:** ['قيد الانتظار', 'مؤكد', 'تم الشحن', 'تم التوصيل', 'ملغي']
 - **Validation:** Backend validates status using `Order.isValidStatus()` method
 - **Conversion:** Backend converts English status to bilingual using `Order.convertStatusToBilingual()` method
-

Auth Routes

1. Register User

- **POST** `/api/auth/register`
 - **Description:** Register a new customer user with automatic verification based on phone number presence.
 - **Body:**
 - `firstname` (string, required)
 - `lastname` (string, required)
 - `email` (string, required)
 - `phone` (string, optional)
 - `password` (string, required)
 - `country` (string, required)
 - `language` (string, optional, default: 'en')
 - **Verification Logic:**
 - If `phone` is provided: `isPhoneVerified = true, isEmailVerified = false`
 - If `phone` is not provided: `isEmailVerified = true, isPhoneVerified = false`
 - **Response:**
 - **201 Created:** User info + JWT token with verification status
-

2. Register Business

- **POST** `/api/auth/business-register`
 - **Description:** Register a new business user (requires approval) with automatic verification based on phone number presence.
 - **Body:**
 - `firstname, lastname, email, password, crNumber, vatNumber, companyName, companyType, country, city, district, streetName, phone` (all required)
 - **Verification Logic:**
 - If `phone` is provided: `isPhoneVerified = true, isEmailVerified = false`
 - If `phone` is not provided: `isEmailVerified = true, isPhoneVerified = false`
 - **Response:**
 - **201 Created:** Business info (under review) with verification status
-

3. Send Email OTP

- **POST** `/api/auth/send-email-otp`

- **Description:** Send an OTP to a new email (fails if email already exists).
 - **Body:**
 - **email** (string, required)
 - **Response:**
 - **200 OK:** Success message (bilingual)
-

4. Send Phone OTP

- **POST** `/api/auth/send-phone-otp`
 - **Description:** Send an OTP to a new phone (fails if phone already exists).
 - **Body:**
 - **phone** (string, required)
 - **Response:**
 - **200 OK:** Success message (bilingual)
-

5. Confirm OTP

- **POST** `/api/auth/confirm-otp`
 - **Description:** Confirm an OTP for any email or phone identifier (works for both registered and non-registered users).
 - **Body:**
 - **identifier** (string, required)
 - **otp** (string, required)
 - **Response:**
 - **200 OK:** OTP verified successfully (bilingual message)
-

6. Confirm Login OTP

- **POST** `/api/auth/confirm-login-otp`
 - **Description:** Confirm an OTP for registered users and return user data with JWT token (like login API).
 - **Body:**
 - **identifier** (string, required)
 - **otp** (string, required)
 - **Response:**
 - **200 OK:** User info + JWT token (bilingual message)
 - **404 Not Found:** User not found (bilingual message)
-

7. Login

- **POST** `/api/auth/login`
- **Description:** Login with email/phone and password.
- **Body:**
 - **identifier** (email or phone, required)
 - **password** (string, required)
- **Response:**

- **200 OK:** User info + JWT token (bilingual message)
-

8. Login with OTP

- **POST** `/api/auth/login-with-otp`
 - **Description:** Request an OTP for login (email or phone).
 - **Body:**
 - `identifier` (email or phone, required)
 - **Response:**
 - **200 OK:** OTP sent (bilingual message)
-

9. Forgot Password

- **POST** `/api/auth/forgot-password`
 - **Description:** Change password for authenticated user.
 - **Headers:** `Authorization: Bearer <token>`
 - **Body:**
 - `newPassword` (string, required)
 - **Response:**
 - **200 OK:** Password updated (bilingual message)
-

10. Create Admin User

- **POST** `/api/auth/create-admin`
 - **Description:** Create a new admin user. Only accessible by authenticated admin users.
 - **Headers:** `Authorization: Bearer <token>`
 - **Body:**
 - `firstname` (string, required)
 - `lastname` (string, required)
 - `email` (string, required)
 - `phone` (string, optional)
 - `password` (string, required)
 - `country` (string, required)
 - `language` (string, optional, default: 'en')
 - **Response:**
 - **201 Created:** Admin user info (bilingual message)
 - **403 Forbidden:** Insufficient permissions (bilingual message)
 - **400 Bad Request:** Email/phone already registered (bilingual message)
-

11. Create Magnet Employee User

- **POST** `/api/auth/create-magnet-employee`
- **Description:** Create a new magnet employee user. Only accessible by authenticated admin users.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**

- **firstname** (string, required)
 - **lastname** (string, required)
 - **email** (string, required)
 - **phone** (string, optional)
 - **password** (string, required)
 - **country** (string, required)
 - **language** (string, optional, default: 'en')
 - **Response:**
 - **201 Created:** Magnet employee user info (bilingual message)
 - **403 Forbidden:** Insufficient permissions (bilingual message)
 - **400 Bad Request:** Email/phone already registered (bilingual message)
-

Product Routes

Language Support

Products support bilingual content (Arabic and English). You can:

- **Get products in specific language:** Add **?lang=en** or **?lang=ar** to the URL
- **Get products in user's preferred language:** The system uses the user's language preference
- **Get full bilingual data:** Use **?lang=both** to get both languages

1. Get Products

- **GET** **/api/products**
- **GET** **/api/products?lang=en** (English only)
- **GET** **/api/products?lang=ar** (Arabic only)
- **GET** **/api/products?lang=both** (Both languages)
- **Description:** Get all approved products (requires authentication). Admin/magnet_employee can see all products.
- **Headers:** **Authorization: Bearer <token>**
- **Response:**
 - **200 OK:** List of products
- **Product Object:**
 - **code** (string, auto-generated if not provided, e.g. "A001")
 - **category** (object, required, bilingual: { **en**: "English Category", **ar**: "Arabic Category" })
 - **name** (object, required, bilingual: { **en**: "English Name", **ar**: "Arabic Name" })
 - **images** (array of strings)
 - **description** (object, optional, bilingual: { **en**: "English Description", **ar**: "Arabic Description" })
 - **attachments** (array of product IDs, references to other products)
 - **unit** (object, optional, bilingual: { **en**: "English Unit", **ar**: "Arabic Unit" })
 - **minOrder** (number)
 - **pricePerUnit** (string)
 - **stock** (number)

- **customFields** (array of objects, min 3, max 10, each: { key: { en: "English Key", ar: "Arabic Key" }, value: { en: "English Value", ar: "Arabic Value" } })
 - **status** (string: 'pending', 'approved', 'declined')
 - **owner** (object, populated with business user details)
 - **approvedBy** (object, populated with admin/employee details who approved)
 - **createdAt** (date)
-

1a. Get Product by ID

- **GET** /api/products/:id
 - **GET** /api/products/:id?lang=en (English only)
 - **GET** /api/products/:id?lang=ar (Arabic only)
 - **GET** /api/products/:id?lang=both (Both languages)
 - **Description:** Get a single product by its ID. Requires authentication. Admin, business, and magnet_employee can access any product (including pending/declined).
 - **Headers:** Authorization: Bearer <token>
 - **Response:**
 - **200 OK:** Product object (see above)
 - **404 Not Found:** If product does not exist
 - **403 Forbidden:** If trying to access a non-approved product without proper role
-

2. Add Product (Business)

- **POST** /api/products/addProductsByBusiness
 - **Description:** Business user adds a new product (pending approval). Product code is auto-generated if not provided.
 - **Headers:** Authorization: Bearer <token>
 - **Body:**
 - **category** (object, required, bilingual: { en: "English Category", ar: "Arabic Category" })
 - **name** (object, required, bilingual: { en: "English Name", ar: "Arabic Name" })
 - **images** (array of strings, optional)
 - **attachments** (array of product IDs, references to other products, optional)
 - **description** (object, optional, bilingual: { en: "English Description", ar: "Arabic Description" })
 - **unit** (object, optional, bilingual: { en: "English Unit", ar: "Arabic Unit" })
 - **minOrder, pricePerUnit, stock** (all optional)
 - **customFields** (array of objects, min 3, max 10, each: { key: { en: "English Key", ar: "Arabic Key" }, value: { en: "English Value", ar: "Arabic Value" } }, required)
 - **Response:**
 - **201 Created:** Product info (pending approval) with bilingual message
-

3. Add Product (Admin/Magnet Employee)

- **POST** /api/products/addProductsByMagnet_employee

- **Description:** Admin or magnet employee adds a new product (approved immediately). Product code is auto-generated if not provided.
 - **Headers:** `Authorization: Bearer <token>`
 - **Body:**
 - `category` (object, required, bilingual: { `en`: "English Category", `ar`: "Arabic Category" })
 - `name` (object, required, bilingual: { `en`: "English Name", `ar`: "Arabic Name" })
 - `images` (array of strings, optional)
 - `attachments` (array of product IDs, references to other products, optional)
 - `description` (object, optional, bilingual: { `en`: "English Description", `ar`: "Arabic Description" })
 - `unit` (object, optional, bilingual: { `en`: "English Unit", `ar`: "Arabic Unit" })
 - `minOrder`, `pricePerUnit`, `stock` (all optional)
 - `customFields` (array of objects, min 3, max 10, each: { `key`: { `en`: "English Key", `ar`: "Arabic Key" }, `value`: { `en`: "English Value", `ar`: "Arabic Value" } }, required)
 - `owner` (user id, required)
 - **Response:**
 - `201 Created`: Product info (approved) with bilingual message
-

4. Update Product

- **PUT** `/api/products/:id`
 - **Description:** Business user updates their own product (pending approval). Admin/magnet_employee can update and approve/decline.
 - **Headers:** `Authorization: Bearer <token>`
 - **Body:**
 - Any product field (see above)
 - `status` (optional, only admin/magnet_employee can set to 'approved' or 'declined')
 - **Response:**
 - `200 OK`: Updated product info with bilingual message
-

5. Delete Product

- **DELETE** `/api/products/:id`
 - **Description:** Business user deletes their own product, or admin/employee deletes any product.
 - **Headers:** `Authorization: Bearer <token>`
 - **Response:**
 - `200 OK`: Product deleted with bilingual message
-

6. Approve Product

- **PUT** `/api/products/:id/approve`
- **Description:** Admin/magnet_employee approves a product.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**

- **200 OK:** Product approved with bilingual message

7. Decline Product

- **PUT** `/api/products/:id/decline`
 - **Description:** Admin/magnet_employee declines a product.
 - **Headers:** `Authorization: Bearer <token>`
 - **Response:**
 - **200 OK:** Product declined with bilingual message
-

Real-Time Order Tracking (WebSocket)

Overview

- The API supports real-time order status updates using WebSocket (Socket.IO).
- Clients can subscribe to updates for specific orders and receive instant notifications when the order status changes (e.g., confirmed, shipped, delivered).

How It Works

1. **Client authenticates with a JWT token when connecting to the WebSocket.**
2. **Client joins a room for a specific order using the order ID.**
3. **When the order status changes, the server emits an `orderStatusUpdate` event to all clients in that room.**

WebSocket Connection (Socket.IO)

- **URL:** `ws://<your-server>:5000` (or `wss://` for HTTPS)
- **Library:** `socket.io-client`

Client Example (JavaScript/React):

```
import { io } from 'socket.io-client';
const socket = io('http://localhost:5000', {
  auth: { token: '<JWT_TOKEN>' }
});

// Join the order room
socket.emit('joinOrderRoom', '<ORDER_ID>');

// Listen for updates
socket.on('orderStatusUpdate', (data) => {
  // data: { orderId, status, statusLog, updatedAt }
  console.log('Order update:', data);
});
```

Order Room Access Rules

- **Admin & magnet_employee:** Can track any order.
- **Business:** Can track orders that include products they own.
- **Customer:** Can track only their own orders.
- Unauthorized attempts to join order rooms will be ignored.

Server-Side Security

- The server authenticates each socket connection using the JWT token.
- The server enforces the above access rules for joining order rooms.

Order Status Update Event

- **Event:** `orderStatusUpdate`
- **Payload:**

```
{
  "orderId": "...",
  "status": "shipped",
  "statusLog": [
    { "status": "pending", "timestamp": "..." },
    { "status": "confirmed", "timestamp": "..." },
    { "status": "shipped", "timestamp": "..." }
  ],
  "updatedAt": "2024-07-10T12:00:00.000Z"
}
```

Security Notes

- Clients must provide a valid JWT token when connecting.
- The server will only allow joining order rooms for orders the user is authorized to track (see access rules above).
- Unauthorized attempts to join rooms will be ignored.

Additional Utility Features

Email and SMS Utilities

The API includes comprehensive email and SMS functionality for user verification and notifications:

Email Features

- **Email OTP Generation:** Automatic generation of 6-digit verification codes
- **Email Templates:** Pre-formatted HTML email templates for various notifications
- **Business Notifications:** Automatic email notifications for business registration status changes
- **Verification Emails:** Email verification for user registration

SMS Features

- **SMS OTP Generation:** Automatic generation of 6-digit SMS verification codes
- **Saudi Number Support:** Special handling for Saudi phone numbers (+966)
- **SMS Templates:** Pre-formatted SMS messages for various notifications
- **Phone Verification:** SMS verification for user registration

Product Code Generation

The API includes an automatic product code generation system:

Features

- **Auto-Generation:** If no product code is provided, the system automatically generates a unique code
- **Format:** Codes follow the pattern "A001", "A002", etc.
- **Uniqueness:** Each generated code is guaranteed to be unique
- **Custom Codes:** Users can provide their own custom codes if desired

User Model Features

The user model includes several advanced features:

Favorites System

- **Add to Favorites:** Users can add products to their favorites list
- **Remove from Favorites:** Users can remove products from their favorites
- **View Favorites:** Users can view their complete favorites list

Cart System

- **Add to Cart:** Users can add products to their shopping cart
- **Cart Management:** Users can update quantities and remove items
- **Cart Persistence:** Cart data is stored with the user account

Business Approval Workflow

- **Registration Review:** Business registrations require admin/employee approval
- **Status Tracking:** Business approval status is tracked (pending, approved, rejected)
- **Notification System:** Automatic notifications for approval status changes
- **Rejection Reasons:** Admins can provide reasons for business registration rejections

Verification Status Tracking

- **Email Verification:** Track whether user's email is verified
- **Phone Verification:** Track whether user's phone is verified
- **Automatic Verification:** Saudi phone numbers are automatically verified
- **Manual Verification:** Other verification methods available

User Disallowance System

- **Account Disallowance:** Admins can disallow users from logging in and performing actions

- **Disallowance Tracking:** Track who disallowed a user, when, and the reason
- **Allowance Tracking:** Track who allowed a user and when
- **Login Prevention:** Disallowed users cannot login or perform any actions
- **Business Action Prevention:** Disallowed business users cannot add products
- **Self-Protection:** Admins cannot disallow their own accounts
- **Admin Protection:** Admin users cannot be disallowed by other admins

Bilingual Message System

The API includes a comprehensive bilingual message system:

Features

- **Centralized Messages:** All messages are stored in a centralized `messages.js` file
- **Bilingual Support:** All messages are available in both English and Arabic
- **Consistent Format:** All API responses follow the same bilingual format
- **Error Messages:** Comprehensive error messages in both languages
- **Success Messages:** Success confirmations in both languages

Message Format

```
{
  "status": "success",
  "message": {
    "en": "Operation completed successfully",
    "ar": "تم إكمال العملية بنجاح"
  },
  "data": { ... }
}
```

Authentication and Authorization

The API includes a robust authentication and authorization system:

JWT Authentication

- **Token-Based:** Uses JWT tokens for authentication
- **Expiration:** Tokens expire after 7 days
- **Refresh:** Tokens can be refreshed
- **Secure:** Uses environment variables for secret keys

Role-Based Access Control

- **Admin:** Full system access including user management
- **Magnet Employee:** Limited admin access
- **Business:** Business-specific features
- **Customer:** Customer-specific features

Admin User Management

- **User Creation:** Admins can create any type of user (customer, business, magnet_employee, admin)
- **User Management:** Complete CRUD operations on all users
- **User Statistics:** Comprehensive user statistics and analytics
- **User Disallowance:** Ability to disallow users from accessing the system
- **User Allowance:** Ability to re-allow previously disallowed users
- **Audit Trail:** Complete tracking of disallowance/allowance actions
- **Security Protections:** Self-protection and admin protection mechanisms

Middleware System

- **Auth Middleware:** Verifies JWT tokens
 - **Role Middleware:** Enforces role-based access
 - **Validation Middleware:** Validates request data
 - **Error Handling:** Comprehensive error handling
-

Category Routes

Language Support

Categories support bilingual content (Arabic and English). You can:

- **Get categories in specific language:** Add `?lang=en` or `?lang=ar` to the URL
- **Get categories in user's preferred language:** The system uses the user's language preference
- **Get full bilingual data:** Use `?lang=both` to get both languages

Category Object

- `name` (object, required, bilingual: { `en`: "English Name", `ar`: "Arabic Name" })
- `description` (object, optional, bilingual: { `en`: "English Description", `ar`: "Arabic Description" })
- `createdBy` (object, populated with creator details)
- `createdAt` (date)
- `updatedAt` (date)

1. Get Categories

- **GET** `/api/categories`
- **GET** `/api/categories?lang=en` (English only)
- **GET** `/api/categories?lang=ar` (Arabic only)
- **GET** `/api/categories?lang=both` (Both languages)
- **Description:** Get all categories (public).
- **Response:**
 - **200 OK:** List of categories

2. Create Category

- **POST** `/api/categories`
- **Description:** Create a new category (business, admin, or magnet_employee only).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `name` (object, required, bilingual: { `en`: "English Name", `ar`: "Arabic Name" })
 - `description` (object, optional, bilingual: { `en`: "English Description", `ar`: "Arabic Description" })
- **Response:**
 - **201 Created:** Category info (bilingual message)

3. Update Category

- **PUT** `/api/categories/:id`
- **Description:** Update a category (business, admin, or magnet_employee only).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `name` (object, optional, bilingual: { `en`: "English Name", `ar`: "Arabic Name" })
 - `description` (object, optional, bilingual: { `en`: "English Description", `ar`: "Arabic Description" })
- **Response:**
 - **200 OK:** Updated category info (bilingual message)

4. Delete Category

- **DELETE** `/api/categories/:id`
- **Description:** Delete a category (business, admin, or magnet_employee only).
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Category deleted (bilingual message)

Order Routes

Language Support

Orders support bilingual content (Arabic and English). You can:

- **Get orders in specific language:** Add `?lang=en` or `?lang=ar` to the URL
- **Get orders in user's preferred language:** The system uses the user's language preference
- **Get full bilingual data:** Use `?lang=both` to get both languages

Order Object

- `customer` (object, populated with customer details)
- `items` (array of objects, required)
 - Each item: { `product`: `ObjectId`, `quantity`: `Number` }
- `shippingAddress` (`ObjectId`, reference to Address)
- `status` (object, bilingual: { `en`: "pending", `ar`: "قيد الانتظار" })
- `statusLog` (array of objects)

- Each log: { status: { en: "pending", ar: "فيد الانتظار" }, timestamp: Date }
- **createdAt** (date)
- **updatedAt** (date)

Note: Order status is stored as bilingual objects but returned as localized strings based on the **lang** parameter:

- pending → { en: "pending", ar: "فيد الانتظار" }
- confirmed → { en: "confirmed", ar: "مؤكد" }
- shipped → { en: "shipped", ar: "تم الشحن" }
- delivered → { en: "delivered", ar: "تم التوصيل" }
- cancelled → { en: "cancelled", ar: "ملغى" }

1. Create Order

- **POST** /api/orders
- **Description:** Create a new order (customer only).
- **Headers:** Authorization: Bearer <token>
- **Body:**
 - Order details (see order model)
- **Response:**
 - **201 Created:** Order info (bilingual message)

2. Get My Orders

- **GET** /api/orders/my
- **GET** /api/orders/my?lang=en (English only)
- **GET** /api/orders/my?lang=ar (Arabic only)
- **GET** /api/orders/my?lang=both (Both languages)
- **Description:** Get all orders for the authenticated customer.
- **Headers:** Authorization: Bearer <token>
- **Response:**
 - **200 OK:** List of orders (bilingual message)

3. Get Order by ID

- **GET** /api/orders/:id
- **GET** /api/orders/:id?lang=en (English only)
- **GET** /api/orders/:id?lang=ar (Arabic only)
- **GET** /api/orders/:id?lang=both (Both languages)
- **Description:** Get order by ID (admin, magnet_employee, or owner).
- **Headers:** Authorization: Bearer <token>
- **Response:**
 - **200 OK:** Order info (bilingual message)

4. Get All Orders

- **GET** /api/orders
- **GET** /api/orders?lang=en (English only)

- **GET** `/api/orders?lang=ar` (Arabic only)
- **GET** `/api/orders?lang=both` (Both languages)
- **Description:** Get all orders (admin, magnet_employee only).
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** List of orders (bilingual message)

5. Update Order Status

- **PUT** `/api/orders/:id/status`
- **Description:** Update order status (admin, magnet_employee only).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - **status** (string, required, enum: 'pending', 'confirmed', 'shipped', 'delivered', 'cancelled')
- **Response:**
 - **200 OK:** Updated order info (bilingual message)

6. Get Status Options

- **GET** `/api/orders/status-options`
- **GET** `/api/orders/status-options?lang=en` (English only)
- **GET** `/api/orders/status-options?lang=ar` (Arabic only)
- **GET** `/api/orders/status-options?lang=both` (Both languages)
- **Description:** Get available order status options (public).
- **Response:**
 - **200 OK:** Status options in requested language
 - **Example Response:**

```
{
  "status": "success",
  "data": {
    "statusOptions": {
      "pending": "قيد الانتظار",
      "confirmed": "مؤكد",
      "shipped": "تم الشحن",
      "delivered": "تم التوصيل",
      "cancelled": "ملغي"
    },
    "statusEnums": {
      "en": ["pending", "confirmed", "shipped", "delivered",
"cancelled"],
      "ar": ["قيد الانتظار", "مؤكد", "تم الشحن", "تم التوصيل",
"ملغي"]
    },
    "validEnglishStatuses": ["pending", "confirmed", "shipped",
"delivered", "cancelled"]
  }
}
```

7. Get Business Product Orders

- **GET** `/api/orders/business-products`
 - **Description:** Get all orders containing products owned by the authenticated business user.
 - **Headers:** `Authorization: Bearer <token>`
 - **Response:**
 - **200 OK:** List of orders containing the business user's products
 - **Note:** This endpoint returns orders that contain any product owned by the business user, with customer details for order fulfillment.
-

Address Routes

Language Support

Addresses no longer support bilingual content. All address fields are stored as simple strings.

Address Object

- `user` (object, populated with user details)
- `addressLine1` (string, required)
- `addressLine2` (string, optional)
- `city` (string, required)
- `state` (string, required)
- `postalCode` (string, required)
- `country` (string, required)
- `createdAt` (date)
- `updatedAt` (date)

1. Get Addresses

- **GET** `/api/addresses`
- **Description:** Get all addresses for the authenticated customer.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** List of addresses (bilingual message)

2. Add Address

- **POST** `/api/addresses`
- **Description:** Add a new address (customer only).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `addressLine1` (string, required)
 - `addressLine2` (string, optional)
 - `city` (string, required)

- **state** (string, required)
- **postalCode** (string, required)
- **country** (string, required)
- **Response:**
 - **201 Created:** Address info (bilingual message)

3. Update Address

- **PUT** /api/addresses/:id
- **Description:** Update an address (customer only).
- **Headers:** **Authorization:** Bearer <token>
- **Body:**
 - Any address field (see above)
- **Response:**
 - **200 OK:** Updated address info (bilingual message)

4. Delete Address

- **DELETE** /api/addresses/:id
 - **Description:** Delete an address (customer only).
 - **Headers:** **Authorization:** Bearer <token>
 - **Response:**
 - **200 OK:** Address deleted (bilingual message)
-

Wishlist Routes

Wishlist Object

- **user** (object, populated with wishlist owner details)
- **products** (array of objects, populated with product details including owner and approvedBy)
- **createdAt** (date)

1. Get Wishlist

- **GET** /api/wishlist
- **Description:** Get the authenticated customer's wishlist.
- **Headers:** **Authorization:** Bearer <token>
- **Response:**
 - **200 OK:** List of wishlist items (bilingual message)

2. Add to Wishlist

- **POST** /api/wishlist
- **Description:** Add a product to the authenticated customer's wishlist.
- **Headers:** **Authorization:** Bearer <token>
- **Body:**
 - **productId** (string, required)
- **Response:**

- **200 OK:** Wishlist item info (bilingual message)

3. Remove from Wishlist

- **DELETE** `/api/wishlist/:productId`
 - **Description:** Remove a product from the authenticated customer's wishlist.
 - **Headers:** `Authorization: Bearer <token>`
 - **Response:**
 - **200 OK:** Wishlist item removed (bilingual message)
-

Review Routes

Language Support

Reviews no longer support bilingual content. All review comments are stored as simple strings.

Review Object

- **product** (object, populated with product details including owner and approvedBy)
- **user** (object, populated with reviewer details)
- **rating** (number, required, min: 1, max: 5)
- **comment** (string, optional)
- **status** (string, enum: 'accept', 'reject', default: 'accept')
- **rejectedBy** (object, populated with admin details who rejected, only if status is 'reject')
- **rejectedAt** (date, only if status is 'reject')
- **rejectionReason** (string, only if status is 'reject')
- **createdAt** (date)

1. Add Review

- **POST** `/api/reviews/products/:id/reviews`
- **Description:** Add a review to a product (customer only).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - **rating** (number, required, min: 1, max: 5)
 - **comment** (string, optional)
- **Response:**
 - **201 Created:** Review info (bilingual message)

2. Get Product Reviews

- **GET** `/api/reviews/products/:id/reviews`
- **Description:** Get all reviews for a product (public).
- **Response:**
 - **200 OK:** List of reviews (bilingual message)

3. Get Business Products Reviews

- **GET** `/api/reviews/business-products-reviews`
- **Description:** Get all reviews for products owned by the authenticated business user.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** List of reviews for the business user's products
 - **Note:** This endpoint returns reviews for all products owned by the business user, with user and product details.

4. Delete Review

- **DELETE** `/api/reviews/:id`
 - **Description:** Delete a review (admin or magnet_employee only).
 - **Headers:** `Authorization: Bearer <token>`
 - **Response:**
 - **200 OK:** Review deleted (bilingual message)
-

User Routes

1. Get User Profile

- **GET** `/api/user/profile`
- **Description:** Get the authenticated user's profile.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** User profile info (bilingual message)

2. Update User Profile

- **PUT** `/api/user/profile`
- **Description:** Update the authenticated user's profile.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `firstname` (string, optional)
 - `lastname` (string, optional)
 - `email` (string, optional)
 - `phone` (string, optional)
 - `country` (string, optional)
 - `language` (string, optional)
- **Response:**
 - **200 OK:** Updated user profile (bilingual message)

3. Get Business Requests

- **GET** `/api/user/business-requests`
- **Description:** Get all business registration requests (admin/employee only).
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** List of business requests (bilingual message)

4. Business Approval

- **POST** /api/user/business-approval
- **Description:** Approve or reject business registration (admin/employee only).
- **Headers:** Authorization: Bearer <token>
- **Body:**
 - **businessId** (string, required)
 - **status** (string, required, enum: 'approved', 'rejected')
 - **reason** (string, optional, required if status is 'rejected')
- **Response:**
 - **200 OK:** Business approval status updated (bilingual message)

5. Get Business Details

- **GET** /api/user/business/:businessId
- **Description:** Get business details by ID (admin/employee only).
- **Headers:** Authorization: Bearer <token>
- **Response:**
 - **200 OK:** Business details (bilingual message)

6. Get Business Profile

- **GET** /api/user/business-profile
- **Description:** Get business profile (business users only).
- **Headers:** Authorization: Bearer <token>
- **Response:**
 - **200 OK:** Business profile info (bilingual message)

Admin Routes

Overview

Admin routes provide comprehensive user management functionality for system administrators. All admin endpoints require authentication and admin role authorization.

Key Features:

- **User Management:** Create, read, update, delete users (admin only)
- **User Status Control:** Allow/disallow users from accessing the system (admin only)
- **Verification Management:** Manually verify/unverify user email and phone numbers (admin or magnet_employee)
- **Business Approval:** Manage business user approvals and rejections
- **Statistics:** Get comprehensive user statistics for dashboard
- **Role-based Access:** Support for all user roles (customer, business, magnet_employee, admin)
- **Enhanced Data:** All APIs return complete user information with populated related fields

1. Create User

- **POST** /api/admin/users

- **Description:** Create any type of user (customer, business, magnet_employee, admin).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `firstname` (string, required)
 - `lastname` (string, required)
 - `email` (string, required)
 - `phone` (string, optional)
 - `password` (string, required)
 - `role` (string, required, enum: 'customer', 'business', 'magnet_employee', 'admin')
 - `country` (string, required)
 - `language` (string, optional, default: 'en')
 - `imageUrl` (string, optional) - Profile image URL
 - `businessInfo` (object, required if role is 'business')
 - `crNumber` (string, required for business)
 - `vatNumber` (string, required for business)
 - `companyName` (string, required for business)
 - `companyType` (string, required for business)
 - `city` (string, required for business)
 - `district` (string, required for business)
 - `streetName` (string, required for business)
- **Response:**
 - `201 Created`: User created successfully (bilingual message)
 - `400 Bad Request`: Validation errors (bilingual message)
 - `403 Forbidden`: Insufficient permissions (bilingual message)

2. Get All Users

- **GET** `/api/admin/users`
- **Description:** Get all users with pagination, filtering, and search capabilities. Automatically fixes missing `approvedBy` field for approved business users.
- **Headers:** `Authorization: Bearer <token>`
- **Query Parameters:**
 - `page` (number, optional, default: 1)
 - `limit` (number, optional, default: 10)
 - `role` (string, optional, filter by role)
 - `search` (string, optional, search by name, email, or phone)
 - `status` (string, optional, filter by disallow status: 'allowed', 'disallowed')
- **Response:**
 - `200 OK`: List of users with pagination info (bilingual message)

3. Get User Statistics

- **GET** `/api/admin/users/stats`
- **Description:** Get comprehensive user statistics for the admin dashboard.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - `200 OK`: User statistics including counts by role, verification status, etc. (bilingual message)

4. Get User by ID

- **GET** `/api/admin/users/:id`
- **Description:** Get detailed information about a specific user. Automatically fixes missing `approvedBy` field for approved business users. For business users, returns products and their reviews. For customer users, returns orders, wishlist, addresses, and reviews. All products include their first image URL.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** User details with role-specific data (bilingual message)
 - **404 Not Found:** User not found (bilingual message)
- **Business User Response:**
 - **products:** Array of products with `imageUrl` (first image from product's images array)
 - **reviews:** Array of reviews with product details including `imageUrl`
- **Customer User Response:**
 - **orders:** Array of orders with product details including `imageUrl`
 - **wishlist:** Wishlist with products including `imageUrl`
 - **addresses:** Array of addresses
 - **reviews:** Array of reviews with product details including `imageUrl`
- **Admin/Magnet Employee User Response:**
 - **moderatedProducts:** Array of products approved/declined by this admin/employee with owner details and `imageUrl`
 - **rejectedReviews:** Array of reviews rejected by this admin/employee with user and product details including `imageUrl`
 - **moderatedOrders:** Array of orders where this admin/employee made status changes (confirmed, shipped, cancelled, etc.)
 - **approvedBusinessUsers:** Array of business users approved by this admin/employee with complete business information
- **Product Object in Responses:**
 - **id:** Product ID
 - **name:** Product name (bilingual object)
 - **code:** Product code
 - **status:** Product status
 - **category:** Product category (bilingual object)
 - **imageUrl:** First image URL from product's images array (null if no images)

5. Update User

- **PUT** `/api/admin/users/:id`
- **Description:** Update user information (cannot update own account).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - **firstname** (string, optional)
 - **lastname** (string, optional)
 - **email** (string, optional)
 - **phone** (string, optional)
 - **password** (string, optional)
 - **role** (string, optional, enum: 'customer', 'business', 'magnet_employee', 'admin')

- **country** (string, optional)
- **language** (string, optional)
- **imageUrl** (string, optional) - Profile image URL
- **isEmailVerified** (boolean, optional)
- **isPhoneVerified** (boolean, optional)
- **isDisallowed** (boolean, optional)
- **businessInfo** (object, optional for business users)
 - **crNumber** (string, optional)
 - **vatNumber** (string, optional)
 - **companyName** (string, optional)
 - **companyType** (string, optional)
 - **city** (string, optional)
 - **district** (string, optional)
 - **streetName** (string, optional)
- **Response:**
 - **200 OK:** User updated successfully (bilingual message)
 - **400 Bad Request:** Validation errors (bilingual message)
 - **404 Not Found:** User not found (bilingual message)

6. Delete User

- **DELETE** `/api/admin/users/:id`
- **Description:** Permanently delete a user (cannot delete own account).
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** User deleted successfully (bilingual message)
 - **400 Bad Request:** Cannot delete own account (bilingual message)
 - **404 Not Found:** User not found (bilingual message)

7. Disallow User

- **PUT** `/api/admin/users/:id/disallow`
- **Description:** Disallow a user from logging in and performing actions.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - **reason** (string, required) - Reason for disallowing the user
- **Response:**
 - **200 OK:** User disallowed successfully (bilingual message)
 - **400 Bad Request:** Cannot disallow admin or own account (bilingual message)
 - **404 Not Found:** User not found (bilingual message)

8. Allow User

- **PUT** `/api/admin/users/:id/allow`
- **Description:** Allow a previously disallowed user to login and perform actions.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** User allowed successfully (bilingual message)

- **400 Bad Request:** User is not disallowed (bilingual message)
- **404 Not Found:** User not found (bilingual message)

9. Verify User Email

- **PUT** `/api/admin/users/:id/verify-email`
- **Description:** Manually verify a user's email address.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Email verified successfully (bilingual message)
 - **400 Bad Request:** Email is already verified (bilingual message)
 - **404 Not Found:** User not found (bilingual message)
- **Example Response:**

```
{
  "status": "success",
  "data": {
    "user": {
      "id": "user_id",
      "firstname": "John",
      "lastname": "Doe",
      "email": "john@example.com",
      "isEmailVerified": true,
      "isPhoneVerified": false
    }
  },
  "message": {
    "en": "Email verified successfully",
    "ar": "تم التحقق من البريد الإلكتروني بنجاح"
  }
}
```

10. Unverify User Email

- **PUT** `/api/admin/users/:id/unverify-email`
- **Description:** Manually unverify a user's email address.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Email unverified successfully (bilingual message)
 - **400 Bad Request:** Email is not verified (bilingual message)
 - **404 Not Found:** User not found (bilingual message)
- **Example Response:**

```
{
  "status": "success",
  "data": {
    "user": {
      "id": "user_id",
```



```
    "firstname": "John",
    "lastname": "Doe",
    "email": "john@example.com",
    "isEmailVerified": false,
    "isPhoneVerified": false
  }
},
"message": {
  "en": "Email unverified successfully",
  "ar": "تم إلغاء التحقق من البريد الإلكتروني بنجاح"
}
}
```

11. Verify User Phone

- **PUT** /api/admin/users/:id/verify-phone
- **Description:** Manually verify a user's phone number.
- **Headers:** Authorization: Bearer <token>
- **Response:**
 - **200 OK:** Phone verified successfully (bilingual message)
 - **400 Bad Request:** Phone is already verified or user has no phone (bilingual message)
 - **404 Not Found:** User not found (bilingual message)
- **Example Response:**

```
{
  "status": "success",
  "data": {
    "user": {
      "id": "user_id",
      "firstname": "John",
      "lastname": "Doe",
      "phone": "+1234567890",
      "isEmailVerified": true,
      "isPhoneVerified": true
    }
  },
  "message": {
    "en": "Phone verified successfully",
    "ar": "تم التحقق من الهاتف بنجاح"
  }
}
```

12. Unverify User Phone

- **PUT** /api/admin/users/:id/unverify-phone
- **Description:** Manually unverify a user's phone number.
- **Headers:** Authorization: Bearer <token>
- **Response:**

- **200 OK**: Phone unverified successfully (bilingual message)
- **400 Bad Request**: Phone is not verified (bilingual message)
- **404 Not Found**: User not found (bilingual message)

- **Example Response:**

```
{
  "status": "success",
  "data": {
    "user": {
      "id": "user_id",
      "firstname": "John",
      "lastname": "Doe",
      "phone": "+1234567890",
      "isEmailVerified": true,
      "isPhoneVerified": false
    }
  },
  "message": {
    "en": "Phone unverified successfully",
    "ar": "تم إلغاء التحقق من الهاتف بنجاح"
  }
}
```

Verification Management Features

The admin verification management system provides comprehensive control over user verification status:

Email Verification:

- **Verify Email**: Manually mark a user's email as verified
- **Unverify Email**: Remove email verification status
- **Validation**: Prevents duplicate verification or unverification of already unverified emails

Phone Verification:

- **Verify Phone**: Manually mark a user's phone as verified
- **Unverify Phone**: Remove phone verification status
- **Validation**:
 - Prevents verification if user has no phone number
 - Prevents duplicate verification or unverification of already unverified phones

Security Features:

- **Admin or Magnet Employee**: All verification endpoints require admin or magnet_employee authentication
- **Audit Trail**: All verification changes are tracked with timestamps
- **Bilingual Support**: All responses include English and Arabic messages
- **Error Handling**: Comprehensive validation with appropriate error messages

Use Cases:

- **Manual Verification:** Admins can verify users who completed verification through other means
- **Account Recovery:** Help users regain access by re-verifying their contact information
- **Security Management:** Unverify suspicious accounts for security review
- **Compliance:** Ensure verification status meets regulatory requirements

Admin User Object

- **id** (ObjectId)
- **firstname** (string)
- **lastname** (string)
- **email** (string)
- **phone** (string, optional)
- **role** (string, enum: 'admin', 'magnet_employee', 'business', 'customer')
- **country** (string)
- **language** (string, enum: 'en', 'ar')
- **imageUrl** (string, optional)
- **isEmailVerified** (boolean)
- **isPhoneVerified** (boolean)
- **isDisallowed** (boolean)
- **disallowReason** (string, if disallowed)
- **disallowedBy** (object, populated with admin details who disallowed)
- **disallowedAt** (Date, if disallowed)
- **allowedBy** (object, populated with admin details who allowed)
- **allowedAt** (Date, if allowed)
- **businessInfo** (object, for business users)
 - **crNumber** (string)
 - **vatNumber** (string)
 - **companyName** (string)
 - **companyType** (string)
 - **city** (string)
 - **district** (string)
 - **streetName** (string)
 - **isApproved** (boolean)
 - **approvalStatus** (string, enum: 'pending', 'approved', 'rejected')
 - **approvedBy** (object, populated with admin details who approved)
 - **approvedAt** (Date)
 - **rejectionReason** (string, if rejected)
- **createdAt** (Date)
- **updatedAt** (Date)

Admin Wishlist Management Routes

1. Get All Wishlists

- **GET** `/api/admin/wishlists`
- **Description:** Get all wishlists with pagination and filtering capabilities.
- **Headers:** `Authorization: Bearer <token>`

- **Query Parameters:**
 - **page** (number, optional, default: 1)
 - **limit** (number, optional, default: 10)
 - **userId** (string, optional, filter by user ID)
 - **productId** (string, optional, filter by product ID)
- **Response:**
 - **200 OK:** List of wishlists with pagination info (bilingual message)
 - **Example Response:**

```
{
  "status": "success",
  "data": {
    "wishlists": [
      {
        "id": "wishlist_id",
        "user": {
          "id": "user_id",
          "firstname": "John",
          "lastname": "Doe",
          "email": "john@example.com",
          "role": "customer"
        },
        "products": [
          {
            "id": "product_id",
            "name": "Product Name",
            "code": "PROD001",
            "status": "approved"
          }
        ],
        "createdAt": "2024-01-01T00:00:00.000Z"
      }
    ]
  },
  "pagination": {
    "currentPage": 1,
    "totalPages": 1,
    "totalItems": 1,
    "itemsPerPage": 10
  }
}
```

2. Get Wishlist by ID

- **GET** /api/admin/wishlists/:id
- **Description:** Get detailed information about a specific wishlist.
- **Headers:** Authorization: Bearer <token>
- **Response:**
 - **200 OK:** Wishlist details (bilingual message)

- **404 Not Found:** Wishlist not found (bilingual message)

3. Create Wishlist

- **POST** `/api/admin/wishlists`
- **Description:** Add a product to a user's wishlist (creates wishlist if it doesn't exist).
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `userId` (string, required) - User ID
 - `productId` (string, required) - Product ID (must be approved)
- **Response:**
 - **201 Created:** Product added to wishlist successfully (bilingual message)
 - **400 Bad Request:** Validation errors (bilingual message)

4. Update Wishlist

- **PUT** `/api/admin/wishlists/:id`
- **Description:** Update wishlist information or add/remove products.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `userId` (string, optional) - New user ID
 - `productId` (string, optional) - Product ID to add or remove
 - `action` (string, optional, enum: 'add', 'remove') - Action to perform on product
- **Response:**
 - **200 OK:** Wishlist updated successfully (bilingual message)
 - **404 Not Found:** Wishlist not found (bilingual message)

5. Delete Wishlist

- **DELETE** `/api/admin/wishlists/:id`
- **Description:** Permanently delete a wishlist entry.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Wishlist deleted successfully (bilingual message)
 - **404 Not Found:** Wishlist not found (bilingual message)

Admin Review Management Routes

1. Get All Reviews

- **GET** `/api/admin/reviews`
- **Description:** Get all reviews with pagination and filtering capabilities.
- **Headers:** `Authorization: Bearer <token>`
- **Query Parameters:**
 - `page` (number, optional, default: 1)
 - `limit` (number, optional, default: 10)
 - `userId` (string, optional, filter by user ID)
 - `productId` (string, optional, filter by product ID)

- **rating** (number, optional, filter by rating)
- **Response:**
 - **200 OK:** List of reviews with pagination info (bilingual message)

2. Get Review by ID

- **GET** `/api/admin/reviews/:id`
- **Description:** Get detailed information about a specific review.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Review details (bilingual message)
 - **404 Not Found:** Review not found (bilingual message)

3. Create Review

- **POST** `/api/admin/reviews`
- **Description:** Create a new review for any user and product.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - **userId** (string, required) - User ID
 - **productId** (string, required) - Product ID (must be approved)
 - **rating** (number, required, min: 1, max: 5) - Rating
 - **comment** (string, optional) - Review comment
- **Response:**
 - **201 Created:** Review created successfully (bilingual message)
 - **400 Bad Request:** Validation errors (bilingual message)

4. Update Review

- **PUT** `/api/admin/reviews/:id`
- **Description:** Update review information.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - **rating** (number, optional, min: 1, max: 5) - New rating
 - **comment** (string, optional) - New comment
- **Response:**
 - **200 OK:** Review updated successfully (bilingual message)
 - **404 Not Found:** Review not found (bilingual message)

5. Delete Review

- **DELETE** `/api/admin/reviews/:id`
- **Description:** Permanently delete a review.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Review deleted successfully (bilingual message)
 - **404 Not Found:** Review not found (bilingual message)

6. Reject Review

- **PUT** `/api/admin/reviews/:id/reject`
- **Description:** Reject a review and send email notification to the reviewer.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `reason` (string, required) - Reason for rejecting the review
- **Response:**
 - **200 OK:** Review rejected successfully (bilingual message)
 - **400 Bad Request:** Review already rejected or missing rejection reason (bilingual message)
 - **404 Not Found:** Review not found (bilingual message)
- **Features:**
 - **Email Notification:** Automatically sends email to the reviewer informing them of the rejection
 - **Status Tracking:** Updates review status to 'reject' and tracks rejection details
 - **Audit Trail:** Records who rejected the review, when, and why
 - **Validation:** Prevents rejecting already rejected reviews
- **Example Response:**

```
{
  "status": "success",
  "data": {
    "review": {
      "id": "review_id",
      "user": {
        "id": "user_id",
        "firstname": "John",
        "lastname": "Doe",
        "email": "john@example.com"
      },
      "product": {
        "id": "product_id",
        "name": "Product Name"
      },
      "rating": 4,
      "comment": "Great product!",
      "status": "reject",
      "rejectedBy": {
        "id": "admin_id",
        "firstname": "Admin",
        "lastname": "User",
        "email": "admin@example.com",
        "role": "admin"
      },
      "rejectedAt": "2024-01-01T12:00:00.000Z",
      "rejectionReason": "Inappropriate content",
      "createdAt": "2024-01-01T10:00:00.000Z"
    },
    "message": {
      "en": "Review rejected successfully",
      "ar": "تم رفض التقييم بنجاح"
    }
  }
}
```

```
}  
}
```

Admin Address Management Routes

1. Get All Addresses

- **GET** `/api/admin/addresses`
- **Description:** Get all addresses with pagination and filtering capabilities.
- **Headers:** `Authorization: Bearer <token>`
- **Query Parameters:**
 - `page` (number, optional, default: 1)
 - `limit` (number, optional, default: 10)
 - `userId` (string, optional, filter by user ID)
 - `city` (string, optional, search by city)
 - `country` (string, optional, search by country)
- **Response:**
 - **200 OK:** List of addresses with pagination info (bilingual message)

2. Get Address by ID

- **GET** `/api/admin/addresses/:id`
- **Description:** Get detailed information about a specific address.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Address details (bilingual message)
 - **404 Not Found:** Address not found (bilingual message)

3. Create Address

- **POST** `/api/admin/addresses`
- **Description:** Create a new address for any user.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `userId` (string, required) - User ID
 - `addressLine1` (string, required) - Primary address line
 - `addressLine2` (string, optional) - Secondary address line
 - `city` (string, required) - City
 - `state` (string, required) - State/Province
 - `postalCode` (string, required) - Postal code
 - `country` (string, required) - Country
- **Response:**
 - **201 Created:** Address created successfully (bilingual message)
 - **400 Bad Request:** Validation errors (bilingual message)

4. Update Address

- **PUT** /api/admin/addresses/:id
- **Description:** Update address information.
- **Headers:** Authorization: Bearer <token>
- **Body:**
 - addressLine1 (string, optional) - Primary address line
 - addressLine2 (string, optional) - Secondary address line
 - city (string, optional) - City
 - state (string, optional) - State/Province
 - postalCode (string, optional) - Postal code
 - country (string, optional) - Country
- **Response:**
 - 200 OK: Address updated successfully (bilingual message)
 - 404 Not Found: Address not found (bilingual message)

5. Delete Address

- **DELETE** /api/admin/addresses/:id
 - **Description:** Permanently delete an address.
 - **Headers:** Authorization: Bearer <token>
 - **Response:**
 - 200 OK: Address deleted successfully (bilingual message)
 - 404 Not Found: Address not found (bilingual message)
-

Admin Order Management Routes

1. Get All Orders

- **GET** /api/admin/orders
- **Description:** Get all orders with pagination and filtering capabilities.
- **Headers:** Authorization: Bearer <token>
- **Query Parameters:**
 - page (number, optional, default: 1)
 - limit (number, optional, default: 10)
 - customerId (string, optional, filter by customer ID)
 - status (string, optional, filter by order status)
 - startDate (string, optional, filter orders from date)
 - endDate (string, optional, filter orders to date)
- **Response:**
 - 200 OK: List of orders with pagination info (bilingual message)

2. Get Order by ID

- **GET** /api/admin/orders/:id
- **Description:** Get detailed information about a specific order.
- **Headers:** Authorization: Bearer <token>
- **Response:**
 - 200 OK: Order details (bilingual message)

- **404 Not Found:** Order not found (bilingual message)

3. Create Order

- **POST** `/api/admin/orders`
- **Description:** Create a new order for any customer.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `customerId` (string, required) - Customer ID
 - `items` (array, required) - Array of order items
 - Each item: `{ product: string, quantity: number }`
 - `shippingAddressId` (string, required) - Shipping address ID
- **Response:**
 - **201 Created:** Order created successfully (bilingual message)
 - **400 Bad Request:** Validation errors (bilingual message)

4. Update Order

- **PUT** `/api/admin/orders/:id`
- **Description:** Update order information including status.
- **Headers:** `Authorization: Bearer <token>`
- **Body:**
 - `items` (array, optional) - New order items
 - `shippingAddressId` (string, optional) - New shipping address ID
 - `status` (string, optional) - New order status
- **Response:**
 - **200 OK:** Order updated successfully (bilingual message)
 - **404 Not Found:** Order not found (bilingual message)

5. Delete Order

- **DELETE** `/api/admin/orders/:id`
- **Description:** Permanently delete an order.
- **Headers:** `Authorization: Bearer <token>`
- **Response:**
 - **200 OK:** Order deleted successfully (bilingual message)
 - **404 Not Found:** Order not found (bilingual message)