```
Help
#include <stdlib.h>
#include "bs1d_std.h"
#include "error msg.h"
#define PRECISION 1.0e-7 /*Precision for the localization
    of FD methods*/
static int Psor(double s, NumFunc 1 *p, double t, double r,
    double divid, double sigma,
                int N, int M, double theta, double omega,
    double epsilon, double *ptprice, double *ptdelta)
{
  double k,z,l,h,vv,alpha,beta,gamma,alpha1,beta1,gamma1,x,
    y,error,norm,upwind alphacoef;
  int i,j,Index,loops;
  double *P,*Obst,*Rhs;
  /*Memory Allocation*/
  if (N\%2==1) N++;
 P= malloc((N+1)*sizeof(double));
  if (P==NULL)
    return MEMORY_ALLOCATION_FAILURE;
  Obst= malloc((N+1)*sizeof(double));
  if (Obst==NULL)
    return MEMORY ALLOCATION FAILURE;
  Rhs= malloc((N+1)*sizeof(double));
  if (Rhs==NULL)
    return MEMORY ALLOCATION FAILURE;
  /*Time Step*/
  k=t/(double)M;
  /*Space Localisation*/
  z=(r-divid)-SQR(sigma)/2.0;
  l=sigma*sqrt(t)*sqrt(log(1.0/PRECISION))+fabs(z)*t;
  /*Space Step*/
  h=2.0*1/(double)N;
  /*Peclet Condition-Coefficient of diffusion augmented */
  vv=0.5*SQR(sigma);
```

```
if ((h*fabs(z)) \leq vv)
  upwind alphacoef=0.5;
else {
  if (z>0.) upwind alphacoef=0.0;
  else upwind alphacoef=1.0;
vv-=z*h*(upwind_alphacoef-0.5);
/*Lhs factor of theta-schema*/
alpha=theta*k*(-vv/(h*h)+z/(2.0*h));
beta=1.0+k*theta*(r+2.*vv/(h*h));
gamma=k*theta*(-vv/(h*h)-z/(2.0*h));
/*Rhs factor of theta-schema*/
alpha1=k*(1.0-theta)*(vv/(h*h)-z/(2.0*h));
beta1=1.0-k*(1.0-theta)*(r+2.*vv/(h*h));
gamma1=k*(1.0-theta)*(vv/(h*h)+z/(2.0*h));
/*Terminal Values*/
x = log(s);
for (i=0;i<=N;i++)
    Obst[i]=(p->Compute)(p->Par,exp(x-l+(double)i*h));
    P[i]=Obst[i];
  }
/*Finite Difference Cycle*/
for (i=1;i<=M;i++)
  {
    /*Init Rhs*/
    for(j=1;j<N;j++)
Rhs[j]=P[j]*beta1+alpha1*P[j-1]+gamma1*P[j+1];
    /*Psor Cycle*/
    loops=0;
    do
{
  error=0.;
  norm=0.;
  for(j=1;j<N;j++)
```

```
y=(Rhs[j]-alpha*P[j-1]-gamma*P[j+1])/beta;
        y=MAX(Obst[j],P[j]+omega*(y-P[j]));
        error+=(double)(j+1)*fabs(y-P[j]);
        norm+=fabs(y);
        P[j]=y;
      }
    if (norm<1.0) norm=1.0;
    error=error/norm;
    loops++;
  }
      while ((error>epsilon) && (loops<MAXLOOPS));</pre>
      /*End Psor Cycle*/
  /*End Finite Difference Cycle*/
  Index=(int) floor ((double)N/2.0);
  /*Price*/
  *ptprice=P[Index];
  /*Delta*/
  *ptdelta=(P[Index+1]-P[Index-1])/(2.0*s*h);
  /*Memory Desallocation*/
  free(P);
  free(Obst);
 free(Rhs);
 return OK;
int CALC(FD_Psor)(void *Opt,void *Mod,PricingMethod *Met)
  TYPEOPT* ptOpt=( TYPEOPT*)Opt;
  TYPEMOD* ptMod=( TYPEMOD*)Mod;
  double r, divid;
```

}

```
r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
  divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);
  return Psor(ptMod->S0.Val.V PDOUBLE,ptOpt->PayOff.Val.V
    NUMFUNC 1,
        ptOpt->Maturity.Val.V_DATE-ptMod->T.Val.V_DATE,r,
    divid,ptMod->Sigma.Val.V PDOUBLE,
        Met->Par[0].Val.V_INT,Met->Par[1].Val.V_INT,Met->
    Par[2].Val.V_RGDOUBLE,
        Met->Par[3].Val.V_RGDOUBLE,Met->Par[4].Val.V_RG
    DOUBLE,
        &(Met->Res[0].Val.V_DOUBLE),&(Met->Res[1].Val.V_
    DOUBLE));
}
static int CHK OPT(FD Psor)(void *Opt, void *Mod)
  Option* ptOpt=(Option*)Opt;
 TYPEOPT* opt=(TYPEOPT*)(ptOpt->TypeOpt);
  if ((opt->EuOrAm). Val.V_BOOL==AMER)
    return OK;
 return WRONG;
}
static int MET(Init)(PricingMethod *Met,Option *Opt)
{
  if (Met->init == 0)
    {
      Met->init=1;
      Met->Par[0].Val.V_INT2=100;
      Met->Par[1].Val.V INT2=100;
      Met->Par[2].Val.V_RGDOUBLE=0.5;
      Met->Par[3].Val.V_RGDOUBLE=1.5;
      Met->Par[4].Val.V_RGDOUBLE=0.000001;
    }
```

```
return OK;
}
PricingMethod MET(FD_Psor)=
{
  "FD_Psor",
  {{"SpaceStepNumber",INT2,{100},ALLOW },{"TimeStepNumber"
    ,INT2,{100},ALLOW},
   {"Theta", RGDOUBLE051, {100}, ALLOW}, {"Omega", RGDOUBLE12
    ,{100},ALLOW}, {"Epsilon",RGDOUBLE,{100},ALLOW},{" ",PREM
    IA NULLTYPE, {0}, FORBID}},
  CALC(FD_Psor),
  {{"Price",DOUBLE,{100},FORBID},{"Delta",DOUBLE,{100},FORB
    ID} ,{" ",PREMIA_NULLTYPE,{0},FORBID}},
  CHK_OPT(FD_Psor),
  CHK psor,
  MET(Init)
};
```

References