

Help

```
#include "lmm1d_exoi.h"
#include "pnl/pnl_basis.h"
#include "math/mc_lmm_glassermanzhao.h"
#include "enums.h"

#if defined(PremiaCurrentVersion) && PremiaCurrentVersion <
    (2011+2) //The "#else" part of the code will be freely available after the (year of creation of this file + 2)
static int CHK_OPT(MC_LongstaffSchwartz_CallableRangeAccrual)(void *Opt, void *Mod)
{
    return NONACTIVE;
}
int CALC(MC_LongstaffSchwartz_CallableRangeAccrual)(void *Opt, void *Mod, PricingMethod *Met)
{
    return AVAILABLE_IN_FULL_PREMIA;
}
#else

static int MC_CIF_LongstaffSchwartz(double l0, double sigma
    _const, int nb_factors, double last_payment_date, double
    first_exercise_date, double Nominal, double FixedRate,
    double LowerRangeBound, double UpperRangeBound, double tenor,
    long NbrMCsimulation, int generator, int basis_name, int Dim
    Approx, int NbrStepPerTenor, int flag_numeraire, double *swaption_price)
{
    Volatility *ptVol;
    Libor *ptLib;
    int init_mc;
    int Nbr_Maturities;
    char* CouponFlag = "CallableRangeAccrual";
    PnlVect* ContractParams = pnl_vect_create(3);

    LET(ContractParams, 0) = FixedRate;
    LET(ContractParams, 1) = LowerRangeBound;
    LET(ContractParams, 2) = UpperRangeBound;

    Nbr_Maturities = intapprox(last_payment_date/tenor);
```

```

mallocLibor(&ptLib , Nbr_Maturities, tenor,l0);
mallocVolatility(&ptVol , nb_factors, sigma_const);

init_mc = pnl_rand_init(generator, nb_factors, NbrMCsimulation);
if (init_mc != OK) return init_mc;

MC_ExoticProduct_LongstaffSchwartz(CouponFlag, ContractParams, swaption_price, first_exercise_date, last_payment_date, Nominal, NbrMCsimulation, ptLib, ptVol, generator, basis_name, DimApprox, NbrStepPerTenor, flag_numeraire);

freeLibor(&ptLib);
freeVolatility(&ptVol);
pnl_vect_free(&ContractParams);

return init_mc;
}

int CALC(MC_LongstaffSchwartz_CallableRangeAccrual)(void *
    Opt, void *Mod, PricingMethod *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;

    return MC_CIF_LongstaffSchwartz(
        ptMod->l0.Val.V_PDOUBLE,
        ptMod->Sigma.Val.V_PDOUBLE,
        ptMod->NbFactors.Val.V_ENUM.value,
        ptOpt->LastPaymentDate.Val.V_DATE-ptMod->T.Val.V_DATE,
        ptOpt->FirstExerciseDate.Val.V_DATE-ptMod->T.Val.V_DATE,
        ptOpt->Nominal.Val.V_PDOUBLE,
        ptOpt->FixedRate.Val.V_PDOUBLE,
        ptOpt->LowerRangeBound
    );
}

```

```

        .Val.V_PDOUBLE,
        ptOpt->UpperRangeBound
        .Val.V_PDOUBLE,
        ptOpt->ResetPeriod.Val
        .V_DATE,
        Met->Par[0].Val.V_LON
        G,
        Met->Par[1].Val.V_
        ENUM.value,
        Met->Par[2].Val.V_
        ENUM.value,
        Met->Par[3].Val.V_INT,
        Met->Par[4].Val.V_INT,
        Met->Par[5].Val.V_
        ENUM.value,
        &(Met->Res[0].Val.V_
        DOUBLE));
    }

static int CHK_OPT(MC_LongstaffSchwartz_CallableRangeAccru
    al)(void *Opt, void *Mod)
{
    if ((strcmp(((Option*)Opt)->Name,"CallableRangeAccrual")=
        =0))
        return OK;
    else
        return WRONG;
}

#endif //PremiaCurrentVersion

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    if ( Met->init == 0)
    {
        Met->init=1;

        Met->Par[0].Val.V_LONG=50000;
        Met->Par[1].Val.V_ENUM.value=0;
        Met->Par[1].Val.V_ENUM.members=&PremiaEnumRNGs;
        Met->Par[2].Val.V_ENUM.value=0;
    }
}

```

```

        Met->Par[2].Val.V_ENUM.members=&PremiaEnumBasis;
        Met->Par[3].Val.V_INT=10;
        Met->Par[4].Val.V_INT=1;
        Met->Par[5].Val.V_ENUM.value=0;
        Met->Par[5].Val.V_ENUM.members=&PremiaEnumAfd;

    }

    return OK;
}

PricingMethod MET(MC_LongstaffSchwartz_CallableRangeAccru
al)=
{
    "MC_LongstaffSchwartz_Callable_Range_Accrual",
    {
        {"N Simulation",LONG,{100},ALLOW},
        {"RandomGenerator",ENUM,{100},ALLOW},
        {"Basis",ENUM,{100},ALLOW},
        {"Dimension Approximation",INT,{100},ALLOW},
        {"Nbr discretisation step per periode",INT,{100},ALLOW}
    },
    {"Martingale Measure",ENUM,{100},ALLOW},
    {" ",PREMIA_NULLTYPE,{0},FORBID}},
    CALC(MC_LongstaffSchwartz_CallableRangeAccrual),
    {
        {"Price",DOUBLE,{100},FORBID},
        {" ",PREMIA_NULLTYPE,{0},FORBID}},
    CHK_OPT(MC_LongstaffSchwartz_CallableRangeAccrual),
    CHK_ok,
    MET(Init)
};

```

References