

[Help](#)

```
#include "bs1d_std.h"

/*Critical Price*/
static double PutCriticalPrice(double r,double divid,
    double sigma,double T,double K)
{
    const double precision = 0.0001;
    double previous;
    double current=K;
    double put_price,put_delta;
    do {
        previous = current;
        pnl_cf_put_bs(previous,K,T,r,divid,sigma,&put_price,&
            put_delta);
        current=K-put_price;
    } while(!(fabs((previous-current)/current)<=precision));
    return current;
}

static double CallCriticalPrice(double r,double divid,
    double sigma,double T,double K)
{
    const double precision = 0.0001;
    double previous;
    double current=K;
    double call_price,call_delta;
    do {
        previous=current;
        pnl_cf_call_bs(previous,K,T,r,divid,sigma,&call_price,&
            call_delta);
        current=K+call_price;
    } while(!(fabs((previous-current)/current)<=precision));
    return current;
}

/* 2-points Ho-Stapleton-Subrahmanyam AP*/
static int HoStapletonSubrahmanyam_94(double s,NumFunc_1*p,
    double t,double r,double divid,double sigma,double *ptprice,
    double *ptdelta)
```

```

{
    double p1,p2,crit12,k,price,delta,val,w1,w2,d1,d2,d1c,d2
        c;

    k=p->Par[0].Val.V_PDDOUBLE;

    if ((p->Compute)==&Call)
    {
        val=-1.;
        pnl_cf_call_bs(s,k,t,r,divid,sigma,&price,&delta);
        p1=price;
        crit12=CallCriticalPrice(r,divid,sigma,t/2.,k);
    }
    else
    {
        val=1.;
        pnl_cf_put_bs(s,k,t,r,divid,sigma,&price,&delta);
        p1=price;
        crit12=PutCriticalPrice(r,divid,sigma,t/2.,k);
    }
    d1c= (log(s/crit12)+(r-divid+0.5*SQR(sigma))*t/2.)/(sigma
        *sqrt(t/2.));
    d2c=d1c-sigma*sqrt(t/2.);
    d1=(log(s/k)+(r-divid+0.5*SQR(sigma))*t)/(sigma*sqrt(t));
    d2=d1-sigma*sqrt(t);
    w1=exp(-divid*t/2.)*cdf_nor(-val*d1c)+exp(-divid*t)*pnl_
        cdf2nor(val*d1c,-val*d1,-sqrt(0.5));
    w2=exp(-r*t/2.)*cdf_nor(-val*d2c)+exp(-r*t)*pnl_cdf2nor(
        val*d2c,-val*d2,-sqrt(0.5));
    p2=val*(k*w2-s*w1);

    /*Price*/
    *ptprice=SQR(p2)/p1;

    /*Delta*/
    *ptdelta=(*ptprice)*(-2.*val*w1/p2-delta/p1);

    return OK;
}

```

```

int CALC(AP_HoStapletonSubrahmanyam)(void *Opt,void *Mod,
    PricingMethod *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r,divid;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
    divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);

    return HoStapletonSubrahmanyam_94(ptMod->S0.Val.V_PDOUNB
        LE,
            ptOpt->PayOff.Val.V_NUMFUNC_1,
            ptOpt->Maturity.Val.V_DATE-ptMod->T.Val.V_
DATE,r,divid,
            ptMod->Sigma.Val.V_PDOUNBLE,
            &(Met->Res[0].Val.V_DOUBLE),&(Met->Res[1].
Val.V_DOUBLE) );
}

static int CHK_OPT(AP_HoStapletonSubrahmanyam)(void *Opt,
    void *Mod)
{
    if ( (strcmp( ((Option*)Opt)->Name,"CallAmer")==0) || (
        strcmp( ((Option*)Opt)->Name,"PutAmer")==0) )
        return OK;

    return WRONG;
}

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    if ( Met->init == 0)
    {
        Met->init=1;
    }

    return OK;
}

PricingMethod MET(AP_HoStapletonSubrahmanyam)=

```

```
{
  "AP_HoStapletonSubrahmanyam",
  {{" ", PREMIA_NULLTYPE, {0}, FORBID}},
  CALC(AP_HoStapletonSubrahmanyam),
  {{"Price", DOUBLE, {100}, FORBID}, {"Delta", DOUBLE, {100}, FORB
    ID} }, {" ", PREMIA_NULLTYPE, {0}, FORBID}},
  CHK_OPT(AP_HoStapletonSubrahmanyam),
  CHK_ok ,
  MET(Init)
} ;
```

References