

## Help

```
#include <stdlib.h>
#include "bs1d_pad.h"
#include "error_msg.h"

static int Babbs_95_FloatingCall(int am,double s,double s_
    min,NumFunc_2*p,double t,double r,double divid,double sigma
    ,int N,double *ptprice,double *ptdelta)
{
    int i,j,eta0,npoints;
    double u,d,h,pu,pd,a1,stock,eta,y_0;
    double *P,*iv,*Q,*Boundary;
    double upperstock;
    int odd;
    double flat_price=0.,up_price;

    /*Price, intrinsic value arrays*/
    P= malloc((2*N+1)*sizeof(double));
    if (P==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    Q= malloc((2*N+1)*sizeof(double));
    if (Q==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    iv= malloc((2*N+1)*sizeof(double));
    if (iv==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    Boundary= malloc((N+1)*sizeof(double));
    if (Boundary==NULL)
        return MEMORY_ALLOCATION_FAILURE;

    /*Up and Down factors*/
    y_0=s_min/s;
    h=t/(double)N;
    a1=exp(h*(r-divid));
    u=exp(sigma*sqrt(h));
    d=1./u;

    /*Critical Index*/
    eta=-log(y_0)/(sigma*sqrt(h));
    eta0=(int)floor(eta);
```

```

if (eta0>N)
    eta0=N;

/*Risk-Neutral Probability*/
pu=(a1-d)/(u-d);
pd=1.-pu;
pu*=exp(-r*h)*u;
pd*=exp(-r*h)*d;

if(eta0<N)
{
    /*First Stage:Computation of price value along the
    line spot=maximum*/

    /*Intrinsic value initialisation*/
    for (i=0;i<=N;i++)
Boundary[i]=0.;

    stock=1.;
    for (i=0;i<N+eta0;i++)
{
    iv[i]=(p->Compute)(p->Par,1.,stock);
    P[i]=iv[i];
    Q[i]=P[i];
    stock*=d;
    }

    Boundary[N]=P[0];

    /*Backward Resolution*/
    for (i=1;i<N-eta0;i++)
{
    P[0]=pd*Q[0]+pu*Q[1];
    if (am)
        P[0]=MAX(iv[0],P[0]);
    Boundary[N-i]=P[0];

    for (j=1;j<=N-eta0-i;j++)
    {
        P[j]=pd*Q[j-1]+pu*Q[j+1];
        if (am)

```

```

        P[j]=MAX(iv[j],P[j]);
    }

    for (j=0;j<=N-eta0-i;j++)
        Q[j]=P[j];
    }
}

if (s_min<s)
{
    /*Second Stage:Computation of price value */
    /*Intrinsic value initialization*/
    upperstock=y_0;
    for (i=0;i<N;i++)
upperstock*=d;
    stock=upperstock;
    for (i=0;i<=N+eta0;i++)
{
    iv[i]=(p->Compute)(p->Par,1.,stock);
    stock*=u;
}

    /*Terminal Values*/
    npoints=eta0+(N-eta0)/2;
    for (j=0;j<=npoints;j++)
P[j]=iv[2*j];

    /*Backward Resolution*/
    if (eta0>0) /*The first mesh does not breach the bar
rier*/
{

    /*First part-the barrier is active*/
    odd=1;
    for (i=eta0;i<N-1;i++)
        odd=!odd;

    if (!odd) npoints=npoints-1;

    for (i=1;i<=N-eta0;i++)
    {

```

```

        for (j=0;j<npoints;j++)
    {
        P[j]=pu*P[j]+ pd*P[j+1];
        if (am)
            P[j]=MAX(iv[i+2*j],P[j]);
    }

    /*Special handling of the critical node*/
    if (odd)
    {
        P[npoints]=pu*P[npoints]+pd*Boundary[N+1-i];
        if (am)
            P[npoints]=MAX(iv[i+2*npoints],P[npoints]);
    }

    /*For the critical node at the next iteration*/
    if (!odd)
    {
        npoints=npoints-1;
    }

    odd=!odd;
}

/*Second part-the barrier is strictly below the tree*/
npoints=eta0-1;
for (i=N-eta0+1;i<N;i++)
{
    for (j=0;j<=npoints;j++)
    {
        P[j]=pu*P[j]+ pd*P[j+1];
        if (am)
            P[j]=MAX(iv[i+2*j],P[j]);
    }

    npoints=npoints-1;
}

/*Delta*/
*ptdelta=(P[1]-P[0])/(y_0*(u-d));

/*First time step*/
P[0]=pu*P[0]+pd*P[1];
if (am)

```

```

    P[0]=MAX(iv[N],P[0]);
    /*Price*/
    *ptprice=P[0];
}
    else /*eta0=0, the first mesh breaches the barrier*/
{
    /*The barrier is always active*/
    odd=1;
    for (i=eta0;i<N-1;i++)
        odd=!odd;

    if (!odd) npoints=npoints-1;

    for (i=1;i<=N-eta0-1;i++) /*We go backward until the
    next date*/
    {
        flat_price=P[1]; /*Only for the delta*/

        for (j=0;j<npoinst;j++)
        {
            P[j]=pu*P[j]+ pd*P[j+1];
            if (am)
                P[j]=MAX(iv[i+2*j],P[j]);
        }

        /*Special handling of the critical node*/
        if (odd)
        {
            P[npoinst]=pu*P[npoinst]+pd*Boundary[N+1-i];
            if (am)
                P[npoinst]=MAX(iv[i+2*npoinst],P[npoinst]);;
        }

        if (!odd)
        {
            npoints=npoints-1;
        }

        odd=!odd;

    }

    up_price=P[0];    /*For the delta*/

```

```

    /*First time step*/
    P[0]=pu*P[0]+pd*P[1];

    /*Special handling of the critical node*/
    P[0]=pu*P[0]+pd*Boundary[1];
    if (am)
        P[0]=MAX(iv[N],P[0]);

    /*Delta*/
    /*Corresponds to setting a third point at level s between u*s and d*s*/
    /*One computes the finite difference approximation between s and us*/
    *ptdelta=(up_price-(exp(-r*h)*flat_price+exp(r*h)*P[0])*0.5)/(y_0*(d-1.));
} /*eta0=0*/
}

else /*s=s_min*/
    *ptdelta=(P[1]-P[0])/(d-1.);

/*Price*/
*ptprice=s*P[0];

/*Delta*/
*ptdelta=(*ptdelta)*(-y_0)+P[0];

/*Memory Desallocation*/
free(P);
free(Q);
free(iv);
free(Boundary);

return OK;

}

int CALC(TR\_Babbs\_Call)(void *Opt,void *Mod,PricingMethod *Met)
{

```

```

TYPEOPT* ptOpt=( TYPEOPT*)Opt;
TYPEMOD* ptMod=( TYPEMOD*)Mod;
double r,divid;

r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);

return Babbs_95_FloatingCall(ptOpt->EuOrAm.Val.V_BOOL,pt
    Mod->S0.Val.V_PDOUBLE,(ptOpt->PathDep.Val.V_NUMFUNC_2)->Par[4
    ].Val.V_PDOUBLE,ptOpt->PayOff.Val.V_NUMFUNC_2,ptOpt->Matu
    rity.Val.V_DATE-ptMod->T.Val.V_DATE,r,divid,ptMod->Sigma.Val
    .V_PDOUBLE,Met->Par[0].Val.V_INT2,&(Met->Res[0].Val.V_
    DOUBLE),&(Met->Res[1].Val.V_DOUBLE));
}

static int CHK_OPT(TR_Babbs_Call)(void *Opt, void *Mod)
{
    if ((strcmp(((Option*)Opt)->Name,"    LookBackCallFloatingEuro")==0) || (strcmp
        return OK;
    return WRONG;
}

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    if ( Met->init == 0)
    {
        Met->init=1;
        Met->Par[0].Val.V_INT2=1000;

    }

    return OK;
}

PricingMethod MET(TR_Babbs_Call)=
{
    "TR_Babbs_Call",
    {{{"StepNumber",INT2,{100},ALLOW},{ " ",PREMIA_NULLTYPE,{0}
        ,FORBID}}},
    CALC(TR_Babbs_Call),
    {{{"Price",DOUBLE,{100},FORBID},{ "Delta",DOUBLE,{100},FORB

```

```
    ID} ,{" ",PREMIA_NULLTYPE,{0},FORBID}},  
    CHK_OPT(TR\_Babbs\_Call),  
    CHK_tree,  
    MET(Init)  
};
```

## References