

Help

```

#include "kould_pad.h"
#include "pnl/pnl_fft.h"
#include "pnl/pnl_complex.h"
#include "pnl/pnl_vector.h"

#if defined(PremiaCurrentVersion) && PremiaCurrentVersion <
    (2010+2) //The "#else" part of the code will be freely av
    ailable after the (year of creation of this file + 2)
static int CHK_OPT(FFT_Kou_FloatingLookback)(void *Opt, voi
    d *Mod)
{
    return NONACTIVE;
}
int CALC(FFT_Kou_FloatingLookback)(void*Opt,void *Mod,Prici
    ngMethod *Met)
{
    return AVAILABLE_IN_FULL_PREMIA;
}
#else

// "resultat takes the product of a circulant matrix M(c)
    and a vextor x
static void circulante (PnlVectComplex *resultat, PnlVectC
    omplex *c, PnlVectComplex *x)
{
    PnlVectComplex *temp;
    int i,n;
    n = x->size;
    temp=pnl_vect_complex_create(n);

    pnl_fft (c, temp);
    pnl_fft (x,resultat);
    for (i=0;i<n;i++)
    {
        pnl_vect_complex_set (temp,i,Cmul (pnl_vect_complex_get
            (temp,i), pnl_vect_complex_get(resultat,i)));
    }
    pnl_ifft(temp,resultat);
    pnl_vect_complex_free(&temp);
}

```

```

// "r" takes the product of the toeplitz matrix N(v,w)
// with holes and a vector x
static void toep (PnlVectComplex *v, PnlVectComplex *w, Pn
    lVectComplex *x, PnlVectComplex *r)
{
    int M, i;
    PnlVectComplex *temp;
    PnlVectComplex *temp2;
    PnlVectComplex *x2;
    M=v->size;
    temp=pnl_vect_complex_create(4*M);
    temp2=pnl_vect_complex_create(4*M);
    x2=pnl_vect_complex_create(4*M);
    pnl_vect_complex_set(temp,0,CRmul(CONE,0.5));
    for (i=1;i<2*M+1;i=i+2)
    {
        pnl_vect_complex_set(temp,i,pnl_vect_complex_get(v,(i-1
            )/2));
        pnl_vect_complex_set(temp,i+1,CZERO);
    }
    for ( i=2*M+1;i<4*M-1;i=i+2)
    {
        pnl_vect_complex_set(temp,i,pnl_vect_complex_get(w,(M-1
            )-((i-1)-2*M)/2));
        pnl_vect_complex_set(temp,i+1,CZERO);
    }
    pnl_vect_complex_set(temp,i,pnl_vect_complex_get(w,(M-1)-
        ((4*M-1-1)-2*M)/2));
    for ( i=0;i<2*M+1;i++)
        pnl_vect_complex_set(x2,i,pnl_vect_complex_get(x,i));
    for ( i=2*M+1;i<4*M;i++)
        pnl_vect_complex_set(x2,i,CZERO);
    circulante(temp2,temp,x2);
    for ( i=0;i<2*M+1;i++)
        pnl_vect_complex_set(r,i,pnl_vect_complex_get(temp2,i))
        ;

    pnl_vect_complex_free(& temp);
    pnl_vect_complex_free(& temp2);

```

```

    pnl_vect_complex_free(& x2);
}

// the characteristic function of the Kou's model
static dcomplex fi_kou (double t,double sigma,double d,
    double lambda,double lambdap,double lambdam,double p,dcomplex w,
    double signe)
{
    dcomplex temp1,temp2,u;
    u=CRmul(w,(double)signe);
    temp1=CRmul(CRsub(Cmul(CI,u),lambdam),-1);    //temp1=(I*
        u-lambdam)*(-1)
    temp1=Conj(temp1);                            //temp1=temp1.conj(
        );
    temp2=CRadd(Cmul(CI,u),lambdap);              //temp2=I*u+lambd
        ap;
    temp2=Conj(temp2);                            //temp2=temp2.conj(
        );
    temp1=CRdiv(temp1,Csqr_norm(temp1));           //temp1=(temp1
        /temp1.norm());
    temp2=CRdiv(temp2,Csqr_norm(temp2));           //temp2=
        temp2/(temp2.norm());
    temp1=Cadd(CRmul(temp1,lambdam*p),CRsub(CRmul(temp2,lambd
        ap*(1-p)),1));    //temp1=temp1*lambdam*p+(temp2*lambdap*(1-
        p))-1;
    temp1=CRmul(temp1,-1); //temp1=temp1*-1;
    temp1=CRmul(temp1,lambda); //temp1=temp1*1;
    temp2=Csub(CRdiv(CRmul(Cmul(u,u),sigma*sigma),2.),CRmul(
        Cmul(CI,u),d)); // temp2=u*u*s*s/2-I*u*d;
    temp1=Cadd(temp2,temp1);    //temp1=temp2+temp1;

    temp1=CRmul(temp1,(-t));    //temp1=temp1*(-t);
    temp1=Cexp(temp1); //temp1=temp1.expon();

    return temp1;
}

// the characteristic function of the Kou's model after th
    e Esscher transformation
static dcomplex fi_kou_star (double t,double sigma,double

```

```

        d,double lambda,double lambdap,double lambdam,double p,dcomplex u,double x,double signe)
{
    dcomplex b;
    dcomplex a;
    dcomplex c;
    a=CRmul(CI,-1);
    c= fi_kou ( t, sigma, d, lambda, lambdap, lambdam, p, Cad
        d(u,CRmul(a,x)), signe );
    b= fi_kou ( t, sigma, d, lambda, lambdap, lambdam, p, CR
        mul(a,x) , signe);
    a=Cdiv(c,b);

    return a;
}
//The diagonal matrix which attributes the corresponding
    coefficients to the calculation of F in the Kou's model
static void F_diag_fi_kou (PnlVectComplex *v,double t,
    double sigma,double d,double lambda,double lambdap,double lambdam,double p,dcomplex h,double x,int M,double signe)
{
    int com;

    for (com=0;com<2*M+1;com++)
        pnl_vect_complex_set(v,com,Cmul(pnl_vect_complex_get(v,
            com),fi_kou_star(t,sigma,d,lambda,lambdap,lambdam,p,CRmul(h,(
                double)(M-com)),x,signe)));
}

//The diagonal matrix which attributes the corresponding
    coefficients to the calculation of G in the Kou's model
static void G_diag_fi_kou (PnlVectComplex *v,double t,
    double sigma,double d,double lambda,double lambdap,double lambdam,double p,dcomplex h, double x,int M,double signe)
{
    int i;

    for (i=0;i<2*M+1;i++)
        pnl_vect_complex_set(v,i,Cmul(pnl_vect_complex_get(v,i)
            ,fi_kou_star(t,sigma,d,lambda,lambdap,lambdam,p,Cadd(CRmul
                l(h,(double)(M-i)),CRmul(CI,x)),x, signe)));
}

```

```

}

// the estimation's algorithm in the Kou's model with "n_
// point" maximum observations, and M point of the Hilbert's
// estimation
static dcomplex estiation_kou (double Xmaxmin, PnlVectCompl
    ex *G,double t,double sigma,double d,double lambda,double
    lambdap,double lambdam,double p,dcomplex h,double x,int M,
    int n_points,double signe)
{
    int i,j;
    double Xmax;
    dcomplex C,cte,a,k;
    PnlVectComplex *v,*w,*F,*tempg,*tempf;
    F=pnl_vect_complex_create (2*M+1);
    v=pnl_vect_complex_create (M);    //the first colomn vec
    tor of the Hilbert's matrix
    w=pnl_vect_complex_create (M);    //the first line vector
    of the Hilbert's matrix
    tempg=pnl_vect_complex_create (2*M+1);
    tempf=pnl_vect_complex_create (2*M+1);
    //initialisation of v and w
    cte=CONE;
    C=CRmul(CI,M_1_PI); // 1/pi
    for (i=0;i<M;i=i+1)
        pnl_vect_complex_set (v,i,CRdiv(C,(double)(2*i+1)));
    for (i=0;i<M;i=i+1)
        pnl_vect_complex_set (w,i,CRdiv(C,(double)(-(2*i+1))));
    //intialisation of G_1, F_1 and Cte_1
    Xmax=MAX(Xmaxmin,0);
    for(i=0;i<2*M+1;i++)
    {
        pnl_vect_complex_set (F,i,Cexp( Cmul(      CRmul( CR
mul(h,(double)(i-M)) , Xmax ),CI)  ));
        pnl_vect_complex_set (G,i,Cexp(CRmul(CRadd(Cmul(CRmu
l(h,(double)(i-M)),CI),x),Xmax)));
    }
    F_diag_fi_kou (F, t, sigma, d, lambda, lambdap,lambd
am, p, h,x, M, signe); //G=( fi_kou(1)F(1),...,fi_kou(i)F(i),
...,fi_kou(2M+1)F(2M+1) )
    toep(v,w,F,tempf);

```

```

    pnl_vect_complex_clone(F,tempf);

    cte=CRmul(CRsub(pnl_vect_complex_get(F,M),1.0),-1);/
/1-f(0)

    G_diag_fi_kou (G,t, sigma, d, lambda, lambdap,lambd
am, p, h,x, M, signe);//G=( fi_kou(1)G(1),...,fi_kou(i)G(i),
...,fi_kou(2M+1)G(2M+1) )
    toep(v,w,G,tempg);//temp=C(H)*G
    pnl_vect_complex_clone (G,tempg);

for (j=1;j<n_points;j++)
{
    for(i=0;i<2*M+1;i++)
    {
        pnl_vect_complex_set (F,i,Cadd(cte,pnl_vect_
complex_get(F,i)));//F=F+cte
        pnl_vect_complex_set (G,i,Cadd(cte,pnl_vect_
complex_get(G,i)));//G=G+cte
    }
    F_diag_fi_kou (F, t, sigma, d, lambda, lambdap,lambd
am, p, h,x, M, signe);//G=( fi_kou(1)F(1),...,fi_kou(i)F(i),
...,fi_kou(2M+1)F(2M+1) )
    toep(v,w,F,tempf);//
    pnl_vect_complex_clone(F,tempf);//F=temp=H.Df*F

    G_diag_fi_kou (G,t, sigma, d, lambda, lambdap,lambd
am, p, h,x, M, signe);//G=( fi_kou(1)G(1),...,fi_kou(i)G(i),
...,fi_kou(2M+1)G(2M+1) )
    toep(v,w,G,tempg);//temp=C(H)*G
    pnl_vect_complex_clone (G,tempg);//G=temp=H.Dg*G

    cte=CRmul(CRadd(pnl_vect_complex_get(F,M),-1),-1);

}

k=RCmul(-1,CI);
a=fi_kou ( n_points*t, sigma, d, lambda, lambdap,lam
bdam, p,CRmul(k,x), signe);

```

```

    pnl_vect_complex_set (G,M,Cmul(Cadd(pnl_vect_
complex_get (G,M),cte),a));

    pnl_vect_complex_free(&v);
    pnl_vect_complex_free(&w);
    pnl_vect_complex_free(&tempf);
    pnl_vect_complex_free(&tempg);
    pnl_vect_complex_free(&F);

    return pnl_vect_complex_get(G,M);
}

static int fft_kou_lookbackfloating(double s_maxmin,
    NumFunc_2*P,double S0,double T,double r,double divid,double sigma
    ,double lambda,double lambdam,double lambdap,double p,int
    n_points,long M,double *ptprice)
{
    double pas,d,c,drift,nu,h_temp,x_maxmin,signe,beta;
    dcomplex h,res;
    PnlVectComplex *G;
    beta=0.5826;
    pas=T/n_points;
    //the width of the estimation's strip
    d=MIN(lambdam,lambdap);
    // the optimal h: h(M)//
    nu=2;
    c=sigma*sigma/2;
    h_temp=pow(((M_PI*d)/(pas*c)),1.0/(1+nu))*pow((double)M,-
        nu/(1+nu));
    h=CRmul(CONE,h_temp);
    //condition martingale//
    drift=r-divid-c+lambda*(1-((p*lambdam)/(lambdam-1))-(((1-
        p)*lambdap)/(lambdap+1)));
    G=pnl_vect_complex_create (2*M+1);
    //(pnlvectComplex *G,double t,double s,double d,double l,
        double lambdap,double lambdam,double p,dcomplex h,double x,int
        M,int n_points)
    //CALL
    if ((P->Compute)==&Call_StrikeSpot2)
    {

```

```

    s_maxmin=exp(beta*sigma*sqrt(T/n_points))*s_maxmin;
    signe=-1;
    x_maxmin=signe*log ((s_maxmin/S0));
    res=estiation_kou(x_maxmin,G,pas,sigma,drift,lambda,lam
    bdap,lambdam,p,h,signe,M,n_points, signe);
    res= CRMul(CRsub(CRmul(res,exp(-beta*sigma*sqrt(T/n_po
    ints))*exp(-r*T)),exp(-divid*T)), -S0);
}
//PUT
if ((P->Compute)==&Put_StrikeSpot2)
{
    s_maxmin=exp(-beta*sigma*sqrt(T/n_points))*s_maxmin;
    signe=1;
    x_maxmin=signe*log ((s_maxmin/S0));
    res=estiation_kou(x_maxmin,G,pas,sigma,drift,lambda,lam
    bdap,lambdam,p,h,signe,M,n_points, signe);
    res= CRMul(CRsub(CRmul(res,exp(beta*sigma*sqrt(T/n_po
    ints))*exp(-r*T)),exp(-divid*T)), S0);
}

*ptprice=Creal(res);

pnl_vect_complex_free(&G);
return OK;
}
int CALC(FFT_Kou_FloatingLookback)(void*Opt,void *Mod,Prici
    ngMethod *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r,divid;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
    divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);

    return  fft_kou_lookbackfloating((ptOpt->PathDep.Val.V_
    NUMFUNC_2)->Par[4].Val.V_PDOUBLE,ptOpt->PayOff.Val.V_NUMFUNC_2,pt
    Mod->S0.Val.V_PDOUBLE,ptOpt->Maturity.Val.V_DATE-ptMod->T.Val
    .V_DATE,r,divid,ptMod->Sigma.Val.V_PDOUBLE,ptMod->Lambda.
    Val.V_PDOUBLE,ptMod->LambdaPlus.Val.V_PDOUBLE,ptMod->LambdaM
    inus.Val.V_PDOUBLE,ptMod->P.Val.V_PDOUBLE,Met->Par[0].Val.V_

```



```

        PINT, Met->Par[1].Val.V_LONG, &(Met->Res[0].Val.V_DOUBLE));
    }

static int CHK_OPT(FFT_Kou_FloatingLookback)(void *Opt, void
    *Mod)
{
    if ((strcmp(((Option*)Opt)->Name, "    LookBackCallFloatingEuro")==0) || (strcmp
        return OK;
    return WRONG;
}

#endif //PremiaCurrentVersion
static int MET(Init)(PricingMethod *Met, Option *Mod)
{
    if ( Met->init == 0)
    {
        Met->init=1;
        Met->HelpFilenameHint = "    ap_kou_lookbackfloating_fft";
        Met->Par[0].Val.V_PINT=100;
        Met->Par[1].Val.V_LONG=512;
    }
    return OK;
}

PricingMethod MET(FFT_Kou_FloatingLookback)=
{
    "FFT_Kou_LookbackFloating",
    {{"Number of discretization steps", LONG, {100}, ALLOW}, {"N
        Truncation level (a power of 2)", LONG, {100}, ALLOW}, {" ", PREM
        IA_NULLTYPE, {0}, FORBID}},
    CALC(FFT_Kou_FloatingLookback),
    {{"Price", DOUBLE, {100}, FORBID}, {" ", PREMIA_NULLTYPE, {0},
        FORBID}},
    CHK_OPT(FFT_Kou_FloatingLookback),
    CHK_ok,
    MET(Init)
} ;

```

References