

Help

```

#include "merhes1d_pad.h"
#include "math/alfonsi.h"
#include "enums.h"

#if defined(PremiaCurrentVersion) && PremiaCurrentVersion <
    (2010+2) //The "#else" part of the code will be freely available after the (year of creation of this file + 2)
static int CHK_OPT(MC_AsianAlfonsi_Bates)(void *Opt, void *Mod)
{
    return NONACTIVE;
}
int CALC(MC_AsianAlfonsi_Bates)(void *Opt, void *Mod, PricingMethod *Met)
{
    return AVAILABLE_IN_FULL_PREMIA;
}
#else

static int MCAsianAlfonsiBates(double S0, NumFunc_2 *p,
    double t, double r, double divid, double V0, double k, double theta,
    double sigma, double rho, double mu_jump, double gamma2,
    double lambda, long nb, int M, int generator, double confidence,
    int flag_cir, double *ptprice, double *ptdelta, double *pterror_price,
    double *pterror_delta, double *inf_price, double *sup_price,
    double *inf_delta, double *sup_delta)
{
    long i, ipath;
    double price_sample, delta_sample, mean_price, mean_delta,
        var_price, var_delta;
    int init_mc;
    int simulation_dim;
    double alpha, z_alpha;
    double S_T, A_T, g1, g2;
    double h = t / (double)M;
    double sqrt_h = sqrt(h);
    double *X1a, *X2a, *X3a, *X4a;
    double w_t_1, w_t_2;
    double aaa = k * theta;
    double Kseuil, aux;

```

```

double mu=r-divid;
double prev_jump=0;
double next_jump;
double h2,sqrt_h2,jump;
double correction_mg;
double mu2,sg_jump;

sg_jump=sqrt(gamma2);
correction_mg=lambda*(exp(mu_jump+0.5*gamma2)-1);
mu2=mu-correction_mg;
if(flag_cir==1)
    Kseuil=MAX((0.25*SQR(sigma)-aaa)*psik(h*0.5,k),0.);
else
{
    if (k==0)
        Kseuil=1;
    else Kseuil=(exp(k*h)-1)/(h*k);
    if (sigma*sigma <= 4*k*theta/3) {

        Kseuil=Kseuil*sigma*sqrt(k*theta-sigma*sigma/4)/sqrt(2);
    }
    if (sigma*sigma > 4*k*theta/3 && sigma*sigma <= 4*k*theta){
        aux=(0.5*sigma*sqrt(3+sqrt(6))+sqrt(sigma*sigma/4 - k*theta+sigma*sqrt(-sigma*sigma/4+ k*theta)/sqrt(2)));
        Kseuil=Kseuil*SQR(aux);
    }
    if (sigma*sigma > 4*k*theta){
        aux=0.5*sigma*sqrt(3+sqrt(6))+ sqrt(sigma*sqrt(sigma*sigma/4- k*theta)/sqrt(2));
        Kseuil=Kseuil*(sigma*sigma/4 - k*theta + SQR(aux));
    }
    if (sigma*sigma == 4*k*theta) Kseuil=0;
}

/*Memory allocation*/
X1a = malloc(sizeof(double)*(M+1));
X2a = malloc(sizeof(double)*(M+1));
X3a = malloc(sizeof(double)*(M+1));
X4a = malloc(sizeof(double)*(M+1));

```

```

/* Value to construct the confidence interval */
alpha= (1.- confidence)/2.;
z_alpha= pnl_inv_cdfnor(1.- alpha);

/*Initialisation*/
mean_price= 0.0;
mean_delta= 0.0;
var_price= 0.0;
var_delta= 0.0;

/* Size of the random vector we need in the simulation */
simulation_dim= M;

/* MC sampling */
init_mc= pnl_rand_init(generator, simulation_dim,nb);
/* Test after initialization for the generator */
if(init_mc == OK)
{

    for(ipath= 1;ipath<= nb;ipath++)
    {
        /* Begin of the N iterations */
        X1a[0]=V0; X2a[0]=0; X3a[0]=S0; X4a[0]=0;
        next_jump=-log(pnl_rand_uni(generator))/lambda;
        for(i=1 ; i<=M ; i++)
        {

            /*Discrete law obtained by matching of first
            five moments of a gaussian r.v.*/
            if (next_jump > (double)i*h)
            {
                if(flag_cir==1)
                    g1=DiscLawMatch5(generator);
                else
                    g1=DiscLawMatch7(generator);
                w_t_1=sqrt_h*g1;

                g2= pnl_rand_normal(generator);
                w_t_2=sqrt_h*g2;
            }
        }
    }
}

```

```

X1a[i]=X1a[i-1];
X2a[i]=X2a[i-1];
X3a[i]=X3a[i-1];
X4a[i]=X4a[i-1];
fct_Heston(&X1a[i],&X2a[i],&X3a[i],&X4a[
i],
                                h,w_t_1,w_t_2,aaa,k,sigma,mu2,
rho,Kseuil,generator,flag_cir);
    }
    else
    {
        h2=next_jump-(i-1)*h;
        sqrt_h2=sqrt(h2);
        X1a[i]=X1a[i-1];
        X2a[i]=X2a[i-1];
        X3a[i]=X3a[i-1];
        X4a[i]=X4a[i-1];
        while (next_jump <= (double)i*h)
        {

            if(flag_cir==1)
                g1=DiscLawMatch5(generator);
            else
                g1=DiscLawMatch7(generator);
            w_t_1=sqrt_h2*g1;

            g2= pnl_rand_normal(generator);
            w_t_2=sqrt_h2*g2;
            fct_Heston(&X1a[i],&X2a[i],&X3a[i],&X
4a[i],
                                h2,w_t_1,w_t_2,aaa,k,sigma
,mu2,rho,Kseuil,generator,flag_cir);
                prev_jump=next_jump;
                next_jump=next_jump-log(pnl_rand_uni(generator))/lambd
                h2=next_jump-prev_jump;
                sqrt_h2=sqrt(h2);
                jump= exp(mu_jump+sg_jump*pnl_rand_
normal(generator));
                X3a[i]= X3a[i]*jump;
        }

```

```

        h2=i*h-prev_jump;
        sqrt_h2=sqrt(h2);

        if(flag_cir==1)
            g1=DiscLawMatch5(generator);
        else
            g1=DiscLawMatch7(generator);
        w_t_1=sqrt_h2*g1;

        g2= pnl_rand_normal(generator);
        w_t_2=sqrt_h2*g2;
        fct_Heston(&X1a[i],&X2a[i],&X3a[i],&X4a[
i],
                                h2,w_t_1,w_t_2,aaa,k,sigma,mu2
, rho,Kseuil,generator,flag_cir);
    }
}
/*Price*/
A_T=1./t*X4a[M];
S_T=X3a[M];
price_sample=(p->Compute)(p->Par,S_T,A_T);

/* Delta */
if(price_sample >0.0)
    delta_sample=(A_T/S0);
else delta_sample=0.;

/* Sum */
mean_price+= price_sample;
mean_delta+= delta_sample;

/* Sum of squares */
var_price+= SQR(price_sample);
var_delta+= SQR(delta_sample);
}
/* End of the N iterations */

/* Price estimator */
*ptprice=(mean_price/(double)nb);
*pterror_price= exp(-r*t)*sqrt(var_price/(double)nb-

```

```

    SQR(*ptprice))/sqrt((double)nb-1);
    *ptprice= exp(-r*t)*(*ptprice);

    /* Price Confidence Interval */
    *inf_price= *ptprice - z_alpha*(*pterror_price);
    *sup_price= *ptprice + z_alpha*(*pterror_price);

    /* Delta estimator */
    *ptdelta=exp(-r*t)*(mean_delta/(double)nb);
    if((p->Compute) == &Put_OverSpot2)
        *ptdelta *= (-1);
    *pterror_delta= sqrt(exp(-2.0*r*t)*(var_delta/(
double)nb-SQR(*ptdelta)))/sqrt((double)nb-1);

    /* Delta Confidence Interval */
    *inf_delta= *ptdelta - z_alpha*(*pterror_delta);
    *sup_delta= *ptdelta + z_alpha*(*pterror_delta);
}

/*Memory desallocation*/
free(X1a);
free(X2a);
free(X3a);
free(X4a);

return init_mc;
}

int CALC(MC_AsianAlfonsi_Bates)(void *Opt, void *Mod, Prici
ngMethod *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r,divid;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
    divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);

    return MCAsianAlfonsiBates(ptMod->SO.Val.V_PDOUBLE,

```

```

        ptOpt->PayOff.Val.V_NUMFUNC_2,
        ptOpt->Maturity.Val.V_DATE-ptMod->T.Val.
V_DATE,
        r,
        divid, ptMod->Sigma0.Val.V_PDOUBLE
        ,ptMod->MeanReversion.hal.V_PDOUB
LE,
        ptMod->LongRunVariance.Val.V_PDOUB
LE,
        ptMod->Sigma.Val.V_PDOUBLE,
        ptMod->Rho.Val.V_PDOUBLE,
        ptMod->Mean.Val.V_PDOUBLE,
        ptMod->Variance.Val.V_PDOUBLE,
        ptMod->Lambda.Val.V_PDOUBLE,
        Met->Par[0].Val.V_LONG,
        Met->Par[1].Val.V_INT,
        Met->Par[2].Val.V_ENUM.value,
        Met->Par[3].Val.V_PDOUBLE,
        Met->Par[4].Val.V_ENUM.value,
        &(Met->Res[0].Val.V_DOUBLE),
        &(Met->Res[1].Val.V_DOUBLE),
        &(Met->Res[2].Val.V_DOUBLE),
        &(Met->Res[3].Val.V_DOUBLE),
        &(Met->Res[4].Val.V_DOUBLE),
        &(Met->Res[5].Val.V_DOUBLE),
        &(Met->Res[6].Val.V_DOUBLE),
        &(Met->Res[7].Val.V_DOUBLE));
}

static int CHK_OPT(MC_AsianAlfonsi_Bates)(void *Opt, void *
Mod)
{
    if ( (strcmp( ((Option*)Opt)->Name,"AsianCallFixedEuro")=
=0)
        || (strcmp( ((Option*)Opt)->Name,"    AsianPutFixedEuro")==0) )
        {
            return OK;
        }
    return WRONG;
}

```

```

#endif //PremiaCurrentVersion

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    //int type_generator;
    if ( Met->init == 0)
    {
        Met->init=1;
        Met->HelpFilenameHint = "      mc_am_asian_alfonsi_andersenbroadie_merhes";
        Met->Par[0].Val.V_LONG=15000;
        Met->Par[1].Val.V_INT=100;
        Met->Par[2].Val.V_ENUM.value=0;
        Met->Par[2].Val.V_ENUM.members=&PremiaEnumMCRNGs;
        Met->Par[3].Val.V_DOUBLE= 0.95;
        Met->Par[4].Val.V_ENUM.value=2;
        Met->Par[4].Val.V_ENUM.members=&PremiaEnumCirOrder;
    }

    return OK;
}

PricingMethod MET(MC_AsianAlfonsi_Bates)=
{
    "MC_Alfonsi_Asian_Bates",
    {"N iterations",LONG,{100},ALLOW},
    {"TimeStepNumber",LONG,{100},ALLOW},
    {"RandomGenerator",ENUM,{100},ALLOW},
    {"Confidence Value",DOUBLE,{100},ALLOW},
    {"Cir Order",ENUM,{100},ALLOW},
    {" ",PREMIA_NULLTYPE,{0},FORBID}},
    CALC(MC_AsianAlfonsi_Bates),
    {"Price",DOUBLE,{100},FORBID},
    {"Delta",DOUBLE,{100},FORBID} ,
    {"Error Price",DOUBLE,{100},FORBID},
    {"Error Delta",DOUBLE,{100},FORBID} ,
    {"Inf Price",DOUBLE,{100},FORBID},
    {"Sup Price",DOUBLE,{100},FORBID} ,
    {"Inf Delta",DOUBLE,{100},FORBID},
    {"Sup Delta",DOUBLE,{100},FORBID} ,
    {" ",PREMIA_NULLTYPE,{0},FORBID}},
    CHK_OPT(MC_AsianAlfonsi_Bates),

```



```
    CHK_mc,  
    MET(Init)  
};
```

References