

Help

```
#include <stdlib.h>
#include "bs1d_std.h"
#include "error_msg.h"
#include "enums.h"

static double *Q=NULL, *Weights=NULL, *Trans=NULL, *Price=
    NULL;
static double *Aux_Path=NULL,*Aux_Stock=NULL,*Aux_BS=NULL;
static double *Sigma=NULL;
static int *Path_Int=NULL;

static int RaQ_Allocation(int AL_T_Size, int BS_Dimension,
    int OP_Exercise_Dates)
{
    if (Q==NULL)
        Q= malloc(AL_T_Size*OP_Exercise_Dates*BS_Dimension*sizeof(
            double));
    if (Q==NULL)
        return MEMORY_ALLOCATION_FAILURE;

    if (Trans==NULL)
        Trans= malloc(OP_Exercise_Dates*AL_T_Size*AL_T_Size*sizeof(
            double));
    if (Trans==NULL)
        return MEMORY_ALLOCATION_FAILURE;

    if (Weights==NULL)
        Weights= malloc(OP_Exercise_Dates*AL_T_Size*sizeof(
            double));
    if (Weights==NULL)
        return MEMORY_ALLOCATION_FAILURE;

    if (Price==NULL)
        Price= malloc(OP_Exercise_Dates*AL_T_Size*sizeof(
            double));
    if (Price==NULL)
        return MEMORY_ALLOCATION_FAILURE;

    if (Aux_Path==NULL)
        Aux_Path= malloc(OP_Exercise_Dates*BS_Dimension*sizeof(
```

```
double));
if (Aux_Path==NULL)
    return MEMORY_ALLOCATION_FAILURE;

if (Aux_Stock==NULL)
    Aux_Stock= malloc(BS_Dimension*sizeof(double));
if (Aux_Stock==NULL)
    return MEMORY_ALLOCATION_FAILURE;

if (Aux_BS==NULL)
    Aux_BS= malloc(BS_Dimension*sizeof(double));
if (Aux_BS==NULL)
    return MEMORY_ALLOCATION_FAILURE;

if (Sigma==NULL)
    Sigma= malloc(BS_Dimension*BS_Dimension*sizeof(double))
    ;
if (Sigma==NULL)
    return MEMORY_ALLOCATION_FAILURE;

if (Path_Int==NULL)
    Path_Int= malloc(OP_Exercice_Dates*sizeof(int));
if (Path_Int==NULL)
    return MEMORY_ALLOCATION_FAILURE;

return OK;
}

static void RaQ_Liberation()
{
    if (Q!=NULL) {
        free(Q);
        Q=NULL;
    }
    if (Trans!=NULL) {
        free(Trans);
        Trans=NULL;
    }
    if (Weights!=NULL) {
        free(Weights);
        Weights=NULL;
    }
}
```

```

    }
    if (Price!=NULL) {
        free(Price);
        Price=NULL;
    }
    if (Aux_Path!=NULL) {
        free(Aux_Path);
        Aux_Path=NULL;
    }
    if (Aux_Stock!=NULL) {
        free(Aux_Stock);
        Aux_Stock=NULL;
    }

    if (Aux_BS!=NULL) {
        free(Aux_BS);
        Aux_BS=NULL;
    }

    if (Sigma!=NULL) {
        free(Sigma);
        Sigma=NULL;
    }
    if (Path_Int!=NULL) {
        free(Path_Int);
        Path_Int=NULL;
    }
    return;
}

static int NearestCell(int Time, int AL_T_Size, long OP_Em
    BS_Di, int BS_Dimension)
{
    int j,k,l=0;
    double min=DBL_MAX,aux,auxnorm;
    for (j=0;j<AL_T_Size;j++){
        aux=0;
        for (k=0;k<BS_Dimension;k++){
            auxnorm=Aux_Path[Time*BS_Dimension+k]-
            Q[(long)j*OP_EmBS_Di+Time*BS_Dimension+k];
            aux+=auxnorm*auxnorm;

```

```

    }
    if (min>aux){
        min=aux;
        l=j;
    }
}
return l;
}

static void ForwardPath(double *Path, double *Initial_Stock
    , int Initial_Time,int Number_Dates,int generator,int BS_
    Dimension, double Step, double Sqrt_Step)
{
    int i,j,k;
    double aux;
    double *SigmapjmBS_Dimensionpk;

    for (j=0;j<BS_Dimension;j++) Path[Initial_Time*BS_Dimens
        ion+j]=Initial_Stock[j];

    for (i=Initial_Time+1;i<Initial_Time+Number_Dates;i++){
        for (j=0;j<BS_Dimension;j++){
            Aux_Stock[j]=Sqrt_Step*pn1_rand_normal(generator);
        }
        SigmapjmBS_Dimensionpk=Sigma;

        for (j=0;j<BS_Dimension;j++){
            aux=0.;
            for (k=0;k<=j;k++){
                aux+=(*SigmapjmBS_Dimensionpk)*Aux_Stock[k];
            }
            SigmapjmBS_Dimensionpk+=BS_Dimension-j-1;
            aux-=Step*Aux_BS[j];
            Path[i*BS_Dimension+j]=Path[(i-1)*BS_Dimension+j]*exp
                (aux);
        }
    }
}

```

```

static double Discount(double Time, double BS_Interest_Rate)
{
    return exp(-BS_Interest_Rate*Time);
}

static void Init_Tesselations(long AL_MonteCarlo_Iterations
    , int AL_T_Size,int OP_Exercice_Dates,int generator,int
    BS_Dimension, double *BS_Spot,double Step, double Sqrt_Step)
{
    int i,j,k,Vimoins,Vi;
    long l;
    long OP_ExmBS_Di=(long)OP_Exercice_Dates*BS_Dimension;

    /* Random Quantizers */
    for (i=0;i<AL_T_Size;i++)
        ForwardPath(Q+i*OP_Exercice_Dates*BS_Dimension,BS_Spot,
            0,OP_Exercice_Dates,
            generator,BS_Dimension,Step,Sqrt_Step);

    /* Weights and Transitions */
    for (i=0;i<OP_Exercice_Dates;i++)
        for (j=0;j<AL_T_Size;j++)
            Weights[i*AL_T_Size+j]=0;

    for (i=0;i<OP_Exercice_Dates;i++)
        for (j=0;j<AL_T_Size;j++)
            for (k=0;k<AL_T_Size;k++)
                Trans[i*AL_T_Size*AL_T_Size+j*AL_T_Size+k]=0;

    for (l=0;l<AL_MonteCarlo_Iterations-AL_T_Size;l++){

        /*Black-Sholes Paths from time 0 to maturity*/
        ForwardPath(Aux_Path,BS_Spot,0,OP_Exercice_Dates, generator,BS_Dimension,

        Vimoins=0;
        for (i=1;i<OP_Exercice_Dates;i++){
            Vi=NearestCell(i,AL_T_Size,OP_ExmBS_Di,BS_Dimension);
            Weights[i*AL_T_Size+Vi]+=1;
            Trans[i*AL_T_Size*AL_T_Size+Vimoins*AL_T_Size+Vi]+=1;
            Vimoins=Vi;
        }
    }
}

```

```

    }
}
Weights[0]=AL_MonteCarlo_Iterations-AL_T_Size;
for (i=1;i<OP_Exercise_Dates;i++)
    for (j=0;j<AL_T_Size;j++)
        if (Weights[(i-1)*AL_T_Size+j]>0)
for (k=0;k<AL_T_Size;k++)
    Trans[i*AL_T_Size*AL_T_Size+j*AL_T_Size+k]/=Weights[(i-1)*AL_T_Size+j];
}

static void RaQ(double *PrixDir,long MC_Iterations,NumFunc_
    1 *p,int size,int Fermeture,int generator,int exercise_date_number,double *s_vector, double t, double r, double divid, double sigma,int gj_flag)
{
    int i,j,k,BS_Dimension=1;
    long l;
    double step,Sqrt_Step,DiscountStep,aux,AL_BPrice,AL_FPrice;
    AL_FPrice=0.0;
    *PrixDir=0.;
    step=t/(exercise_date_number-1.);
    Sqrt_Step=sqrt(step);
    DiscountStep=exp(-r*step);

    /*Memory Allocation*/
    RaQ_Allocation(size,BS_Dimension,exercise_date_number);

    /*Black-Sholes initialization parameters*/
    *Sigma=sigma;
    Aux_BS[0]=0.5*SQR(sigma)-r+divid;

    /* Cells Weights and Transitions probabilities */
    Init_Tessellations(MC_Iterations,size,exercise_date_number,generator,BS_Dimension,s_vector,step,Sqrt_Step);

    for (i=0;i<size;i++)
        Price[(exercise_date_number-1)*size+i]=0;

```

```

/* Dynamical programming (backward price)*/
for (i=exercise_date_number-2;i>=1;i--) {
    for (j=0;j<size;j++){
        aux=0;

        /*Payoff control variate*/
        for (k=0;k<size;k++) {
            aux+=(Price[(i+1)*size+k]+(p->Compute)(p->Par,*(Q+k*exercise_date_number*BS_Dimension+(i+1)*BS_Dimension)))*Trans[(i+1)*size*size+j*size+k];
        }
        aux*=DiscountStep;
        aux-=(p->Compute)(p->Par,*(Q+j*exercise_date_number*BS_Dimension+i*BS_Dimension));
        Price[i*size+j]=MAX(0.,aux);
    }
}

aux=0;
for (k=0;k<size;k++)
    aux+=(Price[size+k]+(p->Compute)(p->Par,*(Q+k*exercise_date_number*BS_Dimension+BS_Dimension)))*Trans[size*size+k];
/*Backward Price*/
aux*=DiscountStep;
if(!gj_flag)
    AL_BPrice=MAX((p->Compute)(p->Par,s_vector[0]),aux);
else AL_BPrice=aux;

/* Forward price */
for (k=0;k<size;k++){
    Price[k]=AL_BPrice-(p->Compute)(p->Par,s_vector[0]);
}

for (j=0;j<size;j++){
    i=-1;
    do {
        i++;
    }
}

```

```

    while (0<Price[i*size+j]);

    AL_FPrice+=Discount((double)i*step,r)*(Price[i*size+j]+
    (p->Compute)(p->Par,*(Q+j*exercise_date_number*BS_Dimensio
    n+i*BS_Dimension)));
}

for (l=0;l<MC_Iterations-size;l++){
    ForwardPath(Aux_Path,s_vector,0,exercise_date_number,      generator,BS_Dimens
    Path_Int[0]=0;
    for (i=1;i<exercise_date_number;i++){
        Path_Int[i]=NearestCell(i,size,exercise_date_number*
        BS_Dimension,BS_Dimension);
    }

    i=-1;
    do {
        i++;
    }
    while (0<Price[i*size+Path_Int[i]]);
    AL_FPrice+=Discount((double)i*step,r)*(Price[i*size+
    Path_Int[i]]+(p->Compute)(p->Par,*(Q+Path_Int[i]*exercise_date_
    number*BS_Dimension+i*BS_Dimension)));
}
AL_FPrice/=(double)MC_Iterations;

/*Price = Mean of Forward and Backward Price*/
*PrixDir=0.5*(AL_FPrice+AL_BPrice);

/*Memory Disallocation*/
if (Fermeture)
    RaQ_Liberation();

return;
}

static int MCRandomQuantization(double s, NumFunc_1 *p,
    double t, double r, double divid, double sigma, long N, int      generator, d
    double *ptprice, double *ptdelta)
{

```



```

double p1,p2,p3;
int simulation_dim=1,fermeture=1,init_mc;
double s_vector[1];
double s_vector_plus[1];

/*Initialisation*/
s_vector[0]=s;
s_vector_plus[0]=s*(1.+inc);

/*MC sampling*/
init_mc= pnl_rand_init(generator,simulation_dim,N);

/* Test after initialization for the generator */
if(init_mc == OK)
{

    /*Geske-Johnson Formulae*/
    if (exercise_date_number==0) {
RaQ(&p1,N,p,size_tesselation,fermeture,generator,2,s_vector,t,r,divid,sigma,1);
RaQ(&p2,N,p,size_tesselation,fermeture,generator,3,s_vector,t,r,divid,sigma,1);
RaQ(&p3,N,p,size_tesselation,fermeture,generator,4,s_vector,t,r,divid,sigma,1);
*ptprice=p3+7./2.*(p3-p2)-(p2-p1)/2.;
    } else {
RaQ(ptprice,N,p,size_tesselation,fermeture,generator,exercise_date_number,s_vector,t,r,divid,sigma,0);
    }

    /*Delta*/
    init_mc= pnl_rand_init(generator,simulation_dim,N);

    if (exercise_date_number==0){
RaQ(&p1,N,p,size_tesselation,fermeture,generator,2,s_vector_plus,t,r,divid,sigma,1);
RaQ(&p2,N,p,size_tesselation,fermeture,generator,3,s_vector_plus,t,r,divid,sigma,1);
RaQ(&p3,N,p,size_tesselation,fermeture,generator,4,s_vector

```

```

        tor_plus,t,r,divid,sigma,1);
*ptdelta=((p3+7./2.*(p3-p2)-(p2-p1)/2.)*ptprice)/(s*inc
);
    } else {
RaQ(&p1,N,p,size_tesselation,fermeture,generator,exercis
e_date_number,s_vector_plus,t,r,divid,sigma,0);
*ptdelta=(p1-*ptprice)/(s*inc);
    }
}
return init_mc;
}

int CALC(MC_RandomQuantization)(void *Opt, void *Mod, Prici
ngMethod *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r,divid;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
    divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);

    return MCRandomQuantization(ptMod->S0.Val.V_PDOUBLE,
        ptOpt->PayOff.Val.V_NUMFUNC_1,
        ptOpt->Maturity.Val.V_DATE-ptMod->T.Val.V_DA
TE,
        r,
        divid,
        ptMod->Sigma.Val.V_PDOUBLE,
        Met->Par[0].Val.V_LONG,
        Met->Par[1].Val.V_ENUM.value,
        Met->Par[2].Val.V_PDOUBLE,
        Met->Par[3].Val.V_INT,
        Met->Par[4].Val.V_INT,
        &(Met->Res[0].Val.V_DOUBLE),
        &(Met->Res[1].Val.V_DOUBLE));
}

static int CHK_OPT(MC_RandomQuantization)(void *Opt, void *
Mod)
{

```

```

Option* ptOpt=(Option*)Opt;
TYPEOPT* opt=(TYPEOPT*)(ptOpt->TypeOpt);

if ((opt->EuOrAm).Val.V_BOOL==AMER)
    return OK;
else
    return WRONG;
}

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    if ( Met->init == 0)
    {
        Met->init=1;
        Met->Par[0].Val.V_LONG=20000;
        Met->Par[1].Val.V_ENUM.value=0;
        Met->Par[1].Val.V_ENUM.members=&PremiaEnumMCRNGs;
        Met->Par[2].Val.V_PDOUBLE=0.01;
        Met->Par[3].Val.V_INT=20;
        Met->Par[4].Val.V_INT=150;

    }
    return OK;
}

PricingMethod MET(MC_RandomQuantization)=
{
    "MC_RandomQuantization",
    {{ "N iterations",LONG,{100},ALLOW},
      {"RandomGenerator",ENUM,{100},ALLOW},
      {"Delta Increment Rel",PDOUBLE,{100},ALLOW},
      {"Number of Exercise Dates (0->Geske Johnson Formulae",
        INT,{100},ALLOW},
      {"Tesselation Size",INT,{100},ALLOW},
      {" ",PREMIA_NULLTYPE,{0},FORBID}}},
    CALC(MC_RandomQuantization),
    {{ "Price",DOUBLE,{100},FORBID},
      {"Delta",DOUBLE,{100},FORBID} ,
      {" ",PREMIA_NULLTYPE,{0},FORBID}}},

```

```
CHK_OPT(MC_RandomQuantization),  
CHK_mc,  
MET(Init)  
};
```

References