```
Help
#include <stdlib.h>
#include "bs1d pad.h"
#include "math/ap fusai levy/QDiscreteAsian.h"
#include "math/ap fusai levy/nrutil.h"
#if defined(PremiaCurrentVersion) && PremiaCurrentVersion <</pre>
     (2008+2) //The "#else" part of the code will be freely av
    ailable after the (year of creation of this file + 2)
static int CHK_OPT(AP_FixedAsian_FusaiMeucci)(void *Opt,
    void *Mod)
{
  return NONACTIVE;
int CALC(AP_FixedAsian_FusaiMeucci)(void *Opt,void *Mod,
    PricingMethod *Met)
{
return AVAILABLE_IN_FULL_PREMIA;
#else
static int FusaiMeucci_FixedAsian(double pseudo_stock,
    double pseudo_strike,NumFunc_2 *po,double t,double r,double div
    id, double sigma, int N, int M, double *ptprice, double *ptdelt
    a)
{
  double CTtK,PTtK,Dlt,Plt;
  double lowlim=10.,uplim=15.;
  long int nfft=65536;
  double *price,*solution,delta;
  price=dvector(0,M-1);
  solution=dvector(0,M-1);
  /* Call Price */
  CTtK=Asian_BS_FusaiMeucci(pseudo_stock,pseudo_strike, t,
    r,divid,sigma,N,lowlim,uplim,M, nfft,price,solution,&delta)
  /* Put Price from Parity*/
  if(r==divid)
```

```
PTtK=CTtK+pseudo strike*exp(-r*t)-pseudo stock*exp(-r*
  else
    PTtK=CTtK+pseudo strike*exp(-r*t)-pseudo stock*exp(-r*
    t)*(exp((r-divid)*t)-1.)/(t*(r-divid));
  /*Delta for call option*/
  Dlt=delta:
  /*Delta for put option*/
  if(r==divid)
    Plt=Dlt-exp(-r*t);
  else
    Plt=Dlt-exp(-r*t)*(exp((r-divid)*t)-1.0)/(t*(r-divid));
  /*Price*/
  if ((po->Compute) == &Call OverSpot2)
    *ptprice=CTtK;
  else
    *ptprice=PTtK;
  /*Delta */
  if ((po->Compute) == &Call OverSpot2)
    *ptdelta=Dlt;
  else
    *ptdelta=Plt;
  free dvector(price,0,M-1);
  free_dvector(solution,0,M-1);
  return OK;
}
int CALC(AP_FixedAsian_FusaiMeucci)(void *Opt,void *Mod,
    PricingMethod *Met)
{
  TYPEOPT* ptOpt=(TYPEOPT*)Opt;
  TYPEMOD* ptMod=(TYPEMOD*)Mod;
  int return_value;
  double r,divid,time_spent,pseudo_spot,pseudo_strike;
```

```
double t 0, T 0;
r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
divid=log(1.+ptMod->Divid.Val.V DOUBLE/100.);
T 0 = ptMod->T.Val.V DATE;
t_0= (ptOpt->PathDep.Val.V_NUMFUNC_2)->Par[0].Val.V_PDOUB
if(T_0 < t_0)
  {
    Fprintf(TOSCREEN, "T 0 < t 0, untreated case{n{n{n");}</pre>
    return_value = WRONG;
/* Case t_0 <= T_0 */
else
  {
    time_spent=(ptMod->T.Val.V_DATE-(ptOpt->PathDep.Val.
  V NUMFUNC 2)->Par[0].Val.V PDOUBLE)/(ptOpt->Maturity.Val.V
  DATE-(ptOpt->PathDep.Val.V NUMFUNC 2)->Par[0].Val.V PDOUB
    pseudo_spot=(1.-time_spent)*ptMod->SO.Val.V_PDOUBLE;
    pseudo strike=(ptOpt->PayOff.Val.V NUMFUNC 2)->Par[0]
  .Val.V_PDOUBLE-time_spent*(ptOpt->PathDep.Val.V_NUMFUNC_2)
  ->Par[4].Val.V PDOUBLE;
    if (pseudo strike <= 0.) {
Fprintf(TOSCREEN, "ANALYTIC FORMULA{n{n{n");
return_value=Analytic_KemnaVorst(pseudo_spot,pseudo_stri
  ke, time spent, ptOpt->PayOff.Val.V NUMFUNC 2, ptOpt->Maturit
  y.Val.V DATE-ptMod->T.Val.V DATE,r,divid,&(Met->Res[0].Val.
  V DOUBLE),&(Met->Res[1].Val.V DOUBLE));
    }
    else
return value= FusaiMeucci FixedAsian(pseudo spot,pseudo
  strike,ptOpt->PayOff.Val.V_NUMFUNC_2,ptOpt->Maturity.Val.V_DA
  TE-ptMod->T.Val.V_DATE,r,divid,ptMod->Sigma.Val.V_PDOUBLE,
  Met->Par[0].Val.V INT2,Met->Par[1].Val.V INT2,&(Met->Res[0].
  Val.V DOUBLE),&(Met->Res[1].Val.V DOUBLE));
  }
```

```
return return value;
}
static int CHK OPT(AP FixedAsian FusaiMeucci)(void *Opt,
    void *Mod)
  if ((strcmp(((Option*)Opt)->Name, "AsianCallFixedEuro")==
    0) || (strcmp( ((Option*)Opt)->Name, "AsianPutFixedEuro")==
    0))
    return OK;
  return WRONG;
#endif //PremiaCurrentVersion
static int MET(Init)(PricingMethod *Met,Option *Opt)
{
   if (Met->init == 0)
      Met->init=1;
      Met->Par[0].Val.V INT2=52;
      Met->Par[1].Val.V_INT2=3000;
  return OK;
PricingMethod MET(AP FixedAsian FusaiMeucci)=
  "AP FixedAsian FusaiMeucci",
  {{"Nb.of Monitoring Dates", INT2, {2000}, ALLOW },
   {"Nb.of Integration Points ",INT2,{1000},ALLOW},
   {" ",PREMIA NULLTYPE, {0}, FORBID}},
  CALC(AP FixedAsian FusaiMeucci),
  {{"Price",DOUBLE,{100},FORBID},{"Delta",DOUBLE,{100},FORB
    ID} ,{" ",PREMIA NULLTYPE,{0},FORBID}},
  CHK OPT(AP FixedAsian FusaiMeucci),
  CHK ok,
  MET(Init)
};
```

References