

Help

```

#include <stdlib.h>
#include "bs1d_lim.h"
#include "error_msg.h"
#define PRECISION 1.0e-7 /*Precision for the localization
of FD methods*/

static int Psor_UpOut(double s,NumFunc_1 *p,double l,
double rebate,double t,double r,double divid,double sigma,int N,
int M,double theta,double omega,double epsilon,double *pt
price,double *ptdelta)
{
int      Index,PriceIndex,TimeIndex;
int      j,loops;
double   k,vv,loc,h,z,alpha,beta,gamma,y,alpha1,beta1,gam
ma1,up,upwind_alphacoef;
double   error,norm,x;
double   *P,*Obst,*Rhs;

/*Memory Allocation*/
P= malloc((N+2)*sizeof(double));
if (P==NULL)
return MEMORY_ALLOCATION_FAILURE;
Obst= malloc((N+2)*sizeof(double));
if (Obst==NULL)
return MEMORY_ALLOCATION_FAILURE;
Rhs= malloc((N+2)*sizeof(double));
if (Rhs==NULL)
return MEMORY_ALLOCATION_FAILURE;

/*Time Step*/
k=t/(double)M;

/*Space Localisation*/
vv=0.5*sigma*sigma;
z=(r-divid)-vv;
loc=sigma*sqrt(t)*sqrt(log(1.0/PRECISION))+fabs(z)*t;

/*Space Step*/
x=log(s);
up=log(l);

```

```

h=(up-(x-loc))/(double)(N+1);

/*Coefficient of diffusion augmented*/
if ((h*fabs(z))<=vv)
    upwind_alphacoef=0.5;
else {
    if (z>0.) upwind_alphacoef=0.0;
    else upwind_alphacoef=1.0;
}
vv-=z*h*(upwind_alphacoef-0.5);

/*Lhs factor of theta-schema*/
alpha=theta*k*(-vv/(h*h)+z/(2.0*h));
beta=1.0+k*theta*(r+2.*vv/(h*h));
gamma=k*theta*(-vv/(h*h)-z/(2.0*h));

/*Rhs factor of theta-schema*/
alpha1=k*(1.0-theta)*(vv/(h*h)-z/(2.0*h));
beta1=1.0-k*(1.0-theta)*(r+2.*vv/(h*h));
gamma1=k*(1.0-theta)*(vv/(h*h)+z/(2.0*h));

/*Terminal Values*/
for(PriceIndex=0;PriceIndex<=N;PriceIndex++) {
    Obst[PriceIndex]=(p->Compute)(p->Par,exp(x-loc+(double)
    PriceIndex*h));
    P[PriceIndex]= Obst[PriceIndex];
}
P[N+1]=rebate;

/*Finite Difference Cycle*/
for(TimeIndex=1;TimeIndex<=M;TimeIndex++)
{
    /*Init Rhs*/
    for(j=1;j<=N;j++)
        Rhs[j]=P[j]*beta1+alpha1*P[j-1]+gamma1*P[j+1];

    /*Psor Cycle*/
    loops=0;
    do
    {

```

```

        error=0.;
        norm=0.;

        for(j=1;j<=N;j++)
        {
            y=(Rhs[j]-alpha*P[j-1]-gamma*P[j+1])/beta;
            y=MAX(Obst[j],P[j]+omega*(y-P[j]));

            error+=(double)(j+1)*fabs(y-P[j]);
            norm+=fabs(y);
            P[j]=y;
        }

        if (norm<1.0) norm=1.0;
        error=error/norm;

        loops++;
    }
    while ((error>epsilon) && (loops<MAXLOOPS));
}
Index=(int)floor(loc/h);

*ptprice=P[Index]+(P[Index+1]-P[Index])*(exp(x)-exp(x-
loc+Index*h))/(exp(x-loc+(Index+1)*h)-exp(x-loc+Index*h));

/*Delta*/
if(x==up)
    *ptdelta=(P[Index]-P[Index-1])/(s*h);
else
    *ptdelta=(P[Index+1]-P[Index-1])/(2*s*h);

/*Memory Desallocation*/
free(P);
free(Obst);
free(Rhs);

return OK;
}

int CALC(FD_Psor_UpOut)(void *Opt,void *Mod,PricingMethod *
Met)

```

```

{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r,divid,limit,rebate;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
    divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);
    limit=((ptOpt->Limit.Val.V_NUMFUNC_1)->Compute)((ptOpt->Limit.Val.V_NUMFUN
    rebate=((ptOpt->Rebate.Val.V_NUMFUNC_1)->Compute)((ptOpt->Rebate.Val.V_NUMFUNC_1)->Par,ptMod->T.Val.V_DATE);

    return Psor_UpOut(ptMod->S0.Val.V_PDOUBLE,ptOpt->PayOff.
        Val.V_NUMFUNC_1,limit,rebate,
        ptOpt->Maturity.Val.V_DATE-ptMod->T.Val.V_DATE,r,
        divid,ptMod->Sigma.Val.V_PDOUBLE,
        Met->Par[0].Val.V_INT,Met->Par[1].Val.V_INT, Met-
        >Par[2].Val.V_RGDOUBLE051,
        Met->Par[3].Val.V_RGDOUBLE12,Met->Par[4].Val.V_RG
        DOUBLE,
        &(Met->Res[0].Val.V_DOUBLE),&(Met->Res[1].Val.V_
        DOUBLE));
}

static int CHK_OPT(FD_Psor_UpOut)(void *Opt, void *Mod)
{
    Option* ptOpt=(Option*)Opt;
    TYPEOPT* opt=(TYPEOPT*)(ptOpt->TypeOpt);

    if ((opt->Parisian).Val.V_BOOL==WRONG)
        if ( (strcmp( ((Option*)Opt)->Name,"CallUpOutAmer")==0)
            || (strcmp( ((Option*)Opt)->Name,"PutUpOutAmer")==0) )
            return OK;
    return WRONG;
}

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    if ( Met->init == 0)
    {
        Met->init=1;
    }
}

```

```

    Met->Par[0].Val.V_INT2=100;
    Met->Par[1].Val.V_INT2=100;
    Met->Par[2].Val.V_RGDOUBLE=0.5;
    Met->Par[3].Val.V_RGDOUBLE=1.5;
    Met->Par[4].Val.V_RGDOUBLE=1.0e-7;

}

return OK;
}

PricingMethod MET(FD_Psor_UpOut)=
{
    "FD_Psor_UpOut",
    {"SpaceStepNumber",INT2,{100},ALLOW    },{"TimeStepNumber",INT2,{100},ALLOW},
    {"Theta",RGDOUBLE051,{100},ALLOW},{"Omega",RGDOUBLE12,{100},ALLOW}, {"Epsilon",RGDOUBLE,{100},ALLOW}, {" ",PREMIA_NULLTYPE,{0},FORBID}},
    CALC(FD_Psor_UpOut),
    {"Price",DOUBLE,{100},FORBID}, {"Delta",DOUBLE,{100},FORBID}, {" ",PREMIA_NULLTYPE,{0},FORBID}},
    CHK_OPT(FD_Psor_UpOut),
    CHK_psor,
    MET(Init)
};

```

References