

[Help](#)

```
#include <stdlib.h>
#include "bsdisdiv1d_std.h"
#include "error_msg.h"
#include "pnl/pnl_matrix.h"

#if defined(PremiaCurrentVersion) && PremiaCurrentVersion <
    (2009+2) //The "#else" part of the code will be freely av
    ailable after the (year of creation of this file + 2)
static int CHK_OPT(TR_SingularPoints_Up)(void *Opt, void *
    Mod)
{
    return NONACTIVE;
}
int CALC(TR_SingularPoints_Up)(void*Opt,void *Mod,Pricing
    Method *Met)
{
    return AVAILABLE_IN_FULL_PREMIA;
}
#else

static double *vm, *vpm;

static void Sort2Vect(unsigned long n, double *arr,double *
    arr2)
{
    PnlVect a, b;
    PnlVectInt *i;
    a = pnl_vect_wrap_array (arr, n);
    b = pnl_vect_wrap_array (arr2, n);
    i = pnl_vect_int_create(0);

    pnl_vect_qsort_index(&a, i, 'i');
    pnl_vect_permute_inplace(&b, (PnlPermutation *)i);
    pnl_vect_int_free (&i);
}

static double compute_pricesp(double val,int nb_critical_v)
{
    int k;
```

```

double res;

if(val<vm[0])
    return vpm[0];
else
    if(val>vm[nb_critical_v])
        return vpm[nb_critical_v];
    else
        if(fabs(val-vm[nb_critical_v])<1.e-8)
            return vpm[nb_critical_v];
        else
        {
            k=0;
            while ((vm[k]<val)&&(k<=nb_critical_v)) k++;
            if(k==0)
                res=vpm[0];
            else
                res=((val-vm[k-1])*vpm[k]+(vm[k]-val)*vpm[k-1])
/(vm[k]-vm[k-1]);
            return res;
        }
}

static int SingularPoints_Up(int am,double s,NumFunc_1 *p,
    double t,double r,double sigma,PnlVect *divid_dates,PnlVect *div
    id_amounts,int N,double h_up,double *ptprice,double *ptdelt
    a)
{

    int n;
    double u,d,h,pu,pd,a1;
    double K=p->Par[0].Val.V_DOUBLE;
    double *v_min,*v_max,*new_vm,*new_vm1,*new_vm2,*new_vpm,*
        new_vpm1,*new_vpm2;
    double *vect_t;
    int * nb_critical;
    int *divid_steps;
    double value1,value2,value_price1,value_price2;
    double dist1,dist2;
    double TOL1=0.00000000001;
    double TOL2=0.00000000001;

```

```

int i,j,k,l,jj,kk,Nb_div,new_nb_critical,n_k;
int max_critical=0;
int il,index,nb_critical_put;
double m1,error,errp;
int old_nb_critical;
double x1,x2,y2,y11,a,b;
int n_max;

/*Number of Dividends Dates*/
Nb_div=divid_dates->size;

//Number maximum of singular points
n_max=50000;

/*Compute steps of the tree*/
n=N*Nb_div;

/*Memory allocations*/
divid_steps= malloc((n+1)*sizeof(int));
nb_critical=(int*)malloc(sizeof(int)*(n+1));
v_min=(double*)malloc(sizeof(double)*(n+1));
v_max=(double*)malloc(sizeof(double)*(n+1));
vm=(double*)malloc(sizeof(double)*(n_max));
vpm=(double*)malloc(sizeof(double)*(n_max));
new_vm=(double*)malloc(sizeof(double)*(n_max));
new_vm1=(double*)malloc(sizeof(double)*(n_max));
new_vm2=(double*)malloc(sizeof(double)*(n_max));
new_vpm=(double*)malloc(sizeof(double)*(n_max));
new_vpm1=(double*)malloc(sizeof(double)*(n_max));
new_vpm2=(double*)malloc(sizeof(double)*(n_max));
vect_t= malloc((n+1)*sizeof(double));

/*Up and Down factors*/
h=t/(double)n;
a1= exp(h*r);
u = exp(sigma*sqrt(h));
d= 1./u;

/*Risk-Neutral Probability*/
pu=(a1-d)/(u-d);

```

```

pd=1.-pu;

if ((pd>=1.) || (pd<=0.))
    return NEGATIVE_PROBABILITY;

pu*=exp(-r*h);
pd*=exp(-r*h);

for(i=0;i<=n;i++)
    vect_t[i]=h*(double)i;

//Compute steps related to the dividend dates
for(k=0;k<Nb_div;k++)
{
    i=0;
    while(vect_t[i]<pnl_vect_get(divid_dates,k)) i++;
    if(fabs(pnl_vect_get(divid_dates,k)-vect_t[i])<1.e-10
    )
        divid_steps[k]=i;
    else
    {
        dist1=vect_t[i]-pnl_vect_get(divid_dates,k);
        dist2=pnl_vect_get(divid_dates,k)-vect_t[i-1];
        if (dist1<dist2)
            divid_steps[k]=i;
        else
            divid_steps[k]=i-1;
    }
}

/*Compute Minimum and Maximum of the stock at each step
taking in to account of the dividend payments*/
v_min[0]=s;
v_max[0]=s;
j=0;
for(i=1;i<=n;i++)
{
    v_min[i]=v_min[i-1]*d;
    v_max[i]=v_max[i-1]*u;

    for(k=0;k<Nb_div;k++)

```

```

        if(i==divid_steps[k])
        {
            v_min[i]=v_min[i]-pnl_vect_get(divid_amounts,Nb
_div-k-1);
            v_max[i]=v_max[i]-pnl_vect_get(divid_amounts,Nb
_div-k-1);

        }
    }

    /**Singular points at Maturity***/
    if((v_min[n]<K)&&(v_max[n]>K))
    {
        nb_critical[n]=2;
        //Abscissa
        vm[0]=v_min[n];
        vm[1]=K;
        vm[2]=v_max[n];

        //Ordnate
        vpm[0]=(p->Compute)(p->Par,vm[0]);
        vpm[1]=(p->Compute)(p->Par,vm[1]);
        vpm[2]=(p->Compute)(p->Par,vm[2]);
    }
    else
    {
        nb_critical[n]=1;
        //Abscissa
        vm[0]=v_min[n];
        vm[1]=v_max[n];

        //Ordnate
        vpm[0]=(p->Compute)(p->Par,vm[0]);
        vpm[1]=(p->Compute)(p->Par,vm[1]);
    }

    /**Backward algorithm***/
    for(i=1;i<=n;i++)
    {
        /*Min point*/
        new_vm[0]=v_min[n-i]; //Abscissa

```

```

    value1=new_vm[0]*u;
    value_price1=compute_pricesp(value1,nb_critical[n-i+1
]);
    value2=new_vm[0]*d;
    value_price2=compute_pricesp(value2,nb_critical[n-i+1
]);
    new_vpm[0]=pu*value_price1+pd*value_price2;//Ordnate

/*Middle points*/
n_k=1;
for(j=1;j<nb_critical[n-i+1];j++)
{
    for(jj=-1;jj<=1;jj=jj+2)
    {
        new_vm[n_k]=vm[j]*pow(u,(double)jj);//Abscissa
        if((new_vm[n_k]>v_min[n-i])&&(new_vm[n_k]<v_
max[n-i]))
        {
            value1=new_vm[n_k]*u;
            value_price1=compute_pricesp(value1,nb_cr
itical[n-i+1]);
            value2=new_vm[n_k]*d;
            value_price2=compute_pricesp(value2,nb_cr
itical[n-i+1]);
            new_vpm[n_k]=pu*value_price1+pd*value_
price2;//Ordnate
            n_k++;
        }
    }
}

/*Max point*/
new_vm[n_k]=v_max[n-i];//Abscissa
value1=new_vm[n_k]*u;
value_price1=compute_pricesp(value1,nb_critical[n-i+1
]);
value2=new_vm[n_k]*d;
value_price2=compute_pricesp(value2,nb_critical[n-i+1
]);
new_vpm[n_k]=pu*value_price1+pd*value_price2;//Ordin
ate

```

```

//Shift at the dividends dates
for(k=0;k<Nb_div;k++)
    if(i==divid_steps[k])
    {
        for(j=0;j<=n_k;j++)
            new_vm[j]+=pnl_vect_get(divid_amounts,Nb_div-
k-1);
    }

/*Sorting*/
nb_critical[n-i]=n_k;
Sort2Vect(nb_critical[n-i],new_vm,new_vpm);

//Remove singular points very close TOL1=e-10,TOL2=e-
10
new_vm1[0]=new_vm[0];
new_vpm1[0]=new_vpm[0];
kk=0;
l=0;
do {
    do {
        l++;
    }while((new_vm[l]<=new_vm1[kk]+TOL1)&&(l<nb_criti
cal[n-i]));
    kk++;
    new_vm1[kk]=new_vm[l];
    new_vpm1[kk]=new_vpm[l];
}while((l<nb_critical[n-i]));

new_nb_critical=kk;
nb_critical[n-i]=kk;

if(fabs(new_vm1[nb_critical[n-i]]-new_vm1[nb_criti
cal[n-i]-1])<TOL2)
    nb_critical[n-i]=new_nb_critical-1;

//Upper bound
i1=0;
index=0;

```

```

new_vm2[0]=new_vm1[0];
new_vpm2[0]=new_vpm1[0];
while(i1<nb_critical[n-i]-1)
{
    l=1;
    do
    {
        l++;
        m1=(new_vpm1[i1+l]-new_vpm1[i1])/(new_vm1[i1+
1]-new_vm1[i1]);
        error=0.;
        for(jj=1;jj<=l-1;jj++)
        {
            errp=m1*(new_vm1[i1+jj]-new_vm1[i1])+new_
vpm1[i1]-new_vpm1[i1+jj];
            if (errp<0) errp=-errp;
            if (errp>error) error=errp;
        }
    }
    while(!((error>h_up)||((i1+l)==nb_critical[n-i])))
);
    index++;
    new_vm2[index]=new_vm1[i1+l-1];
    new_vpm2[index]=new_vpm1[i1+l-1];
    i1=i1+l-1;
}
while(i1<nb_critical[n-i])
{
    index++;
    new_vm2[index]=new_vm1[i1+1];
    new_vpm2[index]=new_vpm1[i1+1];
    i1=i1+1;
}
nb_critical[n-i]=index;

//American Call Case
if((am==1)&&((p->Compute)==&Call))
{
    old_nb_critical=nb_critical[n-i];
    if(MAX(0.,new_vm2[0]-K)<=new_vpm2[0])
    {

```



```

        l=1;
        while((new_vpm2[l]>=MAX(0.,new_vm2[l]-K))&&(
l<=nb_critical[n-i]))
        {
            l++;
            if(l>nb_critical[n-i]) break;
        }
        if(l<=nb_critical[n-i])
        {
            nb_critical[n-i]=l+1;
            x1=new_vm2[l-1];
            x2=new_vm2[l];
            y11=new_vpm2[l-1];
            y2=new_vpm2[l];

            a=(y2-y11)/(x2-x1);
            b=(y11*x2-x1*y2)/(x2-x1);

            new_vm2[l]=(K+b)/(1.-a);

            new_vpm2[l]=MAX(0.,new_vm2[l]-K);

            new_vm2[l+1]=new_vm2[old_nb_critical];
            new_vpm2[l+1]=MAX(0.,new_vm2[l+1]-K);
        }
    }

/*
//Dynamic Programming:American Put Case
if((am==1)&&((p->Compute)==&Put))
for(j=0;j<=nb_critical[n-i];j++)
{

    new_vpm2[j]=MAX(new_vpm2[j],K-new_vm2[j]);
}*/

//American Put Case
else
    if((am==1)&&((p->Compute)==&Put))

```

```

{

    if(MAX(0.,K-new_vm2[0])>=new_vpm2[0])
    {
        new_vm1[0]=new_vm2[0];
        new_vpm1[0]=MAX(0.,K-new_vm2[0]);
        l=1;
        while((new_vpm2[l]<MAX(0.,K-new_vm2[l]))&&(
l<=nb_critical[n-i]))
        {
            l++;
            if(l>nb_critical[n-i])    break;
        }

        if(l>nb_critical[n-i])
        {
            new_vm1[1]=new_vm2[nb_critical[n-i]];
            new_vpm1[1]=MAX(0.,K-new_vm1[1]);
            nb_critical[n-i]=1;

        }
    else
        if(l<=nb_critical[n-i])
        {
            x1=new_vm2[l-1];
            x2=new_vm2[l];
            y11=new_vpm2[l-1];
            y2=new_vpm2[l];

            a=(y2-y11)/(x2-x1);
            b=(y11*x2-x1*y2)/(x2-x1);

            new_vm1[1]=(K-b)/(1.+a);
            new_vpm1[1]=MAX(0.,K-new_vm1[1]);

            j=1;
            nb_critical_put=1;
            while((j<=nb_critical[n-i]))
            {
                nb_critical_put++;
                new_vm1[nb_critical_put]=new_vm2[

```

```

j];
                                new_vpm1[nb_critical_put]=new_vp
m2[j];
                                j++;
                                };
                                nb_critical[n-i]=nb_critical_put;
                                }

                                for(j=0;j<=nb_critical[n-i];j++)
                                {
                                    new_vm2[j]=new_vm1[j];
                                    new_vpm2[j]=new_vpm1[j];
                                }

                                }
                                }

                                max_critical=MAX(nb_critical[n-i],max_critical);

                                //Copy
                                for(j=0;j<=nb_critical[n-i];j++)
                                {
                                    vm[j]=new_vm2[j];
                                    vpm[j]=new_vpm2[j];
                                }
                                /*Delta*/
                                if(i==(n-1))
                                    *ptdelta=(vpm[nb_critical[n-i]]-vpm[0])/(vm[nb_cr
                                itical[n-i]]-vm[0]);

                                }

                                /*Price*/
                                *ptprice=vpm[0];

                                //Memory desallocation
                                free(nb_critical);
                                free(divid_steps);

```

```

    free(v_min);
    free(v_max);
    free(vpm);
    free(vm);
    free(new_vm);
    free(new_vm1);
    free(new_vm2);
    free(new_vpm);
    free(new_vpm1);
    free(new_vpm2);
    free(vect_t);

    return OK;
}

int CALC(TR_SingularPoints_Up)(void *Opt,void *Mod,Pricing
    Method *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);

    return SingularPoints_Up(ptOpt->EuOrAm.Val.V_BOOL,ptMod->
        SO.Val.V_PDOUBLE,ptOpt->PayOff.Val.V_NUMFUNC_1,ptOpt->Matu
        rity.Val.V_DATE-ptMod->T.Val.V_DATE,r,ptMod->Sigma.Val.V_PDO
        UBLE,ptMod->Dates.Val.V_PNLVECT,ptMod->Amounts.Val.V_PNLVEC
        T,Met->Par[0].Val.V_INT,Met->Par[1].Val.V_PDOUBLE,&(Met->
        Res[0].Val.V_DOUBLE),&(Met->Res[1].Val.V_DOUBLE));
}

static int CHK_OPT(TR_SingularPoints_Up)(void *Opt, void *
    Mod)
{
    if ( (strcmp( ((Option*)Opt)->Name,"PutAmer")==0) || (
        strcmp( ((Option*)Opt)->Name,"CallAmer")==0) || (strcmp( ((
        Option*)Opt)->Name,"PutEuro")==0) || (strcmp( ((Option*)Opt)->Na
        me,"CallEuro")==0))
        return OK;
    return WRONG;
}

```

```

}

#endif //PremiaCurrentVersion
static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    if ( Met->init == 0)
    {
        Met->init=1;

        Met->Par[0].Val.V_INT2=100;
        Met->Par[1].Val.V_PDOUBLE=0.0001;
    }

    return OK;
}

PricingMethod MET(TR_SingularPoints_Up)=
{
    "TR_SingularPointsUp",
    {"StepNumbers between dividends dates",INT2,{100},ALLOW}
    ,{"Tollerance Error",PDOUBLE,{100},ALLOW},{" ",PREMIA_NULL
    LTYPE,{0},FORBID}},
    CALC(TR_SingularPoints_Up),
    {"Price",DOUBLE,{100},FORBID},{"Delta",DOUBLE,{100},FORB
    ID} ,{" ",PREMIA_NULLLTYPE,{0},FORBID}},
    CHK_OPT(TR_SingularPoints_Up),
    CHK_tree,
    MET(Init)
};

```

References