3 pages 1

```
Help
#include "mer1d std.h"
static int Call Merton(double x, NumFunc 1 *p, double T,
    double r, double divid, double sigma, double lambda, double m,
    double v,double *ptprice,double *ptdelta)
{
  double lambdaT,mv2,exmv2,EU,mu,M,sigma02,sigmasqrt,price,
    delta,test,puissancen1,factorieln,n,d1,d2,sigma2,rT,muT,ex_
    r_1T,K;
  lambdaT=lambda*T;
  K=p->Par[0].Val.V_DOUBLE;
  mv2=m+v/2.;
  exmv2=exp(mv2);
  EU=exmv2-1;
  mu=r-divid-lambda*EU;
 rT=r*T:
  muT=mu*T;
  M=exp(T*(-divid-lambda*exmv2));
  sigma02=sigma*sigma;
  sigmasqrt=sigma*sqrt(T);
  d1=(log(x/K)+sigma02*T/2+muT)/sigmasqrt;
  d2=d1-sigmasqrt;
  price=x*M*cdf nor(d1)-K*exp(-rT-lambdaT)*cdf nor(d2);
  puissancen1=1.;
  factorieln=1.;
  delta=M*cdf_nor(d1);
  ex r lT=exp(-rT-lambdaT);
  test=exp(-lambdaT);
  puissancen1=1.;
  factorieln=1.;
 n=0;
  while (test<0.99999)
    {n++;}
      factorieln*=n;/* n!
      puissancen1*=lambdaT;/* (lambda*T)^n */
```

3 pages 2

```
sigma2=sigma02+v*(double)n/T;
      sigmasqrt=sqrt(sigma2*T);
      d1=(log(x/K)+sigma2*T/2+n*(mv2)+muT)/sigmasqrt;
      d2=d1-sigmasqrt;
      price+=(puissancen1/factorieln)*(x*exp(n*mv2)*M*cdf
    nor(d1)-K*ex r lT*cdf nor(d2));
      test+=exp(-lambdaT)*puissancen1/factorieln;
      delta+=(puissancen1/factorieln)*exp(n*mv2)*M*cdf nor(
    d1);
    }
  *ptprice=price;
  *ptdelta=delta;
  return OK;
}
int CALC(CF Call Merton)(void*Opt,void *Mod,PricingMethod *
    Met)
{
  TYPEOPT* ptOpt=(TYPEOPT*)Opt;
  TYPEMOD* ptMod=(TYPEMOD*)Mod;
  double r,divid;
  r=log(1.+ptMod->R.Val.V DOUBLE/100.);
  divid=log(1.+ptMod->Divid.Val.V DOUBLE/100.);
  return Call_Merton(ptMod->SO.Val.V_PDOUBLE,ptOpt->PayO
    ff.Val.V NUMFUNC 1,ptOpt->Maturity.Val.V DATE-ptMod->T.Val.
    V DATE,
          r,divid,ptMod->Sigma.Val.V PDOUBLE,ptMod->Lambd
    a.Val.V PDOUBLE,ptMod->Mean.Val.V PDOUBLE,ptMod->Variance.
    Val.V PDOUBLE, & (Met->Res[0].Val.V DOUBLE), & (Met->Res[1].Val.
    V DOUBLE));
}
static int CHK OPT(CF Call Merton)(void *Opt, void *Mod)
  /*
```

3 pages

```
Option* ptOpt=(Option*)Opt;
  TYPEOPT* opt=(TYPEOPT*)(ptOpt->TypeOpt);
  */
  return strcmp( ((Option*)Opt)->Name, "CallEuro");
}
static int MET(Init)(PricingMethod *Met,Option *Opt)
  if (Met->init == 0)
    {
      Met->init=1;
    }
  return OK;
PricingMethod MET(CF_Call_Merton)=
  "CF Call Merton",
  {{" ",PREMIA_NULLTYPE,{0},FORBID}}},
  CALC(CF_Call_Merton),
  {{"Price",DOUBLE,{100},FORBID},{"Delta",DOUBLE,{100},FORB
    ID},{" ",PREMIA_NULLTYPE,{0},FORBID}},
  CHK_OPT(CF_Call_Merton),
  CHK ok,
 MET(Init)
} ;
```

References