

Help

```

#include <stdlib.h>
#define WITH_boundary 1
#include "bs1d_lim.h"
#include "error_msg.h"
#define PRECISION 1.0e-7 /*Precision for the localization
    of FD methods*/

static int Cryer_DownIn(double s,NumFunc_1 *p,double l,
    double rebate,double t,double r,double divid,double sigma,int N,
    int M,double *ptprice,double *ptdelta)
{
    int      Index,PriceIndex,TimeIndex,ssl;
    double   k,vv,loc,h,z,alpha,beta,gamma,y,down,upwind_alp
        hacoef,price1;
    double   *Obst,*A,*B,*C,*P,*S,*Z,*Q,pricenh,pricen2h,
        priceph;

    /*Memory Allocation*/
    Obst= malloc((N+1)*sizeof(double));
    if (Obst==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    A= malloc((N+1)*sizeof(double));
    if (A==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    B= malloc((N+1)*sizeof(double));
    if (B==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    C= malloc((N+1)*sizeof(double));
    if (C==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    P= malloc((N+1)*sizeof(double));
    if (P==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    S= malloc((N+1)*sizeof(double));
    if (S==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    Z= malloc((N+1)*sizeof(double));
    if (Z==NULL)
        return MEMORY_ALLOCATION_FAILURE;
    Q= malloc((N+1)*sizeof(double));

```

```

if (Q==NULL)
    return MEMORY_ALLOCATION_FAILURE;

/*Time Step*/
k=t/(double)M;

/*Space Localisation*/
vv=0.5*sigma*sigma;
z=(r-divid)-vv;
loc=sigma*sqrt(t)*sqrt(log(1.0/PRECISION))+fabs(z*t);

/*Space Step*/
y=log(s);
down=log(1);
h=(y+loc-down)/(double)(N);

/*Peclet Condition-Coefficient of diffusion augmented */
if ((h*fabs(z))<=vv)
    upwind_alphacoef=0.5;
else {
    if (z>0.) upwind_alphacoef=0.0;
    else upwind_alphacoef=1.0;
}
vv-=z*h*(upwind_alphacoef-0.5);

/*Lhs Factor of theta-schema*/
alpha=k*(-vv/(h*h)+z/(2.0*h));
beta=1.0+k*(r+2.*vv/(h*h));
gamma=k*(-vv/(h*h)-z/(2.0*h));

for(PriceIndex=0;PriceIndex<=N-2;PriceIndex++)
{
    A[PriceIndex]=alpha;
    B[PriceIndex]=beta;
    C[PriceIndex]=gamma;
}

/*Terminal Values*/
y=log(s);
for (PriceIndex = 1; PriceIndex < N; PriceIndex++)

```

```

    Obst[PriceIndex - 1]=(p->Compute)(p->Par,exp(down+
    PriceIndex* h));
for (PriceIndex = 2; PriceIndex <= N - 2; PriceIndex++)
{
    P[PriceIndex - 1] = alpha * Obst[PriceIndex - 2] +
    beta * Obst[PriceIndex - 1] + gamma * Obst[PriceIndex];
}

P[0] = beta * Obst[0] + gamma * Obst[1];
P[N - 2] = alpha * Obst[N-3] + beta * Obst[N-2];

for (PriceIndex = 0; PriceIndex <= N - 2; PriceIndex++)
{
    S[PriceIndex] = 0.;
    Z[PriceIndex] = 0.;
}
ssl = false;

/*Finite Difference Cycle*/
for (TimeIndex= 1; TimeIndex<= M; TimeIndex++)
{
    if (TimeIndex==1)
for (PriceIndex = 0; PriceIndex <= N- 2; PriceIndex++)
    Z[PriceIndex] =rebate;
    else
for (PriceIndex = 0; PriceIndex <= N- 2; PriceIndex++)
    Z[PriceIndex] =Z[PriceIndex]+Obst[PriceIndex];

    for (PriceIndex = 0; PriceIndex <= N - 2; PriceIndex+
+)
Q[PriceIndex]=P[PriceIndex]-Z[PriceIndex];

    price1=Boundary(1,p,(double)TimeIndex*k,r,divid,sigma
);
    Q[0] += alpha*price1;
    Q[N-2]+=gamma*(p->Compute)(p->Par,exp(y+loc));

    AlgCraye(N,Z,ssl,A,B,C,Q,S);

    for (PriceIndex = 0; PriceIndex <=N-2; PriceIndex++)
S[PriceIndex] = Z[PriceIndex];

```

```

        ssl = true;
    }

    for (PriceIndex = 0; PriceIndex <= N - 2; PriceIndex++)
        P[PriceIndex]=Z[PriceIndex]+Obst[PriceIndex];

    Index=(int)floor((y-down)/h)-1;

    /*Price*/
    *ptprice=P[Index]+(P[Index+1]-P[Index])*(exp(y)-exp(down+
        h+Index*h))/(exp(down+h+(Index+1)*h)-exp(down+h+Index*h));

    /*Delta*/
    pricenh=P[Index+1]+(P[Index+2]-P[Index+1])*(exp(y+h)-exp(
        down+h+(Index+1)*h))/(exp(down+h+(Index+2)*h)-exp(down+h+(
        Index+1)*h));
    if (Index>0)
    {
        priceph=P[Index-1]+(P[Index]-P[Index-1])*(exp(y-h)-
            exp(down+h+(Index-1)*h))/(exp(down+h+(Index)*h)-exp(down+h+(
            Index-1)*h));
        *ptdelta=(pricenh-priceph)/(2*s*h);
    }
    else
    {
        pricen2h=P[Index+2]+(P[Index+3]-P[Index+2])*(exp(y+2*
            h)-exp(down+h+(Index+2)*h))/(exp(down+h+(Index+3)*h)-exp(
            down+h+(Index+2)*h));
        *ptdelta=(4*pricenh-pricen2h-3*(ptprice))/(2*s*h);
    }

    /*Memory Desallocation*/
    free(Obst);
    free(A);
    free(B);
    free(C);
    free(P);
    free(S);
    free(Z);
    free(Q);

```

```

    return OK;
}

int CALC(FD_Cryer_DownIn)(void *Opt,void *Mod,Pricing
    Method *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r,divid,limit,rebate;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
    divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);
    limit=((ptOpt->Limit.Val.V_NUMFUNC_1)->Compute)((ptOpt->Limit.Val.V_NUMFUN
    rebate=((ptOpt->Rebate.Val.V_NUMFUNC_1)->Compute)((ptOpt->Rebate.Val.V_NUMFUNC_1)->Par,ptMod->T.Val.V_DATE);

    return Cryer_DownIn(ptMod->S0.Val.V_PDOUBLE,ptOpt->Pay0
        ff.Val.V_NUMFUNC_1,
            limit,rebate, ptOpt->Maturity.Val.V_DATE-ptMod-
            >T.Val.V_DATE,r,divid,ptMod->Sigma.Val.V_PDOUBLE,
                Met->Par[0].Val.V_INT2,Met->Par[1].Val.V_INT2,
                &(Met->Res[0].Val.V_DOUBLE),&(Met->Res[1].Val.
                V_DOUBLE));
}

static int CHK_OPT(FD_Cryer_DownIn)(void *Opt, void *Mod)
{
    Option* ptOpt=(Option*)Opt;
    TYPEOPT* opt=(TYPEOPT*)(ptOpt->TypeOpt);

    if ((opt->Parisian).Val.V_BOOL==WRONG)
        if ( (strcmp( ((Option*)Opt)->Name,"CallDownInAmer")==0
            ) || (strcmp( ((Option*)Opt)->Name,"PutDownInAmer")==0) )
            return OK;

    return WRONG;
}

static int MET(Init)(PricingMethod *Met,Option *Opt)

```

```

{
  if ( Met->init == 0)
  {
    Met->init=1;
    Met->Par[0].Val.V_INT2=100;
    Met->Par[1].Val.V_INT2=100;
  }

  return OK;
}

PricingMethod MET(FD_Cryer_DownIn)=
{
  "FD_Cryer_DownIn",
  {"SpaceStepNumber",INT2,{100},ALLOW  },{"TimeStepNumber",INT2,{100},ALLOW},
  {" ",PREMIA_NULLTYPE,{0},FORBID}},
  CALC(FD_Cryer_DownIn),
  {"Price",DOUBLE,{100},FORBID},{"Delta",DOUBLE,{100},FORBID},
  {" ",PREMIA_NULLTYPE,{0},FORBID}},
  CHK_OPT(FD_Cryer_DownIn),
  CHK_split,
  MET(Init)
};

```

References