

Help

```

#include<stdlib.h>
#include<math.h>
#include"pnl/pnl_random.h"
#include"pnl/pnl_specfun.h"
#include "cgmy1d_pad.h"
#include "enums.h"

#if defined(PremiaCurrentVersion) && PremiaCurrentVersion <
    (2011+2) //The "#else" part of the code will be freely av
    ailable after the (year of creation of this file + 2)
static int CHK_OPT(MC_CGMY_FloatingAsian)(void *Opt, void *
    Mod)
{
    return NONACTIVE;
}
int CALC(MC_CGMY_FloatingAsian)(void*Opt,void *Mod,Pricing
    Method *Met)
{
    return AVAILABLE_IN_FULL_PREMIA;
}
#else
//Compute the positive or negative jump size between the sm
    allest and the biggest value of cdf_jump_points of the CGMY
    process
static double jump_generator_CGMY(double* cdf_jump_vect,
    double* cdf_jump_points,int cdf_jump_vect_size,double M_G,
    double Y,int generator)
{
    double z,v,y;
    int test,temp,l,j,q;
    test=0;
    v=pnl_rand_uni(generator);
    y=cdf_jump_vect[cdf_jump_vect_size]*v;
    l=cdf_jump_vect_size/2;
    j=cdf_jump_vect_size;
    z=0;
    if(cdf_jump_vect[l]>y)
    {
        l=0;
        j=cdf_jump_vect_size/2;
    }

```

```

    }
    if(v==1)
    {
        z=cdf_jump_points[cdf_jump_vect_size];
    }
    if(v==0)
    {
        z=cdf_jump_points[0];
    }
    if(v!=1 && v!=0)
    {
        while(test==0)
        {
            if(cdf_jump_vect[l+1]>y)
            {
                q=l;
                test=1;
            }
            else
            {
                temp=(j-l-1)/2+1;
                if(cdf_jump_vect[temp]>y)
                {
                    j=temp;
                    l=l+1;
                }
                else
                {
                    l=temp*(temp>l)+(l+1)*(temp<=l);
                }
            }
        }
        z=pow(1/pow(cdf_jump_points[q],Y)-(y-cdf_jump_vect[q])*
        Y*exp(M_G*cdf_jump_points[q]),-1/Y);
    }
    return z;
}

//(exp(x)-1)/x
static double p_func(double x)
{

```

```

double s;
int i,n;
n=1;
s=0;
for(i=0;i<=n;i++)
    s+=pow(x,i)/pnl_fact(i+1);

return s;
}

//(4exp(x)+(2x-3)exp(2x)-1)/x^3
static double var_func(double x)
{
    double s;
    int i,n;
    n=1;
    s=0;
    for(i=0;i<=n;i++)
        s+=4*pow(x,i)/pnl_fact(i+3)-3*pow(2.,i+3)*pow(x,i)/pnl_
            fact(i+3)+pow(2.,i+3)*pow(x,i)/pnl_fact(i+2);

    return s;
}

//exp(x)/x-(exp(x)-1)/x^2
static double cov_func(double x)
{
    double s;
    int i,n;
    n=1;
    s=0;
    for(i=0;i<=n;i++)
        s+=pow(x,i)*(1./pnl_fact(i+1)-1./pnl_fact(i+2));

    return s;
}

static int CGMY_Mc_FloatingAsian(NumFunc_2*P,double S0,
    double T,double r,double divid,double C,double G,double M,
    double Y,int generator,int n_paths,double *ptprice,double *ptde
    lta,double *priceerror,double *deltaerror)

```

```

{
    double eps,s,s1,s2,s3,s4,s5,s6,payoff,dpayoff,control,
    discount,w1,w2,drift,err,u,u0,z,sigma,lambda_p;
    double control_expec,lambda_m,cdf_jump_bound,pas,cov_
    payoff_control,var_payoff,var_control;
    double cor_payoff_control,control_coef,var_dpayoff,*cdf
    _jump_points,*cdf_jump_vect_p;
    double *cdf_jump_vect_m,*Xg,*Xd,tau,*jump_time_vect,*
    jump_time_vect_p,*jump_time_vect_m;
    double var_temp,cov_temp,*vect_temp,g_temp,min_M_G,
    temp,drift_expo;
    int i,j,k,jump_number_p,jump_number_m,jump_number,m1,m2
    ,cdf_jump_vect_size,k1,k2;
    discount=exp(-divid*T);
    err=1E-16;
    eps=0.1;
    cdf_jump_vect_size=1000000;
    jump_number=0;
    s=0;
    s1=0;
    s2=0;
    s3=0;
    s4=0;
    s5=0;
    s6=0;
    if(M<2 || G<=0 || Y>=2 || Y==0)
    {
        printf("Function CGMY_Mc_FloatingAsian: invalid para
        meters. We must have M>=2, G>0, 0<Y<2{n");
    }
    ////////////////////////////////////////////
    //Measure change so that the option can be value as a
    fixed strike asian option
    M=M-1;
    G=G+1;
    temp=M;
    M=G;
    G=temp;
    //drift=-drift;
    if(Y==1)
        drift=-(r-divid)-C*((M-1)*log(1.-1/M)+(G+1)*log(1.+1/

```



```

min_M_G=MIN(M,G);
//Computation of the biggest jump that we tolerate
while(C*exp(-min_M_G*cdf_jump_bound)/(min_M_G*pow(cdf_
jump_bound,1+Y))>err)
    cdf_jump_bound++;

pas=(cdf_jump_bound-eps)/cdf_jump_vect_size;
cdf_jump_points=malloc((cdf_jump_vect_size+1)*sizeof(
double));
cdf_jump_vect_p=malloc((cdf_jump_vect_size+1)*sizeof(
double));
cdf_jump_vect_m=malloc((cdf_jump_vect_size+1)*sizeof(
double));
cdf_jump_points[0]=eps;
cdf_jump_vect_p[0]=0;
cdf_jump_vect_m[0]=0;
//computation of the cdf of the positive and negative
jumps at some points
for(i=1;i<=cdf_jump_vect_size;i++)
{
    cdf_jump_points[i]=i*pas+eps;
    cdf_jump_vect_p[i]=cdf_jump_vect_p[i-1]+exp(-M*cdf_
jump_points[i-1])*(1/pow(cdf_jump_points[i-1],Y)-1/pow(cdf_
jump_points[i],Y))/Y;
    cdf_jump_vect_m[i]=cdf_jump_vect_m[i-1]+exp(-G*cdf_
jump_points[i-1])*(1/pow(cdf_jump_points[i-1],Y)-1/pow(cdf_
jump_points[i],Y))/Y;
}
////////////////////////////////////
m1=(int)(1000*lambda_p*T);
m2=(int)(1000*lambda_m*T);
jump_time_vect_p=malloc((m1)*sizeof(double));
jump_time_vect_m=malloc((m2)*sizeof(double));
jump_time_vect_p[0]=0;
jump_time_vect_m[0]=0;
jump_time_vect=malloc((m1+m2)*sizeof(double));
vect_temp=malloc((m1+m2)*sizeof(double));
jump_time_vect[0]=0;
vect_temp[0]=0;
Xg=malloc((m1+m2)*sizeof(double)); //left value of X at
jump times

```

```

Xd=malloc((m1+m2)*sizeof(double)); //right value of X
at jump times
Xg[0]=0;
Xd[0]=0;
////////////////////////////////////
pnl_rand_init(generator,1,n_paths);
/*Call Case*/
if((P->Compute)==&Call_StrikeSpot2)
{
    for(i=0;i<n_paths;i++)
    {
        //simulation of the positive jump times and number
        tau=-(1/lambda_p)*log(pnl_rand_uni(generator));
        jump_number_p=0;
        while(tau<T)
        {
            jump_number_p++;
            jump_time_vect_p[jump_number_p]=tau;
            tau+=-1/(lambda_p)*log(pnl_rand_uni(generator));
        }
        //simulation of the negative jump times and number
er
        tau=-(1/lambda_m)*log(pnl_rand_uni(generator));
        jump_number_m=0;
        while(tau<T)
        {
            jump_number_m++;
            jump_time_vect_m[jump_number_m]=tau;
            tau+=-1/(lambda_m)*log(pnl_rand_uni(generator));
        }
        jump_time_vect_p[jump_number_p+1]=T;
        jump_time_vect_m[jump_number_m+1]=T;
        jump_number=jump_number_p+jump_number_m;
    }
    //////////////////////////////////////
    //
    //computation of Xg and Xd
    k1=1;
    k2=1;
    u0=0;
    u=0;
    for(k=1;k<=jump_number;k++)

```

```

{
    w1=jump_time_vect_p[k1];
    w2=jump_time_vect_m[k2];
    if(w1<w2)
    {
        u=w1;
        k1++;
        z=jump_generator_CGMY(cdf_jump_vect_p,cdf_jump_
points,cdf_jump_vect_size,M,Y,generator);
    }
    else
    {
        u=w2;
        k2++;
        z=-jump_generator_CGMY(cdf_jump_vect_m,cdf_jump_
points,cdf_jump_vect_size,G,Y,generator);
    }
    g_temp=pnl_rand_normal(generator);
    if(fabs(drift*(u-u0))<1e-4)
    {
        var_temp=(u-u0)*(u-u0)*(u-u0)*var_func(drift*(u-
u0))/2;
        cov_temp=(u-u0)*(u-u0)*cov_func(drift*(u-u0));

    }
    else
    {
        var_temp=(4*exp(drift*(u-u0))+(2*drift*(u-u0)-3)
*exp(2*drift*(u-u0))-1)/(2*drift*drift*drift);
        cov_temp=(u-u0)*exp(drift*(u-u0))/drift-(exp(dr
ift*(u-u0))-1)/(drift*drift);
    }
    jump_time_vect[k]=u;
    vect_temp[k]=cov_temp*g_temp/(sqrt(u-u0))+sqrt(
var_temp-cov_temp*cov_temp/(u-u0))*pnl_rand_normal(generator);
    Xg[k]=drift*(u-u0)+sigma*g_temp*sqrt(u-u0)+Xd[k-1]
;
    Xd[k]=Xg[k]+z;
    u0=u;
}
g_temp=pnl_rand_normal(generator);

```



```

        if(fabs(drift*(T-u0))<1e-4)
        {
            var_temp=(T-u0)*(T-u0)*(T-u0)*var_func(drift*(T-
u0))/2;
            cov_temp=(T-u0)*(T-u0)*cov_func(drift*(T-u0));
        }
        else
        {
            var_temp=(4*exp(drift*(T-u0))+(2*drift*(T-u0)-3)*
exp(2*drift*(T-u0))-1)/(2*drift*drift*drift);
            cov_temp=(T-u0)*exp(drift*(T-u0))/drift-(exp(drif
t*(T-u0))-1)/(drift*drift);
        }
        jump_time_vect[jump_number+1]=T;
        vect_temp[jump_number+1]=cov_temp*g_temp/(sqrt(T-
u0))+sqrt(var_temp-cov_temp*cov_temp/(T-u0))*pnl_rand_nor
mal(generator);
        Xg[jump_number+1]=drift*(T-u0)+sigma*g_temp*sqrt(T-
u0)+Xd[jump_number];
        Xd[jump_number+1]=Xg[jump_number+1];
//////////////////////////////////////
/
        //computation of the payoff
        payoff=0;
        for(j=1;j<=jump_number+1;j++)
        {
            if(fabs(drift*(jump_time_vect[j]-jump_time_vect[
j-1]))<1e-4)
                payoff+=exp(Xd[j-1])*(p_func(drift*(jump_time_v
ect[j]-jump_time_vect[j-1]))*(jump_time_vect[j]-jump_time_v
ect[j-1])+sigma*vect_temp[j]);
            else
                payoff+=exp(Xd[j-1])*((exp(drift*(jump_time_vec
t[j]-jump_time_vect[j-1]))-1)/drift+sigma*vect_temp[j]);
        }
        control=S0*payoff/T;

        dpayoff=discount*(1-payoff/T)*(payoff/T<1);
        payoff=discount*(S0-S0*payoff/T)*(payoff/T<1);

        s1+=payoff;

```

```

        s+=payoff*payoff;
        s2+=control;
        s3+=control*control;
        s4+=control*payoff;
        s5+=dpayoff;
        s6+=dpayoff*dpayoff;
    }
    cov_payoff_control=s4/n_paths-s1*s2/((double)n_
paths*n_paths);
    var_payoff=(s-s1*s1/((double)n_paths))/(n_paths-1);
    var_control=(s3-s2*s2/((double)n_paths))/(n_paths-1
);
    cor_payoff_control=cov_payoff_control/(sqrt(var_pay
off)*sqrt(var_control));
    control_coef=cov_payoff_control/var_control;
    var_dpayoff=(s6-s5*s5/((double)n_paths))/(n_paths-1
);
    *ptprice=(s1/n_paths-control_coef*(s2/n_paths-contr
ol_expec));
    *priceerror=1.96*sqrt(var_payoff*(1-cor_payoff_
control*cor_payoff_control))/sqrt(n_paths);
    *ptdelta=s5/(n_paths);
    *deltaerror=1.96*sqrt(var_dpayoff)/sqrt(n_paths);
}
/*Put case*/
if((P->Compute)==&Put_StrikeSpot2)
{
    for(i=0;i<n_paths;i++)
{
    //simulation of the positive jump times and number
    tau=-(1/lambda_p)*log(pnl_rand_uni(generator));
    jump_number_p=0;
    while(tau<T)
    {
        jump_number_p++;
        jump_time_vect_p[jump_number_p]=tau;
        tau+=-1/(lambda_p)*log(pnl_rand_uni(generator));
    }
    //simulation of the negative jump times and number
    tau=-(1/lambda_m)*log(pnl_rand_uni(generator));
    jump_number_m=0;

```

```

while(tau<T)
{
    jump_number_m++;
    jump_time_vect_m[jump_number_m]=tau;
    tau+=-1/(lambda_m)*log(pnl_rand_uni(generator));
}
jump_time_vect_p[jump_number_p+1]=T;
jump_time_vect_m[jump_number_m+1]=T;
jump_number=jump_number_p+jump_number_m;
////////////////////////////////////
//
//computation of Xg and Xd
k1=1;
k2=1;
u0=0;
u=0;
for(k=1;k<=jump_number;k++)
{
    w1=jump_time_vect_p[k1];
    w2=jump_time_vect_m[k2];
    if(w1<w2)
    {
        u=w1;
        k1++;
        z=jump_generator_CGMY(cdf_jump_vect_p,cdf_jump_points
,cdf_jump_vect_size,M,Y,generator);
    }
    else
    {
        u=w2;
        k2++;
        z=-jump_generator_CGMY(cdf_jump_vect_m,cdf_jump_po
ints,cdf_jump_vect_size,G,Y,generator);
    }
    g_temp=pnl_rand_normal(generator);
    if(fabs(drift*(u-u0))<1e-4)
    {
        var_temp=(u-u0)*(u-u0)*(u-u0)*var_func(drift*(u-u0))/
2;
        cov_temp=(u-u0)*(u-u0)*cov_func(drift*(u-u0));
    }
}

```

```

    }
    else
    {
        var_temp=(4*exp(drift*(u-u0))+(2*drift*(u-u0)-3)*exp(
        2*drift*(u-u0))-1)/(2*drift*drift*drift);
        cov_temp=(u-u0)*exp(drift*(u-u0))/drift-(exp(drift*(
        u-u0))-1)/(drift*drift);
    }
    jump_time_vect[k]=u;
    vect_temp[k]=cov_temp*g_temp/(sqrt(u-u0))+sqrt(var_tem
    p-cov_temp*cov_temp/(u-u0))*pnl_rand_normal(generator);
    Xg[k]=drift*(u-u0)+sigma*g_temp*sqrt(u-u0)+Xd[k-1];
    Xd[k]=Xg[k]+z;
    u0=u;
}
g_temp=pnl_rand_normal(generator);
if(fabs(drift*(T-u0))<1e-4)
{
    var_temp=(T-u0)*(T-u0)*(T-u0)*var_func(drift*(T-u0))/2
    ;
    cov_temp=(T-u0)*(T-u0)*cov_func(drift*(T-u0));
}
else
{
    var_temp=(4*exp(drift*(T-u0))+(2*drift*(T-u0)-3)*exp(2
    *drift*(T-u0))-1)/(2*drift*drift*drift);
    cov_temp=(T-u0)*exp(drift*(T-u0))/drift-(exp(drift*(T-
    u0))-1)/(drift*drift);
}
jump_time_vect[jump_number+1]=T;
vect_temp[jump_number+1]=cov_temp*g_temp/(sqrt(T-u0))+
    sqrt(var_temp-cov_temp*cov_temp/(T-u0))*pnl_rand_normal(generator);
Xg[jump_number+1]=drift*(T-u0)+sigma*g_temp*sqrt(T-u0)+
    Xd[jump_number];
Xd[jump_number+1]=Xg[jump_number+1];
//////////////////////////////////////
/
//computation of the payoff
payoff=0;
for(j=1;j<=jump_number+1;j++)
{

```

```

if(fabs(drift*(jump_time_vect[j]-jump_time_vect[j-1]))
<1e-4)
    payoff+=exp(Xd[j-1])*(p_func(drift*(jump_time_vect[
j]-jump_time_vect[j-1]))*(jump_time_vect[j]-jump_time_vect[
j-1])+sigma*vect_temp[j]);
else
    payoff+=exp(Xd[j-1])*((exp(drift*(jump_time_vect[j]-
jump_time_vect[j-1]))-1)/drift+sigma*vect_temp[j]);
}
control=S0*payoff/T;
dpayoff=discount*(1-payoff/T)*(payoff/T<1);
payoff=discount*(S0-S0*payoff/T)*(payoff/T<1);

s1+=payoff;
s+=payoff*payoff;
s2+=control;
s3+=control*control;
s4+=control*payoff;
s5+=dpayoff;
s6+=dpayoff*dpayoff;
}
cov_payoff_control=s4/n_paths-s1*s2/((double)n_paths*n_
paths);
var_payoff=(s-s1*s1/((double)n_paths))/(n_paths-1);
var_control=(s3-s2*s2/((double)n_paths))/(n_paths-1);
cor_payoff_control=cov_payoff_control/(sqrt(var_payoff)*
sqrt(var_control));
control_coef=cov_payoff_control/var_control;
var_dpayoff=(s6-s5*s5/((double)n_paths))/(n_paths-1);
if(r!=divid)
    *ptprice=(s1/n_paths-control_coef*(s2/n_paths-control_
expec))-S0*exp(-divid*T)+S0*(exp(-divid*T)-exp(-r*T))/((r-
divid)*T);
else
    *ptprice=(s1/n_paths-control_coef*(s2/n_paths-control_
expec))-S0*(exp(-divid*T)-exp(-r*T));
*priceerror=1.96*sqrt(var_payoff*(1-cor_payoff_control*
cor_payoff_control))/sqrt(n_paths);
if(r!=divid)
    *ptdelta=s5/(n_paths)-exp(-divid*T)+(exp(-divid*T)-exp
(-r*T))/((r-divid)*T);

```

```

else
    *ptdelta=s5/(n_paths)-exp(-divid*T)+exp(-r*T);
*deltaerror=1.96*sqrt(var_dpayoff)/sqrt(n_paths);
    }
    free(Xd);
    free(Xg);
    free(cdf_jump_points);
    free(cdf_jump_vect_p);
    free(cdf_jump_vect_m);
    free(jump_time_vect_p);
    free(jump_time_vect_m);
    free(jump_time_vect);
    free(vect_temp);

    return OK;
}
int CALC(MC_CGMY_FloatingAsian)(void*Opt,void *Mod,Pricing
    Method *Met)
{
    TYPEOPT* ptOpt=(TYPEOPT*)Opt;
    TYPEMOD* ptMod=(TYPEMOD*)Mod;
    double r,divid;

    r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
    divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);

    return CGMY_Mc_FloatingAsian(ptOpt->PayOff.Val.V_
        NUMFUNC_2,ptMod->S0.Val.V_PDOUBLE,ptOpt->Maturity.Val.V_DATE-pt
        Mod->T.Val.V_DATE,r,divid,ptMod->C.Val.V_PDOUBLE,ptMod->G.Val
        .V_DOUBLE,ptMod->M.Val.V_SPDOUBLE,ptMod->Y.Val.V_PDOUBLE,
        Met->Par[0].Val.V_ENUM.value,Met->Par[2].Val.V_LONG,&(Met->
        Res[0].Val.V_DOUBLE),&(Met->Res[1].Val.V_DOUBLE),&(Met->Res[
        2].Val.V_DOUBLE),&(Met->Res[3].Val.V_DOUBLE));
}

static int CHK_OPT(MC_CGMY_FloatingAsian)(void *Opt, void *
    Mod)
{
    if ((strcmp(((Option*)Opt)->Name,"AsianCallFloatingEuro")
        ==0) || (strcmp( ((Option*)Opt)->Name," AsianPutFloatingEuro")==0) )
        return OK;
}

```

```

    return WRONG;
}

#endif //PremiaCurrentVersion
static int MET(Init)(PricingMethod *Met,Option *Mod)
{
    if ( Met->init == 0)
    {
        Met->init=1;
        Met->HelpFilenameHint = "mc_cgmy_asianfloating";
        Met->Par[0].Val.V_ENUM.value=0;
        Met->Par[0].Val.V_ENUM.members=&PremiaEnumMCRNGs;
        Met->Par[2].Val.V_LONG=100000;
    }
    return OK;
}

PricingMethod MET(MC_CGMY_FloatingAsian)=
{
    "MC_CGMY_FloatingAsian",
    {{"RandomGenerator",ENUM,{100},ALLOW},
     {"N iterations",LONG,{100},ALLOW},{" " ,PREMIA_NULLTYPE,{
        0},FORBID}},
    CALC(MC_CGMY_FloatingAsian),
    {{"Price",DOUBLE,{100},FORBID},{"Delta",DOUBLE,{100},FORB
        ID},{"Price Error",DOUBLE,{100},FORBID},{"Delta Error",
        DOUBLE,{100},FORBID},{" " ,PREMIA_NULLTYPE,{0},FORBID}},
    CHK_OPT(MC_CGMY_FloatingAsian),
    CHK_ok,
    MET(Init)
} ;

```

References