

[Help](#)

```
#include "bs2d_std2d.h"
#include "error_msg.h"
#include "enums.h"
#define PRECISION 1.0e-7 /*Precision for the localization
    of FD methods*/

/*Compress Diagonal Storage*/
static void cds(int n, double a, double b, double c,
    double d, double e, double f, double g, double i2, double j2,
    double **band)
{
    int j, nsr;

    nsr=(int)sqrt(n);

    for (j=nsr+2; j<=n; j++)
        if (((j-1)%(nsr))!=0)
            band[1][j]=j2;

    for (j=nsr+1; j<=n; j++) band[2][j]=d;

    for (j=nsr+1; j<=n; j++)
        if (((j)%(nsr))!=0)
            band[3][j]=f;

    for (j=2; j<=n; j++)
        if (((j-1)%(nsr))!=0)
            band[4][j]=c;

    for (j=1; j<=n; j++) band[5][j]=a;

    for (j=1; j<=n; j++)
        if (((j)%(nsr))!=0)
            band[6][j]=b;

    for (j=2; j<=n-nsr; j++)
        if (((j-1)%(nsr))!=0)
            band[7][j]=g;
```

```

for (j=1;j<=n-nsr;j++) band[8][j]=e;

for (j=1;j<=n-nsr;j++)
    if ((j%(nsr))!=0)
        band[9][j]=i2;

return;
}

/*Dirichlet Boundary Conditions*/
static void Dirichlet(int N, double a2,double b2, double
    c2, double d2,double e2, double f2,double g2, double i2,
    double j2,double x1,double x2,double limit1,double limit2,
    double h1,double h2, NumFunc_2 *p,double *bound)
{
    int i,j,N1,Ns;

    N1=N-1;
    Ns=SQR(N1);

    for(i=1;i<Ns;i++) bound[i]=0.;

    bound[1]=j2*(p->Compute)(p->Par, exp(x1-limit1),exp(x2+ limit2))+
        d2*(p->Compute)(p->Par, exp(x1-limit1+h1),exp(x2+limit2
        ))+
        f2*(p->Compute)(p->Par, exp(x1-limit1+2.*h1),
            exp(x2+limit2))+c2*(p->Compute)(p->Par, exp(x1- limit1),exp(x2+limit2
            g2*(p->Compute)(p->Par, exp(x1-limit1+h1),exp(x2+limit2
            -2.*h2)));

    for(i=2;i<N-1;i++)
        bound[i]=j2*(p->Compute)(p->Par, exp(x1-limit1+h1*(
            double)(i-1)),exp(x2+limit2))+
            d2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)i),
            exp(x2+limit2))+
            f2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)(i+1
            )),exp(x2+limit2)));

    bound[N-1]=j2*(p->Compute)(p->Par, exp(x1-limit1+h1*(
        double)(N-2)),exp(x2+limit2))+

```

```

d2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)(N-1))
,exp(x2+limit2))+
f2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)N),exp
(x2+limit2))+
b2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)N),exp
(x2+limit2-h2))+
i2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)N),exp
(x2+limit2-2.*h2));

N1=N-1;
j=1;
for(i=N;i<Ns-N1;i=i+N1) {
    bound[i]=j2*(p->Compute)(p->Par,exp(x1-limit1),exp(x2+    limit2-h2*(double)
    c2*(p->Compute)(p->Par,exp(x1-limit1),exp(x2+limit2-(
double)(j))))+
    g2*(p->Compute)(p->Par,exp(x1-limit1),exp(x2+limit2-(
double)(j+1))));
    j++;
}

j=1;
for(i=2*N1;i<Ns-N1;i=i+N1) {
    bound[i]=f2*(p->Compute)(p->Par, exp(x1+limit1),exp(x2+    limit2-h2*(double)
    b2*(p->Compute)(p->Par,exp(x1+limit1),exp(x2+limit2-(
double)(j))))+
    i2*(p->Compute)(p->Par,exp(x1+limit1),exp(x2+limit2-(
double)(j+1))));
    j++;
}

bound[Ns-N1+1]=j2*(p->Compute)(p->Par, exp(x1-limit1),exp
(x2-limit2+2.*h2))+
c2*(p->Compute)(p->Par, exp(x1-limit1),exp(x2-limit2+h2
))+
g2*(p->Compute)(p->Par, exp(x1-limit1),exp(x2-limit2))+
e2*(p->Compute)(p->Par, exp(x1-limit1+h1),exp(x2-limit2
))+
i2*(p->Compute)(p->Par, exp(x1-limit1+2.*h1), exp(x2-    limit2));

for(i=1;i<N-1;i++)
    bound[Ns-N1+1+i]=g2*(p->Compute)(p->Par, exp(x1-limit1+

```

```

        h1*(double)i),exp(x2-limit2))+
        e2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)(i+1
    )),exp(x2-limit2))+
        i2*(p->Compute)(p->Par, exp(x1-limit1+h1*(double)(i+2
    )),exp(x2-limit2));

bound[Ns]=g2*(p->Compute)(p->Par, exp(x1+limit1-h1*(
    double)2),exp(x2-limit2))+
    e2*(p->Compute)(p->Par, exp(x1+limit1+h1),exp(x2-limit2
    ))+
    i2*(p->Compute)(p->Par, exp(x1+limit1),exp(x2-limit2))+
    b2*(p->Compute)(p->Par, exp(x1+limit1),exp(x2+limit2-h2
    ))+
    f2*(p->Compute)(p->Par, exp(x1+limit1),exp(x2+limit2-2.
    *h2));

return;
}

static int BCGStab(int am,double s1,double s2,NumFunc_2 *
    p,double t,double r,double divid1,double divid2,double si
    gma1,double sigma2,double rho,int N, int M,int max_iter,
    double tol,int precondition,double *ptprice,double *ptdelta1,double *
    ptdelta2)
{
    int TimeIndex,j,i,Index;
    int N2;
    double x1,x2,m1,m2,cov;
    double limit1,limit2,h1,h2;
    double a2,b2,c2,d2,e2,f2,g2,i2,j2;
    double k;
    double *P,*b,*Obst,*bound,**band,*pivots;

    /*Memory Allocation*/
    N2=(N-1)*(N-1);

    P=(double *)calloc(N2+1,sizeof(double));
    if (P==NULL)
        return MEMORY_ALLOCATION_FAILURE;

    b=(double *)calloc(N2+1,sizeof(double));

```

```

if (b==NULL)
    return MEMORY_ALLOCATION_FAILURE;

Obst=(double *)calloc(N2+1,sizeof(double));
if (Obst==NULL)
    return MEMORY_ALLOCATION_FAILURE;

bound=(double *)calloc(N2+1,sizeof(double));
if (bound==NULL)
    return MEMORY_ALLOCATION_FAILURE;

pivots=(double *)calloc(N2+1,sizeof(double));
if (pivots==NULL)
    return MEMORY_ALLOCATION_FAILURE;

band=(double**)calloc(10,sizeof(double*));
if (band==NULL)
    return MEMORY_ALLOCATION_FAILURE;
for (i=0;i<10;i++)
{
    band[i]=(double *)calloc(N2+1,sizeof(double));
    if (band[i]==NULL)
        return MEMORY_ALLOCATION_FAILURE;
}

m1=(r-divid1)-SQR(sigma1)/2.0;
m2=(r-divid2)-SQR(sigma2)/2.0;
cov=rho*sigma1*sigma2;

/*Space Localisation*/
limit1=sigma1*sqrt(t)*sqrt(log(1/PRECISION))+fabs(m1)*t;
limit2=sigma2*sqrt(t)*sqrt(log(1/PRECISION))+fabs(m2)*t;

/*Space Step*/
h1=2.*limit1/(double) N;
h2=2.*limit2/(double)N;

/*Time Step*/
k=t/(double)M;

/*Lhs factor*/

```

```

a2=1.+k*(r+SQR(sigma1)/SQR(h1)+SQR(sigma2)/SQR(h2));

b2=-k*(SQR(sigma1)/(2.*SQR(h1))+m1/(2.*h1));

c2=-k*(SQR(sigma1)/(2.*SQR(h1))-m1/(2.*h1));
d2=-k*(SQR(sigma2)/(2.*SQR(h2))+m2/(2.*h2));

e2=-k*(SQR(sigma2)/(2.*SQR(h2))-m2/(2.*h2));

f2=-k*cov/(4.*h1*h2);
g2=-k*cov/(4.*h1*h2);
i2=k*cov/(4.*h1*h2);
j2=k*cov/(4.*h1*h2);

/*Cds format*/
cds(N2,a2,b2,c2,d2,e2,f2,g2,i2,j2,band);

/*Preconditioners*/
if (precond==1)
    Diagonal_Precond(band,N2,pivots);
else
    ILU_Precond(band,N2,pivots);

/*Terminal Values*/
x1=log(s1);
x2=log(s2);

for(i=1;i<N;i++) {
    for (j=1;j<N;j++) {
        P[(i-1)*(N-1)+j]=(p->Compute)(p->Par, exp(x1-limit1+
            h1*(double)j),
            exp(x2+limit2-h2*(double)i));
        Obst[(i-1)*(N-1)+j]=P[(i-1)*(N-1)+j];
    }
}

/*Dirichlet Boundary Conditions*/
Dirichlet(N,a2,b2,c2,d2,e2,f2,g2,i2,j2,x1,x2,limit1,limit2,h1,h2,p,bound);

/*Finite Difference Cycle */

```

```

for (TimeIndex=1;TimeIndex<=M;TimeIndex++)
{
    /*Rhs Term*/
    for(i=1;i<=N2;i++)
b[i]=P[i]-bound[i];

    /*BCGStab Algorithm*/
    bicgstab(band,P,b,N2,max_iter,tol,precond,pivots);

    /*Splitting for American case*/
    if (am)
for(i=1;i<=N2;i++)
    P[i]=MAX(P[i],Obst[i]);
}

Index=(int)((double)(N-1)/2.0);
Index=Index*(N-1)+(Index+1);

/*Price*/
*ptprice=P[Index];

/*Deltas*/
*ptdelta1=(P[Index+1]-P[Index-1])/(2.*s1*h1);
*ptdelta2=(P[Index-(N-1)]-P[Index+(N-1)])/(2.*s2*h2);

/*Memory desallocation*/
free(P);
free(b);
free(Obst);
free(bound);
free(pivots);
for (i=0;i<10;i++)
    free(band[i]);
free(band);
return OK;
}

int CALC(FD_BCGStab)(void *Opt,void *Mod,PricingMethod *
    Met)
{

```

```

TYPEOPT* ptOpt=(TYPEOPT*)Opt;
TYPEMOD* ptMod=(TYPEMOD*)Mod;
double r,divid1,divid2;

r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
divid1=log(1.+ptMod->Divid1.Val.V_DOUBLE/100.);
divid2=log(1.+ptMod->Divid2.Val.V_DOUBLE/100.);

return BCGStab(ptOpt->EuOrAm.Val.V_BOOL,ptMod->S01.Val.V_
PDOUBLE,
    ptMod->S02.Val.V_PDOUBLE,ptOpt->PayOff.Val.V_
NUMFUNC_2,
    ptOpt->Maturity.Val.V_DATE-ptMod->T.Val.V_DATE,
    r,divid1,divid2,ptMod->Sigma1.Val.V_PDOUBLE,ptMod->
Sigma2.Val.V_PDOUBLE,ptMod->Rho.Val.V_RGDOUBLE,
    Met->Par[0].Val.V_INT,Met->Par[1].Val.V_INT,Met->
Par[2].Val.V_INT,Met->Par[3].Val.V_PDOUBLE,Met->Par[4].Val.V_
ENUM.value,
    &(Met->Res[0].Val.V_DOUBLE),&(Met->Res[1].Val.V_
DOUBLE),&(Met->Res[2].Val.V_DOUBLE) );
}

static int CHK_OPT(FD_BCGStab)(void *Opt, void *Mod)
{
    return OK;
}

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
    if ( Met->init == 0)
    {
        Met->init=1;

        Met->Par[0].Val.V_INT2=100;
        Met->Par[1].Val.V_INT2=100;
        Met->Par[2].Val.V_INT2=50;
        Met->Par[3].Val.V_PDOUBLE=0.000001;
        Met->Par[4].Val.V_ENUM.value=1;
        Met->Par[4].Val.V_ENUM.members=&PremiaEnumPrecond;
    }
}

```



```

    }

    return OK;
}

PricingMethod MET(FD_BCGStab)=
{
    "FD_BCGStab",
    {"SpaceStepNumber", INT2, {100}, ALLOW}, {"TimeStepNumber",
        INT2, {100}, ALLOW}
    , {"Max Iter", INT2, {100}, ALLOW}, {"Tol", PDOUBLE, {100}, ALL
        OW},
    {"Preconditioner", ENUM, {100}, ALLOW}, {" ", PREMIA_NULLTYPE,
        {0}, FORBID}},
    CALC(FD_BCGStab),
    {"Price", DOUBLE, {100}, FORBID}, {"Delta1", DOUBLE, {100}, FO
        RBID} ,
    {"Delta2", DOUBLE, {100}, FORBID} ,
    {" ", PREMIA_NULLTYPE, {0}, FORBID}},
    CHK_OPT(FD_BCGStab),
    CHK_ok,
    MET(Init)
};

```

## References