

Help

```
#if defined(PremiaCurrentVersion) && PremiaCurrentVersion <
    (2007+2) //The "#else" part of the code will be freely av
    ailable after the (year of creation of this file + 2)
#else

/// {file numint.hpp
/// {brief template class for numerical integration
/// {author M. Ciuca (MathFi, ENPC)
/// {note (C) Copyright Premia 8 - 2006, under Premia 8 Sof
    tware license
//
// Use, modification and distribution are subject to the
// Premia 8 Software license

#ifndef _NUMINT_H
#define _NUMINT_H

#include <stdexcept>

using namespace std;

template<class T> class NumInt
{
    T* _pt;
    double _integrationStep;
public:
    NumInt(T *pt = 0, double integrationStep = 1.e-03) thro
        w(logic_error) :
        _pt(pt),_integrationStep(integrationStep)
    {
        if(integrationStep <= 0)
            throw logic_error("Numerical integration: the
            integration step must be"
            " strictly positive!");
    }

    void setPt(T *pt)
    {
        _pt = pt;
    }
}
```

```
void setIntegrationStep(double integrationStep) throw(
logic_error)
{
    if(integrationStep <= 0)
        throw logic_error("Numerical integration: the
integration step must be"
        " strictly positive!");
    _integrationStep = integrationStep;
}

typedef double (T::*PtrF)(double);
double compute(PtrF f, double a, double b);
};

template<class T>
double NumInt<T>::compute(PtrF f, double a, double b)
{
    if(a == b)
        return 0.;
    if(a > b)
        return - compute(f, b, a);

    double h = _integrationStep; //RIEMANN_NUM_INTEGR_PRECI
SION;
    int step_no = (int) floor((b-a)/h) ;
    double xi = a;
    double sum = 0;
    for(int i=1; i<(step_no+1); i++)
    {
        if(xi+h > b)
            return sum;
        sum += (_pt->*f)(xi+h) * h;
        xi += h;
    }
    return sum;
}
```

```
#endif
#endif //PremiaCurrentVersion
```

References