Help

```
#include <stdlib.h>
#include  "cir1d_stdi.h"
#include "error_msg.h"

/*Product*/
static double dt,dr,r_min,r_max;
static double *r_vect;
static double *V,*Vp,*Option_values,*Ps,**Obst;
static double *beta,*alpha_r,*beta_r,*gamma_r_,*alpha_l,*
    beta_l,*gamma_l;

/*Memory Allocation*/
static int memory_allocation(int Nt,int Ns)
{
  int i;

  if ((Obst = malloc(sizeof(double *)*(Nt+1))) ==NULL)
    {
      printf("Allocation error");
      exit(1);
    }
  for(i=0;i<=Nt;i++)
    {
      Obst[i] = malloc(sizeof(double)*(Ns+1));
    }

  r_vect= malloc((Ns+1)*sizeof(double));
  if (r_vect==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  V= malloc((Ns+1)*sizeof(double));
  if (V==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  Vp= malloc((Ns+1)*sizeof(double));
  if (Vp==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  Option_values= malloc((Ns+1)*sizeof(double));
  if (Option_values==NULL)
```

```
    return MEMORY_ALLOCATION_FAILURE;

  Ps= malloc((Ns+1)*sizeof(double));
  if (Ps==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  beta= malloc((Ns+1)*sizeof(double));
  if (beta==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  alpha_l= malloc((Ns+1)*sizeof(double));
  if (alpha_l==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  beta_l= malloc((Ns+1)*sizeof(double));
  if (beta_l==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  gamma_l= malloc((Ns+1)*sizeof(double));
  if (gamma_l==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  alpha_r= malloc((Ns+1)*sizeof(double));
  if (alpha_r==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  beta_r= malloc((Ns+1)*sizeof(double));
  if (beta_r==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  gamma_r_= malloc((Ns+1)*sizeof(double));
  if (gamma_r_==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  return OK;
}

/*Memory Desallocation*/
static void free_memory(int Nt)
{
  int i;
```

```
  for (i=0;i<Nt+1;i++)
    free(Obst[i]);
  free(Obst);

  free(beta);
  free(alpha_r);
  free(beta_r);
  free(gamma_r_);
  free(alpha_l);
  free(beta_l);
  free(gamma_l);

  free(r_vect);

  free(V);
  free(Vp);
  free(Ps);
  free(Option_values);

  return;
}

/*Compute Coupon Bearing*/
static int cb_cir(int Nt,int Nt0,int Ns,double K,double pe
    riodicity,double first_payement,int nb_coupon)
{
  int i,z,TimeIndex;

  /*Maturity conditions for Coupon Bearing*/
  for(i=0;i<=Ns;i++)
    Ps[i]=1.+K*periodicity;

  /*Finite Difference Cycle*/
  for(TimeIndex=Nt-1;TimeIndex>=Nt0;TimeIndex--)
    {
      /*Right factor*/
      V[0]=beta_r[0]*Ps[0]+gamma_r_[0]*Ps[1];
      for (i=1;i<Ns;i++)
  V[i]=alpha_r[i]*Ps[i-1]+beta_r[i]*Ps[i]+gamma_r_[i]*Ps[
    i+1];
```

```
      /*Backward Steps*/
      Vp[Ns-1]=V[Ns-1];
      beta[Ns-1]=beta_l[Ns-1];
      for(i=Ns-2;i>=0;i--)
  {
    beta[i]=beta_l[i]-gamma_l[i]*alpha_l[i+1]/beta[i+1];
    Vp[i]=V[i]-gamma_l[i]*Vp[i+1]/beta[i+1];
  }

      /*Forward Steps*/
      Ps[0]=Vp[0]/beta[0];
      for (i=1;i<Ns;i++)
  Ps[i]=(Vp[i]-alpha_l[i]*Ps[i-1])/beta[i];

      /*Coupon adjustment*/
      for (i=0;i<Ns;i++)
  for(z=0;z<nb_coupon;z++)
    {
      if((fabs((double)TimeIndex*dt-(first_payement+(
    double)z*periodicity))<1.0e-10))
        {
    Ps[i]+=K*periodicity;
        }
    }
    }

  return 1.;
}

/*Finite Difference for the options prices*/
static int zbo_implicit(int Nt,int Ns,NumFunc_1 *p)
{
  int i,j,TimeIndex;

  /*Maturity conditions*/
  for(j=0;j<=Ns;j++)
    Option_values[j]=(p->Compute)(p->Par,Ps[j]);

  /*Finite Difference Cycle*/
  for(TimeIndex=Nt-1;TimeIndex>=0;TimeIndex--)
```

```
    {
      /*Right factor*/
      V[0]=beta_r[0]*Option_values[0]+gamma_r_[0]*Option_
    values[1];
      for (i=0;i<Ns;i++)
  V[i]=alpha_r[i]*Option_values[i-1]+beta_r[i]*Option_val
    ues[i]+gamma_r_[i]*Option_values[i+1];

      /*Backward Steps*/
      Vp[Ns-1]=V[Ns-1];
      beta[Ns-1]=beta_l[Ns-1];
      for(i=Ns-2;i>=0;i--)
  {
    beta[i]=beta_l[i]-gamma_l[i]*alpha_l[i+1]/beta[i+1];
    Vp[i]=V[i]-gamma_l[i]*Vp[i+1]/beta[i+1];
  }

      /*Forward Steps*/
      Option_values[0]=Vp[0]/beta[0];
      for (i=1;i<Ns;i++)
  Option_values[i]=(Vp[i]-alpha_l[i]*Option_values[i-1])/
    beta[i];

    }

  return 1.;
}


/*Swaption=Option on Coupon-Bearing Bond*/
static int swaption_cir1d(double r0,double k,double t0,
    double sigma,double theta,double T,double t,NumFunc_1 *p,int am,
    double Nominal,double K,double periodicity,long NtY,int Ns,
    double cn_theta,double *price)
{
  int i,j,nb_coupon,Nt0,Nt;
  double val,val1,tmp,first_payement,sigma2;

  /*Compute probabilities*/
  Nt=NtY*(long)((T-t0)/periodicity);
  memory_allocation(Nt,Ns);
```

```
/*Space Localisation*/
dt=(T-t0)/(double)Nt;
r_min=0.;
r_max=2.;
dr=(r_max-r_min)/(double)Ns;
r_vect[0]=r_min;
for(i=0;i<=Ns;i++)
  r_vect[i]=r_min+(double)i*dr;
sigma2=SQR(sigma);

/*Boundary*/
/*Computation of Rhs coefficients*/
alpha_r[0]=0.;
beta_r[0]=(1.-cn_theta)*(1-k*theta*(dt/dr));
gamma_r_[0]=(1.-cn_theta)*(k*theta*(dt/dr));

/*Computation of Lhs coefficients*/
alpha_l[0]=0.;
beta_l[0]=cn_theta*(1+k*theta*(dt/dr));
gamma_l[0]=cn_theta*(-k*theta*(dt/dr));

/*Computation of the Matrix*/
for(i=1;i<Ns;i++)
  {
    /*Computation of Rhs coefficients*/
    alpha_r[i]=(1.-cn_theta)*(0.5*sigma2*r_vect[i]*(dt/SQ
  R(dr))-0.5*k*(theta-r_vect[i])*(dt/dr));
    beta_r[i]=1.-(1.-cn_theta)*(sigma2*r_vect[i]*(dt/SQR(
  dr))+r_vect[i]*dt);
    gamma_r_[i]=(1.-cn_theta)*(0.5*sigma2*r_vect[i]*(dt/
  SQR(dr))+0.5*k*(theta-r_vect[i])*(dt/dr));

    /*Computation of Lhs coefficients*/
    alpha_l[i]=cn_theta*(-0.5*sigma2*r_vect[i]*(dt/SQR(dr
  ))+0.5*k*(theta-r_vect[i])*(dt/dr));
    beta_l[i]=1.+cn_theta*(sigma2*r_vect[i]*(dt/SQR(dr))+
  r_vect[i]*dt);
    gamma_l[i]=cn_theta*(-0.5*sigma2*r_vect[i]*(dt/SQR(dr
  ))-0.5*k*(theta-r_vect[i])*(dt/dr));
  }
```

```
  /*Number of Step for the Option*/
  Nt0=NtY*(long)((t-t0)/periodicity);

  /*Compute Coupon Bearing*/
  first_payement=t+periodicity;
  nb_coupon=(int)((T-first_payement)/periodicity);
  cb_cir(Nt,Nt0,Ns,K,periodicity,first_payement,nb_coupon);

  /*Compute Option Prices*/
  tmp=p->Par[0].Val.V_DOUBLE;
  p->Par[0].Val.V_DOUBLE=1.;
  zbo_implicit(Nt0,Ns,p);

  /*Linear Interpolation*/
  j=0;
  while(r_vect[j]<r0)
    j++;
  val= Option_values[j];
  val1= Option_values[j-1];

  /*Price*/
  *price=Nominal*(val+(val-val1)*(r0-(r_vect[j]))/((r_vect[
    j])-(r_vect[j-1])));

  /*Memory Disallocation*/
  p->Par[0].Val.V_DOUBLE=tmp;
  free_memory(Nt);


  return OK;
}

int CALC(FD_GaussSWAPTION)(void *Opt,void *Mod,Pricing
    Method *Met)
{
  TYPEOPT* ptOpt=(TYPEOPT*)Opt;
  TYPEMOD* ptMod=(TYPEMOD*)Mod;


  return swaption_cir1d(ptMod->r0.Val.V_PDOUBLE,ptMod->k.
```

```
    Val.V_DOUBLE,ptMod->T.Val.V_DATE,ptMod->Sigma.Val.V_PDOUBLE,
      ptMod->theta.Val.V_PDOUBLE,ptOpt->BMaturity.Val.V_
    DATE,ptOpt->OMaturity.Val.V_DATE,ptOpt->PayOff.Val.V_
    NUMFUNC_1,
      ptOpt->EuOrAm.Val.V_BOOL,ptOpt->Nominal.Val.V_PDO
    UBLE,ptOpt->FixedRate.Val.V_PDOUBLE,ptOpt->ResetPeriod.Val.
    V_DATE,Met->Par[0].Val.V_INT,Met->Par[1].Val.V_INT,Met->
    Par[2].Val.V_RGDOUBLE,&(Met->Res[0].Val.V_DOUBLE));
}


static int CHK_OPT(FD_GaussSWAPTION)(void *Opt, void *Mod)
{

  if ((strcmp(((Option*)Opt)->Name,"PayerSwaption")==0) ||
    (strcmp(((Option*)Opt)->Name,"ReceiverSwaption")==0))
    return OK;
  else
    return WRONG;
}

static int MET(Init)(PricingMethod *Met,Option *Opt)
{
  if ( Met->init == 0)
    {
      Met->init=1;

      Met->Par[0].Val.V_INT2=30;
      Met->Par[1].Val.V_INT2=300;
      Met->Par[2].Val.V_RGDOUBLE=0.5;


    }
  return OK;
}

PricingMethod MET(FD_GaussSWAPTION)=
{
  "FD_Gauss_Cir1d_Swaption",
  {{"TimeStepNumber for Period",LONG,{100},ALLOW},{"SpaceS
    tepNumber",INT2,{100},ALLOW  },{"Theta",RGDOUBLE051,{100},
```

```
    ALLOW},
   {" ",PREMIA_NULLTYPE,{0},FORBID}},
  CALC(FD_GaussSWAPTION),
  {{"Price",DOUBLE,{100},FORBID},{" ",PREMIA_NULLTYPE,{0},
    FORBID}},
  CHK_OPT(FD_GaussSWAPTION),
  CHK_ok,
  MET(Init)
} ;
```

References