# Affine Operators for Efficient Office Inference

Abstract. We study affine profile operators for efficient office workflow inference. The document is intentionally saturated with ligature-prone tokens such as office, efficient, profile, offline, and coefficient to expose parser failures in born-digital academic PDFs.

## 1. Method

Let f(x) denote the normalized office traffic profile. The affine update is written in LaTeX-style text so engines that preserve literal formula strings can be scored directly.

```
E[f(X)] = \int_0^\infty x^2 e^{-x} dx
```

```
\frac{d}{dx} \log(1 + e^x) = \frac{e^x}{1 + e^x}
```

The affine coefficient remains stable when the profile vector is projected onto a low-rank office manifold. In practice, this efficient approximation preserves sufficient signal for retrieval while keeping the pipeline economical.

## 2. Appendix

For completeness, we restate the affine profile objective and the coefficient update in code-style math text. This page adds reading-order pressure with a narrow sidebar note and a footer citation.

```
A(\theta) = \sum_i \alpha_i x_i + \beta
\nabla_x L = \frac{\partial L}{\partial x}
```

The office benchmark profile is intentionally repetitive: efficient, office, affine, profile, coefficient, offline. These tokens are enough to catch broken ligature expansion while staying readable in plain text exports.

**supplementary note: preserve inline formulas**