

EDGAR API

Table of Contents

1. Access	5
2. Endpoints	5
2.1. EDGAROperationalStatusAPI	5
eDGAR System Status	5
Description	5
Parameters	5
Return Type	5
Content Type	6
Responses	6
Samples	6
2.2. FilerManagementAPI	6
add Individuals	6
Description	6
Parameters	6
Return Type	7
Content Type	7
Responses	7
Samples	7
change Roles	7
Description	8
Parameters	8
Return Type	8
Content Type	8
Responses	8
Samples	9
create Custom CCC	9
Description	9
Parameters	9
Return Type	9
Content Type	10
Responses	10
Samples	10
filing Credentials Verification	10
Description	10
Parameters	11
Return Type	11

Content Type	11
Responses	11
Samples	11
generate CCC	11
Description	11
Parameters	12
Return Type	12
Content Type	12
Responses	12
Samples	12
remove Individuals	12
Description	13
Parameters	13
Return Type	13
Content Type	13
Responses	13
Samples	14
request Delegation Invitations	14
Description	14
Parameters	14
Return Type	14
Content Type	15
Responses	15
Samples	15
send Delegation Invitations	15
Description	15
Parameters	16
Return Type	16
Content Type	16
Responses	16
Samples	16
view Delegations	17
Description	17
Parameters	17
Return Type	17
Content Type	17
Responses	17
Samples	18
view Filer Account Information	18
Description	18
Parameters	18

Return Type	18
Content Type	18
Responses	18
Samples	19
view Individuals	19
Description	19
Parameters	19
Return Type	19
Content Type	20
Responses	20
Samples	20
2.3. SubmissionAPI	20
bulk Live Submission	20
Description	20
Parameters	20
Return Type	21
Content Type	21
Responses	21
Samples	22
bulk Test Submission	22
Description	22
Parameters	22
Return Type	23
Content Type	23
Responses	23
Samples	24
single Live Submission	24
Description	24
Parameters	24
Return Type	25
Content Type	25
Responses	25
Samples	26
single Test Submission	26
Description	26
Parameters	26
Return Type	27
Content Type	27
Responses	27
Samples	28
2.4. SubmissionStatusAPI	28

check Multiple Submission Statuses	28
Description	28
Parameters	28
Return Type	29
Content Type	29
Responses	29
Samples	29
check Single Submission Status	29
Description	29
Parameters	30
Return Type	30
Content Type	30
Responses	30
Samples	31
3. Models	31
3.1. <i>ClassItem</i>	31
3.2. <i>Condition</i> Condition	31
3.3. <i>DelegationInfo</i> Delegation Information	31
3.4. <i>DelegationInfoResponse</i> Delegation Info Response	32
3.5. <i>EmailRole</i> Email Role	33
3.6. <i>ErrorResponse</i> Error Response	33
3.7. <i>FilerCCCResponse</i> Filer CCC Update Response	33
3.8. <i>FilerCheckResponse</i> Filer Check Response	34
3.9. <i>FilerInfo</i> Filer Information	35
3.10. <i>FilerInfoResponse</i> Filer Info Response	37
3.11. <i>IndividualInfo</i> Individual Information	38
3.12. <i>IndividualInfoResponse</i> Delegation Info Response	39
3.13. <i>IndividualRole</i> Individual Role	40
3.14. <i>Issuer</i>	40
3.15. <i>IssuingEntity</i>	40
3.16. <i>ListSubmissionResponse</i> Submission Response List	41
3.17. <i>ListSubmissionStatusResponse</i> Submission Status Response List	42
3.18. <i>Message</i> Message	43
3.19. <i>MessageType</i> Message Type	43
3.20. <i>MultipleAccessionNumberRequest</i> Submission Number Request List	44
3.21. <i>Response</i> Status Response	44
3.22. <i>SEFMessage</i> Submission Error Message	46
3.23. <i>SeriesItem</i>	47
3.24. <i>SingleSubmissionResponse</i> Submission Response	47
3.25. <i>SingleSubmissionStatusResponse</i> Submission Status Response	48
3.26. <i>SubmissionItemInformation</i> Submission Item Information	52

3.27. <i>SubmissionMode</i> Submission Mode	53
3.28. <i>SubmissionProcessingStatus</i> Submission Processing Status	53
3.29. <i>SubmissionRegistrant</i> Submission Registrant	53
3.30. <i>SubmissionResponseItem</i> Submission Response Item	54
3.31. <i>SubmissionStatusClassItem</i> Submission Class	55
3.32. <i>SubmissionStatusResponseItem</i> Submission Status Response Item	55
3.33. <i>SubmissionStatusSeriesItem</i> Submission Series	59
3.34. <i>SubmissionType</i> Submission Type	59
3.35. <i>TransmissionStatus</i> Transmission Status	60
3.36. <i>UpdateCCC</i> Update CCC	60

Abstract

*No description provided (generated by Openapi Generator
<https://github.com/openapitools/openapi-generator>)*

1. Access

- **Bearer** Authentication
- **Bearer** Authentication

2. Endpoints

2.1. EDGAROperationalStatusAPI

eDGAR System Status

GET */status*

EDGAR System Status

Description

Uses EDGAR operating hours logic and communicates with other EDGAR components to determine the ability of the system to receive API calls and submissions.

Parameters

Return Type

Response **Status** *Response*

Content Type

- application/json

Responses

Table 1. HTTP Response Codes

Code	Message	Datatype
200	Ok. The EDGAR system was able to provide a status response.	Response Status Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. This resource requires a valid Filer API Token. Please ensure that the token that is being used is a Filer API Token and is active in Filer Management.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

2.2. FilerManagementAPI

add Individuals

POST /fm/{cik}/individuals

Add individuals

Description

The add individuals API allows for one or more individuals to be added in specific role(s) for a filer. This API will require the following inputs: the filer API token, the user API token, the EDGAR account CIK for which individuals are to be added, a list of individuals (identified by their names and Login.gov email addresses), and their new roles. The individual associated with the user API token must be an account administrator of the CIK for which individuals are to be added. The filer API token supplied for the request must either match the CIK for which individuals are to be added or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	/\d{10}/

Body Parameter

Name	Description	Required	Default	Pattern
IndividualRole	List of individuals and associated roles IndividualRole Individual Role	X		

Return Type

[FilerInfoResponse](#) [Filer Info Response](#)

Content Type

- application/json

Responses

Table 2. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerInfoResponse Filer Info Response
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

change Roles

PUT /fm/{cik}/individuals

Change roles

Description

The change roles API provides the ability to update roles for individuals for a CIK. This API will require the following inputs: the filer API token, the user API token, the EDGAR account CIK for which roles are to be changed, a list of the individuals (identified by their Login.gov email addresses), and their new roles (updated roles). The individual associated with the user API token must be an account administrator of the CIK for which roles are to be changed. The filer API token supplied for the request must either match the CIK for which roles are to be changed or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	/\d{10}/

Body Parameter

Name	Description	Required	Default	Pattern
EmailRole	List of emails and related roles for updating individual roles EmailRole Email Role	X		

Return Type

[FilerInfoResponse](#) Filer Info Response

Content Type

- application/json

Responses

Table 3. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerInfoResponse Filer Info Response
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response

Code	Message	Datatype
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

create Custom CCC

PUT /fm/{cik}/ccc

Create custom CCC

Description

The create custom CCC API allows a filer to specify a new CCC. The API will require the following inputs: the filer API token, the user API token, the CIK of the EDGAR account for which the custom CCC will be created, the current CCC, and the new CCC. The individual associated with the user API token must be an account administrator of the EDGAR account/CIK for which the CCC is to be changed. The filer API token supplied for the request must either match the CIK for which the CCC is to be changed or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	^d{10}/

Body Parameter

Name	Description	Required	Default	Pattern
UpdateCCC	Update CCC object (Current CCC, Replacement CCC) UpdateCCC Update CCC	X		

Return Type

[FilerCCCResponse](#) Filer CCC Update Response

Content Type

- application/json

Responses

Table 4. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerCCCResponse Filer CCC Update Response
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

filing Credentials Verification

GET /fm/{cik}/verify

Filing credentials verification

Description

The filing credentials verification API provides the ability to view filing credentials for an EDGAR account/CIK. The API GET method requires the filer API token and the user API token in the header along with the relevant CIK in the path of the URL. The individual associated with the user API token must be a user, account administrator, delegated user, or delegated account administrator of the CIK for which the filing credentials are to be verified. The filer API token supplied for the request must either match the CIK for which filing credentials are to be verified or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	^\d{10}/

Return Type

[FilerCheckResponse](#) Filer Check Response

Content Type

- application/json

Responses

Table 5. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerCheckResponse Filer Check Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

generate CCC

POST /fm/{cik}/ccc

Generate CCC

Description

The generate CCC API allows a filer to have EDGAR randomly generate a new CCC for the filer. This API will require the filer API token, the user API token, and the CIK of the EDGAR account for which the CCC will be generated. The individual associated with the user API token must be an account administrator of the EDGAR account/CIK for which the CCC is to be generated. The filer API token supplied for the request must either match the CIK of the EDGAR account for which the CCC is to be generated or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	^\d{10}/

Return Type

[FilerCCCResponse](#) Filer CCC Update Response

Content Type

- application/json

Responses

Table 6. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerCCCResponse Filer CCC Update Response
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

remove Individuals

DELETE /fm/{cik}/individuals

Remove individuals

Description

The remove individuals API provides the ability to remove one or more individuals. This API will require the following inputs: the filer API token, the user API token, the EDGAR account CIK for which individuals are to be removed, a list of individuals (identified by their Login.gov email addresses), and their roles to be removed. The individual associated with the user API token must be an account administrator of the CIK for which individuals are to be removed. The filer API token supplied for the request must either match the CIK for which individuals are to be removed or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	/\d{10}/

Body Parameter

Name	Description	Required	Default	Pattern
string	List of emails of individuals for removal [string]	X		

Return Type

[FilerInfoResponse](#) Filer Info Response

Content Type

- application/json

Responses

Table 7. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerInfoResponse Filer Info Response
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response

Code	Message	Datatype
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

request Delegation Invitations

POST /fm/{cik}/delegationRequests

Request delegation invitations

Description

The request delegation invitations API provides the ability for an EDGAR account (for example, a filing agent) to request delegation from one or more filers. If a filer accepts the delegation request, a delegation invitation will be sent from the filer to the EDGAR account requesting delegation. If the delegation invitation is accepted by the EDGAR account requesting delegation, that EDGAR account will become a delegated entity that can submit filings on behalf of the filer. This API will require the following inputs: the filer API token, the user API token, the CIK belonging to the requesting EDGAR account that would like to become a delegated entity, and CIK(s) that will receive the delegation request. The individual associated with the user API token must be an account administrator of the CIK requesting a delegation invitation. The filer API token supplied for the request must match the CIK requesting a delegation invitation.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	/\d{10}/

Body Parameter

Name	Description	Required	Default	Pattern
string	List of delegation request filer/entity CIKs [string]	X		

Return Type

[FilerInfoResponse](#) Filer Info Response

Content Type

- application/json

Responses

Table 8. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerInfoResponse Filer Info Response
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

send Delegation Invitations

POST /fm/{cik}/delegations

Send delegation invitations

Description

The send delegation invitations API provides the ability for a filer to delegate to one or more EDGAR accounts. If those EDGAR accounts accept the delegation invitation, those EDGAR accounts will become delegated entities who can submit filings on behalf of the delegating filer. This API will require the following inputs: the filer API token, the user API token, the delegating filer's CIK, and a list of one or more delegated entity CIKs that will receive the delegation invitation. The individual associated with the user API token must be an account administrator of the CIK from which delegation invitations are to be sent. The filer API token supplied for the request must match that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	/\d{10}/

Body Parameter

Name	Description	Required	Default	Pattern
string	List of delegation filer/entity CIKs [string]	X		

Return Type

[FilerInfoResponse](#) Filer Info Response

Content Type

- application/json

Responses

Table 9. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerInfoResponse Filer Info Response
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

view Delegations

GET /fm/{cik}/delegations

View delegations

Description

The view delegations API provides the ability for a filer/EDGAR account to retrieve a list of all its delegations to and from other EDGAR accounts/CIKs. This API will require the following inputs: the filer API token, the user API token, and the EDGAR account/CIK for which delegation information is to be retrieved. The individual associated with the user API token must be a user or an account administrator of the CIK for which delegation information is to be retrieved. The filer API token supplied for the request must match that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	/\d{10}/

Return Type

[DelegationInfoResponse](#) Delegation Info Response

Content Type

- application/json

Responses

Table 10. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	DelegationInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response

Code	Message	Datatype
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

view Filer Account Information

GET /fm/{cik}

View filer account information

Description

The view filer account information API provides the ability to view filer information for an EDGAR account/CIK. This API will require the following inputs: the filer API token, the user API token, and the EDGAR account/CIK for which information is being retrieved. The individual associated with the user API token must be a user, account administrator, delegated user, delegated account administrator, or technical administrator of the CIK for which account information is to be viewed. The filer API token supplied for the request must either match that CIK or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	/\d{10}/

Return Type

[FilerInfoResponse](#) [Filer Info Response](#)

Content Type

- application/json

Responses

Table 11. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	FilerInfoResponse Filer Info Response

Code	Message	Datatype
400	Bad request. The request was not successful, possibly due to invalid data	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

view Individuals

`GET /fm/{cik}/individuals`

View individuals

Description

The view individuals API provides the ability to view all individuals with a role for an EDGAR account/CIK. This API will require the following inputs: the filer API token, the user API token, and the CIK for which individuals are to be viewed. The individual associated with the user API token must be an account administrator of the CIK for which individuals are to be viewed. The filer API token supplied for the request must either match the CIK for which individuals are to be viewed or the CIK of the filer API token must have delegation from that CIK.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
cik		X	null	<code>^d{10}/</code>

Return Type

[IndividualInfoResponse](#) [Delegation Info Response](#)

Content Type

- application/json

Responses

Table 12. HTTP Response Codes

Code	Message	Datatype
200	OK. The request was successful.	IndividualInfoResponse Delegation Info Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to perform the action.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Samples

2.3. SubmissionAPI

bulk Live Submission

POST /submission/bulk/live

Bulk Live Submission

Description

Allows an authorized filer to transmit a BULK LIVE submission file. When an authorized filer transmits a filing to this resource it will transmit the file to EDGAR and return a list of accession numbers. EDGAR will then begin processing the submissions.

Parameters

Body Parameter

Name	Description	Required	Default	Pattern
body	A bulk live submission, in XML format, that will be transmitted to EDGAR and processed. [string]	X		

Header Parameters

Name	Description	Required	Default	Pattern
X-EDGAR-CIK	DEPRECATED in favor of X-EDGAR-LOGIN-CIK. If a value is sent in X-EDGAR-LOGIN-CIK this header will be ignored. If no header value is sent in X-EDGAR-LOGIN-CIK this header's value (if present) will be used. An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	
X-EDGAR-LOGIN-CIK	An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	

Return Type

[ListSubmissionResponse](#) Submission Response List

Content Type

- application/json

Responses

Table 13. HTTP Response Codes

Code	Message	Datatype
202	Accepted. The filing has been transmitted to the BULK TEST resource and the EDGAR system has generated accession number(s) for each contained filing. The submission(s) have begun processing.	ListSubmissionResponse SubmissionResponse List
400	Bad request	ErrorResponse Error Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to file (1) for the CIK associated with the Filer API Token and (2) for any CIKs for which filings are being submitted.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response
503	A request was made to this resource outside of operational hours.	ErrorResponse Error Response

Samples

bulk Test Submission

POST /submission/bulk/test

Bulk Test Submission

Description

Allows an authorized filer to transmit a BULK TEST submission file. When an authorized filer transmits a filing to this resource it will transmit the file to EDGAR and return a list of accession numbers. EDGAR will then begin processing the submissions.

Parameters

Body Parameter

Name	Description	Required	Default	Pattern
body	A bulk test filing, in XML format, that will be transmitted to EDGAR and processed. [string]	X		

Header Parameters

Name	Description	Required	Default	Pattern
X-EDGAR-CIK	DEPRECATED in favor of X-EDGAR-LOGIN-CIK. If a value is sent in X-EDGAR-LOGIN-CIK this header will be ignored. If no header value is sent in X-EDGAR-LOGIN-CIK this header's value (if present) will be used. An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	
X-EDGAR-LOGIN-CIK	An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	

Return Type

[ListSubmissionResponse](#) [Submission Response List](#)

Content Type

- application/json

Responses

Table 14. HTTP Response Codes

Code	Message	Datatype
202	Accepted. The filing has been transmitted to the BULK TEST resource and the EDGAR system has generated accession number(s) for each contained filing. The submission(s) have begun processing.	ListSubmissionResponse Submission Response List

Code	Message	Datatype
400	Bad request	ErrorResponse Error Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to file (1) for the CIK associated with the Filer API Token and (2) for any CIKs for which filings are being submitted.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response
503	A request was made to this resource outside of operational hours.	ErrorResponse Error Response

Samples

single Live Submission

POST /submission/single/live

Single Live Submission

Description

Allows an authorized filer to transmit a SINGLE LIVE submission file. When an authorized filer transmits a filing to this resource it will transmit the file to EDGAR and return an accession number. EDGAR will then begin processing the submission.

Parameters

Body Parameter

Name	Description	Required	Default	Pattern
body	A single live submission, in XML format, that will be transmitted to EDGAR and processed. [string]	X		

Header Parameters

Name	Description	Required	Default	Pattern
X-EDGAR-CIK	DEPRECATED in favor of X-EDGAR-LOGIN-CIK. If a value is sent in X-EDGAR-LOGIN-CIK this header will be ignored. If no header value is sent in X-EDGAR-LOGIN-CIK this header's value (if present) will be used. An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	
X-EDGAR-LOGIN-CIK	An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	

Return Type

[SingleSubmissionResponse](#) [Submission Response](#)

Content Type

- application/json

Responses

Table 15. HTTP Response Codes

Code	Message	Datatype
202	Accepted. The filing has been transmitted to the SINGLE LIVE resource and the EDGAR system has generated an accession number. The submission has begun processing.	SingleSubmissionResponse
400	Bad request	ErrorResponse Error Response

Code	Message	Datatype
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to file (1) for the CIK associated with the Filer API Token and (2) for any CIKs for which filings are being submitted.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response
503	A request was made to this resource outside of operational hours.	ErrorResponse Error Response

Samples

single Test Submission

POST /submission/single/test

Single Test Submission

Description

Allows an authorized filer to transmit a SINGLE TEST submission file. When an authorized filer transmits a filing to this resource it will transmit the file to EDGAR and return an accession number. EDGAR will then begin processing the submission.

Parameters

Body Parameter

Name	Description	Required	Default	Pattern
body	A single test submission, in XML format, that will be transmitted to EDGAR and processed. [string]	X		

Header Parameters

Name	Description	Required	Default	Pattern
X-EDGAR-CIK	DEPRECATED in favor of X-EDGAR-LOGIN-CIK. If a value is sent in X-EDGAR-LOGIN-CIK this header will be ignored. If no header value is sent in X-EDGAR-LOGIN-CIK this header's value (if present) will be used. An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	
X-EDGAR-LOGIN-CIK	An optional header to use to provide an alternate CIK to use to generate the accession number of the submission. The provided CIK must delegate to the CIK that the Filer API Token belongs to and the User API Token must represent a user that has permission to file for that CIK. This must be a valid CIK and cannot be blank or empty.	-	null	

Return Type

[SingleSubmissionResponse](#) [Submission Response](#)

Content Type

- application/json

Responses

Table 16. HTTP Response Codes

Code	Message	Datatype
202	Accepted. The filing has been transmitted to the SINGLE TEST resource and the EDGAR system has generated an accession number. The submission has begun processing.	SingleSubmissionResponse
400	Bad request	ErrorResponse Error Response

Code	Message	Datatype
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. A valid Filer API Token and User Access Token must be provided with this request. Please ensure that the User identified by the User Access Token is authorized to file (1) for the CIK associated with the Filer API Token and (2) for any CIKs for which filings are being submitted.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response
503	A request was made to this resource outside of operational hours.	ErrorResponse Error Response

Samples

2.4. SubmissionStatusAPI

check Multiple Submission Statuses

POST /submission/status

Check Multiple Submission Statuses

Description

When an authorized filer requests the status of multiple submissions that the filer made, the Check Multiple Submission Statuses API will respond with the current status of each, if available.

Parameters

Body Parameter

Name	Description	Required	Default	Pattern
MultipleAccessionNumberRequest	A list of accession numbers as strings that the authorized filer is requesting status for. Please note that the maximum number of accession numbers that can be included in a single request is 25. MultipleAccessionNumberRequest Submission Number Request List	X		

Return Type

[ListSubmissionStatusResponse](#) Submission Status Response List

Content Type

- application/json

Responses

Table 17. HTTP Response Codes

Code	Message	Datatype
200	Ok. A submission filed by the authorized filer, with at least one of the given accession numbers, was found	ListSubmissionStatusResponse Submission Status Response List
204	No Content. None of the provided accession numbers were found even though the request was authorized.	<<>>
400	Bad Request. A correctly formed list of valid accession numbers must be provided.	ErrorResponse Error Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. This resource requires a valid Filer API Token. Please ensure that the token that is being used is a Filer API Token and is active in Filer Management.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response
503	A request was made to this resource outside of operational hours.	ErrorResponse Error Response

Samples

check Single Submission Status

GET /submission/{accessionNumber}/status

Check Single Submission Status

Description

When an authorized filer requests the status of a single submission that the filer made, the Check

Single Submission Status API will respond with the current status of that submission.

Parameters

Path Parameters

Name	Description	Required	Default	Pattern
accessionNumber	The accession number returned when a submission is successfully transmitted.	X	null	

Return Type

[SingleSubmissionStatusResponse](#) Submission Status Response

Content Type

- application/json

Responses

Table 18. HTTP Response Codes

Code	Message	Datatype
200	Ok. A submission filed by the authorized filer, with the given accession number, was found	SingleSubmissionStatusResponse Submission Status Response
404	Not Found. No matching accession number found even though the request was authorized and a validly formatted accession number was provided.	SingleSubmissionStatusResponse Submission Status Response
400	Bad Request. A validly formatted accession number must be provided.	ErrorResponse Error Response
401	Unauthorized. This resource is being accessed with invalid or inactive tokens. Please check that the tokens in use are active in Filer Management or are assigned to active individuals.	ErrorResponse Error Response
403	Forbidden. This resource requires a valid Filer API Token. Please ensure that the token that is being used is a Filer API Token and is active in Filer Management.	ErrorResponse Error Response
500	Server error. An unexpected server-side error has occurred.	ErrorResponse Error Response

Code	Message	Datatype
503	A request was made to this resource outside of operational hours.	ErrorResponse Error Response

Samples

3. Models

3.1. *ClassItem*

Field Name	Required	Nullable	Type	Description	Format
id			String		
name			String		
oldName			String		
seriesId			String		
tickerSymbol			String		
oldTickerSymbol			String		

3.2. *Condition Condition*

The current operating state of EDGAR

Enum Values
ACCEPTING
ACCEPTING_WITH_TECHNICAL_DIFFICULTIES
ACCEPTING_AFTER_HOURS
ACCEPTING_AFTER_HOURS_WITH_TECHNICAL_DIFFICULTIES
OUTSIDE_OPERATING_HOURS
NO_COMMUNICATION

3.3. *DelegationInfo* Delegation Information

A collection of fields pertaining to delegation

Field Name	Required	Nullable	Type	Description	Format
entityCik			String	The Central Index Key is a 10 digit unique identifier of a filer	

Field Name	Required	Nullable	Type	Description	Format
entityName			String	Name of a filer	
status			String	Delegation status	
isRequest			Boolean	Is delegation a request?	
autoAddUsers			Boolean	Is auto add users flag selected for active delegations	
lastUpdated			String	Timestamp when last delegation record was updated (RFC3339 formatted date-time).	

3.4. *DelegationInfoResponse* Delegation Info Response

A filer info response is a response that encapsulates information regarding a filer

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
messages			List of Message	A list of messages providing details associated with the filer management response.	
delegationsTo			List of DelegationInfo	An list containing objects made up of properties related to delegation	
delegationsFrom			List of DelegationInfo	An list containing objects made up of properties related to delegation	

3.5. *EmailRole* Email Role

Represents a request for updating the roles of a user in Filer Management

Field Name	Required	Nullable	Type	Description	Format
email			String	String value belonging to the user whose roles are getting updated	
inAdminRole			Boolean	Boolean value describing if the user is going to be added to the filer administrator role'	
inTechAdminRole			Boolean	Boolean value describing if the user is going to be added to the technical administrator role'	
inUserRole			Boolean	Boolean value describing if the user is going to be added to the user role'	

3.6. *ErrorResponse* Error Response

When an error occurs in the API this is the standard response.

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
messages			List of Message Message		

3.7. *FilerCCCResponse* Filer CCC Update Response

This response will be used to return the response when a Filer's CCC has been updated.

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
messages			List of Message Message	A list of messages providing details associated with the filer management response.	
filerCCC			String	Returns a Filer's ccc	

3.8. *FilerCheckResponse* Filer Check Response

This response returns information about the status of a Filer API Token and User API Token.

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
messages			List of Message Message	A list of messages providing details associated with the filer management response.	

Field Name	Required	Nullable	Type	Description	Format
canFile			Boolean	boolean value describing if a filing can be made or not with the provided user api token, filer api token and cik	
confirmationDueDate			Date		date-time
filerApiTokenExpirationDate			Date		date-time
userApiTokenExpirationDate			Date		date-time

3.9. *FilerInfo* Filer Information

A collection of fields pertaining to the overall information on a filer

Field Name	Required	Nullable	Type	Description	Format
cik			String	The Central Index Key is a 10 digit unique identifier of a filer	
stateCode			String	The state code of the filer	
irsNumber			String	Number used by IRS to track filer	
entityStatus			String	The status of the filer A - Active ...	
entityType			String	The type of entity A - Agent F - Filer	
dateIncorporated			date	The date that the filer incorporated (YYYY-MM-DD)	date
deleteFlag			Integer	A flag to determine if the filer has been deleted	int32
sicCode			String	...	
fyEnd			String	The data that marks the end of the filer's fiscal year	
individualOrCompany			String	Denotes if the filer is a company or an individual C - Company I - Individual	
specialFilerType			String	...	
legalEntityIdentifier			String	Legal entity identifier	
repFileNum			String	Reporting Filer Number	
dateModified			String	Date modified	

Field Name	Required	Nullable	Type	Description	Format
entityName			String	The name of the filer	
entityDbaNmae			String	...	
entityForeignName			String	...	
mailIsForeignAddress			String	Is mailing address of a filer a foreign address	
mailStreet1			String	Mailing address of a filer	
mailStreet2			String	Supplemental information on the mailing address	
mailCity			String	The city of the mailing address	
mailStateCode			String	The state/country code of the mailing address	
mailForeignState			String	Foreign state name of the mailing address	
mailZip			String	Zip code of the mailing address	
businessIsForeignAddress			String	Is business address of a filer a foreign address	
businessStreet1			String	The business street address of the filer	
businessStreet2			String	Supplemental information on the business address	
businessCity			String	City of the business address	
businessStateCode			String	State code/country of the business address	
businessForeignState			String	Foreign state name of the business address	
businessZip			String	Zip code of the business address	
peoStreet1			String	...	
peoStreet2			String	...	
peoCity			String	...	
peoStateCode			String	...	
peoZip			String	...	
acctName			String	Name of the accounting at the filer	
acctPhone			String	Phone number of the accounting at the filer	

Field Name	Required	Nullable	Type	Description	Format
acctStreet1			String	The accounting street address of the filer	
acctStreet2			String	Supplemental information on the accounting address	
acctCity			String	City of the accounting address	
acctStateCode			String	State code/country of the accounting address	
acctZip			String	Zip code of the accounting address	
acctEmail			String	Email address of the accounting at the filer	
contName			String	Name of the contact at the filer	
contPhone			String	Phone number of the contact at the filer	
contEmail			String	Email address of the contact at the filer	
mailingPhone			String	Mailing Phone number of the filer	
businessPhone			String	Business Phone number of the filer	
ccc			String	The CCC is the CIK Confirmation Code	
confirmationDueDate			date	Date in which a filer must confirm the filing information and users are up to date and correct (YYYY-MM-DD)	date
singleEntityCompany			Boolean	Boolean field to denote if filer is a single entity company or not 0 - False 1 - True	
website			String	Company website	
series			List of AnyType	Series Class information	

3.10. *FilerInfoResponse* Filer Info Response

A filer info response is a response that encapsulates information regarding a filer

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
messages			List of Message	A list of messages providing details associated with the filer management response.	
filerInfo			List of FilerInfo	An list containing object that contains a list of fields pertaining to a filer's information	

3.11. *IndividualInfo* Individual Information

A collection of fields pertaining to an individual

Field Name	Required	Nullable	Type	Description	Format
email			String	Email of the individual	
firstName			String	First name of the individual	
middleName			String	Middle name of the individual	
lastName			String	Last name of the individual	
businessPhoneNumber			String	Business phone number of the individual	
delegatedCik			String	Individual's primary CIK (if any)	
delegatedEntityName			String	Individual's primary CIK entity name (if any)	
inAdminRole			Boolean	Is Individual in Account Administration role	
inTechAdminRole			Boolean	Is Individual in Technical Administration role	

Field Name	Required	Nullable	Type	Description	Format
inUserRole			Boolean	Is Individual in User role	
inDelegatedAdminRole			Boolean	Is Individual in Delegated Administration role	
status			String	The status of the individual for the CIK	
minInviteDate			date	Earliest invite date user was invited to a role (YYYY-MM-DD)	date
maxAcceptDate			date	Latest date a user can accept the invitation to a role (YYYY-MM-DD)	date

3.12. IndividualInfoResponse Delegation Info Response

A filer info response is a response that encapsulates information regarding a filer

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
messages			List of Message	A list of messages providing details associated with the filer management response.	
individuals			List of IndividualInfo	An list containing objects made up of properties related individual	

3.13. *IndividualRole* Individual Role

Represents a request to create invites for users for a cik

Field Name	Required	Nullable	Type	Description	Format
firstName			String	String value of the individual's first name that is being invited	
middleName			String	String value of the individual's middle name that is being invited	
lastName			String	String value of the individual's last name that is being invited	
email			String	String value of the individual's email that is being invited	
inAdminRole			Boolean	Boolean value describing if the user is going to be added to the filer administrator role'	
inTechAdminRole			Boolean	Boolean value describing if the user is going to be added to the technical administrator role'	
inUserRole			Boolean	Boolean value describing if the user is going to be added to the user role'	

3.14. *Issuer*

Field Name	Required	Nullable	Type	Description	Format
cik			String		
companyName			String		
docTypeCode			String		

3.15. *IssuingEntity*

Field Name	Required	Nullable	Type	Description	Format
cik			String		
companyName			String		
accepted			Boolean		

3.16. *ListSubmissionResponse* Submission Response List

Provides a response that contains a list of responses as well as a top-level list of messages.

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
status			[String]	A short string that indicates the status of filing that was transmitted to EDGAR. * `RECEIVED` - The transmission has been received by EDGAR and an accession number has been generated * `REJECTED` - The transmission was rejected by EDGAR and will not be processed * `FAILED` - The transmission failed to be transmitted to EDGAR and will not be processed`	Enum: RECEIVED, REJECTED, FAILED,
responses			List of SubmissionResponseItem Submission Response Item	A list of submission responses.	
messages			List of Message Message	A list of messages associated with the submission response. This should include more process/submission level errors like why a submission might be rejected from the API level.	

Field Name	Required	Nullable	Type	Description	Format
transmissionStatus			[String]	A short string that indicates the status of filing that was transmitted to EDGAR. * `RECEIVED` - The transmission has been received by EDGAR and an accession number has been generated * `REJECTED` - The transmission was rejected by EDGAR and will not be processed * `FAILED` - The transmission failed to be transmitted to EDGAR and will not be processed`	Enum: RECEIVED, REJECTED, FAILED,

3.17. *ListSubmissionStatusResponse* Submission Status Response List

Provides a response that contains a list of submission status responses as well as a top-level list of messages.

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
responses			List of SubmissionStatusResponseItem	A list of submission status responses.	

Field Name	Required	Nullable	Type	Description	Format
messages			List of Message Message	A list of messages associated with the submission response list. This should include more process/submission level errors like why a submission might be rejected from the API level.	

3.18. *Message* Message

A Message is a response, from EDGAR, giving detail about an interaction with the API. When messages are provided by the API this standard format allows the same parsing to be performed across all instances.

Field Name	Required	Nullable	Type	Description	Format
type			MessageType Message Type	The type of the message being returned regarding how severe it is or what type of message it contains. * `INFO` - The message is intended only for informational purposes and does not necessarily require action * `NOTICE` - There is something that may require human intervention or interaction but it has not prevented filing * `WARNING` - There is an issue with the filing itself or some of the information provided but it may not prevent filing * `ERROR` - There has been an error that either prevented the filing from being submitted or stopped the processing of the submission	INFO, NOTICE, WARNING, ERROR,
content			String	The content of the message intended to be interpreted by a human consumer of the API output.	

3.19. *MessageType* Message Type

The type of the message being returned regarding how severe it is or what type of message it contains.

Enum Values
INFO
NOTICE
WARNING
ERROR

3.20. *MultipleAccessionNumberRequest* Submission Number Request List

Allows a list of accession numbers to be presented to the Submission Status resource in order to request status on multiple submissions simultaneously.

Field Name	Required	Nullable	Type	Description	Format
accessionNumbers	X		List of [string]	The list of accession numbers that the caller wants to receive status for, maximum 25	

3.21. *Response Status Response*

Provides information on the current operating state of EDGAR

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	

Field Name	Required	Nullable	Type	Description	Format
condition			Condition Condition	Represents the current operating state of EDGAR. ACCEPTING - EDGAR is available because EDGAR is reporting that it is operational and within operating hours. ACCEPTING_WITH_TECHNICAL_DIFFICULTIES - EDGAR is experiencing technical difficulties. Consult the EDGAR News and Announcements page on SEC.gov (https://www.sec.gov/submit-filings/edgar-news-announcements) for more information. ACCEPTING_AFTER_HOURS - EDGAR is operating normally. Certain submissions listed in the EDGAR Filer Manual for which transmission begins now (and is completed prior to 10 p.m.) will be treated as filed today. Other submissions will receive a filing date of the next business day. ACCEPTING_AFTER_HOURS_WITH_TECHNICAL_DIFFICULTIES - EDGAR is experiencing technical difficulties. Consult the EDGAR News and Announcements page on SEC.gov (https://www.sec.gov/submit-filings/edgar-news-announcements) for more information. Certain submissions listed in the EDGAR Filer Manual for which transmission begins now (and is completed prior to 10 p.m.) will be treated as filed today. Other submissions will receive a filing date of the next business day. OUTSIDE_OPERATING_HOURS - EDGAR is not available because EDGAR is reporting that it is not within operating hours. NO_COMMUNICATION - EDGAR is not available for API communication due to technical difficulties or other connection issues.	ACCEPTING, ACCEPTING_WITH_TECHNICAL_DIFFICULTIES, ACCEPTING_AFTER_HOURS, ACCEPTING_AFTER_HOURS_WITH_TECHNICAL_DIFFICULTIES, OUTSIDE_OPERATING_HOURS, NO_COMMUNICATION

Field Name	Required	Nullable	Type	Description	Format
message			String	Optionally provides additional information if any is required	

3.22. *SEFMessage* Submission Error Message

A Submission Error Message is a message that has come from EDGAR and is provided when the submission has reached a final disposition after encountering errors in EDGAR

Field Name	Required	Nullable	Type	Description	Format
type			MessageType Message Type	The type of the message being returned regarding how severe it is or what type of message it contains. * `INFO` - The message is intended only for informational purposes and does not necessarily require action * `NOTICE` - There is something that may require human intervention or interaction but it has not prevented filing * `WARNING` - There is an issue with the filing itself or some of the information provided but it may not prevent filing * `ERROR` - There has been an error that either prevented the filing from being submitted or stopped the processing of the submission	INFO, NOTICE, WARNING, ERROR,
content			String	The content of the message intended to be interpreted by a human consumer of the API output.	
errorNumber			Integer	An error code that corresponds to the error label	int32
docSequenceNum			Integer	The document sequence number the error message refers to	int32
lineNumber			Integer	The line number the error occurs on, 0 if not applicable	int32
lineOffset			Integer	The character offset on the line that the error occurs on, 0 if not applicable	int16

Field Name	Required	Nullable	Type	Description	Format
context			String	Additional information related to the error context, 'none' if not applicable	
errorLabel			String	A unique label for the error	

3.23. *SeriesItem*

Field Name	Required	Nullable	Type	Description	Format
id			String		
name			String		
oldName			String		

3.24. *SingleSubmissionResponse* Submission Response

A submission response is a response to transmitting a submission.

Field Name	Required	Nullable	Type	Description	Format
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
accessionNumber		X	String	The unique number associated with an transmitted submission.	

Field Name	Required	Nullable	Type	Description	Format
messages			List of Message Message	A list of messages providing details associated with the submission response. This could range from a notification about the filing to errors related to the state of the filing. This should include things like submission error codes as well as other EDGAR output.	
mode			SubmissionMode Submission Mode		LIVE, TEST,
status			[String]	A short string that indicates the status of filing that was transmitted to EDGAR. * `RECEIVED` - The transmission has been received by EDGAR and an accession number has been generated * `REJECTED` - The transmission was rejected by EDGAR and will not be processed * `FAILED` - The transmission failed to be transmitted to EDGAR and will not be processed`	Enum: RECEIVED, REJECTED, FAILED,
transmissionStatus			[String]	A short string that indicates the status of filing that was transmitted to EDGAR. * `RECEIVED` - The transmission has been received by EDGAR and an accession number has been generated * `REJECTED` - The transmission was rejected by EDGAR and will not be processed * `FAILED` - The transmission failed to be transmitted to EDGAR and will not be processed`	Enum: RECEIVED, REJECTED, FAILED,

3.25. *SingleSubmissionStatusResponse* Submission Status Response

A submission status response is a response to a request for submission status. It expands on the Submission Response by including additional data regarding the submission's status in EDGAR.

Field Name	Required	Nullable	Type	Description	Format
submissionAccessionNumber			String	The accession number associated with any item submissions.	
submissionFormType			String	The FORM TYPE as it would appear on the Submission Status	
items			List of [string]	The list of ITEM(s) as it would appear on the Submission Status	
tracking			String	A universal tracking identifier that can be used by applications to keep track of individual requests sent to the EDGAR API. The tracking identifier correlates all actions taken in the course of a single request. If seeking support from the EDGAR Help Desk this will be a useful piece of information to provide.	
locator			String	A short identifier that can be used by the EDGAR Help Desk to locate the tracking identifier within the EDGAR system.	
accessionNumber		X	String	The unique number associated with an transmitted submission.	
messages			List of Message Message	A list of messages providing details associated with the submission response. This could range from a notification about the filing to errors related to the state of the filing. This should include things like submission error codes as well as other EDGAR output.	
mode			SubmissionMode Submission Mode		LIVE, TEST,

Field Name	Required	Nullable	Type	Description	Format
status			[String]	A short string that indicates the status of a submission within the EDGAR system. * `PROCESSING` - The submission is currently being processed by EDGAR * `SUSPENDED` - The submission has been suspended by EDGAR * `DISSEMINATED` - The submission has been processed and disseminated * `NO_STATUS` - The current status of the submission cannot be determined * `BLOCKED` - The submission has reached the blocked status and is awaiting further action * `DONE` - The submission has reached the DONE state in the EDGAR system and no further processing is expected * `ACCEPTED` - The submission has been accepted by EDGAR	Enum: PROCESSING, SUSPENDED, DISSEMINATED, NO_STATUS, BLOCKED, DONE, ACCEPTED,
company			String	The COMPANY as it would appear on the Submission Status	
documentCount			Integer	The number of DOCUMENTS as it would appear on the Submission Status	int32
formType			String	The FORM TYPE as it would appear on the Submission Status	
receivedDate			Date		date-time
filingDate			Date		date-time
acceptedDate			Date		date-time
suspendedDate			Date		date-time

Field Name	Required	Nullable	Type	Description	Format
final			Boolean	A boolean indicator that, when true, indicates that EDGAR has stopped processing the submission and that the current status is the final status. Once a submission is marked as having its final disposition the full details of the filing are available.	
submissionMessages			List of SEFMessage Submission Error Message	A list messages that are derived from the Submission Error File. These messages include information about the error including a human-readable description and metadata about the message like the line number or error code.	
fileNumbers			List of [string]	The list of FILE NUMBER(s) as it would appear on the Submission Status	
notification			String	A base64 encoded string that, when decoded, is the plain text contents of the submission notification file matching the data from the "Retrieve Submission Information" function of the EDGAR Filing application. This field is only populated when the 'final' field is true.	
registrants			List of SubmissionRegistrant Submission Registrant	A list of registrants associated with the submission as they would appear in the REGISTRANT(s) section of the Submission Notification.	
seriesInformation			List of SubmissionStatusSeriesItem Submission Series	A list of series information (if present) for the submission.	

Field Name	Required	Nullable	Type	Description	Format
classInformation			List of SubmissionStatusClassItem Submission Class	A list of class information (if present) for the submission.	
submissionProcessingStatus			[String]	A short string that indicates the status of a submission within the EDGAR system. * `PROCESSING` - The submission is currently being processed by EDGAR * `SUSPENDED` - The submission has been suspended by EDGAR * `DISSEMINATED` - The submission has been processed and disseminated * `NO_STATUS` - The current status of the submission cannot be determined * `BLOCKED` - The submission has reached the blocked status and is awaiting further action * `DONE` - The submission has reached the DONE state in the EDGAR system and no further processing is expected * `ACCEPTED` - The submission has been accepted by EDGAR	Enum: PROCESSING, SUSPENDED, DISSEMINATED, NO_STATUS, BLOCKED, DONE, ACCEPTED,

3.26. *SubmissionItemInformation* Submission Item Information

Data item representing information about ITEM(s) associated with the submission.

Field Name	Required	Nullable	Type	Description	Format
submissionAccessionNumber			String	The accession number associated with any item submissions.	
submissionFormType			String	The FORM TYPE as it would appear on the Submission Status	
items			List of [string]	The list of ITEM(s) as it would appear on the Submission Status	

3.27. *SubmissionMode* Submission Mode

The submission mode of a filing: * `TEST` - A submission mode that allows a filing to be tested for correctness * `LIVE` - A submission mode that allows a filing to be evaluated as an official filing For more information see the EDGAR Filing Manual

Enum Values
LIVE
TEST

3.28. *SubmissionProcessingStatus* Submission Processing Status

A short string that indicates the status of a submission within the EDGAR system. * `PROCESSING` - The submission is currently being processed by EDGAR * `SUSPENDED` - The submission has been suspended by EDGAR * `DISSEMINATED` - The submission has been processed and disseminated * `NO\_STATUS` - The current status of the submission cannot be determined * `BLOCKED` - The submission has reached the blocked status and is awaiting further action * `DONE` - The submission has reached the DONE state in the EDGAR system and no further processing is expected * `ACCEPTED` - The submission has been accepted by EDGAR

Enum Values
PROCESSING
SUSPENDED
DISSEMINATED
NO_STATUS
BLOCKED
DONE
ACCEPTED

3.29. *SubmissionRegistrant* Submission Registrant

Data item representing a registrant that can be returned as part of the status for a given submission.

Field Name	Required	Nullable	Type	Description	Format
cik			String	The CIK (Central Index Key) as it would appear on the Submission Status as part of the submission registrant information	

Field Name	Required	Nullable	Type	Description	Format
company			String	The COMPANY as it would appear on the Submission Status as part of the submission registrant information	
filingRole			String	The FILING ROLE for the registrant as it would appear on the Submission Status as part of the submission registrant information. Possible values are `Primary Registrant`, `Primary Subject`, `Nonprimary Registrant`, `Nonprimary filed by registrant`, `Nonprimary Reporting owner`, `Nonprimary Serial`, `Primary Subject Combo`, `Ownership Reporting Owner`.	
formType			String	The FORM TYPE as it would appear on the Submission Status as part of the submission registrant information	
fileNumbers			List of [string]	List of File Numbers for this Registrant	

3.30. *SubmissionResponseItem* Submission Response Item

A submission response item is a one element in a submission response list.

Field Name	Required	Nullable	Type	Description	Format
accessionNumber		X	String	The unique number associated with an transmitted submission.	
messages			List of Message Message	A list of messages providing details associated with the submission response. This could range from a notification about the filing to errors related to the state of the filing. This should include things like submission error codes as well as other EDGAR output.	

Field Name	Required	Nullable	Type	Description	Format
mode			SubmissionMode Submission Mode		LIVE, TEST,
final			Boolean		
transmissionStatus			[String]	A short string that indicates the status of filing that was transmitted to EDGAR. * `RECEIVED` - The transmission has been received by EDGAR and an accession number has been generated * `REJECTED` - The transmission was rejected by EDGAR and will not be processed * `FAILED` - The transmission failed to be transmitted to EDGAR and will not be processed`	<i>Enum:</i> RECEIVED, REJECTED, FAILED,

3.31. *SubmissionStatusClassItem* Submission Class

Details about a Class related to a Submission

Field Name	Required	Nullable	Type	Description	Format
id			String	Identifier for the class	
name			String	Name of the class	
oldName			String	Name of the class before the change induced by this filing, if a change was made.	
seriesId			String	Identifier for the related series	
tickerSymbol			String	Ticker symbol for the class	
oldTickerSymbol			String	Ticker symbol for the class before the change induced by this filing, if a change was made.	

3.32. *SubmissionStatusResponseItem* Submission Status Response Item

A submission status response is a single item in a list of submission responses.

Field Name	Required	Nullable	Type	Description	Format
submissionAccessionNumber			String	The accession number associated with any item submissions.	
submissionFormType			String	The FORM TYPE as it would appear on the Submission Status	
items			List of [string]	The list of ITEM(s) as it would appear on the Submission Status	
accessionNumber		X	String	The unique number associated with an transmitted submission.	
messages			List of Message Message	A list of messages providing details associated with the submission response. This could range from a notification about the filing to errors related to the state of the filing. This should include things like submission error codes as well as other EDGAR output.	
mode			SubmissionMode Submission Mode		LIVE, TEST,
status			[String]	A short string that indicates the status of a submission within the EDGAR system. * `PROCESSING` - The submission is currently being processed by EDGAR * `SUSPENDED` - The submission has been suspended by EDGAR * `DISSEMINATED` - The submission has been processed and disseminated * `NO_STATUS` - The current status of the submission cannot be determined * `BLOCKED` - The submission has reached the blocked status and is awaiting further action * `DONE` - The submission has reached the DONE state in the EDGAR system and no further processing is expected * `ACCEPTED` - The submission has been accepted by EDGAR	<i>Enum:</i> PROCESSING, SUSPENDED, DISSEMINATED, , NO_STATUS, BLOCKED, DONE, ACCEPTED,
company			String	The COMPANY as it would appear on the Submission Status	

Field Name	Required	Nullable	Type	Description	Format
documentCount			Integer	The number of DOCUMENTS as it would appear on the Submission Status	int32
formType			String	The FORM TYPE as it would appear on the Submission Status	
receivedDate			Date		date-time
filingDate			Date		date-time
acceptedDate			Date		date-time
suspendedDate			Date		date-time
final			Boolean	A boolean indicator that, when true, indicates that EDGAR has stopped processing the submission and that the current status is the final status. Once a submission is marked as having its final disposition the full details of the filing are available.	
submissionMessages			List of SEFMessage Submission Error Message	A list messages that are derived from the Submission Error File. These messages include information about the error including a human-readable description and metadata about the message like the line number or error code.	
fileNumbers			List of [string]	The list of FILE NUMBER(s) as it would appear on the Submission Status	

Field Name	Required	Nullable	Type	Description	Format
notification			String	A base64 encoded string that, when decoded, is the plain text contents of the submission notification file matching the data from the "Retrieve Submission Information" function of the EDGAR Filing application. This field is only populated when the 'final' field is true.	base64
registrants			List of SubmissionRegistrant Submission Registrant	A list of registrants associated with the submission as they would appear in the REGISTRANT(s) section of the Submission Notification.	
seriesInformation			List of SubmissionStatusSeriesItem Submission Series	A list of series information (if present) for the submission.	
classInformation			List of SubmissionStatusClassItem Submission Class	A list of class information (if present) for the submission.	

Field Name	Required	Nullable	Type	Description	Format
submissionProcessingStatus			[String]	A short string that indicates the status of a submission within the EDGAR system. * `PROCESSING` - The submission is currently being processed by EDGAR * `SUSPENDED` - The submission has been suspended by EDGAR * `DISSEMINATED` - The submission has been processed and disseminated * `NO_STATUS` - The current status of the submission cannot be determined * `BLOCKED` - The submission has reached the blocked status and is awaiting further action * `DONE` - The submission has reached the DONE state in the EDGAR system and no further processing is expected * `ACCEPTED` - The submission has been accepted by EDGAR	Enum: PROCESSING, SUSPENDED, DISSEMINATED, NO_STATUS, BLOCKED, DONE, ACCEPTED,

3.33. *SubmissionStatusSeriesItem* Submission Series

Details about a Series related to a Submission

Field Name	Required	Nullable	Type	Description	Format
id			String	Identifier for the series	
name			String	Name of the series	
oldName			String	Name of the series before the change induced by this filing, if a change was made.	

3.34. *SubmissionType* Submission Type

The submission type (BULK or SINGLE) of a filing

Enum Values
SINGLE
BULK

3.35. *TransmissionStatus* Transmission Status

A short string that indicates the status of filing that was transmitted to EDGAR. * `RECEIVED` - The transmission has been received by EDGAR and an accession number has been generated * `REJECTED` - The transmission was rejected by EDGAR and will not be processed * `FAILED` - The transmission failed to be transmitted to EDGAR and will not be processed`

Enum Values
RECEIVED
REJECTED
FAILED

3.36. *UpdateCCC* Update CCC

Used to update the CCC of a filer

Field Name	Required	Nullable	Type	Description	Format
ccc			String	The current CCC of the filer	
newCCC			String	The new value of the CCC for the filer	