Qwen

Governing Cyboquatic Deployment in Phoenix: A Foundational Data Spine for Corridor-Gated, SMART-Chain-Aligned Operations

The SMART-Chain Matrix: Mapping Cyboquatic Functions to Policy and Physical Capital

The establishment of a functional and safe cyboquatic deployment framework in Phoenix necessitates a precise and unambiguous data architecture. This architecture must serve as the foundational spine upon which all future hardware and software development rests. It is not a hardware design, but rather a comprehensive specification of the data, governance, and logical relationships required to enable such machinery . The core of this architecture is a matrix that systematically maps canonical cyboquatic functions to their required physical and policy-driven components. The user's directive specifies a particular organizational hierarchy for this matrix, prioritizing policy alignment over pure engineering implementation. The optimal structure leads with Aletheion's SMART-chain IDs, which represent binding policy domains, and then nests the relevant cyboquatic function families underneath each chain . This approach ensures that every potential application of cyboquatic technology is immediately contextualized within its governing treaty and performance quality (PQ) modes, preventing developers from operating in a vacuum and ensuring high-level constraints are respected at the point of implementation.

The analysis identifies two primary families of canonical cyboquatic functions, one tailored for canal infrastructure and the other for neighborhood-scale systems. For canal-centric operations, the defined functions include `canalsegmentstate`, `canalmachineryautopilot`, and `canalheatcoolingprofile` . These functions are designed to manage the state of a canal reach, control machinery like pumps and gates, and regulate thermal profiles, respectively. For neighborhood-scale applications, the functions are `neighborhoodwatersystemstate`, `neighborhoodcyboquaticnodeschedule`, and `neighborhoodmicrotreatygate` . These govern the water system state within a city block, schedule the operation of local nodes, and act as a gatekeeper for micro-treaties

governing resource use at the smallest scale. Each of these functions must be assigned to one or more SMART-chains based on their primary purpose and the capitals they manipulate. The seven required capitals—Water, Thermal, Waste, Biotic, Neurobiome, Somatic, and Treaty—are the fundamental resources and constraints that these functions must observe and manage .

The following table presents the proposed mapping, structured according to the user's guidance. The primary axis is the SMART-chain ID, representing the governing policy domain. Under each chain, the relevant cyboquatic function families are listed, along with the required capitals and specific environmental risk-exposure data streams (`rx`). This format makes it immediately clear which data and policy constraints are necessary to unlock a given function. For instance, a function related to water allocation would fall under a Water-focused SMART-chain, requiring access to Water capital data and likely interacting with the Treaty capital to ensure compliance with rights and obligations. A function managing wastewater treatment would be tied to the Waste and Biotic SMART-chains, requiring continuous monitoring of pollutants like PFAS, E. coli, and plastics. The inclusion of `rmicro` highlights the need for real-time data on microbial activity, which is crucial for both waste treatment and biotic health assessments.

SMART-Chain ID	SMART-Chain Purpose	Canonical Cyboquatic Function Family	Required Capitals	Mandatory rx Names / Monitoring Streams
SMART01 AWP/ thermal	Aquifer/Water/Power Resource Management and Thermal Regulation	`canalmachineryautopilot` `canalheatcoolingprofile`	Water Thermal Treaty	`surcharge` `shear` Flow Velocity Stage Cross-Section Heat Vulnerability Index
SMART02 Waste & Bioremediation	Waste Load Management and Ecological Restoration	`neighborhoodwatersystemstate`	Waste Biotic Neurobiome	`PFAS` `E.coli` `plastics` `rmicro`
SMART03 Synthexis Habitat Repair	Biotic and Neurobiome Envelope Management	`canalheatcoolingprofile`	Biotic Neurobiome	`rmicro` Habitat Suitability Scores Species Presence/ Absence Data
SMART04 Somatic Infrastructure	Public Health and Infrastructure Integrity	`neighborhoodcyboquaticnodeschedule`	Somatic Waste	Noise Levels Pathogen Dispersion Models Infrastructure Stress Metrics
SMART05 Neurobiome Equity	Community Well-being and Equity	`neighborhoodmicrotreatygate`	Neurobiome Somatic	Community Engagement Data Equity Scorecard Metrics Access-to-Resources Data

This matrix serves as a direct operational blueprint. It dictates what data Aletheion must ingest and model before a single line of code for a `canalmachineryautopilot` or `neighborhoodmicrotreatygate` can be written. For example, to develop a `canalmachineryautopilot`, the system must have access to data defining the canal's `flow`, `stage`, and `cross-section` [18]. Furthermore, it must be able to query the `Water` capital ledger to understand allocation rights and the `Treaty` capital to know its operational boundaries. The `rx` streams like `surcharge` and `shear` are not just optional metrics; they are the triggers for the autopilot's logic, dictating when to open, close, or modulate machinery to prevent erosion, flooding, or structural damage. Similarly, a `neighborhoodmicrotreatygate` cannot function without reading the `Somatic` and `Neurobiome` capitals to understand community health priorities and equity considerations, ensuring that its scheduling decisions do not disproportionately impact vulnerable populations. This data-first approach, anchored in the SMART-chain hierarchy, transforms cyboquatic development from a purely technical exercise into a deeply integrated socio-technical one, where every piece of machinery is born with its

governance and ecological context encoded directly into its potential for operation. The ultimate goal is to create a system where a function's existence implies its necessary dependencies, making unsafe or unauthorized deployments computationally impossible from the outset.

The Ecosafety Grammar Spine: Defining the Deployable Cyboquatic Node

To enforce a "corridor-first safety approach," it is essential to define a strict, non-negotiable set of criteria for what constitutes a "deployable" cyboquatic node. This is achieved through the establishment of an ecosafety grammar spine, a minimal but complete specification that acts as an upstream gatekeeper for all physical deployments. The user's directive is unequivocal: a node cannot be simulated or built without first declaring its intended operational corridor and its associated ecosafety profile . This "no corridor, no build" policy is the cornerstone of proactive risk management, designed to prevent any unregulated or poorly understood machine from entering the complex urban ecosystem of Phoenix . The grammar spine provides the formal language and structure for this declaration, ensuring that every node has a well-defined spatial and environmental context before it becomes active. This directly serves the primary KER research line target for this turn ($K \approx 0.94$, $E \approx 0.90$, $R \approx 0.12$), as it tightens the knowledge base (K) around the environment while actively constraining the release of risk (R) .

The ecosafety grammar spine consists of a small set of core data types that describe the relationship between a node and its immediate environment. These types provide a standardized way to capture and evaluate potential risks. The mandatory types specified for a deployable node are `Corridor`, `CyboquaticNodeEcosafety`, `RiskCoord`, `RiskVector`, `LyapunovResidual`, and `CorridorEvalResult` . A `Corridor` defines the specific hydrologic, habitat, or infrastructural segment where the node is intended to operate. This is the fundamental spatial anchor. The `CyboquaticNodeEcosafety` type is a composite object that contains all the parameters and constraints for the node within that corridor. It includes the `RiskCoord` and `RiskVector` definitions, which mathematically describe the nature and direction of potential threats. The `LyapunovResidual` provides a measure of the system's stability, ensuring that the node's operation does not push the local environment towards an unstable or unpredictable state. Finally, the `CorridorEvalResult` is the output of a

safety check, a formal verdict that confirms whether the node's planned activities are permissible within the declared corridor under current conditions.

The table below outlines the minimum viable specification for a deployable node, detailing the required declarations. These are not suggestions but hard requirements enforced by the Aletheion platform. The Vt roles refer to the specific thresholds or vectors that trigger safety protocols. For example, a `Vt` for `E.coli` might be the maximum allowable concentration in a neighborhood water system before a `neighborhoodwatersystemstate` node must initiate treatment or shut down. The `rx` names correspond to the specific environmental monitoring streams identified in the SMART-chain matrix.

Component	Specification Details	Role and Justification
Mandatory Declaration	A unique `CorridorId` must be declared for every node before activation.	Establishes the fundamental spatial and jurisdictional unit for governance and risk assessment. No corridor, no build .
Core Data Type	A `CyboquaticNodeEcosafety` object must be instantiated and linked to the `CorridorId`.	Contains all node-specific safety parameters, constraints, and risk models for the defined corridor.
Required `rx` Streams	The node's `CyboquaticNodeEcosafety` object must specify active monitoring for: - `PFAS` (Per- and polyfluoroalkyl substances) - `E.coli` (Fecal coliform bacteria) - `plastics` (Microplastics concentration) - `rmicro` (Real-time microbial community composition) - `surcharge` (Hydraulic head exceeding capacity) - `shear` (Bed shear stress)	These are the critical environmental indicators for the initial pilot phase. Their continuous monitoring is essential for detecting violations of the `Vt` roles and triggering appropriate responses .
Mandatory `Vt` Roles	For each `rx` stream, the node's configuration must define: - `Vt_max`: Maximum allowable concentration/duration. - `Vt_min`: Minimum acceptable level (e.g., for dissolved oxygen). - `Vt_rate`: Maximum rate of change allowed.	Defines the operational envelope. Violations of `Vt` roles automatically trigger alerts or autonomous corrective actions, enforcing the ecosafety rules in real time.
Stability Metric	The `LyapunovResidual` must be calculable and maintained below a system-defined threshold for the node to remain active.	Ensures that the node's behavior does not destabilize the local ecosystem. This is a dynamic constraint that adapts to changing conditions.
Governance Check	A valid `CorridorEvalResult` from a central Aletheion service is required for node activation and periodic re-validation.	Provides a centralized, authoritative confirmation of safety. This prevents local overrides and ensures consistency across the entire network .

This grammar spine is not merely a technical specification; it is a profound governance tool. By codifying the "no corridor, no build" policy into the very definition of a deployable asset, it shifts the burden of proof onto the developer. Instead of asking "Is this machine safe?", the system asks "What is your corridor, what are your risks, and how do you prove you won't exceed your limits there?". This transforms safety from a post-deployment audit into a pre-deployment condition of existence. The secondary KER lines for MAR (Managed Aquifer Recharge) cyboquatic engines and ecotechnology habitat

repair will benefit immensely from this framework. As nodes are deployed in the pilot corridors, the data collected against their `Vt` roles will generate invaluable calibration data for the broader MAR and Synthexis systems, improving the accuracy of models and expanding the overall knowledge base for these technologies . In essence, every compliantly deployed node becomes a sensor and a learning agent, enriching the system's understanding of its own operational boundaries.

Geospatial Anchors and Pilot Area Specifications for Phoenix Corridors

The successful piloting of cyboquatic systems requires carefully selected geospatial anchors that are representative, manageable in scope, and rich in available data. The user's plan directs the selection of these anchors to reuse existing framework elements: `DowntownCentral` and `canalmetrocenterparkway` . These locations serve as ideal primary anchors due to their centrality, accessibility, and the likelihood of having well-documented infrastructure and environmental data. However, to maximize the scientific yield of the pilot and effectively calibrate the ecosafety grammar, the scope must extend beyond these primary points. The pilot should explicitly incorporate adjacent neighborhoods and canal segments that share critical physical regimes, such as being part of the same canal reach, influenced by the same Managed Aquifer Recharge (MAR) plume, or falling within the same Synthexis habitat envelope . To maintain clarity and analytical rigor, these adjacent areas should be designated as "attached corridors" to the primary pilots rather than being treated as separate, independent test sites .

This strategic expansion of the pilot area is critical for increasing the number of state samples per corridor family. The primary KER target involves tightening the bands for `rx` (risk-exposure) and `Vt` (vector threshold) in the ecosafety grammar . Achieving this requires observing how the system behaves under a wide variety of conditions within a single, coherent geographic entity. By including attached corridors, the research can capture the effects of localized inputs—like stormwater runoff from a specific street grid or variations in building density affecting heat vulnerability—on the shared hydrologic and ecological fabric of the main corridor. This approach respects the interconnectedness of urban systems, where events in one block can have cascading effects downstream in the canal or across the neighborhood's water system.

The table below details the specifications for the initial Phoenix pilot areas, providing a concrete "Cyboquatic Pilot Area Sheet" as requested. This sheet lists the primary anchors,

the attached corridors that form an extended pilot zone, and the exact set of physical datasets that Aletheion must ingest before any simulation or deployment can commence. The availability of these datasets is a prerequisite for activating the "no corridor, no build" policy in these zones.

Pilot Zone Designation	Core Anchor(s)	Attached Corridors / Neighborhoods	Mandatory Ingested Datasets
PZ_CANAL_METRO	`canalmetrocenterparkway`	- Adjacent SRP Canal segments upstream/downstream - `NBH_ARTS_DISTRICT` (shares storm drain outfall) - `NBH_LIGHT_INDUSTRIAL` (potential industrial discharge monitoring point)	Flow, Stage, Cross-Section (SRP Canals) [18]; Water Quality (PFAS, E. coli, Plastics); Heat Vulnerability Index; Waste Load Projections [9].
PZ_DOWNTOWN_CORE	`DowntownCentral`	- `NBH_FINANCIAL_DISTRICT` (high-density water use) - `NBH_RETAIL_CORNER` (impermeable surfaces, stormwater flow) - Canal segment serving City Hall area	Building footprints & impervious surface %; Groundwater elevation data; Local weather station data; Sewer overflow event logs [10] [23].
PZ_MAR_FEED_ZONE	`MAR_SITE_ALPHA` (hypothetical)	- `NBH_SUNNYSIDE` (up-gradient residential area) - `NBH_PARK_TERRACE` (down-gradient area) - Associated ASR (Aquifer Storage and Recovery) well field data	Soil permeability maps; Vadose zone moisture sensors; Downgradient groundwater monitoring well data; Historical recharge rates.

Defining the boundaries of these "corridors" requires a robust geospatial framework. While the user has not specified the exact methodology, leveraging established national standards would provide consistency and interoperability. The United States Geological Survey (USGS) Watershed Boundary Dataset, organized by Hydrologic Unit Code (HUC) levels, offers a hierarchical and georeferenced system for delineating watersheds [3] [11]. Using HUC-12 units as the basis for corridor boundaries would align the Phoenix pilot with a nationally recognized standard, facilitating data sharing and comparison with other regions [24] [26]. For instance, the `PZ_CANAL_METRO` pilot zone would likely span several HUC-12 sub-watersheds that feed into the Salt River Project canal system. The `PZ_DOWNTOWN_CORE` would encompass the HUC-12 units corresponding to the surveyed downtown redevelopment area [23]. This formalizes the concept of a "corridor" as more than just a street or a canal; it is a connected, nested system of hydrologic, ecological, and infrastructural relationships. Before any cyboquatic node can be simulated within these defined pilot zones, Aletheion's ingestion pipelines must be configured to pull and process the full suite of datasets listed above. This ensures that every node has a complete, real-time picture of its operational environment, fulfilling the fundamental requirement of the corridor-first safety approach.

Workflow Integration and Systemic Enforcement of Corridor Governance

The fourth and most critical step in establishing the cyboquatic data spine is to integrate the new corridor-first safety principles into Aletheion's existing operational workflows. The user's clarification provides a definitive strategy: the "no corridor, no build" policy must be universally applied across the State, Service, and Governance tiers of the targeted workflows, regardless of whether they currently contain explicit calls to cyboquatic-specific code . This is a profound architectural decision aimed at achieving systemic integrity. Its purpose is to eliminate "silent unsafe paths"—scenarios where a new piece of cyboquatic logic could be added to a workflow in the future, bypassing the original safety checks because they were only implemented in one isolated location. By embedding the corridor requirement into the fundamental rules of each tier, the policy becomes an inherent property of the workflow itself, creating a robust and resilient defense-in-depth against unintended consequences.

The research focuses on five key workflows that are central to Phoenix's water and environmental management: water allocation, thermal regulation, sewer pollutant monitoring, canal–stormwater integration, and the `aletheioninfracyboquatic` pump asset autopilot . For each of these workflows, the update is not merely about adding a new field; it is about fundamentally altering the workflow's precondition for processing cyboquatic-related requests. The cross-walk table detailed below specifies the new, universal constraints that must be added to the State, Service, and Governance configurations for each workflow. These constraints mandate that any action involving a cyboquatic asset must be associated with a valid, pre-declared `CorridorId`. This forces every interaction—whether it's allocating water to a neighborhood node, adjusting a canal's thermal profile, or scheduling a pump—to be vetted against the ecosafety grammar spine of that specific corridor before execution.

The table below presents the cross-walk, detailing the new fields and constraints to be added to each workflow's three tiers. This table serves as the master plan for engineering teams tasked with updating the system. The changes are categorized as follows:

- **State Tier:** Defines the data and ledger entries that must exist. A new ledger entry for `CorridorConstraints` is required.
- **Service Tier:** Defines the inputs and outputs of the services. Every service call related to cyboquatics must accept a `required_corridor_id`.
- **Governance Tier:** Defines the rules and policies. A new rule must be added to validate that all transactions reference a `CorridorEvalResult`.

Workflow	New Field / Constraint (State Tier)	New Parameter (Service Tier)	New Rule (Governance Tier)
Water Allocation	`CorridorWaterLedger` tracking consumption vs. SMART01 quotas.	`required_corridor_id` parameter for all allocation/de-allocation services.	All allocation transactions must validate against `CorridorWaterLedger` for the specified `required_corridor_id`.
Thermal Regulation	`CorridorThermalProfile` with `Vt` for `canalheatcoolingprofile` functions.	`required_corridor_id` parameter for all thermal control services.	All thermal adjustments must be checked against `CorridorThermalProfile` `Vt` limits for the specified `required_corridor_id`.
Sewer Pollutant Mon.	`CorridorWasteCapacities` tracking load vs. SMART02 quotas.	`required_corridor_id` parameter for all monitoring/alerting services.	All waste load updates must be validated against `CorridorWasteCapacities` for the specified `required_corridor_id`.
Canal–Stormwater Int.	`CorridorFloodModels` predicting `surcharge/shear` from inflows.	`required_corridor_id` parameter for all inflow control services.	All control actions must be evaluated by `CorridorFloodModels` to ensure `surcharge/shear` `Vt` are not exceeded for the specified `required_corridor_id`.
Cyboquatic Pumps	`CyboquaticNodeRegistry` with `CorridorId` and `CyboquaticNodeEcosafety` objects.	`required_corridor_id` parameter for all pump schedule/service calls.	All pump schedules must be approved by a central service that verifies the `CyboquaticNodeEcosafety` object against the `CorridorEvalResult` for the specified `required_corridor_id`.

This systematic enforcement across all tiers creates a tightly coupled and auditable system. When a request to allocate water comes in, the State Tier immediately references the correct `CorridorWaterLedger` for that zone. The Service Tier receives the request along with the mandatory `required_corridor_id`. Finally, the Governance Tier executes a rule that cross-references the transaction amount against the ledger's `Vt` values for that specific corridor. If the transaction would violate the `Vt`, it is rejected. This pattern repeats for every workflow and every potential action. The `CyboquaticNodeRegistry` in the pump workflow is particularly powerful, as it acts as a master manifest of all legal assets, each one bound to a specific corridor's safety profile. Any attempt to move or operate a node outside of its registered corridor would be a direct violation of this newly hardened governance layer. This approach ensures that as Aletheion evolves and new cyboquatic capabilities are developed, they will automatically inherit the full weight of the ecosafety framework, preventing the introduction of risk and ensuring that every new capability increases knowledge without increasing danger.

Research Synthesis and Actionable Framework for Deployment

This research delivers a comprehensive, actionable framework for the safe and governed deployment of cyboquatic machinery in Phoenix, centered on a foundational data spine. The primary objective was to assemble the minimal but complete specifications required to site, govern, and corridor-gate these systems, explicitly avoiding hardware design and focusing on the rules of engagement . The resulting framework is built upon four pillars: a SMART-chain-aligned function matrix, a stringent ecosafety grammar, geospatially-grounded pilot areas, and a universal enforcement of corridor governance across all key workflows. This synthesis directly addresses the user's goal of establishing a "corridor-first safety approach" and provides a clear path forward for Aletheion's development teams.

The core contribution of this report is the transformation of abstract governance principles into concrete, implementable data requirements. The proposed SMART-chain matrix provides a direct blueprint for developers, mapping each canonical cyboquatic function to its required capitals and mandatory environmental monitoring streams (`rx`) . By structuring this matrix around SMART-chain IDs, the framework ensures that policy constraints are woven into the fabric of every cyboquatic application from its inception, preventing a disconnect between high-level treaties and low-level implementation . The ecosafety grammar spine defines the absolute minimum criteria for a "deployable" node, codifying the "no corridor, no build" policy into a set of mandatory data declarations (`Corridor`, `CyboquaticNodeEcosafety`, etc.) and `Vt` role validations . This creates a hard, binary gate that prevents unsafe or unregistered machines from ever becoming active in the environment.

Furthermore, the report establishes a practical starting point for piloting in Phoenix by specifying `DowntownCentral` and `canalmetrocenterparkway` as primary anchors, supplemented by strategically chosen "attached corridors" to maximize data richness . The accompanying "Cyboquatic Pilot Area Sheet" provides a definitive list of the physical datasets—from canal cross-sections and water quality metrics to heat vulnerability indices—that must be ingested before any simulation can occur, grounding the entire digital framework in the physical reality of the target environment . Finally, the cross-walk table detailing the required updates to five key workflows provides a direct-to-engineering instruction manual for enforcing corridor governance system-wide . By mandating corridor declarations across the State, Service, and Governance tiers, this framework eliminates silent unsafe paths and ensures that any future evolution of Aletheion will inherit the robust safety posture established in this research turn.

The research turn's K/E/R target is explicitly declared as primarily supporting the "Ecosafety grammar spine for cyboquatic machines" (K≈0.94, E≈0.90, R≈0.12), with secondary support for MAR cyboquatic engines and ecotechnology habitat repair . The proposed framework directly achieves this by generating calibrated data for the ecosafety grammar and creating a controlled environment (the pilot corridors) where MAR and Synthexis technologies can be safely tested and refined. This entire effort is strictly limited to data and governance specifications; no hardware designs are created, as per the user's directive . In summary, the actionable framework provided herein is a complete, self-contained package. It defines what data must exist, where it must be located, how it must be governed, and what constraints must be enforced. This data spine is the essential foundation upon which all future, safe, and effective cyboquatic systems in Phoenix will be built.

Reference

1. Agronomy, Volume 13, Issue 7 (July 2023) – 292 articles https://www.mdpi.com/2073-4395/13/7
2. (PDF) Adaptation of Agriculture to Climate Change: A Scoping Review https://www.researchgate.net/publication/374512623_Adaptation_of_Agriculture_to_Climate_Change_A_Scoping_Review
3. An interdisciplinary overview of levee setback benefits: Supporting ... https://wires.onlinelibrary.wiley.com/doi/10.1002/wat2.1750
4. [PDF] Verde River Watershed Conservation Plan - Amazon AWS https://azgfd-wdw.s3.amazonaws.com/awcs-2022/documents/TNCAZ_VerdeRiver_ConservationPlan-(3).pdf
5. Reclaiming freshwater sustainability in the Cadillac Desert - PMC https://pmc.ncbi.nlm.nih.gov/articles/PMC3003073/
6. [PDF] Arizona Wildlife Conservation Strategy: 2022-2032. - Amazon AWS https://azgfd-wdw.s3.amazonaws.com/awcs-2022/documents/AWCS_Final_Approved_11-22.pdf
7. https://data-usfs.hub.arcgis.com/api/download/v1/i... https://data-usfs.hub.arcgis.com/api/download/v1/items/a73c6dfb582045ab987e8bf3f327dd3b/csv?layers=0
8. Water, Volume 12, Issue 11 (November 2020) – 343 articles - MDPI https://www.mdpi.com/2073-4441/12/11

9. 2023 Annual Conference and Exposition (ACE23) https://events.tpni.com/gcmmaintenance/awwa/html_files/30000213/onlineagenda/index.htm
10. [PDF] Appendix A Final Scope of Work (FSOW) - NY.Gov https://media.bpca.ny.gov/wp-content/uploads/2024/08/28162946/Appendix-A-FSOW.pdf
11. Watershed Boundary Dataset HUC 12s - Overview - ArcGIS Online https://www.arcgis.com/home/item.html?id=b60aa1d756b245cf9db03a92254af878
12. City of Phoenix Water Services Department: D S M W W S - Scribd https://www.scribd.com/document/798586558/d-033069
13. [PDF] Watershed Restoration and Enhancement Plan - ezview.wa.gov https://www.ezview.wa.gov/Portals/_1962/images/WREC/WRIA14/Final%20Plan/WRIA14-WREC-FinalDraftPlan-Feb2021-FullPlan.pdf
14. [PDF] state of new york - Search / Commission Files https://documents.dps.ny.gov/public/Common/ViewDoc.aspx?DocRefId=%7B003F539C-0000-C755-B433-72965118E284%7D&DocTitle=Memorandum%20and%20Resolution%20Approving%20Adoption%20of%20Public%20Service%20Law%20Article%20VIII%20Regulations
15. Creating Autonomous Vehicle Systems https://innovate.ieee.org/wp-content/uploads/2020/03/MC-CAVS.pdf
16. [PDF] Transport Strategies for Net − Zero Systems by Design | OECD https://www.oecd.org/content/dam/oecd/en/publications/reports/2021/11/transport-strategies-for-net-zero-systems-by-design_50206985/0a20f779-en.pdf
17. USGS Watershed Boundary Dataset HUC12 Units - ArcGIS Hub https://hub.arcgis.com/datasets/4681fab75f3849c4893b27104c580962_0
18. SRP Canals Infrastructure - Overview - ArcGIS Online https://www.arcgis.com/home/item.html?id=a38f306dc15f4022a6e225044476b55b
19. Salt River Region and Valley Map Index - Overview - ArcGIS https://www.arcgis.com/home/item.html?id=a4ed2a67d8a1482c86fc77e75298c262
20. Search - ArcGIS Online https://www.arcgis.com/home/search.html?tags=Salt%20River%20Project
21. glove.6B.100d.txt-vocab.txt - CodaLab https://worksheets.codalab.org/rest/bundles/0xadf98bb30a99476ab56ebff3e462d4fa/contents/blob/glove.6B.100d.txt-vocab.txt
22. [PDF] ARIZONA GOVERNMENTAL MALL MASTER PLAN - Amazon AWS https://imlive.s3.amazonaws.com/Arizona/ID101707620968538337846889121009344122 90/AZ_Govt_Mall_Master_Plan_FEB_2020.pdf
23. Downtown Phoenix Redevelopment Area Study - ArcGIS StoryMaps https://storymaps.arcgis.com/stories/48d5aa74a9064ccdaea0228f4b6f2ee3

24. USGS Watershed Boundary Dataset HUC12 - Overview - ArcGIS https://www.arcgis.com/home/item.html?id=fb210309f6ec445987e56f8567f44940
25. [PDF] 2024 City of Tukwila Surface Water Comprehensive Plan https://tukwilawa.gov/wp-content/uploads/PW-Surface-Water-Comprehensive-Plan.pdf
26. Watershed Boundary Dataset: HUC 12 - ArcGIS Hub https://hub.arcgis.com/datasets/642a918106f24013b816b09e5197aab7_6/explore?uiVersion=content-views