Qwen

From Theory to Code: Implementing the Ecosafety Grammar with Rust Crates, ALN Contracts, and qpudatashards for Canal Systems

Foundational Framework: Normalized Risk Coordinates and the Lyapunov Residual

The implementation of the ecosafety grammar for Cyboquatic deployments in aquatic environments hinges on a robust mathematical foundation capable of transforming disparate environmental measurements into a unified, actionable metric of risk. This foundation rests upon two pillars: the normalization kernel (K_x), which maps raw physical quantities into a standardized risk coordinate space (r_x), and the Lyapunov residual (V_t), which serves as a scalar summary of the system's aggregate ecological risk . The strategic objective is to freeze this theoretical framework and translate it into concrete, machine-readable artifacts, prioritizing the Phoenix canal system as the canonical reference instantiation . This approach ensures that all subsequent applications, from optimal node placement to digital twin architecture, operate as strict clients of a universal, proven safety grammar rather than spawning parallel, unvalidated branches . The primary directive is to move from high-level conceptual alignment to tangible implementation-level guidance, including Rust/Crate specifications, qpudatashard schemas, and ALN contract definitions .

The first step in this process is the creation of the normalized risk coordinate, r_x. Its purpose is to provide a common currency for comparing and aggregating different types of ecological stressors, such as chemical contaminants (e.g., PFAS), nutrient loads, dissolved oxygen levels, and thermal anomalies . Each key parameter monitored in the canal—temperature (SAT), dissolved oxygen (DO), flow velocity, nutrients, pathogens like *E. coli*, and trace organic contaminants—is mapped through a dedicated normalization kernel, K_x, into its corresponding risk coordinate, $r_x \in [0,\infty)$. The most critical operational definition of this mapping is that the value $r_x = 1$ corresponds precisely to the outer boundary of the "goldband"—the hard corridor edge . This edge can be calibrated against regulatory limits, ecotoxicological thresholds, or other defensible

ecological benchmarks relevant to the specific environment . For instance, for Dissolved Oxygen, the kernel would map measured concentrations in mg/L onto the r_{DO} scale based on the known tolerance ranges of local biota . Similarly, for Surface Water Temperature (SAT), the kernel would map deviations from known species-specific stress bands . By anchoring the hard corridor edge at $r_x=1$, the framework creates a clear, quantifiable threshold that separates "within corridor" states from "outside corridor" states. This normalization is fundamental because it allows for the cross-domain comparison of different hazards and unifies all eco-safety decisions into a single, cohesive residual calculation .

The second pillar of the framework is the Lyapunov residual, denoted as V_t. It is mathematically defined as the weighted sum of the squared risk coordinates:

$$V_t=\sum_i w_i r_{x_i}^2$$

where w_i represents the weight assigned to each coordinate r_{x_i} . The residual V_t acts as a powerful scalar proxy for the overall health of the aquatic ecosystem, providing a single number that encapsulates the cumulative pressure from multiple stressors. Its significance lies in its connection to Lyapunov stability theory, a cornerstone of control systems engineering. The requirement that any admissible control action must satisfy a discrete-time Lyapunov condition, specifically $V_{t+1}\leq V_t$ when outside a small, predefined "safe interior," transforms the abstract goal of ecological preservation into a provable mathematical invariant . This means the system's governance structure can formally guarantee that its actions will not lead to an increase in aggregate ecological risk. The weights, w_i, are crucial as they allow the model to reflect the relative importance of different parameters; for example, a small violation of a critical nutrient might be weighted more heavily than a larger but less impactful deviation in a benign parameter. The selection of these weights and the definition of the corridor bands are not arbitrary; they are the subject of empirical calibration campaigns conducted on the reference Phoenix canal system to ensure the model reflects real-world ecological priorities and sensitivities . The entire structure, from raw measurement to the scalar residual, is designed to be embedded within a structured data format, `qpudatashards`, which will serve as the persistent ledger for all state and decision-making information . This integration ensures that every deployment decision is computed on top of the same, consistent mathematical foundation, enabling rigorous testing, validation, and eventual generalization .

The following table outlines the conceptual components of this foundational framework, which will be realized in the subsequent implementation artifacts.

Component	Description	Key Parameters	Mathematical Representation
Normalization Kernel (K_x)	A function that maps a raw physical measurement (x) to a normalized risk coordinate (r_x). It establishes a common scale for disparate environmental parameters.	Calibration against regulatory or ecological thresholds (e.g., species stress bands, toxic loadings) .	$r_x = K_x(x)$, where $r_x \in [0, \infty)$ and $r_x = 1$ at the corridor edge .
Risk Coordinate (r_x)	The output of the normalization kernel, representing the degree of deviation from a "healthy" state for a specific parameter.	Safe/Gold/Hard corridor bands for the parameter (e.g., $r_{SAT,min}$, $r_{SAT,max}$).	$r_x \in [0, \infty)$, typically bounded by corridor edges .
Lyapunov Residual (V_t)	A scalar summary of the system's aggregate ecological risk, calculated as a weighted sum of the squared risk coordinates. It enables provable risk guarantees.	Weights for each risk coordinate (w_i) reflecting their relative importance .	$V_t = \sum_i w_i r_{x_i}^2$.
Lyapunov Condition	A discrete-time stability criterion that mandates the residual cannot increase under admissible control actions. This forms the basis of the `safestep` contract.	A target ceiling for the residual ($V_{t,ceiling}$) and a definition of the "safe interior."	$V_{t+1} \leq V_t$ (when outside the safe interior) .

This foundational framework provides the necessary rigor and mathematical grounding to transition the ecosafety grammar from a theoretical construct to an implementable, verifiable system. By freezing the definitions of the normalization kernels and the Lyapunov residual, and embedding them within machine-readable formats, the path is cleared for developing the specific crate specifications, shard schemas, and ALN contracts that will govern Cyboquatic deployments in the Phoenix canals and, by extension, across future aquatic environments . The success of this endeavor depends entirely on the precision with which these concepts are translated into code and data schemas, ensuring that the resulting system is both powerful enough to capture complex ecological dynamics and restrictive enough to enforce non-increasing risk trajectories. The next sections detail this translation process, moving from the abstract mathematics to concrete implementation artifacts.

Core Logic Specification: Codifying the Distinction Between Natural Variability and True Excursions

The central challenge in implementing the ecosafety grammar is to codify the nuanced distinction between transient, self-correcting natural variability and a true, persistent "excursion" that requires a change in `deploydecision` from `continue` to `derate` or `withdraw` . This distinction is not a simple threshold violation but a sophisticated, multi-layered detection system grounded in empirical ecology and control theory . The implementation must formalize this logic to prevent over-reaction to minor fluctuations

while ensuring a prompt response to genuine threats. The process involves establishing a statistical baseline of "natural" behavior, defining a structured "goldband" with soft and hard edges, and specifying the precise triggers that constitute a "true excursion." These triggers include sustained violations, multi-coordinate deterioration, and matches to empirically validated harm signatures. All of this logic must be integrated into the core runtime enforcement mechanisms, turning a qualitative judgment into a provable property of the system's risk state.

The first layer of this logic is the establishment of an ecological baseline. Before any Cyboquatic nodes are deployed, a comprehensive dataset must be collected from representative canal reaches that are free of such nodes . This dataset must span at least one full seasonal cycle to capture the full range of natural variation driven by factors like temperature cycles, monsoon pulses, and scheduled irrigation releases . This data is used to empirically estimate the mean and variance of each normalized risk coordinate (r_x) under "natural" conditions . Beyond simple statistics, the analysis must quantify the autocorrelation and typical event scales for each parameter. This allows for the creation of a dynamic, statistically informed envelope of expected natural behavior. Any proposed node placement shard must contain references to this baseline data, perhaps in fields like `baseline_mean_rx`, `baseline_variance_rx`, and `typical_recovery_time`. This provides a quantitative standard for what constitutes a "natural" event—one where r_x briefly touches or slightly exceeds 1 but returns to within the baseline band within a characteristic recovery timeframe, often cited as 24–72 hours for SAT and nutrients .

With the baseline established, the "goldband" structure can be formally defined within the shard schema. This corridor is explicitly partitioned into a "soft interior" and a "hard edge." The soft interior is defined by the condition r_x \le r_{\text{soft}} < 1 , where r_{soft} is a value closer to zero than the hard edge . An excursion into this region might trigger a monitoring alert or a slight adjustment in control strategy but does not, by itself, warrant a major derate or stop decision. The hard edge is defined by $r_x \le 1$. Violation of this edge signifies a departure from the empirically observed corridor and initiates the deeper scrutiny of the true excursion logic. The values for r_{soft} and the hard edge (which is 1) are determined during the empirical calibration phase for the Phoenix canal system .

A true excursion, sufficient to flip the `deploydecision`, is not merely a spike above the hard edge. Instead, it is defined by one of three mutually exclusive criteria:

1. **Sustained Violation:** The system remains in a state where r_x > 1 for a duration significantly longer than the measured natural recovery timescale. A practical rule of thumb is a duration greater than 2–3 times the characteristic

return-to-corridor time for that specific parameter . This filters out brief, stochastic spikes and focuses on persistent conditions.

2. **Multi-Coordinate Deterioration:** Even if individual r_x values hover just below their respective hard edges, a true excursion is indicated if the total Lyapunov residual, V_t, increases monotonically over a specified time window. This pattern signals a systemic degradation of the ecosystem that cannot be explained by the independent fluctuation of a single variable. It suggests a compounding effect, such as simultaneous increases in temperature, nutrient loading, and pathogen presence, pushing the system toward a tipping point .
3. **Harm Signature Match:** The system detects a pattern of deteriorating risk coordinates that matches an empirically validated "harm signature." These signatures are not theoretical but are derived from field observations and controlled experiments correlating sensor data with biological outcomes . Examples include the distinct combination of rising SAT, collapsing DO, and elevated nutrient levels that precedes a harmful algal bloom or fish kill event [2] [4], or the chronic elevation of SAT in a designated refugia reach that indicates a failure of the cooling system . These signatures must be cataloged and encoded as additional ALN predicates tied directly to the shard fields storing the time-series data of the relevant risk coordinates.

The following table summarizes the logical conditions for classifying an excursion.

Condition	Description	Example Trigger	Required Data / Calculation
Natural Event	Brief excursion that falls within the statistically defined natural baseline envelope and recovers quickly.	r_{SAT} > 1 for 2 hours, followed by a return to baseline within 48 hours.	Baseline statistics ($mean$,$variance$), autocorrelation, recovery time constants.
Soft Interior Violation	Sustained excursion within the "soft interior" band (r_x \le r_{soft} < 1).	r_{Ecoli}=0.85 for a period of days.	Normalized risk coordinates (r_x), corridor band definitions.
Hard Edge Violation	A spike or short-term excursion exceeding the hard corridor edge (r_x > 1).	r_{PFAS}=1.1 for a few hours.	Normalized risk coordinates (r_x), corridor band definitions.
True Excursion	Meets one of the following criteria:		
• Sustained Violation	Hard edge violation persists longer than the natural recovery timescale.	r_{Nutrient} > 1 for 5 days, well beyond the 72-hour recovery time.	Time-series of r_x, natural recovery timescale.
• Multi-Coordinate Deterioration	Monotonic increase in the total Lyapunov residual (V_t) outside the safe interior.	r_{Temp},r_{DO},r_{Ecoli} all slowly increasing, causing V_t to rise.	Time-series of all r_x, Lyapunov residual calculation.
• Harm Signature Match	The pattern of deteriorating coordinates matches a pre-defined, empirically validated biological event.	Rising SAT, collapsing DO, and specific nutrient ratios matching a historical fish kill event.	Time-series of r_x, catalog of harm signatures.

This layered logic moves the decision-making process from a reactive, threshold-based system to a proactive, context-aware one. It acknowledges that ecosystems are dynamic and that some deviation is normal. However, it also provides a rigorous, evidence-based framework for identifying and responding to genuine threats. The final step is to translate these logical conditions into executable code and formal contracts, which is addressed in the subsequent sections on crate specifications and runtime enforcement. The successful implementation of this core logic is paramount, as it serves as the foundational kernel upon which all other aspects of the ecosafety grammar—including node density, downstream impact avoidance, and refugia design—depend .

Machine-Readable Contracts: Formalizing Governance with ALN and qpudatashards

To transform the abstract principles of the ecosafety grammar into a reliable, auditable, and scalable system, they must be formalized into machine-readable contracts. This is achieved by combining a structured data format, `qpudatashards`, with a declarative language for specifying governance rules, the Agreement Layer Network (ALN). This section details the specifications for the required implementation artifacts: a Rust/Crate named `ecosafety-core` containing the fundamental logic, the schema for the main `NodePlacement` shard, and a canonical `.aln` file that defines the immutable rules governing deployments in the Phoenix canal system. This approach ensures that every Cyboquatic node is a strict client of the frozen ecosafety grammar, preventing ad-hoc or unsafe configurations from ever being deployed .

First, a core Rust crate, tentatively named `ecosafety-core`, must be developed. This crate will house the universal, domain-agnostic logic of the ecosafety grammar, making it a reusable library for all future aquatic applications. Its public API should expose data structures and functions that directly mirror the theoretical constructs discussed previously.

The primary data structures within the crate would be:

- `RiskCoord`: A struct to represent a single normalized risk coordinate. It would contain fields for the current risk value (`rx_value: f64`), a reference to its associated corridor bands (`corridor_bands: CorridorBands`), and metadata such as the version of the normalization kernel used (`kernel_version: String`) and citations for the underlying scientific basis (`citations: Vec`).
- `Residual`: A struct to manage the Lyapunov residual calculation. It would hold a vector of `RiskCoord` objects and a corresponding vector of weights. It would expose a method, `calculate(&self) -> f64`, to compute V_t according to the formula $\sum w_i r_{x_i}^2$.
- `CorridorBands`: A struct to define the permissible range for a risk coordinate. It would contain fields for the `safe` (e.g., $r_x \leq r_{soft}$), `gold`, and `hard` (e.g., $r_x \leq 1$) boundaries, along with timestamps and authorizations for any changes.

The core functions exposed by the crate would include:

- `normalize_measurement(value: f64, bands: &CorridorBands) -> Result`: The implementation of the normalization kernel K_x, which maps a raw measurement

to an r_x value. It would validate the input against the provided bands and return an error if the value is already outside the hard corridor.
- `is_in_safe_interior(vt: f64, threshold: f64) -> bool`: A helper function to check if the system's residual is within the small, safe operating region.
- `safestep_satisfied(current_vt: f64, proposed_vt: f64, corridor_violated: bool) -> bool`: The direct implementation of the `safestep` logic. This function would return `true` only if either no corridor was violated, or if a corridor was violated, the proposed action did not cause the residual to increase ($proposed_vtlecurrent_vt$).

Second, the schema for the `qpudatashard` that records node placements becomes the central ledger for all deployments. This shard, let's call it `PhoenixNodePlacementShard.csv`, must be meticulously designed to capture all necessary information for runtime validation. Crucially, it must include boolean columns to flag the status of the `corridorpresent` and `safestep` invariants.

A proposed schema for this shard is presented in the table below.

Column Name	Data Type	Description	Constraint / Source
`node_id`	String (Primary Key)	Unique identifier for the node, likely a DID or UUID.	Not Null
`placement_timestamp_utc`	Timestamp	The timestamp of when the placement decision was made.	Not Null
`lat` / `lon`	Decimal(10, 8)	Geospatial coordinates of the node's location.	Not Null
`reach_id`	String	Identifier linking the node to a specific canal reach in the network graph.	Foreign Key
`r_TDS` / `r_Pfas` / ...	f64	Normalized risk coordinates for various monitored parameters.	Calculated by node telemetry service
`Vt`	f64	The calculated Lyapunov residual for the node's immediate vicinity.	Calculated by `ecosafety-core` crate
`is_corridor_present`	Boolean	Status flag indicating if all required corridor bands are defined for this node.	Computed by shard validator
`is_safestep_compliant`	Boolean	Status flag indicating if the node's control logic satisfies the safestep invariant.	Computed by shard validator
`deploydecision`	Enum	The current operational status of the node (`Continue`, `Derate`, `Withdraw`).	Computed by governance logic
`evidencehex`	String	Cryptographic hash of the raw telemetry and baseline data used to compute the row.	Generated on write
`signinghex`	String	Digital signature from the deploying entity's DID.	Generated on write

Third, a canonical ALN specification, `canal_goldband_excursion_logic.aln`, must be created. This file serves as the master contract that all implementations and validations must adhere to. It is a declarative document that precisely defines the rules of engagement. Drawing inspiration from the provided research directions, its structure would be as follows:

```
### File: qpudatashards/particles/canal_goldband_excursion_logic.aln
alnversion 1.0
schema phoenix.ecosafety.goldband.v1

# --- REQUIRED RISK COORDINATES ---
required_risk_coordinates
r_TDS
r_Pfas
r_Nutrients
r_DO
r_SAT
r_Ecoli
end_required_risk_coordinates

# --- CORRIDOR PRESENCE RULE ---
corridorpresent_rule
require_columns
r_TDSmin r_TDSmax
r_Pfasmin r_Pfasmax
r_Nutrientsmin r_Nutrientsmax
r_Domin r_Domax
r_SATmin r_SATmax
r_Ecolimin r_Ecolimax
kernel_version
evidencehex
end_require_columns

# --- SAFESTEP RULE ---
safestep_rule
residual_type squared
residual_name Vt
residual_definition "Vt = (w1<em>r_TDS^2 + w2</em>r_Pfas^2 + ...)" # Weigh
vt_ceiling 0.13 # Target residual level, derived from research
on_violation_modes derate, stop
```

```
end_safestep_rule

# --- DEPLOYDECISION KERNEL ---
deploydecision_kernel
inputs K_current, E_current, R_current
condition "K_current >= 0.93 and E_current >= 0.90 and R_current <= 0.13"
on_false_action "reject_deploy"
on_true_action "allow_deploy"
end_deploydecision_kernel

# --- AUDIT AND PROVENANCE FIELDS ---
audit_fields
shard_field node_id
shard_field lat
shard_field lon
shard_field K
shard_field E
shard_field R
shard_field corridorpresent
shard_field safestep
shard_field vtmax
shard_field evidencehex
shard_field signinghex
end_audit_fields
```

This ALN file is machine-parsable and encodes the complete set of requirements. It specifies which risk coordinates are mandatory, defines the exact columnar structure needed in the shard for `corridorpresent` to pass, and formally binds the Lyapunov residual calculation and its associated `safestep` invariant to the `derate/stop` actions. Finally, it gates the ultimate `deploydecision` on the system-level KER metrics, ensuring that even if local residuals are acceptable, poor knowledge, low eco-impact, or high residual risk prevents deployment . Together, the `ecosafety-core` crate, the `PhoenixNodePlacementShard` schema, and the `canal_goldband_excursion_logic.aln` form a closed-loop system of formal verification, where every potential deployment is checked against a frozen, machine-readable contract before it can take effect. This eliminates ambiguity and enforces the highest standards of safety and accountability.

Runtime Enforcement and Downstream Impact Mitigation

While the static specifications of the `ecosafety-core` crate, `qpudatashard` schema, and ALN contract define the rules, the true power of the ecosafety grammar lies in its dynamic, runtime enforcement. This enforcement is governed by two core invariants: `corridorpresent` and `safestep`. The former acts as a prescriptive gatekeeper, enforcing the principle "no corridor, no build," while the latter acts as a reactive guardian, enforcing "violated corridor, derate/stop" . The implementation must translate these principles into a live validation process that scrutinizes every potential control action. Furthermore, for a connected system like a canal network, the logic must be extended beyond the immediate vicinity of a node to mitigate unintended downstream impacts on water rights and ecological corridors. This requires augmenting the node placement shard with adjacency information and modifying the `safestep` contract to consider a network-wide Lyapunov residual.

The enforcement begins with the `corridorpresent` invariant. Before any Cyboquatic node is physically deployed or a new operational plan is activated, a validation service must interrogate the corresponding row in the `PhoenixNodePlacementShard`. This service, likely part of a surface gateway or a centralized governance cluster, parses the canonical ALN contract (`canal_goldband_excursion_logic.aln`) and checks the shard row against it . Specifically, it verifies that for every required risk coordinate listed in the `required_risk_coordinates` block (e.g., `r_TDS`, `r_Pfas`, etc.), the corresponding minimum and maximum columns exist in the shard (e.g., `r_TDSmin`, `r_TDSmax`) and are populated with valid, finite numerical values . It also checks for the presence of metadata columns like `kernel_version` and `evidencehex` . If any of these required fields are missing or invalid, the `is_corridor_present` flag in the shard is set to `false`, and the `deploydecision` is rejected. This automated, pre-deployment screening ensures that no node can exist or operate without a fully defined and documented set of ecological corridors, making "no corridor, no build" a provable property of the system.

Once a node is deployed and operational, the `safestep` contract becomes the active runtime guardrail. At each control timestep, the node's controller proposes a sequence of actions (e.g., adjust valve position, change pump speed). The system's governance logic must then evaluate whether this proposed action is safe. This evaluation is performed by the `ecosafety-core` crate. First, the controller simulates the effect of the proposed action and calculates the resulting risk coordinates ($rx_{proposed}$) and the consequent Lyapunov residual (V_{t+1}). Then, the `safestep_satisfied` function is called with the

current residual (V_t), the proposed residual (V_{t+1}), and a boolean indicating if any corridor was violated by the proposal . The function returns `true` only if the proposal keeps the residual non-increasing ($V_{t+1} \leq V_t$) *or* if no corridor was violated. If the function returns `false`, it means the proposed action would either violate a corridor *and* increase the residual. In this case, the action is rejected, and the `deploydecision` for the node is escalated to `derate` or `withdraw`, depending on the severity and persistence of the unsafe condition . This turns the question of a "true excursion" into a direct, computationally verifiable property of the risk residual trajectory. The system has entered a state where no admissible control input exists that can simultaneously respect all corridors and keep V_t non-increasing.

To address downstream impacts, this logic must be extended. A local action, such as diverting flow through a node, can have significant consequences for water rights and ecological health kilometers downstream. To handle this, the `NodePlacement` shard schema is augmented with fields that encode the canal's hydraulic and legal adjacency map . For each candidate node position, the shard includes a list of **downstream dependency IDs** and associated sensitivity indices that quantify how the node's operation propagates to dependent reaches . These indices could be linearized sensitivities of flow and stage derived from a digital twin simulation, or Monte Carlo-derived sensitivities tracking impacts on downstream flows and rights-sensitive nodes .

The `safestep` contract is then modified to become "downstream-aware." Instead of calculating a local residual, V_t^{local}, the contract now considers a network-wide residual, $V_t^{network}$, which includes not only the local risk coordinates but also those of the downstream dependencies. The extended residual might look something like:

$$V_t^{network} = V_t^{local} + W_{downstream} \cdot (V_t^{dependency1} + V_t^{dependency2} + ...)$$

where the weights $W_{downstream}$ could be derived from the sensitivity indices stored in the placement shard. The `safestep` invariant is then applied to this network-wide residual. A control action is only deemed safe if it results in a non-increasing $V_t^{network}$. This prevents a situation where a local control policy that appears safe in isolation could cumulatively push a downstream rights or ecological coordinate beyond its corridor, thus applying the "no corridor, no build" principle transitively along the entire canal graph . At runtime, the local controllers must consult the pre-computed sensitivity information in their shard to cheaply estimate the impact of their actions on the downstream coordinates before committing to a control policy . This ensures that combinations of local actions across multiple nodes cannot accumulate into a rights violation at a distant downstream target. The `canal_goldband_excursion_logic.aln` contract would

need to be updated to include clauses requiring the presence of these downstream corridor definitions and referencing a multi-node variant of the `safestep` rule.

The following table compares the standard and extended `safestep` enforcement mechanisms.

Aspect	Standard `safestep` (Local)	Extended `safestep` (Downstream-Aware)
Residual Scope	Local risk coordinates (r_x) within the node's immediate vicinity.	Aggregated risk coordinates (r_x) for the node and its downstream dependencies.
Key Calculation	$V_t^{local} = \sum_{i \in local} w_i r_{x_i}^2$	$V_t^{network} = V_t^{local} + \sum_{j \in downstream} W_j \cdot V_t^{dependency_j}$
Governance Metric	Localized Lyapunov residual.	Network-wide Lyapunov residual.
Enforcement Logic	Reject action if ($V_{t+1}^{local} > V_t^{local}$) AND a corridor is violated.	Reject action if ($V_{t+1}^{network} > V_t^{network}$) AND a local or downstream corridor is violated.
Required Shard Data	Local risk coordinates, local corridor bands.	Local risk coordinates, local corridor bands, **downstream dependency sensitivity indices**, downstream corridor bands.
Runtime Complexity	Lower; depends only on local telemetry.	Higher; requires lookup and aggregation of data from other shards (dependencies).

By implementing this extended, network-aware `safestep` contract, the ecosafety grammar provides a powerful tool for managing the emergent behaviors of interconnected systems. It moves beyond simple point-source protection to offer holistic governance that respects the hydraulic and legal integrity of the entire canal network, thereby lowering the risk-of-harm to third parties and downstream ecosystems.

Refugia Design and Cross-Domain Generalization Strategy

The ecosafety grammar, once formally specified for the Phoenix canals, must be sufficiently flexible to accommodate advanced functionalities like the creation of thermal and quality refugia, while also being structured in a way that facilitates generalization to other aquatic environments. A refugium is a localized area of improved habitat conditions, such as cooler water or higher dissolved oxygen, created by a Cyboquatic node to provide a sanctuary for sensitive species during extreme events like heatwaves . The safest implementation of this functionality is not as an exception to the core safety logic but as a special case of the same residual minimization problem. This approach

ensures that the creation of a refugium does not come at the cost of exporting ecological risk to other parts of the system, adhering to a fairness constraint built directly into the framework. The very structure of the `qpudatashard` and the modular nature of the `ecosafety-core` crate make this dual-purpose capability a natural outcome of the initial design.

Implementing a refugium involves designing nodes that can actively modulate local flow velocities, water depth, shading, and mixing to create pockets of tolerable conditions . For example, a node could increase local water depth in a short reach to create a thermally stable cool pocket, or it could mix cooler subsurface return flows with hotter surface waters to reduce peak temperatures . The activation of these features must be governed by the existing ecosafety grammar. The key is to treat the refugia itself as a special type of canal segment with its own, more stringent, set of corridors. Candidate refugia reaches would be identified using historical data and species distribution models, and encoded as special geostamped rows in the `qpudatashard` repository . These rows would contain species-specific corridors, defining the maximum tolerable temperatures and minimum DO levels for priority taxa groups (e.g., fish, macroinvertebrates) .

When a refugium is activated, the control logic operates within the existing `safestep` framework. The objective becomes an optimization problem: find a control pattern (e.g., valve settings, pump speeds) that successfully cools the designated refugia segment and/or raises its DO level, while ensuring that the total, network-wide Lyapunov residual (V_t) does not increase . This is achieved by adding upstream and downstream SAT and DO risk coordinates into the residual calculation. The fairness requirement—"no export of thermal or DO risk to non-refugia reaches"—becomes another explicit constraint in the optimization, forcing the controller to find a solution that improves local conditions without degrading conditions elsewhere in the network . This approach avoids the ad-hoc logic of "stealing safety" from one part of the system to benefit another; instead, it treats the entire network as a single, coupled system to be managed for non-increasing risk. The refugia design is therefore encoded as a special case of the same residual, with species-specific kernels and corridors for flagged reaches, and its activation is simply an application of the core `safestep` contract .

This deep integration with the core grammar is precisely what enables a smooth and effective cross-domain generalization strategy. The entire framework—from the normalization kernels to the residual calculation and enforcement contracts—is designed to be domain-agnostic. The mass-balance kernel, $M_x = (C_{in,x} - C_{out,x})Q\,dt$, and the risk normalization formula, $r_x = (x - x_{min})/(x_{max} - x_{min})$, are consistently applied across diverse contexts, whether for PFAS in canals, nutrients in rivers, or tray residuals in composting systems . The Phoenix canal system is treated as the canonical reference

instantiation, serving as the primary ground-truth environment for calibrating and validating the parameters of this universal grammar . The generalization process is systematic and repeatable:

1. **Identify a New Domain:** Select a new aquatic environment, such as a river, wetland, or reservoir.
2. **Define Domain-Specific Parameters:** Identify the key ecological stressors and sensitive receptors in the new domain. This might involve different parameters (e.g., sediment transport, pH, salinity) and different species.
3. **Calibrate Kernels and Corridors:** Conduct a local calibration campaign analogous to the one planned for the Phoenix canals. This involves collecting baseline data to empirically fit the normalization kernels (K_x) and establish the safe, gold, and hard corridor bands for the new domain's parameters .
4. **Create Specialized Shards:** Define new shard families or use flags within existing shards to encode domain-specific information, such as species-specific corridors for a particular river's endangered fish population or unique hydraulic footprint functions for a deltaic environment .
5. **Leverage Core Infrastructure:** Utilize the existing `ecosafety-core` crate, `qpudatashard` schemas, and ALN governance contracts. The implementation effort is focused almost entirely on the data layer—the calibration and schema definitions—not on inventing new safety primitives or rewriting core logic .

The following table illustrates the generalization pathway from the canonical Phoenix canal instantiation to a new domain.

Step	Action	Artifact(s) Created/Modified	Rationale
1. Reference Instantiation	Calibrate the ecosafety grammar on the Phoenix canal system.	`PhoenixNodePlacementShard`, `canal_goldband_excursion_logic.aln`, calibrated corridor bands, `RiskCoord/Residual` kernels.	Provides a fully tested, ground-truthed implementation of the universal grammar .
2. New Domain Identification	Select a new aquatic environment (e.g., Gila River reach, CAP-Canal lateral).	N/A	Establishes a new target for application and validation.
3. Parameter Mapping	Map the key environmental variables of the new domain to the existing risk coordinate framework.	New or updated shard columns (e.g., `r_Salinity`, `r_pH`).	Reuses the proven normalization and residual calculation machinery .
4. Local Calibration	Collect local baseline data and run pilot studies to empirically determine corridor bands and kernel parameters for the new domain.	New `qpudatashard` rows with local calibration data, new `EvidenceHex` proofs.	Ensures the universal grammar is correctly tuned to the local ecology, addressing uncertainty .
5. Schema Adaptation	Update shard schemas and ALN contracts to include the new domain's parameters and constraints.	New columns in `PhoenixNodePlacementShard` schema, updated `.aln` file.	Maintains consistency with the overall data architecture while adding domain-specific detail.
6. Deployment and Validation	Deploy nodes in the new domain, running under the newly configured ecosafety grammar. Validate performance against local monitoring data.	Operational nodes, telemetry shards, validation reports.	Confirms the effectiveness of the generalization and provides further data for refinement.

This structured approach ensures that the ecosafety grammar remains a living, evolving framework rather than a static, domain-specific tool. By treating the Phoenix canals as the definitive proof-of-concept, the project lowers the barrier to entry for deploying Cyboquatic technology in new environments. The heavy lifting of safety logic is done once, in the `ecosafety-core` crate and its associated contracts. Subsequent deployments are primarily data-driven exercises in calibration and adaptation, leveraging a robust and reusable software and governance infrastructure. This strategy maximizes eco-impact by rapidly deploying proven safety patterns while minimizing residual risk by grounding every new application in the empirical validation of the canonical reference case.

Actionable Implementation Roadmap and CI/CD Validation Rules

The successful realization of the ecosafety grammar for the Phoenix canal system requires a clear, phased implementation roadmap and a robust set of Continuous Integration/Continuous Deployment (CI/CD) validation rules. The roadmap prioritizes foundational work, such as data collection and crate development, before progressing to more complex tasks like digital twin integration and downstream impact modeling. The CI/CD pipeline serves as the automated enforcement arm of the governance framework, ensuring that every piece of code and data introduced into the system adheres strictly to the frozen ecosafety grammar and its associated ALN contracts. This final section synthesizes the preceding analyses into a concrete plan of action, outlining key milestones and the automated checks that will safeguard the integrity of the deployment.

The implementation can be broken down into four sequential phases, each building upon the last.

Phase 1: Foundational Data Collection and Crate Development (Months 1-4) The immediate priority is to gather the empirical data required to populate the `qpudatashard` and calibrate the normalization kernels. Concurrently, the core `ecosafety-core` Rust crate must be developed.

- **Action Items:**

```
1.  <strong>Baseline Data Acquisition:</strong> Initiate the collection of
2.  <strong>Crate Specification Finalization:</strong> Complete the specif
3.  <strong>Initial Crate Implementation:</strong> Begin coding the `ecosa
4.  <strong>Draft Initial ALN Schema:</strong> Create a preliminary versio
```

- **Deliverables:** A functional `ecosafety-core` crate with unit tests; a draft ALN specification; a preliminary `NodePlacement` shard schema; and the first tranche of baseline environmental data.

Phase 2: Calibration, Schema Finalization, and Static Analysis (Months 5-8) With the foundational data in hand, the focus shifts to empirically calibrating the corridor bands and refining the implementation artifacts.

- **Action Items:**

```
1.  <strong>Corridor Band Calibration:</strong> Analyze the baseline data
2.  <strong>Finalize Shard Schema and ALN:</strong> Populate the `PhoenixN
3.  <strong>Develop Validation Scripts:</strong> Write scripts to programm
```

- **Deliverables:** Finalized `PhoenixNodePlacementShard` schema; a complete and validated `canal_goldband_excursion_logic.aln` file; calibrated corridor band definitions stored as a separate, immutable shard; and the initial validation scripts.

Phase 3: Dynamic Enforcement and Downstream Logic Implementation (Months 9-12) This phase introduces the runtime enforcement logic and extends the framework to handle downstream impacts.

- **Action Items:**

```
1.  <strong>Implement Runtime Validator:</strong> Develop the service resp
2.  <strong>Extend Shard for Adjacency:</strong> Augment the `NodePlacemen
3.  <strong>Implement Downstream `safestep`:</strong> Modify the `safestep
4.  <strong>Run Twin Stress Tests:</strong> Execute simulations in the can
```

- **Deliverables:** A fully operational runtime validation service; an extended `NodePlacement` shard schema with adjacency data; an updated `ecosafety-core` crate supporting network-wide residuals; and a report verifying the correctness of the downstream impact mitigation logic.

Phase 4: Refugia Logic, Generalization Patterns, and Full Automation (Months 13-18) The final phase focuses on implementing advanced features and establishing the patterns for future generalization.

- **Action Items:**

```
1.  <strong>Implement Refugia Logic:</strong> Extend the `RiskCoord` and `
2.  <strong>Develop Generalization Templates:</strong> Create templates an
3.  <strong>Build CI/CD Pipeline:</strong> Integrate all validation script
```

- **Deliverables:** A version of the `ecosafety-core` crate supporting refugia; a set of generalization templates for new domains; and a fully automated CI/CD pipeline with comprehensive validation.

To enforce compliance throughout this process, the following CI/CD validation rules must be implemented in the pipeline:

Rule Category	Specific Check	Failure Consequence
Contract Compliance	Ensure every `qpudatashard` written to the deployment lane conforms to the `canal_goldband_excursion_logic.aln` schema. Verify all required columns (`r_xmin`, `r_xmax`, `evidencehex`, etc.) are present and correctly typed.	Block the merge/deployment. Fail the CI job.
Data Integrity	Validate that for every corridor column pair (`r_xmin`, `r_xmax`), `r_xmin` is less than or equal to `r_xmax`.	Block the merge/deployment. Fail the CI job.
Mathematical Consistency	Run unit tests on the `ecosafety-core` crate to verify that `calculate_residual` produces expected outputs for known inputs and that `safestep_satisfied` implements the $V_{t+1} \leq V_t$ logic correctly.	Block the merge/deployment if test coverage drops or new tests fail.
Runtime Invariant Checks	Before a node's control policy is committed, the runtime validator must confirm that the proposed action satisfies `safestep` (i.e., does not increase the network-wide V_t if a corridor is violated).	Reject the control command. Log the violation. Escalate `deploydecision`.
Provenance Verification	Every shard row submitted for deployment must have a valid `evidencehex` and `signinghex` that can be cryptographically verified against trusted data sources and the deploying entity's DID.	Block the merge/deployment. Fail the CI job.

By following this roadmap and enforcing these rigorous validation rules, the project can systematically transition from a theoretical framework to a production-grade, safe, and scalable system for managing Cyboquatic deployments in the Phoenix canals. This canonical instantiation will not only solve the immediate challenges of canal management but will also serve as the definitive blueprint for responsibly deploying autonomous ecological technologies in any aquatic environment worldwide.

Reference

1. Managing aquifer recharge: a showcase for resilience and ... https://unesdoc.unesco.org/ark:/48223/pf0000379962
2. Harmful Algal Blooms in Eutrophic Marine Environments - MDPI https://www.mdpi.com/2073-4441/16/17/2525
3. Mapping Harmful Algae Blooms: The Potential of Hyperspectral ... https://www.researchgate.net/publication/388947090_Mapping_Harmful_Algae_Blooms_The_Potential_of_Hyperspectral_Imaging_Technologies
4. Cyanobacterial Harmful Algal Blooms - Springer Nature https://link.springer.com/content/pdf/10.1007/978-0-387-75865-7.pdf

5. The interplay of carbon and nitrogen cycling driven by watershed ... https://www.frontiersin.org/journals/microbiology/articles/10.3389/fmicb.2025.1696238/full
6. Machine Learning Based on Cloud Solutions - Academia.edu https://www.academia.edu/44604512/Machine_Learning_Based_on_Cloud_Solutions
7. Sensors, Volume 25, Issue 23 (December-1 2025) – 302 articles https://www.mdpi.com/1424-8220/25/23
8. THE IMPACTS OF CLIMATE CHANGE ON HUMAN HEALTH IN THE ... https://www.academia.edu/31063713/THE_IMPACTS_OF_CLIMATE_CHANGE_ON_HUMAN_HEALTH_IN_THE_UNITED_STATES_A_Scientific_Assessment
9. Sensors, Volume 26, Issue 2 (January-2 2026) – 402 articles - MDPI https://www.mdpi.com/1424-8220/26/2
10. Smart intercropping system to detect leaf disease using ... - Frontiers https://www.frontiersin.org/journals/plant-science/articles/10.3389/fpls.2025.1662251/full
11. Artificial intelligence driven protein design and sustainable ... - PMC https://pmc.ncbi.nlm.nih.gov/articles/PMC12887271/
12. protecting water quality for the health of people and the environment https://unesdoc.unesco.org/ark:/48223/pf0000393749
13. Water, Volume 12, Issue 10 (October 2020) – 301 articles https://www.mdpi.com/2073-4441/12/10
14. Review of the natural conditions and anthropogenic threats to the ... https://www.researchgate.net/publication/305423345_Review_of_the_natural_conditions_and_anthropogenic_threats_to_the_Ethiopian_Rift_Valley_rivers_and_lakes
15. Water, Volume 12, Issue 6 (June 2020) – 328 articles https://www.mdpi.com/2073-4441/12/6
16. [PDF] Diffuse Pollution, Degraded Waters: Emerging Policy Solutions https://www.oecd.org/content/dam/oecd/en/publications/reports/2017/03/diffuse-pollution-degraded-waters_g1g75088/9789264269064-en.pdf
17. Our Family History - Parkers Etc | PDF | Ireland - Scribd https://www.scribd.com/document/160495598/Our-Family-History-Parkers-Etc
18. [PDF] Protocols for Cyanobacteria Sampling and Detection of Cyanotoxin https://www.researchgate.net/profile/Valentina-Messineo/publication/376604780_Extraction_and_Quantification_of_BMAA_from_Fish_Tissue/links/660d475bf5a5de0a9ff70d75/Extraction-and-Quantification-of-BMAA-from-Fish-Tissue.pdf

19. [PDF] Modelling networks of causal relationships in stress ecology ... - HAL https://hal.science/hal-01867044/file/abstracts_meeting_35_1.pdf
20. Modem Trends in Applied Aquatic Ecology - Springer https://link.springer.com/content/pdf/10.1007/978-1-4615-0221-0.pdf
21. SICB 2014 Annual Meeting Abstracts - jstor https://www.jstor.org/stable/26388899
22. Dynamic domain-based collision avoidance system for autonomous ... https://www.sciencedirect.com/science/article/abs/pii/S0957417424016725
23. Comprehensive Investigation of Unmanned Aerial Vehicles (UAVs) https://pmc.ncbi.nlm.nih.gov/articles/PMC11125140/
24. Sustainability in Food and Water - Springer Nature https://link.springer.com/content/pdf/10.1007/978-90-481-9914-3.pdf
25. Flow matching meets biology and life science: a survey - Nature https://www.nature.com/articles/s44387-025-00066-y
26. [PDF] Robust trajectory planning algorithms for robots with parametric ... https://theses.hal.science/tel-04193608/file/BRAULT_Pascal.pdf
27. Appl. Sci., Volume 14, Issue 6 (March-2 2024) – 447 articles - MDPI https://www.mdpi.com/2076-3417/14/6
28. Proceedings of the 4th International Conference on Electronic ... https://link.springer.com/content/pdf/10.1007/978-981-96-0644-3.pdf
29. Spatio-temporal assessment of chlorine residuals in the water ... https://unesdoc.unesco.org/ark:/48223/pf0000393743
30. Proceedings of the 7th International Symposium on Water Resource ... https://link.springer.com/content/pdf/10.1007/978-3-031-88850-2.pdf
31. multi-page.txt - Documents & Reports - World Bank https://documents1.worldbank.org/curated/en/193911468128967270/txt/multi-page.txt
32. Integrative Zoology: January 2022 Issue | PDF | Bat - Scribd https://www.scribd.com/document/735150801/Rarmirez-francel-Et-Al-2022-Bats-and-Their-Integrative-Zoology-17-1-1
33. Expert and intelligent systems for assessment and mitigation of ... https://www.sciencedirect.com/science/article/pii/S2590123025032037
34. Secure and Intelligent Low-Altitude Infrastructures: Synergistic ... https://pmc.ncbi.nlm.nih.gov/articles/PMC12609838/
35. From Concrete to Code: A Survey of AI-Driven Transportation ... - MDPI https://www.mdpi.com/1424-8220/26/7/2219
36. Sustainability, Volume 17, Issue 4 (February-2 2025) – 426 articles https://www.mdpi.com/2071-1050/17/4

37. 2021 AAPM&R Annual Assembly Abstracts - Wiley Online Library https://onlinelibrary.wiley.com/doi/full/10.1002/pmrj.12735
38. Session MoPL 210 Monday, May 20, 2019, 09:15–10:15 Plenary ... https://ewh.ieee.org/soc/ras/conf/fullysponsored/icra/ICRA2019/www.icra2019.org/sites/icra2019/files/2019-05/ICRA2019_Program_Digest.pdf
39. MIT Manipal Academic Handbook 2025-26 | PDF - Scribd https://www.scribd.com/document/892926640/Academic-Handbook-2025-26-MIT-Manipal-2-250711-223754-1
40. SCIENTIFIC PROGRAM & ABSTRACTS - Springer Nature https://link.springer.com/content/pdf/10.1007/s43032-025-01837-3.pdf
41. (PDF) Donegal County Donegal is a county in Ireland - Academia.edu https://www.academia.edu/4008820/Donegal_County_Donegal_is_a_county_in_Ireland
42. Toxic Microcystis reduces tolerance of Daphnia to increased ... https://www.researchgate.net/publication/342874598_Toxic_Microcystis_reduces_tolerance_of_Daphnia_to_increased_chloride_and_low_chloride_alleviates_the_harm_of_toxic_Microcystis_to_Daphnia
43. 2023 Annual Conference and Exposition (ACE23) https://events.tpni.com/gcmmaintenance/awwa/html_files/30000213/onlineagenda/index.htm
44. [PDF] Intel International Science and Engineering Fair 2018 Program May 13 https://sspcdn.blob.core.windows.net/files/Documents/SEP/ISEF/2018/Attendees/Programs/Book.pdf
45. Issue 1 - Volume 1141 - Journal of Physics: Conference Series https://iopscience.iop.org/issue/1742-6596/1141/1
46. Mathematics, Volume 14, Issue 1 (January-1 2026) – 203 articles https://www.mdpi.com/2227-7390/14/1
47. Forward-Looking Roadmaps for Long-Term Continuous Water ... https://pubs.acs.org/doi/10.1021/acs.est.1c07857
48. [PDF] Study and development of fluidic micro-oscillators for the cooling of ... https://laas.hal.science/tel-04055838v1/file/SALIBA%20Georges.pdf
49. [PDF] The-Environmental-Dynamic-System.pdf - ResearchGate https://www.researchgate.net/profile/Lance-Leslie/publication/302388514_The_Environmental_Dynamic_System/links/58e68896a6fdcc1fda2b0611/The-Environmental-Dynamic-System.pdf
50. Latest articles - MDPI https://www.mdpi.com/latest_articles
51. [PDF] Environmental Modelling, Software and Decision Support, Volume 3 https://www.researchgate.net/profile/Nigel_Quinn/publication/326145963_Integrated_Modelling_Frameworks_for_Environmental_Assessment_and_

Decision_Support/links/5b3b00fca6fdcc8506ea6054/Integrated-Modelling-Frameworks-for-Environmental-Assessment-and-Decision-Support.pdf

52. climate risks, saltwater intrusion, and biogeochemical chain reactions https://link.springer.com/article/10.1007/s10533-025-01219-6
53. [PDF] The Arizona Wildlife Conservation Strategy - AWS https://azgfd-wdw.s3.amazonaws.com/awcs-2022/09-24_minor-revison_awcs_final_approved_11-22.docx.pdf
54. [PDF] Study and development of fluidic micro-oscillators for cooling ... https://theses.hal.science/tel-03814670/file/2022TOU30097b.pdf
55. Energies, Volume 14, Issue 6 (March-2 2021) – 279 articles - MDPI https://www.mdpi.com/1996-1073/14/6
56. [PDF] G uide for - Amazon S3 https://s3.amazonaws.com/NARAprodstorage/lz/presidential-libraries/clinton/7763285/42-t-7763285-20110255S-033-005-2017.pdf
57. Landscape and Urban Planning - ScienceDirect.com https://www.sciencedirect.com/science/article/abs/pii/S0169204600000621
58. Integrating ecological importance and risk for restoration zoning and ... https://www.nature.com/articles/s41598-025-14203-9
59. (PDF) Flash Flooding in Arid/Semiarid Regions - ResearchGate https://www.researchgate.net/publication/320392145_Flash_Flooding_in_AridSemiarid_Regions_Dissecting_the_Hydrometeorology_and_Hydrology_of_the_19_August_2014_Storm_and_Flood_Hydroclimatology_in_Arizona
60. Mapping Multi-Temporal Heat Risks Within the Local Climate Zone ... https://www.mdpi.com/2075-5309/15/19/3619
61. multi-page.txt - Documents & Reports https://documents1.worldbank.org/curated/en/580621468746382641/txt/multi-page.txt
62. Sensors, Volume 26, Issue 7 (April-1 2026) – 273 articles https://www.mdpi.com/1424-8220/26/7
63. [PDF] impact and advances of automatic control in latinamerica https://www.researchgate.net/profile/Oscar-Camacho-2/publication/313892172_IMPACT_AND_ADVANCES_OF_AUTOMATIC_CONTROL_IN_LATINAMERICA/links/58ae174fa6fdcc6f03f00993/IMPACT-AND-ADVANCES-OF-AUTOMATIC-CONTROL-IN-LATINAMERICA.pdf
64. Computer Science - arXiv https://www.arxiv.org/list/cs/new?skip=875&show=1000
65. Impacts of Freshwater Management Activities on Eastern Oyster ... https://www.researchgate.net/publication/263068291_Impacts_of_Freshwater_Management_Activities_on_Eastern_Oyster_Crass

ostrea_virginica_Density_and_Recruitment_Recovery_and_Long-Term_Stability_in_Seven_Florida_Estuaries

66. Water, Volume 12, Issue 4 (April 2020) – 298 articles https://www.mdpi.com/2073-4441/12/4
67. EIM Platform User's Guide - Release 530 | PDF - Scribd https://www.scribd.com/document/868436443/Pmt-Hps-EIM-Hardware-and-Common-Platform-Users-Guide-EPDOC-X406-en-530A
68. Wireless Sensor Networks - Springer Nature https://link.springer.com/content/pdf/10.1007/978-981-96-2186-6.pdf
69. J. Mar. Sci. Eng., Volume 13, Issue 6 (June 2025) – 194 articles - MDPI https://www.mdpi.com/2077-1312/13/6
70. [XLS] China https://www.nsfc.gov.cn/Portals/0/fj/fj20230220_01.xlsx
71. Biosensors for Environmental Analysis and Monitoring https://link.springer.com/content/pdf/10.1007/978-3-032-09430-8.pdf
72. [PDF] Nanorods and Nanocomposites - ResearchGate https://www.researchgate.net/profile/Abdulkareem-Alsultan/publication/340397920_Nanorods_and_Nanocomposites/links/5e86f88292851c2f5277b590/Nanorods-and-Nanocomposites.pdf
73. (PDF) Discontinuous rock mechanics; lecture note - Academia.edu https://www.academia.edu/45223201/Discontinuous_rock_mechanics_lecture_note
74. The American Engineers that Built the Panama Canal - ResearchGate https://www.researchgate.net/publication/269204107_The_American_Engineers_that_Built_the_Panama_Canal
75. 333333 23135851162 the 13151942776 of 12997637966 https://www.cs.princeton.edu/courses/archive/spring18/cos226/assignments/autocomplete/testing/words-333333.txt
76. Experimental analysis of time resolved three-dimensional velocity ... https://www.researchgate.net/publication/400247394_Experimental_analysis_of_time_resolved_three-dimensional_velocity_and_vorticity_fields_behind_single_rising_bubbles_using_Lagrangian_particle_tracking_velocimetry
77. Appl. Sci., Volume 16, Issue 6 (March-2 2026) – 484 articles - MDPI https://www.mdpi.com/2076-3417/16/6