

# lintrans

by D. Dyson

Centre Name: The Duston School  
Centre Number: 123456  
Candidate Number: 123456

# Contents

<b>1</b>	<b>Analysis</b>	<b>1</b>
1.1	Computational Approach . . . . .	1
1.2	Stakeholders . . . . .	2
1.3	Research on existing solutions . . . . .	2
1.3.1	MIT ‘Matrix Vector’ Mathlet . . . . .	2
1.3.2	Linear Transformation Visualizer . . . . .	3
1.3.3	Desmos app . . . . .	4
1.3.4	Visualizing Linear Transformations . . . . .	4
1.4	Essential features . . . . .	5
1.5	Limitations . . . . .	5
1.6	Hardware and software requirements . . . . .	6
1.6.1	Hardware . . . . .	6
1.6.2	Software . . . . .	6
1.7	Success criteria . . . . .	7
<b>2</b>	<b>Design</b>	<b>9</b>
2.1	Problem decomposition . . . . .	9
2.2	Structure of the solution . . . . .	9
2.2.1	The main project . . . . .	9
2.2.2	The guisubpackages . . . . .	11
2.3	Algorithm design . . . . .	11
2.4	Usability features . . . . .	11
2.5	Variables and validation . . . . .	12
2.6	Iterative test data . . . . .	13
2.7	Post-development test data . . . . .	14
<b>3</b>	<b>Development</b>	<b>15</b>
3.1	Matrices backend . . . . .	15
3.1.1	MatrixWrapperclass . . . . .	15
3.1.2	Rudimentary parsing and evaluating . . . . .	17
3.1.3	Simple matrix expression validation . . . . .	22
3.1.4	Parsing matrix expressions . . . . .	24
3.2	Initial GUI . . . . .	27
3.2.1	First basic GUI . . . . .	27
3.2.2	Numerical definition dialog . . . . .	29
3.2.3	More definition dialogs . . . . .	32
3.3	Visualizing matrices . . . . .	35
3.3.1	Asking strangers on the internet for help . . . . .	35
3.3.2	Creating the plots package . . . . .	36
3.3.3	Implementing basis vectors . . . . .	37
3.3.4	Drawing the transformed grid . . . . .	39
3.3.5	Implementing animation . . . . .	42
3.3.6	Preserving determinants . . . . .	43
3.4	Improving the GUI . . . . .	45
3.4.1	Fixing rendering . . . . .	45
3.4.2	Adding vector arrowheads . . . . .	47
3.4.3	Implementing zoom . . . . .	48
3.4.4	Animation blocks zooming . . . . .	51
3.4.5	Rank 1 transformations . . . . .	51
	<b>References</b>	<b>53</b>

<b>A</b>	<b>Project code</b>	<b>54</b>
A.1	__main__.py . . . . .	54
A.2	__init__.py . . . . .	55
A.3	matrices/__init__.py . . . . .	55
A.4	matrices/parse.py . . . . .	55
A.5	matrices/wrapper.py . . . . .	61
A.6	gui/__init__.py . . . . .	65
A.7	gui/main_window.py . . . . .	65
A.8	gui/validate.py . . . . .	73
A.9	gui/settings.py . . . . .	73
A.10	gui/plots/widgets.py . . . . .	74
A.11	gui/plots/__init__.py . . . . .	76
A.12	gui/plots/classes.py . . . . .	77
A.13	gui/dialogs/__init__.py . . . . .	84
A.14	gui/dialogs/define_new_matrix.py . . . . .	85
A.15	gui/dialogs/settings.py . . . . .	90
A.16	gui/dialogs/misc.py . . . . .	94
A.17	typing/__init__.py . . . . .	95
<b>B</b>	<b>Testing code</b>	<b>97</b>
B.1	matrices/test_rotation_matrices.py . . . . .	97
B.2	matrices/test_parse_and_validate_expression.py . . . . .	98
B.3	matrices/matrix_wrapper/test_evaluate_expression.py . . . . .	100
B.4	matrices/matrix_wrapper/conftest.py . . . . .	104
B.5	matrices/matrix_wrapper/test_misc.py . . . . .	105
B.6	matrices/matrix_wrapper/test_setitem_and_getitem.py . . . . .	105
B.7	gui/test_dialog_utility_functions.py . . . . .	108

# 1 Analysis

One of the topics in the A Level Further Maths course is linear transformations, as represented by matrices. This is a topic all about how vectors move and get transformed in the plane. It's a topic that lends itself exceedingly well to visualization, but students often find it hard to visualize this themselves, and there is a considerable lack of good tools to provide visual intuition on the subject. There is the YouTube series *Essence of Linear Algebra* by 3blue1brown[6], which is excellent, but I couldn't find any good interactive visualizations.

My solution is to develop a desktop application that will allow the user to define  $2 \times 2$  matrices and view these matrices and compositions thereof as linear transformations of a 2D plane. This will give students a way to get to grips with linear transformations in a more hands-on way, and will give teachers the ability to easily and visually show concepts like the determinant and invariant lines.

## 1.1 Computational Approach

This solution is particularly well suited to a computational approach since it is entirely focussed on visualizing transformations, which require complex mathematics to properly display. It will also have lots of settings to allow the user to configure aspects of the visualization. As previously mentioned, visualizing transformations in one's own head is difficult, so a piece of software to do it would be very valuable to teachers and learners, but current solutions are considerably lacking.

My solution will make use of abstraction by allowing the user to define a set of matrices which they can use in expressions. This allows them to use a matrix multiple times and they don't have to keep track of any of the numbers. All the actual processing and mathematics happens behind the scenes and the user never has to worry about it - they just compose their defined matrices into transformations. This abstraction allows the user to focus on exploring the transformations themselves without having to do any actual computations. This will make learning the subject much easier, as they will be able to gain a visual intuition for linear transformations without worrying about computation until after they've built up that intuition.

I will also employ decomposition and modularization by breaking the project down into many smaller parts, such as one module to keep track of defined matrices, one module to validate and parse matrix expressions, one module for the main GUI, as well as sub-modules for the widgets and dialog boxes, etc. This decomposition allows for simpler project design, easier code maintenance (since module coupling is kept to a minimum, so bugs are isolated in their modules), inheritance of classes to reduce code repetition, and unit testing to inform development. I also intend this unit testing to be automated using GitHub Actions.

Selection will also be used widely in the application. The GUI will provide many settings for visualization, and these settings will need to be checked when rendering the transformation. For example, the user will have the option to render the determinant, so I will need to check this setting on every render cycle and only render the determinant parallelogram if the user has enabled that option. The app will have many options for visualization, which will be useful in learning, but if all these options were being rendered at the same time, then there would be too much information for the user to properly process, so I will let the user configure these display options to their liking and only render the things they want to be rendered.

Validation will also be prevalent because the matrix expressions will need to follow a strict format, which will be validated. The buttons to render and animate the matrix will only be clickable when the given expression is valid, so I will need to check this and update the buttons every time the text in the text box is changed. I will also need to parse matrix expressions so that I can evaluate them properly. All this validation ensures that crashes due to malformed input are practically impossible, and makes the user's life easier since they don't need to worry about if their input is in the right format - the app will tell them.

I will also make use of iteration, primarily in animation. I will have to re-calculate positions and

values to render everything for every frame of the animation and this will likely be done with a simple `for` loop. A `for` loop will allow me to just loop over every frame and use the counter variable as a way to measure how far through the animation we are on each frame. This is preferable to a `while` loop, since that would require me to keep track of which frame we're on with a separate variable.

Finally, the core of the application is visualization, so that will definitely be used a lot. I will have to calculate positions of points and lines based on given matrices, and when animating, I will also have to calculate these matrices based on the current frame. Then I will have to use the rendering capabilities of the GUI framework that I choose to render these calculated points and lines onto a widget, which will form the viewport of the main GUI. I may also have to convert between coordinate systems. I will have the origin in the middle with positive  $x$  going to the right and positive  $y$  going up, but I may need to convert that to standard computer graphics coordinates with the origin in the top left, positive  $x$  going to the right, and positive  $y$  going down. This visualization of linear transformations is the core component of the app and is the primary feature, so it is incredibly important.

## 1.2 Stakeholders

Stakeholders for my app include A Level Further Maths students and teachers, who learn and teach linear transformations respectively. They will be able to provide useful input as to what they would like to see in the app, and they can provide feedback on what they like and what I can add or improve. I already know from experience that linear transformations are tricky to visualize and a computer-based visualization would be useful. My stakeholders agreed with this. Many teachers said that a desktop app that could render and animate linear transformations would be useful in a classroom environment and students said that it would be helpful to have something that they could play around with at home and use to get to grips with matrices and linear transformations.

Some teachers also suggested that it would be useful to have an option to save and load sets of matrices. This would allow them to have a single save file containing some matrices, and then just load this file to use for demonstrations in the classroom. This would probably be quite easy to implement. I could just wrap all the relevant information into one object and use Python's `pickle` module to save the binary data to a file, and then load this data back into the app in a similar way.

My stakeholders agreed that being able to see incremental animation - where, for example, we apply matrix **A** to the current scene, pause, and then apply matrix **B** - would be beneficial. This would be a good demonstration of matrix multiplication being non-commutative. **AB** is not always equal to **BA**. Being able to see this in terms of animating linear transformations would be good for learning.

They also agreed that a tutorial on using the software would be useful, so I plan to implement this through an online written tutorial hosted with GitHub Pages, and perhaps a video tutorial as well. This would make the app much easier to use for people who have never seen it before. It wouldn't be a lesson on the maths itself, just a guide on how to use the software.

## 1.3 Research on existing solutions

There are actually quite a few web apps designed to help visualize 2D linear transformations but many of them are hard to use and lacking many features.

### 1.3.1 MIT 'Matrix Vector' Mathlet

Arguably the best app that I found was an MIT 'Mathlet' - a simple web app designed to help visualize a maths concept. This one is called 'Matrix Vector'[7] and allows the user to drag an input vector around the plane and see the corresponding output vector, transformed by a matrix that the user can define, although this definition is finicky since it involves sliders rather than keyboard input.

This app fails in two crucial ways in my opinion. It doesn't show the basis vectors or let the user drag them around, and the user can only define and therefore visualize a single matrix at once. This second problem was common among every solution I found, so I won't mention it again, but it is a big issue in my opinion and my app will allow for multiple matrices. I like the idea of having a draggable input vector and rendering its output, so I will probably have this feature in my app, but I also want the ability to define multiple matrices and be able to drag the basis vectors to visually define a matrix. Being able to drag the basis vectors will help build intuition, so I think this would greatly benefit the app.




Figure 1.1: The MIT 'Matrix Vector' Mathlet

However, in the comments on this Mathlet, a user called 'David S. Bruce' suggested that the Mathlet should display the basis vectors, to which a user called 'hrm' (who I assume to be the 'H. Miller' to whom the copyright of the whole website is accredited) replied saying that this Mathlet is primarily focussed on eigenvectors, that it is perhaps badly named, and that displaying the basis vectors 'would make a good focus for a second Mathlet about  $2 \times 2$  matrices'. This Mathlet does not exist. But I do like the idea of showing the eigenvectors and eigenlines, so I will definitely have that in my app. Showing the invariant lines or lack thereof will help with learning, since these are often hard to visualize.

### 1.3.2 Linear Transformation Visualizer




Figure 1.2: 'Linear Transformation Visualizer' halfway through an animation

Another web app that I found was one simply called 'Linear Transformation Visualizer' by Shad Sharma[20]. This one was similarly inspired by 3blue1brown's YouTube series. This app has the ability to render input and output vectors and eigenlines, but it can also render the determinant parallelogram; it allows the user to drag the basis vectors; and it has the option to snap vectors to the background grid, which is quite useful. It also implements a simple form of animation where the tips of the vectors move in straight lines from where they start to where they end, and the animation is controlled by dragging a slider labelled  $t$ . This isn't particularly intuitive.

I really like the vectors snapping to the grid, the input and output vectors, and rendering the determinant. This app also renders positive and negative determinants in different colours, which is really nice - I intend to use that idea in my own app, since it helps create understanding about negative determinants in terms of orientation changes. However, I think that the animation system here is flawed and not very easy to use. My animation will likely be a button, which just triggers an animation, rather than a slider. I also don't like the way vector dragging is handled. If you click anywhere on the grid, then the closest vector target (the final position of the target's associated vector) snaps to that location. I think it would be more intuitive to have to drag the vector from its current location to where you want it. This was also a problem with the MIT Mathlet.

### 1.3.3 Desmos app

One of the solutions I found was a Desmos app[5], which was quite hard to use and arguably over-complicated. Desmos is not designed for this kind of thing - it's designed to graph pure mathematical functions - and it shows here. However, this app brings some really interesting ideas to the table, mainly functions. This app allows you to define custom functions and view them before and after the transformation. This is achieved by treating the functions parametrically as the set of points  $(t, f(t))$  and then transforming each coordinate by the given matrix to get a new coordinate.



Figure 1.3: The Desmos app halfway through an animation, rendering  $f(x) = \frac{\sin^2 x}{x}$  in orange

Desmos does this for every point and then renders the resulting transformed function parametrically. This is a really interesting technique and idea, but I'm not going to use it in my app. I don't think arbitrary functions fit with the linearity of the whole app, and I don't think it's necessary. It's just overcomplicating things, and rendering it on a widget would be tricky, because I'd have to render every point myself, possibly using something like OpenGL. It's just not worth implementing.

Additionally, this Desmos app makes things quite hard to see. It's hard to tell where any of the vectors are - they just get lost in the sea of grid lines. This image also hides some of the extra information. For instance, this image doesn't show the original function  $f(x) = \frac{\sin^2 x}{x}$ , only the transformed version. This app easily gets quite cluttered. I will give my vectors arrowheads to make them easily identifiable amongst the grid lines.

### 1.3.4 Visualizing Linear Transformations



Figure 1.4: The GeoGebra applet rendering its default matrix

The last solution that I want to talk about is a GeoGebra applet simply titled 'Visualizing Linear Transformations'[9]. This applet has input and output vectors, original and transformed grid lines, a unit circle, and the letter N. It allows the user to define a matrix as 4 numbers and view the aforementioned N (which the user can translate to anywhere on the grid), the unit circle, the input/output vectors, and the grid lines. It also has the input vector snapping to integer coordinates, but that's a standard part of GeoGebra.

I've already talked about most of these features but the thing I wanted to talk about here is the N. I don't particularly want the letter N to be a prominent part of my own app, but I really like the idea of being able to define a custom polygon and see how that polygon gets transformed by a given transformation. I think that would really help with building intuition and it shouldn't be too hard to implement.

## 1.4 Essential features

The primary aim of this application is to visualize linear transformations, so this will obviously be the centre of the app and an essential feature. I will have a widget which can render a background grid and a second version of the grid, transformed according to a user-defined matrix expression. This is necessary because it is the entire purpose of the app. It's designed to visualize linear transformations and would be completely useless without this visual component. I will give the user the ability to render a custom matrix expression containing matrices they have previously defined, as well as reset the canvas to the default identity matrix transformation. This will obviously require an input box to enter the expression, a render button, a reset button, and various dialog boxes to define matrices in different ways. I want the user to be able to define a matrix as a set of 4 numbers, and by dragging the basis vectors  $i$  and  $j$ . These dialogs will allow the user to define new matrices to be used in expressions, and having multiple ways to do it will make it easier, and will aid learning.

Another essential feature is animation. I want the user to be able to smoothly animate between matrices. I see two options for how this could work. If  $\mathbf{C}$  is the matrix for the currently displayed transformation, and  $\mathbf{T}$  is the matrix for the target transformation, then we could either animate from  $\mathbf{C}$  to  $\mathbf{T}$  or we could animate from  $\mathbf{C}$  to  $\mathbf{TC}$ . I would probably call these transitional and applicative animation respectively. Perhaps I'll give the user the option to choose which animation method they want to use. Either way, animation is used in most of the alternative solutions that I found, and it's a great way to build intuition, by allowing students to watch the transformation happen in real time. Compared to simply rendering the transformations, animating them would profoundly benefit learning, and since that's the main aim of the project, I think animation is a necessary part of the app.

Something that I thought was a big problem in every alternative solution I found was the fact that the user could only visualize a single matrix at once. I see this as a fatal flaw and I will allow the user to define 25 different matrices (all capital letters except  $\mathbf{I}$  for the identity matrix) and use all of them in expressions. This will allow teachers to define multiple matrices and then just change the expression to demonstrate different concepts rather than redefine a new transformation every time. It will also make things easier for students as it will allow them to visualize compositions of different matrix transformations without having to do any computations themselves.

Additionally, being able to show information on the currently displayed matrix is an essential tool for learning. Rendering things like the determinant parallelogram and the invariant lines of the transformation will greatly assist with learning and building understanding, so I think that having the option to render these attributes of the currently displayed transformation is necessary for success.

## 1.5 Limitations

The main limitation in this app is likely to be drawing grid lines. Most transformations will be fine but in some cases, the app will be required to draw potentially thousands of grid lines on the canvas and this will probably cause noticeable lag, especially in the animations. I will have to artificially limit the number of grid lines that can be drawn on the screen. This won't look fantastic, because it means that the grid lines will only extend a certain distance from the origin, but it's an inherent limitation of computers. Perhaps if I was using a faster, compiled language like C++ rather than Python, this processing would happen faster and I could render more grid lines, but it's impossible to render all the grid lines and any implementation of this idea must limit them for performance.

An interesting limitation is that I don't think I'll implement panning. I suspect that I'll have to convert between coordinate systems and having the origin in the centre of the canvas will probably make the code much simpler. Also, linear transformations always leave the origin fixed, so always having it in the centre of the canvas seems thematically appropriate. Panning is certainly an option - the Desmos solution in §1.3.3 and GeoGebra solution in §1.3.4 both allow panning as a default part of Desmos and GeoGebra respectively, for example - but I don't think I'll implement it myself. I just don't think it's worth it.



I'm also not going to do any work with 3D linear transformations. 3D transformations are often harder to visualize and thus it would make sense to target them in an app like this, designed to help with learning and intuition, but 3D transformations are also harder to code. I would have to use a full graphics package rather than a simple widget, and I think it would be too much work for this project and I wouldn't be able to do it in the time frame. It's definitely a good idea, but I'm currently incapable of creating an app like that.

There are other limitations inherent to matrices. For instance, it's impossible to take an inverse of a singular matrix. There's nothing I can do about that without rewriting most of mathematics. Matrices can also only represent linear transformations. There's definitely a market for an app that could render any arbitrary transformation from  $\mathbb{R}^2 \rightarrow \mathbb{R}^2$  - I know I'd want an app like that - but matrices can only represent linear transformations, so those are the only kind of transformations that I'll be looking at with this project.

## 1.6 Hardware and software requirements

### 1.6.1 Hardware

Hardware requirements for the project are the same between the release and development environments and they're quite simple. I expect the app to require a processor with at least 1 GHz clock speed, \$BINARY\_SIZE free disk space, and about 1 GB of available RAM. The processor and RAM requirements are needed by the Python runtime and mainly by Qt5 - the GUI library I'll be using. The \$BINARY\_SIZE disk space is just for the executable binary that I'll compile for the public release. The code itself is less than 1 MB, but the compiled binary has to package all the dependencies and the entire CPython runtime to allow it to run on systems that don't have that, so the file size is much bigger.

I will also require that the user has a monitor that is at least  $1920 \times 1080$  pixels in resolution. This isn't necessarily required, because the app will likely run in a smaller window, but a HD monitor is highly recommended. This allows the user to go fullscreen if they want to, and it gives them enough resolution to easily see everything in the app. A large, wall-mounted screen is also highly recommended for use in the classroom, although this is common among schools.

I will also require a keyboard with all standard Latin alphabet characters. This is because the matrices are defined as uppercase Latin letters. Any UK or US keyboard will suffice for this. The app will also require a mouse with at least one button. I don't intend to have right click do anything, so only the primary mouse button is required, although getting a single button mouse to actually work on modern computers is probably quite a challenge. A separate mouse is not strictly required - a laptop trackpad is equally sufficient.

### 1.6.2 Software

Software requirements differ slightly between release and development, although everything that the release environment requires is also required by the development environment. I will require a modern operating system - namely Windows 10 or later, macOS 10.9 'Mavericks'<sup>1</sup> or later, or any modern Linux distro<sup>2</sup>. Basically, it just requires an operating system that is compatible with Python 3.10 and Qt5, since I'll be using these in the project. Of course, Qt5 will need to be installed on the user's computer, although it's standard pretty much everywhere these days.

Python 3.10 won't actually be required for the end user, because I will be compiling the app into a stand-alone binary executable for release, and this binary will contain the required Python runtime and dependencies. However, if the user wishes to download and run the source code themselves, then

---

<sup>1</sup>Python 3.10 won't compile on any earlier versions of macOS[15]

<sup>2</sup>Specifying a Linux version is practically impossible. Python 3.10 isn't available in many package repositories, but will compile on any modern distro. Qt5 is available in many package repositories and can be compiled on any x86 or x86\_64 generic Linux machine with gcc version 5 or later[16]

they will need Python 3.10 and the package dependencies: `numpy`, `nptyping`, and `pyqt5`. These can be automatically installed with the command `python -m pip install -r requirements.txt` from the root of the repository. `numpy` is a maths library that allows for fast matrix maths; `nptyping` is used by `mypy` for type-checking and isn't actually a runtime dependency but the imports in the `typing` module fail if it's not installed at runtime; and `pyqt5` is a library that just allows interop between Python and Qt5, which is originally a C++ library.

In the development environment, I use PyCharm for actually writing my code, and I use a virtual environment to isolate my project dependencies. There are also some development dependencies listed in the file `dev_requirements.txt`. They are: `mypy`, `pyqt5-stubs`, `flake8`, `pycodestyle`, `pydocstyle`, and `pytest`. `mypy` is a static type checker<sup>3</sup>; `pyqt5-stubs` is a collection of type annotations for the PyQt5 API for `mypy` to use; `flake8`, `pycodestyle`, and `pydocstyle` are all linters; and `pytest` is a unit testing framework. I use these libraries to make sure my code is good quality and actually working properly during development.

## 1.7 Success criteria

The main aim of the app is to help teach students about linear transformations. As such, the primary measure of success will be letting teachers get to grips with the app and then asking if they would use it in the classroom or recommend it to students to use at home.

Additionally, the app must fulfil some basic requirements:

1. It must allow the user to define multiple matrices in at least two different ways (numerically and visually)
2. It must be able to validate arbitrary matrix expressions
3. It must be able to render any valid matrix expression
4. It must be able to animate any valid matrix expression
5. It must be able to display information about the currently rendered transformation (determinant, eigenlines, etc.)
6. It must be able to save and load sessions (defined matrices, display settings, etc.)
7. It must allow the user to define and transform arbitrary polygons

Defining multiple matrices is a feature that I thought was lacking from every other solution I researched, and I think it would make the app much easier to use, so I think it's necessary for success. Validating matrix expressions is necessary because if the user tries to render an expression that doesn't make sense, has an undefined matrix, or contains the inverse of a singular matrix, then we have to disallow that or else the app will crash.

Visualizing matrix expressions as linear transformations is the core part of the app, so basic rendering of them is definitely a requirement for success. Animating these expressions is also a pretty crucial part of the app, so I would consider this necessary for success. Displaying the information of a matrix transformation is also very useful for building understanding, so I would consider this needed to succeed.

Saving and loading isn't strictly necessary for success, but it is a standard part of many apps, so will likely be expected by users, and it will benefit the app by allowing teachers to plan lessons in advance and save the matrices they've defined for that lesson to be loaded later.

Transforming polygons is the lowest priority item on this list and will likely be implemented last, but it would definitely benefit learning. I wouldn't consider it necessary for success, but it would be very good to include, and it's certainly a feature that I want to have.

---


<sup>3</sup>Python has weak, dynamic typing with optional type annotations but `mypy` enforces these static type annotations

If the majority of teachers would use and/or recommend the app and it meets all of these points, then I will consider the app as a whole to be a success.

## 2 Design

### 2.1 Problem decomposition

I have decomposed the problem of visualization as follows:



Defining matrices is key to visualization because we need to have matrices to actually visualize. This is a key part of the app, and the user will be able to define multiple separate matrices numerically and visually using the GUI.

Evaluating expressions is another key part of the app and can be further broken down into validating, parsing, and computing the value. Validating an expression simply consists of checking that it adheres to a set of syntax rules for matrix expressions, and that it only contains matrices which have already been defined. Parsing consists of breaking an expression down into tokens, which are then much easier to evaluate. Computing the expression with these tokens is then just a series of simple operations, which will produce a final matrix at the end.


Rendering and animating will likely be the largest part in reality, but I've only decomposed it into simple blocks here. Evaluating positions involves evaluating the matrix expression that the user has input and using the columns of the resultant matrix to find the new positions of the basis vectors, and then extrapolating this for the rest of the plane. Rendering onto the widget is likely to be quite complicated and framework-dependent, so I've abstracted away the details for brevity here. Rendering will involve using the previously calculated values to render grid lines and vectors. Animating will probably be a `for` loop which just renders slightly different matrices onto the widget and sleeps momentarily between frames.

I have deliberately broken this problem down into parts that can be easily translated into modules in my eventual coded solution. This is simply to ease the design and development process, since now I already know my basic project structure. This problem could've been broken down into the parts that the user will directly interact with, but that would be less useful to me when actually starting development, since I would then have to decompose the problem differently to write the actual code.

### 2.2 Structure of the solution

#### 2.2.1 The main project

I have decomposed my solution like so:



The `lintrans` node is simply the root of the whole project. `__main__` is the Python way to make the project executable as `python -m lintrans` on the command line. For release, I will package it into a standalone binary executable.

`matrices` is the package that will allow the user to define, validate, parse, evaluate, and use matrices. The `parse` module will contain functions to validate matrix expressions - likely using regular expressions - and functions to parse matrix expressions. It will not know which matrices are defined, so validation will be naïve and evaluation will be elsewhere. The `wrapper` module will contain a `MatrixWrapper` class, which will hold a dictionary of matrix names and values. It is this class which will have aware validation - making sure that all matrices are actually defined - as well the ability to evaluate matrix expressions, in addition to its basic behaviour of setting and getting matrices. This `matrices` package will also have a `create_rotation_matrix` function that will generate a rotation matrix from an angle using the formula  $\begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}$ . It will be in the `wrapper` module since it's related to defining and manipulating matrices, but it will be exported and accessible as `lintrans.matrices.create_rotation_matrix`.

`gui` is the package that will contain all the frontend code for everything GUI-related. `main_window` is the module that will contain a `LintransMainWindow` class, which will act as the main window of the application and have an instance of `MatrixWrapper` to keep track of which matrices are defined and allow for evaluation of matrix expressions. It will also have methods for rendering and animating matrix expressions, which will be connected to buttons in the GUI. This module will also contain a simple `main()` function to instantiate and launch the application GUI.


The `settings` module will contain a `DisplaySettings` dataclass<sup>4</sup> that will represent the settings for visualizing transformations. The `LintransMainWindow` class will have an instance of this class and check against it when rendering things. The user will be able to open a dialog to change these display settings, which will update the main window's instance of this class.

The `settings` module will also have a `GlobalSettings` class, which will represent the global settings for the application, such as the logging level, where to save the logs, whether to ask the user if they want to be prompted with a tutorial whenever they open the app, etc. This class will have defaults for everything, but the constructor will try to read these settings from a config file if possible. This allows for persistent settings between sessions. This config file will be `~/.config/lintrans.conf` on Unix-like systems, including macOS, and `C:\Users\%USER%\AppData\Roaming\lintrans\config.txt` on Windows. This difference is to remain consistent with operating system conventions<sup>5</sup>.

<sup>4</sup>This is the Python equivalent of a `struct` or `record` in other languages

<sup>5</sup>And also to avoid confusing Windows users with a `.conf` file

### 2.2.2 The gui subpackages



The `dialogs` subpackage will contain modules with different dialog classes. It will have a `define_new_matrices` module, which will have a `DefinedDialog` abstract superclass. It will also contain classes that inherit from this superclass and provide dialogs for defining new matrices visually, numerically, and as an expression in terms of other matrices. Additionally, this subpackage will contain a `settings` module, which will provide a `SettingsDialog` superclass and a `DisplaySettingsDialog` class, which will allow the user to configure the aforementioned display settings. It will also have a `GlobalSettingsDialog` class, which will similarly allow the user to configure the app's global settings through a dialog.

The `plots` subpackage will have a `classes` module and a `widgets` module. The `classes` module will have the abstract superclasses `BackgroundPlot` and `VectorGridPlot`. The former will provide helper methods to convert between coordinate systems and draw the background grid, while the latter will provide helper methods to draw transformations and their components. It will have `point_i` and `point_j` attributes and will provide methods to draw the transformed version of the grid, the vectors and their arrowheads, the eigenlines of the transformation, etc. These methods can then be called from the Qt5 `paintEvent` handler which will be declared abstract and must therefore be implemented by all subclasses.

The `plots` subpackage will also contain a `widgets` module, which will have the classes `VisualizeTransformationWidget` and `DefineVisuallyWidget`, both of which will inherit from `VectorGridPlot`. They will both implement their own `paintEvent` handler to actually draw the respective widgets, and `DefineVisuallyWidget` will also implement handlers for mouse events, allowing the user to drag around the basis vectors.

It's also worth noting here that I don't currently know how I'm going to implement the transformation of arbitrary polygons. It will likely consist of an attribute in `VisualizeTransformationWidget` which is a list of points, and these points can be dragged around with mouse event handlers and then the transformed versions can be rendered, but I'm not yet sure about how I'm going to implement it.

## 2.3 Algorithm design

This section will be completed later.

## 2.4 Usability features

My main concern in terms of usability is colour. In the 3blue1brown videos on linear algebra, red and green are used for the basis vectors, but these colours are often hard to distinguish in most common forms of colour blindness. The most common form is deuteranopia[23], which makes red and green look incredibly similar. I will use blue and red for my basis vectors. These colours are easy to distinguish for people with deuteranopia and protanopia - the two most common forms of colour blindness. Tritanopia makes it harder to distinguish blue and yellow, but my colour scheme is still be accessible for people with tritanopia, as red and blue are very distinct in this form of colour blindness.

I will probably use green for the eigenvectors and eigenlines, which will be hard to distinguish from the red basis vector for people with red-green colour blindness, but I think that the basis vectors and

eigenvectors/eigenlines will look physically different enough from each other that the colour shouldn't be too much of a problem. Additionally, I will use a tool called Color Oracle[10] to make sure that my app is accessible to people with different forms of colour blindness<sup>6</sup>.

Another solution would be to have one default colour scheme, and allow the user to change the colour scheme to something more accessible for colour blind people, but I don't see the point in this. I think it's easier for colour blind people to just have the main colour scheme be accessible, and it's not really an inconvenience to non-colour blind people, so I think this is the best option.

The layout of my app will be self-consistent and follow standard conventions. I will have a menu bar at the top of the main window for actions like saving and loading, as well as accessing the tutorial (which will also be accessible by pressing **F1** at any point) and documentation. The dialogs will always have the confirm button in the bottom right and the cancel button just to the left of that. They will also have the matrix name drop-down on the left. This consistency will make the app easier to learn and understand.

I will also have hotkeys for everything that can have hotkeys - buttons, checkboxes, etc. This makes my life easier, since I'm used to having hotkeys for everything, and thus makes the app faster to test because I don't need to click everything. This also makes things easier for other people like me, who prefer to stay at the keyboard and not use the mouse. Obviously a mouse will be required for things like dragging basis vectors and polygon vertices, but hotkeys will be available wherever possible to help people who don't like using the mouse or find it difficult.

## 2.5 Variables and validation

This project won't actually have many variables. The main ones will be instance attributes on the `LintransMainWindow` class. It will have a `MatrixWrapper` instance, a `DisplaySettings` instance, and a `GlobalSettings` instance. These will handle the matrices and various settings respectively. Having these as instance attributes allows them to be referenced from any method in the class, and Qt5 uses lots of slots (basically callback methods) and handlers, so it's good to be able to access the attributes I need right there rather than having to pass them around from method to method.

The `MatrixWrapper` class will have a dictionary of names and matrices. The names will be single letters<sup>7</sup> and the matrices will be of type `MatrixType`. This will be a custom type alias representing a  $2 \times 2$  numpy array of floats. When setting the values for these matrices, I will have to manually check the types. This is because Python has weak typing, and if we got, say, an integer in place of a matrix, then operations would fail when trying to evaluate a matrix expression, and the program would crash. To prevent this, we have to validate the type of every matrix when it's set. I have chosen to use a dictionary here because it makes accessing a matrix by its name easier. We don't have to check against a list of letters and another list of matrices, we just index into the dictionary.

The settings dataclasses will have instance attributes for each setting. Most of these will be booleans, since they will be simple binary options like *Show determinant*, which will be represented with checkboxes in the GUI. The `DisplaySettings` dataclass will also have an attribute of type `int` representing the time in milliseconds to pause during animations.

The `DefineDialog` superclass have a `MatrixWrapper` instance attribute, which will be a parameter in the constructor. When `LintransMainWindow` spawns a definition dialog (which subclasses `DefineDialog`), it will pass in a copy of its own `MatrixWrapper` and connect the `accepted` signal for the dialog. The slot (method) that this signal is connected to will get called when the dialog is closed with the *Confirm* button<sup>8</sup>. This allows the dialog to mutate its own `MatrixWrapper` object and then the main window can copy that mutated version back into its own instance attribute when the user confirms the change. This reduces coupling and makes everything easier to reason about and debug, as well as reducing

---

<sup>6</sup>I actually had to clone a fork of this project[1] to get it working on Ubuntu 20.04 and adapt it slightly to create a working jar file

<sup>7</sup>I would make these char but Python only has a str type for strings

<sup>8</sup>Actually when the dialog calls `.accept()`. The *Confirm* button is actually connected to a method which first takes the info and updates the instance `MatrixWrapper`, and then calls `.accept()`

the number of bugs, since the classes will be independent of each other. In another language, I could pass a pointer to the wrapper and let the dialog mutate it directly, but this is potentially dangerous, and Python doesn't have pointers anyway.

Validation will also play a very big role in the application. The user will be able to enter matrix expressions and these must be validated. I will define a BNF schema and either write my own RegEx or use that BNF to programmatically generate a RegEx. Every matrix expression input will be checked against it. This is to ensure that the matrix wrapper can actually evaluate the expression. If we didn't validate the expression, then the parsing would fail and the program could crash. I've chosen to use a RegEx here rather than any other option because it's the simplest. Creating a RegEx can be difficult, especially for complicated patterns, but it's then easier to use it. Also, Python can compile a RegEx pattern, which makes it much faster to match against, so I will compile the pattern at initialization time and just compare expressions against that pre-compiled pattern, since we know it won't change at runtime.

Additionally, the buttons to render and animate the current matrix expression will only be enabled when the expression is valid. Textboxes in Qt5 emit a `textChanged` signal, which can be connected to a slot. This is just a method that gets called whenever the text in the textbox is changed, so I can use this method to validate the input and update the buttons accordingly. An empty string will count as invalid, so the buttons will be disabled when the box is empty.

I will also apply this matrix expression validation to the textbox in the dialog which allows the user to define a matrix as an expression involving other matrices, and I will validate the input in the numeric definition dialog to make sure that all the inputs are floats. Again, this is to prevent crashes, since a matrix with non-number values in it will likely crash the program.

## 2.6 Iterative test data

In unit testing, I will test the validation, parsing, and generation of rotation matrices from an angle. I will also unit test the utility functions for the GUI, like `is_valid_float`.

For the validation of matrix expressions, I will have data like the following:

Valid	Invalid
"A"	" "
"AB"	"A^"
"-3.4A"	"rot( )"
"A^2"	"A^{2"
"A^T"	"^12"
"A^{-1}"	"A^{3.2}"
"rot(45)"	"A^B"
"3A^{12}"	".A"
"2B^2+A^TC^{-1}"	"--A"
"3.5A^45.6rot(19.2^T-B^-14.1C^5"	"A--B"

This list is not exhaustive, mostly to save space and time, but the full unit testing code is included in appendix B.

The invalid expressions presented here have been chosen to be almost valid, but not quite. They are edge cases. I will also test blatantly invalid expressions like "This is a matrix expression" to make sure the validation works.

Here's an example of some test data for parsing:



Input	Expected
"A"	[[("", "A", "")]]
"AB"	[[("", "A", ""), ("", "B", "")]]
"2A+B^2"	[[("2", "A", ""), ("", "B", "2")]]
"3A^T2.4B^{-1}-C"	[[("3", "A", "T"), ("2.4", "B", "-1")], [("-1", "C", "")]]

The parsing output is pretty verbose and this table doesn't have enough space for most of the more complicated inputs, so here's a monster one:

"2.14A^{3} 4.5rot(14.5)^{-1} + 8.5B^T 5.97C^{14} - 3.14D^{-1} 6.7E^T"

which should parse to give:

[[("2.14", "A", "3"), ("4.5", "rot(14.5)", "-1")], [("8.5", "B", "T"), ("5.97", "C", "14")],  
[("-3.14", "D", "-1"), ("6.7", "E", "T")]]

Any invalid expression will also raise a parse error, so I will check every invalid input previously mentioned and make sure it raises the appropriate error.

Again, this section is brief to save space and time. All unit tests are included in appendix B.

## 2.7 Post-development test data

This section will be completed later.

### 3 Development

Please note, throughout this section, every code snippet will have two comments at the top. The first is the git commit hash that the snippet was taken from<sup>9</sup>. The second comment is the file name. The line numbers of the snippet reflect the line numbers of the file from where the snippet was taken. After a certain point, I introduced copyright comments at the top of every file. These are always omitted here.

#### 3.1 Matrices backend

##### 3.1.1 MatrixWrapper class

The first real part of development was creating the `MatrixWrapper` class. It needs a simple instance dictionary to be created in the constructor, and it needs a way of accessing the matrices. I decided to use Python's `__getitem__()` and `__setitem__()` special methods[14] to allow indexing into a `MatrixWrapper` object like `wrapper['M']`. This simplifies using the class.

```
# 29ec1fedbf307e3b7ca731c4a381535fec899b0b
# src/lintrans/matrices/wrapper.py

1  """A module containing a simple MatrixWrapper class to wrap matrices and context."""
2
3  import numpy as np
4
5  from lintrans.typing import MatrixType
6
7
8  class MatrixWrapper:
9      """A simple wrapper class to hold all possible matrices and allow access to them."""
10
11     def __init__(self):
12         """Initialise a MatrixWrapper object with a matrices dict."""
13         self._matrices: dict[str, MatrixType | None] = {
14             'A': None, 'B': None, 'C': None, 'D': None,
15             'E': None, 'F': None, 'G': None, 'H': None,
16             'I': np.eye(2), # I is always defined as the identity matrix
17             'J': None, 'K': None, 'L': None, 'M': None,
18             'N': None, 'O': None, 'P': None, 'Q': None,
19             'R': None, 'S': None, 'T': None, 'U': None,
20             'V': None, 'W': None, 'X': None, 'Y': None,
21             'Z': None
22         }
23
24     def __getitem__(self, name: str) -> MatrixType | None:
25         """Get the matrix with `name` from the dictionary.
26
27         Raises:
28             KeyError:
29                 If there is no matrix with the given name
30         """
31         return self._matrices[name]
32
33     def __setitem__(self, name: str, new_matrix: MatrixType) -> None:
34         """Set the value of matrix `name` with the new_matrix.
35
36         Raises:
37             ValueError:
38                 If `name` isn't a valid matrix name
39         """
40         name = name.upper()
41
42         if name == 'I' or name not in self._matrices:
43             raise NameError('Matrix name must be a capital letter and cannot be "I"')
```

<sup>9</sup>A history of all commits can be found in the GitHub repository[2]

```

44
45         self._matrices[name] = new_matrix

```

This code is very simple. The constructor (`__init__()`) creates a dictionary of matrices which all start out as having no value, except the identity matrix **I**. The `__getitem__()` and `__setitem__()` methods allow the user to easily get and set matrices just like a dictionary, and `__setitem__()` will raise an error if the name is invalid. This is a very early prototype, so it doesn't validate the type of whatever the user is trying to assign it to yet. This validation will come later.

I could make this class subclass `dict`, since it's basically just a dictionary at this point, but I want to extend it with much more functionality later, so I chose to handle the dictionary stuff myself.

I then had to write unit tests for this class, and I chose to do all my unit tests using a framework called `pytest`.

```

# 29ec1fedbf307e3b7ca731c4a381535fec899b0b
# tests/test_matrix_wrapper.py

1  """Test the MatrixWrapper class."""
2
3  import numpy as np
4  import pytest
5  from lintrans.matrices import MatrixWrapper
6
7  valid_matrix_names = 'ABCDEFGHJKLMNPOQRSTUVWXYZ'
8  test_matrix = np.array([[1, 2], [4, 3]])
9
10
11 @pytest.fixture
12 def wrapper() -> MatrixWrapper:
13     """Return a new MatrixWrapper object."""
14     return MatrixWrapper()
15
16
17 def test_get_matrix(wrapper) -> None:
18     """Test MatrixWrapper.__getitem__()."""
19     for name in valid_matrix_names:
20         assert wrapper[name] is None
21
22     assert (wrapper['I'] == np.array([[1, 0], [0, 1]])).all()
23
24
25 def test_get_name_error(wrapper) -> None:
26     """Test that MatrixWrapper.__getitem__() raises a KeyError if called with an invalid name."""
27     with pytest.raises(KeyError):
28         _ = wrapper['bad name']
29         _ = wrapper['123456']
30         _ = wrapper['Th15 Is an 1nV@l1D n@m3']
31         _ = wrapper['abc']
32
33
34 def test_set_matrix(wrapper) -> None:
35     """Test MatrixWrapper.__setitem__()."""
36     for name in valid_matrix_names:
37         wrapper[name] = test_matrix
38         assert (wrapper[name] == test_matrix).all()
39
40
41 def test_set_identity_error(wrapper) -> None:
42     """Test that MatrixWrapper.__setitem__() raises a NameError when trying to assign to I."""
43     with pytest.raises(NameError):
44         wrapper['I'] = test_matrix
45
46
47 def test_set_name_error(wrapper) -> None:
48     """Test that MatrixWrapper.__setitem__() raises a NameError when trying to assign to an invalid name."""
49     with pytest.raises(NameError):
50         wrapper['bad name'] = test_matrix
51         wrapper['123456'] = test_matrix

```

```

52     wrapper['Th15 Is an 1nV@l1D n@m3'] = test_matrix
53     wrapper['abc'] = test_matrix

```

These tests are quite simple and just ensure that the expected behaviour works the way it should, and that the correct errors are raised when they should be. It verifies that matrices can be assigned, that every valid name works, and that the identity matrix **I** cannot be assigned to.

The function decorated with `@pytest.fixture` allows functions to use a parameter called `wrapper` and `pytest` will automatically call this function and pass it as that parameter. It just saves on code repetition.

### 3.1.2 Rudimentary parsing and evaluating

This first thing I did here was improve the `__setitem__()` and `__getitem__()` methods to validate input and easily get transposes and simple rotation matrices.

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

60     def __setitem__(self, name: str, new_matrix: MatrixType) -> None:
61         """Set the value of matrix 'name' with the new_matrix.
62
63         :param str name: The name of the matrix to set the value of
64         :param MatrixType new_matrix: The value of the new matrix
65         :rtype: None
66
67         :raises NameError: If the name isn't a valid matrix name or is 'I'
68         """
69         if name not in self._matrices.keys():
70             raise NameError('Matrix name must be a single capital letter')
71
72         if name == 'I':
73             raise NameError('Matrix name cannot be "I"')
74
75         # All matrices must have float entries
76         a = float(new_matrix[0][0])
77         b = float(new_matrix[0][1])
78         c = float(new_matrix[1][0])
79         d = float(new_matrix[1][1])
80
81         self._matrices[name] = np.array([[a, b], [c, d]])

```

In this method, I'm now casting all the values to floats. This is very simple validation, since this cast will raise **ValueError** if it fails to cast the value to a float. I should've declared `:raises ValueError:` in the docstring, but this was an oversight at the time.

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

27     def __getitem__(self, name: str) -> Optional[MatrixType]:
28         """Get the matrix with the given name.
29
30         If it is a simple name, it will just be fetched from the dictionary.
31         If the name is followed with a 't', then we will return the transpose of the named matrix.
32         If the name is 'rot()', with a given angle in degrees, then we return a new rotation matrix with that angle.
33
34         :param str name: The name of the matrix to get
35         :returns: The value of the matrix (may be none)
36         :rtype: Optional[MatrixType]
37
38         :raises NameError: If there is no matrix with the given name
39         """
40         # Return a new rotation matrix

```

```

41     match = re.match(r'rot\\((\\d+)\\)', name)
42     if match is not None:
43         return create_rotation_matrix(float(match.group(1)))
44
45     # Return the transpose of this matrix
46     match = re.match(r'([A-Z])t', name)
47     if match is not None:
48         matrix = self[match.group(1)]
49
50         if matrix is not None:
51             return matrix.T
52         else:
53             return None
54
55     if name not in self._matrices:
56         raise NameError(f'Unrecognised matrix name "{name}"')
57
58     return self._matrices[name]

```

This `__getitem__()` method now allows for easily accessing transposes and rotation matrices by checking input with regular expressions. This makes getting matrices easier and thus makes evaluating full expressions simpler.

The `create_rotation_matrix()` method is also defined in this file and just uses the  $\begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}$  formula from before:

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

158 def create_rotation_matrix(angle: float) -> MatrixType:
159     """Create a matrix representing a rotation by the given number of degrees anticlockwise.
160
161     :param float angle: The number of degrees to rotate by
162     :returns MatrixType: The resultant rotation matrix
163     """
164     rad = np.deg2rad(angle)
165     return np.array([
166         [np.cos(rad), -1 * np.sin(rad)],
167         [np.sin(rad), np.cos(rad)]
168     ])

```

At this stage, I also implemented a simple parser and evaluator using regular expressions. It's not great and it's not very flexible, but it can evaluate simple expressions.

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

83 def parse_expression(self, expression: str) -> MatrixType:
84     """Parse a given expression and return the matrix for that expression.
85
86     Expressions are written with standard LaTeX notation for exponents. All whitespace is ignored.
87
88     Here is documentation on syntax:
89         A single matrix is written as 'A'.
90         Matrix A multiplied by matrix B is written as 'AB'
91         Matrix A plus matrix B is written as 'A+B'
92         Matrix A minus matrix B is written as 'A-B'
93         Matrix A squared is written as 'A^2'
94         Matrix A to the power of 10 is written as 'A^10' or 'A^{10}'
95         The inverse of matrix A is written as 'A^-1' or 'A^{-1}'
96         The transpose of matrix A is written as 'A^T' or 'At'
97
98     :param str expression: The expression to be parsed
99     :returns MatrixType: The matrix result of the expression
100
101     :raises ValueError: If the expression is invalid, such as an empty string
102     """

```

```

103     if expression == '':
104         raise ValueError('The expression cannot be an empty string')
105
106     match = re.search(r'^-+A-Z^{rot()}\d.}', expression)
107     if match is not None:
108         raise ValueError(f'Invalid character "{match.group(0)}"')
109
110     # Remove all whitespace in the expression
111     expression = re.sub(r'\s', '', expression)
112
113     # Wrap all exponents and transposition powers with {}
114     expression = re.sub(r'(<=^)(-?\d+|T)(?=[^]|$)', r'{\g<0>}', expression)
115
116     # Replace all subtractions with additions, multiplied by -1
117     expression = re.sub(r'(<=.)-(<=[A-Z])', '+-1', expression)
118
119     # Replace a possible leading minus sign with -1
120     expression = re.sub(r'^-(<=[A-Z])', '-1', expression)
121
122     # Change all transposition exponents into lowercase
123     expression = expression.replace('^T', 't')
124
125     # Split the expression into groups to be multiplied, and then we add those groups at the end
126     # We also have to filter out the empty strings to reduce errors
127     multiplication_groups = [x for x in expression.split('+') if x != '']
128
129     # Start with the 0 matrix and add each group on
130     matrix_sum: MatrixType = np.array([[0., 0.], [0., 0.]])
131
132     for group in multiplication_groups:
133         # Generate a list of tuples, each representing a matrix
134         # These tuples are (the multiplier, the matrix (with optional
135         # 't' at the end to indicate a transpose), the exponent)
136         string_matrices: list[tuple[str, str, str]]
137
138         # The generate tuple is (multiplier, matrix, full exponent, stripped exponent)
139         # The full exponent contains ^{}, so we ignore it
140         # The multiplier and exponent might be '', so we have to set them to '1'
141         string_matrices = [(t[0] if t[0] != '' else '1', t[1], t[3] if t[3] != '' else '1')
142                             for t in re.findall(r'(-?\d*\.{?\d*})([A-Z]?|rot\(\d+\))(\^{(-?\d+|T)})?', group)]
143
144         # This list is a list of tuple, where each tuple is (a float multiplier,
145         # the matrix (gotten from the wrapper's __getitem__()), the integer power)
146         matrices: list[tuple[float, MatrixType, int]]
147         matrices = [(float(t[0]), self[t[1]], int(t[2])) for t in string_matrices]
148
149         # Process the matrices and make actual MatrixType objects
150         processed_matrices: list[MatrixType] = [t[0] * np.linalg.matrix_power(t[1], t[2]) for t in matrices]
151
152         # Add this matrix product to the sum total
153         matrix_sum += reduce(lambda m, n: m @ n, processed_matrices)
154
155     return matrix_sum

```

I think the comments in the code speak for themselves, but we basically split the expression up into groups to be added, and then for each group, we multiply every matrix in that group to get its value, and then add all these values together at the end.

This code is objectively bad. At the time of writing, it's now quite old, so I can say that. This code has no real error handling, and line 127 introduces the glaring error that 'A++B' is now a valid expression because we disregard empty strings. Not to mention the fact that the method is called `parse_expression()` but actually evaluates an expression. All these issues will be fixed in the future, but this was the first implementation of matrix evaluation, and it does the job decently well.

I then implemented several tests for this parsing.

```

# 60e0c713b244e097bab8ee0f71142b709fde1a8b
# tests/test_matrix_wrapper_parse_expression.py

```

```

1  """Test the MatrixWrapper parse_expression() method."""
2
3  import numpy as np
4  from numpy import linalg as la
5  import pytest
6  from lintrans.matrices import MatrixWrapper
7
8
9  @pytest.fixture
10 def wrapper() -> MatrixWrapper:
11     """Return a new MatrixWrapper object with some preset values."""
12     wrapper = MatrixWrapper()
13
14     root_two_over_two = np.sqrt(2) / 2
15
16     wrapper['A'] = np.array([[1, 2], [3, 4]])
17     wrapper['B'] = np.array([[6, 4], [12, 9]])
18     wrapper['C'] = np.array([[ -1, -3], [4, -12]])
19     wrapper['D'] = np.array([[13.2, 9.4], [-3.4, -1.8]])
20     wrapper['E'] = np.array([
21         [root_two_over_two, -1 * root_two_over_two],
22         [root_two_over_two, root_two_over_two]
23     ])
24     wrapper['F'] = np.array([[ -1, 0], [0, 1]])
25     wrapper['G'] = np.array([[np.pi, np.e], [1729, 743.631]])
26
27     return wrapper
28
29
30 def test_simple_matrix_addition(wrapper: MatrixWrapper) -> None:
31     """Test simple addition and subtraction of two matrices."""
32
33     # NOTE: We assert that all of these values are not None just to stop mypy complaining
34     # These values will never actually be None because they're set in the wrapper() fixture
35     # There's probably a better way do this, because this method is a bit of a bodge, but this works for now
36     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
37         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
38         wrapper['G'] is not None
39
40     assert (wrapper.parse_expression('A+B') == wrapper['A'] + wrapper['B']).all()
41     assert (wrapper.parse_expression('E+F') == wrapper['E'] + wrapper['F']).all()
42     assert (wrapper.parse_expression('G+D') == wrapper['G'] + wrapper['D']).all()
43     assert (wrapper.parse_expression('C+C') == wrapper['C'] + wrapper['C']).all()
44     assert (wrapper.parse_expression('D+A') == wrapper['D'] + wrapper['A']).all()
45     assert (wrapper.parse_expression('B+C') == wrapper['B'] + wrapper['C']).all()
46
47
48 def test_simple_two_matrix_multiplication(wrapper: MatrixWrapper) -> None:
49     """Test simple multiplication of two matrices."""
50     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
51         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
52         wrapper['G'] is not None
53
54     assert (wrapper.parse_expression('AB') == wrapper['A'] @ wrapper['B']).all()
55     assert (wrapper.parse_expression('BA') == wrapper['B'] @ wrapper['A']).all()
56     assert (wrapper.parse_expression('AC') == wrapper['A'] @ wrapper['C']).all()
57     assert (wrapper.parse_expression('DA') == wrapper['D'] @ wrapper['A']).all()
58     assert (wrapper.parse_expression('ED') == wrapper['E'] @ wrapper['D']).all()
59     assert (wrapper.parse_expression('FD') == wrapper['F'] @ wrapper['D']).all()
60     assert (wrapper.parse_expression('GA') == wrapper['G'] @ wrapper['A']).all()
61     assert (wrapper.parse_expression('CF') == wrapper['C'] @ wrapper['F']).all()
62     assert (wrapper.parse_expression('AG') == wrapper['A'] @ wrapper['G']).all()
63
64
65 def test_identity_multiplication(wrapper: MatrixWrapper) -> None:
66     """Test that multiplying by the identity doesn't change the value of a matrix."""
67     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
68         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
69         wrapper['G'] is not None
70
71     assert (wrapper.parse_expression('I') == wrapper['I']).all()
72     assert (wrapper.parse_expression('AI') == wrapper['A']).all()
73     assert (wrapper.parse_expression('IA') == wrapper['A']).all()

```

```

74     assert (wrapper.parse_expression('GI') == wrapper['G']).all()
75     assert (wrapper.parse_expression('IG') == wrapper['G']).all()
76
77     assert (wrapper.parse_expression('EID') == wrapper['E'] @ wrapper['D']).all()
78     assert (wrapper.parse_expression('IED') == wrapper['E'] @ wrapper['D']).all()
79     assert (wrapper.parse_expression('EDI') == wrapper['E'] @ wrapper['D']).all()
80     assert (wrapper.parse_expression('IIDI') == wrapper['E'] @ wrapper['D']).all()
81     assert (wrapper.parse_expression('EI^3D') == wrapper['E'] @ wrapper['D']).all()
82
83
84 def test_simple_three_matrix_multiplication(wrapper: MatrixWrapper) -> None:
85     """Test simple multiplication of two matrices."""
86     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
87         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
88         wrapper['G'] is not None
89
90     assert (wrapper.parse_expression('ABC') == wrapper['A'] @ wrapper['B'] @ wrapper['C']).all()
91     assert (wrapper.parse_expression('ACB') == wrapper['A'] @ wrapper['C'] @ wrapper['B']).all()
92     assert (wrapper.parse_expression('BAC') == wrapper['B'] @ wrapper['A'] @ wrapper['C']).all()
93     assert (wrapper.parse_expression('EFG') == wrapper['E'] @ wrapper['F'] @ wrapper['G']).all()
94     assert (wrapper.parse_expression('DAC') == wrapper['D'] @ wrapper['A'] @ wrapper['C']).all()
95     assert (wrapper.parse_expression('GAE') == wrapper['G'] @ wrapper['A'] @ wrapper['E']).all()
96     assert (wrapper.parse_expression('FAG') == wrapper['F'] @ wrapper['A'] @ wrapper['G']).all()
97     assert (wrapper.parse_expression('GAF') == wrapper['G'] @ wrapper['A'] @ wrapper['F']).all()
98
99
100 def test_matrix_inverses(wrapper: MatrixWrapper) -> None:
101     """Test the inverses of single matrices."""
102     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
103         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
104         wrapper['G'] is not None
105
106     assert (wrapper.parse_expression('A^{-1}') == la.inv(wrapper['A'])).all()
107     assert (wrapper.parse_expression('B^{-1}') == la.inv(wrapper['B'])).all()
108     assert (wrapper.parse_expression('C^{-1}') == la.inv(wrapper['C'])).all()
109     assert (wrapper.parse_expression('D^{-1}') == la.inv(wrapper['D'])).all()
110     assert (wrapper.parse_expression('E^{-1}') == la.inv(wrapper['E'])).all()
111     assert (wrapper.parse_expression('F^{-1}') == la.inv(wrapper['F'])).all()
112     assert (wrapper.parse_expression('G^{-1}') == la.inv(wrapper['G'])).all()
113
114     assert (wrapper.parse_expression('A^{-1}') == la.inv(wrapper['A'])).all()
115     assert (wrapper.parse_expression('B^{-1}') == la.inv(wrapper['B'])).all()
116     assert (wrapper.parse_expression('C^{-1}') == la.inv(wrapper['C'])).all()
117     assert (wrapper.parse_expression('D^{-1}') == la.inv(wrapper['D'])).all()
118     assert (wrapper.parse_expression('E^{-1}') == la.inv(wrapper['E'])).all()
119     assert (wrapper.parse_expression('F^{-1}') == la.inv(wrapper['F'])).all()
120     assert (wrapper.parse_expression('G^{-1}') == la.inv(wrapper['G'])).all()
121
122
123 def test_matrix_powers(wrapper: MatrixWrapper) -> None:
124     """Test that matrices can be raised to integer powers."""
125     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
126         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
127         wrapper['G'] is not None
128
129     assert (wrapper.parse_expression('A^2') == la.matrix_power(wrapper['A'], 2)).all()
130     assert (wrapper.parse_expression('B^4') == la.matrix_power(wrapper['B'], 4)).all()
131     assert (wrapper.parse_expression('C^{12}') == la.matrix_power(wrapper['C'], 12)).all()
132     assert (wrapper.parse_expression('D^{12}') == la.matrix_power(wrapper['D'], 12)).all()
133     assert (wrapper.parse_expression('E^8') == la.matrix_power(wrapper['E'], 8)).all()
134     assert (wrapper.parse_expression('F^{-6}') == la.matrix_power(wrapper['F'], -6)).all()
135     assert (wrapper.parse_expression('G^{-2}') == la.matrix_power(wrapper['G'], -2)).all()

```

These test lots of simple expressions, but don't test any more complicated expressions, nor do they test any validation, mostly because validation doesn't really exist at this point. 'A++B' is still a valid expression and is equivalent to 'A+B'.



### 3.1.3 Simple matrix expression validation

My next major step was to implement proper parsing, but I procrastinated for a while and first implemented proper validation.

```
# 39b918651f60bc72bc19d2018075b24a6fc3af17
# src/lintrans/_parse/matrices.py

9 def compile_valid_expression_pattern() -> Pattern[str]:
10     """Compile the single regular expression that will match a valid matrix expression."""
11     digit_no_zero = '[123456789]'
12     digits = '\\d+'
13     integer_no_zero = '-?' + digit_no_zero + '(' + digits + ')?'
14     real_number = f'({integer_no_zero}(\\.\\{digits}\\})?|-?0?\\.\\{digits}\\})'
15
16     index_content = f'({integer_no_zero}|T)'
17     index = f'\\^\\{index_content\\}\\}\\^\\{index_content\\}|t)'
18     matrix_identifier = f'([A-Z]|rot\\(\\{real_number\\}\\))'
19     matrix = '(' + real_number + '?' + matrix_identifier + index + ')?'
20     expression = f'{matrix}+((\\+|-){matrix}+)*'
21
22     return re.compile(expression)
23
24
25 # This is an expensive pattern to compile, so we compile it when this module is initialized
26 valid_expression_pattern = compile_valid_expression_pattern()
27
28
29 def validate_matrix_expression(expression: str) -> bool:
30     """Validate the given matrix expression.
31
32     This function simply checks the expression against a BNF schema. It is not
33     aware of which matrices are actually defined in a wrapper. For an aware
34     version of this function, use the MatrixWrapper().is_valid_expression() method.
35
36     Here is the schema for a valid expression given in a version of BNF:
37
38         expression      ::= matrices { ( "+" | "-" ) matrices };
39         matrices        ::= matrix { matrix };
40         matrix          ::= [ real_number ] matrix_identifier [ index ];
41         matrix_identifier ::= "A" .. "Z" | "rot(" real_number ")";
42         index           ::= "^{" index_content "}" | "^" index_content | "t";
43         index_content   ::= integer_not_zero | "T";
44
45         digit_no_zero   ::= "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9";
46         digit           ::= "0" | digit_no_zero;
47         digits          ::= digit | digits digit;
48         integer_not_zero ::= [ "-" ] digit_no_zero [ digits ];
49         real_number     ::= ( integer_not_zero [ "." digits ] | [ "-" ] [ "0" ] "." digits );
50
51     :param str expression: The expression to be validated
52     :returns bool: Whether the expression is valid according to the schema
53     """
54     match = valid_expression_pattern.match(expression)
55     return expression == match.group(0) if match is not None else False
```

Here, I'm using a BNF schema to programmatically generate a regular expression. I use a function to generate this pattern and assign it to a variable when the module is initialized. This is because the pattern compilation is expensive and it's more efficient to compile the pattern once and then just use it in the `validate_matrix_expression()` function.

I also created a method `is_valid_expression()` in `MatrixWrapper`, which just validates a given expression. It uses the aforementioned `validate_matrix_expression()` and also checks that every matrix referenced in the expression is defined in the wrapper.

```
# 39b918651f60bc72bc19d2018075b24a6fc3af17
# src/lintrans/matrices/wrapper.py
```

```

99     def is_valid_expression(self, expression: str) -> bool:
100         """Check if the given expression is valid, using the context of the wrapper.
101
102         This method calls _parse.validate_matrix_expression(), but also ensures
103         that all the matrices in the expression are defined in the wrapper.
104
105         :param str expression: The expression to validate
106         :returns bool: Whether the expression is valid according the schema
107         """
108         # Get rid of the transposes to check all capital letters
109         expression = re.sub(r'\^T', 't', expression)
110         expression = re.sub(r'\^[T]', 't', expression)
111
112         # Make sure all the referenced matrices are defined
113         for matrix in {x for x in expression if re.match('[A-Z]', x)}:
114             if self[matrix] is None:
115                 return False
116
117         return _parse.validate_matrix_expression(expression)

```

I then implemented some simple tests to make sure the function works with valid and invalid expressions.

```

# a0fb029f7da995803c24ee36e7e8078e5621f676
# tests/_parse/test_parse_and_validate_expression.py

1  """Test the _parse.matrices module validation and parsing."""
2
3  import pytest
4  from lintrans._parse import validate_matrix_expression
5
6  valid_inputs: list[str] = [
7      'A', 'AB', '3A', '1.2A', '-3.4A', 'A^2', 'A^-1', 'A^{-1}',
8      'A^12', 'A^T', 'A^{5}', 'A^{T}', '4.3A^7', '9.2A^{18}',
9
10     'rot(45)', 'rot(12.5)', '3rot(90)',
11     'rot(135)^3', 'rot(51)^T', 'rot(-34)^-1',
12
13     'A+B', 'A+2B', '4.3A+9B', 'A^2+B^T', '3A^7+0.8B^{16}',
14     'A-B', '3A-4B', '3.2A^3-16.79B^T', '4.752A^{17}-3.32B^{36}',
15     'A--1B', '-A', '--1A'
16
17     '3A4B', 'A^TB', 'A^{T}B', '4A^6B^3',
18     '2A^{3}4B^5', '4rot(90)^3', 'rot(45)rot(13)',
19     'Arot(90)', 'AB^2', 'A^2B^2', '8.36A^T3.4B^12',
20
21     '3.5A^{4}5.6rot(19.2)^T-B^{-1}4.1C^5',
22 ]
23
24  invalid_inputs: list[str] = [
25      '', 'rot()', 'A^', 'A^1.2', 'A^{3.4}', '1,2A', 'ro(12)', '5', '12^2',
26      '^T', '^12}', 'A^{13}', 'A^3}', 'A^A', '^2', 'A--B', '--A'
27
28      'This is 100% a valid matrix expression, I swear'
29  ]
30
31
32  @pytest.mark.parametrize('inputs,output', [(valid_inputs, True), (invalid_inputs, False)])
33  def test_validate_matrix_expression(inputs: list[str], output: bool) -> None:
34      """Test the validate_matrix_expression() function."""
35      for inp in inputs:
36          assert validate_matrix_expression(inp) == output

```

Here, we test some valid data, some definitely invalid data, and some edge cases. At this stage, 'A--1B' was considered a valid expression. This was a quirk of the validator at the time, but I fixed it later. This should obviously be an invalid expression, especially since 'A--B' is considered invalid, but 'A--1B' is valid.

The `@pytest.mark.parametrize` decorator on line 32 means that `pytest` will run one test for valid inputs, and then another test for invalid inputs, and these will count as different tests. This makes it easier to see which tests failed and then debug the app.

### 3.1.4 Parsing matrix expressions

Parsing is quite an interesting problem and something I didn't feel able to tackle head-on, so I wrote the unit tests first. I had a basic idea of what I wanted the parser to return, but no real idea of how to implement that. My unit tests looked like this:

```
# e9f7a81892278fe70684562052f330fb3a02bf9b
# tests/_parse/test_parse_and_validate_expression.py

expressions_and_parsed_expressions: list[tuple[str, MatrixParseList]] = [
    # Simple expressions
    ('A', [(('', 'A', ''))]),
    ('A^2', [(('', 'A', '2'))]),
    ('A^{2}', [(('', 'A', '2'))]),
    ('3A', [(('3', 'A', ''))]),
    ('1.4A^3', [(('1.4', 'A', '3'))]),

    # Multiplications
    ('4A^3 6B^2', [(('4', 'A', '3'), ('6', 'B', '2'))]),
    ('4.2A^{T} 6.1B^{-1}', [(('4.2', 'A', 'T'), ('6.1', 'B', '-1'))]),
    ('-1.2A^2 rot(45)^2', [(('1.2', 'A', '2'), ('', 'rot(45)', '2'))]),
    ('3.2A^T 4.5B^{5} 9.6rot(121.3)', [(('3.2', 'A', 'T'), ('4.5', 'B', '5'), ('9.6', 'rot(121.3)', ''))]),
    ('-1.18A^{-2} 0.1B^{2} 9rot(34.6)^{-1}', [(('1.18', 'A', '-2'), ('0.1', 'B', '2'), ('9', 'rot(34.6)', '-1'))]),

    # Additions
    ('A + B', [(('', 'A', ''), ('', 'B', ''))]),
    ('A + B - C', [(('', 'A', ''), ('', 'B', '')), (('1', 'C', ''))]),
    ('2A^3 + 8B^T - 3C^{-1}', [(('2', 'A', '3'), ('8', 'B', 'T'), ('3', 'C', '-1'))]),

    # Additions with multiplication
    ('2.14A^3 4.5rot(14.5)^{-1} + 8B^T - 3C^{-1}', [(('2.14', 'A', '3'), ('4.5', 'rot(14.5)', '-1'), ('8', 'B', 'T'), ('3', 'C', '-1'))]),
    ('2.14A^3 4.5rot(14.5)^{-1} + 8.5B^T 5.97C^4 - 3.14D^{-1} 6.7E^T', [(('2.14', 'A', '3'), ('4.5', 'rot(14.5)', '-1'), ('8.5', 'B', 'T'), ('5.97', 'C', '4'), ('3.14', 'D', '-1'), ('6.7', 'E', 'T'))]),
]

@pytest.mark.skip(reason='parse_matrix_expression() not implemented')
def test_parse_matrix_expression() -> None:
    """Test the parse_matrix_expression() function."""
    for expression, parsed_expression in expressions_and_parsed_expressions:
        # Test it with and without whitespace
        assert parse_matrix_expression(expression) == parsed_expression
        assert parse_matrix_expression(expression.replace(' ', '')) == parsed_expression
```

I just had example inputs and what I expected as output. I also wanted the parser to ignore whitespace. The decorator on line 69 just skips the test because the parser wasn't implemented yet.

When implementing the parser, I first had to tighten up validation to remove anomalies like 'A--1B' being valid. I did this by factoring out the optional minus signs from being part of a number, to being optionally in front of a number. This eliminated this kind of repetition and made 'A--1B' invalid, as it should be.

```
# fd80d8d3b0e975e92dcc7c10f1f0f1276879f408
# src/lintrans/_parse/matrices.py

def compile_valid_expression_pattern() -> Pattern[str]:
    """Compile the single regular expression that will match a valid matrix expression."""
    digit_no_zero = '[123456789]'
    digits = '\\d+'

```

```

36 integer_no_zero = digit_no_zero + '(' + digits + ')?'
37 real_number = f'({integer_no_zero}(\.\{digits})?|0?\.\{digits})'
38
39 index_content = f'(-?{integer_no_zero}|T)'
40 index = f'(\^\^\{{index_content}\}\^\^\{index_content}|t)'
41 matrix_identifier = f'([A-Z]|rot\((-?{real_number}\)\)'
42 matrix = '(' + real_number + '?' + matrix_identifier + index + '?'
43 expression = f'-?{matrix}+(\(|\+|\-){matrix})*'
44
45 return re.compile(expression)

```

The code can be a bit hard to read with all the RegEx stuff, but the BNF illustrates these changes nicely.

Compare the old version:

```

# 39b918651f60bc72bc19d2018075b24a6fc3af17
# src/lintrans/_parse/matrices.py

38 expression      ::= matrices { ( "+" | "-" ) matrices };
39 matrices        ::= matrix { matrix };
40 matrix           ::= [ real_number ] matrix_identifier [ index ];
41 matrix_identifier ::= "A" .. "Z" | "rot(" real_number ")";
42 index            ::= "^{" index_content "}" | "^" index_content | "t";
43 index_content    ::= integer_not_zero | "T";
44
45 digit_no_zero    ::= "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9";
46 digit            ::= "0" | digit_no_zero;
47 digits           ::= digit | digits digit;
48 integer_not_zero ::= [ "-" ] digit_no_zero [ digits ];
49 real_number      ::= ( integer_not_zero [ "." digits ] | [ "-" ] [ "0" ] "." digits );

```

to the new version:

```

# fd80d8d3b0e975e92dcc7c10f1f0f1276879f408
# src/lintrans/_parse/matrices.py

61 expression      ::= [ "-" ] matrices { ( "+" | "-" ) matrices };
62 matrices        ::= matrix { matrix };
63 matrix           ::= [ real_number ] matrix_identifier [ index ];
64 matrix_identifier ::= "A" .. "Z" | "rot(" [ "-" ] real_number ")";
65 index            ::= "^{" index_content "}" | "^" index_content | "t";
66 index_content    ::= [ "-" ] integer_not_zero | "T";
67
68 digit_no_zero    ::= "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9";
69 digit            ::= "0" | digit_no_zero;
70 digits           ::= digit | digits digit;
71 integer_not_zero ::= digit_no_zero [ digits ];
72 real_number      ::= ( integer_not_zero [ "." digits ] | [ "0" ] "." digits );

```

Then once I'd fixed the validation, I could implement the parser itself.

```

# fd80d8d3b0e975e92dcc7c10f1f0f1276879f408
# src/lintrans/_parse/matrices.py

86 def parse_matrix_expression(expression: str) -> MatrixParseList:
87     """Parse the matrix expression and return a list of results.
88
89     The return value is a list of results. This results list contains lists of tuples.
90     The top list is the expressions that should be added together, and each sublist
91     is expressions that should be multiplied together. These expressions to be
92     multiplied are tuples, where each tuple is (multiplier, matrix identifier, index).
93     The multiplier can be any real number, the matrix identifier is either a named
94     matrix or a new rotation matrix declared with 'rot()', and the index is an
95     integer or 'T' for transpose.
96

```

```

97     :param str expression: The expression to be parsed
98     :returns MatrixParseTuple: A list of results
99     """
100    # Remove all whitespace
101    expression = re.sub(r'\s', '', expression)
102
103    # Check if it's valid
104    if not validate_matrix_expression(expression):
105        raise MatrixParseError('Invalid expression')
106
107    # Wrap all exponents and transposition powers with {}
108    expression = re.sub(r'(?<=^)(-?\d+|T)(?=[^}]|$)', r'{\g<0>}', expression)
109
110    # Remove any standalone minuses
111    expression = re.sub(r'-(?=[A-Z])', '-1', expression)
112
113    # Replace subtractions with additions
114    expression = re.sub(r'-(?=\d+\.?\d*([A-Z]|rot))', '+-', expression)
115
116    # Get rid of a potential leading + introduced by the last step
117    expression = re.sub(r'^+', '', expression)
118
119    return [
120        [
121            # The tuple returned by re.findall is (multiplier, matrix identifier, full index, stripped index),
122            # so we have to remove the full index, which contains the {}
123            (t[0], t[1], t[3])
124            for t in re.findall(r'(-?\d+\.?\d*)?([A-Z]|rot\(-?\d+\.?\d*\))(\^{(-?\d+|T)})?', group)
125        ]
126        # We just split the expression by '+' to have separate groups
127        for group in expression.split('+')
128    ]

```

It works similarly to the old `MatrixWrapper.parse_expression()` method in §3.1.2 but with a powerful list comprehension at the end. It splits the expression up into groups and then uses some RegEx magic to find all the matrices in these groups as a tuple.

This method passes all the unit tests, as expected.

My next step was then to rewrite the evaluation to use this new parser, like so (method name and docstring removed):

```

# a453774bcd824676461f9b9b441d7b94969ea55
# src/lintrans/matrices/wrapper.py

168    if not self.is_valid_expression(expression):
169        raise ValueError('The expression is invalid')
170
171    parsed_result = _parse.parse_matrix_expression(expression)
172    final_groups: list[list[MatrixType]] = []
173
174    for group in parsed_result:
175        f_group: list[MatrixType] = []
176
177        for matrix in group:
178            if matrix[2] == 'T':
179                m = self[matrix[1]]
180                assert m is not None
181                matrix_value = m.T
182            else:
183                matrix_value = np.linalg.matrix_power(self[matrix[1]],
184                1 if (index := matrix[2]) == '' else int(index))
185
186            matrix_value *= 1 if (multiplier := matrix[0]) == '' else float(multiplier)
187            f_group.append(matrix_value)
188
189        final_groups.append(f_group)
190
191    return reduce(add, [reduce(matmul, group) for group in final_groups])

```

Here, we go through the list of tuples and evaluate the matrix represented by each tuple, putting this together in a list as we go. Then at the end, we simply reduce the sublists and then reduce these new matrices using a list comprehension in the `reduce()` call using `add` and `matmul` from the `operator` library. It's written in a functional programming style, and it passes all the previous tests.

## 3.2 Initial GUI

### 3.2.1 First basic GUI

The discrepancy in all the GUI code between `snake_case` and `camelCase` is because Qt5 was originally a C++ framework that was adapted into PyQt5 for Python. All the Qt API is in `camelCase`, but my Python code is in `snake_case`.

```
# 93ce763f7b993439fc0da89fad39456d8cc4b52c
# src/lintrans/gui/main_window.py

1 """The module to provide the main window as a QMainWindow object."""
2
3 import sys
4
5 from PyQt5 import QtCore, QtGui, QtWidgets
6 from PyQt5.QtWidgets import QApplication, QHBoxLayout, QMainWindow, QVBoxLayout
7
8 from lintrans.matrices import MatrixWrapper
9
10
11 class LintransMainWindow(QMainWindow):
12     """The class for the main window in the lintrans GUI."""
13
14     def __init__(self):
15         """Create the main window object, creating every widget in it."""
16         super().__init__()
17
18         self.matrix_wrapper = MatrixWrapper()
19
20         self.setWindowTitle('Linear Transformations')
21         self.setMinimumWidth(750)
22
23         # === Create widgets
24
25         # Left layout: the plot and input box
26
27         # NOTE: This QGraphicsView is only temporary
28         self.plot = QtWidgets.QGraphicsView(self)
29
30         self.text_input_expression = QtWidgets.QLineEdit(self)
31         self.text_input_expression.setPlaceholderText('Input matrix expression...')
32         self.text_input_expression.textChanged.connect(self.update_render_buttons)
33
34         # Right layout: all the buttons
35
36         # Misc buttons
37
38         self.button_create_polygon = QtWidgets.QPushButton(self)
39         self.button_create_polygon.setText('Create polygon')
40         # TODO: Implement create_polygon()
41         # self.button_create_polygon.clicked.connect(self.create_polygon)
42         self.button_create_polygon.setToolTip('Define a new polygon to view the transformation of')
43
44         self.button_change_display_settings = QtWidgets.QPushButton(self)
45         self.button_change_display_settings.setText('Change\ndisplay settings')
46         # TODO: Implement change_display_settings()
47         # self.button_change_display_settings.clicked.connect(self.change_display_settings)
48         self.button_change_display_settings.setToolTip('Change which things are rendered on the plot')
49
50         # Define new matrix buttons
51
```

```

52     self.label_define_new_matrix = QtWidgets.QLabel(self)
53     self.label_define_new_matrix.setText('Define a new matrix')
54     self.label_define_new_matrix.setAlignment(QtCore.Qt.AlignCenter)
55
56     # TODO: Implement defining a new matrix visually, numerically, as a rotation, and as an expression
57
58     self.button_define_visually = QtWidgets.QPushButton(self)
59     self.button_define_visually.setText('Visually')
60     self.button_define_visually.setToolTip('Drag the basis vectors')
61
62     self.button_define_numerically = QtWidgets.QPushButton(self)
63     self.button_define_numerically.setText('Numerically')
64     self.button_define_numerically.setToolTip('Define a matrix just with numbers')
65
66     self.button_define_as_rotation = QtWidgets.QPushButton(self)
67     self.button_define_as_rotation.setText('As a rotation')
68     self.button_define_as_rotation.setToolTip('Define an angle to rotate by')
69
70     self.button_define_as_expression = QtWidgets.QPushButton(self)
71     self.button_define_as_expression.setText('As an expression')
72     self.button_define_as_expression.setToolTip('Define a matrix in terms of other matrices')
73
74     # Render buttons
75
76     self.button_render = QtWidgets.QPushButton(self)
77     self.button_render.setText('Render')
78     self.button_render.setEnabled(False)
79     self.button_render.clicked.connect(self.render_expression)
80     self.button_render.setToolTip('Render the expression<br><b>(Ctrl + Enter)</b>')
81
82     self.button_render_shortcut = QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Return'), self)
83     self.button_render_shortcut.activated.connect(self.button_render.click)
84
85     self.button_animate = QtWidgets.QPushButton(self)
86     self.button_animate.setText('Animate')
87     self.button_animate.setEnabled(False)
88     self.button_animate.clicked.connect(self.animate_expression)
89     self.button_animate.setToolTip('Animate the expression<br><b>(Ctrl + Shift + Enter)</b>')
90
91     self.button_animate_shortcut = QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Shift+Return'), self)
92     self.button_animate_shortcut.activated.connect(self.button_animate.click)
93
94     # === Arrange widgets
95
96     self.setContentsMargins(10, 10, 10, 10)
97
98     self.vlay_left = QVBoxLayout()
99     self.vlay_left.addWidget(self.plot)
100    self.vlay_left.addWidget(self.text_input_expression)
101
102    self.vlay_misc_buttons = QVBoxLayout()
103    self.vlay_misc_buttons.setSpacing(20)
104    self.vlay_misc_buttons.addWidget(self.button_create_polygon)
105    self.vlay_misc_buttons.addWidget(self.button_change_display_settings)
106
107    self.vlay_define_new_matrix = QVBoxLayout()
108    self.vlay_define_new_matrix.setSpacing(20)
109    self.vlay_define_new_matrix.addWidget(self.label_define_new_matrix)
110    self.vlay_define_new_matrix.addWidget(self.button_define_visually)
111    self.vlay_define_new_matrix.addWidget(self.button_define_numerically)
112    self.vlay_define_new_matrix.addWidget(self.button_define_as_rotation)
113    self.vlay_define_new_matrix.addWidget(self.button_define_as_expression)
114
115    self.vlay_render = QVBoxLayout()
116    self.vlay_render.setSpacing(20)
117    self.vlay_render.addWidget(self.button_animate)
118    self.vlay_render.addWidget(self.button_render)
119
120    self.vlay_right = QVBoxLayout()
121    self.vlay_right.setSpacing(50)
122    self.vlay_right.addLayout(self.vlay_misc_buttons)
123    self.vlay_right.addLayout(self.vlay_define_new_matrix)
124    self.vlay_right.addLayout(self.vlay_render)

```

```

125
126     self.hlay_all = QHBoxLayout()
127     self.hlay_all.setSpacing(15)
128     self.hlay_all.addLayout(self.vlay_left)
129     self.hlay_all.addLayout(self.vlay_right)
130
131     self.central_widget = QtWidgets.QWidget()
132     self.central_widget.setLayout(self.hlay_all)
133     self.setCentralWidget(self.central_widget)
134
135     def update_render_buttons(self) -> None:
136         """Enable or disable the render and animate buttons according to the validity of the matrix expression."""
137         valid = self.matrix_wrapper.is_valid_expression(self.text_input_expression.text())
138         self.button_render.setEnabled(valid)
139         self.button_animate.setEnabled(valid)
140
141     def render_expression(self) -> None:
142         """Render the expression in the input box, and then clear the box."""
143         # TODO: Render the expression
144         self.text_input_expression.setText('')
145
146     def animate_expression(self) -> None:
147         """Animate the expression in the input box, and then clear the box."""
148         # TODO: Animate the expression
149         self.text_input_expression.setText('')
150
151
152     def main() -> None:
153         """Run the GUI."""
154         app = QApplication(sys.argv)
155         window = LintransMainWindow()
156         window.show()
157         sys.exit(app.exec_())
158
159
160 if __name__ == '__main__':
161     main()

```




Figure 3.1: The first version of the GUI

A lot of the methods here don't have implementations yet, but they will. This version is just a very early prototype to get a rough draft of the GUI.

I create the widgets and layouts in the constructor as well as configuring all of them. The most important non-constructor method is `update_render_buttons()`. It gets called whenever the text in `text_input_expression` is changed. This happens because we connect it to the `textChanged` signal on line 32.

The big white box here will eventually be replaced with an actual viewport. This is just a prototype.

### 3.2.2 Numerical definition dialog

My next major addition was a dialog that would allow the user to define a matrix numerically.

```

# cedbd3ed126a1183f197c27adf6dabb4e5d301c7
# src/lintrans/gui/dialogs/define_new_matrix.py

1 """The module to provide dialogs for defining new matrices."""
2
3 from numpy import array
4 from PyQt5 import QtGui, QtWidgets
5 from PyQt5.QtWidgets import QDialog, QGridLayout, QHBoxLayout, QVBoxLayout

```



```

6
7 from lintrans.matrices import MatrixWrapper
8
9 ALPHABET_NO_I = 'ABCDEFGHJKLMNPOQRSTUVWXYZ'
10
11
12 def is_float(string: str) -> bool:
13     """Check if a string is a float."""
14     try:
15         float(string)
16         return True
17     except ValueError:
18         return False
19
20
21 class DefineNumericallyDialog(QDialog):
22     """The dialog class that allows the user to define a new matrix numerically."""
23
24     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
25         """Create the dialog, but don't run it yet.
26
27         :param matrix_wrapper: The MatrixWrapper that this dialog will mutate
28         :type matrix_wrapper: MatrixWrapper
29         """
30         super().__init__(*args, **kwargs)
31
32         self.matrix_wrapper = matrix_wrapper
33         self.setWindowTitle('Define a matrix')
34
35         # === Create the widgets
36
37         self.button_confirm = QtWidgets.QPushButton(self)
38         self.button_confirm.setText('Confirm')
39         self.button_confirm.setEnabled(False)
40         self.button_confirm.clicked.connect(self.confirm_matrix)
41         self.button_confirm.setToolTip('Confirm this as the new matrix<br><b>(Ctrl + Enter)</b>')
42
43         QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Return'), self).activated.connect(self.button_confirm.click)
44
45         self.button_cancel = QtWidgets.QPushButton(self)
46         self.button_cancel.setText('Cancel')
47         self.button_cancel.clicked.connect(self.close)
48         self.button_cancel.setToolTip('Cancel this definition<br><b>(Ctrl + Q)</b>')
49
50         QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Q'), self).activated.connect(self.button_cancel.click)
51
52         self.element_tl = QtWidgets.QLineEdit(self)
53         self.element_tl.textChanged.connect(self.update_confirm_button)
54
55         self.element_tr = QtWidgets.QLineEdit(self)
56         self.element_tr.textChanged.connect(self.update_confirm_button)
57
58         self.element_bl = QtWidgets.QLineEdit(self)
59         self.element_bl.textChanged.connect(self.update_confirm_button)
60
61         self.element_br = QtWidgets.QLineEdit(self)
62         self.element_br.textChanged.connect(self.update_confirm_button)
63
64         self.matrix_elements = (self.element_tl, self.element_tr, self.element_bl, self.element_br)
65
66         self.letter_combo_box = QtWidgets.QComboBox(self)
67
68         # Everything except I, because that's the identity
69         for letter in ALPHABET_NO_I:
70             self.letter_combo_box.addItem(letter)
71
72         self.letter_combo_box.activated.connect(self.load_matrix)
73
74         # === Arrange the widgets
75
76         self.setContentsMargins(10, 10, 10, 10)
77
78         self.grid_matrix = QGridLayout()

```

```

79         self.grid_matrix.setSpacing(20)
80         self.grid_matrix.addWidget(self.element_tl, 0, 0)
81         self.grid_matrix.addWidget(self.element_tr, 0, 1)
82         self.grid_matrix.addWidget(self.element_bl, 1, 0)
83         self.grid_matrix.addWidget(self.element_br, 1, 1)
84
85         self.hlay_buttons = QHBoxLayout()
86         self.hlay_buttons.setSpacing(20)
87         self.hlay_buttons.addWidget(self.button_cancel)
88         self.hlay_buttons.addWidget(self.button_confirm)
89
90         self.vlay_right = QVBoxLayout()
91         self.vlay_right.setSpacing(20)
92         self.vlay_right.addLayout(self.grid_matrix)
93         self.vlay_right.addLayout(self.hlay_buttons)
94
95         self.hlay_all = QHBoxLayout()
96         self.hlay_all.setSpacing(20)
97         self.hlay_all.addWidget(self.letter_combo_box)
98         self.hlay_all.addLayout(self.vlay_right)
99
100        self.setLayout(self.hlay_all)
101
102        # Finally, we load the default matrix A into the boxes
103        self.load_matrix(0)
104
105    def update_confirm_button(self) -> None:
106        """Enable the confirm button if there are numbers in every box."""
107        for elem in self.matrix_elements:
108            if elem.text() == '' or not is_float(elem.text()):
109                # If they're not all numbers, then we can't confirm it
110                self.button_confirm.setEnabled(False)
111                return
112
113        # If we didn't find anything invalid
114        self.button_confirm.setEnabled(True)
115
116    def load_matrix(self, index: int) -> None:
117        """If the selected matrix is defined, load it into the boxes."""
118        matrix = self.matrix_wrapper[ALPHABET_NO_I[index]]
119
120        if matrix is None:
121            for elem in self.matrix_elements:
122                elem.setText('')
123
124        else:
125            self.element_tl.setText(str(matrix[0][0]))
126            self.element_tr.setText(str(matrix[0][1]))
127            self.element_bl.setText(str(matrix[1][0]))
128            self.element_br.setText(str(matrix[1][1]))
129
130        self.update_confirm_button()
131
132    def confirm_matrix(self) -> None:
133        """Confirm the inputted matrix and assign it to the name."""
134        letter = self.letter_combo_box.currentText()
135        matrix = array([
136            [float(self.element_tl.text()), float(self.element_tr.text())],
137            [float(self.element_bl.text()), float(self.element_br.text())]
138        ])
139
140        self.matrix_wrapper[letter] = matrix
141        self.close()

```




Figure 3.2: The first version of the numerical definition dialog

When I add more definition dialogs, I will factor out a superclass, but this is just a prototype to make sure it all works as intended.

Hopefully the methods are relatively self explanatory, but they're just utility methods to update the GUI when things are changed. We connect the `QLineEdit` widgets to the `update_confirm_button()` slot to make sure the confirm button is always up to date.

The `confirm_matrix()` method just updates the instance's matrix wrapper with the new matrix. We pass a reference to the `LintransMainWindow` instance's matrix wrapper when we open the dialog, so we're just updating the referenced object directly.

In the `LintransMainWindow` class, we're just connecting a lambda slot to the button so that it opens the dialog, as seen here:

```
# cedbd3ed126a1183f197c27adf6dabb4e5d301c7
# src/lintrans/gui/main_window.py

66 self.button_define_numerically.clicked.connect(
67     lambda: DefineNumericallyDialog(self.matrix_wrapper, self).exec()
68 )
```

### 3.2.3 More definition dialogs

I then factored out the constructor into a `DefinedDialog` superclass so that I could easily create other definition dialogs.

```
# 5d04fb7233a03d0cd8fa0768f6387c6678da9df3
# src/lintrans/gui/dialogs/define_new_matrix.py

22 class DefinedDialog(QDialog):
23     """A superclass for definitions dialogs."""
24
25     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
26         """Create the dialog, but don't run it yet.
27
28         :param matrix_wrapper: The MatrixWrapper that this dialog will mutate
29         :type matrix_wrapper: MatrixWrapper
30         """
31         super().__init__(*args, **kwargs)
32
33         self.matrix_wrapper = matrix_wrapper
34         self.setWindowTitle('Define a matrix')
35
36         # === Create the widgets
37
38         self.button_confirm = QtWidgets.QPushButton(self)
39         self.button_confirm.setText('Confirm')
40         self.button_confirm.setEnabled(False)
41         self.button_confirm.clicked.connect(self.confirm_matrix)
42         self.button_confirm.setToolTip('Confirm this as the new matrix<br><b>(Ctrl + Enter)</b>')
43         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self.button_confirm.click)
44
45         self.button_cancel = QtWidgets.QPushButton(self)
46         self.button_cancel.setText('Cancel')
47         self.button_cancel.clicked.connect(self.close)
48         self.button_cancel.setToolTip('Cancel this definition<br><b>(Ctrl + Q)</b>')
49         QShortcut(QKeySequence('Ctrl+Q'), self).activated.connect(self.button_cancel.click)
50
51         self.label_equals = QtWidgets.QLabel()
```

```

52         self.label_equals.setText('=')
53
54         self.letter_combo_box = QtWidgets.QComboBox(self)
55
56         # Everything except I, because that's the identity
57         for letter in ALPHABET_NO_I:
58             self.letter_combo_box.addItem(letter)
59
60         self.letter_combo_box.activated.connect(self.load_matrix)

```

This superclass just has a constructor that subclasses can use. When I added the `DefineAsARotationDialog` class, I also moved the cancel and confirm buttons into the constructor and added abstract methods that all dialog subclasses must implement.

```

# 0d534c35c6a4451e317d41a0d2b3ecb17827b45f
# src/lintrans/gui/dialogs/define_new_matrix.py

61         # === Arrange the widgets
62
63         self.setContentsMargins(10, 10, 10, 10)
64
65         self.horizontal_spacer = QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum)
66
67         self.hlay_buttons = QHBoxLayout()
68         self.hlay_buttons.setSpacing(20)
69         self.hlay_buttons.addItem(self.horizontal_spacer)
70         self.hlay_buttons.addWidget(self.button_cancel)
71         self.hlay_buttons.addWidget(self.button_confirm)
72
73         @property
74         def selected_letter(self) -> str:
75             """The letter currently selected in the combo box."""
76             return self.letter_combo_box.currentText()
77
78         @abc.abstractmethod
79         def update_confirm_button(self) -> None:
80             """Enable the confirm button if it should be enabled."""
81             ...
82
83         @abc.abstractmethod
84         def confirm_matrix(self) -> None:
85             """Confirm the inputted matrix and assign it.
86
87             This should mutate self.matrix_wrapper and then call self.accept().
88             """
89             ...

```

I then added the class for the rotation definition dialog.

```

# 0d534c35c6a4451e317d41a0d2b3ecb17827b45f
# src/lintrans/gui/dialogs/define_new_matrix.py

182 class DefineAsARotationDialog(DefinedDialog):
183     """The dialog that allows the user to define a new matrix as a rotation."""
184
185     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
186         """Create the dialog, but don't run it yet."""
187         super().__init__(matrix_wrapper, *args, **kwargs)
188
189         # === Create the widgets
190
191         self.label_equals.setText('= rot(')
192
193         self.text_angle = QtWidgets.QLineEdit(self)
194         self.text_angle.setPlaceholderText('angle')
195         self.text_angle.textChanged.connect(self.update_confirm_button)
196
197         self.label_close_paren = QtWidgets.QLabel(self)

```

```

198         self.label_close_paren.setText('')
199
200         self.checkbox_radians = QtWidgets.QCheckBox(self)
201         self.checkbox_radians.setText('Radians')
202
203         # === Arrange the widgets
204
205         self.hlay_checkbox_and_buttons = QHBoxLayout()
206         self.hlay_checkbox_and_buttons.setSpacing(20)
207         self.hlay_checkbox_and_buttons.addWidget(self.checkbox_radians)
208         self.hlay_checkbox_and_buttons.addItem(self.horizontal_spacer)
209         self.hlay_checkbox_and_buttons.addLayout(self.hlay_buttons)
210
211         self.hlay_definition = QHBoxLayout()
212         self.hlay_definition.addWidget(self.letter_combo_box)
213         self.hlay_definition.addWidget(self.label_equals)
214         self.hlay_definition.addWidget(self.text_angle)
215         self.hlay_definition.addWidget(self.label_close_paren)
216
217         self.vlay_all = QVBoxLayout()
218         self.vlay_all.setSpacing(20)
219         self.vlay_all.addLayout(self.hlay_definition)
220         self.vlay_all.addLayout(self.hlay_checkbox_and_buttons)
221
222         self.setLayout(self.vlay_all)
223
224     def update_confirm_button(self) -> None:
225         """Enable the confirm button if there is a valid float in the angle box."""
226         self.button_confirm.setEnabled(is_float(self.text_angle.text()))
227
228     def confirm_matrix(self) -> None:
229         """Confirm the inputted matrix and assign it."""
230         self.matrix_wrapper[self.selected_letter] = create_rotation_matrix(
231             float(self.text_angle.text()),
232             degrees=not self.checkbox_radians.isChecked()
233         )
234         self.accept()

```

This dialog class just overrides the abstract methods of the superclass with its own implementations. This will be the pattern that all of the definition dialogs will follow.

It has a checkbox for radians, since this is supported in `create_rotation_matrix()`, but the textbox only supports numbers, so the user would have to calculate some multiple of  $\pi$  and paste in several decimal places. I expect people to only use degrees, because these are easier to use.




Figure 3.3: The first version of the rotation definition dialog

I also then implemented a simple `DefineAsAnExpressionDialog`, which evaluates a given expression in the current `MatrixWrapper` context and assigns the result to the given matrix name.

```

# d5f930e15c3c8798d4990486532da46e926a6cb9
# src/lintrans/gui/dialogs/define_new_matrix.py

241 class DefineAsAnExpressionDialog(DefineDialog):
242     """The dialog that allows the user to define a matrix as an expression."""
243
244     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
245         """Create the dialog, but don't run it yet."""
246         super().__init__(matrix_wrapper, *args, **kwargs)
247
248         self.setMinimumWidth(450)
249
250         # === Create the widgets
251
252         self.text_box_expression = QtWidgets.QLineEdit(self)

```

```

253     self.text_box_expression.setPlaceholderText('Enter matrix expression...')
254     self.text_box_expression.textChanged.connect(self.update_confirm_button)
255
256     # === Arrange the widgets
257
258     self.hlay_definition.addWidget(self.text_box_expression)
259
260     self.vlay_all = QVBoxLayout()
261     self.vlay_all.setSpacing(20)
262     self.vlay_all.addLayout(self.hlay_definition)
263     self.vlay_all.addLayout(self.hlay_buttons)
264
265     self.setLayout(self.vlay_all)
266
267     def update_confirm_button(self) -> None:
268         """Enable the confirm button if the expression is valid."""
269         self.button_confirm.setEnabled(
270             self.matrix_wrapper.is_valid_expression(self.text_box_expression.text())
271         )
272
273     def confirm_matrix(self) -> None:
274         """Evaluate the matrix expression and assign its value to the chosen matrix."""
275         self.matrix_wrapper[self.selected_letter] = \
276             self.matrix_wrapper.evaluate_expression(self.text_box_expression.text())
277         self.accept()

```

My next dialog that I wanted to implement was a visual definition dialog, which would allow the user to drag around the basis vectors to define a transformation. However, I would first need to create the `lintrans.gui.plots` package to allow for actually visualizing matrices and transformations.

### 3.3 Visualizing matrices

#### 3.3.1 Asking strangers on the internet for help

After creating most of the GUI skeleton, I wanted to build the viewport. Unfortunately, I had no idea what I was doing.

While looking through the PyQt5 docs, I found a pretty comprehensive explanation of the Qt5 ‘Graphics View Framework’[13], which seemed pretty good, but not really what I was looking for. I wanted a way to easily draw lots of straight, parallel lines. This framework seemed more focussed on manipulating objects on a canvas, almost like sprites. I knew of a different Python library called `matplotlib`, which has various backends available. I learned that it could be embedded in a standard PyQt5 GUI, so I started doing some research.

I didn’t get very far with `matplotlib`. I hadn’t used it much before and it’s designed for visualizing data. It can draw manually defined straight lines on a canvas, but that’s not what it’s designed for and it’s not very good at it. Thankfully, my horrific `matplotlib` code has been lost to time. I used the `Qt5Agg` backend from `matplotlib` to create a custom PyQt5 widget for the GUI and I could graph randomly generated data with it after following a tutorial[12].

I realised that I wasn’t going to get very far with `matplotlib`, but I didn’t know what else to do. I couldn’t find any relevant examples on the internet, so I decided to post a question on a forum myself. I’d had experience with StackOverflow and its unfriendly community before, so I decided to ask the `r/learnpython` subreddit[3].

I only got one response, but it was incredibly helpful. The person told me that if I couldn’t find an easy way to do what I wanted, I could write a custom PyQt5 widget. I knew this was possible with a class that just inherited from `QWidget`, but had no idea how to actually make something useful. Thankfully, this person provided a link to a GitLab repository of theirs, where they had multiple examples of custom widgets with PyQt5[4].

When looking through this repo, I found out how to draw on a widget like a simple canvas. All I have

to do is override the `paintEvent()` method and use a `QPainter` object to draw on the widget. I used this knowledge to start creating the actual viewport for the GUI, starting with the background axes.

### 3.3.2 Creating the plots package

Initially, the `lintrans.gui.plots` package just has some classes for widgets. `TransformationPlotWidget` acts as a base class and then `ViewTransformationWidget` acts as a wrapper. I will expand this class in the future.

```
# 4af63072b383dc9cef9adbb8900323aa007e7f26
# src/lintrans/gui/plots/plot_widget.py

1  """This module provides the basic classes for plotting transformations."""
2
3  from __future__ import annotations
4
5  from PyQt5.QtCore import Qt
6  from PyQt5.QtGui import QColor, QPainter, QPaintEvent, QPen
7  from PyQt5.QtWidgets import QWidget
8
9
10 class TransformationPlotWidget(QWidget):
11     """An abstract superclass for plot widgets.
12
13     This class provides a background (untransformed) plane, and all the backend
14     details for a Qt application, but does not provide useful functionality. To
15     be useful, this class must be subclassed and behaviour must be implemented
16     by the subclass.
17
18     .. warning:: This class should never be directly instantiated, only subclassed.
19
20     .. note::
21         I would make this class have ``metaclass=abc.ABCMeta``, but I can't because it subclasses ``QWidget``,
22         and a every superclass of a class must have the same metaclass, and ``QWidget`` is not an abstract class.
23     """
24
25     def __init__(self, *args, **kwargs):
26         """Create the widget, passing ``*args`` and ``**kwargs`` to the superclass constructor (``QWidget``)."""
27         super().__init__(*args, **kwargs)
28
29         self.setAutoFillBackground(True)
30
31         # Set the background to white
32         palette = self.palette()
33         palette.setColor(self.backgroundRole(), Qt.white)
34         self.setPalette(palette)
35
36         # Set the grid colour to grey and the axes colour to black
37         self.grid_colour = QColor(128, 128, 128)
38         self.axes_colour = QColor(0, 0, 0)
39
40         self.grid_spacing: int = 50
41         self.line_width: float = 0.4
42
43     @property
44     def w(self) -> int:
45         """Return the width of the widget."""
46         return self.size().width()
47
48     @property
49     def h(self) -> int:
50         """Return the height of the widget."""
51         return self.size().height()
52
53     def paintEvent(self, e: QPaintEvent):
54         """Handle a ``QPaintEvent`` by drawing the widget."""
55         qp = QPainter()
56         qp.begin(self)
57         self.draw_widget(qp)
```

```

58         qp.end()
59
60     def draw_widget(self, qp: QPainter):
61         """Draw the grid and axes in the widget."""
62         qp.setRenderHint(QPainter.Antialiasing)
63         qp.setBrush(Qt.NoBrush)
64
65         # Draw the grid
66         qp.setPen(QPen(self.grid_colour, self.line_width))
67
68         # We draw the background grid, centered in the middle
69         # We deliberately exclude the axes - these are drawn separately
70         for x in range(self.w // 2 + self.grid_spacing, self.w, self.grid_spacing):
71             qp.drawLine(x, 0, x, self.h)
72             qp.drawLine(self.w - x, 0, self.w - x, self.h)
73
74         for y in range(self.h // 2 + self.grid_spacing, self.h, self.grid_spacing):
75             qp.drawLine(0, y, self.w, y)
76             qp.drawLine(0, self.h - y, self.w, self.h - y)
77
78         # Now draw the axes
79         qp.setPen(QPen(self.axes_colour, self.line_width))
80         qp.drawLine(self.w // 2, 0, self.w // 2, self.h)
81         qp.drawLine(0, self.h // 2, self.w, self.h // 2)
82
83
84     class ViewTransformationWidget(TransformationPlotWidget):
85         """This class is used to visualise matrices as transformations."""
86
87         def __init__(self, *args, **kwargs):
88             """Create the widget, passing ``*args`` and ``**kwargs`` to the superclass constructor."""
89             super().__init__(*args, **kwargs)

```




Figure 3.4: The GUI with background axes

The meat of this class is the `draw_widget()` method. Right now, this method only draws the background axes. My next step is to implement basis vector attributes and draw them in `draw_widget()`. After changing the the `plot` attribute in `LintransMainWindow` to an instance of `ViewTransformationWidget`, the plot was visible in the GUI.

I then refactored the code slightly to rename `draw_widget()` to `draw_background()` and then call it from the `paintEvent()` method in `ViewTransformationWidget`.

### 3.3.3 Implementing basis vectors

My first step in implementing basis vectors was to add some utility methods to convert between coordinate systems. The matrices are using Cartesian coordinates with  $(0,0)$  in the middle, positive  $x$  going to the right, and positive  $y$  going up. However, Qt5 is using standard computer graphics coordinates, with  $(0,0)$  in the top left, positive  $x$  going to the right, and positive  $y$  going down. I needed a way to convert Cartesian ‘grid’ coordinates to Qt5 ‘canvas’ coordinates, so I wrote some little utility methods.

```

# 1fa7e1c61d61cb6aeff773b9698541f82fee39ea
# src/lintrans/gui/plots/plot_widget.py

45     @property
46     def origin(self) -> tuple[int, int]:
47         """Return the canvas coords of the origin."""

```



```

48         return self.width() // 2, self.height() // 2
49
50     def trans_x(self, x: float) -> int:
51         """Transform an x coordinate from grid coords to canvas coords."""
52         return int(self.origin[0] + x * self.grid_spacing)
53
54     def trans_y(self, y: float) -> int:
55         """Transform a y coordinate from grid coords to canvas coords."""
56         return int(self.origin[1] - y * self.grid_spacing)
57
58     def trans_coords(self, x: float, y: float) -> tuple[int, int]:
59         """Transform a coordinate in grid coords to canvas coords."""
60         return self.trans_x(x), self.trans_y(y)

```

Once I had a way to convert coordinates, I could add the basis vectors themselves. I did this by creating attributes for the points in the constructor and creating a `transform_by_matrix()` method to change these point attributes accordingly.

```

# 37e7c208a33d7cbbc8e0bb6c94cd889e2918c605
# src/lintrans/gui/plots/plot_widget.py

92 class ViewTransformationWidget(TransformationPlotWidget):
93     """This class is used to visualise matrices as transformations."""
94
95     def __init__(self, *args, **kwargs):
96         """Create the widget, passing ``*args`` and ``**kwargs`` to the superclass constructor."""
97         super().__init__(*args, **kwargs)
98
99         self.point_i: tuple[float, float] = (1., 0.)
100        self.point_j: tuple[float, float] = (0., 1.)
101
102        self.colour_i = QColor(37, 244, 15)
103        self.colour_j = QColor(8, 8, 216)
104
105        self.width_vector_line = 1
106        self.width_transformed_grid = 0.6
107
108    def transform_by_matrix(self, matrix: MatrixType) -> None:
109        """Transform the plane by the given matrix."""
110        self.point_i = (matrix[0][0], matrix[1][0])
111        self.point_j = (matrix[0][1], matrix[1][1])
112        self.update()

```

I also created a `draw_transformed_grid()` method which gets called in `paintEvent()`.

```

# 37e7c208a33d7cbbc8e0bb6c94cd889e2918c605
# src/lintrans/gui/plots/plot_widget.py

122    def draw_transformed_grid(self, painter: QPainter) -> None:
123        """Draw the transformed version of the grid, given by the unit vectors."""
124        # Draw the unit vectors
125        painter.setPen(QPen(self.colour_i, self.width_vector_line))
126        painter.drawLine(*self.origin, *self.trans_coords(*self.point_i))
127        painter.setPen(QPen(self.colour_j, self.width_vector_line))
128        painter.drawLine(*self.origin, *self.trans_coords(*self.point_j))

```

I then changed the `render_expression()` method in `LintransMainWindow` to call this new `transform_by_matrix()` method.

```

# 37e7c208a33d7cbbc8e0bb6c94cd889e2918c605
# src/lintrans/gui/main_window.py

229    def render_expression(self) -> None:
230        """Render the expression in the input box, and then clear the box."""
231        self.plot.transform_by_matrix(

```

```

232         self.matrix_wrapper.evaluate_expression(
233             self.lineedit_expression_box.text()
234         )
235     )

```

Testing this new code shows that it works well.




Figure 3.5: Basis vectors drawn for a  $45^\circ$  rotation

### 3.3.4 Drawing the transformed grid

After drawing the basis vectors, I wanted to draw the transformed version of the grid. I first created a `grid_corner()` utility method to return the grid coordinates of the top right corner of the canvas. This allows me to find the bounding box in which to draw the grid lines.

```

# 2ade98ac28d1c3f6691e4afa819142a3ab8e9fd9
# src/lintrans/gui/plots/plot_widget.py

64     def grid_corner(self) -> tuple[float, float]:
65         """Return the grid coords of the top right corner."""
66         return self.width() / (2 * self.grid_spacing), self.height() / (2 * self.grid_spacing)

```

I then created a `draw_parallel_lines()` method that would fill the bounding box with a set of lines parallel to a given vector with spacing defined by the intersection with a given point.

```

# 2ade98ac28d1c3f6691e4afa819142a3ab8e9fd9
# src/lintrans/gui/plots/plot_widget.py

126     def draw_parallel_lines(self, painter: QPainter, vector: tuple[float, float], point: tuple[float, float]) ->
127         None:
128         """Draw a set of grid lines parallel to `vector` intersecting `point`."""
129         max_x, max_y = self.grid_corner()
130         vector_x, vector_y = vector
131         point_x, point_y = point
132
133         if vector_x == 0:
134             painter.drawLine(self.trans_x(0), 0, self.trans_x(0), self.height())

```

```

135         for i in range(int(max_x / point_x)):
136             painter.drawLine(
137                 self.trans_x((i + 1) * point_x),
138                 0,
139                 self.trans_x((i + 1) * point_x),
140                 self.height()
141             )
142             painter.drawLine(
143                 self.trans_x(-1 * (i + 1) * point_x),
144                 0,
145                 self.trans_x(-1 * (i + 1) * point_x),
146                 self.height()
147             )
148
149     elif vector_y == 0:
150         painter.drawLine(0, self.trans_y(0), self.width(), self.trans_y(0))
151
152     for i in range(int(max_y / point_y)):
153         painter.drawLine(
154             0,
155             self.trans_y((i + 1) * point_y),
156             self.width(),
157             self.trans_y((i + 1) * point_y)
158         )
159         painter.drawLine(
160             0,
161             self.trans_y(-1 * (i + 1) * point_y),
162             self.width(),
163             self.trans_y(-1 * (i + 1) * point_y)
164         )

```

I then called this method from `draw_transformed_grid()`.

```

# 2ade98ac28d1c3f6691e4afa819142a3ab8e9fd9
# src/lintrans/gui/plots/plot_widget.py

166     def draw_transformed_grid(self, painter: QPainter) -> None:
167         """Draw the transformed version of the grid, given by the unit vectors."""
168         # Draw the unit vectors
169         painter.setPen(QPen(self.colour_i, self.width_vector_line))
170         painter.drawLine(*self.origin, *self.trans_coords(*self.point_i))
171         painter.setPen(QPen(self.colour_j, self.width_vector_line))
172         painter.drawLine(*self.origin, *self.trans_coords(*self.point_j))
173
174         # Draw all the parallel lines
175         painter.setPen(QPen(self.colour_i, self.width_transformed_grid))
176         self.draw_parallel_lines(painter, self.point_i, self.point_j)
177         painter.setPen(QPen(self.colour_j, self.width_transformed_grid))
178         self.draw_parallel_lines(painter, self.point_j, self.point_i)

```

This worked quite well when the matrix involved no rotation, as seen in Figure ??, but this didn't work with rotation. When trying `rot(45)` for example, it looked the same as in Figure 3.5.

Also, the vectors aren't particularly clear. They'd be much better with arrowheads on their tips, but this is just a prototype. The arrowheads will come later.

My next step was to make the transformed grid lines work with rotations.




Figure 3.6: Parallel lines being drawn for matrix  $1.2\mathbf{I}$

```

# 7dfe1e24729562501e2fd88a839dca6b653a3375
# src/lintrans/gui/plots/plot_widget.py

126 def draw_parallel_lines(self, painter: QPainter, vector: tuple[float, float], point: tuple[float, float]) -> None:
127     """Draw a set of grid lines parallel to ``vector`` intersecting ``point``."""
128     max_x, max_y = self.grid_corner()
129     vector_x, vector_y = vector
130     point_x, point_y = point
131
132     print(max_x, max_y, vector_x, vector_y, point_x, point_y)
133
134     # We want to use  $y = mx + c$  but  $m = y / x$  and if either of those are 0, then this
135     # equation is harder to work with, so we deal with these edge cases first
136     if abs(vector_x) < 1e-12 and abs(vector_y) < 1e-12:
137         # If both components of the vector are practically 0, then we can't render any grid lines
138         return
139
140     elif abs(vector_x) < 1e-12:
141         painter.drawLine(self.trans_x(0), 0, self.trans_x(0), self.height())
142
143         for i in range(abs(int(max_x / point_x))):
144             painter.drawLine(
145                 self.trans_x((i + 1) * point_x),
146                 0,
147                 self.trans_x((i + 1) * point_x),
148                 self.height()
149             )
150             painter.drawLine(
151                 self.trans_x(-1 * (i + 1) * point_x),
152                 0,
153                 self.trans_x(-1 * (i + 1) * point_x),
154                 self.height()
155             )
156
157     elif abs(vector_y) < 1e-12:
158         painter.drawLine(0, self.trans_y(0), self.width(), self.trans_y(0))
159
160         for i in range(abs(int(max_y / point_y))):
161             painter.drawLine(
162                 0,
163                 self.trans_y((i + 1) * point_y),
164                 self.width(),
165                 self.trans_y((i + 1) * point_y)
166             )
167             painter.drawLine(
168                 0,
169                 self.trans_y(-1 * (i + 1) * point_y),
170                 self.width(),
171                 self.trans_y(-1 * (i + 1) * point_y)
172             )
173
174     else: # If the line is not horizontal or vertical, then we can use  $y = mx + c$ 
175         m = vector_y / vector_x
176         c = point_y - m * point_x
177
178         # For  $c = 0$ 
179         painter.drawLine(
180             *self.trans_coords(
181                 -1 * max_x,
182                 m * -1 * max_x
183             ),
184             *self.trans_coords(
185                 max_x,
186                 m * max_x
187             )
188         )
189
190         # Count up how many multiples of  $c$  we can have without wasting time rendering lines off screen
191         multiples_of_c: int = 0
192         ii: int = 1
193         while True:
194             y1 = m * max_x + ii * c
195             y2 = -1 * m * max_x + ii * c

```

```

196         if y1 < max_y or y2 < max_y:
197             multiples_of_c += 1
198             ii += 1
199
200
201         else:
202             break
203
204     # Once we know how many lines we can draw, we just draw them all
205     for i in range(1, multiples_of_c + 1):
206         painter.drawLine(
207             *self.trans_coords(
208                 -1 * max_x,
209                 m * -1 * max_x + i * c
210             ),
211             *self.trans_coords(
212                 max_x,
213                 m * max_x + i * c
214             )
215         )
216         painter.drawLine(
217             *self.trans_coords(
218                 -1 * max_x,
219                 m * -1 * max_x - i * c
220             ),
221             *self.trans_coords(
222                 max_x,
223                 m * max_x - i * c
224             )
225         )

```

This code checks if  $x$  or  $y$  is zero<sup>10</sup> and if they're not, then we have to use the standard straight line equation  $y = mx + c$  to create parallel lines. We find our value of  $m$  and then iterate through all the values of  $c$  that keep the line within the bounding box.




Figure 3.7: An example of a 20° rotation

There are some serious logical errors in this code. It works fine for things like `3rot(45)` or `0.5rot(20)`, but something like `rot(115)` will leave the program hanging indefinitely.

In fact, this code only works for rotations between 0° and 90°, and will hang forever when given a matrix like  $\begin{pmatrix} 12 & 4 \\ -2 & 3 \end{pmatrix}$ , because it's just not very good.

I will fix these issues in the future, but it works somewhat decently, so I decided to do animation next, because that sounded more fun.

### 3.3.5 Implementing animation

Now that I had a very crude renderer, I could create a method to animate a matrix. Eventually I want to be able to apply a given matrix to the currently rendered scene and animate between them. However, I wanted to start simple by animating from the identity to the given matrix.

```

# 829a130af5aee9819bf0269c03ecfb20bec1a108
# src/lintrans/gui/main_window.py

238     def animate_expression(self) -> None:
239         """Animate the expression in the input box, and then clear the box."""

```

<sup>10</sup>We actually check if they're less than  $10^{-12}$  to allow for floating point errors

```

240     self.button_render.setEnabled(False)
241     self.button_animate.setEnabled(False)
242
243     matrix = self.matrix_wrapper.evaluate_expression(self.lineEdit_expression_box.text())
244     matrix_move = matrix - self.matrix_wrapper['I']
245     steps: int = 100
246
247     for i in range(0, steps + 1):
248         self.plot.visualize_matrix_transformation(
249             self.matrix_wrapper['I'] + (i / steps) * matrix_move
250         )
251
252         self.update()
253         self.repaint()
254
255         time.sleep(0.01)
256
257     self.button_render.setEnabled(False)
258     self.button_animate.setEnabled(False)

```

This code creates the `matrix_move` variable and adds scaled versions of it to the identity matrix and renders that each frame. It's simple, but it works well for this simple use case. Unfortunately, it's very hard to show off an animation in a PDF, since all these images are static. The git commit hashes are included in the code snippets if you want to clone the repo[2], checkout this commit, and run it yourself if you want.

### 3.3.6 Preserving determinants

Ignoring the obvious flaw with not being able to render transformations with a more than 90° rotation, the animations don't respect determinants. When rotating 90°, the determinant changes during the animation, even though we're going from a determinant 1 matrix (the identity) to another determinant 1 matrix. This is because we're just moving each vector to its new position in a straight line. I want to animate in a way that smoothly transitions the determinant.




Figure 3.8: What we would expect halfway through a 90° rotation




Figure 3.9: What we actually get halfway through a 90° rotation

In order to smoothly animate the determinant, I had to do some maths. I first defined the matrix  $\mathbf{A}$  to be equivalent to the `matrix_move` variable from before - the target matrix minus the identity, scaled by the proportion. I then wanted to normalize  $\mathbf{A}$  so that it had a determinant of 1 so that I could scale it up with the `proportion` variable through the animation.

I think I first tried just multiplying  $\mathbf{A}$  by  $\frac{1}{\det(\mathbf{A})}$  but that didn't work, so I googled it. I found a post[11] on ResearchGate about the topic, and thanks to a very helpful comment from Jeffrey L Stuart, I learned that for a  $2 \times 2$  matrix  $\mathbf{A}$  and a scalar  $c$ ,  $\det(c\mathbf{A}) = c^2 \det(\mathbf{A})$ .

I wanted a  $c$  such that  $\det(c\mathbf{A}) = 1$ . Therefore  $c = \frac{1}{\sqrt{|\det(\mathbf{A})|}}$ . I then defined matrix  $\mathbf{B}$  to be  $c\mathbf{A}$ .

Then I wanted to scale this normalized matrix  $\mathbf{B}$  to have the same determinant as the target matrix  $\mathbf{T}$  using some scalar  $d$ . We know that  $\det(d\mathbf{B}) = d^2 \det(\mathbf{B}) = \det(\mathbf{T})$ . We can just rearrange to find  $d$  and get  $d = \sqrt{\frac{\det(\mathbf{T})}{\det(\mathbf{B})}}$ . But  $\mathbf{B}$  is defined so that  $\det(\mathbf{B}) = 1$ , so we can get  $d = \sqrt{|\det(\mathbf{T})|}$ .

However, we want to scale this over time with our proportion variable  $p$ , so our final scalar  $s = 1 + p(\sqrt{|\det(\mathbf{T})|} - 1)$ . We define a matrix  $\mathbf{C} = s\mathbf{B}$  and render  $\mathbf{C}$  each frame. When in code form, this is the following:

```
# 6ff49450d8438ea2b2e7d2a97125dc518e648bc5
# src/lintrans/gui/main_window.py

245     # Get the target matrix and it's determinant
246     matrix_target = self.matrix_wrapper.evaluate_expression(self.linedit_expression_box.text())
247     det_target = linalg.det(matrix_target)
248
249     identity = self.matrix_wrapper['I']
250     steps: int = 100
251
252     for i in range(0, steps + 1):
253         # This proportion is how far we are through the loop
254         proportion = i / steps
255
256         # matrix_a is the identity plus some part of the target, scaled by the proportion
257         # If we just used matrix_a, then things would animate, but the determinants would be weird
258         matrix_a = identity + proportion * (matrix_target - identity)
259
260         # So to fix the determinant problem, we get the determinant of matrix_a and use it to normalise
261         det_a = linalg.det(matrix_a)
262
263         # For a 2x2 matrix A and a scalar c, we know that det(cA) = c^2 det(A)
264         # We want B = cA such that det(B) = 1, so then we can scale it with the animation
265         # So we get c^2 det(A) = 1 => c = sqrt(1 / abs(det(A)))
266         # Then we scale A down to get a determinant of 1, and call that matrix_b
267         if det_a == 0:
268             c = 0
269         else:
270             c = np.sqrt(1 / abs(det_a))
271
272         matrix_b = c * matrix_a
273
274         # matrix_c is the final matrix that we transform by
275         # It's B, but we scale it up over time to have the target determinant
276
277         # We want some C = dB such that det(C) is some target determinant T
278         # det(dB) = d^2 det(B) = T => d = sqrt(abs(T / det(B)))
279         # But we defined B to have det 1, so we can ignore it there
280
281         # We're also subtracting 1 and multiplying by the proportion and then adding one
282         # This just scales the determinant along with the animation
283         scalar = 1 + proportion * (np.sqrt(abs(det_target)) - 1)
284
285         matrix_c = scalar * matrix_b
286
287         self.plot.visualize_matrix_transformation(matrix_c)
288
289         self.repaint()
290         time.sleep(0.01)
```

Unfortunately, the system I use to render matrices is still quite bad at its job. This makes it hard to test properly. But, transformations like `2rot(90)` work exactly as expected, which is very good.

## 3.4 Improving the GUI

### 3.4.1 Fixing rendering

Now that I had the basics of matrix visualization sorted, I wanted to make the GUI and UX better. My first step was overhauling the rendering code to make it actually work with rotations of more than 90°.

I narrowed down the issue with PyCharm's debugger and found that the loop in `VectorGridPlot.draw_parallel_lines()` was looping forever if it tried to do anything outside of the top right quadrant. To fix this, I decided to instead delegate this task of drawing a set of oblique lines to a separate method, and work on that instead.

```
# cf05e09e5ebb6ea7a96db8660d0d8de6b946490a
# src/lintrans/gui/plots/classes.py

203         else: # If the line is not horizontal or vertical, then we can use y = mx + c
204             m = vector_y / vector_x
205             c = point_y - m * point_x
206
207             # For c = 0
208             painter.drawLine(
209                 *self.trans_coords(
210                     -1 * max_x,
211                     m * -1 * max_x
212                 ),
213                 *self.trans_coords(
214                     max_x,
215                     m * max_x
216                 )
217             )
218
219             # We keep looping and increasing the multiple of c until we stop drawing lines on the canvas
220             multiple_of_c = 1
221             while self.draw_pair_of_oblique_lines(painter, m, multiple_of_c * c):
222                 multiple_of_c += 1
```

This separation of functionality made designing and debugging this part of the solution much easier. The `draw_pair_of_oblique_lines()` method looked like this:

```
# cf05e09e5ebb6ea7a96db8660d0d8de6b946490a
# src/lintrans/gui/plots/classes.py

224     def draw_pair_of_oblique_lines(self, painter: QPainter, m: float, c: float) -> bool:
225         """Draw a pair of oblique lines, using the equation y = mx + c.
226
227         This method just calls :meth:`draw_oblique_line` with ``c`` and ``-c``,
228         and returns True if either call returned True.
229
230         :param QPainter painter: The ``QPainter`` object to use for drawing the vectors and grid lines
231         :param float m: The gradient of the lines to draw
232         :param float c: The y-intercept of the lines to draw. We use the positive and negative versions
233         :returns bool: Whether we were able to draw any lines on the canvas
234         """
235         return any([
236             self.draw_oblique_line(painter, m, c),
237             self.draw_oblique_line(painter, m, -c)
238         ])
239
240     def draw_oblique_line(self, painter: QPainter, m: float, c: float) -> bool:
241         """Draw an oblique line, using the equation y = mx + c.
242
243         We only draw the part of the line that fits within the canvas, returning True if
244         we were able to draw a line within the boundaries, and False if we couldn't draw a line
245
246         :param QPainter painter: The ``QPainter`` object to use for drawing the vectors and grid lines
```



```

247 :param float m: The gradient of the line to draw
248 :param float c: The y-intercept of the line to draw
249 :returns bool: Whether we were able to draw a line on the canvas
250 """
251 max_x, max_y = self.grid_corner()
252
253 # These variable names are shortened for convenience
254 # myi is max_y_intersection, mmyi is minus_max_y_intersection, etc.
255 myi = (max_y - c) / m
256 mmyi = (-max_y - c) / m
257 mxi = max_x * m + c
258 mmxi = -max_x * m + c
259
260 # The inner list here is a list of coords, or None
261 # If an intersection fits within the bounds, then we keep its coord,
262 # else it is None, and then gets discarded from the points list
263 # By the end, points is a list of two coords, or an empty list
264 points: list[tuple[float, float]] = [
265     x for x in [
266         (myi, max_y) if -max_x < myi < max_x else None,
267         (mmyi, -max_y) if -max_x < mmyi < max_x else None,
268         (max_x, mxi) if -max_y < mxi < max_y else None,
269         (-max_x, mmxi) if -max_y < mmxi < max_y else None
270     ] if x is not None
271 ]
272
273 # If no intersections fit on the canvas
274 if len(points) < 2:
275     return False
276
277 # If we can, then draw the line
278 else:
279     painter.drawLine(
280         *self.trans_coords(*points[0]),
281         *self.trans_coords(*points[1])
282     )
283     return True

```

To illustrate what this code is doing, I'll use a diagram.




Figure 3.10: Two example lines and the viewport box




Figure 3.11: A demonstration of the new oblique lines system.

The red box represents the viewport of the GUI. The dashed lines represent the extensions of the red box. For a given line we want to draw, we first want to find where it intersects these orthogonal lines. Any oblique line will intersect each of these lines exactly once. This is what the myi, mmyi, mxi, and

`mmxi` variables represent. The value of `myi` is the  $x$  value where the line intersects the maximum  $y$  line, for example.

In the case of the blue line, all 4 intersection points are outside the bounds of the box, whereas the green line intersects with the box, as shown with the crosses. We use a list comprehension over a list of ternaries to get the `points` list. This list contains 0 or 2 coordinates, and we may or may not draw a line accordingly.

That's how the `draw_oblique_line()` method works, and the `draw_pair_of_oblique_lines()` method just calls it with positive and negative values of  $c$ .

### 3.4.2 Adding vector arrowheads




Figure 3.12: An example of a vector with the arrowheads highlighted in green

Now that I had a good renderer, I wanted to add arrowheads to the vectors to make them easier to see. They were already thicker than the gridlines, but adding arrowheads like in the `3blue1brown` series would make them much easier to see. Unfortunately, I couldn't work out how to do this.

I wanted a function that would take a coordinate, treat it as a unit vector, and draw lines at  $45^\circ$  angles at the tip. This wasn't how I was conceptualising the problem at the time and because of that, I couldn't work out how to solve this problem. I could create this  $45^\circ$  lines in the top right quadrant, but none of my possible solutions worked for any arbitrary point.

So I started googling and found a very nice algorithm on [csharpshelper.com](http://csharpshelper.com)<sup>[21]<sup>11</sup>, which I adapted for Python.</sup>

```
# 5373b1ad8040f6726147cccea523c0570251cf67
# src/lintrans/gui/plots/widgets.py
```

```
52 def draw_arrowhead_away_from_origin(self, painter: QPainter, point: tuple[float, float]) -> None:
53     """Draw an arrowhead at ``point``, pointing away from the origin.
54
55     :param QPainter painter: The ``QPainter`` object to use to draw the arrowheads with
56     :param point: The point to draw the arrowhead at, given in grid coords
57     :type point: tuple[float, float]
58     """
59     # This algorithm was adapted from a C# algorithm found at
60     # http://csharpshelper.com/blog/2014/12/draw-lines-with-arrowheads-in-c/
61
62     # Get the x and y coords of the point, and then normalize them
63     # We have to normalize them, or else the size of the arrowhead will
64     # scale with the distance of the point from the origin
65     x, y = point
66     nx = x / np.sqrt(x * x + y * y)
67     ny = y / np.sqrt(x * x + y * y)
68
69     # We choose a length and do some magic to find the steps in the x and y directions
70     length = 0.15
71     dx = length * (-nx - ny)
72     dy = length * (nx - ny)
73
74     # Then we just plot those lines
75     painter.drawLine(*self.trans_coords(x, y), *self.trans_coords(x + dx, y + dy))
76     painter.drawLine(*self.trans_coords(x, y), *self.trans_coords(x - dy, y + dx))
```

<sup>11</sup>This website is currently being rewritten and this arrowheads tutorial is listed as 'not rebuilt' on <http://csharpshelper.com>

```

77
78 def draw_vector_arrowheads(self, painter: QPainter) -> None:
79     """Draw arrowheads at the tips of the basis vectors.
80
81     :param QPainter painter: The ``QPainter`` object to use to draw the arrowheads with
82     """
83     painter.setPen(QPen(self.colour_i, self.width_vector_line))
84     self.draw_arrowhead_away_from_origin(painter, self.point_i)
85     painter.setPen(QPen(self.colour_j, self.width_vector_line))
86     self.draw_arrowhead_away_from_origin(painter, self.point_j)

```

As the comments suggest, we get the  $x$  and  $y$  components of the normalised vector, and then do some magic with a chosen length and get some distance values, and then draw those lines. I don't really understand how this code works, but I'm happy that it does. All we have to do is call `draw_vector_arrowheads()` from `paintEvent()`.




Figure 3.13: An example of the  $i$  and  $j$  vectors with arrowheads

### 3.4.3 Implementing zoom

The next thing I wanted to do was add the ability to zoom in and out of the viewport, and I wanted a button to reset the zoom level as well. I added a `default_grid_spacing` class attribute in `BackgroundPlot` and used that as the `grid_spacing` instance attribute in `__init__()`.

```

# d944e86e1d0fdc2c4be4d63479bc6bc3a31568ef
# src/lintrans/gui/plots/classes.py

27 default_grid_spacing: int = 50
28
29 def __init__(self, *args, **kwargs):
30     """Create the widget and setup backend stuff for rendering.
31
32     .. note:: ``*args`` and ``**kwargs`` are passed the superclass constructor (``QWidget``).
33     """

```

```

34     super().__init__(*args, **kwargs)
35
36     self.setAutoFillBackground(True)
37
38     # Set the background to white
39     palette = self.palette()
40     palette.setColor(self.backgroundRole(), Qt.white)
41     self.setPalette(palette)
42
43     # Set the grid colour to grey and the axes colour to black
44     self.colour_background_grid = QColor(128, 128, 128)
45     self.colour_background_axes = QColor(0, 0, 0)
46
47     self.grid_spacing = BackgroundPlot.default_grid_spacing

```

The reset button in `LintransMainWindow` simply sets `plot.grid_spacing` to the default.

To actually allow for zooming, I had to implement the `wheelEvent()` method in `BackgroundPlot` to listen for mouse wheel events. After reading through the docs for the `QWheelEvent` class<sup>[17]</sup>, I learned how to handle this event.

```

# d944e86e1d0fdc2c4be4d63479bc6bc3a31568ef
# src/lintrans/gui/plots/classes.py

119 def wheelEvent(self, event: QWheelEvent) -> None:
120     """Handle a ``QWheelEvent`` by zooming in or out of the grid."""
121     # angleDelta() returns a number of units equal to 8 times the number of degrees rotated
122     degrees = event.angleDelta() / 8
123
124     if degrees is not None:
125         self.grid_spacing = max(1, self.grid_spacing + degrees.y())
126
127     event.accept()
128     self.update()

```

All we do is get the amount that the user scrolled and add that to the current spacing, taking the max with 1, which acts as a minimum grid spacing. We need to use `degrees.y()` on line 125 because Qt5 allows for mice that can scroll in the  $x$  and  $y$  directions, and we only want the  $y$  component. Line 127 marks the event as accepted so that the parent widget doesn't try to act on it.




Figure 3.14: The GUI zoomed in a bit




Figure 3.15: The GUI zoomed out as far as possible

There are two things I don't like here. Firstly, the minimum grid spacing is too small. The user can zoom out too far. Secondly, the arrowheads are too big in figure 3.14.

The first problem is minor and won't be fixed for quite a while, but I fixed the second problem quite quickly.

We want the arrowhead length to not just be 0.15, but to scale with the zoom level (the ratio between default grid spacing and current spacing).

This creates a slight issue when zoomed out all the way, because the arrowheads are then far larger than the vectors themselves, so we take the minimum of the scaled length and the vector length.

I factored out the default arrowhead length into the `arrowhead_length` instance attribute and initialize it in `__init__()`.

```
# 3d19a003368ae992ebb60049685bb04fde0836b5
# src/lintrans/gui/plots/widgets.py

68     vector_length = np.sqrt(x * x + y * y)
69     nx = x / vector_length
70     ny = y / vector_length
71
72     # We choose a length and find the steps in the x and y directions
73     length = min(
74         self.arrowhead_length * self.default_grid_spacing / self.grid_spacing,
75         vector_length
76     )
```

This code results in arrowheads that stay the same length unless the user is zoomed out basically as far as possible.




Figure 3.16: The arrowheads adjusted for zoom level

### 3.4.4 Animation blocks zooming

The biggest problem with this new zoom feature is that when animating between matrices, the user is unable to zoom. This is because when `LintransMainWindow.animate_expression()` is called, it uses Python's standard library `time.sleep()` function to delay each frame, which prevents Qt from handling user interaction while we're animating. This was a problem.

I did some googling and found a helpful post on StackOverflow[8] that gave me a nice solution. The user `ekhumoro` used the functions `QApplication.processEvents()` and `QThread.msleep()` to solve the problem, and I used these functions in my own app, with much success.

After reading 'The Event System' in the Qt5 documentation[22], I learned that Qt5 uses an event loop, a lot like JavaScript. This means that events are scheduled to be executed on the next pass of the event loop. I also read the documentation for the `repaint()` and `update()` methods on the `QWidget` class[18, 19] and decided that it would be better to just queue a repaint by calling `update()` on the plot rather than immediately repaint with `repaint()`, and then call `QApplication.processEvents()` to process the pending events on the main thread. This is a nicer way of repainting, which reduces potential flickering issues, and using `QThread.msleep()` allows for asynchronous processing and therefore non-blocking animation.

### 3.4.5 Rank 1 transformations

The rank of a matrix is the dimension of its column space. This is the dimension of the span of its columns, which is to say the dimension of the output space. The rank of a matrix must be less than or equal to the dimension of the matrix, so we only need to worry about ranks 0, 1, and 2. There is only one rank 0 matrix, which is the **0** matrix itself. I've already covered this case by just not drawing any transformed grid lines.

Rank 2 matrices encompass most 2D matrices, and I've already covered this case in §3.3.4 and §3.4.1. A rank 1 matrix collapses all of 2D space onto a single line, so for this type of matrix, we should just draw this line.

This code is in `VectorGridPlot.draw_parallel_lines()`. We assemble the matrix  $\begin{pmatrix} \text{vector\_x} & \text{point\_x} \\ \text{vector\_y} & \text{point\_y} \end{pmatrix}$  (which is actually the matrix used to create the transformation we're trying to render lines for) and use this matrix to check determinant and rank.

```
# 677b38c87bb6722b16aaf35058cf3cef66e43c21
# src/lintrans/gui/plots/classes.py

177     # If the determinant is 0
178     if abs(vector_x * point_y - vector_y * point_x) < 1e-12:
179         rank = np.linalg.matrix_rank(
180             np.array([
181                 [vector_x, point_x],
182                 [vector_y, point_y]
183             ])
184         )
185
186     # If the matrix is rank 1, then we can draw the column space line
187     if rank == 1:
188         self.draw_oblique_line(painter, vector_y / vector_x, 0)
189
190     # If the rank is 0, then we don't draw any lines
191     else:
192         return
```

Additionally, there was a bug with animating these determinant 0 matrices, since we try to scale the determinant through the animation, as documented in §3.3.6, but when the determinant is 0, this causes

issues. To fix this, we just check the `det_target` variable in `LintransMainWindow.animate_expression` and if it's 0, we use the non-scaled version of the matrix.

```
# b889b686d997c2b64124bee786bccba3fc4f6b08  
# src/lintrans/gui/main_window.py
```

```
307         # If we're animating towards a det 0 matrix, then we don't want to scale the  
308         # determinant with the animation, because this makes the process not work  
309         # I'm doing this here rather than wrapping the whole animation logic in an  
310         # if block mainly because this looks nicer than an extra level of indentation  
311         # The extra processing cost is negligible thanks to NumPy's optimizations  
312         if det_target == 0:  
313             matrix_c = matrix_a  
314         else:  
315             matrix_c = scalar * matrix_b
```

## References

- [1] Alan O'Callaghan (Alanocallaghan). *color-oracle-java*. Version 1.3. URL: <https://github.com/Alanocallaghan/color-oracle-java>.
- [2] D. Dyson (DoctorDalek1963). *lintrans*. URL: <https://github.com/DoctorDalek1963/lintrans>.
- [3] D. Dyson (DoctorDalek1963). *Which framework should I use for creating draggable points and connecting lines on a 2D grid?* 26th Jan. 2022. URL: <https://www.reddit.com/r/learnpython/comments/sd2lbr>.
- [4] Ross Wilson (rzzzwilson). *Python-Etudes/PyQtCustomWidget*. URL: <https://gitlab.com/rzzzwilson/python-etudes/-/tree/master/PyQtCustomWidget>.
- [5] *2D linear transformation*. URL: <https://www.desmos.com/calculator/upooihuy4s>.
- [6] Grant Sanderson (3blue1brown). *Essence of Linear Algebra*. 6th Aug. 2016. URL: [https://www.youtube.com/playlist?list=PLZHQ0b0WTQDPD3MizzM2xVFitgF8hE\\_ab](https://www.youtube.com/playlist?list=PLZHQ0b0WTQDPD3MizzM2xVFitgF8hE_ab).
- [7] H. Hohn et al. *Matrix Vector*. MIT. 2001. URL: <https://mathlets.org/mathlets/matrix-vector/>.
- [8] Jacek Wodecki and ekhumoro. *How to update window in PyQt5?* URL: <https://stackoverflow.com/questions/42045676/how-to-update-window-in-pyqt5>.
- [9] jel324. *Visualizing Linear Transformations*. 15th Mar. 2018. URL: <https://www.geogebra.org/m/YCZa8TAH>.
- [10] Nathaniel Vaughn Kelso and Bernie Jenny. *Color Oracle*. Version 1.3. URL: <https://colororacle.org/>.
- [11] *Normalize a matrix such that the determinat = 1*. ResearchGate. 26th June 2017. URL: [https://www.researchgate.net/post/normalize\\_a\\_matrix\\_such\\_that\\_the\\_determinat\\_1](https://www.researchgate.net/post/normalize_a_matrix_such_that_the_determinat_1).
- [12] *Plotting with Matplotlib. Create PyQt5 plots with the popular Python plotting library*. URL: <https://www.pythonguis.com/tutorials/plotting-matplotlib/>.
- [13] *PyQt5 Graphics View Framework*. The Qt Company. URL: <https://doc.qt.io/qtforpython-5/overviews/graphicsview.html>.
- [14] *Python 3 Data model - special methods*. Python Software Foundation. URL: <https://docs.python.org/3/reference/datamodel.html#special-method-names>.
- [15] *Python 3.10 Downloads*. Python Software Foundation. URL: <https://www.python.org/downloads/release/python-3100/>.
- [16] *Qt5 for Linux/X11*. The Qt Company. URL: <https://doc.qt.io/qt-5/linux.html>.
- [17] *QWheelEvent class*. The Qt Company. URL: <https://doc.qt.io/qt-5/qwheelevent.html>.
- [18] *QWidget Class (repaint() method)*. The Qt Company. URL: <https://doc.qt.io/qt-5/qwidget.html#repaint>.
- [19] *QWidget Class (update() method)*. The Qt Company. URL: <https://doc.qt.io/qt-5/qwidget.html#update>.
- [20] Shad Sharma. *Linear Transformation Visualizer*. 4th May 2017. URL: <https://shad.io/MatVis/>.
- [21] Rod Stephens. *Draw lines with arrowheads in C#*. 5th Dec. 2014. URL: <http://csharp-helper.com/blog/2014/12/draw-lines-with-arrowheads-in-c/>.
- [22] *The Event System*. The Qt Company. URL: <https://doc.qt.io/qt-5/eventsandfilters.html>.
- [23] *Types of Color Blindness*. National Eye Institute. URL: <https://www.nei.nih.gov/learn-about-eye-health/eye-conditions-and-diseases/color-blindness/types-color-blindness>.



## A Project code

### A.1 \_\_main\_\_.py

```

1  #!/usr/bin/env python
2
3  # lintrans - The linear transformation visualizer
4  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
5
6  # This program is licensed under GNU GPLv3, available here:
7  # <https://www.gnu.org/licenses/gpl-3.0.html>
8
9  """This module provides a :func:`main` function to interpret command line arguments and run the program."""
10
11  import sys
12  from argparse import ArgumentParser
13  from textwrap import dedent
14
15  from lintrans import __version__
16  from lintrans.gui import main_window
17
18
19  def main(args: list[str]) -> None:
20      """Interpret program-specific command line arguments and run the main window in most cases.
21
22      If the user supplies --help or --version, then we simply respond to that and then return.
23      If they don't supply either of these, then we run :func:`lintrans.gui.main_window.main`.
24
25      :param list[str] args: The full argument list (including program name)
26      """
27      parser = ArgumentParser(add_help=False)
28
29      parser.add_argument(
30          '-h',
31          '--help',
32          default=False,
33          action='store_true'
34      )
35
36      parser.add_argument(
37          '-V',
38          '--version',
39          default=False,
40          action='store_true'
41      )
42
43      parsed_args, unparsed_args = parser.parse_known_args()
44
45      if parsed_args.help:
46          print(dedent('''
47              Usage: lintrans [option]
48
49              Options:
50                  -h, --help      Display this help text and exit
51                  -V, --version   Display the version information and exit
52
53              Any other options will get passed to the QApplication constructor.
54              If you don't know what that means, then don't provide any arguments and just the run the program.'''[1:]))
55          return
56
57      if parsed_args.version:
58          print(dedent(f'''
59              lintrans (version {__version__})
60              The linear transformation visualizer
61
62              Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
63
64              This program is licensed under GNU GPLv3, available here:
65              <https://www.gnu.org/licenses/gpl-3.0.html>'''[1:]))
66          return
67

```

```

68     for arg in unparsed_args:
69         print(f'Passing "{arg}" to QApplication. See --help for recognised args')
70
71     main_window.main(args[:1] + unparsed_args)
72
73
74 if __name__ == '__main__':
75     main(sys.argv)

```

## A.2 \_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This is the top-level ``lintrans`` package, which contains all the subpackages of the project."""
8
9  from . import gui, matrices, typing_
10
11  __version__ = '0.2.2-alpha'
12
13  __all__ = ['gui', 'matrices', 'typing_', '__version__']

```

## A.3 matrices/\_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package supplies classes and functions to parse, evaluate, and wrap matrices."""
8
9  from . import parse
10  from .wrapper import create_rotation_matrix, MatrixWrapper
11
12  __all__ = ['create_rotation_matrix', 'MatrixWrapper', 'parse']

```

## A.4 matrices/parse.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides functions to parse and validate matrix expressions."""
8
9  from __future__ import annotations
10
11  import re
12  from dataclasses import dataclass
13  from typing import Pattern
14
15  from lintrans.typing_ import MatrixParseList
16
17  NAIVE_CHARACTER_CLASS = r'[-+\sA-Z0-9.\rot()^{}]'
18
19
20  class MatrixParseError(Exception):
21      """A simple exception to be raised when an error is found when parsing."""
22
23

```

```

24 def compile_naive_expression_pattern() -> Pattern[str]:
25     """Compile the single RegEx pattern that will match a valid matrix expression."""
26     digit_no_zero = '[123456789]'
27     digits = '\\d+'
28     integer_no_zero = digit_no_zero + '(' + digits + ')?'
29     real_number = f'({integer_no_zero}(\\.{digits})?|0\\.\\{digits})'
30
31     index_content = f'(-?{integer_no_zero}|T)'
32     index = f'(^{index_content})|(^{index_content})'
33     matrix_identifier = f'([A-Z]|rot\\(-?{real_number}\\)|\\({NAIVE_CHARACTER_CLASS}\\})'
34     matrix = '(' + real_number + '?' + matrix_identifier + index + '?'
35     expression = f'^~?{matrix}+((\\+~?|~){matrix}+)*$'
36
37     return re.compile(expression)
38
39
40 # This is an expensive pattern to compile, so we compile it when this module is initialized
41 naive_expression_pattern = compile_naive_expression_pattern()
42
43
44 def find_sub_expressions(expression: str) -> list[str]:
45     """Find all the sub-expressions in the given expression.
46
47     This function only goes one level deep, so may return strings like ``A(BC)D``.
48
49     :raises MatrixParseError: If there are unbalanced parentheses
50     """
51     sub_expressions: list[str] = []
52     string = ''
53     paren_depth = 0
54     pointer = 0
55
56     while True:
57         char = expression[pointer]
58
59         if char == '(' and expression[pointer - 3:pointer] != 'rot':
60             paren_depth += 1
61
62             # This is a bit of a manual bodge, but it eliminates extraneous parens
63             if paren_depth == 1:
64                 pointer += 1
65                 continue
66
67         elif char == ')' and re.match(f'{NAIVE_CHARACTER_CLASS}*rot\\([-\\d.]+$', expression[:pointer]) is None:
68             paren_depth -= 1
69
70         if paren_depth > 0:
71             string += char
72
73         if paren_depth == 0 and string:
74             sub_expressions.append(string)
75             string = ''
76
77         pointer += 1
78
79         if pointer >= len(expression):
80             break
81
82     if paren_depth != 0:
83         raise MatrixParseError('Unbalanced parentheses in expression')
84
85     return sub_expressions
86
87
88 def validate_matrix_expression(expression: str) -> bool:
89     """Validate the given matrix expression.
90
91     This function simply checks the expression against the BNF schema documented in
92     :ref:`expression-syntax-docs`. It is not aware of which matrices are actually defined
93     in a wrapper. For an aware version of this function, use the
94     :meth:`lintrans.matrices.wrapper.MatrixWrapper.is_valid_expression` method.
95
96     :param str expression: The expression to be validated

```

```

97         :returns bool: Whether the expression is valid according to the schema
98         """
99         # Remove all whitespace
100        expression = re.sub(r'\s', '', expression)
101
102        match = naive_expression_pattern.match(expression)
103
104        if match is None:
105            return False
106
107        # Check that the whole expression was matched against
108        if expression != match.group(0):
109            return False
110
111        try:
112            sub_expressions = find_sub_expressions(expression)
113        except MatrixParseError:
114            return False
115
116        if not sub_expressions:
117            return True
118
119        return all(validate_matrix_expression(m) for m in sub_expressions)
120
121
122    @dataclass
123    class MatrixToken:
124        """A simple dataclass to hold information about a matrix token being parsed."""
125
126        multiplier: str = ''
127        identifier: str = ''
128        exponent: str = ''
129
130        @property
131        def tuple(self) -> tuple[str, str, str]:
132            """Create a tuple of the token for parsing."""
133            return self.multiplier, self.identifier, self.exponent
134
135
136    class ExpressionParser:
137        """A class to hold state during parsing.
138
139        Most of the methods in this class are class-internal and should not be used from outside.
140
141        This class should be used like this:
142
143        >>> ExpressionParser('3A~1B').parse()
144        [[('3', 'A', '-1'), ('', 'B', '')]]
145        >>> ExpressionParser('4(M^TA^2)^-2').parse()
146        [[('4', 'M^{T}A^{2}', '-2')]]
147        """
148
149        def __init__(self, expression: str):
150            """Create an instance of the parser with the given expression and initialise variables to use during
151            ↪ parsing."""
152            # Remove all whitespace
153            expression = re.sub(r'\s', '', expression)
154
155            # Check if it's valid
156            if not validate_matrix_expression(expression):
157                raise MatrixParseError('Invalid expression')
158
159            # Wrap all exponents and transposition powers with {}
160            expression = re.sub(r'(<=^)(-?\d+|T)(?=[^}]|$)', r'{\g<0>}', expression)
161
162            # Remove any standalone minuses
163            expression = re.sub(r'-(?=[A-Z])', '-1', expression)
164
165            # Replace subtractions with additions
166            expression = re.sub(r'-(?=\d+\.?\d*([A-Z]|rot))', '+-', expression)
167
168            # Get rid of a potential leading + introduced by the last step
169            expression = re.sub(r'^\+', '', expression)

```

```

169
170     self.expression = expression
171     self.pointer: int = 0
172
173     self.current_token = MatrixToken()
174     self.current_group: list[tuple[str, str, str]] = []
175
176     self.final_list: MatrixParseList = []
177
178     def __repr__(self) -> str:
179         """Return a simple repr containing the expression."""
180         return f'{self.__class__.__module__}.{self.__class__.__name__}("{self.expression}")'
181
182     @property
183     def char(self) -> str:
184         """Return the char pointed to by the pointer."""
185         return self.expression[self.pointer]
186
187     def parse(self) -> MatrixParseList:
188         """Fully parse the instance's matrix expression and return the :attr:`lintrans.typing.MatrixParseList`.
189
190         This method uses all the private methods of this class to parse the
191         expression in parts. All private methods mutate the instance variables.
192
193         :returns: The parsed expression
194         :rtype: :attr:`lintrans.typing.MatrixParseList`
195         """
196         self._parse_multiplication_group()
197
198         while self.pointer < len(self.expression):
199             if self.expression[self.pointer] != '+':
200                 raise MatrixParseError('Expected "+" between multiplication groups')
201
202             self.pointer += 1
203             self._parse_multiplication_group()
204
205         return self.final_list
206
207     def _parse_multiplication_group(self) -> None:
208         """Parse a group of matrices to be multiplied together.
209
210         This method just parses matrices until we get to a ``+``.
211         """
212         # This loop continues to parse matrices until we fail to do so
213         while self._parse_matrix():
214             # Once we get to the end of the multiplication group, we add it the final list and reset the group list
215             if self.pointer >= len(self.expression) or self.char == '+':
216                 self.final_list.append(self.current_group)
217                 self.current_group = []
218                 self.pointer += 1
219
220     def _parse_matrix(self) -> bool:
221         """Parse a full matrix using :meth:`_parse_matrix_part`.
222
223         This method will parse an optional multiplier, an identifier, and an optional exponent. If we
224         do this successfully, we return True. If we fail to parse a matrix (maybe we've reached the
225         end of the current multiplication group and the next char is ``+``), then we return False.
226
227         :returns bool: Success or failure
228         """
229         self.current_token = MatrixToken()
230
231         while self._parse_matrix_part():
232             pass # The actual execution is taken care of in the loop condition
233
234         if self.current_token.identifier == '':
235             return False
236
237         self.current_group.append(self.current_token.tuple)
238         return True
239
240     def _parse_matrix_part(self) -> bool:
241         """Parse part of a matrix (multiplier, identifier, or exponent).

```

```

242
243 Which part of the matrix we parse is dependent on the current value of the pointer and the expression.
244 This method will parse whichever part of matrix token that it can. If it can't parse a part of a matrix,
245 or it's reached the next matrix, then we just return False. If we succeeded to parse a matrix part, then
246 we return True.
247
248 :returns bool: Success or failure
249 :raises MatrixParseError: If we fail to parse this part of the matrix
250 """
251 if self.pointer >= len(self.expression):
252     return False
253
254 if self.char.isdigit() or self.char == '-':
255     if self.current_token.multiplier != '' \
256         or (self.current_token.multiplier == '' and self.current_token.identifier != ''):
257         return False
258
259     self._parse_multiplier()
260
261 elif self.char.isalpha() and self.char.isupper():
262     if self.current_token.identifier != '':
263         return False
264
265     self.current_token.identifier = self.char
266     self.pointer += 1
267
268 elif self.char == 'r':
269     if self.current_token.identifier != '':
270         return False
271
272     self._parse_rot_identifier()
273
274 elif self.char == '(':
275     if self.current_token.identifier != '':
276         return False
277
278     self._parse_sub_expression()
279
280 elif self.char == '^':
281     if self.current_token.exponent != '':
282         return False
283
284     self._parse_exponent()
285
286 elif self.char == '+':
287     return False
288
289 else:
290     raise MatrixParseError(f'Unrecognised character "{self.char}" in matrix expression')
291
292 return True
293
294 def _parse_multiplier(self) -> None:
295     """Parse a multiplier from the expression and pointer.
296
297     This method just parses a numerical multiplier, which can include
298     zero or one ``.`` character and optionally a ``-`` at the start.
299
300     :raises MatrixParseError: If we fail to parse this part of the matrix
301     """
302     multiplier = ''
303
304     while self.char.isdigit() or self.char in ('.', '-'):
305         multiplier += self.char
306         self.pointer += 1
307
308     try:
309         float(multiplier)
310     except ValueError as e:
311         raise MatrixParseError(f'Invalid multiplier "{multiplier}"') from e
312
313     self.current_token.multiplier = multiplier
314

```

```

315 def _parse_rot_identifier(self) -> None:
316     """Parse a ``rot()``-style identifier from the expression and pointer.
317
318     This method will just parse something like ``rot(12.5)``. The angle number must be a real number.
319
320     :raises MatrixParseError: If we fail to parse this part of the matrix
321     """
322     if match := re.match(r'rot\(((\d.-]+\))\)', self.expression[self.pointer:]):
323         # Ensure that the number in brackets is a valid float
324         try:
325             float(match.group(1))
326         except ValueError as e:
327             raise MatrixParseError(f'Invalid angle number "{match.group(1)}" in rot-identifier') from e
328
329         self.current_token.identifier = match.group(0)
330         self.pointer += len(match.group(0))
331     else:
332         raise MatrixParseError(f'Invalid rot-identifier "{self.expression[self.pointer:self.pointer + 15]}'
333     }...")
334
335 def _parse_sub_expression(self) -> None:
336     """Parse a parenthesized sub-expression as the identifier.
337
338     This method will also validate the expression in the parentheses.
339
340     :raises MatrixParseError: If we fail to parse this part of the matrix
341     """
342     if self.char != '(':
343         raise MatrixParseError('Sub-expression must start with "("')
344
345     self.pointer += 1
346     paren_depth = 1
347     identifier = ''
348
349     while paren_depth > 0:
350         if self.char == '(':
351             paren_depth += 1
352         elif self.char == ')':
353             paren_depth -= 1
354
355         if paren_depth == 0:
356             self.pointer += 1
357             break
358
359         identifier += self.char
360         self.pointer += 1
361
362     if not validate_matrix_expression(identifier):
363         raise MatrixParseError(f'Invalid sub-expression identifier "{identifier}"')
364
365     self.current_token.identifier = identifier
366
367 def _parse_exponent(self) -> None:
368     """Parse a matrix exponent from the expression and pointer.
369
370     The exponent must be an integer or ``T`` for transpose.
371
372     :raises MatrixParseError: If we fail to parse this part of the token
373     """
374     if match := re.match(r'\^{\d+|T}\}', self.expression[self.pointer:]):
375         exponent = match.group(1)
376
377         try:
378             if exponent != 'T':
379                 int(exponent)
380         except ValueError as e:
381             raise MatrixParseError(f'Invalid exponent "{match.group(1)}"') from e
382
383         self.current_token.exponent = exponent
384         self.pointer += len(match.group(0))
385     else:
386         raise MatrixParseError(f'Invalid exponent "{self.expression[self.pointer:self.pointer + 10]}...'")

```

```

387
388 def parse_matrix_expression(expression: str) -> MatrixParseList:
389     """Parse the matrix expression and return a :data:`lintrans.typing_.MatrixParseList`.
390
391     :Example:
392
393     >>> parse_matrix_expression('A')
394     [[(' ', 'A', ' ')]]
395     >>> parse_matrix_expression('-3M^2')
396     [[(' -3', 'M', '2')]]
397     >>> parse_matrix_expression('1.2rot(12)^{3}2B^T')
398     [[('1.2', 'rot(12)', '3'), ('2', 'B', 'T')]]
399     >>> parse_matrix_expression('A^2 + 3B')
400     [[(' ', 'A', '2')], [('3', 'B', ' ')]]
401     >>> parse_matrix_expression('-3A^{-1}3B^T - 45M^2')
402     [[(' -3', 'A', ' -1'), ('3', 'B', 'T'), [(' -45', 'M', '2')]]]
403     >>> parse_matrix_expression('5.3A^{4} 2.6B^{-2} + 4.6D^T 8.9E^{-1}')
404     [[('5.3', 'A', '4'), ('2.6', 'B', ' -2'), [('4.6', 'D', 'T'), ('8.9', 'E', ' -1')]]]
405     >>> parse_matrix_expression('2(A+B^TC)^2D')
406     [[('2', 'A+B^{T}C', '2'), (' ', 'D', ' ')]]
407
408     :param str expression: The expression to be parsed
409     :returns: A list of parsed components
410     :rtype: :data:`lintrans.typing_.MatrixParseList`
411     """
412     return ExpressionParser(expression).parse()

```

## A.5 matrices/wrapper.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module contains the main :class:`MatrixWrapper` class and a function to create a matrix from an angle."""
8
9  from __future__ import annotations
10
11  import re
12  from copy import copy
13  from functools import reduce
14  from operator import add, matmul
15  from typing import Any, Optional, Union
16
17  import numpy as np
18
19  from .parse import parse_matrix_expression, validate_matrix_expression
20  from lintrans.typing_ import is_matrix_type, MatrixType
21
22
23  class MatrixWrapper:
24     """A wrapper class to hold all possible matrices and allow access to them.
25
26     .. note::
27         When defining a custom matrix, its name must be a capital letter and cannot be ``I``.
28
29     The contained matrices can be accessed and assigned to using square bracket notation.
30
31     :Example:
32
33     >>> wrapper = MatrixWrapper()
34     >>> wrapper['I']
35     array([[1., 0.],
36           [0., 1.]])
37     >>> wrapper['M'] # Returns None
38     >>> wrapper['M'] = np.array([[1, 2], [3, 4]])
39     >>> wrapper['M']
40     array([[1., 2.],
41           [3., 4.]])

```



```

42     """
43
44     def __init__(self):
45         """Initialize a :class:`MatrixWrapper` object with a dictionary of matrices which can be accessed."""
46         self._matrices: dict[str, Optional[Union[MatrixType, str]]] = {
47             'A': None, 'B': None, 'C': None, 'D': None,
48             'E': None, 'F': None, 'G': None, 'H': None,
49             'I': np.eye(2), # I is always defined as the identity matrix
50             'J': None, 'K': None, 'L': None, 'M': None,
51             'N': None, 'O': None, 'P': None, 'Q': None,
52             'R': None, 'S': None, 'T': None, 'U': None,
53             'V': None, 'W': None, 'X': None, 'Y': None,
54             'Z': None
55         }
56
57     def __repr__(self) -> str:
58         """Return a nice string repr of the :class:`MatrixWrapper` for debugging."""
59         defined_matrices = ''.join([k for k, v in self._matrices.items() if v is not None])
60         return f'<{self.__class__.__module__}.{self.__class__.__name__} object with ' \
61             f'{len(defined_matrices)} defined matrices: '{defined_matrices}'>'
62
63     def __eq__(self, other: Any) -> bool:
64         """Check for equality in wrappers by comparing dictionaries.
65
66         :param Any other: The object to compare this wrapper to
67         """
68         if not isinstance(other, self.__class__):
69             return NotImplemented
70
71         # We loop over every matrix and check if every value is equal in each
72         for name in self._matrices:
73             s_matrix = self[name]
74             o_matrix = other[name]
75
76             if s_matrix is None and o_matrix is None:
77                 continue
78
79             elif (s_matrix is None and o_matrix is not None) or \
80                  (s_matrix is not None and o_matrix is None):
81                 return False
82
83             # This is mainly to satisfy mypy, because we know these must be matrices
84             elif not is_matrix_type(s_matrix) or not is_matrix_type(o_matrix):
85                 return False
86
87             # Now we know they're both NumPy arrays
88             elif np.array_equal(s_matrix, o_matrix):
89                 continue
90
91             else:
92                 return False
93
94         return True
95
96     def __hash__(self) -> int:
97         """Return the hash of the matrices dictionary."""
98         return hash(self._matrices)
99
100     def __getitem__(self, name: str) -> Optional[MatrixType]:
101         """Get the matrix with the given name.
102
103         If it is a simple name, it will just be fetched from the dictionary. If the name is ``rot(x)``, with
104         a given angle in degrees, then we return a new matrix representing a rotation by that angle.
105
106         .. note::
107             If the named matrix is defined as an expression, then this method will return its evaluation.
108             If you want the expression itself, use :meth:`get_expression`.
109
110         :param str name: The name of the matrix to get
111         :returns Optional[MatrixType]: The value of the matrix (could be None)
112
113         :raises NameError: If there is no matrix with the given name
114         """

```

```

115         # Return a new rotation matrix
116         if (match := re.match(r'^rot\((-?\d*\.\d*)\)$', name)) is not None:
117             return create_rotation_matrix(float(match.group(1)))
118
119         if name not in self._matrices:
120             if validate_matrix_expression(name):
121                 return self.evaluate_expression(name)
122
123             raise NameError(f'Unrecognised matrix name "{name}"')
124
125         # We copy the matrix before we return it so the user can't accidentally mutate the matrix
126         matrix = copy(self._matrices[name])
127
128         if isinstance(matrix, str):
129             return self.evaluate_expression(matrix)
130
131         return matrix
132
133     def __setitem__(self, name: str, new_matrix: Optional[Union[MatrixType, str]]) -> None:
134         """Set the value of matrix ``name`` with the new_matrix.
135
136         The new matrix may be a simple 2x2 NumPy array, or it could be a string, representing an
137         expression in terms of other, previously defined matrices.
138
139         :param str name: The name of the matrix to set the value of
140         :param Optional[Union[MatrixType, str]] new_matrix: The value of the new matrix (could be None)
141
142         :raises NameError: If the name isn't a legal matrix name
143         :raises TypeError: If the matrix isn't a valid 2x2 NumPy array or expression in terms of other defined
144         ↪ matrices
145         :raises ValueError: If you attempt to define a matrix in terms of itself
146         """
147         if not (name in self._matrices and name != 'I'):
148             raise NameError('Matrix name is illegal')
149
150         if new_matrix is None:
151             self._matrices[name] = None
152             return
153
154         if isinstance(new_matrix, str):
155             if self.is_valid_expression(new_matrix):
156                 if name not in self._matrices:
157                     self._matrices[name] = new_matrix
158                     return
159             else:
160                 raise ValueError('Cannot define a matrix recursively')
161
162         if not is_matrix_type(new_matrix):
163             raise TypeError('Matrix must be a 2x2 NumPy array')
164
165         # All matrices must have float entries
166         a = float(new_matrix[0][0])
167         b = float(new_matrix[0][1])
168         c = float(new_matrix[1][0])
169         d = float(new_matrix[1][1])
170
171         self._matrices[name] = np.array([[a, b], [c, d]])
172
173     def get_expression(self, name: str) -> Optional[str]:
174         """If the named matrix is defined as an expression, return that expression, else return None.
175
176         :param str name: The name of the matrix
177         :returns Optional[str]: The expression that the matrix is defined as, or None
178
179         :raises NameError: If the name is invalid
180         """
181         if name not in self._matrices:
182             raise NameError('Matrix must have a legal name')
183
184         matrix = self._matrices[name]
185         if isinstance(matrix, str):
186             return matrix

```

```

187         return None
188
189     def is_valid_expression(self, expression: str) -> bool:
190         """Check if the given expression is valid, using the context of the wrapper.
191
192         This method calls :func:`lintrans.matrices.parse.validate_matrix_expression`, but also
193         ensures that all the matrices in the expression are defined in the wrapper.
194
195         :param str expression: The expression to validate
196         :returns bool: Whether the expression is valid in this wrapper
197
198         :raises LinAlgError: If a matrix is defined in terms of the inverse of a singular matrix
199         """
200         # Get rid of the transposes to check all capital letters
201         new_expression = expression.replace('^T', '').replace('^T}', '')
202
203         # Make sure all the referenced matrices are defined
204         for matrix in [x for x in new_expression if re.match('[A-Z]', x)]:
205             if self[matrix] is None:
206                 return False
207
208             if (expr := self.get_expression(matrix)) is not None:
209                 if not self.is_valid_expression(expr):
210                     return False
211
212         return validate_matrix_expression(expression)
213
214     def evaluate_expression(self, expression: str) -> MatrixType:
215         """Evaluate a given expression and return the matrix evaluation.
216
217         :param str expression: The expression to be parsed
218         :returns MatrixType: The matrix result of the expression
219
220         :raises ValueError: If the expression is invalid
221         """
222         if not self.is_valid_expression(expression):
223             raise ValueError('The expression is invalid')
224
225         parsed_result = parse_matrix_expression(expression)
226         final_groups: list[list[MatrixType]] = []
227
228         for group in parsed_result:
229             f_group: list[MatrixType] = []
230
231             for multiplier, identifier, index in group:
232                 if index == 'T':
233                     m = self[identifier]
234
235                     # This assertion is just so mypy doesn't complain
236                     # We know this won't be None, because we know that this matrix is defined in this wrapper
237                     assert m is not None
238                     matrix_value = m.T
239
240                 else:
241                     matrix_value = np.linalg.matrix_power(self[identifier], 1 if index == '' else int(index))
242
243                 matrix_value *= 1 if multiplier == '' else float(multiplier)
244                 f_group.append(matrix_value)
245
246             final_groups.append(f_group)
247
248         return reduce(add, [reduce(matmul, group) for group in final_groups])
249
250
251     def create_rotation_matrix(angle: float, *, degrees: bool = True) -> MatrixType:
252         """Create a matrix representing a rotation (anticlockwise) by the given angle.
253
254         :Example:
255
256         >>> create_rotation_matrix(30)
257         array([[ 0.8660254, -0.5      ],
258               [ 0.5      ,  0.8660254]])
259         >>> create_rotation_matrix(45)

```

```

260     array([[ 0.70710678, -0.70710678],
261           [ 0.70710678,  0.70710678]])
262     >>> create_rotation_matrix(np.pi / 3, degrees=False)
263     array([[ 0.5        , -0.8660254],
264           [ 0.8660254,  0.5        ]])
265
266     :param float angle: The angle to rotate anticlockwise by
267     :param bool degrees: Whether to interpret the angle as degrees (True) or radians (False)
268     :returns MatrixType: The resultant matrix
269     """
270     rad = np.deg2rad(angle) if degrees else angle
271     return np.array([
272         [np.cos(rad), -1 * np.sin(rad)],
273         [np.sin(rad), np.cos(rad)]
274     ])

```

## A.6 gui/\_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package supplies the main GUI and associated dialogs for visualization."""
8
9  from . import dialogs, plots, settings, validate
10 from .main_window import main
11
12 __all__ = ['dialogs', 'main', 'plots', 'settings', 'validate']

```

## A.7 gui/main\_window.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides the :class:`LintransMainWindow` class, which provides the main window for the GUI."""
8
9  from __future__ import annotations
10
11 import sys
12 import webbrowser
13 from copy import deepcopy
14 from typing import Type
15
16 import numpy as np
17 from numpy import linalg
18 from numpy.linalg import LinAlgError
19 from PyQt5 import QtWidgets
20 from PyQt5.QtCore import pyqtSlot, QThread
21 from PyQt5.QtGui import QKeySequence
22 from PyQt5.QtWidgets import QApplication, QHBoxLayout, QMainWindow, QMessageBox,
23                               QShortcut, QSizePolicy, QSpacerItem, QVBoxLayout
24
25 from lintrans.matrices import MatrixWrapper
26 from lintrans.matrices.parse import validate_matrix_expression
27 from lintrans.typing_ import MatrixType
28 from . import dialogs
29 from .dialogs import DefineAsAnExpressionDialog, DefineDialog, DefineNumericallyDialog, DefineVisuallyDialog
30 from .dialogs.settings import DisplaySettingsDialog
31 from .plots import VisualizeTransformationWidget
32 from .settings import DisplaySettings
33 from .validate import MatrixExpressionValidator
34
35

```

```

36 class LintransMainWindow(QMainWindow):
37     """This class provides a main window for the GUI using the Qt framework.
38
39     This class should not be used directly, instead call :func:`lintrans.gui.main_window.main` to create the GUI.
40     """
41
42     def __init__(self):
43         """Create the main window object, and create and arrange every widget in it.
44
45         This doesn't show the window, it just constructs it. Use :func:`lintrans.gui.main_window.main` to show the
46         ↩ GUI.
47         """
48         super().__init__()
49
50         self.matrix_wrapper = MatrixWrapper()
51
52         self.setWindowTitle('lintrans')
53         self.setMinimumSize(1000, 750)
54
55         self.animating: bool = False
56         self.animating_sequence: bool = False
57
58         # === Create menubar
59         self.menubar = QtWidgets.QMenuBar(self)
60
61         self.menu_file = QtWidgets.QMenu(self.menubar)
62         self.menu_file.setTitle('&File')
63
64         self.menu_help = QtWidgets.QMenu(self.menubar)
65         self.menu_help.setTitle('&Help')
66
67         self.action_new = QtWidgets.QAction(self)
68         self.action_new.setText('&New')
69         self.action_new.setShortcut('Ctrl+N')
70         self.action_new.triggered.connect(lambda: print('new'))
71
72         self.action_open = QtWidgets.QAction(self)
73         self.action_open.setText('&Open')
74         self.action_open.setShortcut('Ctrl+O')
75         self.action_open.triggered.connect(lambda: print('open'))
76
77         self.action_save = QtWidgets.QAction(self)
78         self.action_save.setText('&Save')
79         self.action_save.setShortcut('Ctrl+S')
80         self.action_save.triggered.connect(lambda: print('save'))
81
82         self.action_save_as = QtWidgets.QAction(self)
83         self.action_save_as.setText('Save as...')
84         self.action_save_as.triggered.connect(lambda: print('save as'))
85
86         self.action_tutorial = QtWidgets.QAction(self)
87         self.action_tutorial.setText('&Tutorial')
88         self.action_tutorial.setShortcut('F1')
89         self.action_tutorial.triggered.connect(lambda: print('tutorial'))
90
91         self.action_docs = QtWidgets.QAction(self)
92         self.action_docs.setText('&Docs')
93         self.action_docs.triggered.connect(
94             lambda: webbrowser.open_new_tab('https://doctordalek1963.github.io/lintrans/docs/index.html')
95         )
96
97         self.action_about = QtWidgets.QAction(self)
98         self.action_about.setText('&About')
99         self.action_about.triggered.connect(lambda: dialogs.AboutDialog(self).open())
100
101         # TODO: Implement these actions and enable them
102         self.action_new.setEnabled(False)
103         self.action_open.setEnabled(False)
104         self.action_save.setEnabled(False)
105         self.action_save_as.setEnabled(False)
106         self.action_tutorial.setEnabled(False)
107

```

```

108     self.menu_file.addAction(self.action_new)
109     self.menu_file.addAction(self.action_open)
110     self.menu_file.addSeparator()
111     self.menu_file.addAction(self.action_save)
112     self.menu_file.addAction(self.action_save_as)
113
114     self.menu_help.addAction(self.action_tutorial)
115     self.menu_help.addAction(self.action_docs)
116     self.menu_help.addSeparator()
117     self.menu_help.addAction(self.action_about)
118
119     self.menubar.addAction(self.menu_file.menuAction())
120     self.menubar.addAction(self.menu_help.menuAction())
121
122     self.setMenuBar(self.menubar)
123
124     # === Create widgets
125
126     # Left layout: the plot and input box
127
128     self.plot = VisualizeTransformationWidget(self, display_settings=DisplaySettings())
129
130     self.lineedit_expression_box = QtWidgets.QLineEdit(self)
131     self.lineedit_expression_box.setPlaceholderText('Enter matrix expression...')
132     self.lineedit_expression_box.setValidator(MatrixExpressionValidator(self))
133     self.lineedit_expression_box.textChanged.connect(self.update_render_buttons)
134
135     # Right layout: all the buttons
136
137     # Misc buttons
138
139     self.button_create_polygon = QtWidgets.QPushButton(self)
140     self.button_create_polygon.setText('Create polygon')
141     # self.button_create_polygon.clicked.connect(self.create_polygon)
142     self.button_create_polygon.setToolTip('Define a new polygon to view the transformation of')
143
144     # TODO: Implement this and enable button
145     self.button_create_polygon.setEnabled(False)
146
147     self.button_change_display_settings = QtWidgets.QPushButton(self)
148     self.button_change_display_settings.setText('Change\ndisplay settings')
149     self.button_change_display_settings.clicked.connect(self.dialog_change_display_settings)
150     self.button_change_display_settings.setToolTip(
151         "Change which things are rendered and how they're rendered<br><b>(Ctrl + D)</b>"
152     )
153     QShortcut(QKeySequence('Ctrl+D'), self).activated.connect(self.button_change_display_settings.click)
154
155     self.button_reset_zoom = QtWidgets.QPushButton(self)
156     self.button_reset_zoom.setText('Reset zoom')
157     self.button_reset_zoom.clicked.connect(self.reset_zoom)
158     self.button_reset_zoom.setToolTip('Reset the zoom level back to normal<br><b>(Ctrl + Shift + R)</b>')
159     QShortcut(QKeySequence('Ctrl+Shift+R'), self).activated.connect(self.button_reset_zoom.click)
160
161     # Define new matrix buttons and their groupbox
162
163     self.button_define_visually = QtWidgets.QPushButton(self)
164     self.button_define_visually.setText('Visually')
165     self.button_define_visually.setToolTip('Drag the basis vectors<br><b>(Alt + 1)</b>')
166     self.button_define_visually.clicked.connect(lambda: self.dialog_define_matrix(DefineVisuallyDialog))
167     QShortcut(QKeySequence('Alt+1'), self).activated.connect(self.button_define_visually.click)
168
169     self.button_define_numerically = QtWidgets.QPushButton(self)
170     self.button_define_numerically.setText('Numerically')
171     self.button_define_numerically.setToolTip('Define a matrix just with numbers<br><b>(Alt + 2)</b>')
172     self.button_define_numerically.clicked.connect(lambda: self.dialog_define_matrix(DefineNumericallyDialog))
173     QShortcut(QKeySequence('Alt+2'), self).activated.connect(self.button_define_numerically.click)
174
175     self.button_define_as_expression = QtWidgets.QPushButton(self)
176     self.button_define_as_expression.setText('As an expression')
177     self.button_define_as_expression.setToolTip('Define a matrix in terms of other matrices<br><b>(Alt +
178     ↵ 3)</b>')
    self.button_define_as_expression.clicked.connect(lambda:
    ↵ self.dialog_define_matrix(DefineAsAnExpressionDialog))

```

```

179         QShortcut(QKeySequence('Alt+3'), self).activated.connect(self.button_define_as_expression.click)
180
181         self.vlay_define_new_matrix = QVBoxLayout()
182         self.vlay_define_new_matrix.setSpacing(20)
183         self.vlay_define_new_matrix.addWidget(self.button_define_visually)
184         self.vlay_define_new_matrix.addWidget(self.button_define_numerically)
185         self.vlay_define_new_matrix.addWidget(self.button_define_as_expression)
186
187         self.groupbox_define_new_matrix = QtWidgets.QGroupBox('Define a new matrix', self)
188         self.groupbox_define_new_matrix.setLayout(self.vlay_define_new_matrix)
189
190         # Render buttons
191
192         self.button_reset = QtWidgets.QPushButton(self)
193         self.button_reset.setText('Reset')
194         self.button_reset.clicked.connect(self.reset_transformation)
195         self.button_reset.setToolTip('Reset the visualized transformation back to the identity<br><b>(Ctrl +  

196         ↩ R)</b>')
197         QShortcut(QKeySequence('Ctrl+R'), self).activated.connect(self.button_reset.click)
198
199         self.button_render = QtWidgets.QPushButton(self)
200         self.button_render.setText('Render')
201         self.button_render.setEnabled(False)
202         self.button_render.clicked.connect(self.render_expression)
203         self.button_render.setToolTip('Render the expression<br><b>(Ctrl + Enter)</b>')
204         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self.button_render.click)
205
206         self.button_animate = QtWidgets.QPushButton(self)
207         self.button_animate.setText('Animate')
208         self.button_animate.setEnabled(False)
209         self.button_animate.clicked.connect(self.animate_expression)
210         self.button_animate.setToolTip('Animate the expression<br><b>(Ctrl + Shift + Enter)</b>')
211         QShortcut(QKeySequence('Ctrl+Shift+Return'), self).activated.connect(self.button_animate.click)
212
213         # === Arrange widgets
214
215         self.vlay_left = QVBoxLayout()
216         self.vlay_left.addWidget(self.plot)
217         self.vlay_left.addWidget(self.linedit_expression_box)
218
219         self.vlay_misc_buttons = QVBoxLayout()
220         self.vlay_misc_buttons.setSpacing(20)
221         self.vlay_misc_buttons.addWidget(self.button_create_polygon)
222         self.vlay_misc_buttons.addWidget(self.button_change_display_settings)
223         self.vlay_misc_buttons.addWidget(self.button_reset_zoom)
224
225         self.vlay_render = QVBoxLayout()
226         self.vlay_render.setSpacing(20)
227         self.vlay_render.addWidget(self.button_reset)
228         self.vlay_render.addWidget(self.button_animate)
229         self.vlay_render.addWidget(self.button_render)
230
231         self.vlay_right = QVBoxLayout()
232         self.vlay_right.setSpacing(50)
233         self.vlay_right.addLayout(self.vlay_misc_buttons)
234         self.vlay_right.addItem(QSpacerItem(100, 2, hPolicy=QSizePolicy.Minimum, vPolicy=QSizePolicy.Expanding))
235         self.vlay_right.addWidget(self.groupbox_define_new_matrix)
236         self.vlay_right.addItem(QSpacerItem(100, 2, hPolicy=QSizePolicy.Minimum, vPolicy=QSizePolicy.Expanding))
237         self.vlay_right.addLayout(self.vlay_render)
238
239         self.hlay_all = QHBoxLayout()
240         self.hlay_all.setSpacing(15)
241         self.hlay_all.addLayout(self.vlay_left)
242         self.hlay_all.addLayout(self.vlay_right)
243
244         self.central_widget = QtWidgets.QWidget()
245         self.central_widget.setLayout(self.hlay_all)
246         self.central_widget.setContentsMargins(10, 10, 10, 10)
247
248         self.setCentralWidget(self.central_widget)
249
250     def update_render_buttons(self) -> None:
        """Enable or disable the render and animate buttons according to whether the matrix expression is valid."""

```

```

251     text = self.lineEdit_expression_box.text()
252
253     # Let's say that the user defines a non-singular matrix A, then defines B as A^-1
254     # If they then redefine A and make it singular, then we get a LinAlgError when
255     # trying to evaluate an expression with B in it
256     # To fix this, we just do naive validation rather than aware validation
257     if ',' in text:
258         self.button_render.setEnabled(False)
259
260         try:
261             valid = all(self.matrix_wrapper.is_valid_expression(x) for x in text.split(','))
262         except LinAlgError:
263             valid = all(validate_matrix_expression(x) for x in text.split(','))
264
265         self.button_animate.setEnabled(valid)
266
267     else:
268         try:
269             valid = self.matrix_wrapper.is_valid_expression(text)
270         except LinAlgError:
271             valid = validate_matrix_expression(text)
272
273         self.button_render.setEnabled(valid)
274         self.button_animate.setEnabled(valid)
275
276 @pyqtSlot()
277 def reset_zoom(self) -> None:
278     """Reset the zoom level back to normal."""
279     self.plot.grid_spacing = self.plot.default_grid_spacing
280     self.plot.update()
281
282 @pyqtSlot()
283 def reset_transformation(self) -> None:
284     """Reset the visualized transformation back to the identity."""
285     self.plot.visualize_matrix_transformation(self.matrix_wrapper['I'])
286     self.animating = False
287     self.animating_sequence = False
288     self.plot.update()
289
290 @pyqtSlot()
291 def render_expression(self) -> None:
292     """Render the transformation given by the expression in the input box."""
293     try:
294         matrix = self.matrix_wrapper.evaluate_expression(self.lineEdit_expression_box.text())
295
296     except LinAlgError:
297         self.show_error_message('Singular matrix', 'Cannot take inverse of singular matrix')
298         return
299
300     if self.is_matrix_too_big(matrix):
301         self.show_error_message('Matrix too big', 'This matrix doesn't fit on the canvas')
302         return
303
304     self.plot.visualize_matrix_transformation(matrix)
305     self.plot.update()
306
307 @pyqtSlot()
308 def animate_expression(self) -> None:
309     """Animate from the current matrix to the matrix in the expression box."""
310     self.button_render.setEnabled(False)
311     self.button_animate.setEnabled(False)
312
313     matrix_start: MatrixType = np.array([
314         [self.plot.point_i[0], self.plot.point_j[0]],
315         [self.plot.point_i[1], self.plot.point_j[1]]
316     ])
317
318     text = self.lineEdit_expression_box.text()
319
320     # If there's commas in the expression, then we want to animate each part at a time
321     if ',' in text:
322         current_matrix = matrix_start
323         self.animating_sequence = True

```



```

324
325     # For each expression in the list, right multiply it by the current matrix,
326     # and animate from the current matrix to that new matrix
327     for expr in text.split(',')[:-1]:
328         try:
329             new_matrix = self.matrix_wrapper.evaluate_expression(expr) @ current_matrix
330         except LinAlgError:
331             self.show_error_message('Singular matrix', 'Cannot take inverse of singular matrix')
332             return
333
334         if not self.animating_sequence:
335             break
336
337         self.animate_between_matrices(current_matrix, new_matrix)
338         current_matrix = new_matrix
339
340         # Here we just redraw and allow for other events to be handled while we pause
341         self.plot.update()
342         QApplication.processEvents()
343         QThread.sleep(self.plot.display_settings.animation_pause_length)
344
345     self.animating_sequence = False
346
347     # If there's no commas, then just animate directly from the start to the target
348     else:
349         # Get the target matrix and it's determinant
350         try:
351             matrix_target = self.matrix_wrapper.evaluate_expression(text)
352
353         except LinAlgError:
354             self.show_error_message('Singular matrix', 'Cannot take inverse of singular matrix')
355             return
356
357         # The concept of applicative animation is explained in /gui/settings.py
358         if self.plot.display_settings.applicative_animation:
359             matrix_target = matrix_target @ matrix_start
360
361         # If we want a transitional animation and we're animating the same matrix, then restart the animation
362         # We use this check rather than equality because of small floating point errors
363         elif (abs(matrix_start - matrix_target) < 1e-12).all():
364             matrix_start = self.matrix_wrapper['I']
365
366         # We pause here for 200 ms to make the animation look a bit nicer
367         self.plot.visualize_matrix_transformation(matrix_start)
368         self.plot.update()
369         QApplication.processEvents()
370         QThread.sleep(200)
371
372         self.animate_between_matrices(matrix_start, matrix_target)
373
374     self.update_render_buttons()
375
376 def animate_between_matrices(self, matrix_start: MatrixType, matrix_target: MatrixType, steps: int = 100) ->
↪ None:
377     """Animate from the start matrix to the target matrix."""
378     det_target = linalg.det(matrix_target)
379     det_start = linalg.det(matrix_start)
380
381     self.animating = True
382
383     for i in range(0, steps + 1):
384         if not self.animating:
385             break
386
387         # This proportion is how far we are through the loop
388         proportion = i / steps
389
390         # matrix_a is the start matrix plus some part of the target, scaled by the proportion
391         # If we just used matrix_a, then things would animate, but the determinants would be weird
392         matrix_a = matrix_start + proportion * (matrix_target - matrix_start)
393
394         if self.plot.display_settings.smoothen_determinant and det_start * det_target > 0:
395             # To fix the determinant problem, we get the determinant of matrix_a and use it to normalize

```

```

396         det_a = linalg.det(matrix_a)
397
398         # For a 2x2 matrix A and a scalar c, we know that det(cA) = c^2 det(A)
399         # We want B = cA such that det(B) = det(S), where S is the start matrix,
400         # so then we can scale it with the animation, so we get
401         # det(cA) = c^2 det(A) = det(S) => c = sqrt(abs(det(S) / det(A)))
402         # Then we scale A to get the determinant we want, and call that matrix_b
403         if det_a == 0:
404             c = 0
405         else:
406             c = np.sqrt(abs(det_start / det_a))
407
408         matrix_b = c * matrix_a
409         det_b = linalg.det(matrix_b)
410
411         # matrix_to_render is the final matrix that we then render for this frame
412         # It's B, but we scale it over time to have the target determinant
413
414         # We want some C = dB such that det(C) is some target determinant T
415         # det(dB) = d^2 det(B) = T => d = sqrt(abs(T / det(B)))
416
417         # We're also subtracting 1 and multiplying by the proportion and then adding one
418         # This just scales the determinant along with the animation
419
420         # That is all of course, if we can do that
421         # We'll crash if we try to do this with det(B) == 0
422         if det_b != 0:
423             scalar = 1 + proportion * (np.sqrt(abs(det_target / det_b)) - 1)
424             matrix_to_render = scalar * matrix_b
425
426         else:
427             matrix_to_render = matrix_a
428
429         else:
430             matrix_to_render = matrix_a
431
432         if self.is_matrix_too_big(matrix_to_render):
433             self.show_error_message('Matrix too big', "This matrix doesn't fit on the canvas")
434             return
435
436         self.plot.visualize_matrix_transformation(matrix_to_render)
437
438         # We schedule the plot to be updated, tell the event loop to
439         # process events, and asynchronously sleep for 10ms
440         # This allows for other events to be processed while animating, like zooming in and out
441         self.plot.update()
442         QApplication.processEvents()
443         QThread.sleep(1000 // steps)
444
445         self.animating = False
446
447     @pyqtSlot(DefineDialog)
448     def dialog_define_matrix(self, dialog_class: Type[DefineDialog]) -> None:
449         """Open a generic definition dialog to define a new matrix.
450
451         The class for the desired dialog is passed as an argument. We create an
452         instance of this class and the dialog is opened asynchronously and modally
453         (meaning it blocks interaction with the main window) with the proper method
454         connected to the :meth:`QDialog.accepted` signal.
455
456         .. note:: `dialog_class` must subclass :class:`lintrans.gui.dialogs.define_new_matrix.DefineDialog`.
457
458         :param dialog_class: The dialog class to instantiate
459         :type dialog_class: Type[lintrans.gui.dialogs.define_new_matrix.DefineDialog]
460         """
461
462         # We create a dialog with a deepcopy of the current matrix_wrapper
463         # This avoids the dialog mutating this one
464         dialog: DefineDialog
465
466         if dialog_class == DefineVisuallyDialog:
467             dialog = DefineVisuallyDialog(
468                 self,
469                 matrix_wrapper=deepcopy(self.matrix_wrapper),

```

```

469         display_settings=self.plot.display_settings
470     )
471     else:
472         dialog = dialog_class(self, matrix_wrapper=deepcopy(self.matrix_wrapper))
473
474     # .open() is asynchronous and doesn't spawn a new event loop, but the dialog is still modal (blocking)
475     dialog.open()
476
477     # So we have to use the accepted signal to call a method when the user accepts the dialog
478     dialog.accepted.connect(self.assign_matrix_wrapper)
479
480 @pyqtSlot()
481 def assign_matrix_wrapper(self) -> None:
482     """Assign a new value to ``self.matrix_wrapper`` and give the expression box focus."""
483     self.matrix_wrapper = self.sender().matrix_wrapper
484     self.lineedit_expression_box.setFocus()
485     self.update_render_buttons()
486
487 @pyqtSlot()
488 def dialog_change_display_settings(self) -> None:
489     """Open the dialog to change the display settings."""
490     dialog = DisplaySettingsDialog(self, display_settings=self.plot.display_settings)
491     dialog.open()
492     dialog.accepted.connect(lambda: self.assign_display_settings(dialog.display_settings))
493
494 @pyqtSlot(DisplaySettings)
495 def assign_display_settings(self, display_settings: DisplaySettings) -> None:
496     """Assign a new value to ``self.plot.display_settings`` and give the expression box focus."""
497     self.plot.display_settings = display_settings
498     self.plot.update()
499     self.lineedit_expression_box.setFocus()
500     self.update_render_buttons()
501
502 def show_error_message(self, title: str, text: str, info: str | None = None) -> None:
503     """Show an error message in a dialog box.
504
505     :param str title: The window title of the dialog box
506     :param str text: The simple error message
507     :param info: The more informative error message
508     :type info: Optional[str]
509     """
510     dialog = QMessageBox(self)
511     dialog.setIcon(QMessageBox.Critical)
512     dialog.setWindowTitle(title)
513     dialog.setText(text)
514
515     if info is not None:
516         dialog.setInformativeText(info)
517
518     dialog.open()
519
520     # This is 'finished' rather than 'accepted' because we want to update the buttons no matter what
521     dialog.finished.connect(self.update_render_buttons)
522
523 def is_matrix_too_big(self, matrix: MatrixType) -> bool:
524     """Check if the given matrix will actually fit onto the canvas.
525
526     Convert the elements of the matrix to canvas coords and make sure they fit within Qt's 32-bit integer limit.
527
528     :param MatrixType matrix: The matrix to check
529     :returns bool: Whether the matrix fits on the canvas
530     """
531     coords: list[tuple[int, int]] = [self.plot.canvas_coords(*vector) for vector in matrix.T]
532
533     for x, y in coords:
534         if not (-2147483648 <= x <= 2147483647 and -2147483648 <= y <= 2147483647):
535             return True
536
537     return False
538
539
540 def main(args: list[str]) -> None:
541     """Run the GUI by creating and showing an instance of :class:`LintransMainWindow`.

```

```

542
543     :param list[str] args: The args to pass to :class:`QApplication`
544     """
545     app = QApplication(args)
546     window = LintransMainWindow()
547     window.show()
548     sys.exit(app.exec_())

```

## A.8 gui/validate.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This simple module provides a :class:`MatrixExpressionValidator` class to validate matrix expression input."""
8
9  from __future__ import annotations
10
11  import re
12
13  from PyQt5.QtGui import QValidator
14
15  from lintrans.matrices import parse
16
17
18  class MatrixExpressionValidator(QValidator):
19     """This class validates matrix expressions in a Qt input box."""
20
21     def validate(self, text: str, pos: int) -> tuple[QValidator.State, str, int]:
22         """Validate the given text according to the rules defined in the :mod:`lintrans.matrices` module."""
23         clean_text = re.sub(parse.NAIVE_CHARACTER_CLASS[:-1] + ',]', '', text)
24
25         if clean_text == '':
26             if parse.validate_matrix_expression(clean_text):
27                 return QValidator.Acceptable, text, pos
28             else:
29                 return QValidator.Intermediate, text, pos
30
31         return QValidator.Invalid, text, pos

```

## A.9 gui/settings.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module contains the :class:`DisplaySettings` class, which holds configuration for display."""
8
9  from __future__ import annotations
10
11  from dataclasses import dataclass
12
13
14  @dataclass
15  class DisplaySettings:
16     """This class simply holds some attributes to configure display."""
17
18     # === Basic stuff
19
20     draw_background_grid: bool = True
21     """This controls whether we want to draw the background grid.
22
23     The background axes will always be drawn. This makes it easy to identify the center of the space.
24     """

```

```

25
26 draw_transformed_grid: bool = True
27 """This controls whether we want to draw the transformed grid. Vectors are handled separately."""
28
29 draw_basis_vectors: bool = True
30 """This controls whether we want to draw the transformed basis vectors."""
31
32 # === Animations
33
34 smoothen_determinant: bool = True
35 """This controls whether we want the determinant to change smoothly during the animation.
36
37 .. note::
38     Even if this is True, it will be ignored if we're animating from a positive det matrix to
39     a negative det matrix, or vice versa, because if we try to smoothly animate that determinant,
40     things blow up and the app often crashes.
41 """
42
43 applicative_animation: bool = True
44 """There are two types of simple animation, transitional and applicative.
45
46 Let ``C`` be the matrix representing the currently displayed transformation, and let ``T`` be the target matrix.
47 Transitional animation means that we animate directly from ``C`` from ``T``,
48 and applicative animation means that we animate from ``C`` to ``TC``, so we apply ``T`` to ``C``.
49 """
50
51 animation_pause_length: int = 400
52 """This is the number of milliseconds that we wait between animations when using comma syntax."""
53
54 # === Matrix info
55
56 draw_determinant_parallelogram: bool = False
57 """This controls whether or not we should shade the parallelogram representing the determinant of the matrix."""
58
59 show_determinant_value: bool = True
60 """This controls whether we should write the text value of the determinant inside the parallelogram.
61
62 The text only gets draw if :attr:`draw_determinant_parallelogram` is also True.
63 """
64
65 draw_eigenvectors: bool = False
66 """This controls whether we should draw the eigenvectors of the transformation."""
67
68 draw_eigenlines: bool = False
69 """This controls whether we should draw the eigenlines of the transformation."""

```

## A.10 gui/plots/widgets.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """This module provides the actual widgets that can be used to visualize transformations in the GUI."""
8
9 from __future__ import annotations
10
11 from PyQt5.QtCore import Qt
12 from PyQt5.QtGui import QMouseEvent, QPainter, QPaintEvent
13
14 from .classes import VectorGridPlot
15 from lintrans.typing_ import MatrixType
16 from lintrans.gui.settings import DisplaySettings
17
18
19 class VisualizeTransformationWidget(VectorGridPlot):
20     """This class is the widget that is used in the main window to visualize transformations.
21
22     It handles all the rendering itself, and the only method that the user needs to

```

```

23     worry about is :meth:`visualize_matrix_transformation`, which allows you to visualize
24     the given matrix transformation.
25     """
26
27     def __init__(self, *args, display_settings: DisplaySettings, **kwargs):
28         """Create the widget and assign its display settings, passing ``*args`` and ``**kwargs`` to super."""
29         super().__init__(*args, **kwargs)
30
31         self.display_settings = display_settings
32
33     def visualize_matrix_transformation(self, matrix: MatrixType) -> None:
34         """Transform the grid by the given matrix.
35
36         .. warning:: This method does not call ``update()``. This must be done by the caller.
37
38         .. note::
39             This method transforms the background grid, not the basis vectors. This
40             means that it cannot be used to compose transformations. Compositions
41             should be done by the user.
42
43             :param MatrixType matrix: The matrix to transform by
44             """
45         self.point_i = (matrix[0][0], matrix[1][0])
46         self.point_j = (matrix[0][1], matrix[1][1])
47
48     def paintEvent(self, event: QPaintEvent) -> None:
49         """Handle a :class:`QPaintEvent` by drawing the background grid and the transformed grid.
50
51         The transformed grid is defined by the basis vectors i and j, which can
52         be controlled with the :meth:`visualize_matrix_transformation` method.
53         """
54         painter = QPainter()
55         painter.begin(self)
56
57         painter.setRenderHint(QPainter.Antialiasing)
58         painter.setBrush(Qt.NoBrush)
59
60         self.draw_background(painter, self.display_settings.draw_background_grid)
61
62         if self.display_settings.draw_eigenlines:
63             self.draw_eigenlines(painter)
64
65         if self.display_settings.draw_eigenvectors:
66             self.draw_eigenvectors(painter)
67
68         if self.display_settings.draw_determinant_parallelogram:
69             self.draw_determinant_parallelogram(painter)
70
71             if self.display_settings.show_determinant_value:
72                 self.draw_determinant_text(painter)
73
74         if self.display_settings.draw_transformed_grid:
75             self.draw_transformed_grid(painter)
76
77         if self.display_settings.draw_basis_vectors:
78             self.draw_basis_vectors(painter)
79
80         painter.end()
81         event.accept()
82
83
84     class DefineVisuallyWidget(VisualizeTransformationWidget):
85         """This class is the widget that allows the user to visually define a matrix.
86
87         This is just the widget itself. If you want the dialog, use
88         :class:`lintrans.gui.dialogs.define_new_matrix.DefineVisuallyDialog`.
89         """
90
91     def __init__(self, *args, display_settings: DisplaySettings, **kwargs):
92         """Create the widget and enable mouse tracking. ``*args`` and ``**kwargs`` are passed to ``super()``."""
93         super().__init__(*args, display_settings=display_settings, **kwargs)
94
95         self.dragged_point: tuple[float, float] | None = None

```

```

96
97     # This is the distance that the cursor needs to be from the point to drag it
98     self.epsilon: int = 5
99
100 def mousePressEvent(self, event: QMouseEvent) -> None:
101     """Handle a QMouseEvent when the user pressed a button."""
102     mx = event.x()
103     my = event.y()
104     button = event.button()
105
106     if button != Qt.LeftButton:
107         event.ignore()
108         return
109
110     for point in (self.point_i, self.point_j):
111         px, py = self.canvas_coords(*point)
112         if abs(px - mx) <= self.epsilon and abs(py - my) <= self.epsilon:
113             self.dragged_point = point[0], point[1]
114
115     event.accept()
116
117 def mouseReleaseEvent(self, event: QMouseEvent) -> None:
118     """Handle a QMouseEvent when the user release a button."""
119     if event.button() == Qt.LeftButton:
120         self.dragged_point = None
121         event.accept()
122     else:
123         event.ignore()
124
125 def mouseMoveEvent(self, event: QMouseEvent) -> None:
126     """Handle the mouse moving on the canvas."""
127     mx = event.x()
128     my = event.y()
129
130     if self.dragged_point is not None:
131         x, y = self.grid_coords(mx, my)
132
133         if self.dragged_point == self.point_i:
134             self.point_i = x, y
135
136         elif self.dragged_point == self.point_j:
137             self.point_j = x, y
138
139         self.dragged_point = x, y
140
141         self.update()
142
143         event.accept()
144
145     event.ignore()

```

## A.11 gui/plots/\_\_init\_\_.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """This package provides widgets for the visualization plot in the main window and the visual definition dialog."""
8
9 from . import classes
10 from .widgets import DefineVisuallyWidget, VisualizeTransformationWidget
11
12 __all__ = ['classes', 'DefineVisuallyWidget', 'VisualizeTransformationWidget']

```

## A.12 gui/plots/classes.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides superclasses for plotting transformations."""
8
9  from __future__ import annotations
10
11  from abc import abstractmethod
12  from typing import Iterable
13
14  import numpy as np
15  from nptyping import Float, NDArray
16  from PyQt5.QtCore import QPoint, QRectF, Qt
17  from PyQt5.QtGui import QBrush, QColor, QPainter, QPainterPath, QPaintEvent, QPen, QWheelEvent
18  from PyQt5.QtWidgets import QWidget
19
20  from lintrans.typing_ import MatrixType
21
22
23  class BackgroundPlot(QWidget):
24      """This class provides a background for plotting, as well as setup for a Qt widget.
25
26      This class provides a background (untransformed) plane, and all the backend
27      details for a Qt application, but does not provide useful functionality. To
28      be useful, this class must be subclassed and behaviour must be implemented
29      by the subclass.
30
31      .. warning:: This class should never be directly instantiated, only subclassed.
32
33      .. note::
34      I would make this class have ``metaclass=abc.ABCMeta``, but I can't because it subclasses :class:`QWidget`,
35      and every superclass of a class must have the same metaclass, and :class:`QWidget` is not an abstract class.
36      """
37
38      default_grid_spacing: int = 85
39      minimum_grid_spacing: int = 5
40
41      def __init__(self, *args, **kwargs):
42          """Create the widget and setup backend stuff for rendering.
43
44          .. note:: ``*args`` and ``**kwargs`` are passed the superclass constructor (:class:`QWidget`).
45          """
46          super().__init__(*args, **kwargs)
47
48          self.setAutoFillBackground(True)
49
50          # Set the background to white
51          palette = self.palette()
52          palette.setColor(self.backgroundRole(), Qt.white)
53          self.setPalette(palette)
54
55          # Set the grid colour to grey and the axes colour to black
56          self.colour_background_grid = QColor('#808080')
57          self.colour_background_axes = QColor('#000000')
58
59          self.grid_spacing = BackgroundPlot.default_grid_spacing
60          self.width_background_grid: float = 0.3
61
62      @property
63      def canvas_origin(self) -> tuple[int, int]:
64          """Return the canvas coords of the grid origin.
65
66          The return value is intended to be unpacked and passed to a :meth:`QPainter.drawLine:iiii` call.
67
68          See :meth:`canvas_coords`.
69
70          :returns: The canvas coordinates of the grid origin

```



```

71         :rtype: tuple[int, int]
72         """
73         return self.width() // 2, self.height() // 2
74
75     def canvas_x(self, x: float) -> int:
76         """Convert an x coordinate from grid coords to canvas coords."""
77         return int(self.canvas_origin[0] + x * self.grid_spacing)
78
79     def canvas_y(self, y: float) -> int:
80         """Convert a y coordinate from grid coords to canvas coords."""
81         return int(self.canvas_origin[1] - y * self.grid_spacing)
82
83     def canvas_coords(self, x: float, y: float) -> tuple[int, int]:
84         """Convert a coordinate from grid coords to canvas coords.
85
86         This method is intended to be used like
87
88         .. code::
89
90             painter.drawLine(*self.canvas_coords(x1, y1), *self.canvas_coords(x2, y2))
91
92         or like
93
94         .. code::
95
96             painter.drawLine(*self.canvas_origin, *self.canvas_coords(x, y))
97
98         See :attr:`canvas_origin`.
99
100        :param float x: The x component of the grid coordinate
101        :param float y: The y component of the grid coordinate
102        :returns: The resultant canvas coordinates
103        :rtype: tuple[int, int]
104        """
105        return self.canvas_x(x), self.canvas_y(y)
106
107     def grid_corner(self) -> tuple[float, float]:
108         """Return the grid coords of the top right corner."""
109         return self.width() / (2 * self.grid_spacing), self.height() / (2 * self.grid_spacing)
110
111     def grid_coords(self, x: int, y: int) -> tuple[float, float]:
112         """Convert a coordinate from canvas coords to grid coords.
113
114        :param int x: The x component of the canvas coordinate
115        :param int y: The y component of the canvas coordinate
116        :returns: The resultant grid coordinates
117        :rtype: tuple[float, float]
118        """
119        # We get the maximum grid coords and convert them into canvas coords
120        return (x - self.canvas_origin[0]) / self.grid_spacing, (-y + self.canvas_origin[1]) / self.grid_spacing
121
122     @abstractmethod
123     def paintEvent(self, event: QPaintEvent) -> None:
124         """Handle a :class:`QPaintEvent`.
125
126        .. note:: This method is abstract and must be overridden by all subclasses.
127        """
128
129     def draw_background(self, painter: QPainter, draw_grid: bool) -> None:
130         """Draw the background grid.
131
132        .. note:: This method is just a utility method for subclasses to use to render the background grid.
133
134        :param QPainter painter: The painter to draw the background with
135        :param bool draw_grid: Whether to draw the grid lines
136        """
137        if draw_grid:
138            painter.setPen(QPen(self.colour_background_grid, self.width_background_grid))
139
140            # Draw equally spaced vertical lines, starting in the middle and going out
141            # We loop up to half of the width. This is because we draw a line on each side in each iteration
142            for x in range(self.width() // 2 + self.grid_spacing, self.width(), self.grid_spacing):
143                painter.drawLine(x, 0, x, self.height())

```

```

144         painter.drawLine(self.width() - x, 0, self.width() - x, self.height())
145
146         # Same with the horizontal lines
147         for y in range(self.height() // 2 + self.grid_spacing, self.height(), self.grid_spacing):
148             painter.drawLine(0, y, self.width(), y)
149             painter.drawLine(0, self.height() - y, self.width(), self.height() - y)
150
151         # Now draw the axes
152         painter.setPen(QPen(self.colour_background_axes, self.width_background_grid))
153         painter.drawLine(self.width() // 2, 0, self.width() // 2, self.height())
154         painter.drawLine(0, self.height() // 2, self.width(), self.height() // 2)
155
156     def wheelEvent(self, event: QWheelEvent) -> None:
157         """Handle a :class:`QWheelEvent` by zooming in or out of the grid."""
158         # angleDelta() returns a number of units equal to 8 times the number of degrees rotated
159         degrees = event.angleDelta() / 8
160
161         if degrees is not None:
162             new_spacing = max(1, self.grid_spacing + degrees.y())
163
164             if new_spacing >= self.minimum_grid_spacing:
165                 self.grid_spacing = new_spacing
166
167         event.accept()
168         self.update()
169
170
171     class VectorGridPlot(BackgroundPlot):
172         """This class represents a background plot, with vectors and their grid drawn on top.
173
174         This class should be subclassed to be used for visualization and matrix definition widgets.
175         All useful behaviour should be implemented by any subclass.
176
177         .. warning:: This class should never be directly instantiated, only subclassed.
178         """
179
180         def __init__(self, *args, **kwargs):
181             """Create the widget with ``point_i`` and ``point_j`` attributes.
182
183             .. note:: ``*args`` and ``**kwargs`` are passed to the superclass constructor (:class:`BackgroundPlot`).
184             """
185             super().__init__(*args, **kwargs)
186
187             self.point_i: tuple[float, float] = (1., 0.)
188             self.point_j: tuple[float, float] = (0., 1.)
189
190             self.colour_i = QColor('#0808d8')
191             self.colour_j = QColor('#e90000')
192             self.colour_eigen = QColor('#13cf00')
193             self.colour_text = QColor('#000000')
194
195             self.width_vector_line = 1.8
196             self.width_transformed_grid = 0.8
197
198             self.arrowhead_length = 0.15
199
200             self.max_parallel_lines = 150
201
202         @property
203         def matrix(self) -> MatrixType:
204             """Return the assembled matrix of the basis vectors."""
205             return np.array([
206                 [self.point_i[0], self.point_j[0]],
207                 [self.point_i[1], self.point_j[1]]
208             ])
209
210         @property
211         def det(self) -> float:
212             """Return the determinant of the assembled matrix."""
213             return float(np.linalg.det(self.matrix))
214
215         @property
216         def eigs(self) -> Iterable[tuple[float, NDArray[(1, 2), Float]]]:

```

```

217         """Return the eigenvalues and eigenvectors zipped together to be iterated over.
218
219         :rtype: Iterable[tuple[float, NDArray[(1, 2), Float]]]
220         """
221         values, vectors = np.linalg.eig(self.matrix)
222         return zip(values, vectors.T)
223
224     @abstractmethod
225     def paintEvent(self, event: QPaintEvent) -> None:
226         """Handle a :class:`QPaintEvent`.
227
228         .. note:: This method is abstract and must be overridden by all subclasses.
229         """
230
231     def draw_parallel_lines(self, painter: QPainter, vector: tuple[float, float], point: tuple[float, float]) ->
232         None:
233         """Draw a set of evenly spaced grid lines parallel to ``vector`` intersecting ``point``.
234
235         :param QPainter painter: The painter to draw the lines with
236         :param vector: The vector to draw the grid lines parallel to
237         :type vector: tuple[float, float]
238         :param point: The point for the lines to intersect with
239         :type point: tuple[float, float]
240         """
241         max_x, max_y = self.grid_corner()
242         vector_x, vector_y = vector
243         point_x, point_y = point
244
245         # If the determinant is 0
246         if abs(vector_x * point_y - vector_y * point_x) < 1e-12:
247             rank = np.linalg.matrix_rank(
248                 np.array([
249                     [vector_x, point_x],
250                     [vector_y, point_y]
251                 ])
252             )
253
254             # If the matrix is rank 1, then we can draw the column space line
255             if rank == 1:
256                 if abs(vector_x) < 1e-12:
257                     painter.drawLine(self.width() // 2, 0, self.width() // 2, self.height())
258                 elif abs(vector_y) < 1e-12:
259                     painter.drawLine(0, self.height() // 2, self.width(), self.height() // 2)
260                 else:
261                     self.draw_oblique_line(painter, vector_y / vector_x, 0)
262
263             # If the rank is 0, then we don't draw any lines
264             else:
265                 return
266
267         elif abs(vector_x) < 1e-12 and abs(vector_y) < 1e-12:
268             # If both components of the vector are practically 0, then we can't render any grid lines
269             return
270
271         # Draw vertical lines
272         elif abs(vector_x) < 1e-12:
273             painter.drawLine(self.canvas_x(0), 0, self.canvas_x(0), self.height())
274
275             for i in range(max(abs(int(max_x / point_x)), self.max_parallel_lines)):
276                 painter.drawLine(
277                     self.canvas_x((i + 1) * point_x),
278                     0,
279                     self.canvas_x((i + 1) * point_x),
280                     self.height()
281                 )
282             painter.drawLine(
283                 self.canvas_x(-1 * (i + 1) * point_x),
284                 0,
285                 self.canvas_x(-1 * (i + 1) * point_x),
286                 self.height()
287             )
288
289         # Draw horizontal lines

```

```

289     elif abs(vector_y) < 1e-12:
290         painter.drawLine(0, self.canvas_y(0), self.width(), self.canvas_y(0))
291
292     for i in range(max(abs(int(max_y / point_y)), self.max_parallel_lines)):
293         painter.drawLine(
294             0,
295             self.canvas_y((i + 1) * point_y),
296             self.width(),
297             self.canvas_y((i + 1) * point_y)
298         )
299         painter.drawLine(
300             0,
301             self.canvas_y(-1 * (i + 1) * point_y),
302             self.width(),
303             self.canvas_y(-1 * (i + 1) * point_y)
304         )
305
306     # If the line is oblique, then we can use y = mx + c
307     else:
308         m = vector_y / vector_x
309         c = point_y - m * point_x
310
311         self.draw_oblique_line(painter, m, 0)
312
313         # We don't want to overshoot the max number of parallel lines,
314         # but we should also stop looping as soon as we can't draw any more lines
315         for i in range(1, self.max_parallel_lines + 1):
316             if not self.draw_pair_of_oblique_lines(painter, m, i * c):
317                 break
318
319 def draw_pair_of_oblique_lines(self, painter: QPainter, m: float, c: float) -> bool:
320     """Draw a pair of oblique lines, using the equation y = mx + c.
321
322     This method just calls :meth:`draw_oblique_line` with ``c`` and ``-c``,
323     and returns True if either call returned True.
324
325     :param QPainter painter: The painter to draw the vectors and grid lines with
326     :param float m: The gradient of the lines to draw
327     :param float c: The y-intercept of the lines to draw. We use the positive and negative versions
328     :returns bool: Whether we were able to draw any lines on the canvas
329     """
330     return any([
331         self.draw_oblique_line(painter, m, c),
332         self.draw_oblique_line(painter, m, -c)
333     ])
334
335 def draw_oblique_line(self, painter: QPainter, m: float, c: float) -> bool:
336     """Draw an oblique line, using the equation y = mx + c.
337
338     We only draw the part of the line that fits within the canvas, returning True if
339     we were able to draw a line within the boundaries, and False if we couldn't draw a line
340
341     :param QPainter painter: The painter to draw the vectors and grid lines with
342     :param float m: The gradient of the line to draw
343     :param float c: The y-intercept of the line to draw
344     :returns bool: Whether we were able to draw a line on the canvas
345     """
346     max_x, max_y = self.grid_corner()
347
348     # These variable names are shortened for convenience
349     # myi is max_y_intersection, mmyi is minus_max_y_intersection, etc.
350     myi = (max_y - c) / m
351     mmyi = (-max_y - c) / m
352     mx_i = max_x * m + c
353     mmxi = -max_x * m + c
354
355     # The inner list here is a list of coords, or None
356     # If an intersection fits within the bounds, then we keep its coord,
357     # else it is None, and then gets discarded from the points list
358     # By the end, points is a list of two coords, or an empty list
359     points: list[tuple[float, float]] = [
360         x for x in [
361             (myi, max_y) if -max_x < myi < max_x else None,

```

```

362         (mmyi, -max_y) if -max_x < mmyi < max_x else None,
363         (max_x, mxi) if -max_y < mxi < max_y else None,
364         (-max_x, mmxi) if -max_y < mmxi < max_y else None
365     ] if x is not None
366 ]
367
368 # If no intersections fit on the canvas
369 if len(points) < 2:
370     return False
371
372 # If we can, then draw the line
373 else:
374     painter.drawLine(
375         *self.canvas_coords(*points[0]),
376         *self.canvas_coords(*points[1])
377     )
378     return True
379
380 def draw_transformed_grid(self, painter: QPainter) -> None:
381     """Draw the transformed version of the grid, given by the basis vectors.
382
383     .. note:: This method draws the grid, but not the basis vectors. Use :meth:`draw_basis_vectors` to draw
↪ them.
384
385     :param QPainter painter: The painter to draw the grid lines with
386     """
387     # Draw all the parallel lines
388     painter.setPen(QPen(self.colour_i, self.width_transformed_grid))
389     self.draw_parallel_lines(painter, self.point_i, self.point_j)
390     painter.setPen(QPen(self.colour_j, self.width_transformed_grid))
391     self.draw_parallel_lines(painter, self.point_j, self.point_i)
392
393 def draw_arrowhead_away_from_origin(self, painter: QPainter, point: tuple[float, float]) -> None:
394     """Draw an arrowhead at ``point``, pointing away from the origin.
395
396     :param QPainter painter: The painter to draw the arrowhead with
397     :param point: The point to draw the arrowhead at, given in grid coords
398     :type point: tuple[float, float]
399     """
400     # This algorithm was adapted from a C# algorithm found at
401     # http://csharpshelper.com/blog/2014/12/draw-lines-with-arrowheads-in-c/
402
403     # Get the x and y coords of the point, and then normalize them
404     # We have to normalize them, or else the size of the arrowhead will
405     # scale with the distance of the point from the origin
406     x, y = point
407     vector_length = np.sqrt(x * x + y * y)
408
409     if vector_length < 1e-12:
410         return
411
412     nx = x / vector_length
413     ny = y / vector_length
414
415     # We choose a length and find the steps in the x and y directions
416     length = min(
417         self.arrowhead_length * self.default_grid_spacing / self.grid_spacing,
418         vector_length
419     )
420     dx = length * (-nx - ny)
421     dy = length * (nx - ny)
422
423     # Then we just plot those lines
424     painter.drawLine(*self.canvas_coords(x, y), *self.canvas_coords(x + dx, y + dy))
425     painter.drawLine(*self.canvas_coords(x, y), *self.canvas_coords(x - dy, y + dx))
426
427 def draw_position_vector(self, painter: QPainter, point: tuple[float, float], colour: QColor) -> None:
428     """Draw a vector from the origin to the given point.
429
430     :param QPainter painter: The painter to draw the position vector with
431     :param point: The tip of the position vector in grid coords
432     :type point: tuple[float, float]
433     :param QColor colour: The colour to draw the position vector in

```

```

434         """
435         painter.setPen(QPen(colour, self.width_vector_line))
436         painter.drawLine(*self.canvas_origin, *self.canvas_coords(*point))
437         self.draw_arrowhead_away_from_origin(painter, point)
438
439     def draw_basis_vectors(self, painter: QPainter) -> None:
440         """Draw arrowheads at the tips of the basis vectors.
441
442         :param QPainter painter: The painter to draw the basis vectors with
443         """
444         self.draw_position_vector(painter, self.point_i, self.colour_i)
445         self.draw_position_vector(painter, self.point_j, self.colour_j)
446
447     def draw_determinant_parallelagram(self, painter: QPainter) -> None:
448         """Draw the parallelogram of the determinant of the matrix.
449
450         :param QPainter painter: The painter to draw the parallelogram with
451         """
452         if self.det == 0:
453             return
454
455         path = QPainterPath()
456         path.moveTo(*self.canvas_origin)
457         path.lineTo(*self.canvas_coords(*self.point_i))
458         path.lineTo(*self.canvas_coords(self.point_i[0] + self.point_j[0], self.point_i[1] + self.point_j[1]))
459         path.lineTo(*self.canvas_coords(*self.point_j))
460
461         color = (16, 235, 253) if self.det > 0 else (253, 34, 16)
462         brush = QBrush(QColor(*color, alpha=128), Qt.SolidPattern)
463
464         painter.fillPath(path, brush)
465
466     def draw_determinant_text(self, painter: QPainter) -> None:
467         """Write the string value of the determinant in the middle of the parallelogram.
468
469         :param QPainter painter: The painter to draw the determinant text with
470         """
471         painter.setPen(QPen(self.colour_text, self.width_vector_line))
472
473         # We're building a QRect that encloses the determinant parallelogram
474         # Then we can center the text in this QRect
475         coords: list[tuple[float, float]] = [
476             (0, 0),
477             self.point_i,
478             self.point_j,
479             (
480                 self.point_i[0] + self.point_j[0],
481                 self.point_i[1] + self.point_j[1]
482             )
483         ]
484
485         xs = [t[0] for t in coords]
486         ys = [t[1] for t in coords]
487
488         top_left = QPoint(*self.canvas_coords(min(xs), max(ys)))
489         bottom_right = QPoint(*self.canvas_coords(max(xs), min(ys)))
490
491         rect = QRectF(top_left, bottom_right)
492
493         painter.drawText(
494             rect,
495             Qt.AlignHCenter | Qt.AlignVCenter,
496             f'{self.det:.2f}'
497         )
498
499     def draw_eigenvectors(self, painter: QPainter) -> None:
500         """Draw the eigenvectors of the displayed matrix transformation.
501
502         :param QPainter painter: The painter to draw the eigenvectors with
503         """
504         for value, vector in self.eigs:
505             x = value * vector[0]
506             y = value * vector[1]

```

```

507
508         if x.imag != 0 or y.imag != 0:
509             continue
510
511         self.draw_position_vector(painter, (x, y), self.colour_eigen)
512
513         # Now we need to draw the eigenvalue at the tip of the eigenvector
514
515         offset = 3
516         top_left: QPoint
517         bottom_right: QPoint
518         alignment_flags: int
519
520         if x >= 0 and y >= 0: # Q1
521             top_left = QPoint(self.canvas_x(x) + offset, 0)
522             bottom_right = QPoint(self.width(), self.canvas_y(y) - offset)
523             alignment_flags = Qt.AlignLeft | Qt.AlignBottom
524
525         elif x < 0 and y >= 0: # Q2
526             top_left = QPoint(0, 0)
527             bottom_right = QPoint(self.canvas_x(x) - offset, self.canvas_y(y) - offset)
528             alignment_flags = Qt.AlignRight | Qt.AlignBottom
529
530         elif x < 0 and y < 0: # Q3
531             top_left = QPoint(0, self.canvas_y(y) + offset)
532             bottom_right = QPoint(self.canvas_x(x) - offset, self.height())
533             alignment_flags = Qt.AlignRight | Qt.AlignTop
534
535         else: # Q4
536             top_left = QPoint(self.canvas_x(x) + offset, self.canvas_y(y) + offset)
537             bottom_right = QPoint(self.width(), self.height())
538             alignment_flags = Qt.AlignLeft | Qt.AlignTop
539
540         painter.setPen(QPen(self.colour_text, self.width_vector_line))
541         painter.drawText(QRectF(top_left, bottom_right), alignment_flags, f'{value:.2f}')
542
543     def draw_eigenlines(self, painter: QPainter) -> None:
544         """Draw the eigenlines (invariant lines).
545
546         :param QPainter painter: The painter to draw the eigenlines with
547         """
548         painter.setPen(QPen(self.colour_eigen, self.width_transformed_grid))
549
550         for value, vector in self.eigs:
551             if value.imag != 0:
552                 continue
553
554             x, y = vector
555
556             if x == 0:
557                 x_mid = int(self.width() / 2)
558                 painter.drawLine(x_mid, 0, x_mid, self.height())
559
560             elif y == 0:
561                 y_mid = int(self.height() / 2)
562                 painter.drawLine(0, y_mid, self.width(), y_mid)
563
564             else:
565                 self.draw_oblique_line(painter, y / x, 0)

```

## A.13 gui/dialogs/\_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package provides separate dialogs for the main GUI.
8

```

```

9     These dialogs are for defining new matrices in different ways and editing settings.
10     """
11
12     from .define_new_matrix import DefineAsAnExpressionDialog, DefineDialog, DefineNumericallyDialog,
13     ↪ DefineVisuallyDialog
14     from .misc import AboutDialog
15     from .settings import DisplaySettingsDialog
16
17     __all__ = ['DefineAsAnExpressionDialog', 'DefineDialog', 'DefineNumericallyDialog', 'DefineVisuallyDialog',
18               'AboutDialog', 'DisplaySettingsDialog']

```

## A.14 gui/dialogs/define\_new\_matrix.py

```

1     # lintrans - The linear transformation visualizer
2     # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4     # This program is licensed under GNU GPLv3, available here:
5     # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7     """This module provides an abstract :class:`DefineDialog` class and subclasses, allowing definition of new
8     ↪ matrices."""
9
10    from __future__ import annotations
11
12    import abc
13
14    from numpy import array
15    from PyQt5 import QtWidgets
16    from PyQt5.QtCore import pyqtSlot
17    from PyQt5.QtGui import QDoubleValidator, QKeySequence
18    from PyQt5.QtWidgets import QGridLayout, QHBoxLayout, QShortcut, QSizePolicy, QSpacerItem, QVBoxLayout
19
20    from lintrans.gui.dialogs.misc import FixedSizeDialog
21    from lintrans.gui.plots import DefineVisuallyWidget
22    from lintrans.gui.settings import DisplaySettings
23    from lintrans.gui.validate import MatrixExpressionValidator
24    from lintrans.matrices import MatrixWrapper
25    from lintrans.typing_ import MatrixType
26
27    ALPHABET_NO_I = 'ABCDEFGHJKLMNPQRSTUVWXYZ'
28
29    def is_valid_float(string: str) -> bool:
30        """Check if the string is a valid float (or anything that can be cast to a float, such as an int).
31
32        This function simply checks that ``float(string)`` doesn't raise an error.
33
34        .. note:: An empty string is not a valid float, so will return False.
35
36        :param str string: The string to check
37        :returns bool: Whether the string is a valid float
38        """
39        try:
40            float(string)
41            return True
42        except ValueError:
43            return False
44
45    def round_float(num: float, precision: int = 5) -> str:
46        """Round a floating point number to a given number of decimal places for pretty printing.
47
48        :param float num: The number to round
49        :param int precision: The number of decimal places to round to
50        :returns str: The rounded number for pretty printing
51        """
52
53        # Round to ``precision`` number of decimal places
54        string = str(round(num, precision))
55
56        # Cut off the potential final zero

```



```

57     if string.endswith('.0'):
58         return string[:-2]
59
60     elif 'e' in string: # Scientific notation
61         split = string.split('e')
62         # The leading 0 only happens when the exponent is negative, so we know there'll be a minus sign
63         return split[0] + 'e-' + split[1][1:].lstrip('0')
64
65     else:
66         return string
67
68
69 class DefineDialog(FixedSizeDialog):
70     """An abstract superclass for definitions dialogs.
71
72     .. warning:: This class should never be directly instantiated, only subclassed.
73
74     .. note::
75         I would make this class have ``metaclass=abc.ABCMeta``, but I can't because it subclasses :class:`QDialog`,
76         and every superclass of a class must have the same metaclass, and :class:`QDialog` is not an abstract class.
77     """
78
79     def __init__(self, *args, matrix_wrapper: MatrixWrapper, **kwargs):
80         """Create the widgets and layout of the dialog.
81
82         .. note:: ``*args`` and ``**kwargs`` are passed to the super constructor (:class:`QDialog`).
83
84         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
85         """
86         super().__init__(*args, **kwargs)
87
88         self.matrix_wrapper = matrix_wrapper
89         self.setWindowTitle('Define a matrix')
90
91         # === Create the widgets
92
93         self.button_confirm = QtWidgets.QPushButton(self)
94         self.button_confirm.setText('Confirm')
95         self.button_confirm.setEnabled(False)
96         self.button_confirm.clicked.connect(self.confirm_matrix)
97         self.button_confirm.setToolTip('Confirm this as the new matrix<br><b>(Ctrl + Enter)</b>')
98         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self.button_confirm.click)
99
100        self.button_cancel = QtWidgets.QPushButton(self)
101        self.button_cancel.setText('Cancel')
102        self.button_cancel.clicked.connect(self.reject)
103        self.button_cancel.setToolTip('Cancel this definition<br><b>(Escape)</b>')
104
105        self.label_equals = QtWidgets.QLabel()
106        self.label_equals.setText('=')
107
108        self.combobox_letter = QtWidgets.QComboBox(self)
109
110        for letter in ALPHABET_NO_I:
111            self.combobox_letter.addItem(letter)
112
113        self.combobox_letter.activated.connect(self.load_matrix)
114
115        # === Arrange the widgets
116
117        self.setContentsMargins(10, 10, 10, 10)
118
119        self.hlay_buttons = QHBoxLayout()
120        self.hlay_buttons.setSpacing(20)
121        self.hlay_buttons.addItem(QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum))
122        self.hlay_buttons.addWidget(self.button_cancel)
123        self.hlay_buttons.addWidget(self.button_confirm)
124
125        self.hlay_definition = QHBoxLayout()
126        self.hlay_definition.setSpacing(20)
127        self.hlay_definition.addWidget(self.combobox_letter)
128        self.hlay_definition.addWidget(self.label_equals)
129

```

```

130         self.vlay_all = QVBoxLayout()
131         self.vlay_all.setSpacing(20)
132
133         self.setLayout(self.vlay_all)
134
135     @property
136     def selected_letter(self) -> str:
137         """Return the letter currently selected in the combo box."""
138         return str(self.combobox_letter.currentText())
139
140     @abc.abstractmethod
141     @pyqtSlot()
142     def update_confirm_button(self) -> None:
143         """Enable the confirm button if it should be enabled, else, disable it."""
144
145     @pyqtSlot(int)
146     def load_matrix(self, index: int) -> None:
147         """Load the selected matrix into the dialog.
148
149         This method is optionally able to be overridden. If it is not overridden,
150         then no matrix is loaded when selecting a name.
151
152         We have this method in the superclass so that we can define it as the slot
153         for the :meth:`QComboBox.activated` signal in this constructor, rather than
154         having to define that in the constructor of every subclass.
155         """
156
157     @abc.abstractmethod
158     @pyqtSlot()
159     def confirm_matrix(self) -> None:
160         """Confirm the inputted matrix and assign it.
161
162         .. note:: When subclassing, this method should mutate ``self.matrix_wrapper`` and then call
163         ↳ ``self.accept()``.
164         """
165
166 class DefineVisuallyDialog(DefineDialog):
167     """The dialog class that allows the user to define a matrix visually."""
168
169     def __init__(self, *args, matrix_wrapper: MatrixWrapper, display_settings: DisplaySettings, **kwargs):
170         """Create the widgets and layout of the dialog.
171
172         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
173         """
174         super().__init__(*args, matrix_wrapper=matrix_wrapper, **kwargs)
175
176         self.setMinimumSize(700, 550)
177
178         # === Create the widgets
179
180         self.plot = DefineVisuallyWidget(self, display_settings=display_settings)
181
182         # === Arrange the widgets
183
184         self.hlay_definition.addWidget(self.plot)
185         self.hlay_definition.setStretchFactor(self.plot, 1)
186
187         self.vlay_all.addLayout(self.hlay_definition)
188         self.vlay_all.addLayout(self.hlay_buttons)
189
190         # We load the default matrix A into the plot
191         self.load_matrix(0)
192
193         # We also enable the confirm button, because any visually defined matrix is valid
194         self.button_confirm.setEnabled(True)
195
196     @pyqtSlot()
197     def update_confirm_button(self) -> None:
198         """Enable the confirm button.
199
200         .. note::
201         The confirm button is always enabled in this dialog and this method is never actually used,

```

```

202         so it's got an empty body. It's only here because we need to implement the abstract method.
203         """
204
205     @pyqtSlot(int)
206     def load_matrix(self, index: int) -> None:
207         """Show the selected matrix on the plot. If the matrix is None, show the identity."""
208         matrix = self.matrix_wrapper[self.selected_letter]
209
210         if matrix is None:
211             matrix = self.matrix_wrapper['I']
212
213         self.plot.visualize_matrix_transformation(matrix)
214         self.plot.update()
215
216     @pyqtSlot()
217     def confirm_matrix(self) -> None:
218         """Confirm the matrix that's been defined visually."""
219         matrix: MatrixType = array([
220             [self.plot.point_i[0], self.plot.point_j[0]],
221             [self.plot.point_i[1], self.plot.point_j[1]]
222         ])
223
224         self.matrix_wrapper[self.selected_letter] = matrix
225         self.accept()
226
227
228 class DefineNumericallyDialog(Definedialog):
229     """The dialog class that allows the user to define a new matrix numerically."""
230
231     def __init__(self, *args, matrix_wrapper: MatrixWrapper, **kwargs):
232         """Create the widgets and layout of the dialog.
233
234         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
235         """
236         super().__init__(*args, matrix_wrapper=matrix_wrapper, **kwargs)
237
238         # === Create the widgets
239
240         # tl = top left, br = bottom right, etc.
241         self.element_tl = QtWidgets.QLineEdit(self)
242         self.element_tl.textChanged.connect(self.update_confirm_button)
243         self.element_tl.setValidator(QDoubleValidator())
244
245         self.element_tr = QtWidgets.QLineEdit(self)
246         self.element_tr.textChanged.connect(self.update_confirm_button)
247         self.element_tr.setValidator(QDoubleValidator())
248
249         self.element_bl = QtWidgets.QLineEdit(self)
250         self.element_bl.textChanged.connect(self.update_confirm_button)
251         self.element_bl.setValidator(QDoubleValidator())
252
253         self.element_br = QtWidgets.QLineEdit(self)
254         self.element_br.textChanged.connect(self.update_confirm_button)
255         self.element_br.setValidator(QDoubleValidator())
256
257         self.matrix_elements = (self.element_tl, self.element_tr, self.element_bl, self.element_br)
258
259         # === Arrange the widgets
260
261         self.grid_matrix = QGridLayout()
262         self.grid_matrix.setSpacing(20)
263         self.grid_matrix.addWidget(self.element_tl, 0, 0)
264         self.grid_matrix.addWidget(self.element_tr, 0, 1)
265         self.grid_matrix.addWidget(self.element_bl, 1, 0)
266         self.grid_matrix.addWidget(self.element_br, 1, 1)
267
268         self.hlay_definition.addLayout(self.grid_matrix)
269
270         self.vlay_all.addLayout(self.hlay_definition)
271         self.vlay_all.addLayout(self.hlay_buttons)
272
273         # We load the default matrix A into the boxes
274         self.load_matrix(0)

```

```

275         self.element_tl.setFocus()
276
277     @pyqtSlot()
278     def update_confirm_button(self) -> None:
279         """Enable the confirm button if there are valid floats in every box."""
280         for elem in self.matrix_elements:
281             if not is_valid_float(elem.text()):
282                 # If they're not all numbers, then we can't confirm it
283                 self.button_confirm.setEnabled(False)
284                 return
285
286         # If we didn't find anything invalid
287         self.button_confirm.setEnabled(True)
288
289     @pyqtSlot(int)
290     def load_matrix(self, index: int) -> None:
291         """If the selected matrix is defined, load its values into the boxes."""
292         matrix = self.matrix_wrapper[self.selected_letter]
293
294         if matrix is None:
295             for elem in self.matrix_elements:
296                 elem.setText('')
297
298         else:
299             self.element_tl.setText(round_float(matrix[0][0]))
300             self.element_tr.setText(round_float(matrix[0][1]))
301             self.element_bl.setText(round_float(matrix[1][0]))
302             self.element_br.setText(round_float(matrix[1][1]))
303
304         self.update_confirm_button()
305
306     @pyqtSlot()
307     def confirm_matrix(self) -> None:
308         """Confirm the matrix in the boxes and assign it to the name in the combo box."""
309         matrix: MatrixType = array([
310             [float(self.element_tl.text()), float(self.element_tr.text())],
311             [float(self.element_bl.text()), float(self.element_br.text())]
312         ])
313
314         self.matrix_wrapper[self.selected_letter] = matrix
315         self.accept()
316
317
318
319 class DefineAsAnExpressionDialog(DefinedDialog):
320     """The dialog class that allows the user to define a matrix as an expression of other matrices."""
321
322     def __init__(self, *args, matrix_wrapper: MatrixWrapper, **kwargs):
323         """Create the widgets and layout of the dialog.
324
325         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
326         """
327         super().__init__(*args, matrix_wrapper=matrix_wrapper, **kwargs)
328
329         self.setMinimumWidth(450)
330
331         # === Create the widgets
332
333         self.lineedit_expression_box = QtWidgets.QLineEdit(self)
334         self.lineedit_expression_box.setPlaceholderText('Enter matrix expression...')
335         self.lineedit_expression_box.textChanged.connect(self.update_confirm_button)
336         self.lineedit_expression_box.setValidator(MatrixExpressionValidator())
337
338         # === Arrange the widgets
339
340         self.hlay_definition.addWidget(self.lineedit_expression_box)
341
342         self.vlay_all.addLayout(self.hlay_definition)
343         self.vlay_all.addLayout(self.hlay_buttons)
344
345         # Load the matrix if it's defined as an expression
346         self.load_matrix(0)
347

```

```

348         self.linedit_expression_box.setFocus()
349
350     @pyqtSlot()
351     def update_confirm_button(self) -> None:
352         """Enable the confirm button if the matrix expression is valid in the wrapper."""
353         text = self.linedit_expression_box.text()
354         valid_expression = self.matrix_wrapper.is_valid_expression(text)
355
356         self.button_confirm.setEnabled(valid_expression and self.selected_letter not in text)
357
358     @pyqtSlot(int)
359     def load_matrix(self, index: int) -> None:
360         """If the selected matrix is defined an expression, load that expression into the box."""
361         if (expr := self.matrix_wrapper.get_expression(self.selected_letter)) is not None:
362             self.linedit_expression_box.setText(expr)
363         else:
364             self.linedit_expression_box.setText('')
365
366     @pyqtSlot()
367     def confirm_matrix(self) -> None:
368         """Evaluate the matrix expression and assign its value to the name in the combo box."""
369         self.matrix_wrapper[self.selected_letter] = self.linedit_expression_box.text()
370         self.accept()

```

## A.15 gui/dialogs/settings.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides dialogs to edit settings within the app."""
8
9  from __future__ import annotations
10
11  import abc
12
13  from PyQt5 import QtWidgets
14  from PyQt5.QtGui import QIntValidator, QKeyEvent, QKeySequence
15  from PyQt5.QtWidgets import QCheckBox, QGroupBox, QHBoxLayout, QShortcut, QSizePolicy, QSpacerItem, QVBoxLayout
16
17  from lintrans.gui.dialogs.misc import FixedSizeDialog
18  from lintrans.gui.settings import DisplaySettings
19
20
21  class SettingsDialog(FixedSizeDialog):
22      """An abstract superclass for other simple dialogs."""
23
24      def __init__(self, *args, **kwargs):
25          """Create the widgets and layout of the dialog, passing ``*args`` and ``**kwargs`` to super."""
26          super().__init__(*args, **kwargs)
27
28          # === Create the widgets
29
30          self.button_confirm = QtWidgets.QPushButton(self)
31          self.button_confirm.setText('Confirm')
32          self.button_confirm.clicked.connect(self.confirm_settings)
33          self.button_confirm.setToolTip('Confirm these new settings<br><b>(Ctrl + Enter)</b>')
34          QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self.button_confirm.click)
35
36          self.button_cancel = QtWidgets.QPushButton(self)
37          self.button_cancel.setText('Cancel')
38          self.button_cancel.clicked.connect(self.reject)
39          self.button_cancel.setToolTip('Revert these settings<br><b>(Escape)</b>')
40
41          # === Arrange the widgets
42
43          self.setContentsMargins(10, 10, 10, 10)
44

```

```

45     self.hlay_buttons = QHBoxLayout()
46     self.hlay_buttons.setSpacing(20)
47     self.hlay_buttons.addItem(QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum))
48     self.hlay_buttons.addWidget(self.button_cancel)
49     self.hlay_buttons.addWidget(self.button_confirm)
50
51     self.vlay_options = QVBoxLayout()
52     self.vlay_options.setSpacing(20)
53
54     self.vlay_all = QVBoxLayout()
55     self.vlay_all.setSpacing(20)
56     self.vlay_all.addLayout(self.vlay_options)
57     self.vlay_all.addLayout(self.hlay_buttons)
58
59     self.setLayout(self.vlay_all)
60
61     @abc.abstractmethod
62     def load_settings(self) -> None:
63         """Load the current settings into the widgets."""
64
65     @abc.abstractmethod
66     def confirm_settings(self) -> None:
67         """Confirm the settings chosen in the dialog."""
68
69
70 class DisplaySettingsDialog(SettingsDialog):
71     """The dialog to allow the user to edit the display settings."""
72
73     def __init__(self, *args, display_settings: DisplaySettings, **kwargs):
74         """Create the widgets and layout of the dialog.
75
76         :param DisplaySettings display_settings: The :class:`lintrans.gui.settings.DisplaySettings` object to mutate
77         """
78         super().__init__(*args, **kwargs)
79
80         self.display_settings = display_settings
81         self.setWindowTitle('Change display settings')
82
83         self.dict_checkboxes: dict[str, QCheckBox] = dict()
84
85         # === Create the widgets
86
87         # Basic stuff
88
89         self.checkbox_draw_background_grid = QCheckBox(self)
90         self.checkbox_draw_background_grid.setText('Draw &background grid')
91         self.checkbox_draw_background_grid.setToolTip(
92             'Draw the background grid (axes are always drawn)'
93         )
94         self.dict_checkboxes['b'] = self.checkbox_draw_background_grid
95
96         self.checkbox_draw_transformed_grid = QCheckBox(self)
97         self.checkbox_draw_transformed_grid.setText('Draw t&transformed grid')
98         self.checkbox_draw_transformed_grid.setToolTip(
99             'Draw the transformed grid (vectors are handled separately)'
100        )
101        self.dict_checkboxes['r'] = self.checkbox_draw_transformed_grid
102
103        self.checkbox_draw_basis_vectors = QCheckBox(self)
104        self.checkbox_draw_basis_vectors.setText('Draw basis &vectors')
105        self.checkbox_draw_basis_vectors.setToolTip(
106            'Draw the transformed basis vectors'
107        )
108        self.dict_checkboxes['v'] = self.checkbox_draw_basis_vectors
109
110        # Animations
111
112        self.checkbox_smooththen_determinant = QCheckBox(self)
113        self.checkbox_smooththen_determinant.setText('&Smoothen determinant')
114        self.checkbox_smooththen_determinant.setToolTip(
115            'Smoothly animate the determinant transition during animation (if possible)'
116        )
117        self.dict_checkboxes['s'] = self.checkbox_smooththen_determinant

```

```

118
119     self.checkbox_applicative_animation = QCheckBox(self)
120     self.checkbox_applicative_animation.setText('&Applicative animation')
121     self.checkbox_applicative_animation.setToolTip(
122         'Animate the new transformation applied to the current one,\n'
123         'rather than just that transformation on its own'
124     )
125     self.dict_checkboxes['a'] = self.checkbox_applicative_animation
126
127     self.label_animation_pause_length = QtWidgets.QLabel(self)
128     self.label_animation_pause_length.setText('Animation pause length (ms)')
129     self.label_animation_pause_length.setToolTip(
130         'How many milliseconds to pause for in comma-separated animations'
131     )
132
133     self.lineedit_animation_pause_length = QtWidgets.QLineEdit(self)
134     self.lineedit_animation_pause_length.setValidator(QIntValidator(1, 999, self))
135
136     # Matrix info
137
138     self.checkbox_draw_determinant_parallelogram = QCheckBox(self)
139     self.checkbox_draw_determinant_parallelogram.setText('Draw &determinant parallelogram')
140     self.checkbox_draw_determinant_parallelogram.setToolTip(
141         'Shade the parallelogram representing the determinant of the matrix'
142     )
143     self.checkbox_draw_determinant_parallelogram.clicked.connect(self.update_gui)
144     self.dict_checkboxes['d'] = self.checkbox_draw_determinant_parallelogram
145
146     self.checkbox_show_determinant_value = QCheckBox(self)
147     self.checkbox_show_determinant_value.setText('Show de&terminant value')
148     self.checkbox_show_determinant_value.setToolTip(
149         'Show the value of the determinant inside the parallelogram'
150     )
151     self.dict_checkboxes['t'] = self.checkbox_show_determinant_value
152
153     self.checkbox_draw_eigenvectors = QCheckBox(self)
154     self.checkbox_draw_eigenvectors.setText('Draw &eigenvectors')
155     self.checkbox_draw_eigenvectors.setToolTip('Draw the eigenvectors of the transformations')
156     self.dict_checkboxes['e'] = self.checkbox_draw_eigenvectors
157
158     self.checkbox_draw_eigenlines = QCheckBox(self)
159     self.checkbox_draw_eigenlines.setText('Draw eigen&lines')
160     self.checkbox_draw_eigenlines.setToolTip('Draw the eigenlines (invariant lines) of the transformations')
161     self.dict_checkboxes['l'] = self.checkbox_draw_eigenlines
162
163     # === Arrange the widgets in QGroupBoxes
164
165     # Basic stuff
166
167     self.vlay_groupbox_basic_stuff = QVBoxLayout()
168     self.vlay_groupbox_basic_stuff.setSpacing(20)
169     self.vlay_groupbox_basic_stuff.addWidget(self.checkbox_draw_background_grid)
170     self.vlay_groupbox_basic_stuff.addWidget(self.checkbox_draw_transformed_grid)
171     self.vlay_groupbox_basic_stuff.addWidget(self.checkbox_draw_basis_vectors)
172
173     self.groupbox_basic_stuff = QGroupBox('Basic stuff', self)
174     self.groupbox_basic_stuff.setLayout(self.vlay_groupbox_basic_stuff)
175
176     # Animations
177
178     self.hlay_animation_pause_length = QHBoxLayout()
179     self.hlay_animation_pause_length.addWidget(self.label_animation_pause_length)
180     self.hlay_animation_pause_length.addWidget(self.lineedit_animation_pause_length)
181
182     self.vlay_groupbox_animations = QVBoxLayout()
183     self.vlay_groupbox_animations.setSpacing(20)
184     self.vlay_groupbox_animations.addWidget(self.checkbox_smooththen_determinant)
185     self.vlay_groupbox_animations.addWidget(self.checkbox_applicative_animation)
186     self.vlay_groupbox_animations.addLayout(self.hlay_animation_pause_length)
187
188     self.groupbox_animations = QGroupBox('Animations', self)
189     self.groupbox_animations.setLayout(self.vlay_groupbox_animations)
190

```

```

191         # Matrix info
192
193         self.vlay_groupbox_matrix_info = QVBoxLayout()
194         self.vlay_groupbox_matrix_info.setSpacing(20)
195         self.vlay_groupbox_matrix_info.addWidget(self.checkbox_draw_determinant_parallelogram)
196         self.vlay_groupbox_matrix_info.addWidget(self.checkbox_show_determinant_value)
197         self.vlay_groupbox_matrix_info.addWidget(self.checkbox_draw_eigenvectors)
198         self.vlay_groupbox_matrix_info.addWidget(self.checkbox_draw_eigenlines)
199
200         self.groupbox_matrix_info = QGroupBox('Matrix info', self)
201         self.groupbox_matrix_info.setLayout(self.vlay_groupbox_matrix_info)
202
203         # Now arrange the groupboxes
204         self.vlay_options.addWidget(self.groupbox_basic_stuff)
205         self.vlay_options.addWidget(self.groupbox_animations)
206         self.vlay_options.addWidget(self.groupbox_matrix_info)
207
208         # Finally, we load the current settings and update the GUI
209         self.load_settings()
210         self.update_gui()
211
212     def load_settings(self) -> None:
213         """Load the current display settings into the widgets."""
214         # Basic stuff
215         self.checkbox_draw_background_grid.setChecked(self.display_settings.draw_background_grid)
216         self.checkbox_draw_transformed_grid.setChecked(self.display_settings.draw_transformed_grid)
217         self.checkbox_draw_basis_vectors.setChecked(self.display_settings.draw_basis_vectors)
218
219         # Animations
220         self.checkbox_smoothen_determinant.setChecked(self.display_settings.smoothen_determinant)
221         self.checkbox_applicative_animation.setChecked(self.display_settings.applicative_animation)
222         self.linedit_animation_pause_length.setText(str(self.display_settings.animation_pause_length))
223
224         # Matrix info
225         self.checkbox_draw_determinant_parallelogram.setChecked(
226             self.display_settings.draw_determinant_parallelogram)
227         self.checkbox_show_determinant_value.setChecked(self.display_settings.show_determinant_value)
228         self.checkbox_draw_eigenvectors.setChecked(self.display_settings.draw_eigenvectors)
229         self.checkbox_draw_eigenlines.setChecked(self.display_settings.draw_eigenlines)
230
231     def confirm_settings(self) -> None:
232         """Build a :class:`lintrans.gui.settings.DisplaySettings` object and assign it."""
233         # Basic stuff
234         self.display_settings.draw_background_grid = self.checkbox_draw_background_grid.isChecked()
235         self.display_settings.draw_transformed_grid = self.checkbox_draw_transformed_grid.isChecked()
236         self.display_settings.draw_basis_vectors = self.checkbox_draw_basis_vectors.isChecked()
237
238         # Animations
239         self.display_settings.smoothen_determinant = self.checkbox_smoothen_determinant.isChecked()
240         self.display_settings.applicative_animation = self.checkbox_applicative_animation.isChecked()
241         self.display_settings.animation_pause_length = int(self.linedit_animation_pause_length.text())
242
243         # Matrix info
244         self.display_settings.draw_determinant_parallelogram =
245             self.checkbox_draw_determinant_parallelogram.isChecked()
246         self.display_settings.show_determinant_value = self.checkbox_show_determinant_value.isChecked()
247         self.display_settings.draw_eigenvectors = self.checkbox_draw_eigenvectors.isChecked()
248         self.display_settings.draw_eigenlines = self.checkbox_draw_eigenlines.isChecked()
249
250         self.accept()
251
252     def update_gui(self) -> None:
253         """Update the GUI according to other widgets in the GUI.
254
255         For example, this method updates which checkboxes are enabled based on the values of other checkboxes.
256         """
257         self.checkbox_show_determinant_value.setEnabled(self.checkbox_draw_determinant_parallelogram.isChecked())
258
259     def keyPressEvent(self, event: QKeyEvent) -> None:
260         """Handle a :class:`QKeyEvent` by manually activating toggling checkboxes.
261
262         Qt handles these shortcuts automatically and allows the user to do ``Alt + Key``
263         to activate a simple shortcut defined with ``&``. However, I like to be able to

```



```

262         just hit ``Key`` and have the shortcut activate.
263         """
264         letter = event.text().lower()
265         key = event.key()
266
267         if letter in self.dict_checkboxes:
268             self.dict_checkboxes[letter].animateClick()
269
270         # Return or keypad enter
271         elif key == 0x01000004 or key == 0x01000005:
272             self.button_confirm.click()
273
274         # Escape
275         elif key == 0x01000000:
276             self.button_cancel.click()
277
278         else:
279             event.ignore()

```

## A.16 gui/dialogs/misc.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2022 D. Dyson (DoctorDalek1963)
3  #
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides miscellaneous dialog classes like :class:`AboutDialog`."""
8
9  from __future__ import annotations
10
11  import platform
12
13  from PyQt5 import QtWidgets
14  from PyQt5.QtCore import Qt
15  from PyQt5.QtWidgets import QDialog, QVBoxLayout
16
17  import lintrans
18
19
20  class FixedSizeDialog(QDialog):
21      """A simple superclass to create modal dialog boxes with fixed size.
22
23      We override the :meth:`open` method to set the fixed size as soon as the dialog is opened modally.
24      """
25
26      def open(self) -> None:
27          """Override :meth:`QDialog.open` to set the dialog to a fixed size."""
28          super().open()
29          self.setFixedSize(self.size())
30
31
32  class AboutDialog(FixedSizeDialog):
33      """A simple dialog class to display information about the app to the user.
34
35      It only has an :meth:`__init__` method because it only has label widgets, so no other methods are necessary
36      ↪ here.
37      """
38
39      def __init__(self, *args, **kwargs):
40          """Create an :class:`AboutDialog` object with all the label widgets."""
41          super().__init__(*args, **kwargs)
42
43          self.setWindowTitle('About lintrans')
44
45          # === Create the widgets
46
47          label_title = QtWidgets.QLabel(self)
48          label_title.setText(f'lintrans (version {lintrans.__version__})')
49          label_title.setAlignment(Qt.AlignCenter)

```

```

49
50     font_title = label_title.font()
51     font_title.setPointSize(font_title.pointSize() * 2)
52     label_title.setFont(font_title)
53
54     label_version_info = QtWidgets.QLabel(self)
55     label_version_info.setText(
56         f'With Python version {platform.python_version()}\n'
57         f'Running on {platform.platform()}'
58     )
59     label_version_info.setAlignment(Qt.AlignCenter)
60
61     label_info = QtWidgets.QLabel(self)
62     label_info.setText(
63         'lintrans is a program designed to help visualise<br>'
64         '2D linear transformations represented with matrices.<br><br>'
65         "It's designed for teachers and students and any feedback<br>"
66         'is greatly appreciated at <a href="https://github.com/DoctorDalek1963/lintrans" '
67         'style="color: black;">my GitHub page</a><br>or via email '
68         '(<a href="mailto:dyson.dyson@icloud.com" style="color: black;">dyson.dyson@icloud.com</a>).'
69     )
70     label_info.setAlignment(Qt.AlignCenter)
71     label_info.setTextFormat(Qt.RichText)
72     label_info.setOpenExternalLinks(True)
73
74     label_copyright = QtWidgets.QLabel(self)
75     label_copyright.setText(
76         'This program is free software.<br>Copyright 2021-2022 D. Dyson (DoctorDalek1963).<br>'
77         'This program is licensed under GPLv3, which can be found '
78         '<a href="https://www.gnu.org/licenses/gpl-3.0.html" style="color: black;">here</a>.'
79     )
80     label_copyright.setAlignment(Qt.AlignCenter)
81     label_copyright.setTextFormat(Qt.RichText)
82     label_copyright.setOpenExternalLinks(True)
83
84     # === Arrange the widgets
85
86     self.setContentsMargins(10, 10, 10, 10)
87
88     vlay = QVBoxLayout()
89     vlay.setSpacing(20)
90     vlay.addWidget(label_title)
91     vlay.addWidget(label_version_info)
92     vlay.addWidget(label_info)
93     vlay.addWidget(label_copyright)
94
95     self.setLayout(vlay)

```

## A.17 typing/\_init\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package supplies type aliases for linear algebra and transformations.
8
9  .. note::
10     This package is called ``typing_`` and not ``typing`` to avoid name collisions with the
11     builtin :mod:`typing`. I don't quite know how this collision occurs, but renaming
12     this module fixed the problem.
13 """
14
15 from __future__ import annotations
16
17 from typing import Any, TypeGuard
18
19 from numpy import ndarray
20 from nptyping import NDArray, Float

```

```
21
22 __all__ = ['is_matrix_type', 'MatrixType', 'MatrixParseList']
23
24 MatrixType = NDArray[(2, 2), Float]
25 """This type represents a 2x2 matrix as a NumPy array."""
26
27 MatrixParseList = list[list[tuple[str, str, str]]]
28 """This is a list containing lists of tuples. Each tuple represents a matrix and is ``(multiplier,
29 matrix_identifier, index)`` where all of them are strings. These matrix-representing tuples are
30 contained in lists which represent multiplication groups. Every matrix in the group should be
31 multiplied together, in order. These multiplication group lists are contained by a top level list,
32 which is this type. Once these multiplication group lists have been evaluated, they should be summed.
33
34 In the tuples, the multiplier is a string representing a real number, the matrix identifier
35 is a capital letter or ``rot(x)`` where x is a real number angle, and the index is a string
36 representing an integer, or it's the letter ``T`` for transpose.
37 """
38
39
40 def is_matrix_type(matrix: Any) -> TypeGuard[NDArray[(2, 2), Float]]:
41     """Check if the given value is a valid matrix type.
42
43     .. note::
44         This function is a TypeGuard, meaning if it returns True, then the
45         passed value must be a :attr:`lintrans.typing_.MatrixType`.
46     """
47     return isinstance(matrix, ndarray) and matrix.shape == (2, 2)
```

## B Testing code

### B.1 matrices/test\_rotation\_matrices.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test functions for rotation matrices."""
8
9  import numpy as np
10 import pytest
11
12 from lintrans.matrices import create_rotation_matrix
13 from lintrans.typing_ import MatrixType
14
15 angles_and_matrices: list[tuple[float, float, MatrixType]] = [
16     (0, 0, np.array([[1, 0], [0, 1]])),
17     (90, np.pi / 2, np.array([[0, -1], [1, 0]])),
18     (180, np.pi, np.array([[ -1, 0], [0, -1]])),
19     (270, 3 * np.pi / 2, np.array([[0, 1], [-1, 0]])),
20     (360, 2 * np.pi, np.array([[1, 0], [0, 1]])),
21
22     (45, np.pi / 4, np.array([
23         [np.sqrt(2) / 2, -1 * np.sqrt(2) / 2],
24         [np.sqrt(2) / 2, np.sqrt(2) / 2]
25     ])),
26     (135, 3 * np.pi / 4, np.array([
27         [-1 * np.sqrt(2) / 2, -1 * np.sqrt(2) / 2],
28         [np.sqrt(2) / 2, -1 * np.sqrt(2) / 2]
29     ])),
30     (225, 5 * np.pi / 4, np.array([
31         [-1 * np.sqrt(2) / 2, np.sqrt(2) / 2],
32         [-1 * np.sqrt(2) / 2, -1 * np.sqrt(2) / 2]
33     ])),
34     (315, 7 * np.pi / 4, np.array([
35         [np.sqrt(2) / 2, np.sqrt(2) / 2],
36         [-1 * np.sqrt(2) / 2, np.sqrt(2) / 2]
37     ])),
38
39     (30, np.pi / 6, np.array([
40         [np.sqrt(3) / 2, -1 / 2],
41         [1 / 2, np.sqrt(3) / 2]
42     ])),
43     (60, np.pi / 3, np.array([
44         [1 / 2, -1 * np.sqrt(3) / 2],
45         [np.sqrt(3) / 2, 1 / 2]
46     ])),
47     (120, 2 * np.pi / 3, np.array([
48         [-1 / 2, -1 * np.sqrt(3) / 2],
49         [np.sqrt(3) / 2, -1 / 2]
50     ])),
51     (150, 5 * np.pi / 6, np.array([
52         [-1 * np.sqrt(3) / 2, -1 / 2],
53         [1 / 2, -1 * np.sqrt(3) / 2]
54     ])),
55     (210, 7 * np.pi / 6, np.array([
56         [-1 * np.sqrt(3) / 2, 1 / 2],
57         [-1 / 2, -1 * np.sqrt(3) / 2]
58     ])),
59     (240, 4 * np.pi / 3, np.array([
60         [-1 / 2, np.sqrt(3) / 2],
61         [-1 * np.sqrt(3) / 2, -1 / 2]
62     ])),
63     (300, 10 * np.pi / 6, np.array([
64         [1 / 2, np.sqrt(3) / 2],
65         [-1 * np.sqrt(3) / 2, 1 / 2]
66     ])),
67     (330, 11 * np.pi / 6, np.array([

```

```

68         [np.sqrt(3) / 2, 1 / 2],
69         [-1 / 2, np.sqrt(3) / 2]
70     )))
71 ]
72
73
74 def test_create_rotation_matrix() -> None:
75     """Test that create_rotation_matrix() works with given angles and expected matrices."""
76     for degrees, radians, matrix in angles_and_matrices:
77         assert create_rotation_matrix(degrees, degrees=True) == pytest.approx(matrix)
78         assert create_rotation_matrix(radians, degrees=False) == pytest.approx(matrix)
79
80     assert create_rotation_matrix(-1 * degrees, degrees=True) == pytest.approx(np.linalg.inv(matrix))
81     assert create_rotation_matrix(-1 * radians, degrees=False) == pytest.approx(np.linalg.inv(matrix))

```

## B.2 matrices/test\_parse\_and\_validate\_expression.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the :mod:`matrices.parse` module validation and parsing."""
8
9  import pytest
10
11  from lintrans.matrices.parse import (
12      MatrixParseError, find_sub_expressions, parse_matrix_expression, validate_matrix_expression
13  )
14  from lintrans.typing_ import MatrixParseList
15
16  expected_sub_expressions: list[tuple[str, list[str]]] = [
17      ('2(AB)^-1', ['AB']),
18      ('-3(A+B)^2-C(B^TA)^-1', ['A+B', 'B^TA']),
19      ('rot(45)', []),
20      ('()', []),
21      ('()', ['()']),
22      ('2.3A^-1(AB)^-1+(BC)^2', ['AB', 'BC']),
23      ('(2.3A^-1(AB)^-1+(BC)^2)', ['2.3A^-1(AB)^-1+(BC)^2']),
24  ]
25
26
27 def test_find_sub_expressions() -> None:
28     """Test the :func:`lintrans.matrices.parse.find_sub_expressions` function."""
29     for inp, output in expected_sub_expressions:
30         assert find_sub_expressions(inp) == output
31
32
33  valid_inputs: list[str] = [
34      'A', 'AB', '3A', '1.2A', '-3.4A', 'A^2', 'A^-1', 'A^{-1}',
35      'A^12', 'A^T', 'A^{5}', 'A^{T}', '4.3A^7', '9.2A^{18}', '0.1A'
36
37      'rot(45)', 'rot(12.5)', '3rot(90)',
38      'rot(135)^3', 'rot(51)^T', 'rot(-34)^-1',
39
40      'A+B', 'A+2B', '4.3A+9B', 'A^2+B^T', '3A^7+0.8B^{16}',
41      'A-B', '3A-4B', '3.2A^3-16.79B^T', '4.752A^{17}-3.32B^{36}',
42      'A-1B', '-A', '-1A'
43
44      '3A4B', 'A^TB', 'A^{T}B', '4A^6B^3',
45      '2A^{3}4B^5', '4rot(90)^3', 'rot(45)rot(13)',
46      'Arot(90)', 'AB^2', 'A^2B^2', '8.36A^T3.4B^12',
47
48      '3.5A^{4}5.6rot(19.2)^T-B^{-1}4.1C^5',
49
50      '(A)', '(AB)^-1', '2.3(3B^TA)^2', '-3.4(9D^{2}3F^{-1})^T+C', '(AB)(C)',
51      '3(rot(34)^-7A)^-1+B', '3A^2B+4A(B+C)^-1D^T-A(C(D+E)B)'
52  ]
53

```

```

54 invalid_inputs: list[str] = [
55     '', 'rot()', 'A^', 'A^1.2', 'A^{3.4}', '1,2A', 'ro(12)', '5', '12^2', '^T', '^12}', '.1A',
56     'A^{13}', 'A^3}', 'A^A', '^2', 'A--B', '--A', '+A', '--1A', 'A--B', 'A--1B', '.A', '1.A',
57     '2.3AB^T', '(AB+)', '-4.6(9A)', '-2(3.4A^{-1}-C)^2', '9.2', '3A^2B+4A(B+C)^-1D^T-A(C(D+EB)',
58     '3)^2', '4(your mum)^T', 'rot()', 'rot(10.1.1)', 'rot(--2)',
59
60     'This is 100% a valid matrix expression, I swear'
61 ]
62
63
64 @pytest.mark.parametrize('inputs,output', [(valid_inputs, True), (invalid_inputs, False)])
65 def test_validate_matrix_expression(inputs: list[str], output: bool) -> None:
66     """Test the validate_matrix_expression() function."""
67     for inp in inputs:
68         assert validate_matrix_expression(inp) == output
69
70
71 expressions_and_parsed_expressions: list[tuple[str, MatrixParseList]] = [
72     # Simple expressions
73     ('A', [((' ', 'A', ' ')]]),
74     ('A^2', [((' ', 'A', '2')]]),
75     ('A^{2}', [((' ', 'A', '2')]]),
76     ('3A', [(('3', 'A', ' ')]]),
77     ('1.4A^3', [(('1.4', 'A', '3')]]),
78     ('0.1A', [(('0.1', 'A', ' ')]]),
79     ('0.1A', [(('0.1', 'A', ' ')]]),
80     ('A^12', [((' ', 'A', '12')]]),
81     ('A^234', [((' ', 'A', '234')]]),
82
83     # Multiplications
84     ('A 0.1B', [((' ', 'A', ' '), ('0.1', 'B', ' ')]]),
85     ('A^2 3B', [((' ', 'A', '23'), (' ', 'B', ' ')]]),
86     ('4A^{3} 6B^2', [(('4', 'A', '3'), ('6', 'B', '2')]]),
87     ('4.2A^{T} 6.1B^-1', [(('4.2', 'A', 'T'), ('6.1', 'B', '-1')]]),
88     ('-1.2A^2 rot(45)^2', [(('1.2', 'A', '2'), (' ', 'rot(45)', '2')]]),
89     ('3.2A^T 4.5B^{5} 9.6rot(121.3)', [(('3.2', 'A', 'T'), ('4.5', 'B', '5'), ('9.6', 'rot(121.3)', ' ')]]),
90     ('-1.18A^{-2} 0.1B^{2} 9rot(-34.6)^-1', [(('1.18', 'A', '-2'), ('0.1', 'B', '2'), ('9', 'rot(-34.6)', '-1')]]),
91
92     # Additions
93     ('A + B', [((' ', 'A', ' '), (' ', 'B', ' ')]]),
94     ('A + B - C', [((' ', 'A', ' '), (' ', 'B', ' '), ('-1', 'C', ' ')]]),
95     ('A^2 + 0.5B', [((' ', 'A', '2'), ('0.5', 'B', ' ')]]),
96     ('2A^3 + 8B^T - 3C^-1', [(('2', 'A', '3'), ('8', 'B', 'T'), ('-3', 'C', '-1')]]),
97     ('4.9A^2 - 3rot(134.2)^-1 + 7.6B^8', [(('4.9', 'A', '2'), ('-3', 'rot(134.2)', '-1'), ('7.6', 'B', '8')]]),
98
99     # Additions with multiplication
100     ('2.14A^{3} 4.5rot(14.5)^-1 + 8B^T - 3C^-1', [(('2.14', 'A', '3'), ('4.5', 'rot(14.5)', '-1'),
101         [('8', 'B', 'T'), ('-3', 'C', '-1')]]),
102     ('2.14A^{3} 4.5rot(14.5)^-1 + 8.5B^T 5.97C^14 - 3.14D^{-1} 6.7E^T',
103         [(('2.14', 'A', '3'), ('4.5', 'rot(14.5)', '-1'), ('8.5', 'B', 'T'), ('5.97', 'C', '14'),
104             [('-3.14', 'D', '-1'), ('6.7', 'E', 'T')])]),
105
106     # Parenthesized expressions
107     ('(AB)^-1', [((' ', 'AB', '-1')]]),
108     ('-3(A+B)^2-C(B^TA)^-1', [(('3', 'A+B', '2'), ('-1', 'C', ' '), (' ', 'B^{T}A', '-1')]]),
109     ('2.3(3B^TA)^2', [(('2.3', '3B^{T}A', '2')]]),
110     ('-3.4(9D^{2}3F^-1)^T+C', [(('3.4', '9D^{2}3F^{-1}', 'T'), (' ', 'C', ' ')]]),
111     ('2.39(3.1A^{-1}2.3B(CD)^-1)^T + (AB^T)^-1', [(('2.39', '3.1A^{-1}2.3B(CD)^{-1}', 'T'), (' ', 'AB^{T}',
112         '\rightarrow -1')]]),
113
114
115 def test_parse_matrix_expression() -> None:
116     """Test the parse_matrix_expression() function."""
117     for expression, parsed_expression in expressions_and_parsed_expressions:
118         # Test it with and without whitespace
119         assert parse_matrix_expression(expression) == parsed_expression
120         assert parse_matrix_expression(expression.replace(' ', '')) == parsed_expression
121
122
123 def test_parse_error() -> None:
124     """Test that parse_matrix_expression() raises a MatrixParseError."""
125     for expression in invalid_inputs:

```

```

126         with pytest.raises(MatrixParseError):
127             parse_matrix_expression(expression)

```

### B.3 matrices/matrix\_wrapper/test\_evaluate\_expression.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the MatrixWrapper evaluate_expression() method."""
8
9  import numpy as np
10 from numpy import linalg as la
11 import pytest
12 from pytest import approx
13
14 from lintrans.matrices import MatrixWrapper, create_rotation_matrix
15 from lintrans.typing_ import MatrixType
16
17 from conftest import get_test_wrapper
18
19
20 def test_simple_matrix_addition(test_wrapper: MatrixWrapper) -> None:
21     """Test simple addition and subtraction of two matrices."""
22
23     # NOTE: We assert that all of these values are not None just to stop mypy complaining
24     # These values will never actually be None because they're set in the wrapper() fixture
25     # There's probably a better way do this, because this method is a bit of a bodge, but this works for now
26     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
27         test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
28         test_wrapper['G'] is not None
29
30     assert (test_wrapper.evaluate_expression('A+B') == test_wrapper['A'] + test_wrapper['B']).all()
31     assert (test_wrapper.evaluate_expression('E+F') == test_wrapper['E'] + test_wrapper['F']).all()
32     assert (test_wrapper.evaluate_expression('G+D') == test_wrapper['G'] + test_wrapper['D']).all()
33     assert (test_wrapper.evaluate_expression('C+C') == test_wrapper['C'] + test_wrapper['C']).all()
34     assert (test_wrapper.evaluate_expression('D+A') == test_wrapper['D'] + test_wrapper['A']).all()
35     assert (test_wrapper.evaluate_expression('B+C') == test_wrapper['B'] + test_wrapper['C']).all()
36
37     assert test_wrapper == get_test_wrapper()
38
39
40 def test_simple_two_matrix_multiplication(test_wrapper: MatrixWrapper) -> None:
41     """Test simple multiplication of two matrices."""
42     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
43         test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
44         test_wrapper['G'] is not None
45
46     assert (test_wrapper.evaluate_expression('AB') == test_wrapper['A'] @ test_wrapper['B']).all()
47     assert (test_wrapper.evaluate_expression('BA') == test_wrapper['B'] @ test_wrapper['A']).all()
48     assert (test_wrapper.evaluate_expression('AC') == test_wrapper['A'] @ test_wrapper['C']).all()
49     assert (test_wrapper.evaluate_expression('DA') == test_wrapper['D'] @ test_wrapper['A']).all()
50     assert (test_wrapper.evaluate_expression('ED') == test_wrapper['E'] @ test_wrapper['D']).all()
51     assert (test_wrapper.evaluate_expression('FD') == test_wrapper['F'] @ test_wrapper['D']).all()
52     assert (test_wrapper.evaluate_expression('GA') == test_wrapper['G'] @ test_wrapper['A']).all()
53     assert (test_wrapper.evaluate_expression('CF') == test_wrapper['C'] @ test_wrapper['F']).all()
54     assert (test_wrapper.evaluate_expression('AG') == test_wrapper['A'] @ test_wrapper['G']).all()
55
56     assert test_wrapper.evaluate_expression('A2B') == approx(test_wrapper['A'] @ (2 * test_wrapper['B']))
57     assert test_wrapper.evaluate_expression('2AB') == approx((2 * test_wrapper['A']) @ test_wrapper['B'])
58     assert test_wrapper.evaluate_expression('C3D') == approx(test_wrapper['C'] @ (3 * test_wrapper['D']))
59     assert test_wrapper.evaluate_expression('4.2E1.2A') == approx((4.2 * test_wrapper['E']) @ (1.2 *
60         ↪ test_wrapper['A']))
61
62     assert test_wrapper == get_test_wrapper()
63
64 def test_identity_multiplication(test_wrapper: MatrixWrapper) -> None:

```

```

65     """Test that multiplying by the identity doesn't change the value of a matrix."""
66     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
67           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
68           test_wrapper['G'] is not None
69
70     assert (test_wrapper.evaluate_expression('I') == test_wrapper['I']).all()
71     assert (test_wrapper.evaluate_expression('AI') == test_wrapper['A']).all()
72     assert (test_wrapper.evaluate_expression('IA') == test_wrapper['A']).all()
73     assert (test_wrapper.evaluate_expression('GI') == test_wrapper['G']).all()
74     assert (test_wrapper.evaluate_expression('IG') == test_wrapper['G']).all()
75
76     assert (test_wrapper.evaluate_expression('EID') == test_wrapper['E'] @ test_wrapper['D']).all()
77     assert (test_wrapper.evaluate_expression('IED') == test_wrapper['E'] @ test_wrapper['D']).all()
78     assert (test_wrapper.evaluate_expression('EDI') == test_wrapper['E'] @ test_wrapper['D']).all()
79     assert (test_wrapper.evaluate_expression('EIDI') == test_wrapper['E'] @ test_wrapper['D']).all()
80     assert (test_wrapper.evaluate_expression('EI^3D') == test_wrapper['E'] @ test_wrapper['D']).all()
81
82     assert test_wrapper == get_test_wrapper()
83
84
85 def test_simple_three_matrix_multiplication(test_wrapper: MatrixWrapper) -> None:
86     """Test simple multiplication of two matrices."""
87     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
88           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
89           test_wrapper['G'] is not None
90
91     assert (test_wrapper.evaluate_expression('ABC') == test_wrapper['A'] @ test_wrapper['B'] @
92           ↪ test_wrapper['C']).all()
93     assert (test_wrapper.evaluate_expression('ACB') == test_wrapper['A'] @ test_wrapper['C'] @
94           ↪ test_wrapper['B']).all()
95     assert (test_wrapper.evaluate_expression('BAC') == test_wrapper['B'] @ test_wrapper['A'] @
96           ↪ test_wrapper['C']).all()
97     assert (test_wrapper.evaluate_expression('EFG') == test_wrapper['E'] @ test_wrapper['F'] @
98           ↪ test_wrapper['G']).all()
99     assert (test_wrapper.evaluate_expression('DAC') == test_wrapper['D'] @ test_wrapper['A'] @
100           ↪ test_wrapper['C']).all()
101     assert (test_wrapper.evaluate_expression('GAE') == test_wrapper['G'] @ test_wrapper['A'] @
102           ↪ test_wrapper['E']).all()
103     assert (test_wrapper.evaluate_expression('FAG') == test_wrapper['F'] @ test_wrapper['A'] @
104           ↪ test_wrapper['G']).all()
105     assert (test_wrapper.evaluate_expression('GAF') == test_wrapper['G'] @ test_wrapper['A'] @
106           ↪ test_wrapper['F']).all()
107
108     assert test_wrapper == get_test_wrapper()
109
110
111 def test_matrix_inverses(test_wrapper: MatrixWrapper) -> None:
112     """Test the inverses of single matrices."""
113     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
114           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
115           test_wrapper['G'] is not None
116
117     assert (test_wrapper.evaluate_expression('A^{-1}') == la.inv(test_wrapper['A'])).all()
118     assert (test_wrapper.evaluate_expression('B^{-1}') == la.inv(test_wrapper['B'])).all()
119     assert (test_wrapper.evaluate_expression('C^{-1}') == la.inv(test_wrapper['C'])).all()
120     assert (test_wrapper.evaluate_expression('D^{-1}') == la.inv(test_wrapper['D'])).all()
121     assert (test_wrapper.evaluate_expression('E^{-1}') == la.inv(test_wrapper['E'])).all()
122     assert (test_wrapper.evaluate_expression('F^{-1}') == la.inv(test_wrapper['F'])).all()
123     assert (test_wrapper.evaluate_expression('G^{-1}') == la.inv(test_wrapper['G'])).all()
124
125     assert (test_wrapper.evaluate_expression('A^{-1}') == la.inv(test_wrapper['A'])).all()
126     assert (test_wrapper.evaluate_expression('B^{-1}') == la.inv(test_wrapper['B'])).all()
127     assert (test_wrapper.evaluate_expression('C^{-1}') == la.inv(test_wrapper['C'])).all()
128     assert (test_wrapper.evaluate_expression('D^{-1}') == la.inv(test_wrapper['D'])).all()
129     assert (test_wrapper.evaluate_expression('E^{-1}') == la.inv(test_wrapper['E'])).all()
130     assert (test_wrapper.evaluate_expression('F^{-1}') == la.inv(test_wrapper['F'])).all()
131     assert (test_wrapper.evaluate_expression('G^{-1}') == la.inv(test_wrapper['G'])).all()
132
133     assert test_wrapper == get_test_wrapper()
134
135
136 def test_matrix_powers(test_wrapper: MatrixWrapper) -> None:
137     """Test that matrices can be raised to integer powers."""

```



```

130     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
131           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
132           test_wrapper['G'] is not None
133
134     assert (test_wrapper.evaluate_expression('A^2') == la.matrix_power(test_wrapper['A'], 2)).all()
135     assert (test_wrapper.evaluate_expression('B^4') == la.matrix_power(test_wrapper['B'], 4)).all()
136     assert (test_wrapper.evaluate_expression('C^{12}') == la.matrix_power(test_wrapper['C'], 12)).all()
137     assert (test_wrapper.evaluate_expression('D^{12}') == la.matrix_power(test_wrapper['D'], 12)).all()
138     assert (test_wrapper.evaluate_expression('E^8') == la.matrix_power(test_wrapper['E'], 8)).all()
139     assert (test_wrapper.evaluate_expression('F^{-6}') == la.matrix_power(test_wrapper['F'], -6)).all()
140     assert (test_wrapper.evaluate_expression('G^{-2}') == la.matrix_power(test_wrapper['G'], -2)).all()
141
142     assert test_wrapper == get_test_wrapper()
143
144
145 def test_matrix_transpose(test_wrapper: MatrixWrapper) -> None:
146     """Test matrix transpositions."""
147     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
148           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
149           test_wrapper['G'] is not None
150
151     assert (test_wrapper.evaluate_expression('A^{T}') == test_wrapper['A'].T).all()
152     assert (test_wrapper.evaluate_expression('B^{T}') == test_wrapper['B'].T).all()
153     assert (test_wrapper.evaluate_expression('C^{T}') == test_wrapper['C'].T).all()
154     assert (test_wrapper.evaluate_expression('D^{T}') == test_wrapper['D'].T).all()
155     assert (test_wrapper.evaluate_expression('E^{T}') == test_wrapper['E'].T).all()
156     assert (test_wrapper.evaluate_expression('F^{T}') == test_wrapper['F'].T).all()
157     assert (test_wrapper.evaluate_expression('G^{T}') == test_wrapper['G'].T).all()
158
159     assert (test_wrapper.evaluate_expression('A^T') == test_wrapper['A'].T).all()
160     assert (test_wrapper.evaluate_expression('B^T') == test_wrapper['B'].T).all()
161     assert (test_wrapper.evaluate_expression('C^T') == test_wrapper['C'].T).all()
162     assert (test_wrapper.evaluate_expression('D^T') == test_wrapper['D'].T).all()
163     assert (test_wrapper.evaluate_expression('E^T') == test_wrapper['E'].T).all()
164     assert (test_wrapper.evaluate_expression('F^T') == test_wrapper['F'].T).all()
165     assert (test_wrapper.evaluate_expression('G^T') == test_wrapper['G'].T).all()
166
167     assert test_wrapper == get_test_wrapper()
168
169
170 def test_rotation_matrices(test_wrapper: MatrixWrapper) -> None:
171     """Test that 'rot(angle)' can be used in an expression."""
172     assert (test_wrapper.evaluate_expression('rot(90)') == create_rotation_matrix(90)).all()
173     assert (test_wrapper.evaluate_expression('rot(180)') == create_rotation_matrix(180)).all()
174     assert (test_wrapper.evaluate_expression('rot(270)') == create_rotation_matrix(270)).all()
175     assert (test_wrapper.evaluate_expression('rot(360)') == create_rotation_matrix(360)).all()
176     assert (test_wrapper.evaluate_expression('rot(45)') == create_rotation_matrix(45)).all()
177     assert (test_wrapper.evaluate_expression('rot(30)') == create_rotation_matrix(30)).all()
178
179     assert (test_wrapper.evaluate_expression('rot(13.43)') == create_rotation_matrix(13.43)).all()
180     assert (test_wrapper.evaluate_expression('rot(49.4)') == create_rotation_matrix(49.4)).all()
181     assert (test_wrapper.evaluate_expression('rot(-123.456)') == create_rotation_matrix(-123.456)).all()
182     assert (test_wrapper.evaluate_expression('rot(963.245)') == create_rotation_matrix(963.245)).all()
183     assert (test_wrapper.evaluate_expression('rot(-235.24)') == create_rotation_matrix(-235.24)).all()
184
185     assert test_wrapper == get_test_wrapper()
186
187
188 def test_multiplication_and_addition(test_wrapper: MatrixWrapper) -> None:
189     """Test multiplication and addition of matrices together."""
190     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
191           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
192           test_wrapper['G'] is not None
193
194     assert (test_wrapper.evaluate_expression('AB+C') ==
195           test_wrapper['A'] @ test_wrapper['B'] + test_wrapper['C']).all()
196     assert (test_wrapper.evaluate_expression('DE-D') ==
197           test_wrapper['D'] @ test_wrapper['E'] - test_wrapper['D']).all()
198     assert (test_wrapper.evaluate_expression('FD+AB') ==
199           test_wrapper['F'] @ test_wrapper['D'] + test_wrapper['A'] @ test_wrapper['B']).all()
200     assert (test_wrapper.evaluate_expression('BA-DE') ==
201           test_wrapper['B'] @ test_wrapper['A'] - test_wrapper['D'] @ test_wrapper['E']).all()
202

```

```

203     assert (test_wrapper.evaluate_expression('2AB+3C') ==
204             (2 * test_wrapper['A']) @ test_wrapper['B'] + (3 * test_wrapper['C'])).all()
205     assert (test_wrapper.evaluate_expression('4D7.9E-1.2A') ==
206             (4 * test_wrapper['D']) @ (7.9 * test_wrapper['E']) - (1.2 * test_wrapper['A'])).all()
207
208     assert test_wrapper == get_test_wrapper()
209
210
211 def test_complicated_expressions(test_wrapper: MatrixWrapper) -> None:
212     """Test evaluation of complicated expressions."""
213     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
214            test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
215            test_wrapper['G'] is not None
216
217     assert (test_wrapper.evaluate_expression('-3.2A^T 4B^{-1} 6C^{-1} + 8.1D^{2} 3.2E^4') ==
218             (-3.2 * test_wrapper['A'].T) @ (4 * la.inv(test_wrapper['B'])) @ (6 * la.inv(test_wrapper['C']))
219             + (8.1 * la.matrix_power(test_wrapper['D'], 2)) @ (3.2 * la.matrix_power(test_wrapper['E'], 4))).all()
220
221     assert (test_wrapper.evaluate_expression('53.6D^{2} 3B^T - 4.9F^{2} 2D + A^3 B^{-1}') ==
222             (53.6 * la.matrix_power(test_wrapper['D'], 2)) @ (3 * test_wrapper['B'].T)
223             - (4.9 * la.matrix_power(test_wrapper['F'], 2)) @ (2 * test_wrapper['D'])
224             + la.matrix_power(test_wrapper['A'], 3) @ la.inv(test_wrapper['B'])).all()
225
226     assert test_wrapper == get_test_wrapper()
227
228
229 def test_parenthesized_expressions(test_wrapper: MatrixWrapper) -> None:
230     """Test evaluation of parenthesized expressions."""
231     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
232            test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
233            test_wrapper['G'] is not None
234
235     assert (test_wrapper.evaluate_expression('(A^T)^2') == la.matrix_power(test_wrapper['A'].T, 2)).all()
236     assert (test_wrapper.evaluate_expression('(B^T)^3') == la.matrix_power(test_wrapper['B'].T, 3)).all()
237     assert (test_wrapper.evaluate_expression('(C^T)^4') == la.matrix_power(test_wrapper['C'].T, 4)).all()
238     assert (test_wrapper.evaluate_expression('(D^T)^5') == la.matrix_power(test_wrapper['D'].T, 5)).all()
239     assert (test_wrapper.evaluate_expression('(E^T)^6') == la.matrix_power(test_wrapper['E'].T, 6)).all()
240     assert (test_wrapper.evaluate_expression('(F^T)^7') == la.matrix_power(test_wrapper['F'].T, 7)).all()
241     assert (test_wrapper.evaluate_expression('(G^T)^8') == la.matrix_power(test_wrapper['G'].T, 8)).all()
242
243     assert (test_wrapper.evaluate_expression('(rot(45)^1)^T') == create_rotation_matrix(45).T).all()
244     assert (test_wrapper.evaluate_expression('(rot(45)^2)^T') == la.matrix_power(create_rotation_matrix(45),
245                                         ↪ 2).T).all()
246     assert (test_wrapper.evaluate_expression('(rot(45)^3)^T') == la.matrix_power(create_rotation_matrix(45),
247                                         ↪ 3).T).all()
248     assert (test_wrapper.evaluate_expression('(rot(45)^4)^T') == la.matrix_power(create_rotation_matrix(45),
249                                         ↪ 4).T).all()
250     assert (test_wrapper.evaluate_expression('(rot(45)^5)^T') == la.matrix_power(create_rotation_matrix(45),
251                                         ↪ 5).T).all()
252
253     assert (test_wrapper.evaluate_expression('D^3(A+6.2F-0.397G^TE)^{-2+A}') ==
254             la.matrix_power(test_wrapper['D'], 3) @ la.matrix_power(
255                 test_wrapper['A'] + 6.2 * test_wrapper['F'] - 0.397 * test_wrapper['G'].T @ test_wrapper['E'],
256                 -2
257             ) + test_wrapper['A']).all()
258
259     assert (test_wrapper.evaluate_expression('-1.2F^{3}4.9D^T(A^2(B+3E^TF)^{-1})^2') ==
260             -1.2 * la.matrix_power(test_wrapper['F'], 3) @ (4.9 * test_wrapper['D'].T) @
261             la.matrix_power(
262                 la.matrix_power(test_wrapper['A'], 2) @ la.matrix_power(
263                     test_wrapper['B'] + 3 * test_wrapper['E'].T @ test_wrapper['F'],
264                     -1
265                 ),
266                 2
267             ).all()
268
269
270 def test_value_errors(test_wrapper: MatrixWrapper) -> None:
271     """Test that evaluate_expression() raises a ValueError for any malformed input."""
272     invalid_expressions = ['', '+', '-', 'This is not a valid expression', '3+4',
273                            'A+2', 'A^', '^2', 'A^-', 'At', 'A^t', '3^2']
274
275     for expression in invalid_expressions:

```

```

272         with pytest.raises(ValueError):
273             test_wrapper.evaluate_expression(expression)
274
275
276 def test_linalgerror() -> None:
277     """Test that certain expressions raise np.linalg.LinAlgError."""
278     matrix_a: MatrixType = np.array([
279         [0, 0],
280         [0, 0]
281     ])
282
283     matrix_b: MatrixType = np.array([
284         [1, 2],
285         [1, 2]
286     ])
287
288     wrapper = MatrixWrapper()
289     wrapper['A'] = matrix_a
290     wrapper['B'] = matrix_b
291
292     assert (wrapper.evaluate_expression('A') == matrix_a).all()
293     assert (wrapper.evaluate_expression('B') == matrix_b).all()
294
295     with pytest.raises(np.linalg.LinAlgError):
296         wrapper.evaluate_expression('A^-1')
297
298     with pytest.raises(np.linalg.LinAlgError):
299         wrapper.evaluate_expression('B^-1')
300
301     assert (wrapper['A'] == matrix_a).all()
302     assert (wrapper['B'] == matrix_b).all()

```

## B.4 matrices/matrix\_wrapper/conftest.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """A simple conftest.py containing some re-usable fixtures."""
8
9  import numpy as np
10 import pytest
11
12 from lintrans.matrices import MatrixWrapper
13
14
15 def get_test_wrapper() -> MatrixWrapper:
16     """Return a new MatrixWrapper object with some preset values."""
17     wrapper = MatrixWrapper()
18
19     root_two_over_two = np.sqrt(2) / 2
20
21     wrapper['A'] = np.array([[1, 2], [3, 4]])
22     wrapper['B'] = np.array([[6, 4], [12, 9]])
23     wrapper['C'] = np.array([[-1, -3], [4, -12]])
24     wrapper['D'] = np.array([[13.2, 9.4], [-3.4, -1.8]])
25     wrapper['E'] = np.array([
26         [root_two_over_two, -1 * root_two_over_two],
27         [root_two_over_two, root_two_over_two]
28     ])
29     wrapper['F'] = np.array([[-1, 0], [0, 1]])
30     wrapper['G'] = np.array([[np.pi, np.e], [1729, 743.631]])
31
32     return wrapper
33
34
35 @pytest.fixture
36 def test_wrapper() -> MatrixWrapper:

```

```

37     """Return a new MatrixWrapper object with some preset values."""
38     return get_test_wrapper()
39
40
41 @pytest.fixture
42 def new_wrapper() -> MatrixWrapper:
43     """Return a new MatrixWrapper with no initialized values."""
44     return MatrixWrapper()

```

## B.5 matrices/matrix\_wrapper/test\_misc.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the miscellaneous methods of the MatrixWrapper class."""
8
9  from lintrans.matrices import MatrixWrapper
10
11
12 def test_get_expression(test_wrapper: MatrixWrapper) -> None:
13     """Test the get_expression method of the MatrixWrapper class."""
14     test_wrapper['N'] = 'A^2'
15     test_wrapper['O'] = '4B'
16     test_wrapper['P'] = 'A+C'
17
18     test_wrapper['Q'] = 'N^-1'
19     test_wrapper['R'] = 'P-40'
20     test_wrapper['S'] = 'NOP'
21
22     assert test_wrapper.get_expression('A') is None
23     assert test_wrapper.get_expression('B') is None
24     assert test_wrapper.get_expression('C') is None
25     assert test_wrapper.get_expression('D') is None
26     assert test_wrapper.get_expression('E') is None
27     assert test_wrapper.get_expression('F') is None
28     assert test_wrapper.get_expression('G') is None
29
30     assert test_wrapper.get_expression('N') == 'A^2'
31     assert test_wrapper.get_expression('O') == '4B'
32     assert test_wrapper.get_expression('P') == 'A+C'
33
34     assert test_wrapper.get_expression('Q') == 'N^-1'
35     assert test_wrapper.get_expression('R') == 'P-40'
36     assert test_wrapper.get_expression('S') == 'NOP'

```

## B.6 matrices/matrix\_wrapper/test\_setitem\_and\_getitem.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the MatrixWrapper __setitem__() and __getitem__() methods."""
8
9  import numpy as np
10 from numpy import linalg as la
11 import pytest
12 from typing import Any
13
14 from lintrans.matrices import MatrixWrapper
15 from lintrans.typing import MatrixType
16
17 valid_matrix_names = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ'
18 invalid_matrix_names = ['bad name', '123456', 'Th15 Is an 1nV@l1D n@m3', 'abc', 'a']

```

```

19
20 test_matrix: MatrixType = np.array([[1, 2], [4, 3]])
21
22
23 def test_basic_get_matrix(new_wrapper: MatrixWrapper) -> None:
24     """Test MatrixWrapper().__getitem__()."""
25     for name in valid_matrix_names:
26         assert new_wrapper[name] is None
27
28     assert (new_wrapper['I'] == np.array([[1, 0], [0, 1]])).all()
29
30
31 def test_get_name_error(new_wrapper: MatrixWrapper) -> None:
32     """Test that MatrixWrapper().__getitem__() raises a NameError if called with an invalid name."""
33     for name in invalid_matrix_names:
34         with pytest.raises(NameError):
35             _ = new_wrapper[name]
36
37
38 def test_basic_set_matrix(new_wrapper: MatrixWrapper) -> None:
39     """Test MatrixWrapper().__setitem__()."""
40     for name in valid_matrix_names:
41         new_wrapper[name] = test_matrix
42         assert (new_wrapper[name] == test_matrix).all()
43
44         new_wrapper[name] = None
45         assert new_wrapper[name] is None
46
47
48 def test_set_expression(test_wrapper: MatrixWrapper) -> None:
49     """Test that MatrixWrapper.__setitem__() can accept a valid expression."""
50     test_wrapper['N'] = 'A^2'
51     test_wrapper['O'] = 'BA+2C'
52     test_wrapper['P'] = 'E^T'
53     test_wrapper['Q'] = 'C^-1B'
54     test_wrapper['R'] = 'A^{2}3B'
55     test_wrapper['S'] = 'N^-1'
56     test_wrapper['T'] = 'PQP^-1'
57
58     with pytest.raises(TypeError):
59         test_wrapper['U'] = 'A+1'
60
61     with pytest.raises(TypeError):
62         test_wrapper['V'] = 'K'
63
64     with pytest.raises(TypeError):
65         test_wrapper['W'] = 'L^2'
66
67     with pytest.raises(TypeError):
68         test_wrapper['X'] = 'M^-1'
69
70
71 def test_simple_dynamic_evaluation(test_wrapper: MatrixWrapper) -> None:
72     """Test that expression-defined matrices are evaluated dynamically."""
73     test_wrapper['N'] = 'A^2'
74     test_wrapper['O'] = '4B'
75     test_wrapper['P'] = 'A+C'
76
77     assert (test_wrapper['N'] == test_wrapper.evaluate_expression('A^2')).all()
78     assert (test_wrapper['O'] == test_wrapper.evaluate_expression('4B')).all()
79     assert (test_wrapper['P'] == test_wrapper.evaluate_expression('A+C')).all()
80
81     assert (test_wrapper.evaluate_expression('N^2 + 3O') ==
82             la.matrix_power(test_wrapper.evaluate_expression('A^2'), 2) +
83             3 * test_wrapper.evaluate_expression('4B')
84             ).all()
85     assert (test_wrapper.evaluate_expression('P^-1 - 3N^2') ==
86             la.inv(test_wrapper.evaluate_expression('A+C')) -
87             (3 * test_wrapper.evaluate_expression('A^2')) @
88             la.matrix_power(test_wrapper.evaluate_expression('4B'), 2)
89             ).all()
90
91     test_wrapper['A'] = np.array([

```

```

92         [19, -21.5],
93         [84, 96.572]
94     ])
95     test_wrapper['B'] = np.array([
96         [-0.993, 2.52],
97         [1e10, 0]
98     ])
99     test_wrapper['C'] = np.array([
100         [0, 19512],
101         [1.414, 19]
102     ])
103
104     assert (test_wrapper['N'] == test_wrapper.evaluate_expression('A^2')).all()
105     assert (test_wrapper['O'] == test_wrapper.evaluate_expression('4B')).all()
106     assert (test_wrapper['P'] == test_wrapper.evaluate_expression('A+C')).all()
107
108     assert (test_wrapper.evaluate_expression('N^2 + 30') ==
109             la.matrix_power(test_wrapper.evaluate_expression('A^2'), 2) +
110             3 * test_wrapper.evaluate_expression('4B')
111             ).all()
112     assert (test_wrapper.evaluate_expression('P^-1 - 3N0^2') ==
113             la.inv(test_wrapper.evaluate_expression('A+C')) -
114             (3 * test_wrapper.evaluate_expression('A^2')) @
115             la.matrix_power(test_wrapper.evaluate_expression('4B'), 2)
116             ).all()
117
118
119 def test_recursive_dynamic_evaluation(test_wrapper: MatrixWrapper) -> None:
120     """Test that dynamic evaluation works recursively."""
121     test_wrapper['N'] = 'A^2'
122     test_wrapper['O'] = '4B'
123     test_wrapper['P'] = 'A+C'
124
125     test_wrapper['Q'] = 'N^-1'
126     test_wrapper['R'] = 'P-4O'
127     test_wrapper['S'] = 'NOP'
128
129     assert test_wrapper['Q'] == pytest.approx(test_wrapper.evaluate_expression('A^-2'))
130     assert test_wrapper['R'] == pytest.approx(test_wrapper.evaluate_expression('A + C - 16B'))
131     assert test_wrapper['S'] == pytest.approx(test_wrapper.evaluate_expression('A^{2}4BA + A^{2}4BC'))
132
133
134 def test_set_identity_error(new_wrapper: MatrixWrapper) -> None:
135     """Test that MatrixWrapper().__setitem__() raises a NameError when trying to assign to the identity matrix."""
136     with pytest.raises(NameError):
137         new_wrapper['I'] = test_matrix
138
139
140 def test_set_name_error(new_wrapper: MatrixWrapper) -> None:
141     """Test that MatrixWrapper().__setitem__() raises a NameError when trying to assign to an invalid name."""
142     for name in invalid_matrix_names:
143         with pytest.raises(NameError):
144             new_wrapper[name] = test_matrix
145
146
147 def test_set_type_error(new_wrapper: MatrixWrapper) -> None:
148     """Test that MatrixWrapper().__setitem__() raises a TypeError when trying to set a non-matrix."""
149     invalid_values: list[Any] = [
150         12,
151         [1, 2, 3, 4, 5],
152         [[1, 2], [3, 4]],
153         True,
154         24.3222,
155         'This is totally a matrix, I swear',
156         MatrixWrapper,
157         MatrixWrapper(),
158         np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]]),
159         np.eye(100)
160     ]
161
162     for value in invalid_values:
163         with pytest.raises(TypeError):
164             new_wrapper['M'] = value

```

## B.7 gui/test\_dialog\_utility\_functions.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the utility functions for GUI dialog boxes."""
8
9  import numpy as np
10 import pytest
11
12 from lintrans.gui.dialogs.define_new_matrix import is_valid_float, round_float
13
14 valid_floats: list[str] = [
15     '0', '1', '3', '-2', '123', '-208', '1.2', '-3.5', '4.252634', '-42362.352325',
16     '1e4', '-2.59e3', '4.13e-6', '-5.5244e-12'
17 ]
18
19 invalid_floats: list[str] = [
20     '', 'pi', 'e', '1.2.3', '1,2', '-', '.', 'None', 'no', 'yes', 'float'
21 ]
22
23
24 @pytest.mark.parametrize('inputs,output', [(valid_floats, True), (invalid_floats, False)])
25 def test_is_valid_float(inputs: list[str], output: bool) -> None:
26     """Test the is_valid_float() function."""
27     for inp in inputs:
28         assert is_valid_float(inp) == output
29
30
31 def test_round_float() -> None:
32     """Test the round_float() function."""
33     expected_values: list[tuple[float, int, str]] = [
34         (1.0, 4, '1'), (1e-6, 4, '0'), (1e-5, 6, '1e-5'), (6.3e-8, 5, '0'), (3.2e-8, 10, '3.2e-8'),
35         (np.sqrt(2) / 2, 5, '0.70711'), (-1 * np.sqrt(2) / 2, 5, '-0.70711'),
36         (np.pi, 1, '3.1'), (np.pi, 2, '3.14'), (np.pi, 3, '3.142'), (np.pi, 4, '3.1416'), (np.pi, 5, '3.14159'),
37         (1.23456789, 2, '1.23'), (1.23456789, 3, '1.235'), (1.23456789, 4, '1.2346'), (1.23456789, 5, '1.23457'),
38         (12345.678, 1, '12345.7'), (12345.678, 2, '12345.68'), (12345.678, 3, '12345.678'),
39     ]
40
41     for num, precision, answer in expected_values:
42         assert round_float(num, precision) == answer

```