

# lintrans

by D. Dyson

Centre Name: The Duston School  
Centre Number: 123456  
Candidate Number: 123456

# Contents

<b>1</b>	<b>Analysis</b>	<b>1</b>
1.1	Computational Approach . . . . .	1
1.2	Stakeholders . . . . .	2
1.3	Research on existing solutions . . . . .	2
1.3.1	MIT ‘Matrix Vector’ Mathlet . . . . .	2
1.3.2	Linear Transformation Visualizer . . . . .	3
1.3.3	Desmos app . . . . .	4
1.3.4	Visualizing Linear Transformations . . . . .	4
1.4	Essential features . . . . .	5
1.5	Limitations . . . . .	5
1.6	Hardware and software requirements . . . . .	6
1.6.1	Hardware . . . . .	6
1.6.2	Software . . . . .	6
1.7	Success criteria . . . . .	7
<b>2</b>	<b>Design</b>	<b>9</b>
2.1	Problem decomposition . . . . .	9
2.2	Structure of the solution . . . . .	9
2.3	Algorithm design . . . . .	11
2.4	Usability features . . . . .	13
2.5	Variables and validation . . . . .	14
2.6	Iterative test data . . . . .	15
2.7	Post-development test data . . . . .	16
2.8	Issues with testing . . . . .	16
<b>3</b>	<b>Development</b>	<b>17</b>
3.1	Matrices backend . . . . .	17
3.1.1	MatrixWrapperclass . . . . .	17
3.1.2	Rudimentary parsing and evaluating . . . . .	19
3.1.3	Simple matrix expression validation . . . . .	24
3.1.4	Parsing matrix expressions . . . . .	26
3.2	Initial GUI . . . . .	29
3.2.1	First basic GUI . . . . .	29
3.2.2	Numerical definition dialog . . . . .	31
3.2.3	More definition dialogs . . . . .	34
3.3	Visualizing matrices . . . . .	38
3.3.1	Asking strangers on the internet for help . . . . .	38
3.3.2	Creating the plots package . . . . .	38
3.3.3	Implementing basis vectors . . . . .	40
3.3.4	Drawing the transformed grid . . . . .	42
3.3.5	Implementing animation . . . . .	45
3.3.6	Preserving determinants . . . . .	46
3.4	Improving the GUI . . . . .	48
3.4.1	Fixing rendering . . . . .	48
3.4.2	Adding vector arrowheads . . . . .	50
3.4.3	Implementing zoom . . . . .	51
3.4.4	Animation blocks zooming . . . . .	53
3.4.5	Rank 1 transformations . . . . .	54
3.4.6	Matrices that are too big . . . . .	55
3.4.7	Creating the DefineVisuallyDialog . . . . .	56
3.4.8	Fixing a division by zero bug . . . . .	58
3.4.9	Implementing transitional animation . . . . .	59
3.4.10	Allowing for sequential animation with commas . . . . .	60
3.5	Adding display settings . . . . .	62
3.5.1	Creating the dataclass . . . . .	62
3.5.2	Creating the settings dialog . . . . .	64

<b>References</b>	<b>68</b>
<b>A Project code</b>	<b>69</b>
A.1 global_settings.py . . . . .	69
A.2 updating.py . . . . .	71
A.3 crash_reporting.py . . . . .	73
A.4 __main__.py . . . . .	77
A.5 __init__.py . . . . .	78
A.6 gui/main_window.py . . . . .	79
A.7 gui/session.py . . . . .	93
A.8 gui/utility.py . . . . .	95
A.9 gui/validate.py . . . . .	95
A.10 gui/settings.py . . . . .	96
A.11 gui/__init__.py . . . . .	97
A.12 gui/dialogs/define_new_matrix.py . . . . .	97
A.13 gui/dialogs/settings.py . . . . .	102
A.14 gui/dialogs/misc.py . . . . .	108
A.15 gui/dialogs/__init__.py . . . . .	114
A.16 gui/plots/widgets.py . . . . .	115
A.17 gui/plots/classes.py . . . . .	122
A.18 gui/plots/__init__.py . . . . .	132
A.19 typing/__init__.py . . . . .	132
A.20 matrices/utility.py . . . . .	133
A.21 matrices/wrapper.py . . . . .	135
A.22 matrices/__init__.py . . . . .	139
A.23 matrices/parse.py . . . . .	140
<b>B Testing code</b>	<b>147</b>
B.1 conftest.py . . . . .	147
B.2 backend/test_session.py . . . . .	147
B.3 backend/matrices/test_parse_and_validate_expression.py . . . . .	148
B.4 backend/matrices/utility/test_rotation_matrices.py . . . . .	150
B.5 backend/matrices/utility/test_coord_conversion.py . . . . .	152
B.6 backend/matrices/utility/test_float_utility_functions.py . . . . .	152
B.7 backend/matrices/matrix_wrapper/test_setting_and_getting.py . . . . .	153
B.8 backend/matrices/matrix_wrapper/test_evaluate_expression.py . . . . .	157

# 1 Analysis

One of the topics in the A Level Further Maths course is linear transformations, as represented by matrices. This is a topic all about how vectors move and get transformed in the plane. It's a topic that lends itself exceedingly well to visualization, but students often find it hard to visualize this themselves, and there is a considerable lack of good tools to provide visual intuition on the subject. There is the YouTube series *Essence of Linear Algebra* by 3blue1brown[7], which is excellent, but I couldn't find any good interactive visualizations.

My solution is to develop a desktop application that will allow the user to define  $2 \times 2$  matrices and view these matrices and compositions thereof as linear transformations of a 2D plane. This will give students a way to get to grips with linear transformations in a more hands-on way, and will give teachers the ability to easily and visually show concepts like the determinant and invariant lines.

## 1.1 Computational Approach

This solution is particularly well suited to a computational approach since it is entirely focussed on visualizing transformations, which require complex mathematics to properly display. It will also have lots of settings to allow the user to configure aspects of the visualization. As previously mentioned, visualizing transformations in one's own head is difficult, so a piece of software to do it would be very valuable to teachers and learners, but current solutions are considerably lacking.

My solution will make use of abstraction by allowing the user to define a set of matrices which they can use in expressions. This allows them to use a matrix multiple times and they don't have to keep track of any of the numbers. All the actual processing and mathematics happens behind the scenes and the user never has to worry about it - they just compose their defined matrices into transformations. This abstraction allows the user to focus on exploring the transformations themselves without having to do any actual computations. This will make learning the subject much easier, as they will be able to gain a visual intuition for linear transformations without worrying about computation until after they've built up that intuition.

I will also employ decomposition and modularization by breaking the project down into many smaller parts, such as one module to keep track of defined matrices, one module to validate and parse matrix expressions, one module for the main GUI, as well as sub-modules for the widgets and dialog boxes, etc. This decomposition allows for simpler project design, easier code maintenance (since module coupling is kept to a minimum, so bugs are isolated in their modules), inheritance of classes to reduce code repetition, and unit testing to inform development. I also intend this unit testing to be automated using GitHub Actions.

Selection will also be used widely in the application. The GUI will provide many settings for visualization, and these settings will need to be checked when rendering the transformation. For example, the user will have the option to render the determinant, so I will need to check this setting on every render cycle and only render the determinant parallelogram if the user has enabled that option. The app will have many options for visualization, which will be useful in learning, but if all these options were being rendered at the same time, then there would be too much information for the user to properly process, so I will let the user configure these display options to their liking and only render the things they want to be rendered.

Validation will also be prevalent because the matrix expressions will need to follow a strict format, which will be validated. The buttons to render and animate the matrix will only be clickable when the given expression is valid, so I will need to check this and update the buttons every time the text in the text box is changed. I will also need to parse matrix expressions so that I can evaluate them properly. All this validation ensures that crashes due to malformed input are practically impossible, and makes the user's life easier since they don't need to worry about if their input is in the right format - the app will tell them.

I will also make use of iteration, primarily in animation. I will have to re-calculate positions and

values to render everything for every frame of the animation and this will likely be done with a simple `for` loop. A `for` loop will allow me to just loop over every frame and use the counter variable as a way to measure how far through the animation we are on each frame. This is preferable to a `while` loop, since that would require me to keep track of which frame we're on with a separate variable.

Finally, the core of the application is visualization, so that will definitely be used a lot. I will have to calculate positions of points and lines based on given matrices, and when animating, I will also have to calculate these matrices based on the current frame. Then I will have to use the rendering capabilities of the GUI framework that I choose to render these calculated points and lines onto a widget, which will form the viewport of the main GUI. I may also have to convert between coordinate systems. I will have the origin in the middle with positive  $x$  going to the right and positive  $y$  going up, but I may need to convert that to standard computer graphics coordinates with the origin in the top left, positive  $x$  going to the right, and positive  $y$  going down. This visualization of linear transformations is the core component of the app and is the primary feature, so it is incredibly important.

## 1.2 Stakeholders

Stakeholders for my app include A Level Further Maths students and teachers, who learn and teach linear transformations respectively. They will be able to provide useful input as to what they would like to see in the app, and they can provide feedback on what they like and what I can add or improve. I already know from experience that linear transformations are tricky to visualize and a computer-based visualization would be useful. My stakeholders agreed with this. Multiple teachers said that a desktop app that could render and animate linear transformations would be useful in a classroom environment and students said that it would be helpful to have something that they could play around with at home and use to get to grips with matrices and linear transformations. They also said that an online version would probably be easier to use, but I have absolutely no experience in web development and I'm much more comfortable making a desktop app.

Some teachers also suggested that it would be useful to have an option to save and load sets of matrices. This would allow them to have a single save file containing some matrices, and then just load this file to use for demonstrations in the classroom. This would probably be quite easy to implement. I could just wrap all the relevant information into one object and use Python's `pickle` module to save the binary data to a file, and then load this data back into the app in a similar way.

My stakeholders agreed that being able to see incremental animation - where, for example, we apply matrix **A** to the current scene, pause, and then apply matrix **B** - would be beneficial. This would be a good demonstration of matrix multiplication being non-commutative. **AB** is not always equal to **BA**. Being able to see this in terms of animating linear transformations would be good for learning.

They also agreed that a tutorial on using the software would be useful, so I plan to implement this through an online written tutorial hosted with GitHub Pages, and perhaps a video tutorial as well. This would make the app much easier to use for people who have never seen it before. It wouldn't be a lesson on the maths itself, but just a guide on how to use the software.

## 1.3 Research on existing solutions

There are actually quite a few web apps designed to help visualize 2D linear transformations but many of them are hard to use and lacking many features.

### 1.3.1 MIT 'Matrix Vector' Mathlet

Arguably the best app that I found was an MIT 'Mathlet' - a simple web app designed to help visualize a maths concept. This one is called 'Matrix Vector'[8] and allows the user to drag an input vector

around the plane and see the corresponding output vector, transformed by a matrix that the user can define, although this definition is finicky since it involves sliders rather than keyboard input.

This app fails in two crucial ways in my opinion. It doesn't show the basis vectors or let the user drag them around, and the user can only define and therefore visualize a single matrix at once. This second problem was common among every solution I found, so I won't mention it again, but it is a big issue in my opinion and my app will allow for multiple matrices. I like the idea of having a draggable input vector and rendering its output, so I will probably have this feature in my app, but I also want the ability to define multiple matrices and be able to drag the basis vectors to visually define a matrix. Being able to drag the basis vectors will help build intuition, so I think this would greatly benefit the app.




Figure 1.1: The MIT 'Matrix Vector' Mathlet

However, in the comments on this Mathlet, a user called 'David S. Bruce' suggested that the Mathlet should display the basis vectors, to which a user called 'hrm' (who I assume to be the 'H. Miller' to whom the copyright of the whole website is accredited) replied saying that this Mathlet is primarily focussed on eigenvectors, that it is perhaps badly named, and that displaying the basis vectors 'would make a good focus for a second Mathlet about  $2 \times 2$  matrices'. This Mathlet does not exist. But I do like the idea of showing the eigenvectors and eigenlines, so I will definitely have that in my app. Showing the invariant lines or lack thereof will help with learning, since these are often hard to visualize.

### 1.3.2 Linear Transformation Visualizer




Figure 1.2: 'Linear Transformation Visualizer' halfway through an animation

Another web app that I found was one simply called 'Linear Transformation Visualizer' by Shad Sharma[22]. This one was similarly inspired by 3blue1brown's YouTube series. This app has the ability to render input and output vectors and eigenlines, but it can also render the determinant parallelogram; it allows the user to drag the basis vectors; and it has the option to snap vectors to the background grid, which is quite useful. It also implements a simple form of animation where the tips of the vectors move in straight lines from where they start to where they end, and the animation is controlled by dragging a slider labelled  $t$ . This isn't particularly intuitive.

I really like the vectors snapping to the grid, the input and output vectors, and rendering the determinant. This app also renders positive and negative determinants in different colours, which is really nice - I intend to use that idea in my own app, since it helps create understanding about negative determinants in terms of orientation changes. However, I think that the animation system here is flawed and not very easy to use. My animation will likely be a button, which just triggers an animation, rather than a slider. I also don't like the way vector dragging is handled. If you click anywhere on the grid, then the closest vector target (the final position of the target's associated vector) snaps to that location. I think it would be more intuitive to have to drag the vector from its current location to where you want it. This was also a problem with the MIT Mathlet.

### 1.3.3 Desmos app

One of the solutions I found was a Desmos app[6], which was quite hard to use and arguably over-complicated. Desmos is not designed for this kind of thing - it's designed to graph pure mathematical functions - and it shows here. However, this app brings some really interesting ideas to the table, mainly functions. This app allows you to define custom functions and view them before and after the transformation. This is achieved by treating the functions parametrically as the set of points  $(t, f(t))$  and then transforming each coordinate by the given matrix to get a new coordinate.




Figure 1.3: The Desmos app halfway through an animation, rendering  $f(x) = \frac{\sin^2 x}{x}$  in orange

Desmos does this for every point and then renders the resulting transformed function parametrically. This is a really interesting technique and idea, but I'm not going to use it in my app. I don't think arbitrary functions fit with the linearity of the whole app, and I don't think it's necessary. It's just overcomplicating things, and rendering it on a widget would be tricky, because I'd have to render every point myself, possibly using something like OpenGL. It's just not worth implementing.

Additionally, this Desmos app makes things quite hard to see. It's hard to tell where any of the vectors are - they just get lost in the sea of grid lines. This image also hides some of the extra information. For instance, this image doesn't show the original function  $f(x) = \frac{\sin^2 x}{x}$ , only the transformed version. This app easily gets quite cluttered. I will give my vectors arrowheads to make them easily identifiable amongst the grid lines.

### 1.3.4 Visualizing Linear Transformations



Figure 1.4: The GeoGebra applet rendering its default matrix

The last solution that I want to talk about is a GeoGebra applet simply titled 'Visualizing Linear Transformations'[10]. This applet has input and output vectors, original and transformed grid lines, a unit circle, and the letter N. It allows the user to define a matrix as 4 numbers and view the aforementioned N (which the user can translate to anywhere on the grid), the unit circle, the input/output vectors, and the grid lines. It also has the input vector snapping to integer coordinates, but that's a standard part of GeoGebra.

I've already talked about most of these features but the thing I wanted to talk about here is the N. I don't particularly want the letter N to be a prominent part of my own app, but I really like the idea of being able to define a custom polygon and see how that polygon gets transformed by a given transformation. I think that would really help with building intuition and it shouldn't be too hard to implement.

## 1.4 Essential features

The primary aim of this application is to visualize linear transformations, so this will obviously be the centre of the app and an essential feature. I will have a widget which can render a background grid and a second version of the grid, transformed according to a user-defined matrix expression. This is necessary because it is the entire purpose of the app. It's designed to visualize linear transformations and would be completely useless without this visual component. I will give the user the ability to render a custom matrix expression containing matrices they have previously defined, as well as reset the canvas to the default identity matrix transformation. This will obviously require an input box to enter the expression, a render button, a reset button, and various dialog boxes to define matrices in different ways. I want the user to be able to define a matrix as a set of 4 numbers, and by dragging the basis vectors  $i$  and  $j$ . These dialogs will allow the user to define new matrices to be used in expressions, and having multiple ways to do it will make it easier, and will aid learning.

Another essential feature is animation. I want the user to be able to smoothly animate between matrices. I see two options for how this could work. If  $\mathbf{C}$  is the matrix for the currently displayed transformation, and  $\mathbf{T}$  is the matrix for the target transformation, then we could either animate from  $\mathbf{C}$  to  $\mathbf{T}$  or we could animate from  $\mathbf{C}$  to  $\mathbf{TC}$ . I would probably call these transitional and applicative animation respectively. Perhaps I'll give the user the option to choose which animation method they want to use. I might even have an option for sequential animation, where the user can define a sequence of matrices, perhaps separated with commas or semicolons, and the app will animate through the sequence, applying one at a time. Sequential animation would be nice, but is not crucial.

Either way, animation is used in most of the alternative solutions that I found, and it's a great way to build intuition, by allowing students to watch the transformation happen in real time. Compared to simply rendering the transformations, animating them would profoundly benefit learning, and since that's the main aim of the project, I think animation is a necessary part of the app.

Something that I thought was a big problem in every alternative solution I found was the fact that the user could only visualize a single matrix at once. I see this as a fatal flaw and I will allow the user to define 25 different matrices (all capital letters except  $\mathbf{I}$  for the identity matrix) and use all of them in expressions. This will allow teachers to define multiple matrices and then just change the expression to demonstrate different concepts rather than redefine a new transformation every time. It will also make things easier for students as it will allow them to visualize compositions of different matrix transformations without having to do any computations themselves.

Additionally, being able to show information on the currently displayed matrix is an essential tool for learning. Rendering things like the determinant parallelogram and the invariant lines of the transformation will greatly assist with learning and building understanding, so I think that having the option to render these attributes of the currently displayed transformation is necessary for success.

## 1.5 Limitations

The main limitation in this app is likely to be drawing grid lines. Most transformations will be fine but in some cases, the app will be required to draw potentially thousands of grid lines on the canvas and this will probably cause noticeable lag, especially in the animations. I will have to artificially limit the number of grid lines that can be drawn on the screen. This won't look fantastic, because it means that the grid lines will only extend a certain distance from the origin, but it's an inherent limitation of computers. Perhaps if I was using a faster, compiled language like C++ rather than Python, this processing would happen faster and I could render more grid lines, but it's impossible to render all the grid lines and any implementation of this idea must limit them for performance.

An interesting limitation is that I don't think I'll implement panning. I suspect that I'll have to convert between coordinate systems and having the origin in the centre of the canvas will probably make the code much simpler. Also, linear transformations always leave the origin fixed, so always having it in the centre of the canvas seems thematically appropriate. Panning is certainly an option - the Desmos solution in §1.3.3 and GeoGebra solution in §1.3.4 both allow panning as a default part



of Desmos and GeoGebra respectively, for example - but I don't think I'll implement it myself. I just don't think it's worth it.

I'm also not going to do any work with 3D linear transformations. 3D transformations are often harder to visualize and thus it would make sense to target them in an app like this, designed to help with learning and intuition, but 3D transformations are also harder to code. I would have to use a full graphics package rather than a simple widget, and I think it would be too much work for this project and I wouldn't be able to do it in the time frame. It's definitely a good idea, but I'm currently incapable of creating an app like that.

There are other limitations inherent to matrices. For instance, it's impossible to take an inverse of a singular matrix. There's nothing I can do about that without rewriting most of mathematics. Matrices can also only represent linear transformations. There's definitely a market for an app that could render any arbitrary transformation from  $\mathbb{R}^2 \rightarrow \mathbb{R}^2$  - I know I'd want an app like that - but matrices can only represent linear transformations, so those are the only kind of transformations that I'll be looking at with this project.

## 1.6 Hardware and software requirements

### 1.6.1 Hardware

Hardware requirements for the project are the same between the release and development environments and they're quite simple. I expect the app to require a processor with at least 1 GHz clock speed, \$BINARY\_SIZE free disk space, and about 1 GB of available RAM. The processor and RAM requirements are needed by the Python runtime and mainly by Qt5 - the GUI library I'll be using. The \$BINARY\_SIZE disk space is just for the executable binary that I'll compile for the public release. The code itself is less than 1 MB, but the compiled binary has to package all the dependencies and the entire CPython runtime to allow it to run on systems that don't have that, so the file size is much bigger.

I will also require that the user has a monitor that is at least  $1920 \times 1080$  pixels in resolution. This isn't necessarily required, because the app will likely run in a smaller window, but a HD monitor is highly recommended. This allows the user to go fullscreen if they want to, and it gives them enough resolution to easily see everything in the app. A large, wall-mounted screen is also highly recommended for use in the classroom, although this is common among schools.

I will also require a keyboard with all standard Latin alphabet characters. This is because the matrices are defined as uppercase Latin letters. Any UK or US keyboard will suffice for this. The app will also require a mouse with at least one button. I don't intend to have right click do anything, so only the primary mouse button is required, although getting a single button mouse to actually work on modern computers is probably quite a challenge. A separate mouse is not strictly required - a laptop trackpad is equally sufficient.

### 1.6.2 Software

Software requirements differ slightly between release and development, although everything that the release environment requires is also required by the development environment. I will require a modern operating system - namely Windows 10 or later, macOS 10.9 'Mavericks'<sup>1</sup> or later, or any modern Linux distro<sup>2</sup>. Basically, it just requires an operating system that is compatible with Python 3.8 or higher as well as Qt5, since I'll be using these in the project. Of course, Qt5 will need to be installed on the user's computer, although it's standard pretty much everywhere these days.

---

<sup>1</sup>Python 3.8 or higher won't compile on any earlier versions of macOS[16]

<sup>2</sup>Specifying a Linux version is practically impossible. Python 3.8 or higher is available in many package repositories, but all modern Python versions will compile on any modern distro. Qt5 is available in many package repositories and can be compiled on any x86 or x86\_64 generic Linux machine with gcc version 5 or later[17]

Python won't actually be required for the end user, because I will be compiling the app into a stand-alone binary executable for release, and this binary will contain the required Python runtime and dependencies. However, if the user wishes to download and run the source code themselves, then they will need Python 3.8 or higher and the package dependencies: `numpy`, `nptyping`, and `pyqt5`. These can be automatically installed with the command `python -m pip install -r requirements.txt` from the root of the repository, although the whole project will be an installable Python package, so using `pip install -e .` will be preferred.

`numpy` is a maths library that allows for fast matrix maths; `nptyping` is used by `mypy` for type-checking and isn't actually a runtime dependency but the imports in the `typing` module fail if it's not installed at runtime<sup>3</sup>; and `pyqt5` is a library that just allows interop between Python and Qt5, which is originally a C++ library.

In the development environment, I use PyCharm for actually writing my code, and I use a virtual environment to isolate my project dependencies. There are also some development dependencies listed in the file `dev_requirements.txt`. They are: `mypy`, `pyqt5-stubs`, `flake8`, `pycodestyle`, `pydocstyle`, and `pytest`. `mypy` is a static type checker<sup>4</sup>; `pyqt5-stubs` is a collection of type annotations for the PyQt5 API for `mypy` to use; `flake8`, `pycodestyle`, and `pydocstyle` are all linters; and `pytest` is a unit testing framework. I use these libraries to make sure my code is good quality and actually working properly during development.

## 1.7 Success criteria

The main aim of the app is to help teach students about linear transformations. As such, the primary measure of success will be letting teachers get to grips with the app and then asking if they would use it in the classroom or recommend it to students to use at home.

Additionally, the app must fulfil some basic requirements:

1. It must allow the user to define multiple matrices in at least two different ways (numerically and visually)
2. It must be able to validate arbitrary matrix expressions
3. It must be able to render any valid matrix expression
4. It must be able to animate any valid matrix expression
5. It must be able to apply a matrix expression to the current scene and animate this (animate from **C** to **TC**, and perhaps do sequential animation)
6. It must be able to display information about the currently rendered transformation (determinant, eigenlines, etc.)
7. It must be able to save and load sessions (defined matrices, display settings, etc.)
8. It must allow the user to define and transform arbitrary polygons

Defining multiple matrices is a feature that I thought was lacking from every other solution I researched, and I think it would make the app much easier to use, so I think it's necessary for success. Validating matrix expressions is necessary because if the user tries to render an expression that doesn't make sense, has an undefined matrix, or contains the inverse of a singular matrix, then we have to disallow that or else the app will crash.

Visualizing matrix expressions as linear transformations is the core part of the app, so basic rendering of them is definitely a requirement for success. Animating these expressions is also a pretty crucial part of the app, so I would consider this necessary for success. Displaying the information of a matrix

---

<sup>3</sup>These `nptyping` imports are needed for type annotations all over the code base, so factoring them out is not feasible

<sup>4</sup>Python has weak, dynamic typing with optional type annotations but `mypy` enforces these static type annotations

transformation is also very useful for building understanding, so I would consider this needed to succeed.

Saving and loading isn't strictly necessary for success, but it is a standard part of many apps, so will likely be expected by users, and it will benefit the app by allowing teachers to plan lessons in advance and save the matrices they've defined for that lesson to be loaded later.


Transforming polygons is the lowest priority item on this list and will likely be implemented last, but it would definitely benefit learning. I wouldn't consider it necessary for success, but it would be very good to include, and it's certainly a feature that I want to have.

If the majority of teachers would use and/or recommend the app and it meets all of these points, then I will consider the app as a whole to be a success.

## 2 Design

### 2.1 Problem decomposition

I have decomposed the problem of visualization as follows:



Defining matrices is key to visualization because we need to have matrices to actually visualize. This is a key part of the app, and the user will be able to define multiple separate matrices numerically and visually using the GUI.


Evaluating expressions is another key part of the app and can be further broken down into validating, parsing, and computing the value. Validating an expression simply consists of checking that it adheres to a set of syntax rules for matrix expressions, and that it only contains matrices which have already been defined. Parsing consists of breaking an expression down into tokens, which are then much easier to evaluate. Computing the expression with these tokens is then just a series of simple operations, which will produce a final matrix at the end.

Rendering and animating will likely be the largest part in reality, but I've only decomposed it into simple blocks here. Evaluating positions involves evaluating the matrix expression that the user has input and using the columns of the resultant matrix to find the new positions of the basis vectors, and then extrapolating this for the rest of the plane. Rendering onto the widget is likely to be quite complicated and framework-dependent, so I've abstracted away the details for brevity here. Rendering will involve using the previously calculated values to render grid lines and vectors. Animating will probably be a `for` loop which just renders slightly different matrices onto the widget and sleeps momentarily between frames.

I have deliberately broken this problem down into parts that can be easily translated into modules in my eventual coded solution. This is simply to ease the design and development process, since now I already know my basic project structure. This problem could've been broken down into the parts that the user will directly interact with, but that would be less useful to me when actually starting development, since I would then have to decompose the problem differently to write the actual code.

### 2.2 Structure of the solution

I have decomposed my solution like so:



The `lintrans` node is simply the root of the whole project. `__main__` is the Python way to make the project executable as `python -m lintrans` on the command line. For release, I will package it into a standalone binary executable, using this module as the entry point.

The `global_settings` module will define a `GlobalSettings` singleton class. This class will manage global settings and variables - things like where to save sessions by default, etc. I'm not entirely sure what I want to put in here, but I expect that I'll want global settings in the future. Having this class will allow me to easily read and write these settings to a file to have them persist between sessions.

`matrices` is the package that will allow the user to define, validate, parse, evaluate, and use matrices. The `matrices.parse` module will contain functions to validate matrix expressions - likely using regular expressions - and functions to parse matrix expressions. It will not know which matrices are defined, so validation will be naïve and evaluation will be in the `matrices.wrapper` module. This `wrapper` module will contain a `MatrixWrapper` class, which will hold a dictionary of matrix names and values. It is this class which will have aware validation - making sure that all the matrices used in an expression are actually defined in the wrapper - as well the ability to evaluate matrix expressions, in addition to its basic behaviour of setting and getting matrices by name. There will also be a `matrices.utility` module, which will contain some simple functions for simple functionality. Functions like `create_rotation_matrix()`, which will generate a rotation matrix from an angle using the formula  $\begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}$ .

`gui` is the package that will contain all the frontend code for everything GUI-related. `gui.main_window` is the module that will define the `LintransMainWindow` class, which will act as the main window of the application and have an instance of `MatrixWrapper` to keep track of which matrices are defined and allow for evaluation of matrix expressions. It will also have methods for rendering and animating matrix expressions, which will be connected to buttons in the GUI. The most important part of the main window is the viewport, which will be discussed shortly. This module will also contain a simple `main()` function to instantiate and launch the application GUI.

The `gui.session` module will contain functions to save and load a session from a file. A session will consist of the `MatrixWrapper`, along with perhaps the display settings and maybe some other things. I know that saving the wrapper will be essential, but I'll see what else should be saved as the project evolves.

The `gui.settings` module will contain a `DisplaySettings` dataclass<sup>5</sup> that will represent the settings for visualizing transformations. The viewport class will have an instance of this class and check against it when rendering things. The user will be able to open a dialog to change these display settings, which will update the main window's instance of this class.

The `gui.dialogs` subpackage will contain modules with different dialog classes. It will have a `gui.dialogs.define_new_matrices` module, which will have a `DefinedDialog` abstract superclass. It will then contain classes that inherit from this superclass and provide dialogs for defining new matrices visually,

<sup>5</sup>This is the Python equivalent of a struct or record in other languages

numerically, and as an expression in terms of other matrices. Additionally, it will contain a `gui.dialogs.settings` module, which will provide a `SettingsDialog` superclass and a `DisplaySettingsDialog` class, which will allow the user to configure the aforementioned display settings. It may also have a `GlobalSettingsDialog` class in the future, which would similarly allow the user to configure the app's global settings through a dialog. This will only be implemented once I've actually got global settings to configure.

The `gui.dialogs.misc` module will contain small miscellaneous dialog boxes - things like the about box which are very simple and don't need a dedicated module.

The `gui.plots` subpackage will have a `gui.plots.classes` module and a `gui.plots.widgets` module. The `classes` module will have the abstract superclasses `BackgroundPlot` and `VectorGridPlot`. The former will provide helper methods to convert between coordinate systems and draw the background grid, while the latter will provide helper methods to draw transformations and their components. It will have `point_i` and `point_j` attributes and will provide methods to draw the transformed version of the grid, the vectors and their arrowheads, the eigenlines of the transformation, etc. These methods can then be called from the Qt5 `paintEvent` handler which will be declared abstract and must therefore be implemented by all subclasses.

The `gui.plots.widgets` module will have the classes `VisualizeTransformationWidget` and `DefineVisuallyWidget`, which will both inherit from `VectorGridPlot`. They will both implement their own `paintEvent` handler to actually draw the respective widgets, and `DefineVisuallyWidget` will also implement handlers for mouse events, allowing the user to drag around the basis vectors.

I also want the user to be able to define arbitrary polygons and view their transformations. I imagine this polygon definition will happen in a separate dialog, but I don't know where that's going to fit just yet. I'll probably have the widget in `gui.plots.widgets`, but possibly elsewhere.

## 2.3 Algorithm design

The project will have many algorithms but a lot of them will be related to drawing transformations on the canvas itself, and almost all of the algorithms will evolve over time. In this section, I will present pseudocode for some of the most interesting parts of the project. My pseudocode is actually Python, purely to allow for syntax highlighting.

The `lintrans.matrices.utility` module will look like this:

```

1  import numpy as np
2
3  def create_rotation_matrix(angle: float, *, degrees: bool = True) -> MatrixType:
4      """Create a matrix representing a rotation (anticlockwise) by the given angle."""
5      rad = np.deg2rad(angle % 360) if degrees else angle % (2 * np.pi)
6      return np.array([
7          [np.cos(rad), -1 * np.sin(rad)],
8          [np.sin(rad), np.cos(rad)]
9      ])

```

And the `lintrans.matrices.wrapper` module will look like this:

```

1  import re
2  import numpy as np
3
4  # The `utility` syntax means that the utility module is next to this one in the tree
5  from .utility import create_rotation_matrix
6
7  class MatrixWrapper:
8      def __init__(self):
9          # This dictionary maps all letters of the alphabet to an optional matrix
10         self._matrices: Dict[str, Optional[Union[MatrixType, str]]] = {
11             'A': None, 'B': None, 'C': None, 'D': None,

```

```

12         'E': None, 'F': None, 'G': None, 'H': None,
13         'I': np.eye(2), # I is always defined as the identity matrix
14         'J': None, 'K': None, 'L': None, 'M': None,
15         'N': None, 'O': None, 'P': None, 'Q': None,
16         'R': None, 'S': None, 'T': None, 'U': None,
17         'V': None, 'W': None, 'X': None, 'Y': None,
18         'Z': None
19     }
20
21     def __getitem__(self, name: str) -> Optional[MatrixType]:
22         """Get the matrix with the given name.
23
24         If it is a simple name, it will just be fetched from the dictionary. If the name is ``rot(x)``, with
25         a given angle in degrees, then we return a new matrix representing a rotation by that angle.
26
27         Using ``__getitem__`` here allows for syntax like ``wrapper['A']`` as if it was a dictionary.
28         """
29         # Return a new rotation matrix
30         if (match := re.match(r'^rot\((-?\d*\.\d*)\)$', name)) is not None:
31             return create_rotation_matrix(float(match.group(1)))
32
33         if name not in self._matrices:
34             raise NameError(f'Unrecognised matrix name "{name}"')
35
36         # We copy the matrix before we return it so the user can't accidentally mutate the matrix
37         matrix = copy(self._matrices[name])
38
39         return matrix
40
41     def __setitem__(self, name: str, new_matrix: Optional[MatrixType]) -> None:
42         """Set the value of matrix ``name`` with the new_matrix.
43
44         If ``new_matrix`` is None, then that effectively unsets the matrix name.
45
46         Using ``__getitem__`` here allows for syntax like ``wrapper['A'] = matrix`` as if it was a dictionary.
47         """
48         if not (name in self._matrices and name != 'I'):
49             raise NameError('Matrix name is illegal')
50
51         if new_matrix is None:
52             self._matrices[name] = None
53             return
54
55         if not is_matrix_type(new_matrix):
56             raise TypeError('Matrix must be a 2x2 NumPy array')
57
58         # All matrices must have float entries
59         a = float(new_matrix[0][0])
60         b = float(new_matrix[0][1])
61         c = float(new_matrix[1][0])
62         d = float(new_matrix[1][1])
63
64         self._matrices[name] = np.array([[a, b], [c, d]])

```

These modules handle the creation, storage, and use of matrices. Their implementations are deliberately simple, since they don't have to do much. I will eventually extend the `MatrixWrapper` class to allow strings as matrices, so they can be defined as expressions, but this is unnecessary for now. It will simply be more conditions in `__getitem__` and `__setitem__` and a method to evaluate expressions.

Parsing matrix expressions will be quite tricky and I don't really know how I'm going to do it. I think it will be possible with regular expressions, since I won't support nested expressions at first. But adding support for nested expressions may require something more complicated. I will have a function to validate a matrix expression, which can definitely be done with regular expressions, and I'll have another public function to parse matrix expressions, although this one may use some private functions to implement it properly.

I'm not sure on any algorithms yet, but here's the full BNF specification for matrix expressions (including nested expressions):

```

expression      ::= [ "-" ] matrices { ( "+" | "-" ) matrices };
matrices        ::= matrix { matrix };
matrix          ::= [ real_number ] matrix_identfier [ index ] | "(" expression ")";
matrix_identfier ::= "A" .. "Z" | "rot(" [ "-" ] real_number ")";
index           ::= "^{" index_content "}" | "^" index_content;
index_content   ::= [ "-" ] integer_not_zero | "T";

digit_no_zero   ::= "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9";
digit           ::= "0" | digit_no_zero;
digits          ::= digit | digits digit;
integer_not_zero ::= digit_no_zero [ digits ];
real_number     ::= ( integer_not_zero [ "." digits ] | "0" "." digits );

```

Obviously the data structure returned by the parser is very important. I have decided to use `list[list[tuple[str, str, str]]]`. Each tuple represents a real number multiplier, a matrix identifier, and an index. The multiplier and index may be empty strings. These tuples are contained in lists which represent matrices to be multiplied together, in order. Those lists are contained in a top level list, which represents multiplication groups which should be summed.

This type makes the structure of the input clear, and makes it very easy for the `MatrixWrapper` to evaluate a parsed expression.

## 2.4 Usability features

My main concern in terms of usability is colour. In the 3blue1brown videos on linear algebra, red and green are used for the basis vectors, but these colours are often hard to distinguish in most common forms of colour blindness. The most common form is deuteranopia[25], which makes red and green look incredibly similar. I will use blue and red for my basis vectors. These colours are easy to distinguish for people with deuteranopia and protanopia - the two most common forms of colour blindness. Tritanopia makes it harder to distinguish blue and yellow, but my colour scheme is still be accessible for people with tritanopia, as red and blue are very distinct in this form of colour blindness.

I will probably use green for the eigenvectors and eigenlines, which will be hard to distinguish from the red basis vector for people with red-green colour blindness, but I think that the basis vectors and eigenvectors/eigenlines will look physically different enough from each other that the colour shouldn't be too much of a problem. Additionally, I will use a tool called Color Oracle[11] to make sure that my app is accessible to people with different forms of colour blindness<sup>6</sup>.

Another solution would be to have one default colour scheme, and allow the user to change the colour scheme to something more accessible for colour blind people, but I don't see the point in this. I think it's easier for colour blind people to just have the main colour scheme be accessible, and it's not really an inconvenience to non-colour blind people, so I think this is the best option.

The layout of my app will be self-consistent and follow standard conventions. I will have a menu bar at the top of the main window for actions like saving and loading, as well as accessing the tutorial (which will also be accessible by pressing `F1` at any point) and documentation. The dialogs will always have the confirm button in the bottom right and the cancel button just to the left of that. They will also have the matrix name drop-down on the left. This consistency will make the app easier to learn and understand.

I will also have hotkeys for everything that can have hotkeys - buttons, checkboxes, etc. This makes my life easier, since I'm used to having hotkeys for everything, and thus makes the app faster to test because I don't need to click everything. This also makes things easier for other people like me, who prefer to stay at the keyboard and not use the mouse. Obviously a mouse will be required for things

<sup>6</sup>I actually had to clone a fork of this project[1] to get it working on Ubuntu 20.04 and adapt it slightly to create a working jar file



like dragging basis vectors and polygon vertices, but hotkeys will be available wherever possible to help people who don't like using the mouse or find it difficult.

## 2.5 Variables and validation

The most important variables in the project will be instance attributes on the `LintransMainWindow` class. It will have a `MatrixWrapper` instance, a `DisplaySettings` instance, and most importantly, a `VisualizeTransformationWidget` instance. These will handle the matrices and various settings respectively. Having these as instance attributes allows them to be referenced from any method in the class, and Qt5 uses lots of slots (basically callback methods) and handlers, so it's good to be able to access the attributes I need right there rather than having to pass them around from method to method.

The `MatrixWrapper` class will have a dictionary of names and matrices. The names will be single letters<sup>7</sup> and the matrices will be of type `MatrixType`. This will be a custom type alias representing a  $2 \times 2$  numpy array of floats. When setting the values for these matrices, I will have to manually check the types. This is because Python has weak typing, and if we got, say, an integer in place of a matrix, then operations would fail when trying to evaluate a matrix expression, and the program would crash. To prevent this, we have to validate the type of every matrix when it's set. I have chosen to use a dictionary here because it makes accessing a matrix by its name easier. We don't have to check against a list of letters and another list of matrices, we just index into the dictionary.

The settings dataclasses will have instance attributes for each setting. Most of these will be booleans, since they will be simple binary options like *Show determinant*, which will be represented with checkboxes in the GUI. The `DisplaySettings` dataclass will also have an attribute of type `int` representing the time in milliseconds to pause during animations.

The `DefineDialog` superclass have a `MatrixWrapper` instance attribute, which will be a parameter in the constructor. When `LintransMainWindow` spawns a definition dialog (which subclasses `DefineDialog`), it will pass in a copy of its own `MatrixWrapper` and connect the `accepted` signal for the dialog. The slot (method) that this signal is connected to will get called when the dialog is closed with the *Confirm* button<sup>8</sup>. This allows the dialog to mutate its own `MatrixWrapper` object and then the main window can copy that mutated version back into its own instance attribute when the user confirms the change. This reduces coupling and makes everything easier to reason about and debug, as well as reducing the number of bugs, since the classes will be independent of each other. In another language, I could pass a pointer to the wrapper and let the dialog mutate it directly, but this is potentially dangerous, and Python doesn't have pointers anyway.

Validation will also play a very big role in the application. The user will be able to enter matrix expressions and these must be validated. I will define a BNF schema and either write my own RegEx or use that BNF to programmatically generate a RegEx. Every matrix expression input will be checked against it. This is to ensure that the matrix wrapper can actually evaluate the expression. If we didn't validate the expression, then the parsing would fail and the program could crash. I've chosen to use a RegEx here rather than any other option because it's the simplest. Creating a RegEx can be difficult, especially for complicated patterns, but it's then easier to use it. Also, Python can compile a RegEx pattern, which makes it much faster to match against, so I will compile the pattern at initialization time and just compare expressions against that pre-compiled pattern, since we know it won't change at runtime.

Additionally, the buttons to render and animate the current matrix expression will only be enabled when the expression is valid. Textboxes in Qt5 emit a `textChanged` signal, which can be connected to a slot. This is just a method that gets called whenever the text in the textbox is changed, so I can use this method to validate the input and update the buttons accordingly. An empty string will count as invalid, so the buttons will be disabled when the box is empty.

---

<sup>7</sup>I would make these char but Python only has a `str` type for strings

<sup>8</sup>Actually when the dialog calls `.accept()`. The *Confirm* button is actually connected to a method which first takes the info and updates the instance `MatrixWrapper`, and then calls `.accept()`

I will also apply this matrix expression validation to the textbox in the dialog which allows the user to define a matrix as an expression involving other matrices, and I will validate the input in the numeric definition dialog to make sure that all the inputs are floats. Again, this is to prevent crashes, since a matrix with non-number values in it will likely crash the program.

## 2.6 Iterative test data

In unit testing, I will test the validation, parsing, and generation of rotation matrices from an angle. I will also unit test the utility functions for the GUI, like `is_valid_float`, which is needed to verify input when defining a matrix visually.

For the validation of matrix expressions, I will have data like the following:

Valid	Invalid
"A"	" "
"AB"	"A^"
"-3.4A"	"rot( )"
"A^2"	"A^{2"
"A^T"	"^12"
"A^{-1}"	"A^{3.2"
"rot(45)"	"A^B"
"3A^{12}"	".A"
"2B^2+A^TC^{-1}"	"--A"
"3.5A^{4}5.6rot(19.2^T-B^{-1})4.1C^5"	"A--B"

This list is not exhaustive, mostly to save space and time, but the full unit testing code is included in appendix B.

The invalid expressions presented here have been chosen to be almost valid, but not quite. They are edge cases. I will also test blatantly invalid expressions like "This is a matrix expression" to make sure the validation works.

Here's an example of some test data for parsing:

Input	Expected
"A"	[[(" ", "A", " ")]]
"AB"	[[(" ", "A", " "), (" ", "B", " ")]]
"2A+B^2"	[[("2", "A", " "), (" ", "B", "2")]]
"3A^T2.4B^{-1}-C"	[[("3", "A", "T"), ("2.4", "B", "-1")], [("-", "C", " ")]]

The parsing output is pretty verbose and this table doesn't have enough space for most of the more complicated inputs, so here's a monster one:

"2.14A^{3} 4.5rot(14.5)^{-1} + 8.5B^T 5.97C^{14} - 3.14D^{-1} 6.7E^T"

which should parse to give:

[[("2.14", "A", "3"), ("4.5", "rot(14.5)", "-1")], [("8.5", "B", "T"), ("5.97", "C", "14")], [("-", "3.14", "D", "-1"), ("6.7", "E", "T")]]

Any invalid expression will also raise a `MatrixParseError`, so I will check every invalid input previously mentioned and make sure it raises the appropriate error.

Again, this section is brief to save space and time. All unit tests are included in appendix B.

## 2.7 Post-development test data

This section will be completed later.

## 2.8 Issues with testing

Since `lintrans` is a graphical application about visualizing things, it will be mainly GUI focussed. Unfortunately, unit testing GUIs is a lot harder than unit testing library or API code. I don't think there's any way to easily and reliably unit test a graphical interface, so my unit tests will only cover the backend code for handling matrices. Testing the GUI will be entirely manual; mostly defining matrices, thinking about what I expect them to look like, and then making sure they look like that. I don't see a way around this limitation. I will make my backend unit tests very thorough, but testing the GUI can only be done manually.

### 3 Development

Please note, throughout this section, every code snippet will have two comments at the top. The first is the git commit hash that the snippet was taken from<sup>9</sup>. The second comment is the file name. The line numbers of the snippet reflect the line numbers of the file from where the snippet was taken. After a certain point, I introduced copyright comments at the top of every file. These are always omitted here.

#### 3.1 Matrices backend

##### 3.1.1 MatrixWrapper class

The first real part of development was creating the `MatrixWrapper` class. It needs a simple instance dictionary to be created in the constructor, and it needs a way of accessing the matrices. I decided to use Python's `__getitem__()` and `__setitem__()` special methods[15] to allow indexing into a `MatrixWrapper` object like `wrapper['M']`. This simplifies using the class.

```
# 29ec1fedbf307e3b7ca731c4a381535fec899b0b
# src/lintrans/matrices/wrapper.py

1  """A module containing a simple MatrixWrapper class to wrap matrices and context."""
2
3  import numpy as np
4
5  from lintrans.typing import MatrixType
6
7
8  class MatrixWrapper:
9      """A simple wrapper class to hold all possible matrices and allow access to them."""
10
11     def __init__(self):
12         """Initialise a MatrixWrapper object with a matrices dict."""
13         self._matrices: dict[str, MatrixType | None] = {
14             'A': None, 'B': None, 'C': None, 'D': None,
15             'E': None, 'F': None, 'G': None, 'H': None,
16             'I': np.eye(2), # I is always defined as the identity matrix
17             'J': None, 'K': None, 'L': None, 'M': None,
18             'N': None, 'O': None, 'P': None, 'Q': None,
19             'R': None, 'S': None, 'T': None, 'U': None,
20             'V': None, 'W': None, 'X': None, 'Y': None,
21             'Z': None
22         }
23
24     def __getitem__(self, name: str) -> MatrixType | None:
25         """Get the matrix with `name` from the dictionary.
26
27         Raises:
28             KeyError:
29                 If there is no matrix with the given name
30         """
31         return self._matrices[name]
32
33     def __setitem__(self, name: str, new_matrix: MatrixType) -> None:
34         """Set the value of matrix `name` with the new_matrix.
35
36         Raises:
37             ValueError:
38                 If `name` isn't a valid matrix name
39         """
40         name = name.upper()
41
42         if name == 'I' or name not in self._matrices:
43             raise NameError('Matrix name must be a capital letter and cannot be "I"')
```

<sup>9</sup>A history of all commits can be found in the GitHub repository[2]

```

44
45         self._matrices[name] = new_matrix

```

This code is very simple. The constructor (`__init__()`) creates a dictionary of matrices which all start out as having no value, except the identity matrix **I**. The `__getitem__()` and `__setitem__()` methods allow the user to easily get and set matrices just like a dictionary, and `__setitem__()` will raise an error if the name is invalid. This is a very early prototype, so it doesn't validate the type of whatever the user is trying to assign it to yet. This validation will come later.

I could make this class subclass `dict`, since it's basically just a dictionary at this point, but I want to extend it with much more functionality later, so I chose to handle the dictionary stuff myself.

I then had to write unit tests for this class, and I chose to do all my unit tests using a framework called `pytest`.

```

# 29ec1fedbf307e3b7ca731c4a381535fec899b0b
# tests/test_matrix_wrapper.py

1  """Test the MatrixWrapper class."""
2
3  import numpy as np
4  import pytest
5  from lintrans.matrices import MatrixWrapper
6
7  valid_matrix_names = 'ABCDEFGHJKLMNPOQRSTUVWXYZ'
8  test_matrix = np.array([[1, 2], [4, 3]])
9
10
11 @pytest.fixture
12 def wrapper() -> MatrixWrapper:
13     """Return a new MatrixWrapper object."""
14     return MatrixWrapper()
15
16
17 def test_get_matrix(wrapper) -> None:
18     """Test MatrixWrapper.__getitem__()."""
19     for name in valid_matrix_names:
20         assert wrapper[name] is None
21
22     assert (wrapper['I'] == np.array([[1, 0], [0, 1]])).all()
23
24
25 def test_get_name_error(wrapper) -> None:
26     """Test that MatrixWrapper.__getitem__() raises a KeyError if called with an invalid name."""
27     with pytest.raises(KeyError):
28         _ = wrapper['bad name']
29         _ = wrapper['123456']
30         _ = wrapper['Th15 Is an 1nV@l1D n@m3']
31         _ = wrapper['abc']
32
33
34 def test_set_matrix(wrapper) -> None:
35     """Test MatrixWrapper.__setitem__()."""
36     for name in valid_matrix_names:
37         wrapper[name] = test_matrix
38         assert (wrapper[name] == test_matrix).all()
39
40
41 def test_set_identity_error(wrapper) -> None:
42     """Test that MatrixWrapper.__setitem__() raises a NameError when trying to assign to I."""
43     with pytest.raises(NameError):
44         wrapper['I'] = test_matrix
45
46
47 def test_set_name_error(wrapper) -> None:
48     """Test that MatrixWrapper.__setitem__() raises a NameError when trying to assign to an invalid name."""
49     with pytest.raises(NameError):
50         wrapper['bad name'] = test_matrix
51         wrapper['123456'] = test_matrix

```

```

52     wrapper['Th15 Is an 1nV@l1D n@m3'] = test_matrix
53     wrapper['abc'] = test_matrix

```

These tests are quite simple and just ensure that the expected behaviour works the way it should, and that the correct errors are raised when they should be. It verifies that matrices can be assigned, that every valid name works, and that the identity matrix **I** cannot be assigned to.

The function decorated with `@pytest.fixture` allows functions to use a parameter called `wrapper` and `pytest` will automatically call this function and pass it as that parameter. It just saves on code repetition.

### 3.1.2 Rudimentary parsing and evaluating

This first thing I did here was improve the `__setitem__()` and `__getitem__()` methods to validate input and easily get transposes and simple rotation matrices.

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

60     def __setitem__(self, name: str, new_matrix: MatrixType) -> None:
61         """Set the value of matrix 'name' with the new_matrix.
62
63         :param str name: The name of the matrix to set the value of
64         :param MatrixType new_matrix: The value of the new matrix
65         :rtype: None
66
67         :raises NameError: If the name isn't a valid matrix name or is 'I'
68         """
69         if name not in self._matrices.keys():
70             raise NameError('Matrix name must be a single capital letter')
71
72         if name == 'I':
73             raise NameError('Matrix name cannot be "I"')
74
75         # All matrices must have float entries
76         a = float(new_matrix[0][0])
77         b = float(new_matrix[0][1])
78         c = float(new_matrix[1][0])
79         d = float(new_matrix[1][1])
80
81         self._matrices[name] = np.array([[a, b], [c, d]])

```

In this method, I'm now casting all the values to floats. This is very simple validation, since this cast will raise **ValueError** if it fails to cast the value to a float. I should've declared `:raises ValueError:` in the docstring, but this was an oversight at the time.

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

27     def __getitem__(self, name: str) -> Optional[MatrixType]:
28         """Get the matrix with the given name.
29
30         If it is a simple name, it will just be fetched from the dictionary.
31         If the name is followed with a 't', then we will return the transpose of the named matrix.
32         If the name is 'rot()', with a given angle in degrees, then we return a new rotation matrix with that angle.
33
34         :param str name: The name of the matrix to get
35         :returns: The value of the matrix (may be none)
36         :rtype: Optional[MatrixType]
37
38         :raises NameError: If there is no matrix with the given name
39         """
40         # Return a new rotation matrix

```

```

41     match = re.match(r'rot\\((\\d+)\\)', name)
42     if match is not None:
43         return create_rotation_matrix(float(match.group(1)))
44
45     # Return the transpose of this matrix
46     match = re.match(r'([A-Z])t', name)
47     if match is not None:
48         matrix = self[match.group(1)]
49
50         if matrix is not None:
51             return matrix.T
52         else:
53             return None
54
55     if name not in self._matrices:
56         raise NameError(f'Unrecognised matrix name "{name}"')
57
58     return self._matrices[name]

```

This `__getitem__()` method now allows for easily accessing transposes and rotation matrices by checking input with regular expressions. This makes getting matrices easier and thus makes evaluating full expressions simpler.

The `create_rotation_matrix()` method is also defined in this file and just uses the  $\begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}$  formula from before:

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

158 def create_rotation_matrix(angle: float) -> MatrixType:
159     """Create a matrix representing a rotation by the given number of degrees anticlockwise.
160
161     :param float angle: The number of degrees to rotate by
162     :returns MatrixType: The resultant rotation matrix
163     """
164     rad = np.deg2rad(angle)
165     return np.array([
166         [np.cos(rad), -1 * np.sin(rad)],
167         [np.sin(rad), np.cos(rad)]
168     ])

```

At this stage, I also implemented a simple parser and evaluator using regular expressions. It's not great and it's not very flexible, but it can evaluate simple expressions.

```

# f89fc9fd8d5917d07557fc50df3331123b55ad6b
# src/lintrans/matrices/wrapper.py

83 def parse_expression(self, expression: str) -> MatrixType:
84     """Parse a given expression and return the matrix for that expression.
85
86     Expressions are written with standard LaTeX notation for exponents. All whitespace is ignored.
87
88     Here is documentation on syntax:
89         A single matrix is written as 'A'.
90         Matrix A multiplied by matrix B is written as 'AB'
91         Matrix A plus matrix B is written as 'A+B'
92         Matrix A minus matrix B is written as 'A-B'
93         Matrix A squared is written as 'A^2'
94         Matrix A to the power of 10 is written as 'A^10' or 'A^{10}'
95         The inverse of matrix A is written as 'A^-1' or 'A^{-1}'
96         The transpose of matrix A is written as 'A^T' or 'At'
97
98     :param str expression: The expression to be parsed
99     :returns MatrixType: The matrix result of the expression
100
101     :raises ValueError: If the expression is invalid, such as an empty string
102     """

```

```

103     if expression == '':
104         raise ValueError('The expression cannot be an empty string')
105
106     match = re.search(r'^-+A-Z^{rot()}\d.}', expression)
107     if match is not None:
108         raise ValueError(f'Invalid character "{match.group(0)}"')
109
110     # Remove all whitespace in the expression
111     expression = re.sub(r'\s', '', expression)
112
113     # Wrap all exponents and transposition powers with {}
114     expression = re.sub(r'(<=^)(-?\d+|T)(?=[^]|$)', r'{\g<0>}', expression)
115
116     # Replace all subtractions with additions, multiplied by -1
117     expression = re.sub(r'(<=.)-(?=[A-Z])', '+-1', expression)
118
119     # Replace a possible leading minus sign with -1
120     expression = re.sub(r'^~-(?=[A-Z])', '-1', expression)
121
122     # Change all transposition exponents into lowercase
123     expression = expression.replace('^T', 't')
124
125     # Split the expression into groups to be multiplied, and then we add those groups at the end
126     # We also have to filter out the empty strings to reduce errors
127     multiplication_groups = [x for x in expression.split('+') if x != '']
128
129     # Start with the 0 matrix and add each group on
130     matrix_sum: MatrixType = np.array([[0., 0.], [0., 0.]])
131
132     for group in multiplication_groups:
133         # Generate a list of tuples, each representing a matrix
134         # These tuples are (the multiplier, the matrix (with optional
135         # 't' at the end to indicate a transpose), the exponent)
136         string_matrices: list[tuple[str, str, str]]
137
138         # The generate tuple is (multiplier, matrix, full exponent, stripped exponent)
139         # The full exponent contains ^{}, so we ignore it
140         # The multiplier and exponent might be '', so we have to set them to '1'
141         string_matrices = [(t[0] if t[0] != '' else '1', t[1], t[3] if t[3] != '' else '1')
142                             for t in re.findall(r'(-?\d*\.?*\d*)([A-Z]?|rot\(\d+\))(\^{{(-?\d+|T)}})?', group)]
143
144         # This list is a list of tuple, where each tuple is (a float multiplier,
145         # the matrix (gotten from the wrapper's __getitem__()), the integer power)
146         matrices: list[tuple[float, MatrixType, int]]
147         matrices = [(float(t[0]), self[t[1]], int(t[2])) for t in string_matrices]
148
149         # Process the matrices and make actual MatrixType objects
150         processed_matrices: list[MatrixType] = [t[0] * np.linalg.matrix_power(t[1], t[2]) for t in matrices]
151
152         # Add this matrix product to the sum total
153         matrix_sum += reduce(lambda m, n: m @ n, processed_matrices)
154
155     return matrix_sum

```

I think the comments in the code speak for themselves, but we basically split the expression up into groups to be added, and then for each group, we multiply every matrix in that group to get its value, and then add all these values together at the end.

This code is objectively bad. At the time of writing, it's now quite old, so I can say that. This code has no real error handling, and line 127 introduces the glaring error that 'A++B' is now a valid expression because we disregard empty strings. Not to mention the fact that the method is called `parse_expression()` but actually evaluates an expression. All these issues will be fixed in the future, but this was the first implementation of matrix evaluation, and it does the job decently well.

I then implemented several tests for this parsing.

```

# 60e0c713b244e097bab8ee0f71142b709fde1a8b
# tests/test_matrix_wrapper_parse_expression.py

```



```

1  """Test the MatrixWrapper parse_expression() method."""
2
3  import numpy as np
4  from numpy import linalg as la
5  import pytest
6  from lintrans.matrices import MatrixWrapper
7
8
9  @pytest.fixture
10 def wrapper() -> MatrixWrapper:
11     """Return a new MatrixWrapper object with some preset values."""
12     wrapper = MatrixWrapper()
13
14     root_two_over_two = np.sqrt(2) / 2
15
16     wrapper['A'] = np.array([[1, 2], [3, 4]])
17     wrapper['B'] = np.array([[6, 4], [12, 9]])
18     wrapper['C'] = np.array([[-1, -3], [4, -12]])
19     wrapper['D'] = np.array([[13.2, 9.4], [-3.4, -1.8]])
20     wrapper['E'] = np.array([
21         [root_two_over_two, -1 * root_two_over_two],
22         [root_two_over_two, root_two_over_two]
23     ])
24     wrapper['F'] = np.array([[-1, 0], [0, 1]])
25     wrapper['G'] = np.array([[np.pi, np.e], [1729, 743.631]])
26
27     return wrapper
28
29
30 def test_simple_matrix_addition(wrapper: MatrixWrapper) -> None:
31     """Test simple addition and subtraction of two matrices."""
32
33     # NOTE: We assert that all of these values are not None just to stop mypy complaining
34     # These values will never actually be None because they're set in the wrapper() fixture
35     # There's probably a better way do this, because this method is a bit of a bodge, but this works for now
36     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
37         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
38         wrapper['G'] is not None
39
40     assert (wrapper.parse_expression('A+B') == wrapper['A'] + wrapper['B']).all()
41     assert (wrapper.parse_expression('E+F') == wrapper['E'] + wrapper['F']).all()
42     assert (wrapper.parse_expression('G+D') == wrapper['G'] + wrapper['D']).all()
43     assert (wrapper.parse_expression('C+C') == wrapper['C'] + wrapper['C']).all()
44     assert (wrapper.parse_expression('D+A') == wrapper['D'] + wrapper['A']).all()
45     assert (wrapper.parse_expression('B+C') == wrapper['B'] + wrapper['C']).all()
46
47
48 def test_simple_two_matrix_multiplication(wrapper: MatrixWrapper) -> None:
49     """Test simple multiplication of two matrices."""
50     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
51         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
52         wrapper['G'] is not None
53
54     assert (wrapper.parse_expression('AB') == wrapper['A'] @ wrapper['B']).all()
55     assert (wrapper.parse_expression('BA') == wrapper['B'] @ wrapper['A']).all()
56     assert (wrapper.parse_expression('AC') == wrapper['A'] @ wrapper['C']).all()
57     assert (wrapper.parse_expression('DA') == wrapper['D'] @ wrapper['A']).all()
58     assert (wrapper.parse_expression('ED') == wrapper['E'] @ wrapper['D']).all()
59     assert (wrapper.parse_expression('FD') == wrapper['F'] @ wrapper['D']).all()
60     assert (wrapper.parse_expression('GA') == wrapper['G'] @ wrapper['A']).all()
61     assert (wrapper.parse_expression('CF') == wrapper['C'] @ wrapper['F']).all()
62     assert (wrapper.parse_expression('AG') == wrapper['A'] @ wrapper['G']).all()
63
64
65 def test_identity_multiplication(wrapper: MatrixWrapper) -> None:
66     """Test that multiplying by the identity doesn't change the value of a matrix."""
67     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
68         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
69         wrapper['G'] is not None
70
71     assert (wrapper.parse_expression('I') == wrapper['I']).all()
72     assert (wrapper.parse_expression('AI') == wrapper['A']).all()
73     assert (wrapper.parse_expression('IA') == wrapper['A']).all()

```

```

74     assert (wrapper.parse_expression('GI') == wrapper['G']).all()
75     assert (wrapper.parse_expression('IG') == wrapper['G']).all()
76
77     assert (wrapper.parse_expression('EID') == wrapper['E'] @ wrapper['D']).all()
78     assert (wrapper.parse_expression('IED') == wrapper['E'] @ wrapper['D']).all()
79     assert (wrapper.parse_expression('EDI') == wrapper['E'] @ wrapper['D']).all()
80     assert (wrapper.parse_expression('IIDI') == wrapper['E'] @ wrapper['D']).all()
81     assert (wrapper.parse_expression('EI^3D') == wrapper['E'] @ wrapper['D']).all()
82
83
84 def test_simple_three_matrix_multiplication(wrapper: MatrixWrapper) -> None:
85     """Test simple multiplication of two matrices."""
86     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
87         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
88         wrapper['G'] is not None
89
90     assert (wrapper.parse_expression('ABC') == wrapper['A'] @ wrapper['B'] @ wrapper['C']).all()
91     assert (wrapper.parse_expression('ACB') == wrapper['A'] @ wrapper['C'] @ wrapper['B']).all()
92     assert (wrapper.parse_expression('BAC') == wrapper['B'] @ wrapper['A'] @ wrapper['C']).all()
93     assert (wrapper.parse_expression('EFG') == wrapper['E'] @ wrapper['F'] @ wrapper['G']).all()
94     assert (wrapper.parse_expression('DAC') == wrapper['D'] @ wrapper['A'] @ wrapper['C']).all()
95     assert (wrapper.parse_expression('GAE') == wrapper['G'] @ wrapper['A'] @ wrapper['E']).all()
96     assert (wrapper.parse_expression('FAG') == wrapper['F'] @ wrapper['A'] @ wrapper['G']).all()
97     assert (wrapper.parse_expression('GAF') == wrapper['G'] @ wrapper['A'] @ wrapper['F']).all()
98
99
100 def test_matrix_inverses(wrapper: MatrixWrapper) -> None:
101     """Test the inverses of single matrices."""
102     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
103         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
104         wrapper['G'] is not None
105
106     assert (wrapper.parse_expression('A^{-1}') == la.inv(wrapper['A'])).all()
107     assert (wrapper.parse_expression('B^{-1}') == la.inv(wrapper['B'])).all()
108     assert (wrapper.parse_expression('C^{-1}') == la.inv(wrapper['C'])).all()
109     assert (wrapper.parse_expression('D^{-1}') == la.inv(wrapper['D'])).all()
110     assert (wrapper.parse_expression('E^{-1}') == la.inv(wrapper['E'])).all()
111     assert (wrapper.parse_expression('F^{-1}') == la.inv(wrapper['F'])).all()
112     assert (wrapper.parse_expression('G^{-1}') == la.inv(wrapper['G'])).all()
113
114     assert (wrapper.parse_expression('A^{-1}') == la.inv(wrapper['A'])).all()
115     assert (wrapper.parse_expression('B^{-1}') == la.inv(wrapper['B'])).all()
116     assert (wrapper.parse_expression('C^{-1}') == la.inv(wrapper['C'])).all()
117     assert (wrapper.parse_expression('D^{-1}') == la.inv(wrapper['D'])).all()
118     assert (wrapper.parse_expression('E^{-1}') == la.inv(wrapper['E'])).all()
119     assert (wrapper.parse_expression('F^{-1}') == la.inv(wrapper['F'])).all()
120     assert (wrapper.parse_expression('G^{-1}') == la.inv(wrapper['G'])).all()
121
122
123 def test_matrix_powers(wrapper: MatrixWrapper) -> None:
124     """Test that matrices can be raised to integer powers."""
125     assert wrapper['A'] is not None and wrapper['B'] is not None and wrapper['C'] is not None and \
126         wrapper['D'] is not None and wrapper['E'] is not None and wrapper['F'] is not None and \
127         wrapper['G'] is not None
128
129     assert (wrapper.parse_expression('A^2') == la.matrix_power(wrapper['A'], 2)).all()
130     assert (wrapper.parse_expression('B^4') == la.matrix_power(wrapper['B'], 4)).all()
131     assert (wrapper.parse_expression('C^{12}') == la.matrix_power(wrapper['C'], 12)).all()
132     assert (wrapper.parse_expression('D^{12}') == la.matrix_power(wrapper['D'], 12)).all()
133     assert (wrapper.parse_expression('E^8') == la.matrix_power(wrapper['E'], 8)).all()
134     assert (wrapper.parse_expression('F^{-6}') == la.matrix_power(wrapper['F'], -6)).all()
135     assert (wrapper.parse_expression('G^{-2}') == la.matrix_power(wrapper['G'], -2)).all()

```

These test lots of simple expressions, but don't test any more complicated expressions, nor do they test any validation, mostly because validation doesn't really exist at this point. 'A++B' is still a valid expression and is equivalent to 'A+B'.

### 3.1.3 Simple matrix expression validation

My next major step was to implement proper parsing, but I procrastinated for a while and first implemented proper validation.

```
# 39b918651f60bc72bc19d2018075b24a6fc3af17
# src/lintrans/_parse/matrices.py

9 def compile_valid_expression_pattern() -> Pattern[str]:
10     """Compile the single regular expression that will match a valid matrix expression."""
11     digit_no_zero = '[123456789]'
12     digits = '\\d+'
13     integer_no_zero = '-?' + digit_no_zero + '(' + digits + ')?'
14     real_number = f'({integer_no_zero}(\\.\\{digits}\\})?|-?0?\\.\\{digits}\\})'
15
16     index_content = f'({integer_no_zero}|T)'
17     index = f'\\^\\{\\{index_content\\}\\}\\^\\{index_content\\}|t)'
18     matrix_identifier = f'([A-Z]|rot\\(\\{real_number\\}\\))'
19     matrix = '(' + real_number + '?' + matrix_identifier + index + ')?'
20     expression = f'{matrix}+((\\+|-){matrix}+)*'
21
22     return re.compile(expression)
23
24
25 # This is an expensive pattern to compile, so we compile it when this module is initialized
26 valid_expression_pattern = compile_valid_expression_pattern()
27
28
29 def validate_matrix_expression(expression: str) -> bool:
30     """Validate the given matrix expression.
31
32     This function simply checks the expression against a BNF schema. It is not
33     aware of which matrices are actually defined in a wrapper. For an aware
34     version of this function, use the MatrixWrapper().is_valid_expression() method.
35
36     Here is the schema for a valid expression given in a version of BNF:
37
38         expression      ::= matrices { ( "+" | "-" ) matrices };
39         matrices        ::= matrix { matrix };
40         matrix          ::= [ real_number ] matrix_identifier [ index ];
41         matrix_identifier ::= "A" .. "Z" | "rot(" real_number ")";
42         index           ::= "^{" index_content "}" | "^" index_content | "t";
43         index_content   ::= integer_not_zero | "T";
44
45         digit_no_zero   ::= "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9";
46         digit           ::= "0" | digit_no_zero;
47         digits          ::= digit | digits digit;
48         integer_not_zero ::= [ "-" ] digit_no_zero [ digits ];
49         real_number     ::= ( integer_not_zero [ "." digits ] | [ "-" ] [ "0" ] "." digits );
50
51     :param str expression: The expression to be validated
52     :returns bool: Whether the expression is valid according to the schema
53     """
54     match = valid_expression_pattern.match(expression)
55     return expression == match.group(0) if match is not None else False
```

Here, I'm using a BNF schema to programmatically generate a regular expression. I use a function to generate this pattern and assign it to a variable when the module is initialized. This is because the pattern compilation is expensive and it's more efficient to compile the pattern once and then just use it in the `validate_matrix_expression()` function.

I also created a method `is_valid_expression()` in `MatrixWrapper`, which just validates a given expression. It uses the aforementioned `validate_matrix_expression()` and also checks that every matrix referenced in the expression is defined in the wrapper.

```
# 39b918651f60bc72bc19d2018075b24a6fc3af17
# src/lintrans/matrices/wrapper.py
```

```

99     def is_valid_expression(self, expression: str) -> bool:
100         """Check if the given expression is valid, using the context of the wrapper.
101
102         This method calls _parse.validate_matrix_expression(), but also ensures
103         that all the matrices in the expression are defined in the wrapper.
104
105         :param str expression: The expression to validate
106         :returns bool: Whether the expression is valid according the schema
107         """
108         # Get rid of the transposes to check all capital letters
109         expression = re.sub(r'\^T', 't', expression)
110         expression = re.sub(r'\^{T}', 't', expression)
111
112         # Make sure all the referenced matrices are defined
113         for matrix in {x for x in expression if re.match('[A-Z]', x)}:
114             if self[matrix] is None:
115                 return False
116
117         return _parse.validate_matrix_expression(expression)

```

I then implemented some simple tests to make sure the function works with valid and invalid expressions.

```

# a0fb029f7da995803c24ee36e7e8078e5621f676
# tests/_parse/test_parse_and_validate_expression.py

1 """Test the _parse.matrices module validation and parsing."""
2
3 import pytest
4 from lintrans._parse import validate_matrix_expression
5
6 valid_inputs: list[str] = [
7     'A', 'AB', '3A', '1.2A', '-3.4A', 'A^2', 'A^-1', 'A^{-1}',
8     'A^12', 'A^T', 'A^{5}', 'A^{T}', '4.3A^7', '9.2A^{18}',
9
10     'rot(45)', 'rot(12.5)', '3rot(90)',
11     'rot(135)^3', 'rot(51)^T', 'rot(-34)^-1',
12
13     'A+B', 'A+2B', '4.3A+9B', 'A^2+B^T', '3A^7+0.8B^{16}',
14     'A-B', '3A-4B', '3.2A^3-16.79B^T', '4.752A^{17}-3.32B^{36}',
15     'A--1B', '-A', '--1A'
16
17     '3A4B', 'A^TB', 'A^{T}B', '4A^6B^3',
18     '2A^{3}4B^5', '4rot(90)^3', 'rot(45)rot(13)',
19     'Arot(90)', 'AB^2', 'A^2B^2', '8.36A^T3.4B^12',
20
21     '3.5A^{4}5.6rot(19.2)^T-B^{-1}4.1C^5',
22 ]
23
24 invalid_inputs: list[str] = [
25     '', 'rot()', 'A^', 'A^1.2', 'A^{3.4}', '1,2A', 'ro(12)', '5', '12^2',
26     '^T', '^12', 'A^{13}', 'A^3', 'A^A', '^2', 'A--B', '--A'
27
28     'This is 100% a valid matrix expression, I swear'
29 ]
30
31
32 @pytest.mark.parametrize('inputs,output', [(valid_inputs, True), (invalid_inputs, False)])
33 def test_validate_matrix_expression(inputs: list[str], output: bool) -> None:
34     """Test the validate_matrix_expression() function."""
35     for inp in inputs:
36         assert validate_matrix_expression(inp) == output

```

Here, we test some valid data, some definitely invalid data, and some edge cases. At this stage, 'A--1B' was considered a valid expression. This was a quirk of the validator at the time, but I fixed it later. This should obviously be an invalid expression, especially since 'A--B' is considered invalid, but 'A--1B' is valid.

The `@pytest.mark.parametrize` decorator on line 32 means that `pytest` will run one test for valid inputs, and then another test for invalid inputs, and these will count as different tests. This makes it easier to see which tests failed and then debug the app.

### 3.1.4 Parsing matrix expressions

Parsing is quite an interesting problem and something I didn't feel able to tackle head-on, so I wrote the unit tests first. I had a basic idea of what I wanted the parser to return, but no real idea of how to implement that. My unit tests looked like this:

```
# e9f7a81892278fe70684562052f330fb3a02bf9b
# tests/_parse/test_parse_and_validate_expression.py

40 expressions_and_parsed_expressions: list[tuple[str, MatrixParseList]] = [
41     # Simple expressions
42     ('A', [[(' ', 'A', ' ')]]),
43     ('A^2', [[(' ', 'A', '2')]]),
44     ('A^{2}', [[(' ', 'A', '2')]]),
45     ('3A', [[('3', 'A', ' ')]]),
46     ('1.4A^3', [[('1.4', 'A', '3')]]),
47
48     # Multiplications
49     ('4A^{3} 6B^2', [[('4', 'A', '3'), ('6', 'B', '2')]]),
50     ('4.2A^{T} 6.1B^{-1}', [[('4.2', 'A', 'T'), ('6.1', 'B', '-1')]]),
51     ('-1.2A^2 rot(45)^2', [[('1.2', 'A', '2'), (' ', 'rot(45)', '2')]]),
52     ('3.2A^T 4.5B^{5} 9.6rot(121.3)', [[('3.2', 'A', 'T'), ('4.5', 'B', '5'), ('9.6', 'rot(121.3)', ' ')]]),
53     ('-1.18A^{-2} 0.1B^{2} 9rot(34.6)^{-1}', [[('1.18', 'A', '-2'), ('0.1', 'B', '2'), ('9', 'rot(34.6)', '-1')]]),
54
55     # Additions
56     ('A + B', [[(' ', 'A', ' '), (' ', 'B', ' ')]]),
57     ('A + B - C', [[(' ', 'A', ' '), (' ', 'B', ' '), ('-1', 'C', ' ')]]),
58     ('2A^3 + 8B^T - 3C^{-1}', [[('2', 'A', '3'), ('8', 'B', 'T'), ('-3', 'C', '-1')]]),
59
60     # Additions with multiplication
61     ('2.14A^{3} 4.5rot(14.5)^{-1} + 8B^T - 3C^{-1}', [[('2.14', 'A', '3'), ('4.5', 'rot(14.5)', '-1'),
62                                                         [ ('8', 'B', 'T'), ('-3', 'C', '-1') ] ]),
63     ('2.14A^{3} 4.5rot(14.5)^{-1} + 8.5B^T 5.97C^4 - 3.14D^{-1} 6.7E^T',
64      [[('2.14', 'A', '3'), ('4.5', 'rot(14.5)', '-1'), ('8.5', 'B', 'T'), ('5.97', 'C', '4'),
65        [ ('-3.14', 'D', '-1'), ('6.7', 'E', 'T') ] ]),
66 ]
67
68
69 @pytest.mark.skip(reason='parse_matrix_expression() not implemented')
70 def test_parse_matrix_expression() -> None:
71     """Test the parse_matrix_expression() function."""
72     for expression, parsed_expression in expressions_and_parsed_expressions:
73         # Test it with and without whitespace
74         assert parse_matrix_expression(expression) == parsed_expression
75         assert parse_matrix_expression(expression.replace(' ', '')) == parsed_expression
```

I just had example inputs and what I expected as output. I also wanted the parser to ignore whitespace. The decorator on line 69 just skips the test because the parser wasn't implemented yet.

When implementing the parser, I first had to tighten up validation to remove anomalies like `'A--1B'` being valid. I did this by factoring out the optional minus signs from being part of a number, to being optionally in front of a number. This eliminated this kind of repetition and made `'A--1B'` invalid, as it should be.

```
# fd80d8d3b0e975e92dcc7c10f1f0f1276879f408
# src/lintrans/_parse/matrices.py

32 def compile_valid_expression_pattern() -> Pattern[str]:
33     """Compile the single regular expression that will match a valid matrix expression."""
34     digit_no_zero = '[123456789]'
35     digits = '\\d+'

```

```

36 integer_no_zero = digit_no_zero + '(' + digits + ')?'
37 real_number = f'({integer_no_zero}(\.{digits})?|0?\.{digits})'
38
39 index_content = f'(-?{integer_no_zero}|T)'
40 index = f'(\^\^\{{index_content}\}\^\^\{{index_content}}|t)'
41 matrix_identifier = f'([A-Z]|rot\((-?{real_number}\)\)'
42 matrix = '(' + real_number + '?' + matrix_identifier + index + '?'
43 expression = f'-?{matrix}+(\{\\+|-\\){matrix})*'
44
45 return re.compile(expression)

```

The code can be a bit hard to read with all the RegEx stuff, but the BNF illustrates these changes nicely.

Compare the old version:

```

# 39b918651f60bc72bc19d2018075b24a6fc3af17
# src/lintrans/_parse/matrices.py

38 expression      ::= matrices { ( "+" | "-" ) matrices };
39 matrices        ::= matrix { matrix };
40 matrix           ::= [ real_number ] matrix_identifier [ index ];
41 matrix_identifier ::= "A" .. "Z" | "rot(" real_number ")";
42 index            ::= "^{" index_content "}" | "^" index_content | "t";
43 index_content    ::= integer_not_zero | "T";
44
45 digit_no_zero    ::= "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9";
46 digit            ::= "0" | digit_no_zero;
47 digits           ::= digit | digits digit;
48 integer_not_zero ::= [ "-" ] digit_no_zero [ digits ];
49 real_number      ::= ( integer_not_zero [ "." digits ] | [ "-" ] [ "0" ] "." digits );

```

to the new version:

```

# fd80d8d3b0e975e92dcc7c10f1f0f1276879f408
# src/lintrans/_parse/matrices.py

61 expression      ::= [ "-" ] matrices { ( "+" | "-" ) matrices };
62 matrices        ::= matrix { matrix };
63 matrix           ::= [ real_number ] matrix_identifier [ index ];
64 matrix_identifier ::= "A" .. "Z" | "rot(" [ "-" ] real_number ")";
65 index            ::= "^{" index_content "}" | "^" index_content | "t";
66 index_content    ::= [ "-" ] integer_not_zero | "T";
67
68 digit_no_zero    ::= "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9";
69 digit            ::= "0" | digit_no_zero;
70 digits           ::= digit | digits digit;
71 integer_not_zero ::= digit_no_zero [ digits ];
72 real_number      ::= ( integer_not_zero [ "." digits ] | [ "0" ] "." digits );

```

Then once I'd fixed the validation, I could implement the parser itself.

```

# fd80d8d3b0e975e92dcc7c10f1f0f1276879f408
# src/lintrans/_parse/matrices.py

86 def parse_matrix_expression(expression: str) -> MatrixParseList:
87     """Parse the matrix expression and return a list of results.
88
89     The return value is a list of results. This results list contains lists of tuples.
90     The top list is the expressions that should be added together, and each sublist
91     is expressions that should be multiplied together. These expressions to be
92     multiplied are tuples, where each tuple is (multiplier, matrix identifier, index).
93     The multiplier can be any real number, the matrix identifier is either a named
94     matrix or a new rotation matrix declared with 'rot()', and the index is an
95     integer or 'T' for transpose.
96

```

```

97     :param str expression: The expression to be parsed
98     :returns MatrixParseTuple: A list of results
99     """
100    # Remove all whitespace
101    expression = re.sub(r'\s', '', expression)
102
103    # Check if it's valid
104    if not validate_matrix_expression(expression):
105        raise MatrixParseError('Invalid expression')
106
107    # Wrap all exponents and transposition powers with {}
108    expression = re.sub(r'(?<=\^)(-?\d+|T)(?=[^}]|$)', r'{\g<0>}', expression)
109
110    # Remove any standalone minuses
111    expression = re.sub(r'-(?=[A-Z])', '-1', expression)
112
113    # Replace subtractions with additions
114    expression = re.sub(r'-(?=\d+\.?\d*([A-Z]|rot))', '+-', expression)
115
116    # Get rid of a potential leading + introduced by the last step
117    expression = re.sub(r'^+', '', expression)
118
119    return [
120        [
121            # The tuple returned by re.findall is (multiplier, matrix identifier, full index, stripped index),
122            # so we have to remove the full index, which contains the {}
123            (t[0], t[1], t[3])
124            for t in re.findall(r'(-?\d+\.?\d*)?([A-Z]|rot\(-?\d+\.?\d*\))(\^{(-?\d+|T)})?', group)
125        ]
126        # We just split the expression by '+' to have separate groups
127        for group in expression.split('+')
128    ]

```

It works similarly to the old `MatrixWrapper.parse_expression()` method in §3.1.2 but with a powerful list comprehension at the end. It splits the expression up into groups and then uses some RegEx magic to find all the matrices in these groups as a tuple.

This method passes all the unit tests, as expected.

My next step was then to rewrite the evaluation to use this new parser, like so (method name and docstring removed):

```

# a453774bcd824676461f9b9b441d7b94969ea55
# src/lintrans/matrices/wrapper.py

168    if not self.is_valid_expression(expression):
169        raise ValueError('The expression is invalid')
170
171    parsed_result = _parse.parse_matrix_expression(expression)
172    final_groups: list[list[MatrixType]] = []
173
174    for group in parsed_result:
175        f_group: list[MatrixType] = []
176
177        for matrix in group:
178            if matrix[2] == 'T':
179                m = self[matrix[1]]
180                assert m is not None
181                matrix_value = m.T
182            else:
183                matrix_value = np.linalg.matrix_power(self[matrix[1]],
184                1 if (index := matrix[2]) == '' else int(index))
185
186            matrix_value *= 1 if (multiplier := matrix[0]) == '' else float(multiplier)
187            f_group.append(matrix_value)
188
189        final_groups.append(f_group)
190
191    return reduce(add, [reduce(matmul, group) for group in final_groups])

```

Here, we go through the list of tuples and evaluate the matrix represented by each tuple, putting this together in a list as we go. Then at the end, we simply reduce the sublists and then reduce these new matrices using a list comprehension in the `reduce()` call using `add` and `matmul` from the `operator` library. It's written in a functional programming style, and it passes all the previous tests.

## 3.2 Initial GUI

### 3.2.1 First basic GUI

The discrepancy in all the GUI code between `snake_case` and `camelCase` is because Qt5 was originally a C++ framework that was adapted into PyQt5 for Python. All the Qt API is in `camelCase`, but my Python code is in `snake_case`.

```
# 93ce763f7b993439fc0da89fad39456d8cc4b52c
# src/lintrans/gui/main_window.py

1  """The module to provide the main window as a QMainWindow object."""
2
3  import sys
4
5  from PyQt5 import QtCore, QtGui, QtWidgets
6  from PyQt5.QtWidgets import QApplication, QHBoxLayout, QMainWindow, QVBoxLayout
7
8  from lintrans.matrices import MatrixWrapper
9
10
11 class LintransMainWindow(QMainWindow):
12     """The class for the main window in the lintrans GUI."""
13
14     def __init__(self):
15         """Create the main window object, creating every widget in it."""
16         super().__init__()
17
18         self.matrix_wrapper = MatrixWrapper()
19
20         self.setWindowTitle('Linear Transformations')
21         self.setMinimumWidth(750)
22
23         # === Create widgets
24
25         # Left layout: the plot and input box
26
27         # NOTE: This QGraphicsView is only temporary
28         self.plot = QtWidgets.QGraphicsView(self)
29
30         self.text_input_expression = QtWidgets.QLineEdit(self)
31         self.text_input_expression.setPlaceholderText('Input matrix expression...')
32         self.text_input_expression.textChanged.connect(self.update_render_buttons)
33
34         # Right layout: all the buttons
35
36         # Misc buttons
37
38         self.button_create_polygon = QtWidgets.QPushButton(self)
39         self.button_create_polygon.setText('Create polygon')
40         # TODO: Implement create_polygon()
41         # self.button_create_polygon.clicked.connect(self.create_polygon)
42         self.button_create_polygon.setToolTip('Define a new polygon to view the transformation of')
43
44         self.button_change_display_settings = QtWidgets.QPushButton(self)
45         self.button_change_display_settings.setText('Change\ndisplay settings')
46         # TODO: Implement change_display_settings()
47         # self.button_change_display_settings.clicked.connect(self.change_display_settings)
48         self.button_change_display_settings.setToolTip('Change which things are rendered on the plot')
49
50         # Define new matrix buttons
51
```



```

52     self.label_define_new_matrix = QtWidgets.QLabel(self)
53     self.label_define_new_matrix.setText('Define a new matrix')
54     self.label_define_new_matrix.setAlignment(QtCore.Qt.AlignCenter)
55
56     # TODO: Implement defining a new matrix visually, numerically, as a rotation, and as an expression
57
58     self.button_define_visually = QtWidgets.QPushButton(self)
59     self.button_define_visually.setText('Visually')
60     self.button_define_visually.setToolTip('Drag the basis vectors')
61
62     self.button_define_numerically = QtWidgets.QPushButton(self)
63     self.button_define_numerically.setText('Numerically')
64     self.button_define_numerically.setToolTip('Define a matrix just with numbers')
65
66     self.button_define_as_rotation = QtWidgets.QPushButton(self)
67     self.button_define_as_rotation.setText('As a rotation')
68     self.button_define_as_rotation.setToolTip('Define an angle to rotate by')
69
70     self.button_define_as_expression = QtWidgets.QPushButton(self)
71     self.button_define_as_expression.setText('As an expression')
72     self.button_define_as_expression.setToolTip('Define a matrix in terms of other matrices')
73
74     # Render buttons
75
76     self.button_render = QtWidgets.QPushButton(self)
77     self.button_render.setText('Render')
78     self.button_render.setEnabled(False)
79     self.button_render.clicked.connect(self.render_expression)
80     self.button_render.setToolTip('Render the expression<br><b>(Ctrl + Enter)</b>')
81
82     self.button_render_shortcut = QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Return'), self)
83     self.button_render_shortcut.activated.connect(self.button_render.click)
84
85     self.button_animate = QtWidgets.QPushButton(self)
86     self.button_animate.setText('Animate')
87     self.button_animate.setEnabled(False)
88     self.button_animate.clicked.connect(self.animate_expression)
89     self.button_animate.setToolTip('Animate the expression<br><b>(Ctrl + Shift + Enter)</b>')
90
91     self.button_animate_shortcut = QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Shift+Return'), self)
92     self.button_animate_shortcut.activated.connect(self.button_animate.click)
93
94     # === Arrange widgets
95
96     self.setContentsMargins(10, 10, 10, 10)
97
98     self.vlay_left = QVBoxLayout()
99     self.vlay_left.addWidget(self.plot)
100    self.vlay_left.addWidget(self.text_input_expression)
101
102    self.vlay_misc_buttons = QVBoxLayout()
103    self.vlay_misc_buttons.setSpacing(20)
104    self.vlay_misc_buttons.addWidget(self.button_create_polygon)
105    self.vlay_misc_buttons.addWidget(self.button_change_display_settings)
106
107    self.vlay_define_new_matrix = QVBoxLayout()
108    self.vlay_define_new_matrix.setSpacing(20)
109    self.vlay_define_new_matrix.addWidget(self.label_define_new_matrix)
110    self.vlay_define_new_matrix.addWidget(self.button_define_visually)
111    self.vlay_define_new_matrix.addWidget(self.button_define_numerically)
112    self.vlay_define_new_matrix.addWidget(self.button_define_as_rotation)
113    self.vlay_define_new_matrix.addWidget(self.button_define_as_expression)
114
115    self.vlay_render = QVBoxLayout()
116    self.vlay_render.setSpacing(20)
117    self.vlay_render.addWidget(self.button_animate)
118    self.vlay_render.addWidget(self.button_render)
119
120    self.vlay_right = QVBoxLayout()
121    self.vlay_right.setSpacing(50)
122    self.vlay_right.addLayout(self.vlay_misc_buttons)
123    self.vlay_right.addLayout(self.vlay_define_new_matrix)
124    self.vlay_right.addLayout(self.vlay_render)

```

```

125
126     self.hlay_all = QHBoxLayout()
127     self.hlay_all.setSpacing(15)
128     self.hlay_all.addLayout(self.vlay_left)
129     self.hlay_all.addLayout(self.vlay_right)
130
131     self.central_widget = QtWidgets.QWidget()
132     self.central_widget.setLayout(self.hlay_all)
133     self.setCentralWidget(self.central_widget)
134
135     def update_render_buttons(self) -> None:
136         """Enable or disable the render and animate buttons according to the validity of the matrix expression."""
137         valid = self.matrix_wrapper.is_valid_expression(self.text_input_expression.text())
138         self.button_render.setEnabled(valid)
139         self.button_animate.setEnabled(valid)
140
141     def render_expression(self) -> None:
142         """Render the expression in the input box, and then clear the box."""
143         # TODO: Render the expression
144         self.text_input_expression.setText('')
145
146     def animate_expression(self) -> None:
147         """Animate the expression in the input box, and then clear the box."""
148         # TODO: Animate the expression
149         self.text_input_expression.setText('')
150
151
152     def main() -> None:
153         """Run the GUI."""
154         app = QApplication(sys.argv)
155         window = LintransMainWindow()
156         window.show()
157         sys.exit(app.exec_())
158
159
160 if __name__ == '__main__':
161     main()

```




Figure 3.1: The first version of the GUI

A lot of the methods here don't have implementations yet, but they will. This version is just a very early prototype to get a rough draft of the GUI.

I create the widgets and layouts in the constructor as well as configuring all of them. The most important non-constructor method is `update_render_buttons()`. It gets called whenever the text in `text_input_expression` is changed. This happens because we connect it to the `textChanged` signal on line 32.

The big white box here will eventually be replaced with an actual viewport. This is just a prototype.

### 3.2.2 Numerical definition dialog

My next major addition was a dialog that would allow the user to define a matrix numerically.

```

# cedbd3ed126a1183f197c27adf6dabb4e5d301c7
# src/lintrans/gui/dialogs/define_new_matrix.py

1 """The module to provide dialogs for defining new matrices."""
2
3 from numpy import array
4 from PyQt5 import QtGui, QtWidgets
5 from PyQt5.QtWidgets import QDialog, QGridLayout, QHBoxLayout, QVBoxLayout

```

```
6
7 from lintrans.matrices import MatrixWrapper
8
9 ALPHABET_NO_I = 'ABCDEFGHJKLMNPOQRSTUVWXYZ'
10
11
12 def is_float(string: str) -> bool:
13     """Check if a string is a float."""
14     try:
15         float(string)
16         return True
17     except ValueError:
18         return False
19
20
21 class DefineNumericallyDialog(QDialog):
22     """The dialog class that allows the user to define a new matrix numerically."""
23
24     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
25         """Create the dialog, but don't run it yet.
26
27         :param matrix_wrapper: The MatrixWrapper that this dialog will mutate
28         :type matrix_wrapper: MatrixWrapper
29         """
30         super().__init__(*args, **kwargs)
31
32         self.matrix_wrapper = matrix_wrapper
33         self.setWindowTitle('Define a matrix')
34
35         # === Create the widgets
36
37         self.button_confirm = QtWidgets.QPushButton(self)
38         self.button_confirm.setText('Confirm')
39         self.button_confirm.setEnabled(False)
40         self.button_confirm.clicked.connect(self.confirm_matrix)
41         self.button_confirm.setToolTip('Confirm this as the new matrix<br><b>(Ctrl + Enter)</b>')
42
43         QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Return'), self).activated.connect(self.button_confirm.click)
44
45         self.button_cancel = QtWidgets.QPushButton(self)
46         self.button_cancel.setText('Cancel')
47         self.button_cancel.clicked.connect(self.close)
48         self.button_cancel.setToolTip('Cancel this definition<br><b>(Ctrl + Q)</b>')
49
50         QtWidgets.QShortcut(QtGui.QKeySequence('Ctrl+Q'), self).activated.connect(self.button_cancel.click)
51
52         self.element_tl = QtWidgets.QLineEdit(self)
53         self.element_tl.textChanged.connect(self.update_confirm_button)
54
55         self.element_tr = QtWidgets.QLineEdit(self)
56         self.element_tr.textChanged.connect(self.update_confirm_button)
57
58         self.element_bl = QtWidgets.QLineEdit(self)
59         self.element_bl.textChanged.connect(self.update_confirm_button)
60
61         self.element_br = QtWidgets.QLineEdit(self)
62         self.element_br.textChanged.connect(self.update_confirm_button)
63
64         self.matrix_elements = (self.element_tl, self.element_tr, self.element_bl, self.element_br)
65
66         self.letter_combo_box = QtWidgets.QComboBox(self)
67
68         # Everything except I, because that's the identity
69         for letter in ALPHABET_NO_I:
70             self.letter_combo_box.addItem(letter)
71
72         self.letter_combo_box.activated.connect(self.load_matrix)
73
74         # === Arrange the widgets
75
76         self.setContentsMargins(10, 10, 10, 10)
77
78         self.grid_matrix = QGridLayout()
```

```

79         self.grid_matrix.setSpacing(20)
80         self.grid_matrix.addWidget(self.element_tl, 0, 0)
81         self.grid_matrix.addWidget(self.element_tr, 0, 1)
82         self.grid_matrix.addWidget(self.element_bl, 1, 0)
83         self.grid_matrix.addWidget(self.element_br, 1, 1)
84
85         self.hlay_buttons = QHBoxLayout()
86         self.hlay_buttons.setSpacing(20)
87         self.hlay_buttons.addWidget(self.button_cancel)
88         self.hlay_buttons.addWidget(self.button_confirm)
89
90         self.vlay_right = QVBoxLayout()
91         self.vlay_right.setSpacing(20)
92         self.vlay_right.addLayout(self.grid_matrix)
93         self.vlay_right.addLayout(self.hlay_buttons)
94
95         self.hlay_all = QHBoxLayout()
96         self.hlay_all.setSpacing(20)
97         self.hlay_all.addWidget(self.letter_combo_box)
98         self.hlay_all.addLayout(self.vlay_right)
99
100        self.setLayout(self.hlay_all)
101
102        # Finally, we load the default matrix A into the boxes
103        self.load_matrix(0)
104
105    def update_confirm_button(self) -> None:
106        """Enable the confirm button if there are numbers in every box."""
107        for elem in self.matrix_elements:
108            if elem.text() == '' or not is_float(elem.text()):
109                # If they're not all numbers, then we can't confirm it
110                self.button_confirm.setEnabled(False)
111                return
112
113        # If we didn't find anything invalid
114        self.button_confirm.setEnabled(True)
115
116    def load_matrix(self, index: int) -> None:
117        """If the selected matrix is defined, load it into the boxes."""
118        matrix = self.matrix_wrapper[ALPHABET_NO_I[index]]
119
120        if matrix is None:
121            for elem in self.matrix_elements:
122                elem.setText('')
123
124        else:
125            self.element_tl.setText(str(matrix[0][0]))
126            self.element_tr.setText(str(matrix[0][1]))
127            self.element_bl.setText(str(matrix[1][0]))
128            self.element_br.setText(str(matrix[1][1]))
129
130        self.update_confirm_button()
131
132    def confirm_matrix(self) -> None:
133        """Confirm the inputted matrix and assign it to the name."""
134        letter = self.letter_combo_box.currentText()
135        matrix = array([
136            [float(self.element_tl.text()), float(self.element_tr.text())],
137            [float(self.element_bl.text()), float(self.element_br.text())]
138        ])
139
140        self.matrix_wrapper[letter] = matrix
141        self.close()

```




Figure 3.2: The first version of the numerical definition dialog

When I add more definition dialogs, I will factor out a superclass, but this is just a prototype to make sure it all works as intended.

Hopefully the methods are relatively self explanatory, but they're just utility methods to update the GUI when things are changed. We connect the `QLineEdit` widgets to the `update_confirm_button()` slot to make sure the confirm button is always up to date.

The `confirm_matrix()` method just updates the instance's matrix wrapper with the new matrix. We pass a reference to the `LintransMainWindow` instance's matrix wrapper when we open the dialog, so we're just updating the referenced object directly.

In the `LintransMainWindow` class, we're just connecting a lambda slot to the button so that it opens the dialog, as seen here:

```
# cedbd3ed126a1183f197c27adf6dabb4e5d301c7
# src/lintrans/gui/main_window.py

66 self.button_define_numerically.clicked.connect(
67     lambda: DefineNumericallyDialog(self.matrix_wrapper, self).exec()
68 )
```

### 3.2.3 More definition dialogs

I then factored out the constructor into a `DefinedDialog` superclass so that I could easily create other definition dialogs.

```
# 5d04fb7233a03d0cd8fa0768f6387c6678da9df3
# src/lintrans/gui/dialogs/define_new_matrix.py

22 class DefinedDialog(QDialog):
23     """A superclass for definitions dialogs."""
24
25     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
26         """Create the dialog, but don't run it yet.
27
28         :param matrix_wrapper: The MatrixWrapper that this dialog will mutate
29         :type matrix_wrapper: MatrixWrapper
30         """
31         super().__init__(*args, **kwargs)
32
33         self.matrix_wrapper = matrix_wrapper
34         self.setWindowTitle('Define a matrix')
35
36         # === Create the widgets
37
38         self.button_confirm = QtWidgets.QPushButton(self)
39         self.button_confirm.setText('Confirm')
40         self.button_confirm.setEnabled(False)
41         self.button_confirm.clicked.connect(self.confirm_matrix)
42         self.button_confirm.setToolTip('Confirm this as the new matrix<br><b>(Ctrl + Enter)</b>')
43         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self.button_confirm.click)
44
45         self.button_cancel = QtWidgets.QPushButton(self)
46         self.button_cancel.setText('Cancel')
47         self.button_cancel.clicked.connect(self.close)
48         self.button_cancel.setToolTip('Cancel this definition<br><b>(Ctrl + Q)</b>')
49         QShortcut(QKeySequence('Ctrl+Q'), self).activated.connect(self.button_cancel.click)
50
51         self.label_equals = QtWidgets.QLabel()
```

```

52         self.label_equals.setText('=')
53
54         self.letter_combo_box = QtWidgets.QComboBox(self)
55
56         # Everything except I, because that's the identity
57         for letter in ALPHABET_NO_I:
58             self.letter_combo_box.addItem(letter)
59
60         self.letter_combo_box.activated.connect(self.load_matrix)

```

This superclass just has a constructor that subclasses can use. When I added the `DefineAsARotationDialog` class, I also moved the cancel and confirm buttons into the constructor and added abstract methods that all dialog subclasses must implement.

```

# 0d534c35c6a4451e317d41a0d2b3ecb17827b45f
# src/lintrans/gui/dialogs/define_new_matrix.py

61         # === Arrange the widgets
62
63         self.setContentsMargins(10, 10, 10, 10)
64
65         self.horizontal_spacer = QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum)
66
67         self.hlay_buttons = QHBoxLayout()
68         self.hlay_buttons.setSpacing(20)
69         self.hlay_buttons.addItem(self.horizontal_spacer)
70         self.hlay_buttons.addWidget(self.button_cancel)
71         self.hlay_buttons.addWidget(self.button_confirm)
72
73         @property
74         def selected_letter(self) -> str:
75             """The letter currently selected in the combo box."""
76             return self.letter_combo_box.currentText()
77
78         @abc.abstractmethod
79         def update_confirm_button(self) -> None:
80             """Enable the confirm button if it should be enabled."""
81             ...
82
83         @abc.abstractmethod
84         def confirm_matrix(self) -> None:
85             """Confirm the inputted matrix and assign it.
86
87             This should mutate self.matrix_wrapper and then call self.accept().
88             """
89             ...

```

I then added the class for the rotation definition dialog.

```

# 0d534c35c6a4451e317d41a0d2b3ecb17827b45f
# src/lintrans/gui/dialogs/define_new_matrix.py

182 class DefineAsARotationDialog(Definedialog):
183     """The dialog that allows the user to define a new matrix as a rotation."""
184
185     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
186         """Create the dialog, but don't run it yet."""
187         super().__init__(matrix_wrapper, *args, **kwargs)
188
189         # === Create the widgets
190
191         self.label_equals.setText('= rot(')
192
193         self.text_angle = QtWidgets.QLineEdit(self)
194         self.text_angle.setPlaceholderText('angle')
195         self.text_angle.textChanged.connect(self.update_confirm_button)
196
197         self.label_close_paren = QtWidgets.QLabel(self)

```

```

198         self.label_close_paren.setText('')
199
200         self.checkbox_radians = QtWidgets.QCheckBox(self)
201         self.checkbox_radians.setText('Radians')
202
203         # === Arrange the widgets
204
205         self.hlay_checkbox_and_buttons = QHBoxLayout()
206         self.hlay_checkbox_and_buttons.setSpacing(20)
207         self.hlay_checkbox_and_buttons.addWidget(self.checkbox_radians)
208         self.hlay_checkbox_and_buttons.addItem(self.horizontal_spacer)
209         self.hlay_checkbox_and_buttons.addLayout(self.hlay_buttons)
210
211         self.hlay_definition = QHBoxLayout()
212         self.hlay_definition.addWidget(self.letter_combo_box)
213         self.hlay_definition.addWidget(self.label_equals)
214         self.hlay_definition.addWidget(self.text_angle)
215         self.hlay_definition.addWidget(self.label_close_paren)
216
217         self.vlay_all = QVBoxLayout()
218         self.vlay_all.setSpacing(20)
219         self.vlay_all.addLayout(self.hlay_definition)
220         self.vlay_all.addLayout(self.hlay_checkbox_and_buttons)
221
222         self.setLayout(self.vlay_all)
223
224     def update_confirm_button(self) -> None:
225         """Enable the confirm button if there is a valid float in the angle box."""
226         self.button_confirm.setEnabled(is_float(self.text_angle.text()))
227
228     def confirm_matrix(self) -> None:
229         """Confirm the inputted matrix and assign it."""
230         self.matrix_wrapper[self.selected_letter] = create_rotation_matrix(
231             float(self.text_angle.text()),
232             degrees=not self.checkbox_radians.isChecked()
233         )
234         self.accept()

```

This dialog class just overrides the abstract methods of the superclass with its own implementations. This will be the pattern that all of the definition dialogs will follow.

It has a checkbox for radians, since this is supported in `create_rotation_matrix()`, but the textbox only supports numbers, so the user would have to calculate some multiple of  $\pi$  and paste in several decimal places. I expect people to only use degrees, because these are easier to use.




Figure 3.3: The first version of the rotation definition dialog

Additionally, I created a helper method in `LintransMainWindow`. Rather than connecting the clicked signal of the buttons to lambdas that instantiate an instance of the `DefineDialog` subclass and call `.exec()` on it, I now connect the clicked signal of the buttons to lambdas that call `self.dialog_define_matrix()` with the specific subclass.

```

# 6269e04d453df7be2d2f9c7ee176e83406cccc139
# src/lintrans/gui/main_window.py

170     def dialog_define_matrix(self, dialog_class: Type[DefineDialog]) -> None:
171         """Open a generic definition dialog to define a new matrix.
172
173         The class for the desired dialog is passed as an argument. We create an
174         instance of this class and the dialog is opened asynchronously and modally
175         (meaning it blocks interaction with the main window) with the proper method
176         connected to the ``dialog.finished`` slot.
177
178         .. note::

```

```

179         ``dialog_class`` must subclass :class:`lintrans.gui.dialogs.define_new_matrix.DefineDialog`.
180
181     :param dialog_class: The dialog class to instantiate
182     :type dialog_class: Type[lintrans.gui.dialogs.define_new_matrix.DefineDialog]
183     """
184     # We create a dialog with a deepcopy of the current matrix_wrapper
185     # This avoids the dialog mutating this one
186     dialog = dialog_class(deepcopy(self.matrix_wrapper), self)
187
188     # .open() is asynchronous and doesn't spawn a new event loop, but the dialog is still modal (blocking)
189     dialog.open()
190
191     # So we have to use the finished slot to call a method when the user accepts the dialog
192     # If the user rejects the dialog, this matrix_wrapper will be the same as the current one, because we copied
193     ↪ it
194     # So we don't care, we just assign the wrapper anyway
195     dialog.finished.connect(lambda: self._assign_matrix_wrapper(dialog.matrix_wrapper))
196
197     def _assign_matrix_wrapper(self, matrix_wrapper: MatrixWrapper) -> None:
198         """Assign a new value to self.matrix_wrapper.
199
200         This is a little utility function that only exists because a lambda
201         callback can't directly assign a value to a class attribute.
202
203         :param matrix_wrapper: The new value of the matrix wrapper to assign
204         :type matrix_wrapper: MatrixWrapper
205         """
206         self.matrix_wrapper = matrix_wrapper

```

I also then implemented a simple `DefineAsAnExpressionDialog`, which evaluates a given expression in the current `MatrixWrapper` context and assigns the result to the given matrix name.

```

# d5f930e15c3c8798d4990486532da46e926a6cb9
# src/lintrans/gui/dialogs/define_new_matrix.py

241 class DefineAsAnExpressionDialog(DefineDialog):
242     """The dialog that allows the user to define a matrix as an expression."""
243
244     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
245         """Create the dialog, but don't run it yet."""
246         super().__init__(matrix_wrapper, *args, **kwargs)
247
248         self.setMinimumWidth(450)
249
250         # === Create the widgets
251
252         self.text_box_expression = QtWidgets.QLineEdit(self)
253         self.text_box_expression.setPlaceholderText('Enter matrix expression...')
254         self.text_box_expression.textChanged.connect(self.update_confirm_button)
255
256         # === Arrange the widgets
257
258         self.hlay_definition.addWidget(self.text_box_expression)
259
260         self.vlay_all = QVBoxLayout()
261         self.vlay_all.setSpacing(20)
262         self.vlay_all.addLayout(self.hlay_definition)
263         self.vlay_all.addLayout(self.hlay_buttons)
264
265         self.setLayout(self.vlay_all)
266
267     def update_confirm_button(self) -> None:
268         """Enable the confirm button if the expression is valid."""
269         self.button_confirm.setEnabled(
270             self.matrix_wrapper.is_valid_expression(self.text_box_expression.text())
271         )
272
273     def confirm_matrix(self) -> None:
274         """Evaluate the matrix expression and assign its value to the chosen matrix."""
275         self.matrix_wrapper[self.selected_letter] = \

```



```

276         self.matrix_wrapper.evaluate_expression(self.text_box_expression.text())
277     self.accept()

```

My next dialog that I wanted to implement was a visual definition dialog, which would allow the user to drag around the basis vectors to define a transformation. However, I would first need to create the `lintrans.gui.plots` package to allow for actually visualizing matrices and transformations.

### 3.3 Visualizing matrices

#### 3.3.1 Asking strangers on the internet for help

After creating most of the GUI skeleton, I wanted to build the viewport. Unfortunately, I had no idea what I was doing.

While looking through the PyQt5 docs, I found a pretty comprehensive explanation of the Qt5 ‘Graphics View Framework’[14], which seemed pretty good, but not really what I was looking for. I wanted a way to easily draw lots of straight, parallel lines. This framework seemed more focussed on manipulating objects on a canvas, almost like sprites. I knew of a different Python library called `matplotlib`, which has various backends available. I learned that it could be embedded in a standard PyQt5 GUI, so I started doing some research.

I didn’t get very far with `matplotlib`. I hadn’t used it much before and it’s designed for visualizing data. It can draw manually defined straight lines on a canvas, but that’s not what it’s designed for and it’s not very good at it. Thankfully, my horrific `matplotlib` code has been lost to time. I used the `Qt5Agg` backend from `matplotlib` to create a custom PyQt5 widget for the GUI and I could graph randomly generated data with it after following a tutorial[13].

I realised that I wasn’t going to get very far with `matplotlib`, but I didn’t know what else to do. I couldn’t find any relevant examples on the internet, so I decided to post a question on a forum myself. I’d had experience with StackOverflow and its unfriendly community before, so I decided to ask the `r/learnpython` subreddit[3].

I only got one response, but it was incredibly helpful. The person told me that if I couldn’t find an easy way to do what I wanted, I could write a custom PyQt5 widget. I knew this was possible with a class that just inherited from `QWidget`, but had no idea how to actually make something useful. Thankfully, this person provided a link to a GitLab repository of theirs, where they had multiple examples of custom widgets with PyQt5[4].

When looking through this repo, I found out how to draw on a widget like a simple canvas. All I have to do is override the `paintEvent()` method and use a `QPainter` object to draw on the widget. I used this knowledge to start creating the actual viewport for the GUI, starting with the background axes.

#### 3.3.2 Creating the plots package

Initially, the `lintrans.gui.plots` package just has some classes for widgets. `TransformationPlotWidget` acts as a base class and then `ViewTransformationWidget` acts as a wrapper. I will expand this class in the future.

```

# 4af63072b383dc9cef9adb8900323aa007e7f26
# src/lintrans/gui/plots/plot_widget.py

1  """This module provides the basic classes for plotting transformations."""
2
3  from __future__ import annotations
4
5  from PyQt5.QtCore import Qt

```

```

6  from PyQt5.QtGui import QColor, QPainter, QPaintEvent, QPen
7  from PyQt5.QtWidgets import QWidget
8
9
10 class TransformationPlotWidget(QWidget):
11     """An abstract superclass for plot widgets.
12
13     This class provides a background (untransformed) plane, and all the backend
14     details for a Qt application, but does not provide useful functionality. To
15     be useful, this class must be subclassed and behaviour must be implemented
16     by the subclass.
17
18     .. warning:: This class should never be directly instantiated, only subclassed.
19
20     .. note::
21     I would make this class have ``metaclass=abc.ABCMeta``, but I can't because it subclasses ``QWidget``,
22     and a every superclass of a class must have the same metaclass, and ``QWidget`` is not an abstract class.
23     """
24
25     def __init__(self, *args, **kwargs):
26         """Create the widget, passing ``*args`` and ``**kwargs`` to the superclass constructor (``QWidget``)."""
27         super().__init__(*args, **kwargs)
28
29         self.setAutoFillBackground(True)
30
31         # Set the background to white
32         palette = self.palette()
33         palette.setColor(self.backgroundRole(), Qt.white)
34         self.setPalette(palette)
35
36         # Set the grid colour to grey and the axes colour to black
37         self.grid_colour = QColor(128, 128, 128)
38         self.axes_colour = QColor(0, 0, 0)
39
40         self.grid_spacing: int = 50
41         self.line_width: float = 0.4
42
43     @property
44     def w(self) -> int:
45         """Return the width of the widget."""
46         return self.size().width()
47
48     @property
49     def h(self) -> int:
50         """Return the height of the widget."""
51         return self.size().height()
52
53     def paintEvent(self, e: QPaintEvent):
54         """Handle a ``QPaintEvent`` by drawing the widget."""
55         qp = QPainter()
56         qp.begin(self)
57         self.draw_widget(qp)
58         qp.end()
59
60     def draw_widget(self, qp: QPainter):
61         """Draw the grid and axes in the widget."""
62         qp.setRenderHint(QPainter.Antialiasing)
63         qp.setBrush(Qt.NoBrush)
64
65         # Draw the grid
66         qp.setPen(QPen(self.grid_colour, self.line_width))
67
68         # We draw the background grid, centered in the middle
69         # We deliberately exclude the axes - these are drawn separately
70         for x in range(self.w // 2 + self.grid_spacing, self.w, self.grid_spacing):
71             qp.drawLine(x, 0, x, self.h)
72             qp.drawLine(self.w - x, 0, self.w - x, self.h)
73
74         for y in range(self.h // 2 + self.grid_spacing, self.h, self.grid_spacing):
75             qp.drawLine(0, y, self.w, y)
76             qp.drawLine(0, self.h - y, self.w, self.h - y)
77
78         # Now draw the axes

```

```

79         qp.setPen(QPen(self.axes_colour, self.line_width))
80         qp.drawLine(self.w // 2, 0, self.w // 2, self.h)
81         qp.drawLine(0, self.h // 2, self.w, self.h // 2)
82
83
84     class ViewTransformationWidget(TransformationPlotWidget):
85         """This class is used to visualise matrices as transformations."""
86
87         def __init__(self, *args, **kwargs):
88             """Create the widget, passing ``*args`` and ``**kwargs`` to the superclass constructor."""
89             super().__init__(*args, **kwargs)

```




Figure 3.4: The GUI with background axes

The meat of this class is the `draw_widget()` method. Right now, this method only draws the background axes. My next step is to implement basis vector attributes and draw them in `draw_widget()`. After changing the `plot` attribute in `LintransMainWindow` to an instance of `ViewTransformationWidget`, the plot was visible in the GUI.

I then refactored the code slightly to rename `draw_widget()` to `draw_background()` and then call it from the `paintEvent()` method in `ViewTransformationWidget`.

### 3.3.3 Implementing basis vectors

My first step in implementing basis vectors was to add some utility methods to convert between coordinate systems. The matrices are using Cartesian coordinates with (0,0) in the middle, positive  $x$  going to the right, and positive  $y$  going up. However, Qt5 is using standard computer graphics coordinates, with (0,0) in the top left, positive  $x$  going to the right, and positive  $y$  going down. I needed a way to convert Cartesian ‘grid’ coordinates to Qt5 ‘canvas’ coordinates, so I wrote some little utility methods.

```

# 1fa7e1c61d61cb6aeff773b9698541f82fee39ea
# src/lintrans/gui/plots/plot_widget.py

45     @property
46     def origin(self) -> tuple[int, int]:
47         """Return the canvas coords of the origin."""
48         return self.width() // 2, self.height() // 2
49
50     def trans_x(self, x: float) -> int:
51         """Transform an x coordinate from grid coords to canvas coords."""
52         return int(self.origin[0] + x * self.grid_spacing)
53
54     def trans_y(self, y: float) -> int:
55         """Transform a y coordinate from grid coords to canvas coords."""
56         return int(self.origin[1] - y * self.grid_spacing)
57
58     def trans_coords(self, x: float, y: float) -> tuple[int, int]:
59         """Transform a coordinate in grid coords to canvas coords."""
60         return self.trans_x(x), self.trans_y(y)

```

Once I had a way to convert coordinates, I could add the basis vectors themselves. I did this by creating attributes for the points in the constructor and creating a `transform_by_matrix()` method to change these point attributes accordingly.

```

# 37e7c208a33d7cbbc8e0bb6c94cd889e2918c605
# src/lintrans/gui/plots/plot_widget.py

```

```

92 class ViewTransformationWidget(TransformationPlotWidget):
93     """This class is used to visualise matrices as transformations."""
94
95     def __init__(self, *args, **kwargs):
96         """Create the widget, passing ``*args`` and ``**kwargs`` to the superclass constructor."""
97         super().__init__(*args, **kwargs)
98
99         self.point_i: tuple[float, float] = (1., 0.)
100        self.point_j: tuple[float, float] = (0., 1.)
101
102        self.colour_i = QColor(37, 244, 15)
103        self.colour_j = QColor(8, 8, 216)
104
105        self.width_vector_line = 1
106        self.width_transformed_grid = 0.6
107
108    def transform_by_matrix(self, matrix: MatrixType) -> None:
109        """Transform the plane by the given matrix."""
110        self.point_i = (matrix[0][0], matrix[1][0])
111        self.point_j = (matrix[0][1], matrix[1][1])
112        self.update()

```

I also created a `draw_transformed_grid()` method which gets called in `paintEvent()`.

```

# 37e7c208a33d7cbbc8e0bb6c94cd889e2918c605
# src/lintrans/gui/plots/plot_widget.py

122    def draw_transformed_grid(self, painter: QPainter) -> None:
123        """Draw the transformed version of the grid, given by the unit vectors."""
124        # Draw the unit vectors
125        painter.setPen(QPen(self.colour_i, self.width_vector_line))
126        painter.drawLine(*self.origin, *self.trans_coords(*self.point_i))
127        painter.setPen(QPen(self.colour_j, self.width_vector_line))
128        painter.drawLine(*self.origin, *self.trans_coords(*self.point_j))

```

I then changed the `render_expression()` method in `LintransMainWindow` to call this new `transform_by_matrix()` method.


```

# 37e7c208a33d7cbbc8e0bb6c94cd889e2918c605
# src/lintrans/gui/main_window.py

229    def render_expression(self) -> None:
230        """Render the expression in the input box, and then clear the box."""
231        self.plot.transform_by_matrix(
232            self.matrix_wrapper.evaluate_expression(
233                self.lineedit_expression_box.text()
234            )
235        )

```

Testing this new code shows that it works well.

Figure 3.5: Basis vectors drawn for a  $45^\circ$  rotation

### 3.3.4 Drawing the transformed grid

After drawing the basis vectors, I wanted to draw the transformed version of the grid. I first created a `grid_corner()` utility method to return the grid coordinates of the top right corner of the canvas. This allows me to find the bounding box in which to draw the grid lines.

```
# 2ade98ac28d1c3f6691e4afa819142a3ab8e9fd9
# src/lintrans/gui/plots/plot_widget.py

64     def grid_corner(self) -> tuple[float, float]:
65         """Return the grid coords of the top right corner."""
66         return self.width() / (2 * self.grid_spacing), self.height() / (2 * self.grid_spacing)
```

I then created a `draw_parallel_lines()` method that would fill the bounding box with a set of lines parallel to a given vector with spacing defined by the intersection with a given point.

```
# 2ade98ac28d1c3f6691e4afa819142a3ab8e9fd9
# src/lintrans/gui/plots/plot_widget.py

126     def draw_parallel_lines(self, painter: QPainter, vector: tuple[float, float], point: tuple[float, float]) ->
127         ↪ None:
128         """Draw a set of grid lines parallel to `vector` intersecting `point`."""
129         max_x, max_y = self.grid_corner()
130         vector_x, vector_y = vector
131         point_x, point_y = point
132
133         if vector_x == 0:
134             painter.drawLine(self.trans_x(0), 0, self.trans_x(0), self.height())
135
136         for i in range(int(max_x / point_x)):
137             painter.drawLine(
138                 self.trans_x((i + 1) * point_x),
139                 0,
140                 self.trans_x((i + 1) * point_x),
141                 self.height()
142             )
143             painter.drawLine(
144                 self.trans_x(-1 * (i + 1) * point_x),
```

```

144         0,
145         self.trans_x(-1 * (i + 1) * point_x),
146         self.height()
147     )
148
149     elif vector_y == 0:
150         painter.drawLine(0, self.trans_y(0), self.width(), self.trans_y(0))
151
152     for i in range(int(max_y / point_y)):
153         painter.drawLine(
154             0,
155             self.trans_y((i + 1) * point_y),
156             self.width(),
157             self.trans_y((i + 1) * point_y)
158         )
159         painter.drawLine(
160             0,
161             self.trans_y(-1 * (i + 1) * point_y),
162             self.width(),
163             self.trans_y(-1 * (i + 1) * point_y)
164         )

```

I then called this method from `draw_transformed_grid()`.

```

# 2ade98ac28d1c3f6691e4afa819142a3ab8e9fd9
# src/lintrans/gui/plots/plot_widget.py

166 def draw_transformed_grid(self, painter: QPainter) -> None:
167     """Draw the transformed version of the grid, given by the unit vectors."""
168     # Draw the unit vectors
169     painter.setPen(QPen(self.colour_i, self.width_vector_line))
170     painter.drawLine(*self.origin, *self.trans_coords(*self.point_i))
171     painter.setPen(QPen(self.colour_j, self.width_vector_line))
172     painter.drawLine(*self.origin, *self.trans_coords(*self.point_j))
173
174     # Draw all the parallel lines
175     painter.setPen(QPen(self.colour_i, self.width_transformed_grid))
176     self.draw_parallel_lines(painter, self.point_i, self.point_j)
177     painter.setPen(QPen(self.colour_j, self.width_transformed_grid))
178     self.draw_parallel_lines(painter, self.point_j, self.point_i)

```

This worked quite well when the matrix involved no rotation, as seen on the right, but this didn't work with rotation. When trying `'rot(45)'` for example, it looked the same as in Figure 3.5.

Also, the vectors aren't particularly clear. They'd be much better with arrowheads on their tips, but this is just a prototype. The arrowheads will come later.

My next step was to make the transformed grid lines work with rotations.




Figure 3.6: Parallel lines being drawn for matrix  $1.2\mathbf{I}$

```

# 7dfe1e24729562501e2fd88a839dca6b653a3375
# src/lintrans/gui/plots/plot_widget.py

126 def draw_parallel_lines(self, painter: QPainter, vector: tuple[float, float], point: tuple[float, float]) -> None:
127     """Draw a set of grid lines parallel to `vector` intersecting `point`."""
128     max_x, max_y = self.grid_corner()
129     vector_x, vector_y = vector
130     point_x, point_y = point

```

```
131
132     print(max_x, max_y, vector_x, vector_y, point_x, point_y)
133
134     # We want to use y = mx + c but m = y / x and if either of those are 0, then this
135     # equation is harder to work with, so we deal with these edge cases first
136     if abs(vector_x) < 1e-12 and abs(vector_y) < 1e-12:
137         # If both components of the vector are practically 0, then we can't render any grid lines
138         return
139
140     elif abs(vector_x) < 1e-12:
141         painter.drawLine(self.trans_x(0), 0, self.trans_x(0), self.height())
142
143         for i in range(abs(int(max_x / point_x))):
144             painter.drawLine(
145                 self.trans_x((i + 1) * point_x),
146                 0,
147                 self.trans_x((i + 1) * point_x),
148                 self.height()
149             )
150             painter.drawLine(
151                 self.trans_x(-1 * (i + 1) * point_x),
152                 0,
153                 self.trans_x(-1 * (i + 1) * point_x),
154                 self.height()
155             )
156
157     elif abs(vector_y) < 1e-12:
158         painter.drawLine(0, self.trans_y(0), self.width(), self.trans_y(0))
159
160         for i in range(abs(int(max_y / point_y))):
161             painter.drawLine(
162                 0,
163                 self.trans_y((i + 1) * point_y),
164                 self.width(),
165                 self.trans_y((i + 1) * point_y)
166             )
167             painter.drawLine(
168                 0,
169                 self.trans_y(-1 * (i + 1) * point_y),
170                 self.width(),
171                 self.trans_y(-1 * (i + 1) * point_y)
172             )
173
174     else: # If the line is not horizontal or vertical, then we can use y = mx + c
175         m = vector_y / vector_x
176         c = point_y - m * point_x
177
178         # For c = 0
179         painter.drawLine(
180             *self.trans_coords(
181                 -1 * max_x,
182                 m * -1 * max_x
183             ),
184             *self.trans_coords(
185                 max_x,
186                 m * max_x
187             )
188         )
189
190         # Count up how many multiples of c we can have without wasting time rendering lines off screen
191         multiples_of_c: int = 0
192         ii: int = 1
193         while True:
194             y1 = m * max_x + ii * c
195             y2 = -1 * m * max_x + ii * c
196
197             if y1 < max_y or y2 < max_y:
198                 multiples_of_c += 1
199                 ii += 1
200
201         else:
202             break
203
```

```

204     # Once we know how many lines we can draw, we just draw them all
205     for i in range(1, multiples_of_c + 1):
206         painter.drawLine(
207             *self.trans_coords(
208                 -1 * max_x,
209                 m * -1 * max_x + i * c
210             ),
211             *self.trans_coords(
212                 max_x,
213                 m * max_x + i * c
214             )
215         )
216         painter.drawLine(
217             *self.trans_coords(
218                 -1 * max_x,
219                 m * -1 * max_x - i * c
220             ),
221             *self.trans_coords(
222                 max_x,
223                 m * max_x - i * c
224             )
225         )

```

This code checks if  $x$  or  $y$  is zero<sup>10</sup> and if they're not, then we have to use the standard straight line equation  $y = mx + c$  to create parallel lines. We find our value of  $m$  and then iterate through all the values of  $c$  that keep the line within the bounding box.




Figure 3.7: An example of a 20° rotation

There are some serious logical errors in this code. It works fine for things like '3rot(45)' or '0.5rot(20)', but something like 'rot(115)' will leave the program hanging indefinitely.

In fact, this code only works for rotations between 0° and 90°, and will hang forever when given a matrix like  $\begin{pmatrix} 12 & 4 \\ -2 & 3 \end{pmatrix}$ , because it's just not very good.

I will fix these issues in the future, but it works somewhat decently, so I decided to do animation next, because that sounded more fun.

### 3.3.5 Implementing animation

Now that I had a very crude renderer, I could create a method to animate a matrix. Eventually I want to be able to apply a given matrix to the currently rendered scene and animate between them. However, I wanted to start simple by animating from the identity to the given matrix.

```

# 829a130af5aee9819bf0269c03ecfb20bec1a108
# src/lintrans/gui/main_window.py

238     def animate_expression(self) -> None:
239         """Animate the expression in the input box, and then clear the box."""
240         self.button_render.setEnabled(False)
241         self.button_animate.setEnabled(False)
242
243         matrix = self.matrix_wrapper.evaluate_expression(self.lineEdit_expression_box.text())
244         matrix_move = matrix - self.matrix_wrapper['I']
245         steps: int = 100
246
247         for i in range(0, steps + 1):

```

<sup>10</sup>We actually check if they're less than  $10^{-12}$  to allow for floating point errors



```

248         self.plot.visualize_matrix_transformation(
249             self.matrix_wrapper['I'] + (i / steps) * matrix_move
250         )
251
252         self.update()
253         self.repaint()
254
255         time.sleep(0.01)
256
257         self.button_render.setEnabled(False)
258         self.button_animate.setEnabled(False)

```

This code creates the `matrix_move` variable and adds scaled versions of it to the identity matrix and renders that each frame. It's simple, but it works well for this simple use case. Unfortunately, it's very hard to show off an animation in a PDF, since all these images are static. The git commit hashes are included in the code snippets if you want to clone the repo[2], checkout this commit, and run it yourself if you want.

### 3.3.6 Preserving determinants

Ignoring the obvious flaw with not being able to render transformations with a more than  $90^\circ$  rotation, the animations don't respect determinants. When rotating  $90^\circ$ , the determinant changes during the animation, even though we're going from a determinant 1 matrix (the identity) to another determinant 1 matrix. This is because we're just moving each vector to its new position in a straight line. I want to animate in a way that smoothly transitions the determinant.




Figure 3.8: What we would expect halfway through a  $90^\circ$  rotation




Figure 3.9: What we actually get halfway through a  $90^\circ$  rotation

In order to smoothly animate the determinant, I had to do some maths. I first defined the matrix **A** to be equivalent to the `matrix_move` variable from before - the target matrix minus the identity, scaled by the proportion. I then wanted to normalize **A** so that it had a determinant of 1 so that I could scale it up with the `proportion` variable through the animation.

I think I first tried just multiplying **A** by  $\frac{1}{\det(\mathbf{A})}$  but that didn't work, so I googled it. I found a post[12] on ResearchGate about the topic, and thanks to a very helpful comment from Jeffrey L Stuart, I learned that for a  $2 \times 2$  matrix **A** and a scalar  $c$ ,  $\det(c\mathbf{A}) = c^2 \det(\mathbf{A})$ .

I wanted a  $c$  such that  $\det(c\mathbf{A}) = 1$ . Therefore  $c = \frac{1}{\sqrt{|\det(\mathbf{A})|}}$ . I then defined matrix **B** to be  $c\mathbf{A}$ .

Then I wanted to scale this normalized matrix **B** to have the same determinant as the target matrix **T** using some scalar  $d$ . We know that  $\det(d\mathbf{B}) = d^2 \det(\mathbf{B}) = \det(\mathbf{T})$ . We can just rearrange to find  $d$

and get  $d = \sqrt{\left| \frac{\det(\mathbf{T})}{\det(\mathbf{B})} \right|}$ . But  $\mathbf{B}$  is defined so that  $\det(\mathbf{B}) = 1$ , so we can get  $d = \sqrt{|\det(\mathbf{T})|}$ .

However, we want to scale this over time with our proportion variable  $p$ , so our final scalar  $s = 1 + p \left( \sqrt{|\det(\mathbf{T})|} - 1 \right)$ . We define a matrix  $\mathbf{C} = s\mathbf{B}$  and render  $\mathbf{C}$  each frame. When in code form, this is the following:

```
# 6ff49450d8438ea2b2e7d2a97125dc518e648bc5
# src/lintrans/gui/main_window.py

245     # Get the target matrix and it's determinant
246     matrix_target = self.matrix_wrapper.evaluate_expression(self.lineedit_expression_box.text())
247     det_target = linalg.det(matrix_target)
248
249     identity = self.matrix_wrapper['I']
250     steps: int = 100
251
252     for i in range(0, steps + 1):
253         # This proportion is how far we are through the loop
254         proportion = i / steps
255
256         # matrix_a is the identity plus some part of the target, scaled by the proportion
257         # If we just used matrix_a, then things would animate, but the determinants would be weird
258         matrix_a = identity + proportion * (matrix_target - identity)
259
260         # So to fix the determinant problem, we get the determinant of matrix_a and use it to normalise
261         det_a = linalg.det(matrix_a)
262
263         # For a 2x2 matrix A and a scalar c, we know that det(cA) = c^2 det(A)
264         # We want B = cA such that det(B) = 1, so then we can scale it with the animation
265         # So we get c^2 det(A) = 1 => c = sqrt(1 / abs(det(A)))
266         # Then we scale A down to get a determinant of 1, and call that matrix_b
267         if det_a == 0:
268             c = 0
269         else:
270             c = np.sqrt(1 / abs(det_a))
271
272         matrix_b = c * matrix_a
273
274         # matrix_c is the final matrix that we transform by
275         # It's B, but we scale it up over time to have the target determinant
276
277         # We want some C = dB such that det(C) is some target determinant T
278         # det(dB) = d^2 det(B) = T => d = sqrt(abs(T / det(B)))
279         # But we defined B to have det 1, so we can ignore it there
280
281         # We're also subtracting 1 and multiplying by the proportion and then adding one
282         # This just scales the determinant along with the animation
283         scalar = 1 + proportion * (np.sqrt(abs(det_target)) - 1)
284
285         matrix_c = scalar * matrix_b
286
287         self.plot.visualize_matrix_transformation(matrix_c)
288
289         self.repaint()
290         time.sleep(0.01)
```

Unfortunately, the system I use to render matrices is still quite bad at its job. This makes it hard to test properly. But, transformations like `'2rot(90)'` work exactly as expected, which is very good.

## 3.4 Improving the GUI

### 3.4.1 Fixing rendering

Now that I had the basics of matrix visualization sorted, I wanted to make the GUI and UX better. My first step was overhauling the rendering code to make it actually work with rotations of more than  $90^\circ$ .

I narrowed down the issue with PyCharm's debugger and found that the loop in `VectorGridPlot.draw_parallel_lines()` was looping forever if it tried to do anything outside of the top right quadrant. To fix this, I decided to instead delegate this task of drawing a set of oblique lines to a separate method, and work on that instead.

```
# cf05e09e5ebb6ea7a96db8660d0d8de6b946490a
# src/lintrans/gui/plots/classes.py

203         else: # If the line is not horizontal or vertical, then we can use  $y = mx + c$ 
204             m = vector_y / vector_x
205             c = point_y - m * point_x
206
207             # For  $c = 0$ 
208             painter.drawLine(
209                 *self.trans_coords(
210                     -1 * max_x,
211                     m * -1 * max_x
212                 ),
213                 *self.trans_coords(
214                     max_x,
215                     m * max_x
216                 )
217             )
218
219             # We keep looping and increasing the multiple of  $c$  until we stop drawing lines on the canvas
220             multiple_of_c = 1
221             while self.draw_pair_of_oblique_lines(painter, m, multiple_of_c * c):
222                 multiple_of_c += 1
```

This separation of functionality made designing and debugging this part of the solution much easier. The `draw_pair_of_oblique_lines()` method looked like this:

```
# cf05e09e5ebb6ea7a96db8660d0d8de6b946490a
# src/lintrans/gui/plots/classes.py

224     def draw_pair_of_oblique_lines(self, painter: QPainter, m: float, c: float) -> bool:
225         """Draw a pair of oblique lines, using the equation  $y = mx + c$ .
226
227         This method just calls :meth:`draw_oblique_line` with ``c`` and ``-c``,
228         and returns True if either call returned True.
229
230         :param QPainter painter: The ``QPainter`` object to use for drawing the vectors and grid lines
231         :param float m: The gradient of the lines to draw
232         :param float c: The y-intercept of the lines to draw. We use the positive and negative versions
233         :returns bool: Whether we were able to draw any lines on the canvas
234         """
235         return any([
236             self.draw_oblique_line(painter, m, c),
237             self.draw_oblique_line(painter, m, -c)
238         ])
239
240     def draw_oblique_line(self, painter: QPainter, m: float, c: float) -> bool:
241         """Draw an oblique line, using the equation  $y = mx + c$ .
242
243         We only draw the part of the line that fits within the canvas, returning True if
244         we were able to draw a line within the boundaries, and False if we couldn't draw a line
245
246         :param QPainter painter: The ``QPainter`` object to use for drawing the vectors and grid lines
```

```

247 :param float m: The gradient of the line to draw
248 :param float c: The y-intercept of the line to draw
249 :returns bool: Whether we were able to draw a line on the canvas
250 """
251 max_x, max_y = self.grid_corner()
252
253 # These variable names are shortened for convenience
254 # myi is max_y_intersection, mmyi is minus_max_y_intersection, etc.
255 myi = (max_y - c) / m
256 mmyi = (-max_y - c) / m
257 mxi = max_x * m + c
258 mmxi = -max_x * m + c
259
260 # The inner list here is a list of coords, or None
261 # If an intersection fits within the bounds, then we keep its coord,
262 # else it is None, and then gets discarded from the points list
263 # By the end, points is a list of two coords, or an empty list
264 points: list[tuple[float, float]] = [
265     x for x in [
266         (myi, max_y) if -max_x < myi < max_x else None,
267         (mmyi, -max_y) if -max_x < mmyi < max_x else None,
268         (max_x, mxi) if -max_y < mxi < max_y else None,
269         (-max_x, mmxi) if -max_y < mmxi < max_y else None
270     ] if x is not None
271 ]
272
273 # If no intersections fit on the canvas
274 if len(points) < 2:
275     return False
276
277 # If we can, then draw the line
278 else:
279     painter.drawLine(
280         *self.trans_coords(*points[0]),
281         *self.trans_coords(*points[1])
282     )
283     return True

```

To illustrate what this code is doing, I'll use a diagram.




Figure 3.10: Two example lines and the viewport box




Figure 3.11: A demonstration of the new oblique lines system.

The red box represents the viewport of the GUI. The dashed lines represent the extensions of the red box. For a given line we want to draw, we first want to find where it intersects these orthogonal lines. Any oblique line will intersect each of these lines exactly once. This is what the myi, mmyi, mxi, and

`mmxi` variables represent. The value of `myi` is the  $x$  value where the line intersects the maximum  $y$  line, for example.

In the case of the blue line, all 4 intersection points are outside the bounds of the box, whereas the green line intersects with the box, as shown with the crosses. We use a list comprehension over a list of ternaries to get the `points` list. This list contains 0 or 2 coordinates, and we may or may not draw a line accordingly.

That's how the `draw_oblique_line()` method works, and the `draw_pair_of_oblique_lines()` method just calls it with positive and negative values of  $c$ .

### 3.4.2 Adding vector arrowheads




Figure 3.12: An example of a vector with the arrowheads highlighted in green

Now that I had a good renderer, I wanted to add arrowheads to the vectors to make them easier to see. They were already thicker than the gridlines, but adding arrowheads like in the 3blue1brown series would make them much easier to see. Unfortunately, I couldn't work out how to do this.

I wanted a function that would take a coordinate, treat it as a unit vector, and draw lines at  $45^\circ$  angles at the tip. This wasn't how I was conceptualising the problem at the time and because of that, I couldn't work out how to solve this problem. I could create this  $45^\circ$  lines in the top right quadrant, but none of my possible solutions worked for any arbitrary point.

So I started googling and found a very nice algorithm on [csharp-helper.com](http://csharp-helper.com)[23], which I adapted for Python.

```
# 5373b1ad8040f6726147cccea523c0570251cf67
# src/lintrans/gui/plots/widgets.py

52 def draw_arrowhead_away_from_origin(self, painter: QPainter, point: tuple[float, float]) -> None:
53     """Draw an arrowhead at ``point``, pointing away from the origin.
54
55     :param QPainter painter: The ``QPainter`` object to use to draw the arrowheads with
56     :param point: The point to draw the arrowhead at, given in grid coords
57     :type point: tuple[float, float]
58     """
59     # This algorithm was adapted from a C# algorithm found at
60     # http://csharp-helper.com/blog/2014/12/draw-lines-with-arrowheads-in-c/
61
62     # Get the x and y coords of the point, and then normalize them
63     # We have to normalize them, or else the size of the arrowhead will
64     # scale with the distance of the point from the origin
65     x, y = point
66     nx = x / np.sqrt(x * x + y * y)
67     ny = y / np.sqrt(x * x + y * y)
68
69     # We choose a length and do some magic to find the steps in the x and y directions
70     length = 0.15
71     dx = length * (-nx - ny)
72     dy = length * (nx - ny)
73
74     # Then we just plot those lines
75     painter.drawLine(*self.trans_coords(x, y), *self.trans_coords(x + dx, y + dy))
76     painter.drawLine(*self.trans_coords(x, y), *self.trans_coords(x - dy, y + dx))
77
78 def draw_vector_arrowheads(self, painter: QPainter) -> None:
79     """Draw arrowheads at the tips of the basis vectors.
```

```

80
81 :param QPainter painter: The ``QPainter`` object to use to draw the arrowheads with
82 """
83 painter.setPen(QPen(self.colour_i, self.width_vector_line))
84 self.draw_arrowhead_away_from_origin(painter, self.point_i)
85 painter.setPen(QPen(self.colour_j, self.width_vector_line))
86 self.draw_arrowhead_away_from_origin(painter, self.point_j)

```

As the comments suggest, we get the  $x$  and  $y$  components of the normalised vector, and then do some magic with a chosen length and get some distance values, and then draw those lines. I don't really understand how this code works, but I'm happy that it does. All we have to do is call `draw_vector_arrowheads()` from `paintEvent()`.




Figure 3.13: An example of the  $i$  and  $j$  vectors with arrowheads

### 3.4.3 Implementing zoom

The next thing I wanted to do was add the ability to zoom in and out of the viewport, and I wanted a button to reset the zoom level as well. I added a `default_grid_spacing` class attribute in `BackgroundPlot` and used that as the `grid_spacing` instance attribute in `__init__()`.

```

# d944e86e1d0fdc2c4be4d63479bc6bc3a31568ef
# src/lintrans/gui/plots/classes.py

27 default_grid_spacing: int = 50
28
29 def __init__(self, *args, **kwargs):
30     """Create the widget and setup backend stuff for rendering.
31
32     .. note:: ``*args`` and ``**kwargs`` are passed the superclass constructor (``QWidget``).
33     """
34     super().__init__(*args, **kwargs)
35
36     self.setAutoFillBackground(True)

```

```

37
38     # Set the background to white
39     palette = self.palette()
40     palette.setColor(self.backgroundRole(), Qt.white)
41     self.setPalette(palette)
42
43     # Set the grid colour to grey and the axes colour to black
44     self.colour_background_grid = QColor(128, 128, 128)
45     self.colour_background_axes = QColor(0, 0, 0)
46
47     self.grid_spacing = BackgroundPlot.default_grid_spacing

```

The reset button in LintransMainWindow simply sets `plot.grid_spacing` to the default.

To actually allow for zooming, I had to implement the `wheelEvent()` method in `BackgroundPlot` to listen for mouse wheel events. After reading through the docs for the `QWheelEvent` class[18], I learned how to handle this event.

```

# d944e86e1d0fdc2c4be4d63479bc6bc3a31568ef
# src/lintrans/gui/plots/classes.py

119     def wheelEvent(self, event: QWheelEvent) -> None:
120         """Handle a ``QWheelEvent`` by zooming in or out of the grid."""
121         # angleDelta() returns a number of units equal to 8 times the number of degrees rotated
122         degrees = event.angleDelta() / 8
123
124         if degrees is not None:
125             self.grid_spacing = max(1, self.grid_spacing + degrees.y())
126
127         event.accept()
128         self.update()

```

All we do is get the amount that the user scrolled and add that to the current spacing, taking the max with 1, which acts as a minimum grid spacing. We need to use `degrees.y()` on line 125 because Qt5 allows for mice that can scroll in the  $x$  and  $y$  directions, and we only want the  $y$  component. Line 127 marks the event as accepted so that the parent widget doesn't try to act on it.




Figure 3.14: The GUI zoomed in a bit




Figure 3.15: The GUI zoomed out as far as possible

There are two things I don't like here. Firstly, the minimum grid spacing is too small. The user can zoom out too far. Secondly, the arrowheads are too big in figure 3.14.

The first problem is minor and won't be fixed for quite a while, but I fixed the second problem quite quickly.

We want the arrowhead length to not just be 0.15, but to scale with the zoom level (the ratio between default grid spacing and current spacing).

This creates a slight issue when zoomed out all the way, because the arrowheads are then far larger than the vectors themselves, so we take the minimum of the scaled length and the vector length.

I factored out the default arrowhead length into the `arrowhead_length` instance attribute and initialize it in `__init__()`.

```
# 3d19a003368ae992ebb60049685bb04fde0836b5
# src/lintrans/gui/plots/widgets.py

68     vector_length = np.sqrt(x * x + y * y)
69     nx = x / vector_length
70     ny = y / vector_length
71
72     # We choose a length and find the steps in the x and y directions
73     length = min(
74         self.arrowhead_length * self.default_grid_spacing / self.grid_spacing,
75         vector_length
76     )
```

This code results in arrowheads that stay the same length unless the user is zoomed out basically as far as possible.




Figure 3.16: The arrowheads adjusted for zoom level

### 3.4.4 Animation blocks zooming

The biggest problem with this new zoom feature is that when animating between matrices, the user is unable to zoom. This is because when `LintransMainWindow.animate_expression()` is called, it uses



Python's standard library `time.sleep()` function to delay each frame, which prevents Qt from handling user interaction while we're animating. This was a problem.

I did some googling and found a helpful post on StackOverflow[9] that gave me a nice solution. The user `ekhumoro` used the functions `QApplication.processEvents()` and `QThread.msleep()` to solve the problem, and I used these functions in my own app, with much success.

After reading 'The Event System' in the Qt5 documentation[24], I learned that Qt5 uses an event loop, a lot like JavaScript. This means that events are scheduled to be executed on the next pass of the event loop. I also read the documentation for the `repaint()` and `update()` methods on the `QWidget` class[20, 21] and decided that it would be better to just queue a repaint by calling `update()` on the plot rather than immediately repaint with `repaint()`, and then call `QApplication.processEvents()` to process the pending events on the main thread. This is a nicer way of repainting, which reduces potential flickering issues, and using `QThread.msleep()` allows for asynchronous processing and therefore non-blocking animation.

### 3.4.5 Rank 1 transformations

The rank of a matrix is the dimension of its column space. This is the dimension of the span of its columns, which is to say the dimension of the output space. The rank of a matrix must be less than or equal to the dimension of the matrix, so we only need to worry about ranks 0, 1, and 2. There is only one rank 0 matrix, which is the **0** matrix itself. I've already covered this case by just not drawing any transformed grid lines.

Rank 2 matrices encompass most 2D matrices, and I've already covered this case in §3.3.4 and §3.4.1. A rank 1 matrix collapses all of 2D space onto a single line, so for this type of matrix, we should just draw this line.

This code is in `VectorGridPlot.draw_parallel_lines()`. We assemble the matrix  $\begin{pmatrix} \text{vector\_x} & \text{point\_x} \\ \text{vector\_y} & \text{point\_y} \end{pmatrix}$  (which is actually the matrix used to create the transformation we're trying to render lines for) and use this matrix to check determinant and rank.

```
# 677b38c87bb6722b16aaf35058cf3cef66e43c21
# src/lintrans/gui/plots/classes.py

177     # If the determinant is 0
178     if abs(vector_x * point_y - vector_y * point_x) < 1e-12:
179         rank = np.linalg.matrix_rank(
180             np.array([
181                 [vector_x, point_x],
182                 [vector_y, point_y]
183             ])
184         )
185
186     # If the matrix is rank 1, then we can draw the column space line
187     if rank == 1:
188         self.draw_oblique_line(painter, vector_y / vector_x, 0)
189
190     # If the rank is 0, then we don't draw any lines
191     else:
192         return
```

Additionally, there was a bug with animating these determinant 0 matrices, since we try to scale the determinant through the animation, as documented in §3.3.6, but when the determinant is 0, this causes issues. To fix this, we just check the `det_target` variable in `LintransMainWindow.animate_expression` and if it's 0, we use the non-scaled version of the matrix.

```
# b889b686d997c2b64124bee786bccba3fc4f6b08
# src/lintrans/gui/main_window.py
```

```

307         # If we're animating towards a det 0 matrix, then we don't want to scale the
308         # determinant with the animation, because this makes the process not work
309         # I'm doing this here rather than wrapping the whole animation logic in an
310         # if block mainly because this looks nicer than an extra level of indentation
311         # The extra processing cost is negligible thanks to NumPy's optimizations
312         if det_target == 0:
313             matrix_c = matrix_a
314         else:
315             matrix_c = scalar * matrix_b

```

### 3.4.6 Matrices that are too big

One of my friends was playing around with the prototype and she discovered a bug. When trying to render really big matrices, we can get errors like ‘**OverflowError: argument 3 overflowed: value must be in the range -2147483648 to 2147483647**’ because PyQt5 is a wrapper over Qt5, which is a C++ library that uses the C++ **int** type for the `painter.drawLine()` call. This type is a 32-bit integer. Python can store integers of arbitrary precision, but when PyQt5 calls the underlying C++ library code, this gets cast to a C++ **int** and we can get an **OverflowError**.

This isn’t a problem with the gridlines, because we only draw them inside the viewport, as discussed in §3.4.1, and these calculations all happen in Python, so integer precision is not a concern. However, when drawing the basis vectors, we just draw them directly, so we’ll have to check that they’re within the limit.

I’d previously created a `LintransMainWindow.show_error_message()` method for telling the user when they try to take the inverse of a singular matrix<sup>11</sup>.

```

# 0f699dd95b6431e95b2311dcb03e7af49c19613f
# src/lintrans/gui/main_window.py

378     def show_error_message(self, title: str, text: str, info: str | None = None) -> None:
379         """Show an error message in a dialog box.
380
381         :param str title: The window title of the dialog box
382         :param str text: The simple error message
383         :param info: The more informative error message
384         :type info: Optional[str]
385         """
386         dialog = QMessageBox(self)
387         dialog.setIcon(QMessageBox.Critical)
388         dialog.setWindowTitle(title)
389         dialog.setText(text)
390
391         if info is not None:
392             dialog.setInformativeText(info)
393
394         dialog.open()
395
396         dialog.finished.connect(self.update_render_buttons)

```

I then created the `is_matrix_too_big()` method to just check that the elements of the matrix are within the desired bounds. If it returns **True** when we try to render or animate, then we call `show_error_message()`.

```

# 4682a7b225747cfd77aca0fe3abccdd1397b7c5dd
# src/lintrans/gui/main_window.py

407     def is_matrix_too_big(self, matrix: MatrixType) -> bool:
408         """Check if the given matrix will actually fit onto the canvas.
409

```

<sup>11</sup>This commit didn’t get a standalone section in this write-up because it was so small

```

410         Convert the elements of the matrix to canvas coords and make sure they fit within Qt's 32-bit integer limit.
411
412         :param MatrixType matrix: The matrix to check
413         :returns bool: Whether the matrix fits on the canvas
414         """
415         coords: list[tuple[int, int]] = [self.plot.trans_coords(*vector) for vector in matrix.T]
416
417         for x, y in coords:
418             if not (-2147483648 <= x <= 2147483647 and -2147483648 <= y <= 2147483647):
419                 return True
420
421         return False

```

### 3.4.7 Creating the DefineVisuallyDialog

Next, I wanted to allow the user to define a matrix visually by dragging the basis vectors. To do this, I obviously needed a new DefineDialog subclass for it.

```

# 16ca0229aab73b3f4a8fe752dee3608f3ed6ead5
# src/lintrans/gui/dialogs/define_new_matrix.py

135 class DefineVisuallyDialog(DefineDialog):
136     """The dialog class that allows the user to define a matrix visually."""
137
138     def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
139         """Create the widgets and layout of the dialog.
140
141         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
142         """
143         super().__init__(matrix_wrapper, *args, **kwargs)
144
145         self.setMinimumSize(500, 450)
146
147         # === Create the widgets
148
149         self.combobox_letter.activated.connect(self.show_matrix)
150
151         self.plot = DefineVisuallyWidget(self)
152
153         # === Arrange the widgets
154
155         self.hlay_definition.addWidget(self.plot)
156         self.hlay_definition.setStretchFactor(self.plot, 1)
157
158         self.vlay_all = QVBoxLayout()
159         self.vlay_all.setSpacing(20)
160         self.vlay_all.addLayout(self.hlay_definition)
161         self.vlay_all.addLayout(self.hlay_buttons)
162
163         self.setLayout(self.vlay_all)
164
165         # We load the default matrix A into the plot
166         self.show_matrix(0)
167
168         # We also enable the confirm button, because any visually defined matrix is valid
169         self.button_confirm.setEnabled(True)
170
171     def update_confirm_button(self) -> None:
172         """Enable the confirm button.
173
174         .. note::
175             The confirm button is always enabled in this dialog and this method is never actually used,
176             so it's got an empty body. It's only here because we need to implement the abstract method.
177         """
178
179     def show_matrix(self, index: int) -> None:
180         """Show the selected matrix on the plot. If the matrix is None, show the identity."""
181         matrix = self.matrix_wrapper[ALPHABET_NO_I[index]]
182

```

```

183         if matrix is None:
184             matrix = self.matrix_wrapper['I']
185
186         self.plot.visualize_matrix_transformation(matrix)
187         self.plot.update()
188
189     def confirm_matrix(self) -> None:

```

This DefineVisuallyDialog class just implements the normal methods needed for a DefineDialog and has a plot attribute to handle drawing graphics and handling mouse movement. After creating the DefineVisuallyWidget as a skeleton and doing some more research in the Qt5 docs[19], I renamed the trans\_coords() methods to canvas\_coords() to make the intent more clear, and created a grid\_coords() method.

```

# 417aea6555029b049c470faff18df29f064f6101
# src/lintrans/gui/plots/classes.py

```

```

85     def grid_coords(self, x: int, y: int) -> tuple[float, float]:
86         """Convert a coordinate from canvas coords to grid coords.
87
88         :param int x: The x component of the canvas coordinate
89         :param int y: The y component of the canvas coordinate
90         :returns: The resultant grid coordinates
91         :rtype: tuple[float, float]
92         """
93         # We get the maximum grid coords and convert them into canvas coords
94         return (x - self.canvas_origin[0]) / self.grid_spacing, (-y + self.canvas_origin[1]) / self.grid_spacing

```

I then needed to implement the methods to handle mouse movement in the DefineVisuallyWidget class. Thankfully, Ross Wilson, the person who helped me learn about the QWidget.paintEvent() method in §3.3.1, also wrote an example of draggable points[5]. In my post, I had explained that I needed draggable points on my canvas, and Ross was helpful enough to create an example in their own time. I probably could've worked it out myself eventually, but this example allowed me to learn a lot quicker.

```

# 417aea6555029b049c470faff18df29f064f6101
# src/lintrans/gui/plots/widgets.py

```

```

56 class DefineVisuallyWidget(VisualizeTransformationWidget):
57     """This class is the widget that allows the user to visually define a matrix.
58
59     This is just the widget itself. If you want the dialog, use
60     :class:`lintrans.gui.dialogs.define_new_matrix.DefineVisuallyDialog`.
61     """
62
63     def __init__(self, *args, **kwargs):
64         """Create the widget and enable mouse tracking. ``*args`` and ``**kwargs`` are passed to ``super()``."""
65         super().__init__(*args, **kwargs)
66
67         # self.setMouseTracking(True)
68         self.dragged_point: tuple[float, float] | None = None
69
70         # This is the distance that the cursor needs to be from the point to drag it
71         self.epsilon: int = 5
72
73     def mousePressEvent(self, event: QMouseEvent) -> None:
74         """Handle a QMouseEvent when the user pressed a button."""
75         mx = event.x()
76         my = event.y()
77         button = event.button()
78
79         if button != Qt.LeftButton:
80             event.ignore()
81             return
82
83         for point in (self.point_i, self.point_j):

```

```

84         px, py = self.canvas_coords(*point)
85         if abs(px - mx) <= self.epsilon and abs(py - my) <= self.epsilon:
86             self.dragged_point = point[0], point[1]
87
88     event.accept()
89
90     def mouseReleaseEvent(self, event: QMouseEvent) -> None:
91         """Handle a QMouseEvent when the user release a button."""
92         if event.button() == Qt.LeftButton:
93             self.dragged_point = None
94             event.accept()
95         else:
96             event.ignore()
97
98     def mouseMoveEvent(self, event: QMouseEvent) -> None:
99         """Handle the mouse moving on the canvas."""
100         mx = event.x()
101         my = event.y()
102
103         if self.dragged_point is not None:
104             x, y = self.grid_coords(mx, my)
105
106             if self.dragged_point == self.point_i:
107                 self.point_i = x, y
108
109             elif self.dragged_point == self.point_j:
110                 self.point_j = x, y
111
112             self.dragged_point = x, y
113
114             self.update()
115
116             print(self.dragged_point)
117             print(self.point_i, self.point_j)
118
119             event.accept()
120
121         event.ignore()

```

This snippet has the line ‘`self.setMouseTracking(True)`’ commented out. This line was in the example, but it turns out that I don’t want it. Mouse tracking means that a widget will receive a `QMouseEvent` every time the mouse moves. But if it’s disabled (the default), then the widget will only receive a `QMouseEvent` for mouse movement when a button is held down at the same time.

I’ve also left in some print statements on lines 116 and 117. These small oversights are there because I just forgot to remove them before I committed these changes. They were removed 3 commits later.

### 3.4.8 Fixing a division by zero bug

When drawing the rank line for a determinant 0, rank 1 matrix, we can encounter a division by zero error. I’m sure this originally manifested in a crash with a **ZeroDivisionError** at runtime, but now I can only get a **RuntimeWarning** when running the old code from commit `16ca0229aab73b3f4a8fe752dee3608f3ed6ead5`.

Whether it crashes or just warns the user, there is a division by zero bug when trying to render  $\begin{pmatrix} k & 0 \\ 0 & 0 \end{pmatrix}$  or  $\begin{pmatrix} 0 & 0 \\ 0 & k \end{pmatrix}$ . To fix this, I just handled those cases separately in `VectorGridPlot.draw_parallel_lines()`.

```

# 40bee6461d477a5c767ed132359cd511c0051e3b
# src/lintrans/gui/plots/classes.py

196     # If the matrix is rank 1, then we can draw the column space line
197     if rank == 1:
198         if abs(vector_x) < 1e-12:
199             painter.drawLine(self.width() // 2, 0, self.width() // 2, self.height())

```

```

200         elif abs(vector_y) < 1e-12:
201             painter.drawLine(0, self.height() // 2, self.width(), self.height() // 2)
202         else:
203             self.draw_oblique_line(painter, vector_y / vector_x, 0)
204
205     # If the rank is 0, then we don't draw any lines
206     else:
207         return

```

### 3.4.9 Implementing transitional animation

Currently, all animation animates from  $\mathbf{I}$  to the target matrix  $\mathbf{T}$ . This means it resets the plot at the start. I eventually want an applicative animation system, where the matrix in the box is applied to the current scene. But I also want an option for a transitional animation, where the program animates from the start matrix  $\mathbf{S}$  to the target matrix  $\mathbf{T}$ , and this seems easier to implement, so I'll do it first.

In `LintransMainWindow`, I created a new method called `animate_between_matrices()` and I call it from `animate_expression()`. The maths for smoothening determinants in §3.3.6 assumed the starting matrix had a determinant of 1, but when using transitional animation, this may not always be true.

If we let  $\mathbf{S}$  be the starting matrix, and  $\mathbf{A}$  be the matrix from the first stage of calculation as specified in §3.3.6, then we want a  $c$  such that  $\det(c\mathbf{A}) = \det(\mathbf{S})$ , so we get  $c = \sqrt{\left|\frac{\det(\mathbf{S})}{\det(\mathbf{A})}\right|}$  by the identity  $\det(c\mathbf{A}) = c^2 \det(\mathbf{A})$ .

Following the same logic as in §3.3.6, we can let  $\mathbf{B} = c\mathbf{A}$  and then scale it by  $d$  to get the same determinant as the target matrix  $\mathbf{T}$  and find that  $d = \sqrt{\left|\frac{\det(\mathbf{T})}{\det(\mathbf{B})}\right|}$ . Unlike previously,  $\det(\mathbf{B})$  could be any scalar, so we can't simplify our expression for  $d$ .

We then scale this with our proportion variable  $p$  to get a scalar  $s = 1 + p \left( \sqrt{\left|\frac{\det(\mathbf{T})}{\det(\mathbf{B})}\right|} - 1 \right)$  and render  $\mathbf{C} = s\mathbf{B}$  on each frame.

In code, that looks like this:

```

# 4017b84fbce67d8e041bc9ce84cefc0b6e65e1f
# src/lintrans/gui/main_window.py

275     def animate_expression(self) -> None:
276         """Animate from the current matrix to the matrix in the expression box."""
277         self.button_render.setEnabled(False)
278         self.button_animate.setEnabled(False)
279
280         # Get the target matrix and it's determinant
281         try:
282             matrix_target = self.matrix_wrapper.evaluate_expression(self.lineEdit_expression_box.text())
283
284         except linalg.LinAlgError:
285             self.show_error_message('Singular matrix', 'Cannot take inverse of singular matrix')
286             return
287
288         matrix_start: MatrixType = np.array([
289             [self.plot.point_i[0], self.plot.point_j[0]],
290             [self.plot.point_i[1], self.plot.point_j[1]]
291         ])
292
293         self.animate_between_matrices(matrix_start, matrix_target)
294
295         self.button_render.setEnabled(True)
296         self.button_animate.setEnabled(True)
297

```

```

298 def animate_between_matrices(self, matrix_start: MatrixType, matrix_target: MatrixType, steps: int = 100) ->
↳ None:
299     """Animate from the start matrix to the target matrix."""
300     det_target = linalg.det(matrix_target)
301     det_start = linalg.det(matrix_start)
302
303     for i in range(0, steps + 1):
304         # This proportion is how far we are through the loop
305         proportion = i / steps
306
307         # matrix_a is the start matrix plus some part of the target, scaled by the proportion
308         # If we just used matrix_a, then things would animate, but the determinants would be weird
309         matrix_a = matrix_start + proportion * (matrix_target - matrix_start)
310
311         # So to fix the determinant problem, we get the determinant of matrix_a and use it to normalise
312         det_a = linalg.det(matrix_a)
313
314         # For a 2x2 matrix A and a scalar c, we know that det(cA) = c^2 det(A)
315         # We want B = cA such that det(B) = det(S), where S is the start matrix,
316         # so then we can scale it with the animation, so we get
317         # det(cA) = c^2 det(A) = det(S) => c = sqrt(abs(det(S) / det(A)))
318         # Then we scale A to get the determinant we want, and call that matrix_b
319         if det_a == 0:
320             c = 0
321         else:
322             c = np.sqrt(abs(det_start / det_a))
323
324         matrix_b = c * matrix_a
325         det_b = linalg.det(matrix_b)
326
327         # matrix_c is the final matrix that we then render for this frame
328         # It's B, but we scale it over time to have the target determinant
329
330         # We want some C = dB such that det(C) is some target determinant T
331         # det(dB) = d^2 det(B) = T => d = sqrt(abs(T / det(B)))
332
333         # We're also subtracting 1 and multiplying by the proportion and then adding one
334         # This just scales the determinant along with the animation
335         scalar = 1 + proportion * (np.sqrt(abs(det_target / det_b)) - 1)
336
337         # If we're animating towards a det 0 matrix, then we don't want to scale the
338         # determinant with the animation, because this makes the process not work
339         # I'm doing this here rather than wrapping the whole animation logic in an
340         # if block mainly because this looks nicer than an extra level of indentation
341         # The extra processing cost is negligible thanks to NumPy's optimizations
342         if det_target == 0:
343             matrix_c = matrix_a
344         else:
345             matrix_c = scalar * matrix_b
346
347         if self.is_matrix_too_big(matrix_c):
348             self.show_error_message('Matrix too big', "This matrix doesn't fit on the canvas")
349             return
350
351         self.plot.visualize_matrix_transformation(matrix_c)
352
353         # We schedule the plot to be updated, tell the event loop to
354         # process events, and asynchronously sleep for 10ms
355         # This allows for other events to be processed while animating, like zooming in and out
356         self.plot.update()

```

This change results in an animation system that will transition from the current matrix to whatever the user types into the input box.

### 3.4.10 Allowing for sequential animation with commas

Applicative animation has two main forms. There's the version where a standard matrix expression gets applied to the current scene, and the kind where the user defines a sequence of matrices and

we animate through the sequence, applying one at a time. Both of these are referenced in success criterion 5.

I want the user to be able to decide if they want applicative animation or transitional animation, so I'll need to create some form of display settings. However, transitional animation doesn't make much sense for sequential animation<sup>12</sup>, so I can implement this now.

Applicative animation is just animating from the matrix **C** representing the current scene to the composition **TC** with the target matrix **T**.

We use **TC** instead of **CT** because matrix multiplication can be thought of as applying successive transformations from right to left. **TC** is the same as starting with the identity **I**, applying **C** (to get to the current scene), and then applying **T**.

Doing this in code is very simple. We just split the expression on commas, and then apply each sub-expression to the current scene one by one, pausing on each comma.

```
# 60584d2559cacbf23479a1bebbb986a800a32331
# src/lintrans/gui/main_window.py

284 def animate_expression(self) -> None:
285     """Animate from the current matrix to the matrix in the expression box."""
286     self.button_render.setEnabled(False)
287     self.button_animate.setEnabled(False)
288
289     matrix_start: MatrixType = np.array([
290         [self.plot.point_i[0], self.plot.point_j[0]],
291         [self.plot.point_i[1], self.plot.point_j[1]]
292     ])
293
294     text = self.lineedit_expression_box.text()
295
296     # If there's commas in the expression, then we want to animate each part at a time
297     if ',' in text:
298         current_matrix = matrix_start
299
300         # For each expression in the list, right multiply it by the current matrix,
301         # and animate from the current matrix to that new matrix
302         for expr in text.split(',')[:-1]:
303             new_matrix = self.matrix_wrapper.evaluate_expression(expr) @ current_matrix
304
305             self.animate_between_matrices(current_matrix, new_matrix)
306             current_matrix = new_matrix
307
308             # Here we just redraw and allow for other events to be handled while we pause
309             self.plot.update()
310             QApplication.processEvents()
311             QThread.sleep(500)
312
313     # If there's no commas, then just animate directly from the start to the target
314     else:
315         # Get the target matrix and it's determinant
316         try:
317             matrix_target = self.matrix_wrapper.evaluate_expression(text)
318
319         except linalg.LinAlgError:
320             self.show_error_message('Singular matrix', 'Cannot take inverse of singular matrix')
321             return
322
323         self.animate_between_matrices(matrix_start, matrix_target)
324
325     self.update_render_buttons()
```

We're deliberately not checking if the sub-expressions are valid here. We would normally validate the expression in `LintransMainWindow.update_render_buttons()` and only allow the user to render or

<sup>12</sup>I have since changed my thoughts on this, and I allowed sequential transitional animation much later, in commit 41907b81661f3878e435b794d9d719491ef14237



animate an expression if it's valid. Now we have to check all the sub-expressions if the expression contains commas. Additionally, we can only animate these expressions with commas in them, so rendering should be disabled when the expression contains commas.

Compare the old code to the new code:

```
# 4017b84fbce67d8e041bc9ce84cefc0b6e65e1f
# src/lintrans/gui/main_window.py

243     def update_render_buttons(self) -> None:
244         """Enable or disable the render and animate buttons according to whether the matrix expression is valid."""
245         valid = self.matrix_wrapper.is_valid_expression(self.lineEdit_expression_box.text())
246         self.button_render.setEnabled(valid)
247         self.button_animate.setEnabled(valid)

# 60584d2559cacbf23479a1bebbb986a800a32331
# src/lintrans/gui/main_window.py

243     def update_render_buttons(self) -> None:
244         """Enable or disable the render and animate buttons according to whether the matrix expression is valid."""
245         text = self.lineEdit_expression_box.text()
246
247         if ',' in text:
248             self.button_render.setEnabled(False)
249
250         valid = all(self.matrix_wrapper.is_valid_expression(x) for x in text.split(','))
251         self.button_animate.setEnabled(valid)
252
253     else:
254         valid = self.matrix_wrapper.is_valid_expression(text)
255         self.button_render.setEnabled(valid)
256         self.button_animate.setEnabled(valid)
```

## 3.5 Adding display settings

### 3.5.1 Creating the dataclass

The first step of adding display settings is creating a dataclass to hold all of the settings. This dataclass will hold attributes to manage how a matrix transformation is displayed. Things like whether to show eigenlines or the determinant parallelogram. It will also hold information for animation. We can factor out the code used to smoothen the determinant, as written in §3.3.6, and make it dependant on a `bool` attribute of the `DisplaySettings` dataclass.

This is a standard class rather than some form of singleton to allow different plots to have different display settings. For example, the user might want different settings for the main view and the visual definition dialog. Allowing each instance of a subclass of `VectorGridPlot` to have its own `DisplaySettings` attribute allows for separate settings for separate plots.

However, this class initially just contained attributes relevant to animation, so it was only an attribute on `LintransMainWindow`.

```
# 2041c7a24d963d8d142d6f0f20ec3828ba8257c6
# src/lintrans/gui/settings.py

1  """This module contains the :class:`DisplaySettings` class, which holds configuration for display."""
2
3  from dataclasses import dataclass
4
5
6  @dataclass
7  class DisplaySettings:
8      """This class simply holds some attributes to configure display."""
```

```

9
10     animate_determinant: bool = True
11     """This controls whether we want the determinant to change smoothly during the animation."""
12
13     applicative_animation: bool = True
14     """There are two types of simple animation, transitional and applicative.
15
16     Let ``C`` be the matrix representing the currently displayed transformation, and let ``T`` be the target matrix.
17     Transitional animation means that we animate directly from ``C`` from ``T``,
18     and applicative animation means that we animate from ``C`` to ``TC``, so we apply ``T`` to ``C``.
19     """
20
21     animation_pause_length: int = 400
22     """This is the number of milliseconds that we wait between animations when using comma syntax."""

```

Once I had the dataclass, I just had to add `from .settings import DisplaySettings` to the top of the file, and `self.display_settings = DisplaySettings()` to the constructor of `LintransMainWindow`. I could then use the attributes of this dataclass in `animate_expression()`.

```

# 2041c7a24d963d8d142d6f0f20ec3828ba8257c6
# src/lintrans/gui/main_window.py

286     def animate_expression(self) -> None:
287         """Animate from the current matrix to the matrix in the expression box."""
288         self.button_render.setEnabled(False)
289         self.button_animate.setEnabled(False)
290
291         matrix_start: MatrixType = np.array([
292             [self.plot.point_i[0], self.plot.point_j[0]],
293             [self.plot.point_i[1], self.plot.point_j[1]]
294         ])
295
296         text = self.lineedit_expression_box.text()
297
298         # If there's commas in the expression, then we want to animate each part at a time
299         if ',' in text:
300             current_matrix = matrix_start
301
302             # For each expression in the list, right multiply it by the current matrix,
303             # and animate from the current matrix to that new matrix
304             for expr in text.split(',')[::-1]:
305                 new_matrix = self.matrix_wrapper.evaluate_expression(expr) @ current_matrix
306
307                 self.animate_between_matrices(current_matrix, new_matrix)
308                 current_matrix = new_matrix
309
310             # Here we just redraw and allow for other events to be handled while we pause
311             self.plot.update()
312             QApplication.processEvents()
313             QThread.sleep(self.display_settings.animation_pause_length)
314
315         # If there's no commas, then just animate directly from the start to the target
316         else:
317             # Get the target matrix and it's determinant
318             try:
319                 matrix_target = self.matrix_wrapper.evaluate_expression(text)
320
321             except linalg.LinAlgError:
322                 self.show_error_message('Singular matrix', 'Cannot take inverse of singular matrix')
323                 return
324
325             # The concept of applicative animation is explained in /gui/settings.py
326             if self.display_settings.applicative_animation:
327                 matrix_target = matrix_target @ matrix_start
328
329             self.animate_between_matrices(matrix_start, matrix_target)
330
331         self.update_render_buttons()

```

I also wrapped the main logic of `animate_between_matrices()` in an `if` block to check if the user wants

the determinant to be smoothed.

```
# 03e154e1326dc256ffc1a539e97d8ef5ec89f6fd
# src/lintrans/gui/main_window.py

333     def animate_between_matrices(self, matrix_start: MatrixType, matrix_target: MatrixType, steps: int = 100) ->
334         ↪ None:
335         """Animate from the start matrix to the target matrix."""
336         det_target = linalg.det(matrix_target)
337         det_start = linalg.det(matrix_start)
338
339         for i in range(0, steps + 1):
340             # This proportion is how far we are through the loop
341             proportion = i / steps
342
343             # matrix_a is the start matrix plus some part of the target, scaled by the proportion
344             # If we just used matrix_a, then things would animate, but the determinants would be weird
345             matrix_a = matrix_start + proportion * (matrix_target - matrix_start)
346
347             if self.display_settings.animate_determinant and det_target != 0:
348                 # To fix the determinant problem, we get the determinant of matrix_a and use it to normalise
349                 det_a = linalg.det(matrix_a)
350
351                 # For a 2x2 matrix A and a scalar c, we know that det(cA) = c^2 det(A)
352                 # We want B = cA such that det(B) = det(S), where S is the start matrix,
353                 # so then we can scale it with the animation, so we get
354                 # det(cA) = c^2 det(A) = det(S) => c = sqrt(abs(det(S) / det(A)))
355                 # Then we scale A to get the determinant we want, and call that matrix_b
356                 if det_a == 0:
357                     c = 0
358                 else:
359                     c = np.sqrt(abs(det_start / det_a))
360
361                 matrix_b = c * matrix_a
362                 det_b = linalg.det(matrix_b)
363
364                 # matrix_to_render is the final matrix that we then render for this frame
365                 # It's B, but we scale it over time to have the target determinant
366
367                 # We want some C = dB such that det(C) is some target determinant T
368                 # det(dB) = d^2 det(B) = T => d = sqrt(abs(T / det(B)))
369
370                 # We're also subtracting 1 and multiplying by the proportion and then adding one
371                 # This just scales the determinant along with the animation
372                 scalar = 1 + proportion * (np.sqrt(abs(det_target / det_b)) - 1)
373                 matrix_to_render = scalar * matrix_b
374
375             else:
376                 matrix_to_render = matrix_a
377
378             if self.is_matrix_too_big(matrix_to_render):
379                 self.show_error_message('Matrix too big', "This matrix doesn't fit on the canvas")
380                 return
381
382             self.plot.visualize_matrix_transformation(matrix_to_render)
383
384             # We schedule the plot to be updated, tell the event loop to
385             # process events, and asynchronously sleep for 10ms
386             # This allows for other events to be processed while animating, like zooming in and out
387             self.plot.update()
388             QApplication.processEvents()
389             QThread.msleep(1000 // steps)
```

### 3.5.2 Creating the settings dialog

Display settings are good, but useless on their own. My next step was to add a settings dialog that would allow the user to edit these settings.

I first had to create the dialog class itself, so I created the `SettingsDialog` superclass first, so that I

could use it for global settings in the future, as well as the specific `DisplaySettingsDialog` subclass now.

As far as I know, a dialog in Qt can't really return a value when it's closed, so the dialog keeps a public instance attribute for the `DisplaySettings` class itself, and then the main window can copy that instance attribute when the dialog is closed.

```
# e4d3aa7eab70daecd16814972a281745110d64a5
# src/lintrans/gui/dialogs/settings.py

1  """This module provides dialogs to edit settings within the app."""
2
3  from __future__ import annotations
4
5  import abc
6  import copy
7
8  from PyQt5 import QtWidgets
9  from PyQt5.QtCore import Qt
10 from PyQt5.QtGui import QKeySequence
11 from PyQt5.QtWidgets import QCheckBox, QDialog, QHBoxLayout, QShortcut, QSizePolicy, QSpacerItem, QVBoxLayout
12
13 from lintrans.gui.settings import DisplaySettings
14
15
16 class SettingsDialog(QDialog):
17     """An abstract superclass for other simple dialogs."""
18
19     def __init__(self, *args, **kwargs):
20         """Create the widgets and layout of the dialog, passing ``*args`` and ``**kwargs`` to super."""
21         super().__init__(*args, **kwargs)
22
23         # === Create the widgets
24
25         self.button_confirm = QtWidgets.QPushButton(self)
26         self.button_confirm.setText('Confirm')
27         self.button_confirm.clicked.connect(self.confirm_settings)
28         self.button_confirm.setToolTip('Confirm these new settings<br><b>(Ctrl + Enter)</b>')
29         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self.button_confirm.click)
30
31         self.button_cancel = QtWidgets.QPushButton(self)
32         self.button_cancel.setText('Cancel')
33         self.button_cancel.clicked.connect(self.reject)
34         self.button_cancel.setToolTip('Cancel this definition<br><b>(Escape)</b>')
35
36         # === Arrange the widgets
37
38         self.setContentsMargins(10, 10, 10, 10)
39
40         self.hlay_buttons = QHBoxLayout()
41         self.hlay_buttons.setSpacing(20)
42         self.hlay_buttons.addItem(QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum))
43         self.hlay_buttons.addWidget(self.button_cancel)
44         self.hlay_buttons.addWidget(self.button_confirm)
45
46         self.vlay_options = QVBoxLayout()
47         self.vlay_options.setSpacing(20)
48
49         self.vlay_all = QVBoxLayout()
50         self.vlay_all.setSpacing(20)
51         self.vlay_all.addLayout(self.vlay_options)
52         self.vlay_all.addLayout(self.hlay_buttons)
53
54         self.setLayout(self.vlay_all)
55
56     @abc.abstractmethod
57     def load_settings(self) -> None:
58         """Load the current settings into the widgets."""
59
60     @abc.abstractmethod
61     def confirm_settings(self) -> None:
```

```

62         """Confirm the settings chosen in the dialog."""
63
64
65 class DisplaySettingsDialog(SettingsDialog):
66     """The dialog to allow the user to edit the display settings."""
67
68     def __init__(self, display_settings: DisplaySettings, *args, **kwargs):
69         """Create the widgets and layout of the dialog.
70
71         :param DisplaySettings display_settings: The :class:`lintrans.gui.settings.DisplaySettings` object to mutate
72         """
73         super().__init__(*args, **kwargs)
74
75         self.display_settings = display_settings
76         self.setWindowTitle('Change display settings')
77
78         # === Create the widgets
79
80         font_label = self.font()
81         font_label.setUnderline(True)
82         font_label.setPointSize(int(font_label.pointSize() * 1.2))
83
84         self.label_animations = QtWidgets.QLabel(self)
85         self.label_animations.setText('Animations')
86         self.label_animations.setAlignment(Qt.AlignCenter)
87         self.label_animations.setFont(font_label)
88
89         self.checkbox_animate_determinant = QCheckBox(self)
90         self.checkbox_animate_determinant.setText('Animate determinant')
91         self.checkbox_animate_determinant.setToolTip('Smoothly animate the determinant during animation')
92
93         self.checkbox_applicative_animation = QCheckBox(self)
94         self.checkbox_applicative_animation.setText('Applicative animation')
95         self.checkbox_applicative_animation.setToolTip(
96             'Animate the new transformation applied to the current one,\n'
97             'rather than just that transformation on its own'
98         )
99
100        # === Arrange the widgets
101
102        self.vlay_options.addWidget(self.label_animations)
103        self.vlay_options.addWidget(self.checkbox_animate_determinant)
104        self.vlay_options.addWidget(self.checkbox_applicative_animation)
105
106        # Finally, we load the current settings
107        self.load_settings()
108
109    def load_settings(self) -> None:
110        """Load the current display settings into the widgets."""
111        self.checkbox_animate_determinant.setChecked(self.display_settings.animate_determinant)
112        self.checkbox_applicative_animation.setChecked(self.display_settings.applicative_animation)
113
114    def confirm_settings(self) -> None:
115        """Build a :class:`lintrans.gui.settings.DisplaySettings` object and assign it."""
116        self.display_settings.animate_determinant = self.checkbox_animate_determinant.isChecked()
117        self.display_settings.applicative_animation = self.checkbox_applicative_animation.isChecked()
118
119        self.accept()

```

I then just had to enable the button in the main GUI and implement the method to open the new dialog. I have to use a lambda to capture the local `dialog` variable, but a separate method to actually assign its display settings, since Python doesn't allow assignments in lambda expressions.

```

# e4d3aa7eab70daecd16814972a281745110d64a5
# src/lintrans/gui/main_window.py

425 def dialog_change_display_settings(self) -> None:
426     """Open the dialog to change the display settings."""
427     dialog = DisplaySettingsDialog(self.display_settings, self)
428     dialog.open()

```

```
429         dialog.finished.connect(lambda: self._assign_display_settings(dialog.display_settings))
430
431     def _assign_display_settings(self, display_settings: DisplaySettings) -> None:
432         """Assign a new value to ``self.display_settings``."""
433         self.display_settings = display_settings
```

The `dialog.finished` signal on line 429 should really be `dialog.accepted`. Currently, we re-assign the display settings whenever the dialog is closed in any way. Really, we should only re-assign them when the user hits the confirm button, but trying to cancel the changes will currently save them. This was a silly mistake and I fixed it along with some similar signal-related bugs a few weeks later.

## References

- [1] Alan O'Callaghan (Alanocallaghan). *color-oracle-java*. Version 1.3. URL: <https://github.com/Alanocallaghan/color-oracle-java>.
- [2] D. Dyson (DoctorDalek1963). *lintrans*. URL: <https://github.com/DoctorDalek1963/lintrans>.
- [3] D. Dyson (DoctorDalek1963). *Which framework should I use for creating draggable points and connecting lines on a 2D grid?* 26th Jan. 2022. URL: <https://www.reddit.com/r/learnpython/comments/sd2lbr>.
- [4] Ross Wilson (rzzzwilson). *Python-Etudes/PyQtCustomWidget*. URL: <https://gitlab.com/rzzzwilson/python-etudes/-/tree/master/PyQtCustomWidget>.
- [5] Ross Wilson (rzzzwilson). *Python-Etudes/PyQtCustomWidget - ijvectors.py*. 26th Jan. 2022. URL: <https://gitlab.com/rzzzwilson/python-etudes/-/blob/2b43f5d3c95aa4410db5bed77195bf242318a304/PyQtCustomWidget/ijvectors.py>.
- [6] *2D linear transformation*. URL: <https://www.desmos.com/calculator/upooihuy4s>.
- [7] Grant Sanderson (3blue1brown). *Essence of Linear Algebra*. 6th Aug. 2016. URL: [https://www.youtube.com/playlist?list=PLZHQB0WTQDPD3MizzM2xVFitgF8hE\\_ab](https://www.youtube.com/playlist?list=PLZHQB0WTQDPD3MizzM2xVFitgF8hE_ab).
- [8] H. Hohn et al. *Matrix Vector*. MIT. 2001. URL: <https://mathlets.org/mathlets/matrix-vector/>.
- [9] Jacek Wodecki and ekhumoro. *How to update window in PyQt5?* URL: <https://stackoverflow.com/questions/42045676/how-to-update-window-in-pyqt5>.
- [10] jel324. *Visualizing Linear Transformations*. 15th Mar. 2018. URL: <https://www.geogebra.org/m/YCZa8TAH>.
- [11] Nathaniel Vaughn Kelso and Bernie Jenny. *Color Oracle*. Version 1.3. URL: <https://colororacle.org/>.
- [12] *Normalize a matrix such that the determinat = 1*. ResearchGate. 26th June 2017. URL: [https://www.researchgate.net/post/normalize\\_a\\_matrix\\_such\\_that\\_the\\_determinat\\_1](https://www.researchgate.net/post/normalize_a_matrix_such_that_the_determinat_1).
- [13] *Plotting with Matplotlib. Create PyQt5 plots with the popular Python plotting library*. URL: <https://www.pythonguis.com/tutorials/plotting-matplotlib/>.
- [14] *PyQt5 Graphics View Framework*. The Qt Company. URL: <https://doc.qt.io/qtforpython-5/overviews/graphicsview.html>.
- [15] *Python 3 Data model - special methods*. Python Software Foundation. URL: <https://docs.python.org/3/reference/datamodel.html#special-method-names>.
- [16] *Python 3.10 Downloads*. Python Software Foundation. URL: <https://www.python.org/downloads/release/python-3100/>.
- [17] *Qt5 for Linux/X11*. The Qt Company. URL: <https://doc.qt.io/qt-5/linux.html>.
- [18] *QWheelEvent class*. The Qt Company. URL: <https://doc.qt.io/qt-5/qwheelevent.html>.
- [19] *QWidget Class (mouseMoveEvent() method)*. The Qt Company. URL: <https://doc.qt.io/qt-5/qwidget.html#mouseMoveEvent>.
- [20] *QWidget Class (repaint() method)*. The Qt Company. URL: <https://doc.qt.io/qt-5/qwidget.html#repaint>.
- [21] *QWidget Class (update() method)*. The Qt Company. URL: <https://doc.qt.io/qt-5/qwidget.html#update>.
- [22] Shad Sharma. *Linear Transformation Visualizer*. 4th May 2017. URL: <https://shad.io/MatVis/>.
- [23] Rod Stephens. *Draw lines with arrowheads in C#*. 5th Dec. 2014. URL: [http://csharpshelper.com/howtos/howto\\_draw\\_arrows.html](http://csharpshelper.com/howtos/howto_draw_arrows.html).
- [24] *The Event System*. The Qt Company. URL: <https://doc.qt.io/qt-5/eventsandfilters.html>.
- [25] *Types of Color Blindness*. National Eye Institute. URL: <https://www.nei.nih.gov/learn-about-eye-health/eye-conditions-and-diseases/color-blindness/types-color-blindness>.

## A Project code

### A.1 global\_settings.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides the :class:`GlobalSettings` class, which is used to access global settings."""
8
9  from __future__ import annotations
10
11  import configparser
12  import os
13  import subprocess
14  import sys
15  from enum import Enum
16  from pathlib import Path
17
18  from singleton_decorator import singleton
19
20  _DEFAULT_CONFIG = '''
21  [General]
22  # Valid options are "auto", "prompt", or "never"
23  # An unknown option will default to "never"
24  Updates = prompt
25  '''[1:]
26
27
28  @singleton
29  class GlobalSettings():
30      """A singleton class to provide global settings that can be shared throughout the app.
31
32      .. note::
33          This is a singleton class because we only want :meth:`__init__` to be called once
34          to reduce processing time. We also can't cache it as a global variable because that
35          would be created at import time, leading to infinite process recursion when lintrans
36          tries to call its own executable to find out if it's compiled or interpreted.
37
38          The directory methods are split up into things like :meth:`get_save_directory` and
39          :meth:`get_crash_reports_directory` to make sure the directories exist and discourage
40          the use of other directories in the root one.
41      """
42
43      UpdateType = Enum('UpdateType', 'auto prompt never')
44
45      def __init__(self) -> None:
46          """Create the global settings object and initialize state."""
47          # The root directory is OS-dependent
48          if os.name == 'posix':
49              self._directory = os.path.join(
50                  os.path.expanduser('~'),
51                  '.lintrans'
52              )
53
54          elif os.name == 'nt':
55              self._directory = os.path.join(
56                  os.path.expandvars('%APPDATA%'),
57                  'lintrans'
58              )
59
60          else:
61              # This should be unreachable because the only other option for os.name is 'java'
62              # for Jython, but Jython only supports Python 2.7, which has been EOL for a while
63              # lintrans is only compatible with Python >= 3.8 anyway
64              raise OSError(f'Unrecognised OS "{os.name}"')
65
66          sub_directories = ['saves', 'crash_reports']
67

```



```

68         os.makedirs(self._directory, exist_ok=True)
69     for sub_directory in sub_directories:
70         os.makedirs(os.path.join(self._directory, sub_directory), exist_ok=True)
71
72     self._executable_path = ''
73
74     executable_path = sys.executable
75     if os.path.isfile(executable_path):
76         version_output = subprocess.run(
77             [executable_path, '--version'],
78             stdout=subprocess.PIPE,
79             shell=(os.name == 'nt')
80         ).stdout.decode()
81
82         if 'lintrans' in version_output:
83             self._executable_path = executable_path
84
85     self._settings_file = os.path.join(self._directory, 'settings.ini')
86     config = configparser.ConfigParser()
87     config.read(self._settings_file)
88
89     try:
90         self._general_settings = config['General']
91     except KeyError:
92         with open(self._settings_file, 'w', encoding='utf-8') as f:
93             f.write(_DEFAULT_CONFIG)
94
95         default_config = configparser.ConfigParser()
96         default_config.read(self._settings_file)
97
98         self._general_settings = default_config['General']
99
100 def get_save_directory(self) -> str:
101     """Return the default directory for save files."""
102     return os.path.join(self._directory, 'saves')
103
104 def get_crash_reports_directory(self) -> str:
105     """Return the default directory for crash reports."""
106     return os.path.join(self._directory, 'crash_reports')
107
108 def get_executable_path(self) -> str:
109     """Return the path to the binary executable, or an empty string if lintrans is not installed standalone."""
110     return self._executable_path
111
112 def get_update_type(self) -> UpdateType:
113     """Return the update type defined in the settings file."""
114     try:
115         update_type = self._general_settings['Updates'].lower()
116     except KeyError:
117         return self.UpdateType.never
118
119     # This is just to satisfy mypy and ensure that we return the Literal
120     if update_type == 'auto':
121         return self.UpdateType.auto
122
123     if update_type == 'prompt':
124         return self.UpdateType.prompt
125
126     return self.UpdateType.never
127
128 def set_update_type(self, update_type: UpdateType) -> None:
129     """Set the update type in the settings file to the given type."""
130     self._general_settings['Updates'] = update_type.name
131
132     new_settings_file = _DEFAULT_CONFIG.replace(
133         'Updates = prompt',
134         f'Updates = {update_type.name}'
135     )
136
137     with open(self._settings_file, 'w', encoding='utf-8') as f:
138         f.write(new_settings_file)
139
140 def get_settings_file(self) -> str:

```

```

141         """Return the full path of the settings file."""
142         return self._settings_file
143
144     def get_update_download_filename(self) -> str:
145         """Return a name for a temporary file next to the executable.
146
147         This method is used when downloading a new version of lintrans into a temporary file.
148         This is needed to allow :func:`os.rename` instead of :func:`shutil.move`. The first
149         requires the src and dest to be on the same partition, but also allows us to replace
150         the running executable.
151         """
152         return str(Path(self._executable_path).parent / 'lintrans-update-temp.dat')
153
154     def get_update_replace_bat_filename(self) -> str:
155         """Return the full path of the ``replace.bat`` file needed to update on Windows.
156
157         See :meth:`get_update_download_filename`.
158         """
159         return str(Path(self._executable_path).parent / 'replace.bat')

```

## A.2 updating.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides functions for updating the lintrans executable in a proper installation.
8
9  If the user is using a standalone executable for lintrans, then we don't know where it is and
10 we therefore can't update it.
11 """
12
13 from __future__ import annotations
14
15 import os
16 import re
17 import subprocess
18 from threading import Thread
19 from typing import Optional, Tuple
20 from urllib.error import URLError
21 from urllib.request import urlopen
22
23 from packaging import version
24
25 from lintrans.global_settings import GlobalSettings
26
27
28 def new_version_exists() -> Tuple[bool, Optional[str]]:
29     """Check if the latest version of lintrans is newer than the current version.
30
31     This function either returns (False, None) or (True, str) where the string is the new version.
32
33     .. note::
34         This function will default to False if it can't get the current or latest version, or if
35         :meth:`~lintrans.global_settings.GlobalSettings.get_executable_path` returns ''
36         (probablybecause lintrans is being run as a Python package)
37
38         However, it will return True if the executable path is defined but the executable doesn't actually exist.
39
40         This last behaviour is mostly to make testing easier by spoofing
41         :meth:`~lintrans.global_settings.GlobalSettings.get_executable_path`.
42     """
43     executable_path = GlobalSettings().get_executable_path()
44     if executable_path == '':
45         return False, None
46
47     try:
48         html: str = urlopen('https://github.com/DoctorDalek1963/lintrans/releases/latest').read().decode()

```

```

49     except (UnicodeDecodeError, URLError):
50         return False, None
51
52     match = re.search(
53         r'(?<=DoctorDalek1963/lintrans/releases/tag/v)\d+\.\d+\.\d+(?=?;)',
54         html
55     )
56     if match is None:
57         return False, None
58
59     latest_version_str = match.group(0)
60     latest_version = version.parse(latest_version_str)
61
62     # If the executable doesn't exist, then we definitely want to update it
63     if not os.path.isfile(executable_path):
64         return True, latest_version_str
65
66     # Now check the current version
67     version_output = subprocess.run(
68         [executable_path, '--version'],
69         stdout=subprocess.PIPE,
70         shell=(os.name == 'nt')
71     ).stdout.decode()
72
73     match = re.search(r'(?<=lintrans \(\version \)\d+\.\d+\.\d+(-\w+(-?\d+))?(?=\))', version_output)
74
75     if match is None:
76         return False, None
77
78     current_version = version.parse(match.group(0))
79
80     if latest_version > current_version:
81         return True, latest_version_str
82
83     return False, None
84
85
86 def update_lintrans() -> None:
87     """Update the lintrans binary executable, failing silently.
88
89     This function only makes sense if lintrans was installed, rather than being used as an executable.
90     We ask the :class:`~lintrans.global_settings.GlobalSettings` singleton where the executable is and,
91     if it exists, then we replace the old executable with the new one. This means that the next time
92     lintrans gets run, it will use the most recent version.
93
94     .. note::
95         This function doesn't care if the latest version on GitHub is actually newer than the current
96         version. Use :func:`new_version_exists` to check.
97     """
98     executable_path = GlobalSettings().get_executable_path()
99     if executable_path == '':
100         return
101
102     try:
103         html: str = urlopen('https://github.com/DoctorDalek1963/lintrans/releases/latest').read().decode()
104     except (UnicodeDecodeError, URLError):
105         return
106
107     match = re.search(
108         r'(?<=DoctorDalek1963/lintrans/releases/tag/v)\d+\.\d+\.\d+(?=?;)',
109         html
110     )
111     if match is None:
112         return
113
114     latest_version = version.parse(match.group(0))
115
116     # We now know that the latest version is newer, and where the executable is,
117     # so we can begin the replacement process
118     url = 'https://github.com/DoctorDalek1963/lintrans/releases/download/'
119
120     if os.name == 'posix':
121         url += f'v{latest_version}/lintrans-Linux-{latest_version}'

```

```

122
123     elif os.name == 'nt':
124         url += f'v{latest_version}/lintrans-Windows-{latest_version}.exe'
125
126     else:
127         return
128
129     temp_file = GlobalSettings().get_update_download_filename()
130
131     # If the temp file already exists, then another instance of lintrans (probably
132     # in a background thread) is currently updating, so we don't want to interfere
133     if os.path.isfile(temp_file):
134         return
135
136     with open(temp_file, 'wb') as f:
137         try:
138             f.write(urlopen(url).read())
139         except URLError:
140             return
141
142     if os.name == 'posix':
143         os.rename(temp_file, executable_path)
144         subprocess.run(['chmod', '+x', executable_path])
145
146     elif os.name == 'nt':
147         # On Windows, we need to leave a process running in the background to automatically
148         # replace the exe file when lintrans stops running
149         script = '@echo off\n' \
150             ':loop\n\n' \
151             'timeout 5 >nul\n' \
152             'tasklist /fi "IMAGENAME eq lintrans.exe" /fo csv 2>nul | find /I "lintrans.exe" >nul\n' \
153             'if "%ERRORLEVEL%"=="0" goto :loop\n\n' \
154             f'del "{executable_path}"\n\n' \
155             f'rename "{temp_file}" lintrans.exe\n\n' \
156             'start /b "" cmd /c del "%~f0"&exit /b'
157
158         replace_bat = GlobalSettings().get_update_replace_bat_filename()
159         with open(replace_bat, 'w', encoding='utf-8') as f:
160             f.write(script)
161
162         subprocess.Popen(['start', '/min', replace_bat], shell=True)
163
164
165 def update_lintrans_in_background(*, check: bool) -> None:
166     """Use multithreading to run :func:`update_lintrans` in the background."""
167     def func() -> None:
168         if check:
169             if new_version_exists()[0]:
170                 update_lintrans()
171         else:
172             update_lintrans()
173
174     p = Thread(target=func)
175     p.start()

```

### A.3 crash\_reporting.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides functions to report crashes and log them.
8
9  The only functions you should be calling directly are :func:`set_excepthook`
10 and :func:`set_signal_handler` to setup handlers for unhandled exceptions
11 and unhandled operating system signals respectively.
12 """
13

```

```

14 from __future__ import annotations
15
16 import os
17 import platform
18 import signal
19 import sys
20 from datetime import datetime
21 from signal import SIGABRT, SIGFPE, SIGILL, SIGSEGV, SIGTERM
22 from textwrap import indent
23 from types import FrameType, TracebackType
24 from typing import NoReturn, Type
25
26 from PyQt5.QtCore import PYQT_VERSION_STR, QT_VERSION_STR
27 from PyQt5.QtWidgets import QApplication
28
29 import lintrans
30 from lintrans.typing_ import is_matrix_type
31
32 from .global_settings import GlobalSettings
33 from .gui.main_window import LintransMainWindow
34
35
36 def _get_datetime_string() -> str:
37     """Get the date and time as a string with a space in the middle."""
38     return datetime.now().strftime('%Y-%m-%d %H:%M:%S')
39
40
41 def _get_main_window() -> LintransMainWindow:
42     """Return the only instance of :class:`~lintrans.gui.main_window.LintransMainWindow`.
43
44     :raises RuntimeError: If there is not exactly 1 instance of
45     ↪ :class:`~lintrans.gui.main_window.LintransMainWindow`
46     """
47     widgets = [
48         x for x in QApplication.topLevelWidgets()
49         if isinstance(x, LintransMainWindow)
50     ]
51
52     if len(widgets) != 1:
53         raise RuntimeError(f'Expected 1 widget of type LintransMainWindow but found {len(widgets)}')
54
55     return widgets[0]
56
57 def _get_system_info() -> str:
58     """Return a string of all the system we could gather."""
59     info = 'SYSTEM INFO:\n'
60
61     info += f'  lintrans: {lintrans.__version__}\n'
62     info += f'  Python: {platform.python_version()}\n'
63     info += f'  Qt5: {QT_VERSION_STR}\n'
64     info += f'  PyQt5: {PYQT_VERSION_STR}\n'
65     info += f'  Platform: {platform.platform()}\n'
66
67     info += '\n'
68     return info
69
70
71 def _get_error_origin(
72     *,
73     exc_type: Type[BaseException] | None,
74     exc_value: BaseException | None,
75     traceback: TracebackType | None,
76     signal_number: int | None,
77     stack_frame: FrameType | None
78 ) -> str:
79     """Return a string specifying the full origin of the error, as best as we can determine.
80
81     This function has effectively two signatures. If the fatal error is caused by an exception,
82     then the first 3 arguments will be used to match the signature of :func:`~sys.excepthook`.
83     If it's caused by a signal, then the last two will be used to match the signature of the
84     handler in :func:`~signal.signal`. This function should never be used outside this file, so
85     we don't account for a mixture of arguments.

```

```

86
87     :param exc_type: The type of the exception that caused the crash
88     :param exc_value: The value of the exception itself
89     :param traceback: The traceback object
90     :param signal_number: The number of the signal that caused the crash
91     :param stack_frame: The current stack frame object
92
93     :type exc_type: Type[BaseException] | None
94     :type exc_value: BaseException | None
95     :type traceback: types.TracebackType | None
96     :type signal_number: int | None
97     :type stack_frame: types.FrameType | None
98     """
99     origin = 'CRASH ORIGIN:\n'
100
101     if exc_type is not None and exc_value is not None and traceback is not None:
102         # We want the frame where the exception actually occurred, so we have to descend the traceback
103         # I don't know why we aren't given this traceback in the first place
104         tb = traceback
105         while tb.tb_next is not None:
106             tb = tb.tb_next
107
108         frame = tb.tb_frame
109
110         origin += f' Exception "{exc_value}"\n of type {exc_type.__name__} in call to {frame.f_code.co_name}()\n'
111         ↪ f' on line {frame.f_lineno} of {frame.f_code.co_filename}'
112
113     elif signal_number is not None and stack_frame is not None:
114         origin += f' Signal "{signal.strsignal(signal_number)}" received in call to
115         ↪ {stack_frame.f_code.co_name}()\n' \
116         f' on line {stack_frame.f_lineno} of {stack_frame.f_code.co_filename}'
117
118     else:
119         origin += ' UNKNOWN (not exception or signal)'
120
121     origin += '\n\n'
122     return origin
123
124
125 def _get_display_settings() -> str:
126     """Return a string representing all of the display settings."""
127     display_settings = {
128         k: v
129         for k, v in _get_main_window()._plot.display_settings.__dict__.items()
130         if not k.startswith('_')
131     }
132
133     string = 'Display settings:\n'
134
135     for setting, value in display_settings.items():
136         string += f' {setting}: {value}\n'
137
138     return string
139
140
141 def _get_post_mortem() -> str:
142     """Return whatever post mortem data we could gather from the window."""
143     window = _get_main_window()
144
145     try:
146         matrix_wrapper = window._matrix_wrapper
147         expression_history = window._expression_history
148         exp_hist_index = window._expression_history_index
149         plot = window._plot
150         point_i = plot.point_i
151         point_j = plot.point_j
152
153     except (AttributeError, RuntimeError) as e:
154         return f'UNABLE TO GET POST MORTEM DATA:\n {e!r}\n'
155
156     post_mortem = 'Matrix wrapper:\n'

```

```

157
158     for matrix_name, matrix_value in matrix_wrapper.get_defined_matrices():
159         post_mortem += f'    {matrix_name}: '
160
161         if is_matrix_type(matrix_value):
162             post_mortem += f'[{matrix_value[0][0]} {matrix_value[0][1]}; {matrix_value[1][0]} {matrix_value[1][1]}]'
163         else:
164             post_mortem += f'"{matrix_value}"'
165
166         post_mortem += '\n'
167
168     post_mortem += f'\nExpression box: "{window._linedit_expression_box.text()}"'
169     post_mortem += f'\nCurrently displayed: [{point_i[0]} {point_j[0]}; {point_i[1]} {point_j[1]}]'
170     post_mortem += f'\nAnimating (sequence): {window._animating} ({window._animating_sequence})\n'
171
172     post_mortem += f'\nExpression history (index={exp_hist_index}):'
173     post_mortem += '\n ['
174     for item in expression_history:
175         post_mortem += f'\n     {item!r},'
176     post_mortem += '\n ]\n'
177
178     post_mortem += f'\nGrid spacing: {plot.grid_spacing}'
179     post_mortem += f'\nWindow size: {window.width()} x {window.height()}'
180     post_mortem += f'\nViewport size: {plot.width()} x {plot.height()}'
181     post_mortem += f'\nGrid corner: {plot._grid_corner()}\n'
182
183     post_mortem += '\n' + _get_display_settings()
184
185     string = 'POST MORTEM:\n'
186     string += indent(post_mortem, ' ')
187     return string
188
189
190 def _get_crash_report(datetime_string: str, error_origin: str) -> str:
191     """Return a string crash report, ready to be written to a file and stderr.
192
193     :param str datetime_string: The datetime to use in the report; should be the same as the one in the filename
194     :param str error_origin: The origin of the error. Get this by calling :func:`_get_error_origin`
195     """
196     report = f'CRASH REPORT at {datetime_string}\n\n'
197     report += _get_system_info()
198     report += error_origin
199     report += _get_post_mortem()
200
201     return report
202
203
204 def _report_crash(
205     *,
206     exc_type: Type[BaseException] | None = None,
207     exc_value: BaseException | None = None,
208     traceback: TracebackType | None = None,
209     signal_number: int | None = None,
210     stack_frame: FrameType | None = None
211 ) -> NoReturn:
212     """Generate a crash report and write it to a log file and stderr.
213
214     See :func:`_get_error_origin` for an explanation of the arguments. Everything is
215     handled internally if you just use the public functions :func:`set_excepthook` and
216     :func:`set_signal_handler`.
217     """
218     datetime_string = _get_datetime_string()
219
220     filename = os.path.join(
221         GlobalSettings().get_crash_reports_directory(),
222         datetime_string.replace(" ", "_") + '.log'
223     )
224     report = _get_crash_report(
225         datetime_string,
226         _get_error_origin(
227             exc_type=exc_type,
228             exc_value=exc_value,
229             traceback=traceback,

```

```

230         signal_number=signal_number,
231         stack_frame=stack_frame
232     )
233 )
234
235 print('\n\n' + report, end='', file=sys.stderr)
236 with open(filename, 'w', encoding='utf-8') as f:
237     f.write(report)
238
239 sys.exit(255)
240
241
242 def set_excepthook() -> None:
243     """Change :func:`sys.excepthook` to generate a crash report first."""
244     def _custom_excepthook(
245         exc_type: Type[BaseException],
246         exc_value: BaseException,
247         traceback: TracebackType | None
248     ) -> None:
249         _report_crash(exc_type=exc_type, exc_value=exc_value, traceback=traceback)
250
251     sys.excepthook = _custom_excepthook
252
253
254 def set_signal_handler() -> None:
255     """Set the signal handlers to generate crash reports first."""
256     def _handler(number, frame) -> None:
257         _report_crash(signal_number=number, stack_frame=frame)
258
259     for sig_num in (SIGABRT, SIGFPE, SIGILL, SIGSEGV, SIGTERM):
260         if sig_num in signal.valid_signals():
261             signal.signal(sig_num, _handler)
262
263     try:
264         from signal import SIGQUIT
265         signal.signal(SIGQUIT, _handler)
266     except ImportError:
267         pass

```

## A.4 \_\_main\_\_.py

```

1  #!/usr/bin/env python
2
3  # lintrans - The linear transformation visualizer
4  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
5
6  # This program is licensed under GNU GPLv3, available here:
7  # <https://www.gnu.org/licenses/gpl-3.0.html>
8
9  """This module provides a :func:`main` function to interpret command line arguments and run the program."""
10
11 from argparse import ArgumentParser
12 from textwrap import dedent
13
14 from lintrans import __version__, gui
15 from lintrans.crash_reporting import set_excepthook, set_signal_handler
16
17
18 def main() -> None:
19     """Interpret program-specific command line arguments and run the main window in most cases.
20
21     If the user supplies ``--help`` or ``--version``, then we simply respond to that and then return.
22     If they don't supply either of these, then we run :func:`lintrans.gui.main_window.main`.
23
24     :param List[str] args: The full argument list (including program name)
25     """
26     parser = ArgumentParser(add_help=False)
27
28     parser.add_argument(
29         'filename',

```



```

30     nargs='?',
31     type=str,
32     default=None
33 )
34
35 parser.add_argument(
36     '-h',
37     '--help',
38     default=False,
39     action='store_true'
40 )
41
42 parser.add_argument(
43     '-V',
44     '--version',
45     default=False,
46     action='store_true'
47 )
48
49 parsed_args = parser.parse_args()
50
51 if parsed_args.help:
52     print(dedent('''
53     Usage: lintrans [option] [filename]
54
55     Arguments:
56         filename          The name of a session file to open
57
58     Options:
59         -h, --help        Display this help text and exit
60         -V, --version      Display the version information and exit'''[1:]))
61     return
62
63 if parsed_args.version:
64     print(dedent(f'''
65     lintrans (version {__version__})
66     The linear transformation visualizer
67
68     Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
69
70     This program is licensed under GNU GPLv3, available here:
71     <https://www.gnu.org/licenses/gpl-3.0.html>'''[1:]))
72     return
73
74 gui.main(parsed_args.filename)
75
76
77 if __name__ == '__main__':
78     set_excepthook()
79     set_signal_handler()
80     main()

```

## A.5 \_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This is the top-level ``lintrans`` package, which contains all the subpackages of the project."""
8
9  from . import (crash_reporting, global_settings, gui, matrices, typing_,
10                updating)
11
12  __version__ = '0.4.0-alpha'
13
14  __all__ = ['crash_reporting', 'global_settings', 'gui', 'matrices', 'typing_', 'updating', '__version__']

```

## A.6 gui/main\_window.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides the :class:`LintransMainWindow` class, which provides the main window for the GUI."""
8
9  from __future__ import annotations
10
11  import os
12  import re
13  import sys
14  import webbrowser
15  from copy import deepcopy
16  from pathlib import Path
17  from pickle import UnpicklingError
18  from typing import List, NoReturn, Optional, Type
19
20  import numpy as np
21  from numpy import linalg
22  from numpy.linalg import LinAlgError
23  from PyQt5 import QtWidgets
24  from PyQt5.QtCore import QObject, Qt, QThread, pyqtSignal, pyqtSlot
25  from PyQt5.QtGui import QCloseEvent, QIcon, QKeyEvent, QKeySequence
26  from PyQt5.QtWidgets import QAction, QApplication, QFileDialog, QHBoxLayout,
27  QMainWindow, QMenu, QMessageBox, QPushButton,
28  QShortcut, QSizePolicy, QSpacerItem,
29  QStyleFactory, QVBoxLayout)
30
31  import lintrans
32  from lintrans import updating
33  from lintrans.global_settings import GlobalSettings
34  from lintrans.matrices import MatrixWrapper
35  from lintrans.matrices.parse import validate_matrix_expression
36  from lintrans.matrices.utility import polar_coords, rotate_coord
37  from lintrans.typing import MatrixType, VectorType
38
39  from .dialogs import (AboutDialog, DefineAsExpressionDialog,
40  DefineMatrixDialog, DefineNumericallyDialog,
41  DefinePolygonDialog, DefineVisuallyDialog,
42  DisplaySettingsDialog, FileSelectDialog, InfoPanelDialog,
43  PromptUpdateDialog)
44  from .plots import MainViewportWidget
45  from .session import Session
46  from .settings import DisplaySettings
47  from .utility import qapp
48  from .validate import MatrixExpressionValidator
49
50
51  class _UpdateChecker(QObject):
52      """A simple class to act as a worker for a :class:`QThread`."""
53
54      signal_prompt_update: pyqtSignal = pyqtSignal(str)
55      """A signal that is emitted if a new version is found. The argument is the new version string."""
56
57      finished: pyqtSignal = pyqtSignal()
58      """A signal that is emitted when the worker has finished. Intended to be used for cleanup."""
59
60      def check_for_updates_and_emit(self) -> None:
61          """Check for updates, and emit :attr:`signal_prompt_update` if there's a new version.
62
63          This method exists to be run in a background thread to trigger a prompt if a new version is found.
64          """
65          update_type = GlobalSettings().get_update_type()
66
67          if update_type == GlobalSettings().UpdateType.never:
68              return
69
70          if update_type == GlobalSettings().UpdateType.auto:

```

```

71         updating.update_lintrans_in_background(check=True)
72         return
73
74     # If we get here, then update_type must be prompt,
75     # so we can check for updates and possibly prompt the user
76     new, version = updating.new_version_exists()
77     if new:
78         self.signal_prompt_update.emit(version)
79
80     self.finished.emit()
81
82
83 class LintransMainWindow(QMainWindow):
84     """This class provides a main window for the GUI using the Qt framework.
85
86     This class should not be used directly, instead call :func:`main` to create the GUI.
87     """
88
89     def __init__(self):
90         """Create the main window object, and create and arrange every widget in it.
91
92         This doesn't show the window, it just constructs it. Use :func:`main` to show the GUI.
93         """
94         super().__init__()
95
96         self._matrix_wrapper = MatrixWrapper()
97
98         self._expression_history: List[str] = []
99         self._expression_history_index: Optional[int] = None
100
101         self.setWindowTitle('[*]lintrans')
102         self.setMinimumSize(800, 650)
103
104         path = Path(__file__).parent.absolute() / 'assets' / 'icon.jpg'
105         self.setWindowIcon(QIcon(str(path)))
106
107         self._animating: bool = False
108         self._animating_sequence: bool = False
109         self._reset_during_animation: bool = False
110
111         self._save_filename: Optional[str] = None
112
113         # Set up thread and worker to check for updates
114
115         self._thread_updates = QThread()
116         self._worker_updates = _UpdateChecker()
117         self._worker_updates.moveToThread(self._thread_updates)
118
119         self._thread_updates.started.connect(self._worker_updates.check_for_updates_and_emit)
120         self._worker_updates.signal_prompt_update.connect(self._prompt_update)
121         self._worker_updates.finished.connect(self._thread_updates.quit)
122         self._worker_updates.finished.connect(self._worker_updates.deleteLater)
123         self._thread_updates.finished.connect(self._thread_updates.deleteLater)
124
125         # === Create menubar
126
127         menubar = QtWidgets.QMenuBar(self)
128
129         menu_file = QMenu(menubar)
130         menu_file.setTitle('&File')
131
132         menu_help = QMenu(menubar)
133         menu_help.setTitle('&Help')
134
135         action_reset_session = QAction(self)
136         action_reset_session.setText('Reset session')
137         action_reset_session.triggered.connect(self._reset_session)
138
139         action_open = QAction(self)
140         action_open.setText('&Open')
141         action_open.setShortcut('Ctrl+O')
142         action_open.triggered.connect(self._ask_for_session_file)
143

```

```

144     action_save = QAction(self)
145     action_save.setText('&Save')
146     action_save.setShortcut('Ctrl+S')
147     action_save.triggered.connect(self._save_session)
148
149     action_save_as = QAction(self)
150     action_save_as.setText('Save as...')
151     action_save_as.setShortcut('Ctrl+Shift+S')
152     action_save_as.triggered.connect(self._save_session_as)
153
154     action_quit = QAction(self)
155     action_quit.setText('&Quit')
156     action_quit.triggered.connect(self.close)
157
158     # If this is an old release, use the docs for this release. Else, use the latest docs
159     # We use the latest because most use cases for non-stable releases will be in development and testing
160     docs_link = 'https://lintrans.readthedocs.io/en/'
161
162     if re.match(r'^\d+\.\d+\.\d+$', lintrans.__version__):
163         docs_link += 'v' + lintrans.__version__
164     else:
165         docs_link += 'latest'
166
167     action_tutorial = QAction(self)
168     action_tutorial.setText('&Tutorial')
169     action_tutorial.setShortcut('F1')
170     action_tutorial.triggered.connect(
171         lambda: webbrowser.open_new_tab(docs_link + '/tutorial/index.html')
172     )
173
174     action_docs = QAction(self)
175     action_docs.setText('&Docs')
176     action_docs.triggered.connect(
177         lambda: webbrowser.open_new_tab(docs_link + '/backend/lintrans.html')
178     )
179
180     menu_feedback = QMenu(menu_help)
181     menu_feedback.setTitle('Give feedback')
182
183     action_bug_report = QAction(self)
184     action_bug_report.setText('Report a bug')
185     action_bug_report.triggered.connect(
186         lambda: webbrowser.open_new_tab('https://forms.gle/Q82cLTtgPLcV4xQD6')
187     )
188
189     action_suggest_feature = QAction(self)
190     action_suggest_feature.setText('Suggest a new feature')
191     action_suggest_feature.triggered.connect(
192         lambda: webbrowser.open_new_tab('https://forms.gle/mVWbHiMBw9Zq5Ze37')
193     )
194
195     menu_feedback.addAction(action_bug_report)
196     menu_feedback.addAction(action_suggest_feature)
197
198     action_about = QAction(self)
199     action_about.setText('&About')
200     action_about.triggered.connect(lambda: AboutDialog(self).open())
201
202     menu_file.addAction(action_reset_session)
203     menu_file.addAction(action_open)
204     menu_file.addSeparator()
205     menu_file.addAction(action_save)
206     menu_file.addAction(action_save_as)
207     menu_file.addSeparator()
208     menu_file.addAction(action_quit)
209
210     menu_help.addAction(action_tutorial)
211     menu_help.addAction(action_docs)
212     menu_help.addSeparator()
213     menu_help.addMenu(menu_feedback)
214     menu_help.addSeparator()
215     menu_help.addAction(action_about)
216

```

```

217     menubar.addAction(menu_file.menuAction())
218     menubar.addAction(menu_help.menuAction())
219
220     self.setMenuBar(menubar)
221
222     # === Create widgets
223
224     # Left layout: the plot and input box
225
226     self._plot = MainViewportWidget(self, display_settings=DisplaySettings(), polygon_points=[])
227
228     self._lineEdit_expression_box = QtWidgets.QLineEdit(self)
229     self._lineEdit_expression_box.setPlaceholderText('Enter matrix expression...')
230     self._lineEdit_expression_box.setValidator(MatrixExpressionValidator(self))
231     self._lineEdit_expression_box.textChanged.connect(self._update_render_buttons)
232
233     # Right layout: all the buttons
234
235     # Misc buttons
236
237     button_define_polygon = QPushButton(self)
238     button_define_polygon.setText('Define polygon')
239     button_define_polygon.clicked.connect(self._dialog_define_polygon)
240     button_define_polygon.setToolTip('Define a polygon to view its transformation<br><b>(Ctrl + P)</b>')
241     QShortcut(QKeySequence('Ctrl+P'), self).activated.connect(button_define_polygon.click)
242
243     self._button_change_display_settings = QPushButton(self)
244     self._button_change_display_settings.setText('Change\ndisplay settings')
245     self._button_change_display_settings.clicked.connect(self._dialog_change_display_settings)
246     self._button_change_display_settings.setToolTip(
247         "Change which things are rendered and how they're rendered<br><b>(Ctrl + D)</b>"
248     )
249     QShortcut(QKeySequence('Ctrl+D'), self).activated.connect(self._button_change_display_settings.click)
250
251     button_reset_zoom = QPushButton(self)
252     button_reset_zoom.setText('Reset zoom')
253     button_reset_zoom.clicked.connect(self._reset_zoom)
254     button_reset_zoom.setToolTip('Reset the zoom level back to normal<br><b>(Ctrl + Shift + R)</b>')
255     QShortcut(QKeySequence('Ctrl+Shift+R'), self).activated.connect(button_reset_zoom.click)
256
257     # Define new matrix buttons and their groupbox
258
259     self._button_define_visually = QPushButton(self)
260     self._button_define_visually.setText('Visually')
261     self._button_define_visually.setToolTip('Drag the basis vectors<br><b>(Alt + 1)</b>')
262     self._button_define_visually.clicked.connect(lambda: self._dialog_define_matrix(DefineVisuallyDialog))
263     QShortcut(QKeySequence('Alt+1'), self).activated.connect(self._button_define_visually.click)
264
265     self._button_define_numerically = QPushButton(self)
266     self._button_define_numerically.setText('Numerically')
267     self._button_define_numerically.setToolTip('Define a matrix just with numbers<br><b>(Alt + 2)</b>')
268     self._button_define_numerically.clicked.connect(lambda: self._dialog_define_matrix(DefineNumericallyDialog))
269     QShortcut(QKeySequence('Alt+2'), self).activated.connect(self._button_define_numerically.click)
270
271     self._button_define_as_expression = QPushButton(self)
272     self._button_define_as_expression.setText('As an expression')
273     self._button_define_as_expression.setToolTip('Define a matrix in terms of other matrices<br><b>(Alt +
274     ↩ 3)</b>')
275     self._button_define_as_expression.clicked.connect(
276         lambda: self._dialog_define_matrix(DefineAsExpressionDialog)
277     )
278     QShortcut(QKeySequence('Alt+3'), self).activated.connect(self._button_define_as_expression.click)
279
280     vlay_define_new_matrix = QVBoxLayout()
281     vlay_define_new_matrix.setSpacing(20)
282     vlay_define_new_matrix.addWidget(self._button_define_visually)
283     vlay_define_new_matrix.addWidget(self._button_define_numerically)
284     vlay_define_new_matrix.addWidget(self._button_define_as_expression)
285
286     groupbox_define_new_matrix = QtWidgets.QGroupBox('Define a new matrix', self)
287     groupbox_define_new_matrix.setLayout(vlay_define_new_matrix)
288
289     # Info panel button

```

```

289
290     self._button_info_panel = QPushButton(self)
291     self._button_info_panel.setText('Show defined matrices')
292     self._button_info_panel.clicked.connect(self._open_info_panel)
293     self._button_info_panel.setToolTip(
294         'Open an info panel with all matrices that have been defined in this session<br><b>(Ctrl + M)</b>'
295     )
296     QShortcut(QKeySequence('Ctrl+M'), self).activated.connect(self._button_info_panel.click)
297
298     # Render buttons
299
300     button_reset = QPushButton(self)
301     button_reset.setText('Reset')
302     button_reset.clicked.connect(self._reset_transformation)
303     button_reset.setToolTip('Reset the visualized transformation back to the identity<br><b>(Ctrl + R)</b>')
304     QShortcut(QKeySequence('Ctrl+R'), self).activated.connect(button_reset.click)
305
306     self._button_render = QPushButton(self)
307     self._button_render.setText('Render')
308     self._button_render.setEnabled(False)
309     self._button_render.clicked.connect(self._render_expression)
310     self._button_render.setToolTip('Render the expression<br><b>(Ctrl + Enter)</b>')
311     QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self._button_render.click)
312
313     self._button_animate = QPushButton(self)
314     self._button_animate.setText('Animate')
315     self._button_animate.setEnabled(False)
316     self._button_animate.clicked.connect(self._animate_expression)
317     self._button_animate.setToolTip('Animate the expression<br><b>(Ctrl + Shift + Enter)</b>')
318     QShortcut(QKeySequence('Ctrl+Shift+Return'), self).activated.connect(self._button_animate.click)
319
320     # === Arrange widgets
321
322     vlay_left = QVBoxLayout()
323     vlay_left.addWidget(self._plot)
324     vlay_left.addWidget(self._lineedit_expression_box)
325
326     vlay_misc_buttons = QVBoxLayout()
327     vlay_misc_buttons.setSpacing(20)
328     vlay_misc_buttons.addWidget(button_define_polygon)
329     vlay_misc_buttons.addWidget(self._button_change_display_settings)
330     vlay_misc_buttons.addWidget(button_reset_zoom)
331
332     vlay_info_buttons = QVBoxLayout()
333     vlay_info_buttons.setSpacing(20)
334     vlay_info_buttons.addWidget(self._button_info_panel)
335
336     vlay_render = QVBoxLayout()
337     vlay_render.setSpacing(20)
338     vlay_render.addWidget(button_reset)
339     vlay_render.addWidget(self._button_animate)
340     vlay_render.addWidget(self._button_render)
341
342     vlay_right = QVBoxLayout()
343     vlay_right.setSpacing(50)
344     vlay_right.addLayout(vlay_misc_buttons)
345     vlay_right.addItem(QSpacerItem(100, 2, hPolicy=QSizePolicy.Minimum, vPolicy=QSizePolicy.Expanding))
346     vlay_right.addWidget(groupbox_define_new_matrix)
347     vlay_right.addItem(QSpacerItem(100, 2, hPolicy=QSizePolicy.Minimum, vPolicy=QSizePolicy.Expanding))
348     vlay_right.addLayout(vlay_info_buttons)
349     vlay_right.addItem(QSpacerItem(100, 2, hPolicy=QSizePolicy.Minimum, vPolicy=QSizePolicy.Expanding))
350     vlay_right.addLayout(vlay_render)
351
352     hlay_all = QHBoxLayout()
353     hlay_all.setSpacing(15)
354     hlay_all.addLayout(vlay_left)
355     hlay_all.addLayout(vlay_right)
356
357     central_widget = QWidget()
358     central_widget.setLayout(hlay_all)
359     central_widget.setContentsMargins(10, 10, 10, 10)
360
361     self.setCentralWidget(central_widget)

```

```

362
363 def closeEvent(self, event: QCloseEvent) -> None:
364     """Handle a :class:`QCloseEvent` by confirming if the user wants to save, and cancelling animation."""
365     if not self.isWindowModified():
366         self._animating = False
367         self._animating_sequence = False
368         event.accept()
369         return
370
371     if self._save_filename is not None:
372         text = f"If you don't save, then changes made to {self._save_filename} will be lost."
373     else:
374         text = "If you don't save, then changes made will be lost."
375
376     dialog = QMessageBox(self)
377     dialog.setIcon(QMessageBox.Question)
378     dialog.setWindowTitle('Save changes?')
379     dialog.setText(text)
380     dialog.setStandardButtons(QMessageBox.Save | QMessageBox.Discard | QMessageBox.Cancel)
381     dialog.setDefaultButton(QMessageBox.Save)
382
383     pressed_button = dialog.exec()
384
385     if pressed_button == QMessageBox.Save:
386         self._save_session()
387
388     if pressed_button in (QMessageBox.Save, QMessageBox.Discard):
389         self._animating = False
390         self._animating_sequence = False
391         event.accept()
392     else:
393         event.ignore()
394
395 def keyPressEvent(self, event: QKeyEvent) -> None:
396     """Handle a :class:`QKeyEvent` by scrolling through expression history."""
397     key = event.key()
398
399     # Load previous expression
400     if key == Qt.Key_Up:
401         if self._expression_history_index is None:
402             if len(self._expression_history) == 0:
403                 event.ignore()
404                 return
405
406         # If the index is none and we've got a history, set the index to -1
407         self._expression_history_index = -1
408
409         # If the index is in range of the list (the index is always negative), then decrement it
410         elif self._expression_history_index > -len(self._expression_history):
411             self._expression_history_index -= 1
412
413         self._lineEdit_expression_box.setText(self._expression_history[self._expression_history_index])
414
415     # Load next expression
416     elif key == Qt.Key_Down:
417         if self._expression_history_index is None:
418             event.ignore()
419             return
420
421         self._expression_history_index += 1
422
423         # The index is always negative, so if we've reached 0, then we need to stop
424         if self._expression_history_index == 0:
425             self._expression_history_index = None
426             self._lineEdit_expression_box.setText('')
427         else:
428             self._lineEdit_expression_box.setText(self._expression_history[self._expression_history_index])
429
430     else:
431         event.ignore()
432         return
433
434     event.accept()

```

```

435
436 def _update_render_buttons(self) -> None:
437     """Enable or disable the render and animate buttons according to whether the matrix expression is valid."""
438     text = self._linedit_expression_box.text()
439
440     # Let's say that the user defines a non-singular matrix A, then defines B as A^-1
441     # If they then redefine A and make it singular, then we get a LinAlgError when
442     # trying to evaluate an expression with B in it
443     # To fix this, we just do naive validation rather than aware validation
444     if ',' in text:
445         self._button_render.setEnabled(False)
446
447         try:
448             valid = all(self._matrix_wrapper.is_valid_expression(x) for x in text.split(','))
449         except LinAlgError:
450             valid = all(validate_matrix_expression(x) for x in text.split(','))
451
452         self._button_animate.setEnabled(valid)
453
454     else:
455         try:
456             valid = self._matrix_wrapper.is_valid_expression(text)
457         except LinAlgError:
458             valid = validate_matrix_expression(text)
459
460         self._button_render.setEnabled(valid)
461         self._button_animate.setEnabled(valid)
462
463 def _extend_expression_history(self, text: str) -> None:
464     """Extend the expression history with the given expression."""
465     if len(self._expression_history) == 0 or self._expression_history[-1] != text:
466         self._expression_history.append(text)
467         self._expression_history_index = -1
468
469 @pyqtSlot()
470 def _reset_zoom(self) -> None:
471     """Reset the zoom level back to normal."""
472     self._plot.grid_spacing = self._plot.DEFAULT_GRID_SPACING
473     self._plot.update()
474
475 @pyqtSlot()
476 def _reset_transformation(self) -> None:
477     """Reset the visualized transformation back to the identity."""
478     if self._animating or self._animating_sequence:
479         self._reset_during_animation = True
480
481     self._animating = False
482     self._animating_sequence = False
483
484     self._plot.plot_matrix(self._matrix_wrapper['I'])
485     self._plot.update()
486
487 @pyqtSlot()
488 def _render_expression(self) -> None:
489     """Render the transformation given by the expression in the input box."""
490     try:
491         text = self._linedit_expression_box.text()
492         matrix = self._matrix_wrapper.evaluate_expression(text)
493
494     except LinAlgError:
495         self._show_error_message('Singular matrix', 'Cannot take inverse of singular matrix.')
496         return
497
498     self._extend_expression_history(text)
499
500     if self._is_matrix_too_big(matrix):
501         return
502
503     self._plot.plot_matrix(matrix)
504     self._plot.update()
505
506 @pyqtSlot()
507 def _animate_expression(self) -> None:

```



```

508         """Animate from the current matrix to the matrix in the expression box."""
509         self._button_render.setEnabled(False)
510         self._button_animate.setEnabled(False)
511
512         matrix_start: MatrixType = np.array([
513             [self._plot.point_i[0], self._plot.point_j[0]],
514             [self._plot.point_i[1], self._plot.point_j[1]]
515         ])
516
517         text = self._lineedit_expression_box.text()
518
519         self._extend_expression_history(text)
520
521         # If there's commas in the expression, then we want to animate each part at a time
522         if ',' in text:
523             current_matrix = matrix_start
524             self._animating_sequence = True
525
526             # For each expression in the list, right multiply it by the current matrix,
527             # and animate from the current matrix to that new matrix
528             for expr in text.split(',')[::-1]:
529                 if not self._animating_sequence:
530                     break
531
532                 try:
533                     new_matrix = self._matrix_wrapper.evaluate_expression(expr)
534
535                     if self._plot.display_settings.applicative_animation:
536                         new_matrix = new_matrix @ current_matrix
537                 except LinAlgError:
538                     self._show_error_message('Singular matrix', 'Cannot take inverse of singular matrix.')
539                     return
540
541                 self._animate_between_matrices(current_matrix, new_matrix)
542                 current_matrix = new_matrix
543
544                 # Here we just redraw and allow for other events to be handled while we pause
545                 self._plot.update()
546                 QApplication.processEvents()
547                 QThread.sleep(self._plot.display_settings.animation_pause_length)
548
549             self._animating_sequence = False
550
551         # If there's no commas, then just animate directly from the start to the target
552         else:
553             # Get the target matrix and its determinant
554             try:
555                 matrix_target = self._matrix_wrapper.evaluate_expression(text)
556
557             except LinAlgError:
558                 self._show_error_message('Singular matrix', 'Cannot take inverse of singular matrix.')
559                 return
560
561             # The concept of applicative animation is explained in /gui/settings.py
562             if self._plot.display_settings.applicative_animation:
563                 matrix_target = matrix_target @ matrix_start
564
565             # If we want a transitional animation and we're animating the same matrix, then restart the animation
566             # We use this check rather than equality because of small floating point errors
567             elif (abs(matrix_start - matrix_target) < 1e-12).all():
568                 matrix_start = self._matrix_wrapper['I']
569
570             # We pause here for 200 ms to make the animation look a bit nicer
571             self._plot.plot_matrix(matrix_start)
572             self._plot.update()
573             QApplication.processEvents()
574             QThread.sleep(200)
575
576             self._animate_between_matrices(matrix_start, matrix_target)
577
578         self._update_render_buttons()
579
580     def _get_animation_frame(self, start: MatrixType, target: MatrixType, proportion: float) -> MatrixType:

```

```

581         """Get the matrix to render for this frame of the animation.
582
583         This method will smoothen the determinant if that setting is enabled and if the determinant is positive.
584         It also animates rotation-like matrices using a logarithmic spiral to rotate around and scale continuously.
585         Essentially, it just makes things look good when animating.
586
587         :param MatrixType start: The starting matrix
588         :param MatrixType target: The target matrix
589         :param float proportion: How far we are through the loop
590         """
591         det_target = linalg.det(target)
592         det_start = linalg.det(start)
593
594         # This is the matrix that we're applying to get from start to target
595         # We want to check if it's rotation-like
596         if linalg.det(start) == 0:
597             matrix_application = None
598         else:
599             matrix_application = target @ linalg.inv(start)
600
601         # For a matrix to represent a rotation, it must have a positive determinant,
602         # its vectors must be perpendicular, the same length, and at right angles
603         # The checks for 'abs(value) < 1e-10' are to account for floating point error
604         if matrix_application is not None \
605             and self._plot.display_settings.smoothen_determinant \
606             and linalg.det(matrix_application) > 0 \
607             and abs(np.dot(matrix_application.T[0], matrix_application.T[1])) < 1e-10 \
608             and abs(np.hypot(*matrix_application.T[0]) - np.hypot(*matrix_application.T[1])) < 1e-10:
609             rotation_vector: VectorType = matrix_application.T[0] # Take the i column
610             radius, angle = polar_coords(*rotation_vector)
611
612             # We want the angle to be in [-pi, pi), so we have to subtract 2pi from it if it's too big
613             if angle > np.pi:
614                 angle -= 2 * np.pi
615
616             i: VectorType = start.T[0]
617             j: VectorType = start.T[1]
618
619             # Scale the coords with a list comprehension
620             # It's a bit janky, but rotate_coords() will always return a 2-tuple,
621             # so new_i and new_j will always be lists of length 2
622             scale = (radius - 1) * proportion + 1
623             new_i = [scale * c for c in rotate_coord(i[0], i[1], angle * proportion)]
624             new_j = [scale * c for c in rotate_coord(j[0], j[1], angle * proportion)]
625
626             return np.array(
627                 [
628                     [new_i[0], new_j[0]],
629                     [new_i[1], new_j[1]]
630                 ]
631             )
632
633         # matrix_a is the start matrix plus some part of the target, scaled by the proportion
634         # If we just used matrix_a, then things would animate, but the determinants would be weird
635         matrix_a = start + proportion * (target - start)
636
637         if not self._plot.display_settings.smoothen_determinant or det_start * det_target <= 0:
638             return matrix_a
639
640         # To fix the determinant problem, we get the determinant of matrix_a and use it to normalize
641         det_a = linalg.det(matrix_a)
642
643         # For a 2x2 matrix A and a scalar c, we know that det(cA) = c^2 det(A)
644         # We want B = cA such that det(B) = det(S), where S is the start matrix,
645         # so then we can scale it with the animation, so we get
646         # det(cA) = c^2 det(A) = det(S) => c = sqrt(abs(det(S) / det(A)))
647         # Then we scale A to get the determinant we want, and call that matrix_b
648         if det_a == 0:
649             c = 0
650         else:
651             c = np.sqrt(abs(det_start / det_a))
652
653         matrix_b = c * matrix_a

```

```

654     det_b = linalg.det(matrix_b)
655
656     # We want to return B, but we have to scale it over time to have the target determinant
657
658     # We want some C = dB such that det(C) is some target determinant T
659     # det(dB) = d^2 det(B) = T => d = sqrt(abs(T / det(B)))
660
661     # We're also subtracting 1 and multiplying by the proportion and then adding one
662     # This just scales the determinant along with the animation
663
664     # That is all of course, if we can do that
665     # We'll crash if we try to do this with det(B) == 0
666     if det_b == 0:
667         return matrix_a
668
669     scalar = 1 + proportion * (np.sqrt(abs(det_target / det_b)) - 1)
670     return scalar * matrix_b
671
672 def _animate_between_matrices(self, matrix_start: MatrixType, matrix_target: MatrixType) -> None:
673     """Animate from the start matrix to the target matrix."""
674     self._animating = True
675
676     # Making steps depend on animation_time ensures a smooth animation without
677     # massive overheads for small animation times
678     steps = self._plot.display_settings.animation_time // 10
679
680     for i in range(0, steps + 1):
681         if not self._animating:
682             break
683
684         matrix_to_render = self._get_animation_frame(matrix_start, matrix_target, i / steps)
685
686         if self._is_matrix_too_big(matrix_to_render):
687             self._animating = False
688             self._animating_sequence = False
689             return
690
691         self._plot.plot_matrix(matrix_to_render)
692
693         # We schedule the plot to be updated, tell the event loop to
694         # process events, and asynchronously sleep for 10ms
695         # This allows for other events to be processed while animating, like zooming in and out
696         self._plot.update()
697         QApplication.processEvents()
698         QThread.sleep(self._plot.display_settings.animation_time // steps)
699
700     if not self._reset_during_animation:
701         self._plot.plot_matrix(matrix_target)
702     else:
703         self._plot.plot_matrix(self._matrix_wrapper['I'])
704
705     self._plot.update()
706
707     self._animating = False
708     self._reset_during_animation = False
709
710 @pyqtSlot()
711 def _open_info_panel(self) -> None:
712     """Open the info panel and register a callback to undefine matrices."""
713     dialog = InfoPanelDialog(self._matrix_wrapper, self)
714     dialog.open()
715     dialog.finished.connect(self._assign_matrix_wrapper)
716
717 @pyqtSlot(DefineMatrixDialog)
718 def _dialog_define_matrix(self, dialog_class: Type[DefineMatrixDialog]) -> None:
719     """Open a generic definition dialog to define a new matrix.
720
721     The class for the desired dialog is passed as an argument. We create an
722     instance of this class and the dialog is opened asynchronously and modally
723     (meaning it blocks interaction with the main window) with the proper method
724     connected to the :meth:`QDialog.accepted` signal.
725

```

```

726     .. note:: ``dialog_class`` must subclass
↪ :class:`~lintrans.gui.dialogs.define_new_matrix.DefineMatrixDialog`.
727
728     :param dialog_class: The dialog class to instantiate
729     :type dialog_class: Type[lintrans.gui.dialogs.define_new_matrix.DefineMatrixDialog]
730     """
731     # We create a dialog with a deepcopy of the current matrix_wrapper
732     # This avoids the dialog mutating this one
733     dialog: DefineMatrixDialog
734
735     if dialog_class == DefineVisuallyDialog:
736         dialog = DefineVisuallyDialog(
737             self,
738             matrix_wrapper=deepcopy(self._matrix_wrapper),
739             display_settings=self._plot.display_settings,
740             polygon_points=self._plot.polygon_points,
741             input_vector=self._plot.point_input_vector
742         )
743     else:
744         dialog = dialog_class(self, matrix_wrapper=deepcopy(self._matrix_wrapper))
745
746     # .open() is asynchronous and doesn't spawn a new event loop, but the dialog is still modal (blocking)
747     dialog.open()
748
749     # So we have to use the accepted signal to call a method when the user accepts the dialog
750     dialog.accepted.connect(self._assign_matrix_wrapper)
751
752 @pyqtSlot()
753 def _assign_matrix_wrapper(self) -> None:
754     """Assign a new value to ``self._matrix_wrapper`` and give the expression box focus."""
755     self._matrix_wrapper = self.sender().matrix_wrapper
756     self._lineEdit_expression_box.setFocus()
757     self._update_render_buttons()
758
759     self.setWindowModified(True)
760     self._update_window_title()
761
762 @pyqtSlot()
763 def _dialog_change_display_settings(self) -> None:
764     """Open the dialog to change the display settings."""
765     dialog = DisplaySettingsDialog(self, display_settings=self._plot.display_settings)
766     dialog.open()
767     dialog.accepted.connect(self._assign_display_settings)
768
769 @pyqtSlot()
770 def _assign_display_settings(self) -> None:
771     """Assign a new value to ``self._plot.display_settings`` and give the expression box focus."""
772     self._plot.display_settings = self.sender().display_settings
773     self._plot.update()
774     self._lineEdit_expression_box.setFocus()
775     self._update_render_buttons()
776
777 @pyqtSlot()
778 def _dialog_define_polygon(self) -> None:
779     """Open the dialog to define a polygon."""
780     dialog = DefinePolygonDialog(self, polygon_points=self._plot.polygon_points)
781     dialog.open()
782     dialog.accepted.connect(self._assign_polygon_points)
783
784 @pyqtSlot()
785 def _assign_polygon_points(self) -> None:
786     """Assign a new value to ``self._plot.polygon_points`` and give the expression box focus."""
787     self._plot.polygon_points = self.sender().polygon_points
788     self._plot.update()
789     self._lineEdit_expression_box.setFocus()
790     self._update_render_buttons()
791
792     self.setWindowModified(True)
793     self._update_window_title()
794
795 def _show_error_message(self, title: str, text: str, info: str | None = None, *, warning: bool = False) -> None:
796     """Show an error message in a dialog box.
797

```

```

798         :param str title: The window title of the dialog box
799         :param str text: The simple error message
800         :param info: The more informative error message
801         :type info: Optional[str]
802         """
803         dialog = QMessageBox(self)
804         dialog.setWindowTitle(title)
805         dialog.setText(text)
806
807         if warning:
808             dialog.setIcon(QMessageBox.Warning)
809         else:
810             dialog.setIcon(QMessageBox.Critical)
811
812         if info is not None:
813             dialog.setInformativeText(info)
814
815         dialog.open()
816
817         # This is 'finished' rather than 'accepted' because we want to update the buttons no matter what
818         dialog.finished.connect(self._update_render_buttons)
819
820     def _is_matrix_too_big(self, matrix: MatrixType) -> bool:
821         """Check if the given matrix will actually fit on the grid.
822
823         We're checking against a 1000x1000 grid here, which is far less than the actual space we have available.
824         But even when fully zoomed out 1080p monitor, the grid is only roughly 170x90, so 1000x1000 is plenty.
825
826         :param MatrixType matrix: The matrix to check
827         :returns bool: Whether the matrix is too big to fit on the canvas
828         """
829         for x, y in matrix.T:
830             if not (-1000 <= x <= 1000 and -1000 <= y <= 1000):
831                 self._show_error_message(
832                     'Matrix too big',
833                     "This matrix doesn't fit on the grid.",
834                     'This grid is only 1000x1000, and this matrix\n'
835                     f'[{int(matrix[0][0])} {int(matrix[0][1])}; {int(matrix[1][0])} {int(matrix[1][1])}]\n'
836                     " doesn't fit."
837                 )
838                 return True
839
840         return False
841
842     def _update_window_title(self) -> None:
843         """Update the window title to reflect whether the session has changed since it was last saved."""
844         if self._save_filename:
845             title = os.path.split(self._save_filename)[-1] + ' [*] - lintrans'
846         else:
847             title = ' [*] lintrans'
848
849         self.setWindowTitle(title)
850
851     def _reset_session(self) -> None:
852         """Ask the user if they want to reset the current session.
853
854         Resetting the session means setting the matrix wrapper to a new instance, and rendering I.
855         """
856         dialog = QMessageBox(self)
857         dialog.setIcon(QMessageBox.Question)
858         dialog.setWindowTitle('Reset the session?')
859         dialog.setText('Are you sure you want to reset the current session?')
860         dialog.setStandardButtons(QMessageBox.Yes | QMessageBox.No)
861         dialog.setDefaultButton(QMessageBox.No)
862
863         if dialog.exec() == QMessageBox.Yes:
864             self._matrix_wrapper = MatrixWrapper()
865             self._plot.polygon_points = []
866
867             self._reset_transformation()
868             self._expression_history = []
869             self._expression_history_index = None
870             self._lineedit_expression_box.setText('')

```

```

871         self._lineedit_expression_box.setFocus()
872         self._update_render_buttons()
873
874         self._save_filename = None
875         self.setWindowModified(False)
876         self._update_window_title()
877
878     def open_session_file(self, filename: str) -> None:
879         """Open the given session file.
880
881         If the selected file is not a valid lintrans session file, we just show an error message,
882         but if it's valid, we load it and set it as the default filename for saving.
883         """
884         try:
885             session, version, extra_attrs = Session.load_from_file(filename)
886
887             # load_from_file() can raise errors if the contents is not a valid pickled Python object,
888             # or if the pickled Python object is of the wrong type
889             except (AttributeError, EOFError, FileNotFoundError, ValueError, UnpicklingError):
890                 self._show_error_message(
891                     'Invalid file contents',
892                     'This is not a valid lintrans session file.',
893                     'Not all .lt files are lintrans session files. This file was probably created by an unrelated '
894                     'program.'
895                 )
896                 return
897
898             missing_parts = False
899
900             if session.matrix_wrapper is not None:
901                 self._matrix_wrapper = session.matrix_wrapper
902             else:
903                 self._matrix_wrapper = MatrixWrapper() # type: ignore[unreachable]
904                 missing_parts = True
905
906             if session.polygon_points is not None:
907                 self._plot.polygon_points = session.polygon_points
908             else:
909                 self._plot.polygon_points = [] # type: ignore[unreachable]
910                 missing_parts = True
911
912             if session.display_settings is not None:
913                 self._plot.display_settings = session.display_settings
914             else:
915                 self._plot.display_settings = DisplaySettings() # type: ignore[unreachable]
916                 missing_parts = True
917
918             if session.input_vector is not None:
919                 self._plot.point_input_vector = session.input_vector
920             else:
921                 self._plot.point_input_vector = (1, 1) # type: ignore[unreachable]
922                 missing_parts = True
923
924             if missing_parts:
925                 if version != lintrans.__version__:
926                     info = f"This may be a version conflict. This file was saved with lintrans v{version} " \
927                         f"but you're running lintrans v{lintrans.__version__}."
928                 else:
929                     info = None
930
931                 self._show_error_message(
932                     'Session file missing parts',
933                     'This session file is missing certain elements. It may not work correctly.',
934                     info,
935                     warning=True
936                 )
937             elif extra_attrs:
938                 if version != lintrans.__version__:
939                     info = f"This may be a version conflict. This file was saved with lintrans v{version} " \
940                         f"but you're running lintrans v{lintrans.__version__}."
941                 else:
942                     info = None
943

```

```

944         self._show_error_message(
945             'Session file has extra parts',
946             'This session file has more parts than expected. It will work correctly, '
947             'but you might be missing some features.',
948             info,
949             warning=True
950         )
951
952     self._reset_transformation()
953     self._expression_history = []
954     self._expression_history_index = None
955     self._linedit_expression_box.setText('')
956     self._linedit_expression_box.setFocus()
957     self._update_render_buttons()
958
959     # Set this as the default filename if we could read it properly
960     self._save_filename = filename
961     self.setWindowModified(False)
962     self._update_window_title()
963
964 @pyqtSlot()
965 def _ask_for_session_file(self) -> None:
966     """Ask the user to select a session file, and then open it and load the session."""
967     dialog = QFileDialog(
968         self,
969         'Open a session',
970         GlobalSettings().get_save_directory(),
971         'lintrans sessions (*.lt)'
972     )
973     dialog.setAcceptMode(QFileDialog.AcceptOpen)
974     dialog.setFileMode(QFileDialog.ExistingFile)
975     dialog.setViewMode(QFileDialog.List)
976
977     if dialog.exec():
978         self.open_session_file(dialog.selectedFiles()[0])
979
980 @pyqtSlot()
981 def _save_session(self) -> None:
982     """Save the session to the given file.
983
984     If ``self._save_filename`` is ``None``, then call :meth:`_save_session_as` and return.
985     """
986     if self._save_filename is None:
987         self._save_session_as()
988         return
989
990     Session(
991         matrix_wrapper=self._matrix_wrapper,
992         polygon_points=self._plot.polygon_points,
993         display_settings=self._plot.display_settings,
994         input_vector=self._plot.point_input_vector,
995     ).save_to_file(self._save_filename)
996
997     self.setWindowModified(False)
998     self._update_window_title()
999
1000 @pyqtSlot()
1001 def _save_session_as(self) -> None:
1002     """Ask the user for a file to save the session to, and then call :meth:`_save_session`.
1003
1004     .. note::
1005         If the user doesn't select a file to save the session to, then the session
1006         just doesn't get saved, and :meth:`_save_session` is never called.
1007     """
1008     dialog = FileSelectDialog(
1009         self,
1010         'Save this session',
1011         GlobalSettings().get_save_directory(),
1012         'lintrans sessions (*.lt)'
1013     )
1014     dialog.setAcceptMode(QFileDialog.AcceptSave)
1015     dialog.setFileMode(QFileDialog.AnyFile)
1016     dialog.setViewMode(QFileDialog.List)

```

```

1017         dialog.setDefaultSuffix('.lt')
1018
1019         if dialog.exec():
1020             filename = dialog.selectedFiles()[0]
1021             self._save_filename = filename
1022             self._save_session()
1023
1024     @pyqtSlot(str)
1025     def _prompt_update(self, version: str) -> None:
1026         """Open a modal dialog to prompt the user to update lintrans."""
1027         dialog = PromptUpdateDialog(self, new_version=version)
1028         dialog.open()
1029
1030     def check_for_updates_and_prompt(self) -> None:
1031         """Update lintrans depending on the user's choice of update type.
1032
1033         If they chose 'prompt', then this method will open a prompt dialog (after checking
1034         if a new version actually exists). See :meth:`_prompt_update`.
1035         """
1036         self._thread_updates.start()
1037
1038
1039     def main(filename: Optional[str]) -> NoReturn:
1040         """Run the GUI by creating and showing an instance of :class:`LintransMainWindow`.
1041
1042         :param Optional[str] filename: A session file to optionally open at startup
1043         """
1044         app = QApplication([])
1045         app.setApplicationName('lintrans')
1046         app.setApplicationVersion(lintrans.__version__)
1047
1048         qapp().setStyle(QStyleFactory.create('fusion'))
1049
1050         window = LintransMainWindow()
1051         window.show()
1052         window.check_for_updates_and_prompt()
1053
1054         if filename:
1055             window.open_session_file(filename)
1056
1057         sys.exit(app.exec_())

```

## A.7 gui/session.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides the :class:`Session` class, which provides a way to save and load sessions."""
8
9  from __future__ import annotations
10
11  import os
12  import pathlib
13  import pickle
14  from collections import defaultdict
15  from typing import Any, DefaultDict, List, Tuple
16
17  import lintrans
18  from lintrans.gui.settings import DisplaySettings
19  from lintrans.matrices import MatrixWrapper
20
21
22  def _return_none() -> None:
23      """Return None.
24
25      This function only exists to make the defaultdict in :class:`Session` pickle-able.
26      """

```



```

27     return None
28
29
30 class Session:
31     """Hold information about a session and provide methods to save and load that data."""
32
33     __slots__ = ('matrix_wrapper', 'polygon_points', 'display_settings', 'input_vector')
34     matrix_wrapper: MatrixWrapper
35     polygon_points: List[Tuple[float, float]]
36     display_settings: DisplaySettings
37     input_vector: Tuple[float, float]
38
39     def __init__(
40         self,
41         *,
42         matrix_wrapper: MatrixWrapper,
43         polygon_points: List[Tuple[float, float]],
44         display_settings: DisplaySettings,
45         input_vector: Tuple[float, float],
46     ) -> None:
47         """Create a :class:`Session` object with the given data."""
48         self.matrix_wrapper = matrix_wrapper
49         self.polygon_points = polygon_points
50         self.display_settings = display_settings
51         self.input_vector = input_vector
52
53     def save_to_file(self, filename: str) -> None:
54         """Save the session state to a file, creating parent directories as needed."""
55         parent_dir = pathlib.Path(os.path.expanduser(filename)).parent.absolute()
56
57         if not os.path.isdir(parent_dir):
58             os.makedirs(parent_dir)
59
60         data_dict: DefaultDict[str, Any] = defaultdict(_return_none, lintrans=lintrans.__version__)
61         for attr in self.__slots__:
62             data_dict[attr] = getattr(self, attr)
63
64         with open(filename, 'wb') as f:
65             pickle.dump(data_dict, f, protocol=4)
66
67     @classmethod
68     def load_from_file(cls, filename: str) -> Tuple[Session, str, bool]:
69         """Return the session state that was previously saved to ``filename`` along with some extra information.
70
71         The tuple we return has the :class:`Session` object (with some possibly None arguments),
72         the lintrans version that the file was saved under, and whether the file had any extra
73         attributes that this version doesn't support.
74
75         :raises AttributeError: For specific older versions of :class:`Session` before it used ``__slots__``
76         :raises EOFError: If the file doesn't contain a pickled Python object
77         :raises FileNotFoundError: If the file doesn't exist
78         :raises ValueError: If the file contains a pickled object of the wrong type
79         """
80         with open(filename, 'rb') as f:
81             data_dict = pickle.load(f)
82
83         if not isinstance(data_dict, defaultdict):
84             raise ValueError(f'File {filename} contains pickled object of the wrong type (must be defaultdict)')
85
86         session = cls(
87             matrix_wrapper=data_dict['matrix_wrapper'],
88             polygon_points=data_dict['polygon_points'],
89             display_settings=data_dict['display_settings'],
90             input_vector=data_dict['input_vector'],
91         )
92
93         # Check if the file has more attributes than we expect
94         # If it does, it's probably from a higher version of lintrans
95         extra_attrs = len(
96             set(data_dict.keys()).difference(
97                 set(['lintrans', *cls.__slots__])
98             )
99         ) != 0

```

```

100
101         return session, data_dict['lintrans'], extra_attrs

```

## A.8 gui/utility.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides utility functions for the whole GUI, such as :func:`qapp`."""
8
9  from PyQt5.QtCore import QApplication
10
11
12  def qapp() -> QApplication:
13      """Return the equivalent of the global :class:`QApp` pointer.
14
15      :raises RuntimeError: If :meth:`QCoreApplication.instance` returns ``None``
16      """
17      instance = QApplication.instance()
18
19      if instance is None:
20          raise RuntimeError('qApp undefined')
21
22      return instance

```

## A.9 gui/validate.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This simple module provides a :class:`MatrixExpressionValidator` class to validate matrix expression input."""
8
9  from __future__ import annotations
10
11  import re
12  from typing import Tuple
13
14  from PyQt5.QtGui import QValidator
15
16  from lintrans.matrices import parse
17
18
19  class MatrixExpressionValidator(QValidator):
20      """This class validates matrix expressions in a Qt input box."""
21
22      def validate(self, text: str, pos: int) -> Tuple[QValidator.State, str, int]:
23          """Validate the given text according to the rules defined in the :mod:`~lintrans.matrices` module."""
24          # We want to extend the naive character class by adding a comma, which isn't
25          # normally allowed in expressions, but is allowed for sequential animations
26          bad_chars = re.sub(parse.NAIVE_CHARACTER_CLASS[:-1] + ',,', '', text)
27
28          # If there are bad chars, just reject it
29          if bad_chars != '':
30              return QValidator.Invalid, text, pos
31
32          # Now we need to check if it's actually a valid expression
33          if all(parse.validate_matrix_expression(expression) for expression in text.split(',')):
34              return QValidator.Acceptable, text, pos
35
36          # Else, if it's got all the right characters but it's not a valid expression
37          return QValidator.Intermediate, text, pos

```

## A.10 gui/settings.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module contains the :class:`DisplaySettings` class, which holds configuration for display."""
8
9  from __future__ import annotations
10
11  from dataclasses import dataclass
12
13
14  @dataclass
15  class DisplaySettings:
16      """This class simply holds some attributes to configure display."""
17
18      # === Basic stuff
19
20      draw_background_grid: bool = True
21      """This controls whether we want to draw the background grid.
22
23      The background axes will always be drawn. This makes it easy to identify the center of the space.
24      """
25
26      draw_transformed_grid: bool = True
27      """This controls whether we want to draw the transformed grid. Vectors are handled separately."""
28
29      draw_basis_vectors: bool = True
30      """This controls whether we want to draw the transformed basis vectors."""
31
32      label_basis_vectors: bool = False
33      """This controls whether we want to label the `i` and `j` basis vectors."""
34
35      # === Animations
36
37      smoothen_determinant: bool = True
38      """This controls whether we want the determinant to change smoothly during the animation.
39
40      .. note::
41          Even if this is ``True``, it will be ignored if we're animating from a positive det matrix to
42          a negative det matrix, or vice versa, because if we try to smoothly animate that determinant,
43          things blow up and the app often crashes.
44      """
45
46      applicative_animation: bool = True
47      """There are two types of simple animation, transitional and applicative.
48
49      Let ``C`` be the matrix representing the currently displayed transformation, and let ``T`` be the target matrix.
50      Transitional animation means that we animate directly from ``C`` from ``T``,
51      and applicative animation means that we animate from ``C`` to ``TC``, so we apply ``T`` to ``C``.
52      """
53
54      animation_time: int = 1200
55      """This is the number of milliseconds that an animation takes."""
56
57      animation_pause_length: int = 400
58      """This is the number of milliseconds that we wait between animations when using comma syntax."""
59
60      # === Matrix info
61
62      draw_determinant_parallelogram: bool = False
63      """This controls whether or not we should shade the parallelogram representing the determinant of the matrix."""
64
65      show_determinant_value: bool = True
66      """This controls whether we should write the text value of the determinant inside the parallelogram.
67
68      The text only gets draw if :attr:`draw_determinant_parallelogram` is also True.
69      """
70

```

```

71     draw_eigenvectors: bool = False
72     """This controls whether we should draw the eigenvectors of the transformation."""
73
74     draw_eigenlines: bool = False
75     """This controls whether we should draw the eigenlines of the transformation."""
76
77     # == Polygon
78
79     draw_untransformed_polygon: bool = True
80     """This controls whether we should draw the untransformed version of the user-defined polygon."""
81
82     draw_transformed_polygon: bool = True
83     """This controls whether we should draw the transformed version of the user-defined polygon."""
84
85     # == Input/output vectors
86
87     draw_input_vector: bool = True
88     """This controls whether we should draw the input vector in the main viewport."""
89
90     draw_output_vector: bool = True
91     """This controls whether we should draw the output vector in the main viewport."""

```

## A.11 gui/\_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package supplies the main GUI and associated dialogs for visualization."""
8
9  from . import dialogs, plots, session, settings, utility, validate
10 from .main_window import main
11
12 __all__ = ['dialogs', 'main', 'plots', 'session', 'settings', 'utility', 'validate']

```

## A.12 gui/dialogs/define\_new\_matrix.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides an abstract :class:`DefineMatrixDialog` class and subclasses."""
8
9  from __future__ import annotations
10
11 import abc
12 from typing import List, Tuple
13
14 from numpy import array
15 from PyQt5 import QtWidgets
16 from PyQt5.QtCore import pyqtSlot
17 from PyQt5.QtGui import QDoubleValidator, QKeySequence
18 from PyQt5.QtWidgets import (QGridLayout, QHBoxLayout, QLabel, QLineEdit,
19                             QPushButton, QShortcut, QSizePolicy, QSpacerItem,
20                             QVBoxLayout)
21
22 from lintrans.gui.dialogs.misc import FixedSizeDialog
23 from lintrans.gui.plots import DefineMatrixVisuallyWidget
24 from lintrans.gui.settings import DisplaySettings
25 from lintrans.gui.validate import MatrixExpressionValidator
26 from lintrans.matrices import MatrixWrapper
27 from lintrans.matrices.utility import is_valid_float, round_float
28 from lintrans.typing import MatrixType
29

```

```

30 _ALPHABET_NO_I = 'ABCDEFGHJKLMNOPQRSTUVWXYZ'
31
32
33 def get_first_undefined_matrix(wrapper: MatrixWrapper) -> str:
34     """Return the letter of the first undefined matrix in the given wrapper, or ``A`` if all matrices are
    ↪ defined."""
35     defined_matrices = [x for x, _ in wrapper.get_defined_matrices()]
36     for letter in _ALPHABET_NO_I:
37         if letter not in defined_matrices:
38             return letter
39
40     return 'A'
41
42
43 class DefineMatrixDialog(FixedSizeDialog):
44     """An abstract superclass for definitions dialogs.
45
46     .. warning:: This class should never be directly instantiated, only subclassed.
47     """
48
49     def __init__(self, *args, matrix_wrapper: MatrixWrapper, **kwargs):
50         """Create the widgets and layout of the dialog.
51
52         .. note:: ``*args`` and ``**kwargs`` are passed to the super constructor (:class:`QDialog`).
53
54         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
55         """
56         super().__init__(*args, **kwargs)
57
58         self.matrix_wrapper = matrix_wrapper
59         self.setWindowTitle('Define a matrix')
60
61         # === Create the widgets
62
63         self._button_confirm = QPushButton(self)
64         self._button_confirm.setText('Confirm')
65         self._button_confirm.setEnabled(False)
66         self._button_confirm.clicked.connect(self._confirm_matrix)
67         self._button_confirm.setToolTip('Confirm this as the new matrix<br><b>(Ctrl + Enter)</b>')
68         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self._button_confirm.click)
69
70         button_cancel = QPushButton(self)
71         button_cancel.setText('Cancel')
72         button_cancel.clicked.connect(self.reject)
73         button_cancel.setToolTip('Cancel this definition<br><b>(Escape)</b>')
74
75         label_equals = QLabel(self)
76         label_equals.setText('=')
77
78         self._combobox_letter = QtWidgets.QComboBox(self)
79
80         for letter in _ALPHABET_NO_I:
81             self._combobox_letter.addItem(letter)
82
83         self._combobox_letter.activated.connect(self._load_matrix)
84         self._combobox_letter.setCurrentText(get_first_undefined_matrix(self.matrix_wrapper))
85
86         # === Arrange the widgets
87
88         self.setContentsMargins(10, 10, 10, 10)
89
90         self._hlay_buttons = QHBoxLayout()
91         self._hlay_buttons.setSpacing(20)
92         self._hlay_buttons.addItem(QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum))
93         self._hlay_buttons.addWidget(button_cancel)
94         self._hlay_buttons.addWidget(self._button_confirm)
95
96         self._hlay_definition = QHBoxLayout()
97         self._hlay_definition.setSpacing(20)
98         self._hlay_definition.addWidget(self._combobox_letter)
99         self._hlay_definition.addWidget(label_equals)
100
101         # All subclasses have to manually add the hlay layouts to _vlay_all

```

```

102         # This is because the subclasses add their own widgets and if we add
103         # the layout here, then these new widgets won't be included
104         self._vlay_all = QVBoxLayout()
105         self._vlay_all.setSpacing(20)
106
107         self.setLayout(self._vlay_all)
108
109     @property
110     def _selected_letter(self) -> str:
111         """Return the letter currently selected in the combo box."""
112         return str(self._combobox_letter.currentText())
113
114     @abc.abstractmethod
115     @pyqtSlot()
116     def _update_confirm_button(self) -> None:
117         """Enable the confirm button if it should be enabled, else, disable it."""
118
119     @pyqtSlot(int)
120     def _load_matrix(self, index: int) -> None:
121         """Load the selected matrix into the dialog.
122
123         This method is optionally able to be overridden. If it is not overridden,
124         then no matrix is loaded when selecting a name.
125
126         We have this method in the superclass so that we can define it as the slot
127         for the :meth:`QComboBox.activated` signal in this constructor, rather than
128         having to define that in the constructor of every subclass.
129         """
130
131     @abc.abstractmethod
132     @pyqtSlot()
133     def _confirm_matrix(self) -> None:
134         """Confirm the inputted matrix and assign it.
135
136         .. note:: When subclassing, this method should mutate ``self.matrix_wrapper`` and then call
137         ↪ ``self.accept()``.
138         """
139
140 class DefineVisuallyDialog(DefineMatrixDialog):
141     """The dialog class that allows the user to define a matrix visually."""
142
143     def __init__(
144         self,
145         *args,
146         matrix_wrapper: MatrixWrapper,
147         display_settings: DisplaySettings,
148         polygon_points: List[Tuple[float, float]],
149         input_vector: Tuple[float, float],
150         **kwargs
151     ):
152         """Create the widgets and layout of the dialog.
153
154         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
155         """
156         super().__init__(*args, matrix_wrapper=matrix_wrapper, **kwargs)
157
158         self.setMinimumSize(700, 550)
159
160         # === Create the widgets
161
162         self._plot = DefineMatrixVisuallyWidget(
163             self,
164             display_settings=display_settings,
165             polygon_points=polygon_points,
166             input_vector=input_vector
167         )
168
169         # === Arrange the widgets
170
171         self._hlay_definition.addWidget(self._plot)
172         self._hlay_definition.setStretchFactor(self._plot, 1)
173

```

```

174         self._vlay_all.addLayout(self._hlay_definition)
175         self._vlay_all.addLayout(self._hlay_buttons)
176
177         # We load the default matrix A into the plot
178         self._load_matrix(0)
179
180         # We also enable the confirm button, because any visually defined matrix is valid
181         self._button_confirm.setEnabled(True)
182
183     @pyqtSlot()
184     def _update_confirm_button(self) -> None:
185         """Enable the confirm button.
186
187         .. note::
188             The confirm button is always enabled in this dialog and this method is never actually used,
189             so it's got an empty body. It's only here because we need to implement the abstract method.
190         """
191
192     @pyqtSlot(int)
193     def _load_matrix(self, index: int) -> None:
194         """Show the selected matrix on the plot. If the matrix is None, show the identity."""
195         matrix = self.matrix_wrapper[self._selected_letter]
196
197         if matrix is None:
198             matrix = self.matrix_wrapper['I']
199
200         self._plot.plot_matrix(matrix)
201         self._plot.update()
202
203     @pyqtSlot()
204     def _confirm_matrix(self) -> None:
205         """Confirm the matrix that's been defined visually."""
206         matrix: MatrixType = array([
207             [self._plot.point_i[0], self._plot.point_j[0]],
208             [self._plot.point_i[1], self._plot.point_j[1]]
209         ])
210
211         self.matrix_wrapper[self._selected_letter] = matrix
212         self.accept()
213
214
215 class DefineNumericallyDialog(DefineMatrixDialog):
216     """The dialog class that allows the user to define a new matrix numerically."""
217
218     def __init__(self, *args, matrix_wrapper: MatrixWrapper, **kwargs):
219         """Create the widgets and layout of the dialog.
220
221         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
222         """
223         super().__init__(*args, matrix_wrapper=matrix_wrapper, **kwargs)
224
225         # === Create the widgets
226
227         # tl = top left, br = bottom right, etc.
228         self._element_tl = QLineEdit(self)
229         self._element_tl.textChanged.connect(self._update_confirm_button)
230         self._element_tl.setValidator(QDoubleValidator())
231
232         self._element_tr = QLineEdit(self)
233         self._element_tr.textChanged.connect(self._update_confirm_button)
234         self._element_tr.setValidator(QDoubleValidator())
235
236         self._element_bl = QLineEdit(self)
237         self._element_bl.textChanged.connect(self._update_confirm_button)
238         self._element_bl.setValidator(QDoubleValidator())
239
240         self._element_br = QLineEdit(self)
241         self._element_br.textChanged.connect(self._update_confirm_button)
242         self._element_br.setValidator(QDoubleValidator())
243
244         self._matrix_elements = (self._element_tl, self._element_tr, self._element_bl, self._element_br)
245
246         font_parens = self.font()

```

```

247     font_parens.setPointSize(int(font_parens.pointSize() * 5))
248     font_parens.setWeight(int(font_parens.weight() / 5))
249
250     label_paren_left = QLabel(self)
251     label_paren_left.setText('(')
252     label_paren_left.setFont(font_parens)
253
254     label_paren_right = QLabel(self)
255     label_paren_right.setText('')
256     label_paren_right.setFont(font_parens)
257
258     # === Arrange the widgets
259
260     grid_matrix = QGridLayout()
261     grid_matrix.setSpacing(20)
262     grid_matrix.addWidget(label_paren_left, 0, 0, -1, 1)
263     grid_matrix.addWidget(self._element_tl, 0, 1)
264     grid_matrix.addWidget(self._element_tr, 0, 2)
265     grid_matrix.addWidget(self._element_bl, 1, 1)
266     grid_matrix.addWidget(self._element_br, 1, 2)
267     grid_matrix.addWidget(label_paren_right, 0, 3, -1, 1)
268
269     self._hlay_definition.addLayout(grid_matrix)
270
271     self._vlay_all.addLayout(self._hlay_definition)
272     self._vlay_all.addLayout(self._hlay_buttons)
273
274     # We load the default matrix A into the boxes
275     self._load_matrix(0)
276
277     self._element_tl.setFocus()
278
279 @pyqtSlot()
280 def _update_confirm_button(self) -> None:
281     """Enable the confirm button if there are valid floats in every box."""
282     for elem in self._matrix_elements:
283         if not is_valid_float(elem.text()):
284             # If they're not all numbers, then we can't confirm it
285             self._button_confirm.setEnabled(False)
286             return
287
288     # If we didn't find anything invalid
289     self._button_confirm.setEnabled(True)
290
291 @pyqtSlot(int)
292 def _load_matrix(self, index: int) -> None:
293     """If the selected matrix is defined, load its values into the boxes."""
294     matrix = self.matrix_wrapper[self._selected_letter]
295
296     if matrix is None:
297         for elem in self._matrix_elements:
298             elem.setText('')
299
300     else:
301         self._element_tl.setText(round_float(matrix[0][0]))
302         self._element_tr.setText(round_float(matrix[0][1]))
303         self._element_bl.setText(round_float(matrix[1][0]))
304         self._element_br.setText(round_float(matrix[1][1]))
305
306     self._update_confirm_button()
307
308 @pyqtSlot()
309 def _confirm_matrix(self) -> None:
310     """Confirm the matrix in the boxes and assign it to the name in the combo box."""
311     matrix: MatrixType = array([
312         [float(self._element_tl.text()), float(self._element_tr.text())],
313         [float(self._element_bl.text()), float(self._element_br.text())]
314     ])
315
316     self.matrix_wrapper[self._selected_letter] = matrix
317     self.accept()
318
319

```



```

320 class DefineAsExpressionDialog(DefineMatrixDialog):
321     """The dialog class that allows the user to define a matrix as an expression of other matrices."""
322
323     def __init__(self, *args, matrix_wrapper: MatrixWrapper, **kwargs):
324         """Create the widgets and layout of the dialog.
325
326         :param MatrixWrapper matrix_wrapper: The MatrixWrapper that this dialog will mutate
327         """
328         super().__init__(*args, matrix_wrapper=matrix_wrapper, **kwargs)
329
330         self.setMinimumWidth(450)
331
332         # === Create the widgets
333
334         self._lineedit_expression_box = QLineEdit(self)
335         self._lineedit_expression_box.setPlaceholderText('Enter matrix expression..')
336         self._lineedit_expression_box.textChanged.connect(self._update_confirm_button)
337         self._lineedit_expression_box.setValidator(MatrixExpressionValidator())
338
339         # === Arrange the widgets
340
341         self._hlay_definition.addWidget(self._lineedit_expression_box)
342
343         self._vlay_all.addLayout(self._hlay_definition)
344         self._vlay_all.addLayout(self._hlay_buttons)
345
346         # Load the matrix if it's defined as an expression
347         self._load_matrix(0)
348
349         self._lineedit_expression_box.setFocus()
350
351     @pyqtSlot()
352     def _update_confirm_button(self) -> None:
353         """Enable the confirm button if the matrix expression is valid in the wrapper."""
354         text = self._lineedit_expression_box.text()
355         valid_expression = self.matrix_wrapper.is_valid_expression(text)
356
357         self._button_confirm.setEnabled(
358             valid_expression
359             and self._selected_letter not in text
360             and self._selected_letter not in self.matrix_wrapper.get_expression_dependencies(text)
361         )
362
363     @pyqtSlot(int)
364     def _load_matrix(self, index: int) -> None:
365         """If the selected matrix is defined as an expression, load that expression into the box."""
366         if (expr := self.matrix_wrapper.get_expression(self._selected_letter)) is not None:
367             self._lineedit_expression_box.setText(expr)
368         else:
369             self._lineedit_expression_box.setText('')
370
371     @pyqtSlot()
372     def _confirm_matrix(self) -> None:
373         """Evaluate the matrix expression and assign its value to the name in the combo box."""
374         self.matrix_wrapper[self._selected_letter] = self._lineedit_expression_box.text()
375         self.accept()

```

## A.13 gui/dialogs/settings.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """This module provides dialogs to edit settings within the app."""
8
9 from __future__ import annotations
10
11 import abc

```

```

12 from typing import Dict
13
14 from PyQt5 import QtWidgets
15 from PyQt5.QtCore import Qt
16 from PyQt5.QtGui import QIntValidator, QKeyEvent, QKeySequence
17 from PyQt5.QtWidgets import (QCheckBox, QGroupBox, QHBoxLayout, QLayout,
18                             QShortcut, QSizePolicy, QSpacerItem, QVBoxLayout)
19
20 from lintrans.gui.dialogs.misc import FixedSizeDialog
21 from lintrans.gui.settings import DisplaySettings
22
23
24 class SettingsDialog(FixedSizeDialog):
25     """An abstract superclass for other simple dialogs."""
26
27     def __init__(self, *args, resettable: bool, **kwargs):
28         """Create the widgets and layout of the dialog, passing ``*args`` and ``**kwargs`` to super."""
29         super().__init__(*args, **kwargs)
30
31         # === Create the widgets
32
33         self._button_confirm = QtWidgets.QPushButton(self)
34         self._button_confirm.setText('Confirm')
35         self._button_confirm.clicked.connect(self._confirm_settings)
36         self._button_confirm.setToolTip('Confirm these new settings<br><b>(Ctrl + Enter)</b>')
37         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(self._button_confirm.click)
38
39         self._button_cancel = QtWidgets.QPushButton(self)
40         self._button_cancel.setText('Cancel')
41         self._button_cancel.clicked.connect(self.reject)
42         self._button_cancel.setToolTip('Revert these settings<br><b>(Escape)</b>')
43
44         if resettable:
45             self._button_reset = QtWidgets.QPushButton(self)
46             self._button_reset.setText('Reset to defaults')
47             self._button_reset.clicked.connect(self._reset_settings)
48             self._button_reset.setToolTip('Reset these settings to their defaults<br><b>(Ctrl + R)</b>')
49             QShortcut(QKeySequence('Ctrl+R'), self).activated.connect(self._button_reset.click)
50
51         # === Arrange the widgets
52
53         self.setContentsMargins(10, 10, 10, 10)
54
55         self._hlay_buttons = QHBoxLayout()
56         self._hlay_buttons.setSpacing(20)
57
58         if resettable:
59             self._hlay_buttons.addWidget(self._button_reset)
60
61         self._hlay_buttons.addItem(QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum))
62         self._hlay_buttons.addWidget(self._button_cancel)
63         self._hlay_buttons.addWidget(self._button_confirm)
64
65     def _setup_layout(self, options_layout: QLayout) -> None:
66         """Set the layout of the settings widget.
67
68         .. note:: This method must be called at the end of :meth:`__init__`
69            in subclasses to setup the layout properly.
70         """
71         vlay_all = QVBoxLayout()
72         vlay_all.setSpacing(20)
73         vlay_all.addLayout(options_layout)
74         vlay_all.addLayout(self._hlay_buttons)
75
76         self.setLayout(vlay_all)
77
78     @abc.abstractmethod
79     def _load_settings(self) -> None:
80         """Load the current settings into the widgets."""
81
82     @abc.abstractmethod
83     def _confirm_settings(self) -> None:
84         """Confirm the settings chosen in the dialog."""

```

```

85
86     def _reset_settings(self) -> None:
87         """Reset the settings.
88
89         .. note:: This method is empty but not abstract because not all subclasses will need to implement it.
90         """
91
92
93     class DisplaySettingsDialog(SettingsDialog):
94         """The dialog to allow the user to edit the display settings."""
95
96         def __init__(self, *args, display_settings: DisplaySettings, **kwargs):
97             """Create the widgets and layout of the dialog.
98
99             :param DisplaySettings display_settings: The :class:`~lintrans.gui.settings.DisplaySettings` object to
100             ↪ mutate
101             """
102             super().__init__(*args, resettable=True, **kwargs)
103
104             self.display_settings = display_settings
105             self.setWindowTitle('Change display settings')
106
107             self._dict_checkboxes: Dict[str, QCheckBox] = {}
108
109             # === Create the widgets
110
111             # Basic stuff
112
113             self._checkbox_draw_background_grid = QCheckBox(self)
114             self._checkbox_draw_background_grid.setText('Draw &background grid')
115             self._checkbox_draw_background_grid.setToolTip(
116                 'Draw the background grid (axes are always drawn)'
117             )
118             self._dict_checkboxes['b'] = self._checkbox_draw_background_grid
119
120             self._checkbox_draw_transformed_grid = QCheckBox(self)
121             self._checkbox_draw_transformed_grid.setText('Draw t&transformed grid')
122             self._checkbox_draw_transformed_grid.setToolTip(
123                 'Draw the transformed grid (vectors are handled separately)'
124             )
125             self._dict_checkboxes['r'] = self._checkbox_draw_transformed_grid
126
127             self._checkbox_draw_basis_vectors = QCheckBox(self)
128             self._checkbox_draw_basis_vectors.setText('Draw basis &vectors')
129             self._checkbox_draw_basis_vectors.setToolTip(
130                 'Draw the transformed basis vectors'
131             )
132             self._checkbox_draw_basis_vectors.clicked.connect(self._update_gui)
133             self._dict_checkboxes['v'] = self._checkbox_draw_basis_vectors
134
135             self._checkbox_label_basis_vectors = QCheckBox(self)
136             self._checkbox_label_basis_vectors.setText('Label the bas&is vectors')
137             self._checkbox_label_basis_vectors.setToolTip(
138                 'Label the transformed i and j basis vectors'
139             )
140             self._dict_checkboxes['i'] = self._checkbox_label_basis_vectors
141
142             # Animations
143
144             self._checkbox_smooththen_determinant = QCheckBox(self)
145             self._checkbox_smooththen_determinant.setText('&Smoothen determinant')
146             self._checkbox_smooththen_determinant.setToolTip(
147                 'Smoothly animate the determinant transition during animation (if possible)'
148             )
149             self._dict_checkboxes['s'] = self._checkbox_smooththen_determinant
150
151             self._checkbox_applicative_animation = QCheckBox(self)
152             self._checkbox_applicative_animation.setText('&Applicative animation')
153             self._checkbox_applicative_animation.setToolTip(
154                 'Animate the new transformation applied to the current one,\n'
155                 'rather than just that transformation on its own'
156             )
157             self._dict_checkboxes['a'] = self._checkbox_applicative_animation

```

```

157
158 label_animation_time = QtWidgets.QLabel(self)
159 label_animation_time.setText('Total animation length (ms)')
160 label_animation_time.setToolTip(
161     'How long it takes for an animation to complete'
162 )
163
164 self._lineedit_animation_time = QtWidgets.QLineEdit(self)
165 self._lineedit_animation_time.setValidator(QIntValidator(1, 9999, self))
166 self._lineedit_animation_time.textChanged.connect(self._update_gui)
167
168 label_animation_pause_length = QtWidgets.QLabel(self)
169 label_animation_pause_length.setText('Animation pause length (ms)')
170 label_animation_pause_length.setToolTip(
171     'How many milliseconds to pause for in comma-separated animations'
172 )
173
174 self._lineedit_animation_pause_length = QtWidgets.QLineEdit(self)
175 self._lineedit_animation_pause_length.setValidator(QIntValidator(1, 999, self))
176
177 # Matrix info
178
179 self._checkbox_draw_determinant_parallelogram = QCheckBox(self)
180 self._checkbox_draw_determinant_parallelogram.setText('Draw &determinant parallelogram')
181 self._checkbox_draw_determinant_parallelogram.setToolTip(
182     'Shade the parallelogram representing the determinant of the matrix'
183 )
184 self._checkbox_draw_determinant_parallelogram.clicked.connect(self._update_gui)
185 self._dict_checkboxes['d'] = self._checkbox_draw_determinant_parallelogram
186
187 self._checkbox_show_determinant_value = QCheckBox(self)
188 self._checkbox_show_determinant_value.setText('Show de&terminant value')
189 self._checkbox_show_determinant_value.setToolTip(
190     'Show the value of the determinant inside the parallelogram'
191 )
192 self._dict_checkboxes['t'] = self._checkbox_show_determinant_value
193
194 self._checkbox_draw_eigenvectors = QCheckBox(self)
195 self._checkbox_draw_eigenvectors.setText('Draw &eigenvectors')
196 self._checkbox_draw_eigenvectors.setToolTip('Draw the eigenvectors of the transformations')
197 self._dict_checkboxes['e'] = self._checkbox_draw_eigenvectors
198
199 self._checkbox_draw_eigenlines = QCheckBox(self)
200 self._checkbox_draw_eigenlines.setText('Draw eigen&lines')
201 self._checkbox_draw_eigenlines.setToolTip('Draw the eigenlines (invariant lines) of the transformations')
202 self._dict_checkboxes['l'] = self._checkbox_draw_eigenlines
203
204 # Polygon
205
206 self._checkbox_draw_untransformed_polygon = QCheckBox(self)
207 self._checkbox_draw_untransformed_polygon.setText('&Untransformed polygon')
208 self._checkbox_draw_untransformed_polygon.setToolTip('Draw the untransformed version of the polygon')
209 self._dict_checkboxes['u'] = self._checkbox_draw_untransformed_polygon
210
211 self._checkbox_draw_transformed_polygon = QCheckBox(self)
212 self._checkbox_draw_transformed_polygon.setText('&Transformed &polygon')
213 self._checkbox_draw_transformed_polygon.setToolTip('Draw the transformed version of the polygon')
214 self._dict_checkboxes['p'] = self._checkbox_draw_transformed_polygon
215
216 # Input/output vectors
217
218 self._checkbox_draw_input_vector = QCheckBox(self)
219 self._checkbox_draw_input_vector.setText('Draw the i&nput vector')
220 self._checkbox_draw_input_vector.setToolTip('Draw the input vector (only in the viewport)')
221 self._dict_checkboxes['n'] = self._checkbox_draw_input_vector
222
223 self._checkbox_draw_output_vector = QCheckBox(self)
224 self._checkbox_draw_output_vector.setText('Draw the &output vector')
225 self._checkbox_draw_output_vector.setToolTip('Draw the output vector (only in the viewport)')
226 self._dict_checkboxes['o'] = self._checkbox_draw_output_vector
227
228 # === Arrange the widgets in QGroupBoxes
229

```

```

230     # Basic stuff
231
232     vlay_groupbox_basic_stuff = QVBoxLayout()
233     vlay_groupbox_basic_stuff.setSpacing(20)
234     vlay_groupbox_basic_stuff.addWidget(self._checkbox_draw_background_grid)
235     vlay_groupbox_basic_stuff.addWidget(self._checkbox_draw_transformed_grid)
236     vlay_groupbox_basic_stuff.addWidget(self._checkbox_draw_basis_vectors)
237     vlay_groupbox_basic_stuff.addWidget(self._checkbox_label_basis_vectors)
238
239     groupbox_basic_stuff = QGroupBox('Basic stuff', self)
240     groupbox_basic_stuff.setLayout(vlay_groupbox_basic_stuff)
241
242     # Animations
243
244     hlay_animation_time = QHBoxLayout()
245     hlay_animation_time.addWidget(label_animation_time)
246     hlay_animation_time.addWidget(self._lineedit_animation_time)
247
248     hlay_animation_pause_length = QHBoxLayout()
249     hlay_animation_pause_length.addWidget(label_animation_pause_length)
250     hlay_animation_pause_length.addWidget(self._lineedit_animation_pause_length)
251
252     vlay_groupbox_animations = QVBoxLayout()
253     vlay_groupbox_animations.setSpacing(20)
254     vlay_groupbox_animations.addWidget(self._checkbox_smoother_determinant)
255     vlay_groupbox_animations.addWidget(self._checkbox_applicative_animation)
256     vlay_groupbox_animations.addLayout(hlay_animation_time)
257     vlay_groupbox_animations.addLayout(hlay_animation_pause_length)
258
259     groupbox_animations = QGroupBox('Animations', self)
260     groupbox_animations.setLayout(vlay_groupbox_animations)
261
262     # Matrix info
263
264     vlay_groupbox_matrix_info = QVBoxLayout()
265     vlay_groupbox_matrix_info.setSpacing(20)
266     vlay_groupbox_matrix_info.addWidget(self._checkbox_draw_determinant_parallelogram)
267     vlay_groupbox_matrix_info.addWidget(self._checkbox_show_determinant_value)
268     vlay_groupbox_matrix_info.addWidget(self._checkbox_draw_eigenvectors)
269     vlay_groupbox_matrix_info.addWidget(self._checkbox_draw_eigenlines)
270
271     groupbox_matrix_info = QGroupBox('Matrix info', self)
272     groupbox_matrix_info.setLayout(vlay_groupbox_matrix_info)
273
274     # Polygon
275
276     vlay_groupbox_polygon = QVBoxLayout()
277     vlay_groupbox_polygon.setSpacing(20)
278     vlay_groupbox_polygon.addWidget(self._checkbox_draw_untransformed_polygon)
279     vlay_groupbox_polygon.addWidget(self._checkbox_draw_transformed_polygon)
280
281     groupbox_polygon = QGroupBox('Polygon', self)
282     groupbox_polygon.setLayout(vlay_groupbox_polygon)
283
284     # Input/output vectors
285
286     vlay_groupbox_io_vectors = QVBoxLayout()
287     vlay_groupbox_io_vectors.setSpacing(20)
288     vlay_groupbox_io_vectors.addWidget(self._checkbox_draw_input_vector)
289     vlay_groupbox_io_vectors.addWidget(self._checkbox_draw_output_vector)
290
291     groupbox_io_vectors = QGroupBox('Input/output vectors', self)
292     groupbox_io_vectors.setLayout(vlay_groupbox_io_vectors)
293
294     # Now arrange the groupboxes
295     vlay_left = QVBoxLayout()
296     vlay_left.setSpacing(20)
297     vlay_left.addWidget(groupbox_basic_stuff)
298     vlay_left.addWidget(groupbox_animations)
299
300     vlay_right = QVBoxLayout()
301     vlay_right.setSpacing(20)
302     vlay_right.addWidget(groupbox_matrix_info)

```

```

303         vlay_right.addWidget(groupbox_polygon)
304         vlay_right.addWidget(groupbox_io_vectors)
305
306         options_layout = QHBoxLayout()
307         options_layout.setSpacing(20)
308         options_layout.addLayout(vlay_left)
309         options_layout.addLayout(vlay_right)
310
311         self._setup_layout(options_layout)
312
313         # Finally, we load the current settings and update the GUI
314         self._load_settings()
315         self._update_gui()
316
317     def _load_settings(self) -> None:
318         """Load the current display settings into the widgets."""
319         # Basic stuff
320         self._checkboxbox_draw_background_grid.setChecked(self.display_settings.draw_background_grid)
321         self._checkboxbox_draw_transformed_grid.setChecked(self.display_settings.draw_transformed_grid)
322         self._checkboxbox_draw_basis_vectors.setChecked(self.display_settings.draw_basis_vectors)
323         self._checkboxbox_label_basis_vectors.setChecked(self.display_settings.label_basis_vectors)
324
325         # Animations
326         self._checkboxbox_smooththen_determinant.setChecked(self.display_settings.smooththen_determinant)
327         self._checkboxbox_applicative_animation.setChecked(self.display_settings.applicative_animation)
328         self._lineedit_animation_time.setText(str(self.display_settings.animation_time))
329         self._lineedit_animation_pause_length.setText(str(self.display_settings.animation_pause_length))
330
331         # Matrix info
332         self._checkboxbox_draw_determinant_parallelogram.setChecked(
333             ↪ self.display_settings.draw_determinant_parallelogram)
334         self._checkboxbox_show_determinant_value.setChecked(self.display_settings.show_determinant_value)
335         self._checkboxbox_draw_eigenvectors.setChecked(self.display_settings.draw_eigenvectors)
336         self._checkboxbox_draw_eigenlines.setChecked(self.display_settings.draw_eigenlines)
337
338         # Polygon
339         self._checkboxbox_draw_untransformed_polygon.setChecked(self.display_settings.draw_untransformed_polygon)
340         self._checkboxbox_draw_transformed_polygon.setChecked(self.display_settings.draw_transformed_polygon)
341
342         # Input/output vectors
343         self._checkboxbox_draw_input_vector.setChecked(self.display_settings.draw_input_vector)
344         self._checkboxbox_draw_output_vector.setChecked(self.display_settings.draw_output_vector)
345
346     def _confirm_settings(self) -> None:
347         """Build a :class:`~lintrans.gui.settings.DisplaySettings` object and assign it."""
348         # Basic stuff
349         self.display_settings.draw_background_grid = self._checkboxbox_draw_background_grid.isChecked()
350         self.display_settings.draw_transformed_grid = self._checkboxbox_draw_transformed_grid.isChecked()
351         self.display_settings.draw_basis_vectors = self._checkboxbox_draw_basis_vectors.isChecked()
352         self.display_settings.label_basis_vectors = self._checkboxbox_label_basis_vectors.isChecked()
353
354         # Animations
355         self.display_settings.smooththen_determinant = self._checkboxbox_smooththen_determinant.isChecked()
356         self.display_settings.applicative_animation = self._checkboxbox_applicative_animation.isChecked()
357         self.display_settings.animation_time = int(self._lineedit_animation_time.text())
358         self.display_settings.animation_pause_length = int(self._lineedit_animation_pause_length.text())
359
360         # Matrix info
361         self.display_settings.draw_determinant_parallelogram =
362             ↪ self._checkboxbox_draw_determinant_parallelogram.isChecked()
363         self.display_settings.show_determinant_value = self._checkboxbox_show_determinant_value.isChecked()
364         self.display_settings.draw_eigenvectors = self._checkboxbox_draw_eigenvectors.isChecked()
365         self.display_settings.draw_eigenlines = self._checkboxbox_draw_eigenlines.isChecked()
366
367         # Polygon
368         self.display_settings.draw_untransformed_polygon = self._checkboxbox_draw_untransformed_polygon.isChecked()
369         self.display_settings.draw_transformed_polygon = self._checkboxbox_draw_transformed_polygon.isChecked()
370
371         # Input/output vectors
372         self.display_settings.draw_input_vector = self._checkboxbox_draw_input_vector.isChecked()
373         self.display_settings.draw_output_vector = self._checkboxbox_draw_output_vector.isChecked()
374
375         self.accept()

```

```

374
375     def _reset_settings(self) -> None:
376         """Reset the display settings to their defaults."""
377         self.display_settings = DisplaySettings()
378         self._load_settings()
379         self._update_gui()
380
381     def _update_gui(self) -> None:
382         """Update the GUI according to other widgets in the GUI.
383
384         For example, this method updates which checkboxes are enabled based on the values of other checkboxes.
385         """
386         self._checkbox_show_determinant_value.setEnabled(self._checkbox_draw_determinant_parallelogram.isChecked())
387         self._checkbox_label_basis_vectors.setEnabled(self._checkbox_draw_basis_vectors.isChecked())
388
389         try:
390             self._button_confirm.setEnabled(int(self._lineEdit_animation_time.text()) >= 10)
391         except ValueError:
392             self._button_confirm.setEnabled(False)
393
394     def keyPressEvent(self, event: QKeyEvent) -> None:
395         """Handle a :class:`QKeyEvent` by manually activating toggling checkboxes.
396
397         Qt handles these shortcuts automatically and allows the user to do ``Alt + Key``
398         to activate a simple shortcut defined with ``&``. However, I like to be able to
399         just hit ``Key`` and have the shortcut activate.
400         """
401         letter = event.text().lower()
402         key = event.key()
403
404         if letter in self._dict_checkboxes:
405             self._dict_checkboxes[letter].animateClick()
406
407         # Return or keypad enter
408         elif key == Qt.Key_Return or key == Qt.Key_Enter:
409             self._button_confirm.click()
410
411         # Escape
412         elif key == Qt.Key_Escape:
413             self._button_cancel.click()
414
415         else:
416             event.ignore()
417             return
418
419         event.accept()

```

## A.14 gui/dialogs/misc.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides miscellaneous dialog classes like :class:`AboutDialog`."""
8
9  from __future__ import annotations
10
11  import os
12  import platform
13  from typing import Dict, List, Optional, Tuple, Union
14
15  from PyQt5.QtCore import PYQT_VERSION_STR, QT_VERSION_STR, Qt, pyqtSlot
16  from PyQt5.QtGui import QKeySequence
17  from PyQt5.QtWidgets import QDialog, QDialogBox, QFileDialog, QGridLayout, QGroupBox,
18  QHBoxLayout, QLabel, QPushButton, QRadioButton,
19  QShortcut, QSizePolicy, QSpacerItem,
20  QStackedLayout, QVBoxLayout, QWidget
21

```

```

22 import lintrans
23 from lintrans.global_settings import GlobalSettings
24 from lintrans.gui.plots import DefinePolygonWidget
25 from lintrans.matrices import MatrixWrapper
26 from lintrans.matrices.utility import round_float
27 from lintrans.typing_ import MatrixType, is_matrix_type
28 from lintrans.updating import update_lintrans_in_background
29
30
31 class FixedSizeDialog(QDialog):
32     """A simple superclass to create modal dialog boxes with fixed size.
33
34     We override the :meth:`open` method to set the fixed size as soon as the dialog is opened modally.
35     """
36
37     def __init__(self, *args, **kwargs) -> None:
38         """Set the :cenum:`Qt::WA_DeleteOnClose` attribute to ensure deletion of dialog."""
39         super().__init__(*args, **kwargs)
40         self.setAttribute(Qt.WA_DeleteOnClose)
41         self.setWindowFlag(Qt.WindowContextHelpButtonHint, False)
42
43     def open(self) -> None:
44         """Override :meth:`QDialog.open` to set the dialog to a fixed size."""
45         super().open()
46         self.setFixedSize(self.size())
47
48
49 class AboutDialog(FixedSizeDialog):
50     """A simple dialog class to display information about the app to the user.
51
52     It only has an :meth:`__init__` method because it only has label widgets, so no other methods are necessary
53     ↪ here.
54     """
55
56     def __init__(self, *args, **kwargs):
57         """Create an :class:`AboutDialog` object with all the label widgets."""
58         super().__init__(*args, **kwargs)
59
60         self.setWindowTitle('About lintrans')
61
62         # === Create the widgets
63
64         label_title = QLabel(self)
65         label_title.setText(f'lintrans (version {lintrans.__version__})')
66         label_title.setAlignment(Qt.AlignCenter)
67
68         font_title = label_title.font()
69         font_title.setPointSize(font_title.pointSize() * 2)
70         label_title.setFont(font_title)
71
72         label_version_info = QLabel(self)
73         label_version_info.setText(
74             f'With Python version {platform.python_version()}\n'
75             f'Qt version {QT_VERSION_STR} and PyQt5 version {PYQT_VERSION_STR}\n'
76             f'Running on {platform.platform()}'
77         )
78         label_version_info.setAlignment(Qt.AlignCenter)
79
80         label_info = QLabel(self)
81         label_info.setText(
82             'lintrans is a program designed to help visualise<br>'
83             '2D linear transformations represented with matrices.<br><br>'
84             'It's designed for teachers and students and all feedback<br>'
85             'is greatly appreciated. Go to <em>Help</em> &gt; <em>Give feedback</em><br>'
86             'to report a bug or suggest a new feature, or you can<br>email me directly at '
87             '<a href="mailto:dyson.dyson@icloud.com" style="color: black;">dyson.dyson@icloud.com</a>.'
88         )
89         label_info.setAlignment(Qt.AlignCenter)
90         label_info.setTextFormat(Qt.RichText)
91         label_info.setOpenExternalLinks(True)
92
93         label_copyright = QLabel(self)
94         label_copyright.setText(

```



```

94         'This program is free software.<br>Copyright 2021-2022 D. Dyson (DoctorDalek1963).<br>'
95         'This program is licensed under GPLv3, which can be found '
96         '<a href="https://www.gnu.org/licenses/gpl-3.0.html" style="color: black;">here</a>.'
97     )
98     label_copyright.setAlignment(Qt.AlignCenter)
99     label_copyright.setTextFormat(Qt.RichText)
100    label_copyright.setOpenExternalLinks(True)
101
102    # === Arrange the widgets
103
104    self.setContentsMargins(10, 10, 10, 10)
105
106    vlay = QVBoxLayout()
107    vlay.setSpacing(20)
108    vlay.addWidget(label_title)
109    vlay.addWidget(label_version_info)
110    vlay.addWidget(label_info)
111    vlay.addWidget(label_copyright)
112
113    self.setLayout(vlay)
114
115
116    class InfoPanelDialog(FixedSizeDialog):
117        """A simple dialog class to display an info panel that shows all currently defined matrices."""
118
119        def __init__(self, matrix_wrapper: MatrixWrapper, *args, **kwargs):
120            """Create the dialog box with all the widgets needed to show the information."""
121            super().__init__(*args, **kwargs)
122            self.matrix_wrapper = matrix_wrapper
123
124            self._matrices: Dict[str, Optional[Union[MatrixType, str]]] = {
125                name: value
126                for name, value in self.matrix_wrapper.get_defined_matrices()
127            }
128
129            self.setWindowTitle('Defined matrices')
130            self.setContentsMargins(10, 10, 10, 10)
131
132            self._stacked_layout = QStackedLayout(self)
133            self.setLayout(self._stacked_layout)
134
135            self._draw_ui()
136
137        def _draw_ui(self) -> None:
138            grid_layout = QGridLayout()
139            grid_layout.setSpacing(20)
140
141            for i, (name, value) in enumerate(self._matrices.items()):
142                if value is None:
143                    continue
144
145                grid_layout.addWidget(
146                    self._get_full_matrix_widget(name, value),
147                    i % 4,
148                    i // 4,
149                    Qt.AlignCenter
150                )
151
152            container = QWidget(self)
153            container.setLayout(grid_layout)
154            self._stacked_layout.setCurrentIndex(self._stacked_layout.addWidget(container))
155
156        def _undefine_matrix(self, name: str) -> None:
157            """Undefine the given matrix and redraw the dialog."""
158            for x in self.matrix_wrapper.undefine_matrix(name):
159                self._matrices[x] = None
160
161            self._draw_ui()
162
163        def _get_full_matrix_widget(self, name: str, value: Union[MatrixType, str]) -> QWidget:
164            """Return a :class:`QWidget` containing the whole matrix widget composition.
165
166            Each defined matrix will get a widget group. Each group will be a label for the name,

```

```

167         a label for '=', and a container widget to either show the matrix numerically, or to
168         show the expression that it's defined as.
169
170         See :meth:`_get_matrix_data_widget`.
171         """
172         bold_font = self.font()
173         bold_font.setBold(True)
174
175         label_name = QLabel(self)
176         label_name.setText(name)
177         label_name.setFont(bold_font)
178
179         widget_matrix = self._get_matrix_data_widget(value)
180
181         hlay = QHBoxLayout()
182         hlay.setSpacing(10)
183         hlay.addWidget(label_name)
184         hlay.addWidget(QLabel('=', self))
185         hlay.addWidget(widget_matrix)
186
187         vlay = QVBoxLayout()
188         vlay.setSpacing(10)
189         vlay.addLayout(hlay)
190
191         if name != 'I':
192             button_undefine = QPushButton(self)
193             button_undefine.setText('Undefine')
194             button_undefine.clicked.connect(lambda: self._undefine_matrix(name))
195
196             vlay.addWidget(button_undefine)
197
198         groupbox = QGroupBox(self)
199         groupbox.setContentsMargins(10, 10, 10, 10)
200         groupbox.setLayout(vlay)
201
202         lay = QVBoxLayout()
203         lay.setSpacing(0)
204         lay.addWidget(groupbox)
205
206         container = QWidget(self)
207         container.setLayout(lay)
208
209         return container
210
211 def _get_matrix_data_widget(self, matrix: Union[MatrixType, str]) -> QWidget:
212     """Return a :class:`QWidget` containing the value of the matrix.
213
214     If the matrix is defined as an expression, it will be a simple :class:`QLabel`.
215     If the matrix is defined as a matrix, it will be a :class:`QWidget` container
216     with multiple :class:`QLabel` objects in it.
217     """
218     if isinstance(matrix, str):
219         label = QLabel(self)
220         label.setText(matrix)
221         return label
222
223     elif is_matrix_type(matrix):
224         # tl = top left, br = bottom right, etc.
225         label_tl = QLabel(self)
226         label_tl.setText(round_float(matrix[0][0]))
227
228         label_tr = QLabel(self)
229         label_tr.setText(round_float(matrix[0][1]))
230
231         label_bl = QLabel(self)
232         label_bl.setText(round_float(matrix[1][0]))
233
234         label_br = QLabel(self)
235         label_br.setText(round_float(matrix[1][1]))
236
237         # The parens need to be bigger than the numbers, but increasing the font size also
238         # makes the font thicker, so we have to reduce the font weight by the same factor
239         font_parens = self.font()

```

```

240         font_parens.setPointSize(int(font_parens.pointSize() * 2.5))
241         font_parens.setWeight(int(font_parens.weight() / 2.5))
242
243         label_paren_left = QLabel(self)
244         label_paren_left.setText('(')
245         label_paren_left.setFont(font_parens)
246
247         label_paren_right = QLabel(self)
248         label_paren_right.setText(')')
249         label_paren_right.setFont(font_parens)
250
251         container = QWidget(self)
252         grid_layout = QGridLayout()
253
254         grid_layout.addWidget(label_paren_left, 0, 0, -1, 1)
255         grid_layout.addWidget(label_tl, 0, 1)
256         grid_layout.addWidget(label_tr, 0, 2)
257         grid_layout.addWidget(label_bl, 1, 1)
258         grid_layout.addWidget(label_br, 1, 2)
259         grid_layout.addWidget(label_paren_right, 0, 3, -1, 1)
260
261         container.setLayout(grid_layout)
262
263         return container
264
265     raise ValueError('Matrix was not MatrixType or str')
266
267
268 class FileSelectDialog(QFileDialog):
269     """A subclass of :class:`QFileDialog` that fixes an issue with the default suffix on UNIX platforms."""
270
271     def selectedFiles(self) -> List[str]:
272         """Return a list of strings containing the absolute paths of the selected files in the dialog.
273
274         There is an issue on UNIX platforms where a hidden directory will be recognised as a suffix.
275         For example, ``/home/dyson/.lintrans/saves/test`` should have ``.lt`` appended, but
276         ``.lintrans/saves/test`` gets recognised as the suffix, so the default suffix is not added.
277
278         To fix this, we just look at the basename and see if it needs a suffix added. We do this for
279         every name in the list, but there should be just one name, since this class is only intended
280         to be used for saving files. We still return the full list of filenames.
281         """
282         selected_files: List[str] = []
283
284         for filename in super().selectedFiles():
285             # path will be the full path of the file, without the extension
286             # This method understands hidden directories on UNIX platforms
287             path, ext = os.path.splitext(filename)
288
289             if ext == '':
290                 ext = '.' + self.defaultSuffix()
291
292             selected_files.append(''.join((path, ext)))
293
294         return selected_files
295
296
297 class DefinePolygonDialog(FixedSizeDialog):
298     """This dialog class allows the use to define a polygon with :class:`DefinePolygonWidget`."""
299
300     def __init__(self, *args, polygon_points: List[Tuple[float, float]], **kwargs) -> None:
301         """Create the dialog with the :class:`DefinePolygonWidget` widget."""
302         super().__init__(*args, **kwargs)
303
304         self.setWindowTitle('Define a polygon')
305         self.setMinimumSize(700, 550)
306
307         self.polygon_points = polygon_points
308
309         # === Create the widgets
310
311         self._polygon_widget = DefinePolygonWidget(polygon_points=polygon_points)
312

```

```

313         button_confirm = QPushButton(self)
314         button_confirm.setText('Confirm')
315         button_confirm.clicked.connect(self._confirm_polygon)
316         button_confirm.setToolTip('Confirm this polygon<br><b>(Ctrl + Enter)</b>')
317         QShortcut(QKeySequence('Ctrl+Return'), self).activated.connect(button_confirm.click)
318
319         button_cancel = QPushButton(self)
320         button_cancel.setText('Cancel')
321         button_cancel.clicked.connect(self.reject)
322         button_cancel.setToolTip('Discard this polygon<br><b>(Escape)</b>')
323
324         button_reset = QPushButton(self)
325         button_reset.setText('Reset polygon')
326         button_reset.clicked.connect(self._polygon_widget.reset_polygon)
327         button_reset.setToolTip('Remove all points of the polygon<br><b>(Ctrl + R)</b>')
328         QShortcut(QKeySequence('Ctrl+R'), self).activated.connect(button_reset.click)
329
330         # === Arrange the widgets
331
332         self.setContentsMargins(10, 10, 10, 10)
333
334         hlay_buttons = QHBoxLayout()
335         hlay_buttons.setSpacing(20)
336         hlay_buttons.addWidget(button_reset)
337         hlay_buttons.addItem(QSpacerItem(50, 5, hPolicy=QSizePolicy.Expanding, vPolicy=QSizePolicy.Minimum))
338         hlay_buttons.addWidget(button_cancel)
339         hlay_buttons.addWidget(button_confirm)
340
341         vlay = QVBoxLayout()
342         vlay.setSpacing(20)
343         vlay.addWidget(self._polygon_widget)
344         vlay.addLayout(hlay_buttons)
345
346         self.setLayout(vlay)
347
348     @pyqtSlot()
349     def _confirm_polygon(self) -> None:
350         """Confirm the polygon that the user has defined."""
351         self.polygon_points = self._polygon_widget.points
352         self.accept()
353
354
355     class PromptUpdateDialog(FixedSizeDialog):
356         """A simple dialog to ask the user if they want to upgrade their lintrans installation."""
357
358         def __init__(self, *args, new_version: str, **kwargs) -> None:
359             """Create the dialog with all its widgets."""
360             super().__init__(*args, **kwargs)
361
362             if new_version.startswith('v'):
363                 new_version = new_version[1:]
364
365             self.setWindowTitle('Update available')
366
367             # === Create the widgets
368
369             label_info = QLabel(self)
370             label_info.setText(
371                 'A new version of lintrans is available!\n'
372                 f'({lintrans.__version__} -> {new_version})\n\n'
373                 'Would you like to update now?'
374             )
375             label_info.setAlignment(Qt.AlignCenter)
376
377             label_explanation = QLabel(self)
378             label_explanation.setText(
379                 'The update will run silently in the background, so you can keep using lintrans uninterrupted.\n'
380                 f'You can change your choice at any time by editing {GlobalSettings().get_settings_file()}'
381             )
382             label_explanation.setAlignment(Qt.AlignCenter)
383
384             font = label_explanation.font()
385             font.setPointSize(int(0.9 * font.pointSize()))

```

```

386         font.setItalic(True)
387         label_explanation.setFont(font)
388
389         groupbox_radio_buttons = QGroupBox(self)
390
391         self._radio_button_auto = QRadioButton('Always update automatically', groupbox_radio_buttons)
392         self._radio_button_prompt = QRadioButton('Always ask to update', groupbox_radio_buttons)
393         self._radio_button_never = QRadioButton('Never update', groupbox_radio_buttons)
394
395         # If this prompt is even appearing, then the update type must be 'prompt'
396         self._radio_button_prompt.setChecked(True)
397
398         button_remind_me_later = QPushButton('Remind me later', self)
399         button_remind_me_later.clicked.connect(lambda: self._save_choice_and_update(False))
400         button_remind_me_later.setShortcut(Qt.Key_Escape)
401         button_remind_me_later.setFocus()
402
403         button_update_now = QPushButton('Update now', self)
404         button_update_now.clicked.connect(lambda: self._save_choice_and_update(True))
405
406         # == Arrange the widgets
407
408         self.setContentsMargins(10, 10, 10, 10)
409
410         hlay_buttons = QHBoxLayout()
411         hlay_buttons.setSpacing(20)
412         hlay_buttons.addWidget(button_remind_me_later)
413         hlay_buttons.addWidget(button_update_now)
414
415         vlay = QVBoxLayout()
416         vlay.setSpacing(20)
417         vlay.addWidget(label_info)
418
419         vlay_radio_buttons = QVBoxLayout()
420         vlay_radio_buttons.setSpacing(10)
421         vlay_radio_buttons.addWidget(self._radio_button_auto)
422         vlay_radio_buttons.addWidget(self._radio_button_prompt)
423         vlay_radio_buttons.addWidget(self._radio_button_never)
424
425         groupbox_radio_buttons.setLayout(vlay_radio_buttons)
426
427         vlay.addWidget(groupbox_radio_buttons)
428         vlay.addWidget(label_explanation)
429         vlay.addLayout(hlay_buttons)
430
431         self.setLayout(vlay)
432
433     def _save_choice_and_update(self, update_now: bool) -> None:
434         """Save the user's choice of how to update and optionally trigger an update now."""
435         gs = GlobalSettings()
436         if self._radio_button_auto.isChecked():
437             gs.set_update_type(gs.UpdateType.auto)
438
439         elif self._radio_button_prompt.isChecked():
440             gs.set_update_type(gs.UpdateType.prompt)
441
442         elif self._radio_button_never.isChecked():
443             gs.set_update_type(gs.UpdateType.never)
444
445         if update_now:
446             # We don't need to check because we'll only get here if we know a new version is available
447             update_lintrans_in_background(check=False)
448             self.accept()
449         else:
450             self.reject()

```

## A.15 gui/dialogs/\_\_init\_\_.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)

```

```

3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """This package provides separate dialogs for the main GUI.
8
9 These dialogs are for defining new matrices in different ways and editing settings.
10 """
11
12 from .define_new_matrix import (DefineAsExpressionDialog, DefineMatrixDialog,
13                                DefineNumericallyDialog, DefineVisuallyDialog)
14 from .misc import (AboutDialog, DefinePolygonDialog, FileSelectDialog,
15                   InfoPanelDialog, PromptUpdateDialog)
16 from .settings import DisplaySettingsDialog
17
18 __all__ = ['AboutDialog', 'DefineAsExpressionDialog', 'DefineMatrixDialog',
19           'DefineNumericallyDialog', 'DefinePolygonDialog', 'DefineVisuallyDialog',
20           'DisplaySettingsDialog', 'FileSelectDialog', 'InfoPanelDialog', 'PromptUpdateDialog']

```

## A.16 gui/plots/widgets.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """This module provides the actual widgets that can be used to visualize transformations in the GUI."""
8
9 from __future__ import annotations
10
11 import operator
12 from abc import abstractmethod
13 from copy import copy
14 from math import dist
15 from typing import List, Optional, Tuple
16
17 from PyQt5.QtCore import QPointF, Qt, pyqtSlot
18 from PyQt5.QtGui import (QBrush, QColor, QMouseEvent, QPainter, QPaintEvent,
19                          QPen, QPolygonF)
20
21 from lintrans.gui.settings import DisplaySettings
22 from lintrans.typing_ import MatrixType
23
24 from .classes import InteractivePlot, VisualizeTransformationPlot
25
26
27 class VisualizeTransformationWidget(VisualizeTransformationPlot):
28     """This widget is used in the main window to visualize transformations.
29
30     It handles all the rendering itself, and the only method that the user needs to care about
31     is :meth:`plot_matrix`, which allows you to visualize the given matrix transformation.
32     """
33
34     _COLOUR_OUTPUT_VECTOR = QColor('#f7c216')
35
36     def __init__(self, *args, display_settings: DisplaySettings, polygon_points: List[Tuple[float, float]],
37                  ↪ **kwargs):
38         """Create the widget and assign its display settings, passing ``*args`` and ``**kwargs`` to super."""
39         super().__init__(*args, **kwargs)
40
41         self.display_settings = display_settings
42         self.polygon_points = polygon_points
43
44     def plot_matrix(self, matrix: MatrixType) -> None:
45         """Plot the given matrix on the grid by setting the basis vectors.
46
47         .. warning:: This method does not call :meth:`QWidget.update()`. This must be done by the caller.
48
49         :param MatrixType matrix: The matrix to plot

```

```

49         """
50         self.point_i = (matrix[0][0], matrix[1][0])
51         self.point_j = (matrix[0][1], matrix[1][1])
52
53     def _draw_scene(self, painter: QPainter) -> None:
54         """Draw the default scene of the transformation.
55
56         This method exists to make it easier to split the main viewport from visual definitions while
57         not using multiple :class:`QPainter` objects from a single :meth:`paintEvent` call in a subclass.
58         """
59         painter.setRenderHint(QPainter.Antialiasing)
60         painter.setBrush(Qt.NoBrush)
61
62         self._draw_background(painter, self.display_settings.draw_background_grid)
63
64         if self.display_settings.draw_eigenlines:
65             self._draw_eigenlines(painter)
66
67         if self.display_settings.draw_eigenvectors:
68             self._draw_eigenvectors(painter)
69
70         if self.display_settings.draw_determinant_parallelogram:
71             self._draw_determinant_parallelogram(painter)
72
73             if self.display_settings.show_determinant_value:
74                 self._draw_determinant_text(painter)
75
76         if self.display_settings.draw_transformed_grid:
77             self._draw_transformed_grid(painter)
78
79         if self.display_settings.draw_basis_vectors:
80             self._draw_basis_vectors(painter)
81
82             if self.display_settings.label_basis_vectors:
83                 self._draw_basis_vector_labels(painter)
84
85         if self.display_settings.draw_untransformed_polygon:
86             self._draw_untransformed_polygon(painter)
87
88         if self.display_settings.draw_transformed_polygon:
89             self._draw_transformed_polygon(painter)
90
91     @abstractmethod
92     def paintEvent(self, event: QPaintEvent) -> None:
93         """Paint the scene of the transformation."""
94
95
96 class MainViewportWidget(VisualizeTransformationWidget, InteractivePlot):
97     """This is the widget for the main viewport.
98
99     It extends :class:`VisualizeTransformationWidget` with input and output vectors.
100     """
101
102     def __init__(self, *args, **kwargs):
103         """Create the main viewport widget with its input point."""
104         super().__init__(*args, **kwargs)
105
106         self.point_input_vector: Tuple[float, float] = (1, 1)
107         self._dragging_vector: bool = False
108
109     def _draw_input_vector(self, painter: QPainter) -> None:
110         """Draw the input vector."""
111         pen = QPen(QColor('#000000'), self._WIDTH_VECTOR_LINE)
112         painter.setPen(pen)
113
114         x, y = self.canvas_coords(*self.point_input_vector)
115         painter.drawLine(*self._canvas_origin, x, y)
116
117         painter.setBrush(self._BRUSH_SOLID_WHITE)
118
119         painter.setPen(Qt.NoPen)
120         painter.drawPie(
121             x - self._CURSOR_EPSILON,

```

```

122         y - self._CURSOR_EPSILON,
123         2 * self._CURSOR_EPSILON,
124         2 * self._CURSOR_EPSILON,
125         0,
126         16 * 360
127     )
128
129     painter.setPen(pen)
130     painter.drawArc(
131         x - self._CURSOR_EPSILON,
132         y - self._CURSOR_EPSILON,
133         2 * self._CURSOR_EPSILON,
134         2 * self._CURSOR_EPSILON,
135         0,
136         16 * 360
137     )
138
139     def _draw_output_vector(self, painter: QPainter) -> None:
140         """Draw the output vector."""
141         painter.setPen(QPen(self._COLOUR_OUTPUT_VECTOR, self._WIDTH_VECTOR_LINE))
142         painter.setBrush(QBrush(self._COLOUR_OUTPUT_VECTOR, Qt.SolidPattern))
143
144         x, y = self.canvas_coords(*(self._matrix @ self.point_input_vector))
145
146         painter.drawLine(*self._canvas_origin, x, y)
147         painter.drawPie(
148             x - self._CURSOR_EPSILON,
149             y - self._CURSOR_EPSILON,
150             2 * self._CURSOR_EPSILON,
151             2 * self._CURSOR_EPSILON,
152             0,
153             16 * 360
154         )
155
156     def paintEvent(self, event: QPaintEvent) -> None:
157         """Paint the scene by just calling :meth:`_draw_scene` and drawing the I/O vectors."""
158         painter = QPainter()
159         painter.begin(self)
160
161         self._draw_scene(painter)
162
163         if self.display_settings.draw_output_vector:
164             self._draw_output_vector(painter)
165
166         if self.display_settings.draw_input_vector:
167             self._draw_input_vector(painter)
168
169         painter.end()
170         event.accept()
171
172     def mousePressEvent(self, event: QMouseEvent) -> None:
173         """Check if the user has clicked on the input vector."""
174         cursor_pos = (event.x(), event.y())
175
176         if event.button() != Qt.LeftButton:
177             event.ignore()
178             return
179
180         if self._is_within_epsilon(cursor_pos, self.point_input_vector):
181             self._dragging_vector = True
182
183         event.accept()
184
185     def mouseReleaseEvent(self, event: QMouseEvent) -> None:
186         """Stop dragging the input vector."""
187         if event.button() == Qt.LeftButton:
188             self._dragging_vector = False
189             event.accept()
190         else:
191             event.ignore()
192
193     def mouseMoveEvent(self, event: QMouseEvent) -> None:
194         """Drag the input vector if the user has clicked on it."""

```



```

195         if not self._dragging_vector:
196             event.ignore()
197             return
198
199         x, y = self._round_to_int_coord(self._grid_coords(event.x(), event.y()))
200         self.point_input_vector = (x, y)
201
202         self.update()
203         event.accept()
204
205
206 class DefineMatrixVisuallyWidget(VisualizeTransformationWidget, InteractivePlot):
207     """This widget allows the user to visually define a matrix.
208
209     This is just the widget itself. If you want the dialog, use
210     :class:`~lintrans.gui.dialogs.define_new_matrix.DefineVisuallyDialog`.
211     """
212
213     def __init__(
214         self,
215         *args,
216         display_settings: DisplaySettings,
217         polygon_points: List[Tuple[float, float]],
218         input_vector: Tuple[float, float],
219         **kwargs
220     ) -> None:
221         """Create the widget and enable mouse tracking. ``*args`` and ``**kwargs`` are passed to ``super()``."""
222         super().__init__(*args, display_settings=display_settings, polygon_points=polygon_points, **kwargs)
223
224         self._input_vector = input_vector
225         self._dragged_point: Tuple[float, float] | None = None
226
227     def _draw_input_vector(self, painter: QPainter) -> None:
228         """Draw the input vector."""
229         color = QColor('#000000')
230         color.setAlpha(0x88)
231         pen = QPen(color, self._WIDTH_VECTOR_LINE)
232         painter.setPen(pen)
233
234         x, y = self.canvas_coords(*self._input_vector)
235         painter.drawLine(*self._canvas_origin, x, y)
236
237         painter.setBrush(self._BRUSH_SOLID_WHITE)
238
239         painter.setPen(Qt.NoPen)
240         painter.drawPie(
241             x - self._CURSOR_EPSILON,
242             y - self._CURSOR_EPSILON,
243             2 * self._CURSOR_EPSILON,
244             2 * self._CURSOR_EPSILON,
245             0,
246             16 * 360
247         )
248
249         painter.setPen(pen)
250         painter.drawArc(
251             x - self._CURSOR_EPSILON,
252             y - self._CURSOR_EPSILON,
253             2 * self._CURSOR_EPSILON,
254             2 * self._CURSOR_EPSILON,
255             0,
256             16 * 360
257         )
258
259     def _draw_output_vector(self, painter: QPainter) -> None:
260         """Draw the output vector."""
261         color = copy(self._COLOUR_OUTPUT_VECTOR)
262         color.setAlpha(0x88)
263         painter.setPen(QPen(color, self._WIDTH_VECTOR_LINE))
264         painter.setBrush(QBrush(self._COLOUR_OUTPUT_VECTOR, Qt.SolidPattern))
265
266         x, y = self.canvas_coords(*(self._matrix @ self._input_vector))
267

```

```

268     painter.drawLine(*self._canvas_origin, x, y)
269     painter.drawPie(
270         x - self._CURSOR_EPSILON,
271         y - self._CURSOR_EPSILON,
272         2 * self._CURSOR_EPSILON,
273         2 * self._CURSOR_EPSILON,
274         0,
275         16 * 360
276     )
277
278     def paintEvent(self, event: QPaintEvent) -> None:
279         """Paint the scene by just calling :meth:`_draw_scene`."""
280         painter = QPainter()
281         painter.begin(self)
282
283         self._draw_scene(painter)
284
285         if self.display_settings.draw_output_vector:
286             self._draw_output_vector(painter)
287
288         if self.display_settings.draw_input_vector:
289             self._draw_input_vector(painter)
290
291         painter.end()
292         event.accept()
293
294     def mousePressEvent(self, event: QMouseEvent) -> None:
295         """Set the dragged point if the cursor is within :attr:`_CURSOR_EPSILON`."""
296         cursor_pos = (event.x(), event.y())
297
298         if event.button() != Qt.LeftButton:
299             event.ignore()
300             return
301
302         for point in (self.point_i, self.point_j):
303             if self._is_within_epsilon(cursor_pos, point):
304                 self._dragged_point = point[0], point[1]
305
306         event.accept()
307
308     def mouseReleaseEvent(self, event: QMouseEvent) -> None:
309         """Handle the mouse click being released by unsetting the dragged point."""
310         if event.button() == Qt.LeftButton:
311             self._dragged_point = None
312             event.accept()
313         else:
314             event.ignore()
315
316     def mouseMoveEvent(self, event: QMouseEvent) -> None:
317         """Handle the mouse moving on the canvas."""
318         if self._dragged_point is None:
319             event.ignore()
320             return
321
322         x, y = self._round_to_int_coord(self._grid_coords(event.x(), event.y()))
323
324         if self._dragged_point == self.point_i:
325             self.point_i = x, y
326
327         elif self._dragged_point == self.point_j:
328             self.point_j = x, y
329
330         self._dragged_point = x, y
331
332         self.update()
333         event.accept()
334
335
336     class DefinePolygonWidget(InteractivePlot):
337         """This widget allows the user to define a polygon by clicking and dragging points on the canvas."""
338
339         def __init__(self, *args, polygon_points: List[Tuple[float, float]], **kwargs):
340             """Create the widget with a list of points and a dragged point index."""

```

```

341         super().__init__(*args, **kwargs)
342
343         self._dragged_point_index: Optional[int] = None
344         self.points = polygon_points.copy()
345
346     @pyqtSlot()
347     def reset_polygon(self) -> None:
348         """Reset the polygon and update the widget."""
349         self.points = []
350         self.update()
351
352     def mousePressEvent(self, event: QMouseEvent) -> None:
353         """Handle the mouse being clicked by adding a point or setting the dragged point index to an existing
354         ↔ point."""
355         if event.button() not in (Qt.LeftButton, Qt.RightButton):
356             event.ignore()
357             return
358
359         canvas_pos = (event.x(), event.y())
360         grid_pos = self._grid_coords(*canvas_pos)
361
362         if event.button() == Qt.LeftButton:
363             for i, point in enumerate(self.points):
364                 if self._is_within_epsilon(canvas_pos, point):
365                     self._dragged_point_index = i
366                     event.accept()
367                     return
368
369         new_point = self._round_to_int_coord(grid_pos)
370
371         if len(self.points) < 2:
372             self.points.append(new_point)
373             self._dragged_point_index = -1
374         else:
375             # FIXME: This algorithm doesn't work very well when the new point is far away
376             # from the existing polygon; it just picks the longest side
377
378             # Get a list of line segments and a list of their lengths
379             line_segments = list(zip(self.points, self.points[1:])) + [(self.points[-1], self.points[0])]
380             segment_lengths = map(lambda t: dist(*t), line_segments)
381
382             # Get the distance from each point in the polygon to the new point
383             distances_to_point = [dist(p, new_point) for p in self.points]
384
385             # For each pair of list-adjacent points, zip their distances to
386             # the new point into a tuple, and add them together
387             # This gives us the lengths of the catheti of the triangles that
388             # connect the new point to each pair of adjacent points
389             dist_to_point_pairs = list(zip(distances_to_point, distances_to_point[1:])) + \
390                 [(distances_to_point[-1], distances_to_point[0])]
391
392             # mypy doesn't like the use of sum for some reason. Just ignore it
393             point_triangle_lengths = map(sum, dist_to_point_pairs) # type: ignore[arg-type]
394
395             # The normalized distance is the sum of the distances to the ends of the line segment
396             # (point_triangle_lengths) divided by the length of the segment
397             normalized_distances = list(map(operator.truediv, point_triangle_lengths, segment_lengths))
398
399             # Get the best distance and insert this new point just after the point with that index
400             # This will put it in the middle of the closest line segment
401             best_distance = min(normalized_distances)
402             index = 1 + normalized_distances.index(best_distance)
403
404             self.points.insert(index, new_point)
405             self._dragged_point_index = index
406
407         elif event.button() == Qt.RightButton:
408             for i, point in enumerate(self.points):
409                 if self._is_within_epsilon(canvas_pos, point):
410                     self.points.pop(i)
411                     break
412
413         self.update()

```

```

413         event.accept()
414
415     def mouseReleaseEvent(self, event: QMouseEvent) -> None:
416         """Handle the mouse click being released by unsetting the dragged point index."""
417         if event.button() == Qt.LeftButton:
418             self._dragged_point_index = None
419             event.accept()
420         else:
421             event.ignore()
422
423     def mouseMoveEvent(self, event: QMouseEvent) -> None:
424         """Handle mouse movement by dragging the selected point."""
425         if self._dragged_point_index is None:
426             event.ignore()
427             return
428
429         x, y = self._round_to_int_coord(self._grid_coords(event.x(), event.y()))
430
431         self.points[self._dragged_point_index] = x, y
432
433         self.update()
434
435         event.accept()
436
437     def _draw_polygon(self, painter: QPainter) -> None:
438         """Draw the polygon with circles at its vertices."""
439         painter.setPen(self._PEN_POLYGON)
440
441         if len(self.points) > 2:
442             painter.drawPolygon(QPolygonF(
443                 [QPointF(*self.canvas_coords(*p)) for p in self.points]
444             ))
445         elif len(self.points) == 2:
446             painter.drawLine(
447                 *self.canvas_coords(*self.points[0]),
448                 *self.canvas_coords(*self.points[1])
449             )
450
451         painter.setBrush(self._BRUSH_SOLID_WHITE)
452
453         for point in self.points:
454             x, y = self.canvas_coords(*point)
455
456             painter.setPen(Qt.NoPen)
457             painter.drawPie(
458                 x - self._CURSOR_EPSILON,
459                 y - self._CURSOR_EPSILON,
460                 2 * self._CURSOR_EPSILON,
461                 2 * self._CURSOR_EPSILON,
462                 0,
463                 16 * 360
464             )
465
466             painter.setPen(self._PEN_POLYGON)
467             painter.drawArc(
468                 x - self._CURSOR_EPSILON,
469                 y - self._CURSOR_EPSILON,
470                 2 * self._CURSOR_EPSILON,
471                 2 * self._CURSOR_EPSILON,
472                 0,
473                 16 * 360
474             )
475
476         painter.setBrush(Qt.NoBrush)
477
478     def paintEvent(self, event: QPaintEvent) -> None:
479         """Draw the polygon on the canvas."""
480         painter = QPainter()
481         painter.begin(self)
482
483         painter.setRenderHint(QPainter.Antialiasing)
484         painter.setBrush(Qt.NoBrush)
485

```

```

486         self._draw_background(painter, True)
487
488         self._draw_polygon(painter)
489
490         painter.end()
491         event.accept()

```

## A.17 gui/plots/classes.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides superclasses for plotting transformations."""
8
9  from __future__ import annotations
10
11  from abc import abstractmethod
12  from math import ceil, dist, floor
13  from typing import Iterable, List, Optional, Tuple
14
15  import numpy as np
16  from PyQt5.QtCore import QPoint, QPointF, QRectF, Qt
17  from PyQt5.QtGui import (QBrush, QColor, QFont, QMouseEvent, QPainter,
18                           QPainterPath, QPaintEvent, QPen, QPolygonF,
19                           QWheelEvent)
20  from PyQt5.QtWidgets import QWidget
21
22  from lintrans.typing_ import MatrixType, VectorType
23
24
25  class BackgroundPlot(QWidget):
26      """This class provides a background for plotting, as well as setup for a Qt widget.
27
28      This class provides a background (untransformed) plane, and all the backend details
29      for a Qt application, but does not provide useful functionality. To be useful,
30      this class must be subclassed and behaviour must be implemented by the subclass.
31      """
32
33      DEFAULT_GRID_SPACING: int = 85
34      """This is the starting spacing between grid lines (in pixels)."""
35
36      _MINIMUM_GRID_SPACING: int = 5
37      """This is the minimum spacing between grid lines (in pixels)."""
38
39      _COLOUR_BACKGROUND_GRID: QColor = QColor('#808080')
40      """This is the colour of the background grid lines."""
41
42      _COLOUR_BACKGROUND_AXES: QColor = QColor('#000000')
43      """This is the colour of the background axes."""
44
45      _WIDTH_BACKGROUND_GRID: float = 0.3
46      """This is the width of the background grid lines, as a multiple of the :class:`QPainter` line width."""
47
48      _PEN_POLYGON: QPen = QPen(QColor('#000000'), 1.5)
49      """This is the pen used to draw the normal polygon."""
50
51      _BRUSH_SOLID_WHITE: QBrush = QBrush(QColor('FFFFFF'), Qt.SolidPattern)
52      """This brush is just solid white. Used to draw the insides of circles."""
53
54      def __init__(self, *args, **kwargs):
55          """Create the widget and setup backend stuff for rendering.
56
57          .. note:: ``*args`` and ``**kwargs`` are passed the superclass constructor (:class:`QWidget`).
58          """
59          super().__init__(*args, **kwargs)
60
61          self.setAutoFillBackground(True)

```

```

62
63     # Set the background to white
64     palette = self.palette()
65     palette.setColor(self.backgroundRole(), Qt.white)
66     self.setPalette(palette)
67
68     self.grid_spacing = self.DEFAULT_GRID_SPACING
69
70 @property
71 def _canvas_origin(self) -> Tuple[int, int]:
72     """Return the canvas coords of the grid origin.
73
74     The return value is intended to be unpacked and passed to a :meth:`QPainter.drawLine:iiii` call.
75
76     See :meth:`canvas_coords`.
77
78     :returns: The canvas coordinates of the grid origin
79     :rtype: Tuple[int, int]
80     """
81     return self.width() // 2, self.height() // 2
82
83 def _canvas_x(self, x: float) -> int:
84     """Convert an x coordinate from grid coords to canvas coords."""
85     return int(self._canvas_origin[0] + x * self.grid_spacing)
86
87 def _canvas_y(self, y: float) -> int:
88     """Convert a y coordinate from grid coords to canvas coords."""
89     return int(self._canvas_origin[1] - y * self.grid_spacing)
90
91 def canvas_coords(self, x: float, y: float) -> Tuple[int, int]:
92     """Convert a coordinate from grid coords to canvas coords.
93
94     This method is intended to be used like
95
96     .. code::
97
98         painter.drawLine(*self.canvas_coords(x1, y1), *self.canvas_coords(x2, y2))
99
100     or like
101
102     .. code::
103
104         painter.drawLine(*self._canvas_origin, *self.canvas_coords(x, y))
105
106     See :attr:`_canvas_origin`.
107
108     :param float x: The x component of the grid coordinate
109     :param float y: The y component of the grid coordinate
110     :returns: The resultant canvas coordinates
111     :rtype: Tuple[int, int]
112     """
113     return self._canvas_x(x), self._canvas_y(y)
114
115 def _grid_corner(self) -> Tuple[float, float]:
116     """Return the grid coords of the top right corner."""
117     return self.width() / (2 * self.grid_spacing), self.height() / (2 * self.grid_spacing)
118
119 def _grid_coords(self, x: int, y: int) -> Tuple[float, float]:
120     """Convert a coordinate from canvas coords to grid coords.
121
122     :param int x: The x component of the canvas coordinate
123     :param int y: The y component of the canvas coordinate
124     :returns: The resultant grid coordinates
125     :rtype: Tuple[float, float]
126     """
127     # We get the maximum grid coords and convert them into canvas coords
128     return (x - self._canvas_origin[0]) / self.grid_spacing, (-y + self._canvas_origin[1]) / self.grid_spacing
129
130 @abstractmethod
131 def paintEvent(self, event: QPaintEvent) -> None:
132     """Handle a :class:`QPaintEvent`.
133
134     .. note:: This method is abstract and must be overridden by all subclasses.

```

```

135     """
136
137     def _draw_background(self, painter: QPainter, draw_grid: bool) -> None:
138         """Draw the background grid.
139
140         .. note:: This method is just a utility method for subclasses to use to render the background grid.
141
142         :param QPainter painter: The painter to draw the background with
143         :param bool draw_grid: Whether to draw the grid lines
144         """
145         if draw_grid:
146             painter.setPen(QPen(self._COLOUR_BACKGROUND_GRID, self._WIDTH_BACKGROUND_GRID))
147
148             # Draw equally spaced vertical lines, starting in the middle and going out
149             # We loop up to half of the width. This is because we draw a line on each side in each iteration
150             for x in range(self.width() // 2 + self.grid_spacing, self.width(), self.grid_spacing):
151                 painter.drawLine(x, 0, x, self.height())
152                 painter.drawLine(self.width() - x, 0, self.width() - x, self.height())
153
154             # Same with the horizontal lines
155             for y in range(self.height() // 2 + self.grid_spacing, self.height(), self.grid_spacing):
156                 painter.drawLine(0, y, self.width(), y)
157                 painter.drawLine(0, self.height() - y, self.width(), self.height() - y)
158
159             # Now draw the axes
160             painter.setPen(QPen(self._COLOUR_BACKGROUND_AXES, self._WIDTH_BACKGROUND_GRID))
161             painter.drawLine(self.width() // 2, 0, self.width() // 2, self.height())
162             painter.drawLine(0, self.height() // 2, self.width(), self.height() // 2)
163
164     def wheelEvent(self, event: QWheelEvent) -> None:
165         """Handle a :class:`QWheelEvent` by zooming in or out of the grid."""
166         # angleDelta() returns a number of units equal to 8 times the number of degrees rotated
167         degrees = event.angleDelta() / 8
168
169         if degrees is not None:
170             new_spacing = max(1, self.grid_spacing + degrees.y())
171
172             if new_spacing >= self._MINIMUM_GRID_SPACING:
173                 self.grid_spacing = new_spacing
174
175             event.accept()
176             self.update()
177
178
179     class InteractivePlot(BackgroundPlot):
180         """This class represents an interactive plot, which allows the user to click and/or drag point(s).
181
182         It declares the Qt methods needed for mouse cursor interaction to be abstract,
183         requiring all subclasses to implement these.
184         """
185
186         _CURSOR_EPSILON: int = 5
187         """This is the distance (in pixels) that the cursor needs to be from the point to drag it."""
188
189         _SNAP_DIST = 0.1
190         """This is the distance (in grid coords) that the cursor needs to be from an integer point to snap to it."""
191
192         def _round_to_int_coord(self, point: Tuple[float, float]) -> Tuple[float, float]:
193             """Take a coordinate in grid coords and round it to an integer coordinate if it's within :attr:`_SNAP_DIST`.
194
195             If the point is not close enough, we just return the original point.
196             """
197             x, y = point
198
199             possible_snaps: List[Tuple[int, int]] = [
200                 (floor(x), floor(y)),
201                 (floor(x), ceil(y)),
202                 (ceil(x), floor(y)),
203                 (ceil(x), ceil(y))
204             ]
205
206             snap_distances: List[Tuple[float, Tuple[int, int]]] = [
207                 (dist((x, y), coord), coord)

```

```

208         for coord in possible_snaps
209     ]
210
211     for snap_dist, coord in snap_distances:
212         if snap_dist < self._SNAP_DIST:
213             x, y = coord
214
215     return x, y
216
217 def _is_within_epsilon(self, cursor_pos: Tuple[float, float], point: Tuple[float, float]) -> bool:
218     """Check if the cursor position (in canvas coords) is within range of the given point."""
219     mx, my = cursor_pos
220     px, py = self.canvas_coords(*point)
221     return (abs(px - mx) <= self._CURSOR_EPSILON and abs(py - my) <= self._CURSOR_EPSILON)
222
223 @abstractmethod
224 def mousePressEvent(self, event: QMouseEvent) -> None:
225     """Handle the mouse being pressed."""
226
227 @abstractmethod
228 def mouseReleaseEvent(self, event: QMouseEvent) -> None:
229     """Handle the mouse being released."""
230
231 @abstractmethod
232 def mouseMoveEvent(self, event: QMouseEvent) -> None:
233     """Handle the mouse moving on the widget."""
234
235
236 class VectorGridPlot(BackgroundPlot):
237     """This class represents a background plot, with vectors and their grid drawn on top. It provides utility
238     ↪ methods.
239
240     .. note::
241         This is a simple superclass for vectors and is not for visualizing transformations.
242         See :class:`VisualizeTransformationPlot`.
243
244     This class should be subclassed to be used for visualization and matrix definition widgets.
245     All useful behaviour should be implemented by any subclass.
246
247     .. warning:: This class should never be directly instantiated, only subclassed.
248     """
249     _COLOUR_I = QColor('#0808d8')
250     """This is the colour of the `i` basis vector and associated transformed grid lines."""
251
252     _COLOUR_J = QColor('#e90000')
253     """This is the colour of the `j` basis vector and associated transformed grid lines."""
254
255     _COLOUR_TEXT = QColor('#000000')
256     """This is the colour of the text."""
257
258     _WIDTH_VECTOR_LINE = 1.8
259     """This is the width of the transformed basis vector lines, as a multiple of the :class:`QPainter` line
260     ↪ width."""
261
262     _WIDTH_TRANSFORMED_GRID = 0.8
263     """This is the width of the transformed grid lines, as a multiple of the :class:`QPainter` line width."""
264
265     _ARROWHEAD_LENGTH = 0.15
266     """This is the minimum length (in grid coord size) of the arrowhead parts."""
267
268     _MAX_PARALLEL_LINES = 150
269     """This is the maximum number of parallel transformed grid lines that will be drawn.
270
271     The user can zoom out further, but we will stop drawing grid lines beyond this number.
272     """
273
274     def __init__(self, *args, **kwargs):
275         """Create the widget with ``point_i`` and ``point_j`` attributes.
276
277         .. note:: ``*args`` and ``**kwargs`` are passed to the superclass constructor (:class:`BackgroundPlot`).
278         """
279         super().__init__(*args, **kwargs)

```



```

279
280     self.point_i: Tuple[float, float] = (1., 0.)
281     self.point_j: Tuple[float, float] = (0., 1.)
282
283 @property
284 def _matrix(self) -> MatrixType:
285     """Return the assembled matrix of the basis vectors."""
286     return np.array([
287         [self.point_i[0], self.point_j[0]],
288         [self.point_i[1], self.point_j[1]]
289     ])
290
291 @property
292 def _det(self) -> float:
293     """Return the determinant of the assembled matrix."""
294     return float(np.linalg.det(self._matrix))
295
296 @property
297 def _eigs(self) -> 'Iterable[Tuple[float, VectorType]]':
298     """Return the eigenvalues and eigenvectors zipped together to be iterated over.
299
300     :rtype: Iterable[Tuple[float, VectorType]]
301     """
302     values, vectors = np.linalg.eig(self._matrix)
303     return zip(values, vectors.T)
304
305 @abstractmethod
306 def paintEvent(self, event: QPaintEvent) -> None:
307     """Handle a :class:`QPaintEvent`.
308
309 def _draw_parallel_lines(self, painter: QPainter, vector: Tuple[float, float], point: Tuple[float, float]) ->
↪ None:
310     """Draw a set of evenly spaced grid lines parallel to ``vector`` intersecting ``point``.
311
312     :param QPainter painter: The painter to draw the lines with
313     :param vector: The vector to draw the grid lines parallel to
314     :type vector: Tuple[float, float]
315     :param point: The point for the lines to intersect with
316     :type point: Tuple[float, float]
317     """
318     max_x, max_y = self._grid_corner()
319     vector_x, vector_y = vector
320     point_x, point_y = point
321
322     # If the determinant is 0
323     if abs(vector_x * point_y - vector_y * point_x) < 1e-12:
324         rank = np.linalg.matrix_rank(
325             np.array([
326                 [vector_x, point_x],
327                 [vector_y, point_y]
328             ])
329         )
330
331         # If the matrix is rank 1, then we can draw the column space line
332         if rank == 1:
333             # If the vector does not have a 0 x or y component, then we can just draw the line
334             if abs(vector_x) > 1e-12 and abs(vector_y) > 1e-12:
335                 self._draw_oblique_line(painter, vector_y / vector_x, 0)
336
337             # Otherwise, we have to draw lines along the axes
338             elif abs(vector_x) > 1e-12 and abs(vector_y) < 1e-12:
339                 painter.drawLine(0, self.height() // 2, self.width(), self.height() // 2)
340
341             elif abs(vector_x) < 1e-12 and abs(vector_y) > 1e-12:
342                 painter.drawLine(self.width() // 2, 0, self.width() // 2, self.height())
343
344             # If the vector is (0, 0), then don't draw a line for it
345             else:
346                 return
347
348         # If the rank is 0, then we don't draw any lines
349         else:
350             return

```

```

351
352     elif abs(vector_x) < 1e-12 and abs(vector_y) < 1e-12:
353         # If both components of the vector are practically 0, then we can't render any grid lines
354         return
355
356     # Draw vertical lines
357     elif abs(vector_x) < 1e-12:
358         painter.drawLine(self._canvas_x(0), 0, self._canvas_x(0), self.height())
359
360         for i in range(min(abs(int(max_x / point_x)), self._MAX_PARALLEL_LINES)):
361             painter.drawLine(
362                 self._canvas_x((i + 1) * point_x),
363                 0,
364                 self._canvas_x((i + 1) * point_x),
365                 self.height()
366             )
367             painter.drawLine(
368                 self._canvas_x(-1 * (i + 1) * point_x),
369                 0,
370                 self._canvas_x(-1 * (i + 1) * point_x),
371                 self.height()
372             )
373
374     # Draw horizontal lines
375     elif abs(vector_y) < 1e-12:
376         painter.drawLine(0, self._canvas_y(0), self.width(), self._canvas_y(0))
377
378         for i in range(min(abs(int(max_y / point_y)), self._MAX_PARALLEL_LINES)):
379             painter.drawLine(
380                 0,
381                 self._canvas_y((i + 1) * point_y),
382                 self.width(),
383                 self._canvas_y((i + 1) * point_y)
384             )
385             painter.drawLine(
386                 0,
387                 self._canvas_y(-1 * (i + 1) * point_y),
388                 self.width(),
389                 self._canvas_y(-1 * (i + 1) * point_y)
390             )
391
392     # If the line is oblique, then we can use  $y = mx + c$ 
393     else:
394         m = vector_y / vector_x
395         c = point_y - m * point_x
396
397         self._draw_oblique_line(painter, m, 0)
398
399         # We don't want to overshoot the max number of parallel lines,
400         # but we should also stop looping as soon as we can't draw any more lines
401         for i in range(1, self._MAX_PARALLEL_LINES + 1):
402             if not self._draw_pair_of_oblique_lines(painter, m, i * c):
403                 break
404
405     def _draw_pair_of_oblique_lines(self, painter: QPainter, m: float, c: float) -> bool:
406         """Draw a pair of oblique lines, using the equation  $y = mx + c$ .
407
408         This method just calls :meth:`_draw_oblique_line` with ``c`` and ``-c``,
409         and returns True if either call returned True.
410
411         :param QPainter painter: The painter to draw the vectors and grid lines with
412         :param float m: The gradient of the lines to draw
413         :param float c: The y-intercept of the lines to draw. We use the positive and negative versions
414         :returns bool: Whether we were able to draw any lines on the canvas
415         """
416         return any([
417             self._draw_oblique_line(painter, m, c),
418             self._draw_oblique_line(painter, m, -c)
419         ])
420
421     def _draw_oblique_line(self, painter: QPainter, m: float, c: float) -> bool:
422         """Draw an oblique line, using the equation  $y = mx + c$ .
423

```

```

424 We only draw the part of the line that fits within the canvas, returning True if
425 we were able to draw a line within the boundaries, and False if we couldn't draw a line
426
427 :param QPainter painter: The painter to draw the vectors and grid lines with
428 :param float m: The gradient of the line to draw
429 :param float c: The y-intercept of the line to draw
430 :returns bool: Whether we were able to draw a line on the canvas
431 """
432 max_x, max_y = self._grid_corner()
433
434 # These variable names are shortened for convenience
435 # myi is max_y_intersection, mmyi is minus_max_y_intersection, etc.
436 myi = (max_y - c) / m
437 mmyi = (-max_y - c) / m
438 mxi = max_x * m + c
439 mmxi = -max_x * m + c
440
441 # The inner list here is a list of coords, or None
442 # If an intersection fits within the bounds, then we keep its coord,
443 # else it is None, and then gets discarded from the points list
444 # By the end, points is a list of two coords, or an empty list
445 points: List[Tuple[float, float]] = [
446     x for x in [
447         (myi, max_y) if -max_x < myi < max_x else None,
448         (mmyi, -max_y) if -max_x < mmyi < max_x else None,
449         (max_x, mxi) if -max_y < mxi < max_y else None,
450         (-max_x, mmxi) if -max_y < mmxi < max_y else None
451     ] if x is not None
452 ]
453
454 # If no intersections fit on the canvas
455 if len(points) < 2:
456     return False
457
458 # If we can, then draw the line
459 else:
460     painter.drawLine(
461         *self.canvas_coords(*points[0]),
462         *self.canvas_coords(*points[1])
463     )
464     return True
465
466 def _draw_transformed_grid(self, painter: QPainter) -> None:
467     """Draw the transformed version of the grid, given by the basis vectors.
468
469     .. note:: This method draws the grid, but not the basis vectors. Use :meth:`_draw_basis_vectors` to draw
470     ↪ them.
471
472     :param QPainter painter: The painter to draw the grid lines with
473     """
474     # Draw all the parallel lines
475     painter.setPen(QPen(self._COLOUR_I, self.WIDTH_TRANSFORMED_GRID))
476     self._draw_parallel_lines(painter, self.point_i, self.point_j)
477     painter.setPen(QPen(self._COLOUR_J, self.WIDTH_TRANSFORMED_GRID))
478     self._draw_parallel_lines(painter, self.point_j, self.point_i)
479
480 def _draw_arrowhead_away_from_origin(self, painter: QPainter, point: Tuple[float, float]) -> None:
481     """Draw an arrowhead at ``point``, pointing away from the origin.
482
483     :param QPainter painter: The painter to draw the arrowhead with
484     :param point: The point to draw the arrowhead at, given in grid coords
485     :type point: Tuple[float, float]
486     """
487     # This algorithm was adapted from a C# algorithm found at
488     # http://csharpshelper.com/blog/2014/12/draw-lines-with-arrowheads-in-c/
489
490     # Get the x and y coords of the point, and then normalize them
491     # We have to normalize them, or else the size of the arrowhead will
492     # scale with the distance of the point from the origin
493     x, y = point
494     vector_length = np.sqrt(x * x + y * y)
495
496     if vector_length < 1e-12:

```

```

496         return
497
498     nx = x / vector_length
499     ny = y / vector_length
500
501     # We choose a length and find the steps in the x and y directions
502     length = min(
503         self._ARROWHEAD_LENGTH * self.DEFAULT_GRID_SPACING / self.grid_spacing,
504         vector_length
505     )
506     dx = length * (-nx - ny)
507     dy = length * (nx - ny)
508
509     # Then we just plot those lines
510     painter.drawLine(*self.canvas_coords(x, y), *self.canvas_coords(x + dx, y + dy))
511     painter.drawLine(*self.canvas_coords(x, y), *self.canvas_coords(x - dy, y + dx))
512
513 def _draw_position_vector(self, painter: QPainter, point: Tuple[float, float], colour: QColor) -> None:
514     """Draw a vector from the origin to the given point.
515
516     :param QPainter painter: The painter to draw the position vector with
517     :param point: The tip of the position vector in grid coords
518     :type point: Tuple[float, float]
519     :param QColor colour: The colour to draw the position vector in
520     """
521     painter.setPen(QPen(colour, self._WIDTH_VECTOR_LINE))
522     painter.drawLine(*self._canvas_origin, *self.canvas_coords(*point))
523     self._draw_arrowhead_away_from_origin(painter, point)
524
525 def _draw_basis_vectors(self, painter: QPainter) -> None:
526     """Draw arrowheads at the tips of the basis vectors.
527
528     :param QPainter painter: The painter to draw the basis vectors with
529     """
530     self._draw_position_vector(painter, self.point_i, self._COLOUR_I)
531     self._draw_position_vector(painter, self.point_j, self._COLOUR_J)
532
533 def _draw_basis_vector_labels(self, painter: QPainter) -> None:
534     """Label the basis vectors with 'i' and 'j'."""
535     font = self.font()
536     font.setItalic(True)
537     font.setStyleHint(QFont.Serif)
538
539     self._draw_text_at_vector_tip(painter, self.point_i, 'i', font)
540     self._draw_text_at_vector_tip(painter, self.point_j, 'j', font)
541
542 def _draw_text_at_vector_tip(
543     self,
544     painter: QPainter,
545     point: Tuple[float, float],
546     text: str,
547     font: Optional[QFont] = None
548 ) -> None:
549     """Draw the given text at the point as if it were the tip of a vector, using the custom font if given."""
550     offset = 3
551     top_left: QPoint
552     bottom_right: QPoint
553     alignment_flags: int
554     x, y = point
555
556     if x >= 0 and y >= 0: # Q1
557         top_left = QPoint(self._canvas_x(x) + offset, 0)
558         bottom_right = QPoint(self.width(), self._canvas_y(y) - offset)
559         alignment_flags = Qt.AlignLeft | Qt.AlignBottom
560
561     elif x < 0 and y >= 0: # Q2
562         top_left = QPoint(0, 0)
563         bottom_right = QPoint(self._canvas_x(x) - offset, self._canvas_y(y) - offset)
564         alignment_flags = Qt.AlignRight | Qt.AlignBottom
565
566     elif x < 0 and y < 0: # Q3
567         top_left = QPoint(0, self._canvas_y(y) + offset)
568         bottom_right = QPoint(self._canvas_x(x) - offset, self.height())

```

```

569         alignment_flags = Qt.AlignRight | Qt.AlignTop
570
571     else: # Q4
572         top_left = QPoint(self._canvas_x(x) + offset, self._canvas_y(y) + offset)
573         bottom_right = QPoint(self.width(), self.height())
574         alignment_flags = Qt.AlignLeft | Qt.AlignTop
575
576     original_font = painter.font()
577
578     if font is not None:
579         painter.setFont(font)
580
581     painter.setPen(QPen(self._COLOUR_TEXT, 1))
582     painter.drawText(QRectF(top_left, bottom_right), alignment_flags, text)
583
584     painter.setFont(original_font)
585
586
587 class VisualizeTransformationPlot(VectorGridPlot):
588     """This class is a superclass for visualizing transformations. It provides utility methods."""
589
590     _COLOUR_EIGEN = QColor('#13cf00')
591     """This is the colour of the eigenvectors and eigenlines (the spans of the eigenvectors)."""
592
593     @abstractmethod
594     def paintEvent(self, event: QPaintEvent) -> None:
595         """Handle a :class:`QPaintEvent`."""
596
597     def _draw_determinant_parallelogram(self, painter: QPainter) -> None:
598         """Draw the parallelogram of the determinant of the matrix.
599
600         :param QPainter painter: The painter to draw the parallelogram with
601         """
602         if self._det == 0:
603             return
604
605         path = QPainterPath()
606         path.moveTo(*self._canvas_origin)
607         path.lineTo(*self._canvas_coords(*self.point_i))
608         path.lineTo(*self._canvas_coords(self.point_i[0] + self.point_j[0], self.point_i[1] + self.point_j[1]))
609         path.lineTo(*self._canvas_coords(*self.point_j))
610
611         color = (16, 235, 253) if self._det > 0 else (253, 34, 16)
612         brush = QBrush(QColor(*color, alpha=128), Qt.SolidPattern)
613
614         painter.fillPath(path, brush)
615
616     def _draw_determinant_text(self, painter: QPainter) -> None:
617         """Write the string value of the determinant in the middle of the parallelogram.
618
619         :param QPainter painter: The painter to draw the determinant text with
620         """
621         painter.setPen(QPen(self._COLOUR_TEXT, self._WIDTH_VECTOR_LINE))
622
623         # We're building a QRect that encloses the determinant parallelogram
624         # Then we can center the text in this QRect
625         coords: List[Tuple[float, float]] = [
626             (0, 0),
627             self.point_i,
628             self.point_j,
629             (
630                 self.point_i[0] + self.point_j[0],
631                 self.point_i[1] + self.point_j[1]
632             )
633         ]
634
635         xs = [t[0] for t in coords]
636         ys = [t[1] for t in coords]
637
638         top_left = QPoint(*self._canvas_coords(min(xs), max(ys)))
639         bottom_right = QPoint(*self._canvas_coords(max(xs), min(ys)))
640
641         rect = QRectF(top_left, bottom_right)

```

```

642         painter.drawText(
643             rect,
644             Qt.AlignHCenter | Qt.AlignVCenter,
645             f'{self._det:.2f}'
646         )
647
648
649     def _draw_eigenvectors(self, painter: QPainter) -> None:
650         """Draw the eigenvectors of the displayed matrix transformation.
651
652         :param QPainter painter: The painter to draw the eigenvectors with
653         """
654         for value, vector in self._eigs:
655             x = value * vector[0]
656             y = value * vector[1]
657
658             if x.imag != 0 or y.imag != 0:
659                 continue
660
661             self._draw_position_vector(painter, (x, y), self._COLOUR_EIGEN)
662             self._draw_text_at_vector_tip(painter, (x, y), f'{value:.2f}')
663
664     def _draw_eigenlines(self, painter: QPainter) -> None:
665         """Draw the eigenlines. These are the invariant lines, or the spans of the eigenvectors.
666
667         :param QPainter painter: The painter to draw the eigenlines with
668         """
669         painter.setPen(QPen(self._COLOUR_EIGEN, self._WIDTH_TRANSFORMED_GRID))
670
671         for value, vector in self._eigs:
672             if value.imag != 0:
673                 continue
674
675             x, y = vector
676
677             if x == 0:
678                 x_mid = int(self.width() / 2)
679                 painter.drawLine(x_mid, 0, x_mid, self.height())
680
681             elif y == 0:
682                 y_mid = int(self.height() / 2)
683                 painter.drawLine(0, y_mid, self.width(), y_mid)
684
685             else:
686                 self._draw_oblique_line(painter, y / x, 0)
687
688     def _draw_polygon_from_points(self, painter: QPainter, points: List[Tuple[float, float]]) -> None:
689         """Draw a polygon from a given list of points.
690
691         This is a helper method for :meth:`_draw_untransformed_polygon` and :meth:`_draw_transformed_polygon`.
692         """
693         if len(points) > 2:
694             painter.drawPolygon(QPolygonF(
695                 [QPointF(*self.canvas_coords(*p)) for p in points]
696             ))
697         elif len(points) == 2:
698             painter.drawLine(
699                 *self.canvas_coords(*points[0]),
700                 *self.canvas_coords(*points[1])
701             )
702
703     def _draw_untransformed_polygon(self, painter: QPainter) -> None:
704         """Draw the original untransformed polygon with a dashed line."""
705         pen = QPen(self._PEN_POLYGON)
706         pen.setDashPattern([4, 4])
707         painter.setPen(pen)
708
709         self._draw_polygon_from_points(painter, self.polygon_points)
710
711     def _draw_transformed_polygon(self, painter: QPainter) -> None:
712         """Draw the transformed version of the polygon."""
713         if len(self.polygon_points) == 0:
714             return

```

```

715
716         painter.setPen(self._PEN_POLYGON)
717
718         # This transpose trick lets us do one matrix multiplication to transform every point in the polygon
719         # I learned this from Phil. Thanks Phil
720         self._draw_polygon_from_points(
721             painter,
722             (self._matrix @ np.array(self.polygon_points).T).T
723         )

```

## A.18 gui/plots/\_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package provides widgets for the visualization plot in the main window and the visual definition dialog."""
8
9  from .classes import (BackgroundPlot, VectorGridPlot,
10                       VisualizeTransformationPlot)
11  from .widgets import (DefineMatrixVisuallyWidget, DefinePolygonWidget,
12                       MainViewportWidget, VisualizeTransformationWidget)
13
14  __all__ = ['BackgroundPlot', 'DefinePolygonWidget', 'DefineMatrixVisuallyWidget', 'MainViewportWidget',
15            'VectorGridPlot', 'VisualizeTransformationPlot', 'VisualizeTransformationWidget']

```

## A.19 typing/\_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package supplies type aliases for linear algebra and transformations.
8
9  .. note::
10     This package is called ``typing_`` and not ``typing`` to avoid name collisions with the
11     builtin :mod:`typing`. I don't quite know how this collision occurs, but renaming
12     this module fixed the problem.
13     """
14
15  from __future__ import annotations
16
17  from sys import version_info
18  from typing import Any, List, Tuple
19
20  from nptyping import Float, NDArray
21  from numpy import ndarray
22
23  if version_info >= (3, 10):
24      from typing import TypeAlias, TypeGuard
25
26  __all__ = ['is_matrix_type', 'MatrixType', 'MatrixParseList', 'VectorType']
27
28  MatrixType: TypeAlias = 'NDArray[(2, 2), Float]'
29  """This type represents a 2x2 matrix as a NumPy array."""
30
31  VectorType: TypeAlias = 'NDArray[(2,), Float]'
32  """This type represents a 2D vector as a NumPy array, for use with :attr:`MatrixType`."""
33
34  MatrixParseList: TypeAlias = List[List[Tuple[str, str, str]]]
35  """This is a list containing lists of tuples. Each tuple represents a matrix and is ``(multiplier,
36  matrix_identifier, index)`` where all of them are strings. These matrix-representing tuples are
37  contained in lists which represent multiplication groups. Every matrix in the group should be
38  multiplied together, in order. These multiplication group lists are contained by a top level list,

```

```

39 which is this type. Once these multiplication group lists have been evaluated, they should be summed.
40
41 In the tuples, the multiplier is a string representing a real number, the matrix identifier
42 is a capital letter or ``rot(x)`` where x is a real number angle, and the index is a string
43 representing an integer, or it's the letter ``T`` for transpose.
44 """
45
46
47 def is_matrix_type(matrix: Any) -> TypeGuard[MatrixType]:
48     """Check if the given value is a valid matrix type.
49
50     .. note::
51         This function is a TypeGuard, meaning if it returns True, then the
52         passed value must be a :attr:`MatrixType`.
53     """
54     return isinstance(matrix, ndarray) and matrix.shape == (2, 2)

```

## A.20 matrices/utility.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """This module provides simple utility methods for matrix and vector manipulation."""
8
9 from __future__ import annotations
10
11 import math
12 from typing import Tuple
13
14 import numpy as np
15
16 from lintrans.typing_ import MatrixType
17
18
19 def polar_coords(x: float, y: float, *, degrees: bool = False) -> Tuple[float, float]:
20     """Return the polar coordinates of a given (x, y) Cartesian coordinate.
21
22     .. note:: We're returning the angle in the range :math:`[0, 2\pi)`
23     """
24     radius = math.hypot(x, y)
25
26     # PyCharm complains about np.angle taking a complex argument even though that's what it's designed for
27     # noinspection PyTypeChecker
28     angle = float(np.angle(x + y * 1j, degrees))
29
30     if angle < 0:
31         angle += 2 * np.pi
32
33     return radius, angle
34
35
36 def rect_coords(radius: float, angle: float, *, degrees: bool = False) -> Tuple[float, float]:
37     """Return the rectilinear coordinates of a given polar coordinate."""
38     if degrees:
39         angle = np.radians(angle)
40
41     return radius * np.cos(angle), radius * np.sin(angle)
42
43
44 def rotate_coord(x: float, y: float, angle: float, *, degrees: bool = False) -> Tuple[float, float]:
45     """Rotate a rectilinear coordinate by the given angle."""
46     if degrees:
47         angle = np.radians(angle)
48
49     r, theta = polar_coords(x, y, degrees=degrees)
50     theta = (theta + angle) % (2 * np.pi)
51

```



```

52     return rect_coords(r, theta, degrees=degrees)
53
54
55 def create_rotation_matrix(angle: float, *, degrees: bool = True) -> MatrixType:
56     """Create a matrix representing a rotation (anticlockwise) by the given angle.
57
58     :Example:
59
60     >>> create_rotation_matrix(30)
61     array([[ 0.8660254, -0.5      ],
62            [ 0.5      ,  0.8660254]])
63     >>> create_rotation_matrix(45)
64     array([[ 0.70710678, -0.70710678],
65            [ 0.70710678,  0.70710678]])
66     >>> create_rotation_matrix(np.pi / 3, degrees=False)
67     array([[ 0.5      , -0.8660254],
68            [ 0.8660254,  0.5      ]])
69
70     :param float angle: The angle to rotate anticlockwise by
71     :param bool degrees: Whether to interpret the angle as degrees (True) or radians (False)
72     :returns MatrixType: The resultant matrix
73     """
74     rad = np.deg2rad(angle % 360) if degrees else angle % (2 * np.pi)
75     return np.array([
76         [np.cos(rad), -1 * np.sin(rad)],
77         [np.sin(rad), np.cos(rad)]
78     ])
79
80
81 def is_valid_float(string: str) -> bool:
82     """Check if the string is a valid float (or anything that can be cast to a float, such as an int).
83
84     This function simply checks that ``float(string)`` doesn't raise an error.
85
86     .. note:: An empty string is not a valid float, so will return False.
87
88     :param str string: The string to check
89     :returns bool: Whether the string is a valid float
90     """
91     try:
92         float(string)
93         return True
94     except ValueError:
95         return False
96
97
98 def round_float(num: float, precision: int = 5) -> str:
99     """Round a floating point number to a given number of decimal places for pretty printing.
100
101     :param float num: The number to round
102     :param int precision: The number of decimal places to round to
103     :returns str: The rounded number for pretty printing
104     """
105     # Round to ``precision`` number of decimal places
106     string = str(round(num, precision))
107
108     # Cut off the potential final zero
109     if string.endswith('.0'):
110         return string[:-2]
111
112     elif 'e' in string: # Scientific notation
113         split = string.split('e')
114         # The leading 0 only happens when the exponent is negative, so we know there'll be a minus sign
115         return split[0] + 'e-' + split[1][1:].rstrip('0')
116
117     else:
118         return string

```

## A.21 matrices/wrapper.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module contains the main :class:`MatrixWrapper` class and a function to create a matrix from an angle."""
8
9  from __future__ import annotations
10
11  import re
12  from copy import copy
13  from functools import reduce
14  from operator import add, matmul
15  from typing import Any, Dict, List, Optional, Set, Tuple, Union
16
17  import numpy as np
18
19  from lintrans.typing_ import MatrixType, is_matrix_type
20
21  from .parse import (get_matrix_identifiers, parse_matrix_expression,
22                      validate_matrix_expression)
23  from .utility import create_rotation_matrix
24
25  _ALPHABET_NO_I = 'ABCDEFGHJKLMNOPQRSTUVWXYZ'
26
27
28  class MatrixWrapper:
29      """A wrapper class to hold all possible matrices and allow access to them.
30
31      .. note::
32          When defining a custom matrix, its name must be a capital letter and cannot be ``I``.
33
34      The contained matrices can be accessed and assigned to using square bracket notation.
35
36      :Example:
37
38      >>> wrapper = MatrixWrapper()
39      >>> wrapper['I']
40      array([[1., 0.],
41             [0., 1.]])
42      >>> wrapper['M'] # Returns None
43      >>> wrapper['M'] = np.array([[1, 2], [3, 4]])
44      >>> wrapper['M']
45      array([[1., 2.],
46             [3., 4.]])
47      """
48
49      def __init__(self):
50          """Initialize a :class:`MatrixWrapper` object with a dictionary of matrices which can be accessed."""
51          self._matrices: Dict[str, Optional[Union[MatrixType, str]]] = {
52              'A': None, 'B': None, 'C': None, 'D': None,
53              'E': None, 'F': None, 'G': None, 'H': None,
54              'I': np.eye(2), # I is always defined as the identity matrix
55              'J': None, 'K': None, 'L': None, 'M': None,
56              'N': None, 'O': None, 'P': None, 'Q': None,
57              'R': None, 'S': None, 'T': None, 'U': None,
58              'V': None, 'W': None, 'X': None, 'Y': None,
59              'Z': None
60          }
61
62      def __repr__(self) -> str:
63          """Return a nice string repr of the :class:`MatrixWrapper` for debugging."""
64          defined_matrices = ''.join([k for k, v in self._matrices.items() if v is not None])
65          return f'<{self.__class__.__module__}.{self.__class__.__name__} object with ' \
66                 f'{len(defined_matrices)} defined matrices: '{defined_matrices}'>'
67
68      def __eq__(self, other: Any) -> bool:
69          """Check for equality in wrappers by comparing dictionaries.
70

```

```

71         :param Any other: The object to compare this wrapper to
72         """
73         if not isinstance(other, self.__class__):
74             return NotImplemented
75
76         # We loop over every matrix and check if every value is equal in each
77         for name in self._matrices:
78             s_matrix = self[name]
79             o_matrix = other[name]
80
81             if s_matrix is None and o_matrix is None:
82                 continue
83
84             elif (s_matrix is None and o_matrix is not None) or \
85                  (s_matrix is not None and o_matrix is None):
86                 return False
87
88             # This is mainly to satisfy mypy, because we know these must be matrices
89             elif not is_matrix_type(s_matrix) or not is_matrix_type(o_matrix):
90                 return False
91
92             # Now we know they're both NumPy arrays
93             elif np.array_equal(s_matrix, o_matrix):
94                 continue
95
96             else:
97                 return False
98
99         return True
100
101     def __hash__(self) -> int:
102         """Return the hash of the matrices dictionary."""
103         return hash(self._matrices)
104
105     def __getitem__(self, name: str) -> Optional[MatrixType]:
106         """Get the matrix with the given identifier.
107
108         If it is a simple name, it will just be fetched from the dictionary. If the identifier is ``rot(x)`, with
109         a given angle in degrees, then we return a new matrix representing a rotation by that angle. If the
110         ↪ identifier
111         is something like ``[1 2;3 4]`, then we will evaluate this matrix (we assume it will have whitespace
112         ↪ exactly
113         like the example; see :func:`lintrans.matrices.parse.strip_whitespace`).
114
115         .. note::
116             If the named matrix is defined as an expression, then this method will return its evaluation.
117             If you want the expression itself, use :meth:`get_expression`.
118
119         :param str name: The name of the matrix to get
120         :returns Optional[MatrixType]: The value of the matrix (could be None)
121
122         :raises NameError: If there is no matrix with the given name
123         """
124         # Return a new rotation matrix
125         if (match := re.match(r'^rot\((-?\d*\.\d*)\)$', name)) is not None:
126             return create_rotation_matrix(float(match.group(1)))
127
128         if (match := re.match(
129             r'\[(-?\d+(?:\.\d+)?)(-?\d+(?:\.\d+)?);(-?\d+(?:\.\d+)?)(-?\d+(?:\.\d+)?)\]',
130             name
131         )) is not None:
132             a = float(match.group(1))
133             b = float(match.group(2))
134             c = float(match.group(3))
135             d = float(match.group(4))
136             return np.array([[a, b], [c, d]])
137
138         if name not in self._matrices:
139             if validate_matrix_expression(name):
140                 return self.evaluate_expression(name)
141
142             raise NameError(f'Unrecognised matrix name "{name}"')

```

```

142         # We copy the matrix before we return it so the user can't accidentally mutate the matrix
143         matrix = copy(self._matrices[name])
144
145         if isinstance(matrix, str):
146             return self.evaluate_expression(matrix)
147
148         return matrix
149
150     def __setitem__(self, name: str, new_matrix: Optional[Union[MatrixType, str]]) -> None:
151         """Set the value of matrix ``name`` with the new_matrix.
152
153         The new matrix may be a simple 2x2 NumPy array, or it could be a string, representing an
154         expression in terms of other, previously defined matrices.
155
156         :param str name: The name of the matrix to set the value of
157         :param Optional[Union[MatrixType, str]] new_matrix: The value of the new matrix (could be None)
158
159         :raises NameError: If the name isn't a legal matrix name
160         :raises TypeError: If the matrix isn't a valid 2x2 NumPy array or expression in terms of other defined
161         ↪ matrices
162         :raises ValueError: If you attempt to define a matrix in terms of itself
163         """
164         if not (name in self._matrices and name != 'I'):
165             raise NameError('Matrix name is illegal')
166
167         if new_matrix is None:
168             self._matrices[name] = None
169             return
170
171         if isinstance(new_matrix, str):
172             if self.is_valid_expression(new_matrix):
173                 if name not in new_matrix and \
174                     name not in self.get_expression_dependencies(new_matrix):
175                     self._matrices[name] = new_matrix
176                     return
177             else:
178                 raise ValueError('Cannot define a matrix recursively')
179
180         if not is_matrix_type(new_matrix):
181             raise TypeError('Matrix must be a 2x2 NumPy array')
182
183         # All matrices must have float entries
184         a = float(new_matrix[0][0])
185         b = float(new_matrix[0][1])
186         c = float(new_matrix[1][0])
187         d = float(new_matrix[1][1])
188
189         self._matrices[name] = np.array([[a, b], [c, d]])
190
191     def get_matrix_dependencies(self, matrix_name: str) -> Set[str]:
192         """Return all the matrices (as identifiers) that the given matrix (indirectly) depends on.
193
194         If A depends on nothing, B directly depends on A, and C directly depends on B,
195         then we say C depends on B `and` A.
196         """
197         expression = self.get_expression(matrix_name)
198         if expression is None:
199             return set()
200
201         s = set()
202         identifiers = get_matrix_identifiers(expression)
203         for identifier in identifiers:
204             s.add(identifier)
205             s.update(self.get_matrix_dependencies(identifier))
206
207         return s
208
209     def get_expression_dependencies(self, expression: str) -> Set[str]:
210         """Return all the matrices that the given expression depends on.
211
212         This method just calls :meth:`get_matrix_dependencies` on each matrix
213         identifier in the expression. See that method for details.

```

```

214         If an expression contains a matrix that has no dependencies, then the
215         expression is 'not' considered to depend on that matrix. But it 'is'
216         considered to depend on any matrix that has its own dependencies.
217         """
218         s = set()
219         for iden in get_matrix_identifiers(expression):
220             s.update(self.get_matrix_dependencies(iden))
221         return s
222
223     def get_expression(self, name: str) -> Optional[str]:
224         """If the named matrix is defined as an expression, return that expression, else return None.
225
226         :param str name: The name of the matrix
227         :returns Optional[str]: The expression that the matrix is defined as, or None
228
229         :raises NameError: If the name is invalid
230         """
231         if name not in self._matrices:
232             raise NameError('Matrix must have a legal name')
233
234         matrix = self._matrices[name]
235         if isinstance(matrix, str):
236             return matrix
237
238         return None
239
240     def is_valid_expression(self, expression: str) -> bool:
241         """Check if the given expression is valid, using the context of the wrapper.
242
243         This method calls :func:`lintrans.matrices.parse.validate_matrix_expression`, but also
244         ensures that all the matrices in the expression are defined in the wrapper.
245
246         :param str expression: The expression to validate
247         :returns bool: Whether the expression is valid in this wrapper
248
249         :raises LinAlgError: If a matrix is defined in terms of the inverse of a singular matrix
250         """
251         # Get rid of the transposes to check all capital letters
252         new_expression = expression.replace('^T', '').replace('^{T}', '')
253
254         # Make sure all the referenced matrices are defined
255         for matrix in [x for x in new_expression if re.match('[A-Z]', x)]:
256             if self[matrix] is None:
257                 return False
258
259             if (expr := self.get_expression(matrix)) is not None:
260                 if not self.is_valid_expression(expr):
261                     return False
262
263         return validate_matrix_expression(expression)
264
265     def evaluate_expression(self, expression: str) -> MatrixType:
266         """Evaluate a given expression and return the matrix evaluation.
267
268         :param str expression: The expression to be parsed
269         :returns MatrixType: The matrix result of the expression
270
271         :raises ValueError: If the expression is invalid
272         """
273         if not self.is_valid_expression(expression):
274             raise ValueError('The expression is invalid')
275
276         parsed_result = parse_matrix_expression(expression)
277         final_groups: List[List[MatrixType]] = []
278
279         for group in parsed_result:
280             f_group: List[MatrixType] = []
281
282             for multiplier, identifier, index in group:
283                 if index == 'T':
284                     m = self[identifier]
285
286                 # This assertion is just so mypy doesn't complain

```

```

287         # We know this won't be None, because we know that this matrix is defined in this wrapper
288         assert m is not None
289         matrix_value = m.T
290
291     else:
292         # Again, this assertion is just for mypy
293         # We know this will be a matrix, but since upgrading from NumPy 1.21 to 1.23
294         # (to fix a bug with GH Actions on Windows), mypy complains about matrix_power()
295         base_matrix = self[identifier]
296         assert is_matrix_type(base_matrix)
297
298         matrix_value = np.linalg.matrix_power(base_matrix, 1 if index == '' else int(index))
299
300     matrix_value *= 1 if multiplier == '' else float(multiplier)
301     f_group.append(matrix_value)
302
303     final_groups.append(f_group)
304
305     return reduce(add, [reduce(matmul, group) for group in final_groups])
306
307 def get_defined_matrices(self) -> List[Tuple[str, Union[MatrixType, str]]]:
308     """Return a list of tuples containing the name and value of all defined matrices in the wrapper.
309
310     :returns: A list of tuples where the first element is the name, and the second element is the value
311     :rtype: List[Tuple[str, Union[MatrixType, str]]]
312     """
313     matrices = []
314
315     for name, value in self._matrices.items():
316         if value is not None:
317             matrices.append((name, value))
318
319     return matrices
320
321 def undefine_matrix(self, name: str) -> Set[str]:
322     """Safely undefine the given matrix by also undefining any matrices that depend on it."""
323     if not (name in self._matrices and name != 'I'):
324         raise NameError('Matrix name is illegal')
325
326     # This maps each matrix to all the matrices that depend on it
327     dependents_map = {
328         x: set(y for y in _ALPHABET_NO_I if x in self.get_matrix_dependencies(y))
329         for x in _ALPHABET_NO_I
330     }
331
332     s: Set[str] = set(name)
333     self[name] = None
334     for x in dependents_map[name]:
335         s.update(self.undefine_matrix(x))
336
337     return s

```

## A.22 matrices/\_\_init\_\_.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This package supplies classes and functions to parse, evaluate, and wrap matrices."""
8
9  from . import parse, utility
10 from .utility import create_rotation_matrix
11 from .wrapper import MatrixWrapper
12
13 __all__ = ['create_rotation_matrix', 'MatrixWrapper', 'parse', 'utility']

```

## A.23 matrices/parse.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """This module provides functions to parse and validate matrix expressions."""
8
9  from __future__ import annotations
10
11  import re
12  from dataclasses import dataclass
13  from typing import List, Pattern, Set, Tuple
14
15  from lintrans.typing_ import MatrixParseList
16
17  _ALPHABET = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ'
18
19  NAIVE_CHARACTER_CLASS = r'[-\sA-Z0-9.rot()\{\}\[\];]'
20  """This is a RegEx character class that just holds all the valid characters for an expression.
21
22  See :func:`validate_matrix_expression` to actually validate matrix expressions.
23  """
24
25
26  class MatrixParseError(Exception):
27      """A simple exception to be raised when an error is found when parsing."""
28
29
30  def compile_naive_expression_pattern() -> Pattern[str]:
31      """Compile the single RegEx pattern that will match a valid matrix expression."""
32      digit_no_zero = '[123456789]'
33      digits = '\\d+'
34      integer_no_zero = digit_no_zero + '(' + digits + ')?'
35      real_number = f'({integer_no_zero}(\\.\\{digits}\\})?|0\\.\\{digits}\\})'
36
37      anonymous_matrix = r'\\[(-?\\d+(?:\\.\\d+)?)(-?\\d+(?:\\.\\d+)?);(-?\\d+(?:\\.\\d+)?)(-?\\d+(?:\\.\\d+)?)\\]'
38
39      index_content = f'(-?{integer_no_zero}|T)'
40      index = f'\\^{{{index_content}}}|\\^{{{index_content}}}'
41      matrix_identifier = f'([A-Z]|rot\\^((-?{real_number}\\^)|{anonymous_matrix})\\^\\^({NAIVE_CHARACTER_CLASS}+))'
42      matrix = '(' + real_number + '?' + matrix_identifier + index + ')?'
43      expression = f'^-{matrix}+((\\^+?-){matrix}+)*$'
44
45      return re.compile(expression)
46
47
48  # This is an expensive pattern to compile, so we compile it when this module is initialized
49  _naive_expression_pattern = compile_naive_expression_pattern()
50
51
52  def find_sub_expressions(expression: str) -> List[str]:
53      """Find all the sub-expressions in the given expression.
54
55      This function only goes one level deep, so may return strings like ``A(BC)D``.
56
57      :raises MatrixParseError: If there are unbalanced parentheses
58      """
59      sub_expressions: List[str] = []
60      string = ''
61      paren_depth = 0
62      pointer = 0
63
64      expression = strip_whitespace(expression)
65
66      while True:
67          char = expression[pointer]
68
69          if char == '(' and expression[pointer - 3:pointer] != 'rot':
70              paren_depth += 1

```

```

71
72     # This is a bit of a manual bodge, but it eliminates extraneous parens
73     if paren_depth == 1:
74         pointer += 1
75         continue
76
77     elif char == ')' and re.match(f'{NAIVE_CHARACTER_CLASS}*?rot\\([-\\d.]+$', expression[:pointer]) is None:
78         paren_depth -= 1
79
80     if paren_depth > 0:
81         string += char
82
83     if paren_depth == 0 and string:
84         sub_expressions.append(string)
85         string = ''
86
87     pointer += 1
88
89     if pointer >= len(expression):
90         break
91
92 if paren_depth != 0:
93     raise MatrixParseError('Unbalanced parentheses in expression')
94
95 return sub_expressions
96
97
98 def strip_whitespace(expression: str) -> str:
99     """Strip the whitespace from the given expression, preserving whitespace in anonymous matrices.
100
101     Whitespace in anonymous matrices is preserved such that there is exactly one space in the middle of each pair of
102     numbers, but no space after the semi-colon, like so: `[1 -2;3.4 5]`.
103     """
104     # We replace the necessary whitespace with null bytes to preserve it
105     expression = re.sub(
106         r'\\s*(-?\\d+(?:\\.\\d+)?)\\s+(-?\\d+(?:\\.\\d+)?)\\s*;\\s*(-?\\d+(?:\\.\\d+)?)\\s+(-?\\d+(?:\\.\\d+)?)\\s*\\]',
107         r'[\\g<1> \\g<2>;\\g<3> \\g<4>]'.replace(' ', '\\x00'),
108         expression
109     )
110
111     expression = re.sub(r'\\s', ' ', expression)
112     return re.sub('\\x00', ' ', expression)
113
114
115 def validate_matrix_expression(expression: str) -> bool:
116     """Validate the given matrix expression.
117
118     This function simply checks the expression against the BNF schema documented in
119     :ref:`expression-syntax-docs`. It is not aware of which matrices are actually defined
120     in a wrapper. For an aware version of this function, use the
121     :meth:`~lintrans.matrices.wrapper.MatrixWrapper.is_valid_expression` method on
122     :class:`~lintrans.matrices.wrapper.MatrixWrapper`.
123
124     :param str expression: The expression to be validated
125     :returns bool: Whether the expression is valid according to the schema
126     """
127     # Remove all whitespace
128     expression = strip_whitespace(expression)
129     match = _naive_expression_pattern.match(expression)
130
131     if match is None:
132         return False
133
134     if re.search(r'\\^~?\\d*\\.\\d+', expression) is not None:
135         return False
136
137     # Check that the whole expression was matched against
138     if expression != match.group(0):
139         return False
140
141     try:
142         sub_expressions = find_sub_expressions(expression)
143     except MatrixParseError:

```



```

144         return False
145
146     if len(sub_expressions) == 0:
147         return True
148
149     return all(validate_matrix_expression(m) for m in sub_expressions)
150
151
152 @dataclass
153 class MatrixToken:
154     """A simple dataclass to hold information about a matrix token being parsed."""
155
156     multiplier: str = ''
157     identifier: str = ''
158     exponent: str = ''
159
160     @property
161     def tuple(self) -> Tuple[str, str, str]:
162         """Create a tuple of the token for parsing."""
163         return self.multiplier, self.identifier, self.exponent
164
165
166 class ExpressionParser:
167     """A class to hold state during parsing.
168
169     Most of the methods in this class are class-internal and should not be used from outside.
170
171     This class should be used like this:
172
173     >>> ExpressionParser('3A~-1B').parse()
174     [[('3', 'A', '-1'), ('', 'B', '')]]
175     >>> ExpressionParser('4(M^TA^2)^~2').parse()
176     [[('4', 'M^{T}A^{2}', '-2')]]
177     """
178
179     def __init__(self, expression: str):
180         """Create an instance of the parser with the given expression and initialise variables to use during
181         ↪ parsing."""
182         # Remove all whitespace
183         expression = strip_whitespace(expression)
184
185         # Check if it's valid
186         if not validate_matrix_expression(expression):
187             raise MatrixParseError('Invalid expression')
188
189         # Wrap all exponents and transposition powers with {}
190         expression = re.sub(r'(?<=^)(-?\d+|T)(?=[^}]|$)', r'{\g<0>}', expression)
191
192         # Remove any standalone minuses
193         expression = re.sub(r'-(?=[A-Z])', '-1', expression)
194
195         # Replace subtractions with additions
196         expression = re.sub(r'-(?=\d+\.?\d*([A-Z]|rot))', '+-', expression)
197
198         # Get rid of a potential leading + introduced by the last step
199         expression = re.sub(r'^\+', '', expression)
200
201         self._expression = expression
202         self._pointer: int = 0
203
204         self._current_token = MatrixToken()
205         self._current_group: List[Tuple[str, str, str]] = []
206
207         self._final_list: MatrixParseList = []
208
209     def __repr__(self) -> str:
210         """Return a simple repr containing the expression."""
211         return f'{self.__class__.__module__}.{self.__class__.__name__}("{self._expression}")'
212
213     @property
214     def _char(self) -> str:
215         """Return the character pointed to by the pointer."""
216         return self._expression[self._pointer]

```

```

216
217 def parse(self) -> MatrixParseList:
218     """Fully parse the instance's matrix expression and return the :attr:`~lintrans.typing_.MatrixParseList`.
219
220     This method uses all the private methods of this class to parse the
221 expression in parts. All private methods mutate the instance variables.
222
223     :returns: The parsed expression
224     :rtype: :attr:`~lintrans.typing_.MatrixParseList`
225     """
226     self._parse_multiplication_group()
227
228     while self._pointer < len(self._expression):
229         if self._expression[self._pointer] != '+':
230             raise MatrixParseError('Expected "+" between multiplication groups')
231
232         self._pointer += 1
233         self._parse_multiplication_group()
234
235     return self._final_list
236
237 def _parse_multiplication_group(self) -> None:
238     """Parse a group of matrices to be multiplied together.
239
240     This method just parses matrices until we get to a ``+``.
241     """
242     # This loop continues to parse matrices until we fail to do so
243     while self._parse_matrix():
244         # Once we get to the end of the multiplication group, we add it the final list and reset the group list
245         if self._pointer >= len(self._expression) or self._char == '+':
246             self._final_list.append(self._current_group)
247             self._current_group = []
248             self._pointer += 1
249
250 def _parse_matrix(self) -> bool:
251     """Parse a full matrix using :meth:`_parse_matrix_part`.
252
253     This method will parse an optional multiplier, an identifier, and an optional exponent. If we
254 do this successfully, we return True. If we fail to parse a matrix (maybe we've reached the
255 end of the current multiplication group and the next char is ``+``), then we return False.
256
257     :returns bool: Success or failure
258     """
259     self._current_token = MatrixToken()
260
261     while self._parse_matrix_part():
262         pass # The actual execution is taken care of in the loop condition
263
264     if self._current_token.identifier == '':
265         return False
266
267     self._current_group.append(self._current_token.tuple)
268     return True
269
270 def _parse_matrix_part(self) -> bool:
271     """Parse part of a matrix (multiplier, identifier, or exponent).
272
273     Which part of the matrix we parse is dependent on the current value of the pointer and the expression.
274 This method will parse whichever part of matrix token that it can. If it can't parse a part of a matrix,
275 or it's reached the next matrix, then we just return False. If we succeeded to parse a matrix part, then
276 we return True.
277
278     :returns bool: Success or failure
279     :raises MatrixParseError: If we fail to parse this part of the matrix
280     """
281     if self._pointer >= len(self._expression):
282         return False
283
284     if self._char.isdigit() or self._char == '-':
285         if self._current_token.multiplier != '' \
286             or (self._current_token.multiplier == '' and self._current_token.identifier != ''):
287             return False
288

```

```

289         self._parse_multiplier()
290
291     elif self._char.isalpha() and self._char.isupper():
292         if self._current_token.identifier != '':
293             return False
294
295         self._current_token.identifier = self._char
296         self._pointer += 1
297
298     elif self._char == 'r':
299         if self._current_token.identifier != '':
300             return False
301
302         self._parse_rot_identifier()
303
304     elif self._char == '[':
305         if self._current_token.identifier != '':
306             return False
307
308         self._parse_anonymous_identifier()
309
310     elif self._char == '(':
311         if self._current_token.identifier != '':
312             return False
313
314         self._parse_sub_expression()
315
316     elif self._char == '^':
317         if self._current_token.exponent != '':
318             return False
319
320         self._parse_exponent()
321
322     elif self._char == '+':
323         return False
324
325     else:
326         raise MatrixParseError(f'Unrecognised character "{self._char}" in matrix expression')
327
328     return True
329
330 def _parse_multiplier(self) -> None:
331     """Parse a multiplier from the expression and pointer.
332
333     This method just parses a numerical multiplier, which can include
334     zero or one ``.`` character and optionally a ``-`` at the start.
335
336     :raises MatrixParseError: If we fail to parse this part of the matrix
337     """
338     multiplier = ''
339
340     while self._char.isdigit() or self._char in ('.', '-'):
341         multiplier += self._char
342         self._pointer += 1
343
344     try:
345         float(multiplier)
346     except ValueError as e:
347         raise MatrixParseError(f'Invalid multiplier "{multiplier}"') from e
348
349     self._current_token.multiplier = multiplier
350
351 def _parse_rot_identifier(self) -> None:
352     """Parse a ``rot()``-style identifier from the expression and pointer.
353
354     This method will just parse something like ``rot(12.5)``. The angle number must be a real number.
355
356     :raises MatrixParseError: If we fail to parse this part of the matrix
357     """
358     if match := re.match(r'rot\(([^\d.-]+\d+)\)', self._expression[self._pointer:]):
359         # Ensure that the number in brackets is a valid float
360         try:
361             float(match.group(1))

```

```

362         except ValueError as e:
363             raise MatrixParseError(f'Invalid angle number "{match.group(1)}" in rot-identifier') from e
364
365         self._current_token.identifier = match.group(0)
366         self._pointer += len(match.group(0))
367     else:
368         raise MatrixParseError(
369             f'Invalid rot-identifier "{self._expression[self._pointer : self._pointer + 15]}..."'
370         )
371
372     def _parse_anonymous_identifer(self) -> None:
373         # """
374         if match := re.match(
375             r'^\[(-?\d+(?:\.\d+)?) (-?\d+(?:\.\d+)?);(-?\d+(?:\.\d+)?) (-?\d+(?:\.\d+)?)\]',
376             self._expression[self._pointer:]):
377             ):
378                 for n in range(1, 4 + 1):
379                     try:
380                         float(match.group(n))
381                     except ValueError as e:
382                         raise MatrixParseError(f'Invalid matrix entry "{match.group(1)}" in anonymous matrix') from e
383
384                 self._current_token.identifier = match.group(0)
385                 self._pointer += len(match.group(0))
386             else:
387                 raise MatrixParseError(
388                     f'Invalid anonymous matrix "{self._expression[self._pointer : self._pointer + 15]}..."'
389                 )
390
391     def _parse_sub_expression(self) -> None:
392         """Parse a parenthesized sub-expression as the identifier.
393
394         This method will also validate the expression in the parentheses.
395
396         :raises MatrixParseError: If we fail to parse this part of the matrix
397         """
398         if self._char != '(':
399             raise MatrixParseError('Sub-expression must start with "("')
400
401         self._pointer += 1
402         paren_depth = 1
403         identifier = ''
404
405         while paren_depth > 0:
406             if self._char == '(':
407                 paren_depth += 1
408             elif self._char == ')':
409                 paren_depth -= 1
410
411             if paren_depth == 0:
412                 self._pointer += 1
413                 break
414
415             identifier += self._char
416             self._pointer += 1
417
418         if not validate_matrix_expression(identifier):
419             raise MatrixParseError(f'Invalid sub-expression identifier "{identifier}"')
420
421         self._current_token.identifier = identifier
422
423     def _parse_exponent(self) -> None:
424         """Parse a matrix exponent from the expression and pointer.
425
426         The exponent must be an integer or ``T`` for transpose.
427
428         :raises MatrixParseError: If we fail to parse this part of the token
429         """
430         if match := re.match(r'^\{(-?\d+|T)\}', self._expression[self._pointer:]):
431             exponent = match.group(1)
432
433             try:
434                 if exponent != 'T':

```

```

435         int(exponent)
436     except ValueError as e:
437         raise MatrixParseError(f'Invalid exponent "{match.group(1)}"' from e
438
439     self._current_token.exponent = exponent
440     self._pointer += len(match.group(0))
441     else:
442         raise MatrixParseError(
443             f'Invalid exponent "{self._expression[self._pointer : self._pointer + 10]}...'
444         )
445
446
447 def parse_matrix_expression(expression: str) -> MatrixParseList:
448     """Parse the matrix expression and return a :attr:`~lintrans.typing.MatrixParseList`.
449
450     :Example:
451
452     >>> parse_matrix_expression('A')
453     [[(' ', 'A', ' ')]]
454     >>> parse_matrix_expression('-3M^2')
455     [[(' ', 'M', '2')]]
456     >>> parse_matrix_expression('1.2rot(12)^{3}2B^T')
457     [[('1.2', 'rot(12)', '3'), ('2', 'B', 'T')]]
458     >>> parse_matrix_expression('A^2 + 3B')
459     [[(' ', 'A', '2')], [('3', 'B', ' ')]]
460     >>> parse_matrix_expression('-3A^{1}3B^T - 45M^2')
461     [[(' ', 'A', '1'), ('3', 'B', 'T')], [(' ', 'M', '2')]]
462     >>> parse_matrix_expression('5.3A^{4} 2.6B^{-2} + 4.6D^T 8.9E^{-1}')
463     [[('5.3', 'A', '4'), ('2.6', 'B', '-2')], [('4.6', 'D', 'T'), ('8.9', 'E', '-1')]]
464     >>> parse_matrix_expression('2(A+B^TC)^2D')
465     [[('2', 'A+B^TC', '2'), (' ', 'D', ' ')]]
466
467     :param str expression: The expression to be parsed
468     :returns: A list of parsed components
469     :rtype: :attr:`~lintrans.typing.MatrixParseList`
470     """
471     return ExpressionParser(expression).parse()
472
473
474 def get_matrix_identifiers(expression: str) -> Set[str]:
475     """Return all the matrix identifiers used in the given expression.
476
477     This method works recursively with sub-expressions.
478     """
479     s = set()
480     top_level = [id for sublist in parse_matrix_expression(expression) for _, id, _ in sublist]
481
482     for body in top_level:
483         if body in _ALPHABET:
484             s.add(body)
485
486         elif re.match(r'rot\(\d+(\.\d+)?\)\'', body):
487             continue
488
489         else:
490             s.update(get_matrix_identifiers(body))
491
492     return s

```

## B Testing code

### B.1 conftest.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """A simple ``conftest.py`` containing some re-usable fixtures and functions."""
8
9  import numpy as np
10 import pytest
11
12 from lintrans.matrices import MatrixWrapper
13
14
15 def get_test_wrapper() -> MatrixWrapper:
16     """Return a new MatrixWrapper object with some preset values."""
17     wrapper = MatrixWrapper()
18
19     root_two_over_two = np.sqrt(2) / 2
20
21     wrapper['A'] = np.array([[1, 2], [3, 4]])
22     wrapper['B'] = np.array([[6, 4], [12, 9]])
23     wrapper['C'] = np.array([[ -1, -3], [4, -12]])
24     wrapper['D'] = np.array([[13.2, 9.4], [-3.4, -1.8]])
25     wrapper['E'] = np.array([
26         [root_two_over_two, -1 * root_two_over_two],
27         [root_two_over_two, root_two_over_two]
28     ])
29     wrapper['F'] = np.array([[ -1, 0], [0, 1]])
30     wrapper['G'] = np.array([[np.pi, np.e], [1729, 743.631]])
31
32     return wrapper
33
34
35 @pytest.fixture
36 def test_wrapper() -> MatrixWrapper:
37     """Return a new MatrixWrapper object with some preset values."""
38     return get_test_wrapper()
39
40
41 @pytest.fixture
42 def new_wrapper() -> MatrixWrapper:
43     """Return a new MatrixWrapper with no initialized values."""
44     return MatrixWrapper()

```

### B.2 backend/test\_session.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the functionality of saving and loading sessions."""
8
9  from pathlib import Path
10
11 from conftest import get_test_wrapper
12
13 import lintrans
14 from lintrans.gui.session import Session
15 from lintrans.gui.settings import DisplaySettings
16 from lintrans.matrices.wrapper import MatrixWrapper
17

```

```

18
19 def test_save_and_load(tmp_path: Path, test_wrapper: MatrixWrapper) -> None:
20     """Test that sessions save and load and return the same matrix wrapper."""
21     points = [(1, 0), (-2, 3), (3.2, -10), (0, 0), (-2, -3), (2, -1.3)]
22     session = Session(
23         matrix_wrapper=test_wrapper,
24         polygon_points=points,
25         display_settings=DisplaySettings(),
26         input_vector=(2, 3)
27     )
28
29     path = str((tmp_path / 'test.lt').absolute())
30     session.save_to_file(path)
31
32     loaded_session, version, extra_attrs = Session.load_from_file(path)
33     assert loaded_session.matrix_wrapper == get_test_wrapper()
34     assert loaded_session.polygon_points == points
35     assert loaded_session.display_settings == DisplaySettings()
36     assert loaded_session.input_vector == (2, 3)
37
38     assert version == lintrans.__version__
39     assert not extra_attrs

```

### B.3 backend/matrices/test\_parse\_and\_validate\_expression.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """Test the :mod:`matrices.parse` module validation and parsing."""
8
9 from typing import List, Tuple
10
11 import pytest
12
13 from lintrans.matrices.parse import (MatrixParseError, find_sub_expressions,
14                                     get_matrix_identifiers,
15                                     parse_matrix_expression, strip_whitespace,
16                                     validate_matrix_expression)
17 from lintrans.typing import MatrixParseList
18
19 expected_sub_expressions: List[Tuple[str, List[str]]] = [
20     ('2(AB)^-1', ['AB']),
21     ('-3(A+B)^2-C(B^TA)^-1', ['A+B', 'B^TA']),
22     ('rot(45)', []),
23     ('()', []),
24     ('()', ['()']),
25     ('2.3A^-1(AB)^-1+(BC)^2', ['AB', 'BC']),
26     ('(2.3A^-1(AB)^-1+(BC)^2)', ['2.3A^-1(AB)^-1+(BC)^2']),
27     ('(2.3 A^-1 (A B)^-1 + (B C)^2)', ['2.3A^-1(AB)^-1+(BC)^2']),
28     ('A([1 2; 3 4]M^T)^2', ['[1 2;3 4]M^T']),
29 ]
30
31
32 def test_find_sub_expressions() -> None:
33     """Test the :func:`lintrans.matrices.parse.find_sub_expressions` function."""
34     for inp, output in expected_sub_expressions:
35         assert find_sub_expressions(inp) == output
36
37
38 expected_stripped_whitespace: List[Tuple[str, str]] = [
39     ('[ 1 2 ; 3 4 ]', '[1 2;3 4]'),
40     ('[-3.4 6; 1.2 -9 ]', '[-3.4 6;1.2 -9]'),
41     ('A 4 [ 43 -653.23 ; 32523 -4.3 ] Z^2', 'A4[43 -653.23;32523 -4.3]Z^2'),
42     ('[ 1 2; -4 3.64] [-5 6; 8.3 2]', '[1 2;-4 3.64][-5 6;8.3 2]')
43 ]
44
45

```

```

46 def test_strip_whitespace() -> None:
47     """Test the :func:`lintrans.matrices.parse.strip_whitespace` function."""
48     for inp, output in expected_stripped_whitespace:
49         assert strip_whitespace(inp) == output
50
51
52 valid_inputs: List[str] = [
53     'A', 'AB', '3A', '1.2A', '-3.4A', 'A^2', 'A~-1', 'A^{~1}',
54     'A^12', 'A^T', 'A^{5}', 'A^{T}', '4.3A^7', '9.2A^{18}', '0.1A'
55
56     'rot(45)', 'rot(12.5)', '3rot(90)',
57     'rot(135)^3', 'rot(51)^T', 'rot(-34)^-1',
58
59     'A+B', 'A+2B', '4.3A+9B', 'A^2+B^T', '3A^7+0.8B^{16}',
60     'A-B', '3A-4B', '3.2A^3-16.79B^T', '4.752A^{17}-3.32B^{36}',
61     'A-1B', '-A', '-1A', 'A^{2}3.4B', 'A^{~1}2.3B',
62
63     '3A4B', 'A^TB', 'A^{T}B', '4A^6B^3',
64     '2A^{3}4B^5', '4rot(90)^3', 'rot(45)rot(13)',
65     'Arot(90)', 'AB^2', 'A^2B^2', '8.36A^T3.4B^12',
66
67     '3.5A^{4}5.6rot(19.2)^T-B^{~1}4.1C^5',
68
69     '(A)', '(AB)^-1', '2.3(3B^TA)^2', '-3.4(9D^{2}3F^~1)^T+C', '(AB)(C)',
70     '3(rot(34)^~7A)^-1+B', '3A^2B+4A(B+C)^~1D^T-A(C(D+E)B)',
71
72     '[1 2; 3 4]', '4[1 -2;12 5]^3', '[1 -2; 3.1 -4.1365]', 'A[1 -3; 4 5]^~1',
73     'rot(45)[-13.2 9;1.414 0]^2M^T', '([1 2; 3 4])', '3A^2(M-B^T)^{~1}18([13.2 -6.4; -11 0.2]+F)^2'
74 ]
75
76 invalid_inputs: List[str] = [
77     '', 'rot()', 'A', 'A^1.2', 'A^2 3.4B', 'A^23.4B', 'A^~1 2.3B', 'A^{3.4}', '1,2A', 'ro(12)', '5', '12^2',
78     '^T', '^12]', '.1A', 'A^{13}', 'A^3}', 'A^A', '^2', 'A--B', '--A', '+A', '--1A', 'A--B', 'A--1B',
79     '.A', '1.A', '2.3AB)^T', '(AB+)', '-4.6(9A', '-2(3.4A^{~1}-C^)^2', '9.2)', '3A^2B+4A(B+C)^~1D^T-A(C(D+EB))',
80     '3)^2', '4(your mum)^T', 'rot()', 'rot(10.1.1)', 'rot(--2)', '[]', '[1 2]', '[-1;3]', '[2 3; 5.6]',
81     '1 2; 3 4', '[1 2; 34]', '[1 2 3; 4 5]', '[1 2 3; 4 5 6]', '[;]', '[1; 2 3 4]',
82
83     'This is 100% a valid matrix expression, I swear'
84 ]
85
86
87 @pytest.mark.parametrize('inputs,output', [(valid_inputs, True), (invalid_inputs, False)])
88 def test_validate_matrix_expression(inputs: List[str], output: bool) -> None:
89     """Test the validate_matrix_expression() function."""
90     for inp in inputs:
91         assert validate_matrix_expression(inp) == output
92
93
94 expressions_and_parsed_expressions: List[Tuple[str, MatrixParseList]] = [
95     # Simple expressions
96     ('A', [[(' ', 'A', ' ')]]),
97     ('A^2', [[(' ', 'A', '2')]]),
98     ('A^{2}', [[(' ', 'A', '2')]]),
99     ('3A', [[('3', 'A', ' ')]]),
100     ('1.4A^3', [[('1.4', 'A', '3')]]),
101     ('0.1A', [[('0.1', 'A', ' ')]]),
102     ('0.1A', [[('0.1', 'A', ' ')]]),
103     ('A^12', [[(' ', 'A', '12')]]),
104     ('A^234', [[(' ', 'A', '234')]]),
105
106     # Multiplications
107     ('A 0.1B', [[(' ', 'A', ' '), ('0.1', 'B', ' ')]]),
108     ('A^2 3B', [[(' ', 'A', '23'), (' ', 'B', ' ')]]),
109     ('A^{2}3.4B', [[(' ', 'A', '2'), ('3.4', 'B', ' ')]]),
110     ('4A^{3} 6B^2', [[('4', 'A', '3'), ('6', 'B', '2')]]),
111     ('4.2A^{T} 6.1B^~1', [[('4.2', 'A', 'T'), ('6.1', 'B', '~1')]]),
112     ('~1.2A^2 rot(45)^2', [[('~1.2', 'A', '2'), (' ', 'rot(45)', '2')]]),
113     ('3.2A^T 4.5B^{5} 9.6rot(121.3)', [[('3.2', 'A', 'T'), ('4.5', 'B', '5'), ('9.6', 'rot(121.3)', ' ')]]),
114     ('~1.18A^{~2} 0.1B^{2} 9rot(-34.6)^~1', [[('~1.18', 'A', '~2'), ('0.1', 'B', '2'), ('9', 'rot(-34.6)', '~1')]]),
115
116     # Additions
117     ('A + B', [[(' ', 'A', ' '), (' ', 'B', ' ')]]),
118     ('A + B - C', [[(' ', 'A', ' '), (' ', 'B', ' '), ('~1', 'C', ' ')]]),

```



```

119     ('A^2 + 0.5B', [[(' ', 'A', '2')], [('0.5', 'B', '')]]),
120     ('2A^3 + 8B^T - 3C^-1', [[('2', 'A', '3')], [('8', 'B', 'T')], [(' -3', 'C', ' -1')]]),
121     ('4.9A^2 - 3rot(134.2)^-1 + 7.6B^8', [[('4.9', 'A', '2')], [(' -3', 'rot(134.2)', ' -1')], [('7.6', 'B', '8')]]),
122
123     # Additions with multiplication
124     ('2.14A^3 4.5rot(14.5)^-1 + 8B^T - 3C^-1', [[('2.14', 'A', '3'), ('4.5', 'rot(14.5)', ' -1')],
125                                                    [('8', 'B', 'T')], [(' -3', 'C', ' -1')]]),
126     ('2.14A^3 4.5rot(14.5)^-1 + 8.5B^T 5.97C^14 - 3.14D^-1 6.7E^T',
127      [[('2.14', 'A', '3'), ('4.5', 'rot(14.5)', ' -1')], [('8.5', 'B', 'T'), ('5.97', 'C', '14')],
128      [('-3.14', 'D', ' -1'), ('6.7', 'E', 'T')]]),
129
130     # Parenthesized expressions
131     ('(AB)^-1', [[(' ', 'AB', ' -1')]]),
132     ('-3(A+B)^2-C(B^TA)^-1', [[(' -3', 'A+B', '2')], [(' -1', 'C', ''), (' ', 'B^T A', ' -1')]]),
133     ('2.3(3B^TA)^2', [[('2.3', '3B^T A', '2')]]),
134     ('-3.4(9D^2 3F^-1)^T+C', [[(' -3.4', '9D^2 3F^-1', 'T')], [(' ', 'C', '')]]),
135     ('2.39(3.1A^-1)2.3B(CD)^-1^T + (AB^T)^-1', [[('2.39', '3.1A^-1 2.3B(CD)^-1', 'T')], [(' ', 'AB^T',
136     ↪ ' -1')]]),
137
138     # Anonymous matrices
139     ('[1 2; 3 4]', [[(' ', '[1 2; 3 4]', '')]]),
140     ('A[-3 4; 16.2 87.93]', [[(' ', 'A', ''), (' ', '[-3 4; 16.2 87.93]', '')]]),
141     (
142         '3A^2(M-[ 1 2 ; 5 4 ]^T)^-1 18([13.2 -6.4; -11 0.2]+F)^2+Z',
143         [[('3', 'A', '2'), (' ', 'M-[ 1 2; 5 4 ]^T', ' -1'), ('18', '[13.2 -6.4; -11 0.2]+F', '2')], [(' ', 'Z', '')]]
144     )
145 ]
146
147 def test_parse_matrix_expression() -> None:
148     """Test the parse_matrix_expression() function."""
149     for expression, parsed_expression in expressions_and_parsed_expressions:
150         # Test it with and without whitespace
151         assert parse_matrix_expression(expression) == parsed_expression
152         assert parse_matrix_expression(strip_whitespace(expression)) == parsed_expression
153
154     for expression in valid_inputs:
155         # Assert that it doesn't raise MatrixParseError
156         parse_matrix_expression(expression)
157
158
159 def test_parse_error() -> None:
160     """Test that parse_matrix_expression() raises a MatrixParseError."""
161     for expression in invalid_inputs:
162         with pytest.raises(MatrixParseError):
163             parse_matrix_expression(expression)
164
165
166 def test_get_matrix_identifiers() -> None:
167     """Test that matrix identifiers can be properly found."""
168     assert get_matrix_identifiers('M^T') == {'M'}
169     assert get_matrix_identifiers('ABCDE F') == {'A', 'B', 'C', 'D', 'E', 'F'}
170     assert get_matrix_identifiers('AB^-1 3Crot(45)2A(B^2C^-1)') == {'A', 'B', 'C'}
171     assert get_matrix_identifiers('A^2 3A^-1A^TA') == {'A'}
172     assert get_matrix_identifiers('rot(45)(rot(25)rot(20))^2') == set()
173
174     for expression in invalid_inputs:
175         with pytest.raises(MatrixParseError):
176             get_matrix_identifiers(expression)

```

## B.4 backend/matrices/utility/test\_rotation\_matrices.py

```

1 # lintrans - The linear transformation visualizer
2 # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4 # This program is licensed under GNU GPLv3, available here:
5 # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7 """Test functions for rotation matrices."""
8

```

```

9     from typing import List, Tuple
10
11     import numpy as np
12     import pytest
13
14     from lintrans.matrices import create_rotation_matrix
15     from lintrans.typing_ import MatrixType
16
17     angles_and_matrices: List[Tuple[float, float, MatrixType]] = [
18         (0, 0, np.array([[1, 0], [0, 1]])),
19         (90, np.pi / 2, np.array([[0, -1], [1, 0]])),
20         (180, np.pi, np.array([[ -1, 0], [0, -1]])),
21         (270, 3 * np.pi / 2, np.array([[0, 1], [-1, 0]])),
22         (360, 2 * np.pi, np.array([[1, 0], [0, 1]])),
23
24         (45, np.pi / 4, np.array([
25             [np.sqrt(2) / 2, -1 * np.sqrt(2) / 2],
26             [np.sqrt(2) / 2, np.sqrt(2) / 2]
27         ])),
28         (135, 3 * np.pi / 4, np.array([
29             [-1 * np.sqrt(2) / 2, -1 * np.sqrt(2) / 2],
30             [np.sqrt(2) / 2, -1 * np.sqrt(2) / 2]
31         ])),
32         (225, 5 * np.pi / 4, np.array([
33             [-1 * np.sqrt(2) / 2, np.sqrt(2) / 2],
34             [-1 * np.sqrt(2) / 2, -1 * np.sqrt(2) / 2]
35         ])),
36         (315, 7 * np.pi / 4, np.array([
37             [np.sqrt(2) / 2, np.sqrt(2) / 2],
38             [-1 * np.sqrt(2) / 2, np.sqrt(2) / 2]
39         ])),
40
41         (30, np.pi / 6, np.array([
42             [np.sqrt(3) / 2, -1 / 2],
43             [1 / 2, np.sqrt(3) / 2]
44         ])),
45         (60, np.pi / 3, np.array([
46             [1 / 2, -1 * np.sqrt(3) / 2],
47             [np.sqrt(3) / 2, 1 / 2]
48         ])),
49         (120, 2 * np.pi / 3, np.array([
50             [-1 / 2, -1 * np.sqrt(3) / 2],
51             [np.sqrt(3) / 2, -1 / 2]
52         ])),
53         (150, 5 * np.pi / 6, np.array([
54             [-1 * np.sqrt(3) / 2, -1 / 2],
55             [1 / 2, -1 * np.sqrt(3) / 2]
56         ])),
57         (210, 7 * np.pi / 6, np.array([
58             [-1 * np.sqrt(3) / 2, 1 / 2],
59             [-1 / 2, -1 * np.sqrt(3) / 2]
60         ])),
61         (240, 4 * np.pi / 3, np.array([
62             [-1 / 2, np.sqrt(3) / 2],
63             [-1 * np.sqrt(3) / 2, -1 / 2]
64         ])),
65         (300, 10 * np.pi / 6, np.array([
66             [1 / 2, np.sqrt(3) / 2],
67             [-1 * np.sqrt(3) / 2, 1 / 2]
68         ])),
69         (330, 11 * np.pi / 6, np.array([
70             [np.sqrt(3) / 2, 1 / 2],
71             [-1 / 2, np.sqrt(3) / 2]
72         ]))
73     ]
74
75
76     def test_create_rotation_matrix() -> None:
77         """Test that create_rotation_matrix() works with given angles and expected matrices."""
78         for degrees, radians, matrix in angles_and_matrices:
79             assert create_rotation_matrix(degrees, degrees=True) == pytest.approx(matrix)
80             assert create_rotation_matrix(radians, degrees=False) == pytest.approx(matrix)
81

```

```

82         assert create_rotation_matrix(-1 * degrees, degrees=True) == pytest.approx(np.linalg.inv(matrix))
83         assert create_rotation_matrix(-1 * radians, degrees=False) == pytest.approx(np.linalg.inv(matrix))
84
85     assert (create_rotation_matrix(-90, degrees=True) ==
86            create_rotation_matrix(270, degrees=True)).all()
87     assert (create_rotation_matrix(-0.5 * np.pi, degrees=False) ==
88            create_rotation_matrix(1.5 * np.pi, degrees=False)).all()

```

## B.5 backend/matrices/utility/test\_coord\_conversion.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2022 D. Dyson (DoctorDalek1963)
3  #
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test conversion between polar and rectilinear coordinates in :mod:`lintrans.matrices.utility`."""
8
9  from typing import List, Tuple
10
11  from numpy import pi, sqrt
12  from pytest import approx
13
14  from lintrans.matrices.utility import polar_coords, rect_coords
15
16  expected_coords: List[Tuple[Tuple[float, float], Tuple[float, float]]] = [
17      ((0, 0), (0, 0)),
18      ((1, 1), (sqrt(2), pi / 4)),
19      ((0, 1), (1, pi / 2)),
20      ((1, 0), (1, 0)),
21      ((sqrt(2), sqrt(2)), (2, pi / 4)),
22      ((-3, 4), (5, 2.214297436)),
23      ((4, -3), (5, 5.639684198)),
24      ((5, -0.2), (sqrt(626) / 5, 6.24320662)),
25      ((-1.3, -10), (10.08414597, 4.583113976)),
26      ((23.4, 0), (23.4, 0)),
27      ((pi, -pi), (4.442882938, 1.75 * pi))
28  ]
29
30
31  def test_polar_coords() -> None:
32      """Test that :func:`lintrans.matrices.utility.polar_coords` works as expected."""
33      for rect, polar in expected_coords:
34          assert polar_coords(*rect) == approx(polar)
35
36
37  def test_rect_coords() -> None:
38      """Test that :func:`lintrans.matrices.utility.rect_coords` works as expected."""
39      for rect, polar in expected_coords:
40          assert rect_coords(*polar) == approx(rect)
41
42      assert rect_coords(1, 0) == approx((1, 0))
43      assert rect_coords(1, pi) == approx((-1, 0))
44      assert rect_coords(1, 2 * pi) == approx((1, 0))
45      assert rect_coords(1, 3 * pi) == approx((-1, 0))
46      assert rect_coords(1, 4 * pi) == approx((1, 0))
47      assert rect_coords(1, 5 * pi) == approx((-1, 0))
48      assert rect_coords(1, 6 * pi) == approx((1, 0))
49      assert rect_coords(20, 100) == approx(rect_coords(20, 100 % (2 * pi)))

```

## B.6 backend/matrices/utility/test\_float\_utility\_functions.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3  #
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6

```

```

7  """Test the utility functions for GUI dialog boxes."""
8
9  from typing import List, Tuple
10
11  import numpy as np
12  import pytest
13
14  from lintrans.matrices.utility import is_valid_float, round_float
15
16  valid_floats: List[str] = [
17      '0', '1', '3', '-2', '123', '-208', '1.2', '-3.5', '4.252634', '-42362.352325',
18      '1e4', '-2.59e3', '4.13e-6', '-5.5244e-12'
19  ]
20
21  invalid_floats: List[str] = [
22      '', 'pi', 'e', '1.2.3', '1,2', '-', '.', 'None', 'no', 'yes', 'float'
23  ]
24
25
26  @pytest.mark.parametrize('inputs,output', [(valid_floats, True), (invalid_floats, False)])
27  def test_is_valid_float(inputs: List[str], output: bool) -> None:
28      """Test the is_valid_float() function."""
29      for inp in inputs:
30          assert is_valid_float(inp) == output
31
32
33  def test_round_float() -> None:
34      """Test the round_float() function."""
35      expected_values: List[Tuple[float, int, str]] = [
36          (1.0, 4, '1'), (1e-6, 4, '0'), (1e-5, 6, '1e-5'), (6.3e-8, 5, '0'), (3.2e-8, 10, '3.2e-8'),
37          (np.sqrt(2) / 2, 5, '0.70711'), (-1 * np.sqrt(2) / 2, 5, '-0.70711'),
38          (np.pi, 1, '3.1'), (np.pi, 2, '3.14'), (np.pi, 3, '3.142'), (np.pi, 4, '3.1416'), (np.pi, 5, '3.14159'),
39          (1.23456789, 2, '1.23'), (1.23456789, 3, '1.235'), (1.23456789, 4, '1.2346'), (1.23456789, 5, '1.23457'),
40          (12345.678, 1, '12345.7'), (12345.678, 2, '12345.68'), (12345.678, 3, '12345.678'),
41      ]
42
43      for num, precision, answer in expected_values:
44          assert round_float(num, precision) == answer

```

## B.7 backend/matrices/matrix\_wrapper/test\_setting\_and\_getting.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the MatrixWrapper __setitem__() and __getitem__() methods."""
8
9  from typing import Any, Dict, List
10
11  import numpy as np
12  import pytest
13  from numpy import linalg as la
14
15  from lintrans.matrices import MatrixWrapper
16  from lintrans.typing_ import MatrixType
17
18  valid_matrix_names = 'ABCDEFGHJKLMNPOQRSTUVWXYZ'
19  invalid_matrix_names = ['bad name', '123456', 'Th15 Is an 1nV@l1D n@m3', 'abc', 'a']
20
21  test_matrix: MatrixType = np.array([[1, 2], [4, 3]])
22
23
24  def test_basic_get_matrix(new_wrapper: MatrixWrapper) -> None:
25      """Test MatrixWrapper().__getitem__()."""
26      for name in valid_matrix_names:
27          assert new_wrapper[name] is None
28
29      assert (new_wrapper['I'] == np.array([[1, 0], [0, 1]]).all()

```

```

30
31
32 def test_get_name_error(new_wrapper: MatrixWrapper) -> None:
33     """Test that MatrixWrapper().__getitem__() raises a NameError if called with an invalid name."""
34     for name in invalid_matrix_names:
35         with pytest.raises(NameError):
36             _ = new_wrapper[name]
37
38
39 def test_basic_set_matrix(new_wrapper: MatrixWrapper) -> None:
40     """Test MatrixWrapper().__setitem__()."""
41     for name in valid_matrix_names:
42         new_wrapper[name] = test_matrix
43         assert (new_wrapper[name] == test_matrix).all()
44
45         new_wrapper[name] = None
46         assert new_wrapper[name] is None
47
48
49 def test_set_expression(test_wrapper: MatrixWrapper) -> None:
50     """Test that MatrixWrapper.__setitem__() can accept a valid expression."""
51     test_wrapper['N'] = 'A^2'
52     test_wrapper['O'] = 'BA+2C'
53     test_wrapper['P'] = 'E^T'
54     test_wrapper['Q'] = 'C^-1B'
55     test_wrapper['R'] = 'A^{2}3B'
56     test_wrapper['S'] = 'N^-1'
57     test_wrapper['T'] = 'PQP^-1'
58
59     with pytest.raises(TypeError):
60         test_wrapper['U'] = 'A+1'
61
62     with pytest.raises(TypeError):
63         test_wrapper['V'] = 'K'
64
65     with pytest.raises(TypeError):
66         test_wrapper['W'] = 'L^2'
67
68     with pytest.raises(TypeError):
69         test_wrapper['X'] = 'M^-1'
70
71     with pytest.raises(TypeError):
72         test_wrapper['Y'] = 'A^2B+C'
73
74
75 def test_simple_dynamic_evaluation(test_wrapper: MatrixWrapper) -> None:
76     """Test that expression-defined matrices are evaluated dynamically."""
77     test_wrapper['N'] = 'A^2'
78     test_wrapper['O'] = '4B'
79     test_wrapper['P'] = 'A+C'
80
81     assert (test_wrapper['N'] == test_wrapper.evaluate_expression('A^2')).all()
82     assert (test_wrapper['O'] == test_wrapper.evaluate_expression('4B')).all()
83     assert (test_wrapper['P'] == test_wrapper.evaluate_expression('A+C')).all()
84
85     assert (test_wrapper.evaluate_expression('N^2 + 3O') ==
86             la.matrix_power(test_wrapper.evaluate_expression('A^2'), 2) +
87             3 * test_wrapper.evaluate_expression('4B')
88             ).all()
89     assert (test_wrapper.evaluate_expression('P^-1 - 3N^2') ==
90             la.inv(test_wrapper.evaluate_expression('A+C')) -
91             (3 * test_wrapper.evaluate_expression('A^2')) @
92             la.matrix_power(test_wrapper.evaluate_expression('4B'), 2)
93             ).all()
94
95     test_wrapper['A'] = np.array([
96         [19, -21.5],
97         [84, 96.572]
98     ])
99     test_wrapper['B'] = np.array([
100         [-0.993, 2.52],
101         [1e10, 0]
102     ])

```

```

103     test_wrapper['C'] = np.array([
104         [0, 19512],
105         [1.414, 19]
106     ])
107
108     assert (test_wrapper['N'] == test_wrapper.evaluate_expression('A^2')).all()
109     assert (test_wrapper['O'] == test_wrapper.evaluate_expression('4B')).all()
110     assert (test_wrapper['P'] == test_wrapper.evaluate_expression('A+C')).all()
111
112     assert (test_wrapper.evaluate_expression('N^2 + 30') ==
113             la.matrix_power(test_wrapper.evaluate_expression('A^2'), 2) +
114             3 * test_wrapper.evaluate_expression('4B')
115             ).all()
116     assert (test_wrapper.evaluate_expression('P^-1 - 3N0^2') ==
117             la.inv(test_wrapper.evaluate_expression('A+C')) -
118             (3 * test_wrapper.evaluate_expression('A^2')) @
119             la.matrix_power(test_wrapper.evaluate_expression('4B'), 2)
120             ).all()
121
122
123 def test_recursive_dynamic_evaluation(test_wrapper: MatrixWrapper) -> None:
124     """Test that dynamic evaluation works recursively."""
125     test_wrapper['N'] = 'A^2'
126     test_wrapper['O'] = '4B'
127     test_wrapper['P'] = 'A+C'
128
129     test_wrapper['Q'] = 'N^-1'
130     test_wrapper['R'] = 'P-40'
131     test_wrapper['S'] = 'NOP'
132
133     assert test_wrapper['Q'] == pytest.approx(test_wrapper.evaluate_expression('A^-2'))
134     assert test_wrapper['R'] == pytest.approx(test_wrapper.evaluate_expression('A + C - 16B'))
135     assert test_wrapper['S'] == pytest.approx(test_wrapper.evaluate_expression('A^{2}4BA + A^{2}4BC'))
136
137
138 def test_self_referential_expressions(test_wrapper: MatrixWrapper) -> None:
139     """Test that self-referential expressions raise an error."""
140     expressions: Dict[str, str] = {
141         'A': 'A^2',
142         'B': 'A(C^-1A^T)+rot(45)B',
143         'C': '2Brot(1482.536)(A^-1D^{2}4CE)^3F'
144     }
145
146     for name, expression in expressions.items():
147         with pytest.raises(ValueError):
148             test_wrapper[name] = expression
149
150     test_wrapper['B'] = '3A^2'
151     test_wrapper['C'] = 'ABBA'
152     with pytest.raises(ValueError):
153         test_wrapper['A'] = 'C^-1'
154
155     test_wrapper['E'] = 'rot(45)B^-1+C^T'
156     test_wrapper['F'] = 'EBDBIC'
157     test_wrapper['D'] = 'E'
158     with pytest.raises(ValueError):
159         test_wrapper['D'] = 'F'
160
161
162 def test_get_matrix_dependencies(test_wrapper: MatrixWrapper) -> None:
163     """Test MatrixWrapper's get_matrix_dependencies() and get_expression_dependencies() methods."""
164     test_wrapper['N'] = 'A^2'
165     test_wrapper['O'] = '4B'
166     test_wrapper['P'] = 'A+C'
167     test_wrapper['Q'] = 'N^-1'
168     test_wrapper['R'] = 'P-40'
169     test_wrapper['S'] = 'NOP'
170
171     assert test_wrapper.get_matrix_dependencies('A') == set()
172     assert test_wrapper.get_matrix_dependencies('B') == set()
173     assert test_wrapper.get_matrix_dependencies('C') == set()
174     assert test_wrapper.get_matrix_dependencies('D') == set()
175     assert test_wrapper.get_matrix_dependencies('E') == set()

```

```

176     assert test_wrapper.get_matrix_dependencies('F') == set()
177     assert test_wrapper.get_matrix_dependencies('G') == set()
178
179     assert test_wrapper.get_matrix_dependencies('N') == {'A'}
180     assert test_wrapper.get_matrix_dependencies('O') == {'B'}
181     assert test_wrapper.get_matrix_dependencies('P') == {'A', 'C'}
182     assert test_wrapper.get_matrix_dependencies('Q') == {'A', 'N'}
183     assert test_wrapper.get_matrix_dependencies('R') == {'A', 'B', 'C', 'O', 'P'}
184     assert test_wrapper.get_matrix_dependencies('S') == {'A', 'B', 'C', 'N', 'O', 'P'}
185
186     assert test_wrapper.get_expression_dependencies('ABC') == set()
187     assert test_wrapper.get_expression_dependencies('NOB') == {'A', 'B'}
188     assert test_wrapper.get_expression_dependencies('N^20^Trot(90)B^-1') == {'A', 'B'}
189     assert test_wrapper.get_expression_dependencies('NOP') == {'A', 'B', 'C'}
190     assert test_wrapper.get_expression_dependencies('NOPQ') == {'A', 'B', 'C', 'N'}
191     assert test_wrapper.get_expression_dependencies('NOPQR') == {'A', 'B', 'C', 'N', 'O', 'P'}
192     assert test_wrapper.get_expression_dependencies('NOPQRS') == {'A', 'B', 'C', 'N', 'O', 'P'}
193
194
195 def test_set_identity_error(new_wrapper: MatrixWrapper) -> None:
196     """Test that MatrixWrapper().__setitem__() raises a NameError when trying to assign to the identity matrix."""
197     with pytest.raises(NameError):
198         new_wrapper['I'] = test_matrix
199
200
201 def test_set_name_error(new_wrapper: MatrixWrapper) -> None:
202     """Test that MatrixWrapper().__setitem__() raises a NameError when trying to assign to an invalid name."""
203     for name in invalid_matrix_names:
204         with pytest.raises(NameError):
205             new_wrapper[name] = test_matrix
206
207
208 def test_set_type_error(new_wrapper: MatrixWrapper) -> None:
209     """Test that MatrixWrapper().__setitem__() raises a TypeError when trying to set a non-matrix."""
210     invalid_values: List[Any] = [
211         12,
212         [1, 2, 3, 4, 5],
213         [[1, 2], [3, 4]],
214         True,
215         24.3222,
216         'This is totally a matrix, I swear',
217         MatrixWrapper,
218         MatrixWrapper(),
219         np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]]),
220         np.eye(100)
221     ]
222
223     for value in invalid_values:
224         with pytest.raises(TypeError):
225             new_wrapper['M'] = value
226
227
228 def test_get_expression(test_wrapper: MatrixWrapper) -> None:
229     """Test the get_expression method of the MatrixWrapper class."""
230     test_wrapper['N'] = 'A^2'
231     test_wrapper['O'] = '4B'
232     test_wrapper['P'] = 'A+C'
233
234     test_wrapper['Q'] = 'N^-1'
235     test_wrapper['R'] = 'P-40'
236     test_wrapper['S'] = 'NOP'
237
238     assert test_wrapper.get_expression('A') is None
239     assert test_wrapper.get_expression('B') is None
240     assert test_wrapper.get_expression('C') is None
241     assert test_wrapper.get_expression('D') is None
242     assert test_wrapper.get_expression('E') is None
243     assert test_wrapper.get_expression('F') is None
244     assert test_wrapper.get_expression('G') is None
245
246     assert test_wrapper.get_expression('N') == 'A^2'
247     assert test_wrapper.get_expression('O') == '4B'
248     assert test_wrapper.get_expression('P') == 'A+C'

```

```

249
250     assert test_wrapper.get_expression('Q') == 'N^-1'
251     assert test_wrapper.get_expression('R') == 'P-40'
252     assert test_wrapper.get_expression('S') == 'NOP'

```

## B.8 backend/matrices/matrix\_wrapper/test\_evaluate\_expression.py

```

1  # lintrans - The linear transformation visualizer
2  # Copyright (C) 2021-2022 D. Dyson (DoctorDalek1963)
3
4  # This program is licensed under GNU GPLv3, available here:
5  # <https://www.gnu.org/licenses/gpl-3.0.html>
6
7  """Test the MatrixWrapper evaluate_expression() method."""
8
9  import numpy as np
10 import pytest
11 from conftest import get_test_wrapper
12 from numpy import linalg as la
13 from pytest import approx
14
15 from lintrans.matrices import MatrixWrapper, create_rotation_matrix
16 from lintrans.typing import MatrixType
17
18
19 def test_simple_matrix_addition(test_wrapper: MatrixWrapper) -> None:
20     """Test simple addition and subtraction of two matrices."""
21     # NOTE: We assert that all of these values are not None just to stop mypy complaining
22     # These values will never actually be None because they're set in the wrapper() fixture
23     # There's probably a better way do this, because this method is a bit of a bodge, but this works for now
24     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
25         test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
26         test_wrapper['G'] is not None
27
28     assert (test_wrapper.evaluate_expression('A+B') == test_wrapper['A'] + test_wrapper['B']).all()
29     assert (test_wrapper.evaluate_expression('E+F') == test_wrapper['E'] + test_wrapper['F']).all()
30     assert (test_wrapper.evaluate_expression('G+D') == test_wrapper['G'] + test_wrapper['D']).all()
31     assert (test_wrapper.evaluate_expression('C+C') == test_wrapper['C'] + test_wrapper['C']).all()
32     assert (test_wrapper.evaluate_expression('D+A') == test_wrapper['D'] + test_wrapper['A']).all()
33     assert (test_wrapper.evaluate_expression('B+C') == test_wrapper['B'] + test_wrapper['C']).all()
34
35     assert test_wrapper == get_test_wrapper()
36
37
38 def test_simple_two_matrix_multiplication(test_wrapper: MatrixWrapper) -> None:
39     """Test simple multiplication of two matrices."""
40     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
41         test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
42         test_wrapper['G'] is not None
43
44     assert (test_wrapper.evaluate_expression('AB') == test_wrapper['A'] @ test_wrapper['B']).all()
45     assert (test_wrapper.evaluate_expression('BA') == test_wrapper['B'] @ test_wrapper['A']).all()
46     assert (test_wrapper.evaluate_expression('AC') == test_wrapper['A'] @ test_wrapper['C']).all()
47     assert (test_wrapper.evaluate_expression('DA') == test_wrapper['D'] @ test_wrapper['A']).all()
48     assert (test_wrapper.evaluate_expression('ED') == test_wrapper['E'] @ test_wrapper['D']).all()
49     assert (test_wrapper.evaluate_expression('FD') == test_wrapper['F'] @ test_wrapper['D']).all()
50     assert (test_wrapper.evaluate_expression('GA') == test_wrapper['G'] @ test_wrapper['A']).all()
51     assert (test_wrapper.evaluate_expression('CF') == test_wrapper['C'] @ test_wrapper['F']).all()
52     assert (test_wrapper.evaluate_expression('AG') == test_wrapper['A'] @ test_wrapper['G']).all()
53
54     assert test_wrapper.evaluate_expression('A2B') == approx(test_wrapper['A'] @ (2 * test_wrapper['B']))
55     assert test_wrapper.evaluate_expression('2AB') == approx((2 * test_wrapper['A']) @ test_wrapper['B'])
56     assert test_wrapper.evaluate_expression('C3D') == approx(test_wrapper['C'] @ (3 * test_wrapper['D']))
57     assert test_wrapper.evaluate_expression('4.2E1.2A') == approx((4.2 * test_wrapper['E']) @ (1.2 *
58         ↪ test_wrapper['A']))
59
60     assert test_wrapper == get_test_wrapper()
61
62 def test_identity_multiplication(test_wrapper: MatrixWrapper) -> None:

```



```

63     """Test that multiplying by the identity doesn't change the value of a matrix."""
64     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
65           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
66           test_wrapper['G'] is not None
67
68     assert (test_wrapper.evaluate_expression('I') == test_wrapper['I']).all()
69     assert (test_wrapper.evaluate_expression('AI') == test_wrapper['A']).all()
70     assert (test_wrapper.evaluate_expression('IA') == test_wrapper['A']).all()
71     assert (test_wrapper.evaluate_expression('GI') == test_wrapper['G']).all()
72     assert (test_wrapper.evaluate_expression('IG') == test_wrapper['G']).all()
73
74     assert (test_wrapper.evaluate_expression('EID') == test_wrapper['E'] @ test_wrapper['D']).all()
75     assert (test_wrapper.evaluate_expression('IED') == test_wrapper['E'] @ test_wrapper['D']).all()
76     assert (test_wrapper.evaluate_expression('EDI') == test_wrapper['E'] @ test_wrapper['D']).all()
77     assert (test_wrapper.evaluate_expression('IEIDI') == test_wrapper['E'] @ test_wrapper['D']).all()
78     assert (test_wrapper.evaluate_expression('EI^3D') == test_wrapper['E'] @ test_wrapper['D']).all()
79
80     assert test_wrapper == get_test_wrapper()
81
82
83 def test_simple_three_matrix_multiplication(test_wrapper: MatrixWrapper) -> None:
84     """Test simple multiplication of two matrices."""
85     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
86           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
87           test_wrapper['G'] is not None
88
89     assert (test_wrapper.evaluate_expression('ABC') == test_wrapper['A'] @ test_wrapper['B'] @
90           ↪ test_wrapper['C']).all()
91     assert (test_wrapper.evaluate_expression('ACB') == test_wrapper['A'] @ test_wrapper['C'] @
92           ↪ test_wrapper['B']).all()
93     assert (test_wrapper.evaluate_expression('BAC') == test_wrapper['B'] @ test_wrapper['A'] @
94           ↪ test_wrapper['C']).all()
95     assert (test_wrapper.evaluate_expression('EFG') == test_wrapper['E'] @ test_wrapper['F'] @
96           ↪ test_wrapper['G']).all()
97     assert (test_wrapper.evaluate_expression('DAC') == test_wrapper['D'] @ test_wrapper['A'] @
98           ↪ test_wrapper['C']).all()
99     assert (test_wrapper.evaluate_expression('GAE') == test_wrapper['G'] @ test_wrapper['A'] @
100           ↪ test_wrapper['E']).all()
101     assert (test_wrapper.evaluate_expression('FAG') == test_wrapper['F'] @ test_wrapper['A'] @
102           ↪ test_wrapper['G']).all()
103     assert (test_wrapper.evaluate_expression('GAF') == test_wrapper['G'] @ test_wrapper['A'] @
104           ↪ test_wrapper['F']).all()
105
106     assert test_wrapper == get_test_wrapper()
107
108
109 def test_matrix_inverses(test_wrapper: MatrixWrapper) -> None:
110     """Test the inverses of single matrices."""
111     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
112           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
113           test_wrapper['G'] is not None
114
115     assert (test_wrapper.evaluate_expression('A^{-1}') == la.inv(test_wrapper['A'])).all()
116     assert (test_wrapper.evaluate_expression('B^{-1}') == la.inv(test_wrapper['B'])).all()
117     assert (test_wrapper.evaluate_expression('C^{-1}') == la.inv(test_wrapper['C'])).all()
118     assert (test_wrapper.evaluate_expression('D^{-1}') == la.inv(test_wrapper['D'])).all()
119     assert (test_wrapper.evaluate_expression('E^{-1}') == la.inv(test_wrapper['E'])).all()
120     assert (test_wrapper.evaluate_expression('F^{-1}') == la.inv(test_wrapper['F'])).all()
121     assert (test_wrapper.evaluate_expression('G^{-1}') == la.inv(test_wrapper['G'])).all()
122
123     assert (test_wrapper.evaluate_expression('A^{-1}') == la.inv(test_wrapper['A'])).all()
124     assert (test_wrapper.evaluate_expression('B^{-1}') == la.inv(test_wrapper['B'])).all()
125     assert (test_wrapper.evaluate_expression('C^{-1}') == la.inv(test_wrapper['C'])).all()
126     assert (test_wrapper.evaluate_expression('D^{-1}') == la.inv(test_wrapper['D'])).all()
127     assert (test_wrapper.evaluate_expression('E^{-1}') == la.inv(test_wrapper['E'])).all()
128     assert (test_wrapper.evaluate_expression('F^{-1}') == la.inv(test_wrapper['F'])).all()
129     assert (test_wrapper.evaluate_expression('G^{-1}') == la.inv(test_wrapper['G'])).all()
130
131     assert test_wrapper == get_test_wrapper()
132
133
134 def test_matrix_powers(test_wrapper: MatrixWrapper) -> None:
135     """Test that matrices can be raised to integer powers."""

```

```

128     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
129           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
130           test_wrapper['G'] is not None
131
132     assert (test_wrapper.evaluate_expression('A^2') == la.matrix_power(test_wrapper['A'], 2)).all()
133     assert (test_wrapper.evaluate_expression('B^4') == la.matrix_power(test_wrapper['B'], 4)).all()
134     assert (test_wrapper.evaluate_expression('C^{12}') == la.matrix_power(test_wrapper['C'], 12)).all()
135     assert (test_wrapper.evaluate_expression('D^{12}') == la.matrix_power(test_wrapper['D'], 12)).all()
136     assert (test_wrapper.evaluate_expression('E^8') == la.matrix_power(test_wrapper['E'], 8)).all()
137     assert (test_wrapper.evaluate_expression('F^{-6}') == la.matrix_power(test_wrapper['F'], -6)).all()
138     assert (test_wrapper.evaluate_expression('G^{-2}') == la.matrix_power(test_wrapper['G'], -2)).all()
139
140     assert test_wrapper == get_test_wrapper()
141
142
143 def test_matrix_transpose(test_wrapper: MatrixWrapper) -> None:
144     """Test matrix transpositions."""
145     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
146           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
147           test_wrapper['G'] is not None
148
149     assert (test_wrapper.evaluate_expression('A^{T}') == test_wrapper['A'].T).all()
150     assert (test_wrapper.evaluate_expression('B^{T}') == test_wrapper['B'].T).all()
151     assert (test_wrapper.evaluate_expression('C^{T}') == test_wrapper['C'].T).all()
152     assert (test_wrapper.evaluate_expression('D^{T}') == test_wrapper['D'].T).all()
153     assert (test_wrapper.evaluate_expression('E^{T}') == test_wrapper['E'].T).all()
154     assert (test_wrapper.evaluate_expression('F^{T}') == test_wrapper['F'].T).all()
155     assert (test_wrapper.evaluate_expression('G^{T}') == test_wrapper['G'].T).all()
156
157     assert (test_wrapper.evaluate_expression('A^T') == test_wrapper['A'].T).all()
158     assert (test_wrapper.evaluate_expression('B^T') == test_wrapper['B'].T).all()
159     assert (test_wrapper.evaluate_expression('C^T') == test_wrapper['C'].T).all()
160     assert (test_wrapper.evaluate_expression('D^T') == test_wrapper['D'].T).all()
161     assert (test_wrapper.evaluate_expression('E^T') == test_wrapper['E'].T).all()
162     assert (test_wrapper.evaluate_expression('F^T') == test_wrapper['F'].T).all()
163     assert (test_wrapper.evaluate_expression('G^T') == test_wrapper['G'].T).all()
164
165     assert test_wrapper == get_test_wrapper()
166
167
168 def test_rotation_matrices(test_wrapper: MatrixWrapper) -> None:
169     """Test that 'rot(angle)' can be used in an expression."""
170     assert (test_wrapper.evaluate_expression('rot(90)') == create_rotation_matrix(90)).all()
171     assert (test_wrapper.evaluate_expression('rot(180)') == create_rotation_matrix(180)).all()
172     assert (test_wrapper.evaluate_expression('rot(270)') == create_rotation_matrix(270)).all()
173     assert (test_wrapper.evaluate_expression('rot(360)') == create_rotation_matrix(360)).all()
174     assert (test_wrapper.evaluate_expression('rot(45)') == create_rotation_matrix(45)).all()
175     assert (test_wrapper.evaluate_expression('rot(30)') == create_rotation_matrix(30)).all()
176
177     assert (test_wrapper.evaluate_expression('rot(13.43)') == create_rotation_matrix(13.43)).all()
178     assert (test_wrapper.evaluate_expression('rot(49.4)') == create_rotation_matrix(49.4)).all()
179     assert (test_wrapper.evaluate_expression('rot(-123.456)') == create_rotation_matrix(-123.456)).all()
180     assert (test_wrapper.evaluate_expression('rot(963.245)') == create_rotation_matrix(963.245)).all()
181     assert (test_wrapper.evaluate_expression('rot(-235.24)') == create_rotation_matrix(-235.24)).all()
182
183     assert test_wrapper == get_test_wrapper()
184
185
186 def test_multiplication_and_addition(test_wrapper: MatrixWrapper) -> None:
187     """Test multiplication and addition of matrices together."""
188     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
189           test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
190           test_wrapper['G'] is not None
191
192     assert (test_wrapper.evaluate_expression('AB+C') ==
193           test_wrapper['A'] @ test_wrapper['B'] + test_wrapper['C']).all()
194     assert (test_wrapper.evaluate_expression('DE-D') ==
195           test_wrapper['D'] @ test_wrapper['E'] - test_wrapper['D']).all()
196     assert (test_wrapper.evaluate_expression('FD+AB') ==
197           test_wrapper['F'] @ test_wrapper['D'] + test_wrapper['A'] @ test_wrapper['B']).all()
198     assert (test_wrapper.evaluate_expression('BA-DE') ==
199           test_wrapper['B'] @ test_wrapper['A'] - test_wrapper['D'] @ test_wrapper['E']).all()
200

```

```

201     assert (test_wrapper.evaluate_expression('2AB+3C') ==
202             (2 * test_wrapper['A']) @ test_wrapper['B'] + (3 * test_wrapper['C'])).all()
203     assert (test_wrapper.evaluate_expression('4D7.9E-1.2A') ==
204             (4 * test_wrapper['D']) @ (7.9 * test_wrapper['E']) - (1.2 * test_wrapper['A'])).all()
205
206     assert test_wrapper == get_test_wrapper()
207
208
209 def test_complicated_expressions(test_wrapper: MatrixWrapper) -> None:
210     """Test evaluation of complicated expressions."""
211     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
212            test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
213            test_wrapper['G'] is not None
214
215     assert (test_wrapper.evaluate_expression('-3.2A^T 4B^{-1} 6C^{-1} + 8.1D^{2} 3.2E^4') ==
216             (-3.2 * test_wrapper['A'].T) @ (4 * la.inv(test_wrapper['B'])) @ (6 * la.inv(test_wrapper['C']))
217             + (8.1 * la.matrix_power(test_wrapper['D'], 2)) @ (3.2 * la.matrix_power(test_wrapper['E'], 4))).all()
218
219     assert (test_wrapper.evaluate_expression('53.6D^{2} 3B^T - 4.9F^{2} 2D + A^3 B^{-1}') ==
220             (53.6 * la.matrix_power(test_wrapper['D'], 2)) @ (3 * test_wrapper['B'].T)
221             - (4.9 * la.matrix_power(test_wrapper['F'], 2)) @ (2 * test_wrapper['D'])
222             + la.matrix_power(test_wrapper['A'], 3) @ la.inv(test_wrapper['B'])).all()
223
224     assert test_wrapper == get_test_wrapper()
225
226
227 def test_parenthesized_expressions(test_wrapper: MatrixWrapper) -> None:
228     """Test evaluation of parenthesized expressions."""
229     assert test_wrapper['A'] is not None and test_wrapper['B'] is not None and test_wrapper['C'] is not None and \
230            test_wrapper['D'] is not None and test_wrapper['E'] is not None and test_wrapper['F'] is not None and \
231            test_wrapper['G'] is not None
232
233     assert (test_wrapper.evaluate_expression('(A^T)^2') == la.matrix_power(test_wrapper['A'].T, 2)).all()
234     assert (test_wrapper.evaluate_expression('(B^T)^3') == la.matrix_power(test_wrapper['B'].T, 3)).all()
235     assert (test_wrapper.evaluate_expression('(C^T)^4') == la.matrix_power(test_wrapper['C'].T, 4)).all()
236     assert (test_wrapper.evaluate_expression('(D^T)^5') == la.matrix_power(test_wrapper['D'].T, 5)).all()
237     assert (test_wrapper.evaluate_expression('(E^T)^6') == la.matrix_power(test_wrapper['E'].T, 6)).all()
238     assert (test_wrapper.evaluate_expression('(F^T)^7') == la.matrix_power(test_wrapper['F'].T, 7)).all()
239     assert (test_wrapper.evaluate_expression('(G^T)^8') == la.matrix_power(test_wrapper['G'].T, 8)).all()
240
241     assert (test_wrapper.evaluate_expression('(rot(45)^1)^T') == create_rotation_matrix(45).T).all()
242     assert (test_wrapper.evaluate_expression('(rot(45)^2)^T') == la.matrix_power(create_rotation_matrix(45),
243     ↪ 2).T).all()
244     assert (test_wrapper.evaluate_expression('(rot(45)^3)^T') == la.matrix_power(create_rotation_matrix(45),
245     ↪ 3).T).all()
246     assert (test_wrapper.evaluate_expression('(rot(45)^4)^T') == la.matrix_power(create_rotation_matrix(45),
247     ↪ 4).T).all()
248     assert (test_wrapper.evaluate_expression('(rot(45)^5)^T') == la.matrix_power(create_rotation_matrix(45),
249     ↪ 5).T).all()
250
251     assert (test_wrapper.evaluate_expression('D^3(A+6.2F-0.397G^TE)^{-2+A}') ==
252             la.matrix_power(test_wrapper['D'], 3) @ la.matrix_power(
253                 test_wrapper['A'] + 6.2 * test_wrapper['F'] - 0.397 * test_wrapper['G'].T @ test_wrapper['E'],
254                 -2
255             ) + test_wrapper['A']).all()
256
257     assert (test_wrapper.evaluate_expression('-1.2F^{3}4.9D^T(A^2(B+3E^TF)^{-1})^2') ==
258             -1.2 * la.matrix_power(test_wrapper['F'], 3) @ (4.9 * test_wrapper['D'].T) @
259             la.matrix_power(
260                 la.matrix_power(test_wrapper['A'], 2) @ la.matrix_power(
261                     test_wrapper['B'] + 3 * test_wrapper['E'].T @ test_wrapper['F'],
262                     -1
263                 ),
264                 2
265             )).all()
266
267 def test_value_errors(test_wrapper: MatrixWrapper) -> None:
268     """Test that evaluate_expression() raises a ValueError for any malformed input."""
269     invalid_expressions = ['', '+', '-', 'This is not a valid expression', '3+4',
270                            'A+2', 'A^', '^2', 'A^-', 'At', 'A^t', '3^2']
271
272     for expression in invalid_expressions:

```

```
270         with pytest.raises(ValueError):
271             test_wrapper.evaluate_expression(expression)
272
273
274 def test_linalgerror() -> None:
275     """Test that certain expressions raise np.linalg.LinAlgError."""
276     matrix_a: MatrixType = np.array([
277         [0, 0],
278         [0, 0]
279     ])
280
281     matrix_b: MatrixType = np.array([
282         [1, 2],
283         [1, 2]
284     ])
285
286     wrapper = MatrixWrapper()
287     wrapper['A'] = matrix_a
288     wrapper['B'] = matrix_b
289
290     assert (wrapper.evaluate_expression('A') == matrix_a).all()
291     assert (wrapper.evaluate_expression('B') == matrix_b).all()
292
293     with pytest.raises(np.linalg.LinAlgError):
294         wrapper.evaluate_expression('A~-1')
295
296     with pytest.raises(np.linalg.LinAlgError):
297         wrapper.evaluate_expression('B~-1')
298
299     assert (wrapper['A'] == matrix_a).all()
300     assert (wrapper['B'] == matrix_b).all()
```