MORE ABOUT CLASSES

Bùi Tiến Lên

01/01/2020



Contents



- 1. Constructors
- 2. Destructor
- 3. Member Initialization
- 4. Copy Constructor
- 5. Static Members
- 6. Friends of Classes
- 7. Workshop

Destruct

Member

Сору

Static Memb


Friends

Workshop

Object Life Cycle









Constructor

Activities

Destructor



Concept 1

A constructor is a special member function that is automatically called when a class object is created.

• Remember that when we define a local variable (primary data type) in C++, the memory is not automatically initialized.

Constructor.

- It is **automatically** invoked when a new object is created.
- There is no returned value, even a void.
- A class can have more than one constructor (overload)
- Name of the constructors must be the same as the class name.

Declaring and Implementing a Constructor



```
class Human {
public:
  Human() {
    // constructor code here
    Name = "Le Thi Dep";
    DateOfBirth = "01/01/1990";
    PlaceOfBirth = "Ha noi":
    Gender = "female";
};
```

Destructo

Member Initializatio

Copy Constructor

C. .. 14

_ . .

Classes

Worksho

When and How to Use Constructors



 A constructor is a perfect place for us to initialize class member variables such as integers, pointers, and so on to known initial values

```
#include <iostream>
#include <string>
using namespace std;
class Human {
private:
   // Private member data:
   string Name;
   int Age;
public:
   // constructor
   Human() {
      Age = 0;
```

Destruc

Member

Сору

Static Memb

Friends

Worksho

When and How to Use Constructors (cont.)



```
void SetName (string HumansName) {
      Name = HumansName;
   void SetAge(int HumansAge) {
      Age = HumansAge;
   void IntroduceSelf() {
      cout << "I am " + Name << " and am ":
      cout << Age << " years old" << endl;</pre>
};
int main() {
   Human FirstMan:
   FirstMan.SetName("Adam"):
   FirstMan.SetAge(30);
   Human FirstWoman;
   FirstWoman.SetName("Eve");
```

Destruct

Member

Initializatio

Static Mamba

Ocacio inicina

Classes

vvorksnoj

When and How to Use Constructors (cont.)



```
FirstWoman.SetAge (28);
FirstMan.IntroduceSelf();
FirstWoman.IntroduceSelf();
}
```

Destructo

Member Initializatio

Сору

Static Member

Friends

Worksho

Overloading Constructors



- Default constructor (if no constructor is implemented, the compiler will issue
 a default constructor; if there is at least one constructor, the default
 constructor will not be created by the compiler)
 - No parameters
 - Invoke other default constructors of data members if they are objects.
 - Doesn't initialize other data members if they are not objects.
- Constructor with no parameters
- Constructor with parameter(s)
- Constructor with default parameter(s)
- Copy constructor

Example



• As constructors can be overloaded just like functions, we can create a constructor that requires Human to be created with a name as a parameter, for instance:

```
class Human {
public:
   Human() {
       // default constructor code here
   Human(string HumansName) {
       // overloaded constructor code here
};
Human firstMan:
Human firstWoman("Eve");
```

Class Without a Default Constructor



```
class CDate
public:
  CDate(int day, int month, int year)
  . . .
private:
  . . .
};
```

```
int main() {
  CDate today; // compile error
  . . .
  return 0;
```

Advice: always define our own default constructor!

Destructo

Member Initializatio

Constructor

Static Membe

.....

Friends Classes

Workshop

this Pointer



Concept 2

this is a reserved keyword applicable within the scope of a class that contains the address of the object. In other words, the value of this is &object

• this is a constant pointer, we cannot modify it within a member function.

```
class Human {
    ...
    void SetAge(int HumansAge) {
        this->Age = HumansAge; // same as Age = HumansAge
    }
    ...
}
```

Destruct

Member Initializatio

Copy

Static ivie

Friends Classes

Workshop

sizeof() a Class



Concept 3

The operator sizeof() is valid for classes and basically reports the sum of bytes consumed by each data attribute contained within the class declaration.

Depending on the compiler we use, sizeof() might or might not include padding for certain attributes on word boundaries.

```
int main() {
  Human Tom;
  cout << "sizeof(Human) = " << sizeof(Human) << endl;
  cout << "sizeof(Tom) = " << sizeof(Tom) << endl;
}</pre>
```

Destructor



Destructor

Concept 4

A destructor is a member function that is automatically called when an object is destroyed.

- Destructor is always invoked when an object of a class goes out of scope or is deleted via delete and is destroyed
- Each class can have at most one destructor.
- The destructor name is the name of a class preceded by a tilde sign (~)
- Destructor has no return type (even void)
- Destructor frees the resources used by the object (allocated memory, file descriptors, semaphores etc.)

Static Member

Friends of

Workshop

Example



• Destructor for Human class

```
class Human {
public:
   ~Human() {
      // destructor code here
   }
};
```

When and How to Use Destructors

 Destructor is the ideal place to reset variables and release dynamically allocated memory and other resources.

```
#include <iostream>
using namespace std:
class MyString {
private:
   char* Buffer;
public:
   // Constructor
   MyString(const char* InitialInput) {
      if(InitialInput != NULL) {
         Buffer = new char [strlen(InitialInput) + 1];
         strcpy(Buffer, InitialInput);
```

Destructor

When and How to Use Destructors (cont.)



```
else
         Buffer = NULL:
      Destructor: clears the buffer allocated in constructor
   ~MyString() {
      cout << "Invoking destructor, clearing up" << endl;</pre>
      if (Buffer != NULL)
         delete [] Buffer;
   int GetLength() {
      return strlen(Buffer);
   const char* GetString() {
    return Buffer;
}; // end of class MyString
int main() {
```

Destructor

When and How to Use Destructors (cont.)



```
MyString SayHello("Hello from String Class");
cout << "String buffer in MyString is " << SayHello.GetLength();</pre>
cout << " characters long" << endl;</pre>
cout << "Buffer contains: ";</pre>
cout << "Buffer contains: " << SayHello.GetString() << endl;</pre>
```

Member Initialization



Initialization vs. Assignment



• Distinguish between **Assignment** and **Initialization**

Initialization	Assignment
int a = 2;	a = 3;
double b(4.0);	a = 4;
	b = 2.0;
	a = 3; a = 4; b = 2.0; b = 1.0;

Members Initialization



This is members initialization

```
class CDate {
private:
  int m iDay, m_iMonth, m_iYear;
public:
  CDate():
  CDate(int day, int month, int year):
    m_iDay(day), m_iMonth(month), m_iYear(year)
  {}
  ~CDate():
  . . .
};
```

Classes

Worksho

Mandatory Members Initialization



- References
- Pointers
- Const members
- Sub-objects which require arguments in constructors

```
class Human {
private:
  Ancestor& ref: // reference member
 Descendant* ptr; // pointer member
 const int MAX: // const member
 vector arr; // object member
public:
 Human(Ancestor& r, Descendant *p) :
   ref(r), ptr(p), MAX(100), arr(MAX) {}
};
```



Static Mamb

Friends Classes

Workshop

Copy constructor



Concept 5

A **copy constructor** is a special constructor that is called whenever a new object is created and initialized with another object's data.

- Default copy constructor: if there is no copy constructor, a default copy constructor will be generated. Default copy constructor performs a bitwise copy from the source to the current object (shallow copy).
- Our own copy constructor

Static Member

Friends Classes

Worksho

```
When copies of objects are made
```



• A variable is declared which is initialized from another object

```
Person p("Mickey"); // constructor
Person r(p); // copy constructor
Person q = p; // copy constructor
p = r; // assignment operator
```

• A value parameter is initialized from its corresponding argument.

```
doSomething(p); // copy constructor
```

An object is returned by a function.

```
return p; // copy constructor
```

Friends (

Worksho

Shallow Copying and Associated Problems



 When an object of the class MyString is copied, the pointer member is copied, but not the pointed buffer, resulting in two objects pointing to the same dynamically allocated buffer in memory.

```
void UseMyString(MyString Input) {
  cout << "String buffer in MyString is " <<Input.GetLength();</pre>
  cout << " characters long" << endl;</pre>
  cout << "Buffer contains: " << Input.GetString() << endl;</pre>
int main() {
  MyString SayHello("Hello from String Class");
  // Pass SayHello as a parameter to the function
  UseMyString(SayHello);
  return 0;
```

2001.4000

Member Initialization

Copy Constructor


Static Members

Friends of Classes

Workshop

Shallow Copying and Associated Problems (cont.)





Initializati Copy

Constructor

Friends o

Worksho

Deep Copy Using a Copy Constructor




• C++ requires that a copy constructor's parameter be a reference object.

```
class MyString {
   // Copy constructor
   MyString(const MyString& CopySource) {
      if(CopySource.Buffer != NULL) {
         // ensure deep copy by first allocating own buffer
         Buffer = new char [strlen(CopySource.Buffer) + 1];
         // copy from the source into local buffer
         strcpy(Buffer, CopySource.Buffer);
      else
         Buffer = NULL:
   . . .
```

Сору Constructor

Deep Copy Using a Copy Constructor (cont.)








Instance and Static Members



Concept 6

Each instance of a class has its own copies of the class's instance variables.

- If a member variable is declared static, however, all instances of that class have access to that variable.
- If a member function is declared static, it may be called without any instances of the class being defined.



Static Member Variables




Syntax

static DataType VariableName;

 Even though static member variables are declared in a class, they are actually defined outside the class declaration. The lifetime of a class's static member variable is the lifetime of the program. This means that a class's static member variables come into existence before any instances of the class are created







```
Member
Initialization
```

Static Member

Friends of Classes

Worksho

```
#include <iostream>
using namespace std;
class Tree {
private:
   static int objectCount; // Static member variable.
public:
   // Constructor
   Tree() { objectCount++; }
   // Accessor function for objectCount
   int getObjectCount() const { return objectCount; }
};
// Definition written outside the class.
int Tree::objectCount = 0;
int main() {
   Tree oak, elm, pine;
   cout << "We have " << pine.getObjectCount()</pre>
        << " trees in our program!\n";
   return 0:
```

nstructors

Destructor

Member

Copy


Static Members

Friends (

Workshop

Listing 1 (cont.)





Instances of the Tree class

Static Member Functions



Syntax

static ReturnType FunctionName (ParameterTypeList);

- A function that is a static member of a class cannot access any nonstatic member data in its class.
- A class's static member functions can be called before any instances of the class are created. This means that a class's static member functions can access the class's static member variables before any instances of the class are defined in memory. This gives you the ability to create very specialized setup routines for class objects.

Listing 2



```
#include <iostream>
using namespace std;
class Tree {
private:
   static int objectCount; // Static member variable.
public:
   // Constructor
   Tree() { objectCount++; }
   // Static function for objectCount
   static int getObjectCount() { return objectCount; }
};
// Definition written outside the class.
int Tree::objectCount = 0;
int main() {
   Tree oak, elm, pine;
   cout << "We have " << Tree::getObjectCount()</pre>
        << " trees in our program!\n";
   return 0:
```

Friends of Classes



Destructor

Member Initializatio

Copy Constru

Static Membe

Friends of Classes

Workshop

Friends of Classes



Concept 7

A **friend** is a function or class that is not a member of a class, but has access to the private members of the class

- Friend functions or classes give a flexibility to the class.
- It doesn't violate the encapsulation of the class.
- Friendship is "directional". It means if class A considers class B as its friend, it doesn't mean that class B considers A as a friend

Syntax

friend ReturnType FunctionName (ParameterTypeList)
friend class ClassName

Constructors

Destruct

Member

Copy Construct


Static Memb

Friends of Classes

VVorkshop

UML





Listing 3

```
Member
Initialization
Copy
```

Static Member

Friends of Classes

```
class Human {
private:
   string Name;
   int Age;
   friend void DisplayAge(const Human& Person);
public:
   Human(string InputName, int InputAge) {
      Name = InputName;
      Age = InputAge;
};
void DisplayAge(const Human& Person) {
   cout << Person.Age << endl;</pre>
int main() {
   Human FirstMan("Adam", 25);
   DisplayAge(FirstMan);
   return 0:
```



onstructors

Destru

Quiz

Member

Сору


Static Mem

Friends o Classes

Ι.	what is the this pointer!	
2.	When I create an instance of a class using new, where is the class created?	


Static Member

Friends





3.	My class has a raw pointer int* that contains a dynamically allocated array of integers. Does sizeof report different sizes depending on the number of integers in the dynamic array?
4.	All my class members are private, and my class does not contain any declared friend class or function. Who can access these members?





5. Can one class member method invoke another?
6. What is a constructor good for?
7. What is a destructor good for?

Static Mon

Friends

Classes

Workshop

Exercises

- Programming Challenges of chapter 13 [Gaddis, 2014]
 - 3. Car Class
 - 5. Retailltem Class
- Programming Challenges of chapter 14 [Gaddis, 2014]
 - 1. Numbers Class
 - 2. Day of the Year

References



Deitel, P. (2016).

C++: How to program.

Pearson.



Starting Out with C++ from Control Structures to Objects.

Addison-Wesley Professional, 8th edition.



Jones, B. (2014).

Sams teach yourself C++ in one hour a day.

Sams.