M1 User Access Management Activity Workflow

PDF-friendly swimlane view with technology stack lanes

Step	User / Project Operator	ASP.NET Core Stats Web Razor Pages + JavaScript	Python FastAPI Identity Access API	PostgreSQL stats database
1	Configure first admin email and password.		Load M1 runtime configuration and database URL.	
2	Run the first-admin bootstrap command.		Handle bootstrap request and protect against duplicate bootstrap.	Check whether any user already exists.
3			Create tables through the M1 persistence layer when required.	Store the first active admin with a hashed password.
4	Open /Login and enter credentials.	Render login form and submit login request.	Validate credentials, account status, and password state.	Read user account and password hash.
5	Review login result.	Show controlled error or store bearer token in browser session storage.	Return login error or bearer token.	
6	If required, enter the new password on first login.	Display password setup form and submit password change.	Validate password and update password-change state.	Update password hash and clear required-change flag.
7	Open authenticated landing page.	Request current-user profile and route to the authenticated app.	Validate token and return current user role/status.	
8	If admin, open /Users and enter new user details.	Submit add-user request with bearer token.	Validate admin authorization and user field rules.	
9	Review user creation result.	Show created user or validation/duplicate-user error.	Return creation result or controlled error.	Store new user with hashed temporary password when accepted.
10	If standard user, use authenticated access only.	Do not expose admin-only user management actions.	Reject unauthorized admin endpoints.	
11	Sign out.	Clear browser session token.		

Notes

- This PDF is the page-friendly version of docs/M1-user-management-flow-diagram.md.
- The workflow is aligned to the architecture-hardened structure: Stats Web consumes M1 through API contracts, the Python Identity API owns authentication behavior, and identity records are persisted in the shared PostgreSQL stats database.
- M1 identity data is stored in the shared application database; it is not a separate module-only database.