

sumo logic

1
2
3
4
5
6
7
8
9
10
11
12
13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

id: timeslice-join

title: Timeslice Join Results

sidebar_label: Timeslice Join Results

When you gather data using a [`join`](join.md) operator, you can slice data by time period using the [`timeslice`](timeslice.md) operator.

Syntax

The `timeslice` operator uses the metadata field `__messagetime` to organize the logs by slices. In your query, you need to specify the `timeslice` operator before the `join`, because the `__messagetime` field will no longer exist after the join is performed.

When you add the `timeslice` before the `join`, each of the tables created by the join will include a `__timeslice` field.

You can reference the table's `__timeslice` field to use in your group by operation. The name of the table is appended to the table's fields.

Example

For example, if your table is named `*errors*`, your field would be `errors__timeslice`. (Notice that the name contains two underscores.)

Here's an example query:

```
```sql
```

```
*
```

```
| timeslice 1h
```

```
| join
```

```
(parse "starting stream from * " AS streamId) AS table1,
```

```
(parse "starting search from parent stream * " AS streamId) AS table2
```

```
on table1.streamId = table2.streamId
```

```
| count table1__streamId, table1__timeslice
```

```
| formatDate(fromMillis(table1__timeslice), "MM/dd/yyyy HH:mm:ss z") as timeslice
```

```
```
```