

## Infinite Computations – WS 2015/2016

### Exercises – Series 4

November 13, 2015

#### Exercise 17. (Bachelor)

3 points

Construct a deterministic parity automaton recognizing the  $\omega$ -language

$$L = \{\alpha \in \{a, b, c\}^\omega \mid c \text{ occurs infinitely often in } \alpha \Leftrightarrow a \text{ occurs at least once in } \alpha\}.$$

#### Exercise 18. (Bachelor + Master)

4 points


Let  $\mathcal{A}$  be a nondeterministic parity automaton with  $n$  states. Present (in a formal way) an equivalent nondeterministic Büchi automaton  $\mathcal{B}$  with  $\mathcal{O}(k \cdot n)$  states. Briefly justify the correctness of your construction.

*Hint:* Recall the translation from Muller to Büchi automata.

#### Exercise 19. (Bachelor + Master)

6+1 points

Reconsider the nondeterministic Büchi automaton  $\mathcal{A}$  shown in the lecture:



- Draw the sequence of Safra trees for the input  $cacbc$ .
- Use the sequence obtained in (a) to argue why or why not the input  $cac(bc)^\omega$  is accepted by the deterministic Muller automaton that results from the Safra construction.

#### Exercise 20. (Master)

1+3 points

An *elementary Rabin automaton* has an acceptance component  $\Omega = ((E_1, F_1), \dots, (E_k, F_k))$  where each  $F_i$  is a singleton (i.e., a set with exactly one element). Similarly, an *elementary Muller automaton* has an acceptance component  $\mathcal{F} = \{F_1, \dots, F_k\}$  where each  $F_i$  is a singleton. (Note: This does *not* mean that  $|\mathcal{F}| = 1$ .) Prove the following statements:

- Every Rabin automaton can be simulated by an elementary Rabin automaton.
- There is a Muller automaton that cannot be simulated by any elementary Muller automaton.

Please always consider announcements made in the L<sup>2</sup>P course room.

You can hand in your solutions until **12:15 on Friday, November 20, 2015** at the drop box at the Chair i7.