1. Safety Precautions

1-1. Repair Precaution

Before attempting any repair or detailed tuning, shield the device from RF noise or static electricity discharges.

Use only demagnetized tools that are specifically designed for small electronic repairs, as most electronic parts are sensitive to electromagnetic forces.

Use only high quality screwdrivers when servicing products. Low quality screwdrivers can easily damage the heads of screws.

Use only conductor wire of the properly gauge and insulation for low resistance, because of the low margin of error of most testing equipment.
We recommend 22-gauge twisted copper wire.

Hand-soldering is not recommended, because printed circuit boards (PCBs) can be easily damaged, even with relatively low heat. Never use a soldering iron with a power rating of more than 100 watts and use only lead-free solder with a melting point below 250°C (482°F).

Prior to disassembling the battery charger for repair, ensure that the AC power is disconnected.
Always use the replacement parts that are registered in the SEC system. Third-party replacement parts may not function properly.

1. Safety Precautions

1-2. ESD(Electrostatically Sensitive Devices) Precaution

Many semiconductors and ESDs in electronic devices are particularly sensitive to static discharge and can be easily damaged by it. We recommend protecting these components with conductive anti-static bags when you store or transport them.

Always use an anti-static strap or wristband and remove electrostatic buildup or dissipate static electricity from your body before repairing ESDs.

Ensure that soldering irons have AC adapter with ground wires and that the ground wires are properly connected.

Use only desoldering tools with plastic tips to prevent static discharge.

Properly shield the work environment from accidental electrostatic discharge before opening packages containing ESDs.

The potential for static electricity discharge may be increased in low humidity environments, such as air-conditioned rooms. Increase the airflow to the working area to decrease the chance of accidental static electricity discharges.

2. Specification

2-1. GSM General Specification

Item		GSM 850	EGSM 900	DCS1800	PCS1900
Freq. Band[MHz] Uplink/Downlink		824~849 869~894	880~915 925~960	1710~1785 1805~1880	1850~1910 1930~1990
ARFCN range		128~251	0~124 & 975~1023	512~885	512~810
Tx/Rx spacing		45MHz	45MHz	95MHz	80MHz
Mod. Bit rate/ Bit Period		270.833kbps 3.692us	270.833kbps 3.692us	270.833kbps 3.692us	270.833kbps 3.692us
Time Slot Period/ Frame Period		576.9us 4.615ms	576.9us 4.615ms	576.9us 4.615ms	576.9us 4.615ms
Modulation	GSM/ EGPRS	GMSK/ 8PSK	GMSK/ 8PSK	GMSK/ 8PSK	GMSK/ 8PSK
MS Power		33dBm~5dBm	33dBm~5dBm	30dBm~0dBm	30dBm~0dBm
Power Class		4(GMSK) E2(8PSK)	4(GMSK) E2(8PSK)	1(GMSK) E2(8PSK)	1(GMSK) E2(8PSK)
Sensitivity		-102dBm	-102dBm	-100dBm	-100dBm
TDMA Mux		8	8	8	8

2. Specification

2-2. GSM Tx Power Class

TX Power control level	GSM850	TX Power control level	EGSM900	TX Power control level	DCS1800	TX Power control level	PCS1900
5	33±2 dBm	5	33±2 dBm	0	30±3 dBm	0	30±3 dBm
6	31±2 dBm	6	31±2 dBm	1	28±3 dBm	1	28±3 dBm
7	29±2 dBm	7	29±2 dBm	2	26±3 dBm	2	26±3 dBm
8	27±2 dBm	8	27±2 dBm	3	24±3 dBm	3	24±3 dBm
9	25±2 dBm	9	25±2 dBm	4	22±3 dBm	4	22±3 dBm
10	23±2 dBm	10	23±2 dBm	5	20±3 dBm	5	20±3 dBm
11	21±2 dBm	11	21±2 dBm	6	18±3 dBm	6	18±3 dBm
12	19±2 dBm	12	19±2 dBm	7	16±3 dBm	7	16±3 dBm
13	17±2 dBm	13	17±2 dBm	8	14±3 dBm	8	14±3 dBm
14	15±2 dBm	14	15±2 dBm	9	12±4 dBm	9	12±4 dBm
15	13±2 dBm	15	13±2 dBm	10	10±4 dBm	10	10±4 dBm
16	11±3 dBm	16	11±3 dBm	11	8±4 dBm	11	8±4 dBm
17	9±3 dBm	17	9±3 dBm	12	6±4 dBm	12	6±4 dBm
18	7±3 dBm	18	7±3 dBm	13	4±4 dBm	13	4±4 dBm
19	5±3 dBm	19	5±3 dBm	14	2±5 dBm	14	2±5 dBm
-	-	-	-	15	0±5 dBm	15	0±5 dBm

2. Specification

2-3-1. WCDMA General Specification[SM-A505F/FN/FM]

Item	WCDMA2100(B1)	WCDMA1900(B2)	WCDMA850(B5)	WCDMA900(B8)
Freq. Band[MHz] Uplink/Downlink	1920~1980 2110~2170	1850~1910 1930~1990	824~849 869~894	880~915 925~960
ARFCN range	UL：9612~9888 DL：10562~10838	UL：9262~9538 DL：9662~9938	UL：4132~4233 DL：4357~4458	UL：2712~2868 DL：2937~3088
Tx/Rx spacing	190MHz	80MHz	45MHz	45MHz
Mod. Bit rate/ Bit Period	42.2Mbps(DL) 5.42Mbps(UL)	42.2Mbps(DL) 5.42Mbps(UL)	42.2Mbps(DL) 5.42Mbps(UL)	42.2Mbps(DL) 5.42Mbps(UL)
Time Slot Period/ Frame Period	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms
Modulation	QPSK 16QAM 64QAM	QPSK 16QAM 64QAM	QPSK 16QAM 64QAM	QPSK 16QAM 64QAM
MS Power (dBm)	25.7 ~ -49(↓)	25.7 ~ -49(↓)	25.7 ~ -49(↓)	25.7 ~ -49(↓)
Power Class	3(max+24dBm)	3(max+24dBm)	3(max+24dBm)	3(max+24dBm)
Sensitivity	-106dBm	-104dBm	-104dBm	-103dBm

2. Specification

2-3-2. WCDMA General Specification[SM-A505G/GN/GT]

Item	WCDMA2100(B1)	WCDMA1900(B2)	WCDMA AWS(B4)	WCDMA850(B5)	WCDMA900(B8)
Freq. Band[MHz] Uplink/Downlink	1920~1980 2110~2170	1850~1910 1930~1990	1710~1755 2110~2155	824~849 869~894	880~915 925~960
ARFCN range	UL：9612~9888 DL：10562~10838	UL：9262~9538 DL：9662~9938	UL：1312~1513 DL：1537~1738	UL：4132~4233 DL：4357~4458	UL：2712~2868 DL：2937~3088
Tx/Rx spacing	190MHz	80MHz	400MHz	45MHz	45MHz
Mod. Bit rate/ Bit Period	42.2Mbps(DL) 5.42Mbps(UL)	42.2Mbps(DL) 5.42Mbps(UL)	42.2Mbps(DL) 5.42Mbps(UL)	42.2Mbps(DL) 5.42Mbps(UL)	42.2Mbps(DL) 5.42Mbps(UL)
Time Slot Period/ Frame Period	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms	WCDMA 10ms/0.667ms HSPA 2ms/0.667ms
Modulation	QPSK 16QAM 64QAM	QPSK 16QAM 64QAM	QPSK 16QAM 64QAM	QPSK 16QAM 64QAM	QPSK 16QAM 64QAM
MS Power (dBm)	25.7 ~ -49(↓)	25.7 ~ -49(↓)	25.7 ~ -49(↓)	25.7 ~ -49(↓)	25.7 ~ -49(↓)
Power Class	3(max+24dBm)	3(max+24dBm)	3(max+24dBm)	3(max+24dBm)	3(max+24dBm)
Sensitivity	-106dBm	-104dBm	-106dBm	-104dBm	-103dBm

2. Specification

2-4. LTE General Specification

Item	LTE Band1	LTE Band3	LTE Band5	LTE Band7
Freq. Band[MHz] Uplink/Downlink	1920~1980 2110~2170	1710~1785 1805~1880	824~849 869~894	2500~2570 2620~2690
ARFCN range	UL:18000~18599 DL:0~599	UL:19200~19949 DL:1200~1949	UL:20400~20649 DL:2400~2649	UL:20750~21449 DL:2750~3449
Tx/Rx spacing (MHz)	190	95	45	120
Channel Bandwidth (MHz)	5/10/15/20	1.4/3/5/10/15/20	1.4/3/5/10	5/10/15/20
Modulation	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)
MS Power (dBm)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)
Sensitivity(QPSK, BW 10MHz) (dBm)	-96.3	-93.3	-94.3	-94.3

Item	LTE Band8	LTE Band38	LTE Band40	LTE Band41
Freq. Band[MHz] Uplink/Downlink	880~915 925~960	2570~2620	2300~2400	2496~2690
ARFCN range	UL:21450-21799 DL:3450-3799	UL/DL:37750 ~ 38249	UL/DL:38650 ~ 39649	UL/DL:39650 ~ 41589
Tx/Rx spacing (MHz)	45	0	0	0
Channel Bandwidth (MHz)	1.4/3/5/10	5/10/15/20	5/10/15/20	5/10/15/20
Modulation	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)
MS Power (dBm)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)
Sensitivity(QPSK, BW 10MHz) (dBm)	-93.3	-96.3	-96.3	-94.3

2. Specification

[SM-A505F/FN/FM]

Item	LTE Band20
Freq. Band[MHz] Uplink/Downlink	832~862 791~821
ARFCN range	UL:24150~24449 DL:6150~6449
Tx/Rx spacing (MHz)	-41
Channel Bandwidth (MHz)	5/10/15/20
Modulation	QPSK,16/64QAM 256QAM(DL only)
MS Power (dBm)	25.7~-39(↓)
Sensitivity(QPSK, BW 10MHz) (dBm)	-93.3

2. Specification

[SM-A505G/GN]

Item	LTE Band2	LTE Band4	LTE Band12	LTE Band13
Freq. Band[MHz] Uplink/Downlink	1850~1910 1930~1990	1710~1755 2110~2155	699~716 729~746	777~787 746~756
ARFCN range	UL:18600~19199 DL:600~1199	UL:19950~20399 DL:1950~2399	UL:23010~23179 DL:5010~5179	UL:23180~23279 DL:5180~5279
Tx/Rx spacing (MHz)	80	400	30	-31
Channel Bandwidth (MHz)	1.4/3/5/10/15/20	1.4/3/5/10/15/20	1.4/3/5/10	1.4/3/5/10
Modulation	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)
MS Power (dBm)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)
Sensitivity(QPSK, BW 10MHz)(dBm)	-94.3	-96.3	-93.3	-93.3

Item	LTE Band17	LTE Band28	LTE Band66
Freq. Band[MHz] Uplink/Downlink	704~716 734~746	703~748 758~803	1710~1780 2110~2200
ARFCN range	UL:23730~23849 DL:5730~5849	UL:27210~27659 DL:9210~9659	UL:131972~132671 DL:66436~67335
Tx/Rx spacing (MHz)	30	55	400
Channel Bandwidth (MHz)	5/10	3/5/10/15/20	1.4/3/5/10/15/20
Modulation	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)
MS Power (dBm)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)
Sensitivity (QPSK, BW 10MHz) (dBm)	-93.3	-94.8	-95.8

2. Specification

[SM-A505GT]

Item	LTE Band2	LTE Band4	LTE Band12	LTE Band13
Freq. Band[MHz] Uplink/Downlink	1850~1910 1930~1990	1710~1755 2110~2155	699~716 729~746	777~787 746~756
ARFCN range	UL:18600~19199 DL:600~1199	UL:19950~20399 DL:1950~2399	UL:23010~23179 DL:5010~5179	UL:23180~23279 DL:5180~5279
Tx/Rx spacing (MHz)	80	400	30	-31
Channel Bandwidth (MHz)	1.4/3/5/10/15/20	1.4/3/5/10/15/20	1.4/3/5/10	1.4/3/5/10
Modulation	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)
MS Power (dBm)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)
Sensitivity(QPSK, BW 10MHz)(dBm)	-94.3	-96.3	-93.3	-93.3

Item	LTE Band17	LTE Band20	LTE Band28	LTE Band66
Freq. Band[MHz] Uplink/Downlink	704~716 734~746	832~862 791~821	703~748 758~803	1710~1780 2110~2200
ARFCN range	UL:23730~23849 DL:5730~5849	UL:24150~24449 DL:6150~6449	UL:27210~27659 DL:9210~9659	UL:131972~132671 DL:66436~67335
Tx/Rx spacing (MHz)	30	-41	55	400
Channel Bandwidth (MHz)	5/10	5/10/15/20	3/5/10/15/20	1.4/3/5/10/15/20
Modulation	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)	QPSK,16/64QAM 256QAM(DL only)
MS Power (dBm)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)	25.7~-39(↓)
Sensitivity (QPSK, BW 10MHz) (dBm)	-93.3	-93.3	-94.8	-95.8

3. Product Function

Main Function

Item	Description
OS	Android P OS V9.0
SM-A505F/FN/FM RF	GSM850 / GSM900 / DCS1800 / PCS1900 WCDMA: B1/ B2/ B5/ B8 LTE: B1 / B3 / B5/ B7/ B8/ B20/ B38/ B40/ B41
SM-A505GT RF	GSM850 / GSM900 / DCS1800 / PCS1900 WCDMA: B1/ B2/ B4/ B5/ B8 LTE: B1/ B2/ B3/ B4/ B5/ B7/ B8/ B12/ B13/ B17 / B26 / B28/ B38/ B40/ B41/ B66
SM-A505G/GN RF	GSM850 / GSM900 / DCS1800 / PCS1900 WCDMA: B1/ B2/ B4/ B5/ B8 LTE: B1/ B2/ B3/ B4/ B5/ B7/ B8/ B12/ B13/ B17 B20 /B26/ B28/ B38/ B40/ B41/ B66
Battery	4000mAh
Base Band	2.3Ghz Quad + 1.7GHz Quad
Other RF	GPS, Glonass, Beidou, Galileo / BT5.0 / USB 2.0 / WIFI 802.11 a/b/g/n/ac / NFC
Camera	Triple Camera (25MP(F1.7) + 5MP(F2.2) + 8MP(F2.2)) with LED Flash / Front Camera 25MP(F2.0)
LCD	6.4", FHD+, 2340x1080
SM-A505F(SWA/SEA/MEA) **/FN/G/GT/GN** RAM + ROM	4GB + 64GB
SM-A505F(SWA/SEA/MEA)/GN RAM + ROM	6GB + 64GB
SM-A505F_MEA/FN RAM + ROM	4GB + 128GB
SM-A505F_SEA/FM RAM + ROM	6GB + 128GB
Sensor	Accelerometer, Fingerprint Sensor, Gyro Sensor, Geomagnetic Sensor, Hall Sensor, Proximity Sensor, RGB Light Sensor
Accessory	Charger: 9V/1.67A and 5V/2.0A AFC charging Data cable: 3.0pi, 0.8m(USB-C) Ear phone: 3.5pi, 4pin

6. Level 1 Repair

6-1. S/W Update

6-1-1. Preparation
- S/W Update program : **Fenrir 5.17.xxxx**
- Mobile Phone
- Data Cable

※ **Settings**

Data Cable : GH39-01999A

6. Level 1 Repair

6-1-2. How to use 'Fenrir' S/W update program.

1) Launch Fenrir by clicking on the icon on the desktop

- SVH (Fenrir_Home) : It uses Home binary which does not have user data area in the memory when flashed to a device. (Keep user data)

- SVC (Fenrir_Factory) : It uses Factory binary which erases all user data in the memory when flashed to a device. (Clear user data)
- SVA (Fenrir_All) : It uses Factory and Home binaries. you can download Home and Factory binary in a PC(but requires double HDD storage and NW traffic)

2) Input ID & password
※You need to reset the ID information in case of PC change and format and repair, hard disk change

6. Level 1 Repair

3) Ensure device has sufficient charge (at least 20%) to start firmware update.

4) Connect the device to PC via data cable.

5) Upon USB connection, you will be presented with below screen.

6. Level 1 Repair

=c

6) Once device is detected, you will be presented with below screen. To update S/W, select "S/W Update" or to exit select "SVC Connection". If you select "SVC Connection", only Fenrir connection history (record) will be stored in the FUS server to support warranty validation.   (This is known as "Service Connection" history)

7) Once Fenrir starts, application will display the below screen. And select the Start button & Agree button.

6. Level 1 Repair

8) The status circle increases as the update installs. The update process takes approximately 5-10 minutes to complete. Do not disconnect the device from USB during processing.

9) Once complete, application will present the below screen indicating update complete.
Click Ok and detach device from USB.

6. Level 1 Repair

6-2. How to use 'Odin' program

※ S/W Update via Fenrir is mandatory.
Below is the method to use 'Odin' program in any specific case.

6-2-1. Preparation

- Installation program : **Odin3 v3.13.2.exe or above**
- Mobile Phone
- Data Cable
- S/W Binary files (downloaded from GSPN)

※ Settings

Mobile Phone(with Battery) — Data Cable — PC

Data Cable : GH39-01999A

6. Level 1 Repair

6-2-2. S/W Installation Program (Downloader program)

Open up the S/W Installation Program by executing the **"Odin3 v3.13.2.exe"**

6. Level 1 Repair

1. Enable the check mark by click on the following options

- Check   Auto Reboot, F. Reset Time, Nand Erase

- Check BL, AP, CP, CSC Files

* Note : "Odin v3.13.2 or above" checks MD5 checksum just after file selection.

6. Level 1 Repair

2. Enter into Download Mode
- Enter into Download Mode by pressing Volume Down button, Intelligence button and ON/OFF Button simultaneously followed by pressing Volume up button as a direction of the phone.

VOL UP

VOL DOWN

IF CON

6. Level 1 Repair

3. Connect the device to PC via Data Cable.
Make sure that the one of communication ports [ID:COM] box is highlighted in sky blue.
The device is now connected with the PC and ready to download the binary files in it.

6. Level 1 Repair

4. Start downloading the binary files into the device by clicking Start button on the screen.

The green colored "PASS!" sign will appear on the upper-left box if the binary files have been successfully downloaded into the device.

5. Disconnect the device from the Data cable.

6. Once the device boots up, you can check the version of the binary file or name by pressing the following code in sequence; ***#1234#**

You can perform Factory data Reset by Settings → General Management → Reset

※　**Caution. Never disconnect during the S/W downloading.**

6. Level 1 Repair

6-3. IMEI writing

6-3-1. Preparation

- New IMEI writing Program has been released.
- Supported Model : Models which CAB files are uploaded on HHPsvc INI File category, instead of ini file.
- Refer to below IMEI writing procedure.

**- H/W**

- S/W

① Library Install	To use Daseul, library files should be installed. Refer to SVC Bulletin "(11-82) Daseul (New IMEI writing Program) Library Install guide_rev1.0"
②Launcher	**DASEUL_SVC_Launcher_v3.0.12** or higher -Uploaded on HHPsvc Notice
③ Runtime File	1. **DASEUL_IMEI_ALL_Runtime_3.1.348.0_r00519.CAB** or higher -Uploaded on HHPsvc Notice 2. Make 'SM-M205F' folder at the same position with launcher & Runtime file. DASEUL_IMEI_ALL_Runtime_3.1.348.0_r00519.CAB DASEUL_Launcher_v4.0.0.exe SM-G960F_SS(CSC)_IMEI_Ver_3.1.343.10.CAB
④Model File	Copy Model File under the 'SM-M205F' folder

6. Level 1 Repair

6-3-2. IMEI writing Process

1. Run DASEUL_SVC_Launcher_v3.0.12.exe

DASEUL_SVC_Launcher_v3.0.12.exe

2. Select Service Mode

3. Click [...] and Select folder where the Launcher exists

6. Level 1 Repair

4. Select Model

5. Check IMEI and click System Setting

※Once you setup the setting, you don t have to do it again, unless there is change.
From second run of the IMEI program, check IMEI and click Extract & Run.

6. Level 1 Repair

6. Check IMEI Write / IMEI Check and click IMEI SVC & Repair Option.

7. Check 'SVC , User Ticket No' and click OK

6. Level 1 Repair

8. Click 'Hardware Config'

9. Click 'Port Setting'

6. Level 1 Repair

10. Select Port Number and SAVE

Set IO BUS Configuration

Phone IO Bus Setting

Common

BaudRate	115200
Data Bit	8
Parity	No
Stop Bit	1

No	Port #1
1	1

SAVE

Cancel

11. Click OK to proceed

Set System Configuration
Set System Configuration Dialog...

Test Process

[Process]	[Master]	[Slave]
SMD F/T	☐	☐
PBA F/T	☐	☐
Calibration	☐	☐
Final Auto	☐	☐
Final Manual	☐	☐

IMEI Process

IMEI Write	☑	☐
IMEI Check	☑	☐
MDL +2nd Check	☐	☐
MDL Rework	☐	☐
IMEI Read	☐	☐

WLAN	☐
Power Off-On before WLAN	☐
Bluetooth	☐

Test Condition

Calibration
Real CAL Cycle: on every [20] default CALs
Calibration Mode : Dynamic

Final
Supply RF Signal by [Conduction]

Test Signal Mode : Signaling
Developer Mode ☐

IMEI
Use RFSM ☐
Use Second PC ☐
Save ODS ☐

IMEI SVC&Repair Option

System Config.

Language	English
Line Name	LINE(temp)
Line Type	Block Cell
# of Phone	1
Start Number of Jig	1
IP Address	10.244.114.62

Operation Condition

Operation Condition

Model Information

Hardware Config

OK

6. Level 1 Repair

12. Click Model Info and OK when pop-up shows

13. Click OK

6. Level 1 Repair

14. Input SKU_CODE and BUYER, then click Save button.

※ Refer to HHPsvc→IMEI Review to check SKU Code and buyer

15. Input IMEI Number and click Apply

6. Level 1 Repair

16. ① Click Start → ②Input IMEI writing ID and Password & OTP → ③Input Ticket No

※ OTP(One time Password) : OTP is valid for 6 hours.

After that, you can get new OTP by click the "Forgotten your IMEI OTP PW or Crete new IMEI OTP PW" button.

☞ OTP Location : GSPN → Knowledge → HHP svc → Home

6. Level 1 Repair

17. Connect the phone to Anyway JIG

※ When you connect the phone, the phone should be turned off.
    After connecting the phone, the phone will be booted automatically.

18. IMEI Writing Proceeding

19. IMEI Writing Success

6. Level 1 Repair

6-4. RF Calibration

6-4-1. Required items in order to calibrate RF

• Installation program: RF Calibration Program
- Daseul_Launcher_vx.x.xx.exe
- Daseul_CAL_ALL_Runtime_x.x.xxx.x.CAB
- Model File
  : **SM-xxxx_OPEN_CALIBRATION_Ver_x.x.xxx.x.CAB**

※ **It is required to use the latest program.**

• Mobile Phone
• R&S CMW500
• E3632A Power Supply
• GPIB Cable (2ea)
• JIG BOX (S103)
• Adapter
• UART Serial Cable
• IF Cable (GH81-11962W)

❖ **Table of test cables**

RF Cable (Manual)	**GH81-11962M (2ea)**	GH81-11962U (2ea)	
	1.2T, 102mm	1.2T, 102mm	
4 Port Divider	**GH81-11962A**	**GH81-11962B**	**GH81-11962E**
	Divider	**Divider Cable**	**50Ω terminator**

6. Level 1 Repair

❖ **Setting**

Mobile Phone

IF Cable

JIG BOX

Serial Cable

SAMSUNG
Anyway

CMW 500

E3632A Power Supply

GPIB Cable (2ea)

RF Cable

6. Level 1 Repair

6-4-2. RF Calibration Program

1. Run the RF Calibration Program Launcher, 'DASEUL_Launcher_vx.x.xx.exe'.

DASEUL_CAL_ALL_Runtime_3.1.348.0_r00600.CAB
DASEUL_Launcher_v4.0.0.exe
SM-J410F   OPEN_CALIBRATION_Ver_3.1.347.15.CAB

2. Check the 'Calibration' option and Click 'Extract & Run'.

6. Level 1 Repair

3. Check the 'CAL' and open the model file, then select 'Start' button.

6. Level 1 Repair

4. Change the Line Type to 'Block Cell' and disable 'Smart Cloud Cell'.

6. Level 1 Repair

5. Set the GPIB address of MSTS(CMW500) and Power Supply(E3632A) to enter 'Hardware Config' and 'Save'. (Check the GPIB address of equipments in advance)

6. Level 1 Repair

6. Press 'OK' to start RF Calibration after completing all settings.

9. Reference Abbreviation

Reference Abbreviation

— **AAC**: Advanced Audio Coding.
— **AVC** : Advanced Video Coding.
— **BER** : Bit Error Rate
— **BPSK**: Binary Phase Shift Keying
— **CA**   : Conditional Access
— **CDM** : Code Division Multiplexing
— **C/I** : Carrier to Interference
— **DMB** : Digital Multimedia Broadcasting
— **EN**   **:** European Standard
— **ES**   **:** Elementary Stream
— **ETSI**: European Telecommunications Standards Institute
— **MPEG**: Moving Picture Experts Group
— **PN**   : Pseudo-random Noise
— **PS**   : Pilot Symbol
— **QPSK**: Quadrature Phase Shift Keying
— **RS**   : Reed-Solomon
— **SI**   : Service Information
— **TDM** : Time Division Multiplexing
— **TS**   **:** Transport Stream