

Codeforces Round #465 (Div. 2)

A. Fafa and his Company

time limit per test: 1 second
 memory limit per test: 256 megabytes
 input: standard input
 output: standard output

Fafa owns a company that works on huge projects. There are n employees in Fafa's company. Whenever the company has a new project to start working on, Fafa has to divide the tasks of this project among all the employees.

Fafa finds doing this every time is very tiring for him. So, he decided to choose the best l employees in his company as team leaders. Whenever there is a new project, Fafa will divide the tasks among only the team leaders and each team leader will be responsible of some positive number of employees to give them the tasks. To make this process fair for the team leaders, each one of them should be responsible for the same number of employees. Moreover, every employee, who is not a team leader, has to be under the responsibility of exactly one team leader, and no team leader is responsible for another team leader.

Given the number of employees n , find in how many ways Fafa could choose the number of team leaders l in such a way that it is possible to divide employees between them evenly.

Input

The input consists of a single line containing a positive integer n ($2 \leq n \leq 10^5$) — the number of employees in Fafa's company.

Output

Print a single integer representing the answer to the problem.

Examples

input
2
output
1
input
10
output
3

Note

In the second sample Fafa has 3 ways:

- choose only 1 employee as a team leader with 9 employees under his responsibility.
- choose 2 employees as team leaders with 4 employees under the responsibility of each of them.
- choose 5 employees as team leaders with 1 employee under the responsibility of each of them.

B. Fafa and the Gates

time limit per test: 2 seconds
 memory limit per test: 256 megabytes
 input: standard input
 output: standard output

Two neighboring kingdoms decided to build a wall between them with some gates to enable the citizens to go from one kingdom to another. Each time a citizen passes through a gate, he has to pay one silver coin.

The world can be represented by the first quadrant of a plane and the wall is built along the identity line (i.e. the line with the equation $x = y$). Any point below the wall belongs to the first kingdom while any point above the wall belongs to the second kingdom. There is a gate at any integer point on the line (i.e. at points $(0, 0)$, $(1, 1)$, $(2, 2)$, ...). The wall and the gates do not belong to any of the kingdoms.

Fafa is at the gate at position $(0, 0)$ and he wants to walk around in the two kingdoms. He knows the sequence S of moves he will do. This sequence is a string where each character represents a move. The two possible moves Fafa will do are 'U' (move one step up, from (x, y) to $(x, y + 1)$) and 'R' (move one step right, from (x, y) to $(x + 1, y)$).

Fafa wants to know the number of silver coins he needs to pay to walk around the two kingdoms following the sequence S . Note that if Fafa visits a gate without moving from one kingdom to another, he pays no silver coins. Also assume that he doesn't pay at the gate at point $(0, 0)$, i. e. he is

The single line of the input contains 5 space-separated integers R, x_1, y_1, x_2, y_2 ($1 \leq R \leq 10^5, |x_1|, |y_1|, |x_2|, |y_2| \leq 10^5$).

Output

Print three space-separated numbers x_{ap} , y_{ap} , r where (x_{ap}, y_{ap}) is the position which Fafa chose for the access point and r is the radius of its range.

Your answer will be considered correct if the radius does not differ from optimal more than 10^{-6} absolutely or relatively, and also the radius you printed can be changed by no more than 10^{-6} (absolutely or relatively) in such a way that all points outside the flat and Fafa's laptop position are outside circle of the access point range.

Examples

input
5 3 3 1 1
output
3.7677669529663684 3.7677669529663684 3.914213562373095

input
10 5 5 5 15
output
5.0 5.0 10.0

D. Fafa and Ancient Alphabet

time limit per test: 2 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

Ancient Egyptians are known to have used a large set of symbols Σ to write on the walls of the temples. Fafa and Fafa went to one of the temples and found two non-empty words S_1 and S_2 of equal lengths on the wall of temple written one below the other. Since this temple is very ancient, some symbols from the words were erased. The symbols in the set Σ have equal probability for being in the position of any erased symbol.

Fafa challenged Fafa to calculate the probability that S_1 is lexicographically greater than S_2 . Can you help Fafa with this task?

You know that $|\Sigma| = m$, i. e. there were m distinct characters in Egyptians' alphabet, in this problem these characters are denoted by integers from 1 to m in alphabet order. A word x is lexicographically greater than a word y of the same length, if the words are same up to some position, and then the word x has a larger character, than the word y .

We can prove that the probability equals to some fraction P / Q , where P and Q are coprime integers, and $Q \not\equiv 0 \pmod{10^9 + 7}$. Print as the answer the value $R = P \cdot Q^{-1} \pmod{10^9 + 7}$, i. e. such a non-negative integer less than $10^9 + 7$, such that $R \cdot Q \equiv P \pmod{10^9 + 7}$, where $a \equiv b \pmod{m}$ means that a and b give the same remainders when divided by m .

Input

The first line contains two integers n and m ($1 \leq n, m \leq 10^5$) — the length of each of the two words and the size of the alphabet Σ , respectively.

The second line contains n integers a_1, a_2, \dots, a_n ($0 \leq a_i \leq m$) — the symbols of S_1 . If $a_i = 0$, then the symbol at position i was erased.

The third line contains n integers representing S_2 with the same format as S_1 .

Output

Print the value $P \cdot Q^{-1} \pmod{10^9 + 7}$, where P and Q are coprime and P / Q is the answer to the problem.

Examples

input
1 2 0 1
output
500000004

input
1 2 1 0
output
0

input
7 26

0 15 12 9 13 0 14 11 1 0 13 15 12 0
output
230769233

Note

In the first sample, the first word can be converted into (1) or (2). The second option is the only one that will make it lexicographically larger than the second word. So, the answer to the problem will be $\frac{1}{2} \bmod (10^9 + 7)$, that is 500000004, because $(500000004 \cdot 2) \bmod (10^9 + 7) = 1$.

In the second example, there is no replacement for the zero in the second word that will make the first one lexicographically larger. So, the answer to the problem is $\frac{0}{1} \bmod (10^9 + 7)$, that is 0.

E. Fafa and Ancient Mathematics

time limit per test: 2 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

Ancient Egyptians are known to have understood difficult concepts in mathematics. The ancient Egyptian mathematician Ahmes liked to write a kind of arithmetic expressions on papyrus paper which he called as *Ahmes arithmetic expression*.

An *Ahmes arithmetic expression* can be defined as:

- " d^h " is an Ahmes arithmetic expression, where d is a one-digit positive integer;
- " $(E_1 \text{ op } E_2)$ " is an Ahmes arithmetic expression, where E_1 and E_2 are valid Ahmes arithmetic expressions (without spaces) and op is either plus (+) or minus (-).

For example 5, $(1-1)$ and $((1+(2-3))-5)$ are valid Ahmes arithmetic expressions.
On his trip to Egypt, Fafa found a piece of papyrus paper having one of these Ahmes arithmetic expressions written on it. Being very ancient, the papyrus piece was very worn out. As a result, all the operators were erased, keeping only the numbers and the brackets. Since Fafa loves mathematics, he decided to challenge himself with the following task:

Given the number of plus and minus operators in the original expression, find out the maximum possible value for the expression on the papyrus paper after putting the plus and minus operators in the place of the original erased operators.

Input

The first line contains a string E ($1 \leq |E| \leq 10^4$) — a valid Ahmes arithmetic expression. All operators are erased and replaced with '?'.
The second line contains two space-separated integers P and M ($0 \leq \min(P, M) \leq 100$) — the number of plus and minus operators, respectively.
It is guaranteed that $P + M =$ the number of erased operators.

Output

Print one line containing the answer to the problem.

Examples

input
(1?1) 1 0
output
2
input
(2?(1?2)) 1 1
output
1
input
((1?(5?7))?(6?2)?7)) 3 2
output
18
input
((1?(5?7))?(6?2)?7)) 2 3
output

Note

- The first sample will be $(1 + 1) = 2$.
- The second sample will be $(2 + (1 - 2)) = 1$.
- The third sample will be $((1 - (5 - 7)) + ((6 + 2) + 7)) = 18$.
- The fourth sample will be $((1 + (5 + 7)) - ((6 - 2) - 7)) = 16$.

F. Fafa and Array

time limit per test: 3 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

Fafa has an array A of n positive integers, the function $f(A)$ is defined as $\sum_{i=1}^{n-1} |a_i - a_{i+1}|$. He wants to do q queries of two types:

- 1 $l\ r\ x$ — find the maximum possible value of $f(A)$, if x is to be added to one element in the range $[l, r]$. You can choose to which element to add x .
- 2 $l\ r\ x$ — increase all the elements in the range $[l, r]$ by value x .

Note that queries of type 1 don't affect the array elements.

Input

The first line contains one integer n ($3 \leq n \leq 10^5$) — the length of the array.

The second line contains n positive integers a_1, a_2, \dots, a_n ($0 < a_i \leq 10^9$) — the array elements.

The third line contains an integer q ($1 \leq q \leq 10^5$) — the number of queries.

Then q lines follow, line i describes the i -th query and contains four integers $t_i\ l_i\ r_i\ x_i$ ($t_i \in \{1, 2\}$, $1 < l_i \leq r_i < n$, $0 < x_i \leq 10^9$).

It is guaranteed that at least one of the queries is of type 1.

Output

For each query of type 1, print the answer to the query.

Examples

input
<pre> 5 1 1 1 1 1 5 1 2 4 1 2 2 3 1 2 4 4 2 2 3 4 1 1 3 3 2 </pre>
output
<pre> 2 8 </pre>
input
<pre> 5 1 2 3 4 5 4 1 2 4 2 2 2 4 1 2 3 4 1 1 2 4 2 </pre>
output
<pre> 6 10 </pre>