



Circuit Diagram





## SPECIFICATIONS

- · Core type/size: EI-14
- · Impedance variation: ±10% @ 1KHz
- D.C. resistance tolerance: ±15%
- Insulation:  $>10M\Omega$  @ 100VDC
- · Breakdown voltage: 100VAC HIPOT for 1 minute
- · Maximum output: 75mW
- · Frequency response: ±3dB, 300Hz-3.4KHz @ 1KHz 0dB
- Waxing: vacuum treatment
- · Other: can be water washed with water temperature @ <20°C.
- · PC leads are soft metal wire and can be adjusted to fit a variety of applications.
- · RoHS Compliant

N.A	Innodence (O) Posistance (O) Turne					
Mouser	Impedance $(\Omega)$		Resistance (Ω)		Turns	
Stock No.	Pri.	Sec.	Pri.	Sec.	Pri.	Sec.
42TL001-RC 42TL003-RC 42TL008-RC 42TL012-RC 42TL011-RC 42TL016-RC 42TL018-RC 42TL019-RC 42TL021-RC 42TL021-RC 42TL023-RC 42TL025-RC 42TL025-RC 42TL026-RC 42TL027-RC 42TL027-RC 42TL027-RC 42TL027-RC 42TL027-RC 42TL030-RC 42TL030-RC 42TL031-RC	500 1.2K 200 800 10K 600 20K 7K 1.5K 300 17K 500 10K 10K 500 600	8 8 8 8 600 600 10K 600 600 600 1K 16 2K 100 10K 2500	35 80 12 40 900 60 65 693 400 450 148 125 30 693 43 130 10.9 715 500 40 42.8	1.0 1.0 1.0 500 1.0 566 385 100 64 555 346 1.9 140 9.10 583 200 38 20.2	500 810 400 510 2500 756 680 2840 1720 2000 1320 930 400 2800 540 920 250 1840 2100 510 630	60 80 60 1700 680 320 1460 390 440 540 530 460 96 470 250 1840 600 490 254

Sopecifications are subject to change without notice. No liability or warranty implied by this information. Environmental compliance based on producer documentation.



## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Xicon:

 42TL016-RC
 42TL003-RC
 42TL018-RC
 42TL012-RC
 42TL031-RC
 42TL025-RC
 42TL006-RC
 42TL022-RC

 42TL009-RC
 42TL024-RC
 42TL023-RC
 42TL004-RC
 42TL021-RC
 42TL011-RC
 42TL013-RC
 42TL020-RC

 42TL027-RC
 42TL001-RC
 42TL019-RC
 42TL026-RC
 42TL218-RC
 42TL017-RC
 42TL002-RC
 42TL008-RC

 42TL030-RC