

## Abstract Data Type (ADT)

**Abstraction** is the process to reduce the information content of a concept, typically to retain only information which is relevant for a particular purpose.

In computer science, abstraction is the process by which data and programs are defined with a representation similar in form to its meaning (semantics), while **hiding away the implementation details**.

In OO-programming, we try to separate the logical (external observable) properties of an object from its internal implementation details.

For example, the standardized user interface of an Android phone is a logical property of the device.

The construction of the physical Android phone is the implementation details.

From the point of view of the user, you only need to know the logical property (i.e. the user interface) of the device when you are using the phone, you don't need to know its internal implementation details.

**ADT** is a tool that allows the programmer to separate the logical properties of a data structure from its implementation details.

An ADT has 3 components:

- name of the ADT, called the **type name**
- the set of values belonging to the ADT, called the **domain (or properties)**
- the **set of operations** on the data (corresponds to the member functions in the implementation)

## Abstract Data Type : Stack

A **stack** is a list of homogeneous elements in which the addition and deletion of elements occur only at one end, called the **top** of the stack.

A stack is also called a **Last In First Out** (LIFO) data structure.

Operations on a stack:

- **initialize**: initialize the stack to an empty state
- **empty**: determine if the stack is empty
- **top**: retrieve the value of the top element
- **push**: insert element at the top of stack
- **pop**: remove top element
- **size**: determine the number of elements in the stack (not required in most applications of stack).

In C++, we can define an ADT using an **abstract class**. In our discussion, I will try to follow the notations used in the C++ STL (Standard Template Library).

```
template<class Type>
class stackADT
{
public:
    virtual void initialize() = 0; //pure virtual function
    // remark: the initialize() function is not part of the
    //           C++ STL. The initialization can be taken care
    //           of by the constructor.

    virtual int size() const = 0;
    virtual bool empty() const = 0;

    virtual Type& top() const = 0;
    // return the top element by reference (lvalue reference)

    virtual void push(const Type& item) = 0; //lvalue reference
    virtual void push(Type&& item) = 0;      //rvalue reference

    virtual void pop() = 0;
    // Note that in the C++ STL, the pop function does not
    // return the (old) top element that is removed.

    // Remark: in Java, the pop method of the class Stack
    //           will return the removed element.
}
```

Remarks:

In the textbook, the author includes a function `full()` in the `stackADT`. The function `full()` returns `true` if the stack is full.

However, `full()` is not part of the `stack` class in the C++ STL.

It is not required if the stack is implemented using linked list (conceptually a linked list can always be extended). If the stack is implemented using array, the array can also be expanded on demand.

In the high level applications using stack, we only need to check if the stack is empty.

- If we call the `top()` function on an empty stack, an underflow exception occurs.

The `top()` function in the STL returns the top element by reference. It is different from the example given in the textbook, where the `top()` function returns the top element by value.

There are actually 2 versions of the `top()` function in the STL, one that returns a non-constant reference, and the other one that returns a constant-reference.

```
Type& top();           // non-constant reference
const Type& top() const; // constant reference
```

The compiler chooses the appropriate version of the `top()` function to be used. In our discussion, we only consider the `top()` function that returns a non-constant reference.

We shall first discuss some examples on the uses of stack in algorithm design, and then come back to discuss the internal implementation of the stack ADT.

One common use of stack is for the simulation of recursion, i.e. converting a recursive algorithm to an equivalent non-recursive algorithm using a stack. We shall talk about this after the discussion of recursion.

## **lvalue** and **rvalue**

A **lvalue** is an expression that may appear on the left or on the right of an assignment statement. In general a **lvalue** is a variable or a designated memory location.

A **rvalue** is an expression that can only appear on the right hand side of an assignment statement. Usually, a **rvalue** is a literal (constant value used in an expression) or the intermediate result of some operator.

```
int i;  
i = 2 + 3;
```

In the above assignment statement, the variable `i` is a **lvalue**, and the result of `2+3` is a **rvalue**.

More examples:

**// rvalues:**

```
int j = 2; // OK, j is a lvalue, 2 is a rvalue
```

```
3 = j; // error, 3 is a rvalue
```

```
int foobar(); // foobar() returns a rvalue
```

```
j = foobar(); // ok
```

```
foobar() = 3; // error: foobar() returns a rvalue
```

```
int *p3 = &foobar(); // error: rvalue does not have  
// a persistent address
```

**// lvalues:**

```
int i = 0;
i = 3; // OK

int *p1 = &i; // i is a lvalue, it has a persistent address
*p1 = 6;      // *p1 is a lvalue, change the value of i to 6

int& r = i; // r is a reference variable
r = 5;      // effect : i is set to 5

int& foo(); // foo() returns a lvalue by reference

foo() = 2;  // ok, assign the rvalue 2 to the lvalue
           // returned by the function foo() by reference

int *p2 = &foo(); // p2 is assigned the address of the
                 // lvalue returned by foo()
```

---

More concrete example:

```
int& fn(int list[], int k)
{
    return list[k]; // return list[k] by reference
}

int main()
{
    int a[] = {1, 2, 3, 4, 5};
    int n = 5; // length of a[] = 5

    int k = 4;
    fn(a, k) = 6; // a[4] is changed to 6
                 // a[] = {1, 2, 3, 4, 6}

    ...
}
```

The **rvalue reference** **Type&&** is introduced in C++ 11 standard (2011). It can be used to define the data type of an input parameter to a function.

For further details,

[http://thbecker.net/articles/rvalue\\_references/section\\_01.html](http://thbecker.net/articles/rvalue_references/section_01.html)

Example codes:

```
#include <stack> // class stack in the C++ STL

int gcd(int m, int n) // returns a rvalue
{
    int r;

    while (r = m % n)
    {
        m = n;
        n = r;
    }
    return n;
}

int main()
{
    stack<int> s;

    int i = 10;

    s.push(i); // s.push(const Type& item),
               // i is passed to the function by lvalue reference

    int j = 25;

    s.push(gcd(i, j)); // s.push(Type&& item)
                      // gcd() returns a rvalue
    // return value of gcd() is passed to push() by rvalue ref.

    s.top() -= 2; // top element is changed to 5-2 = 3

}
```

In the following discussion, we assume the concrete class `stack` has been defined:

```
template<class Type>  
class stack: public stackADT<Type>  
{  
private:  
    // member variables  
  
public:  
    void initialize()  
    {  
        // detailed implementation  
    }  
  
    bool empty()  
    {  
        // detailed implementation  
    }  
  
    Type& top()  
    {  
        // detailed implementation  
    }  
  
    ...  
  
    // other member functions, constructors and destructor  
}
```

## Infix, postfix and prefix expression formats

- In infix format, the binary operator is placed in between the 2 operands.
- The order of evaluation is determined by the precedence relation of the operators and parentheses, if any.
- The order of precedence is  
    exponentiation  
    multiplication, division  
    addition, subtraction

Examples,

$$1 + 3 * 2^2 = 13$$

$$(1 + 3) * 2^2 = 16$$

- In postfix format, the operator is placed after the 2 operands. The order of evaluation is the same as the order in which the operators appear in the postfix expression.
- In prefix format, the operator is placed in front of the 2 operands.
- The advantage of postfix (and prefix) format is that it requires **no parentheses**.
- In the examples shown below, \$ represents the exponentiation operator.

$$A\$B = A^B$$

Infix	Postfix	Prefix
$A * B + C / D$	$AB * CD / +$	$+ * AB / CD$
$(A / B - C) * D + E$	$AB / C - D * E +$	$+ * - / ABCDE$
$A / (B * (C - (D + E)))$	$ABCDE + - * /$	$/ A * B - C + DE$
$A \$ B * C - D + E / F / (G + H)$	$AB \$ C * D - EF / GH + / +$	$+ - * \$ ABCD / / EF + GH$
$D + E / ((A * B) \$ C + F)$	$DEAB * C \$ F + / +$	$+ D / E + \$ * ABCF$
$(A * (B + C) - D) / (E - (F + G))$	$ABC + * D - EFG + - /$	$/ - * A + BCD - E + FG$



## Algorithm to evaluate a postfix expression (pseudo code)

To simplify the discussion, we only consider the 5 binary operators, e.g. +, −, \*, / and \$.

```
stack<double> S;

// scan the input expression from left to right
while (not end of expression)
{
    symb = next symbol in expression;

    if (symb is an operand)
    {
        value = convert symb to double;
        S.push(value);
    }
    else // symb is an operator
    {
        opnd2 = S.top(); S.pop();

        opnd1 = S.top(); S.pop();

        result = evaluate(symb, opnd1, opnd2);
        S.push(result);
    }
}
final_result = S.top();
```

## Algorithm to convert an infix expression to postfix format

Observations:

1. The [relative order](#) of the operands in postfix format is the same as that in the infix format.
2. If we construct a fully parenthesized infix expression, the postfix expression can be obtained by moving the operators to the corresponding close bracket “)”.
3. In the conversion algorithm, we scan the input infix expression from left to right and use an [operator stack](#) to delay the time when the operators are sent to the output postfix expression.

Define the precedence relation of the operators

operators	precedence no.
@	0
'\0'	1
(	2
+ or –	3
* or /	4
\$	5

@ is the special symbol to denote the bottom of stack

'\0' denotes the end of input

Defining the precedence relation of the two special symbols '\0' and @ removes the need for special treatment of the boundary conditions.

They are used as [sentinels](#) in this algorithm.

```
// Assumptions: Each operand is represented by a single letter.
//               No white-space char in the input array.
```

```
void infix_to_postfix(char *infix, char *postfix)
{
    stack<char> S;
    S.push('@'); // '@' is used as a sentinel
    int i=0, j=0;

    while (S.top() != '\\0')
    {
        /* '\\0' denotes the end of input; its low precedence
           will cause the other operators to be popped out from
           stack before '\\0' is pushed on to the stack */

        char symb = infix[i++];

        if (isOperand(symb)) // symb >= 'A' && symb <= 'Z'
            postfix[j++] = symb;
        else if (symb == '(')
            S.push('(');
        else if (symb == ')')
        {
            while (S.top() != '(')
            {
                postfix[j++] = S.top();
                S.pop();
            } // the ')' is discarded

            S.pop(); // remove '(' from stack
        }
        else if (isOperator(symb))
            // symb is one of {+, -, *, /, $, '\\0', '@'}
        {
            while (precNum(S.top()) >= precNum(symb))
            {
                postfix[j++] = S.top();
                S.pop();
            }
            S.push(symb);
        }
    } // end of while-loop

    postfix[j] = '\\0'; // terminate the postfix string
}
```

```
// With '@' sitting at the bottom of stack, we need not
// test if stack is not empty before calling top()
```

## Implementation of the class stack using array

```
// file: stack.h
#ifndef STACK_H
#define STACK_H
#include <ostream>

template<class Type>
class stack: public stackADT<Type>
{
private:
    int maxSize;    //var to store the max stack size
    int stackTop;   //var to point to the top element
    Type *list;     //pointer to the array that holds the elements

    void copyStack(const stack<Type>& other);

public:
    stack(int size=100)    //the function body is placed in-line
    {                      //for easy reading
        maxSize = size;
        stackTop = -1;
        list = new Type[maxSize];
    }

    stack(const stack<Type>& other)
    {
        maxSize = 0;
        list = nullptr;
        copyStack(other);
    }

    ~stack()
    { delete[] list; }

    void initialize();
    { stackTop = -1; }

    bool empty() const
    { return stackTop < 0; }

    bool full() const;
    { return stackTop >= maxSize - 1; }

    int size() const
    { return stackTop+1; }
```

```

const stack<Type>& operator=(const stack<Type>& other)
{
    if (this != &other)
        copyStack(other);
    return *this;
}

void push(const Type& item)
{
    if (!full())
        list[++stackTop] = item;
    else
        cerr << "Stack overflow" << endl;

    /* Alternative implementation: expand the array
    if (full())
    {
        maxSize = 2 * maxSize;
        Type *newList = new Type[maxSize];
        for (int i = 0; i <= stackTop; i++)
            newList[i] = list[i];
        delete[] list;
        list = newList;
    }
    list[++stackTop] = item;
    */
}

void push(Type&& item)
{
    // same as push(const Type& item)
}

Type& top()
{
    //precondition: stack is not empty
    return list[stackTop];
}

void pop()
{
    if (!empty())
        stackTop--;
    else
        cerr << "Stack underflow" << endl;
}

};

```

```

//Implementation of copyStack()
template<class Type>
void stack<Type>::copyStack(const stack<Type>& other)
{
    if (maxSize != other.maxSize)
    {
        if (list != nullptr)
            delete [] list;
        maxSize = other.maxSize;
        list = new Type[maxSize];
    }

    stackTop = other.stackTop;
    for (int i = 0; i <= stackTop; i++)
        list[i] = other.list[i];
}

#endif

```

## Queue

A **first-in-first-out** (FIFO) queue is an ordered collection of items from which items may be deleted at one end (called the **front**) and into which items may be inserted at the other end (called the **rear**).

Operations on a queue :

- **initialize**: initialize the queue to an empty state
- **size**: determine the number of elements in the queue
- **empty**: determine if the queue is empty
- **front**: retrieve the value of the front element
- **back**: retrieve the value of the last element (this is not common in the applications of queue)
- **push**: insert element at the rear of queue (in most textbooks, this operation is called **enqueue**)
- **pop**: remove front element (in most textbooks, this operation is called **dequeue or delete**)

```
template<class Type>
class queueADT
{
public:
    virtual void initialize() = 0;
    //remark: the initialize() function is not part of the
    //        C++ STL. The initialization can be taken care
    //        of by the constructor.


    virtual int size() const = 0;
    virtual bool empty() const = 0;

    virtual Type& front() const = 0;

    virtual void push(const Type& item) = 0;
    virtual void push(Type&& item) = 0;

    virtual void pop() = 0;
}
```

## Implementing a FIFO queue using a circular array:



Conventions of the representation:

- The program maintains two indexes, front and rear
- If the queue is empty, front == rear.
- If the queue is not empty,
  - rear points to the last element, and
  - front points to the slot before the first element.

An array of size  $n$  can hold up to  $n-1$  elements.

Example applications of queue:

- message buffering in inter-process communications
- task scheduling in operating system
- breadth-first search of multi-dimensional data structures, e.g. trees and graphs
- event-driven simulations



```

// file: queue.h
#ifndef QUEUE_H
#define QUEUE_H
#include <ostream>

template<class Type>
class queue: public queueADT<Type>
{
private:
    int maxSize;
    int queueFront, queueRear;
    Type *list;

    void copyQueue(const queue<Type>& other);

public:
    queue(int size=100) //the function body is placed in-line
    { //for easy reading
        maxSize = size;
        queueFront = queueRear = 0;
        list = new Type[maxSize];
    }

    queue(const queue<Type>& other)
    {
        maxSize = 0;
        list = nullptr;
        copyQueue(other);
    }

    ~queue()
    { delete [] list; }

    void initialize();
    { queueFront = queueRear = 0; }

    bool empty() const
    { return queueFront == queueRear; }

    bool full() const;
    { return (queueRear + 1) % maxSize == queueFront; }

    int size() const
    { return (maxSize + queueRear - queueFront) % maxSize; }

```

```

const queue<Type>& operator=(const queue<Type>& other)
{
    if (this != &other)
        copyQueue(other);
    return *this;
}

void push(const Type& item)
{
    if (!full())
    {
        queueRear = (queueRear + 1) % maxSize;
        list[queueRear] = item;
    }
    else
        cerr << "Queue overflow" << endl;
}

void push(Type&& item)
{
    if (!full())
    {
        queueRear = (queueRear + 1) % maxSize;
        list[queueRear] = item;
    }
    else
        cerr << "Queue overflow" << endl;
}

Type& front()
{
    //precondition: queue is not empty
    return list[(queueFront + 1) % maxSize];
}

void pop()
{
    if (!empty())
        queueFront = (queueFront + 1) % maxSize;
    else
        cerr << "Queue underflow" << endl;
}

};

```

```

//Implementation of copyQueue()
template<class Type>
void queue<Type>::copyQueue(const queue<Type>& other)
{
    if (maxSize != other.maxSize)
    {
        if (list != NULL)
            delete [] list;
        maxSize = other.maxSize;
        list = new Type[maxSize];
    }

    queueFront = other.queueFront;
    queueRear = other.queueRear;

    int i = queueFront;
    while (i != queueRear)
    {
        i = (i + 1) % maxSize;
        list[i] = other.list[i];
    }
}

#endif

```

Remark: in the C++ STL, stack and queue are implemented using [deque](#) as the default container.

Deque (pronounced like “deck”) is a double-ended queue. It allows insertion and deletion at both ends.

The insertion/deletion functions are called

```

push_front
push_back
pop_front
pop_back

```