

Professional Skills
Agile Fundamentals
Jira
Git
Databases Introduction
Java Beginner
Maven
Testing (Foundation)
Java Intermediate
HTML
CSS
Javascript
<div><div></div>What is JavaScript</div>
<div><div></div>Getting started with JS</div>
<div><div></div>Variables</div>
<div><div></div>Data types</div>
<div><div></div>ASI</div>
<div><div></div>Strict mode</div>
<div><div></div>Iteration</div>
<div><div></div>Conditionals with Truthy / Falsey</div>
<div><div></div>Objects, Arrays + JSON</div>
<div><div></div>Structuring JS Code</div>
<div><div></div>Destructuring</div>
<div><div></div>Scope</div>
<div><div></div>Functions, function expressions and arrow functions</div>
<div><div></div>The ECMAScript 6 Specification</div>
<div><div></div>OOP in JavaScript</div>
<div><div></div>Best Practices</div>
<div><div></div>Closures</div>
<div><div></div>Callbacks and Promises</div>
<div><div></div>Cookies</div>
<div><div></div>Hoisting</div>
<div><div></div>Prototypes</div>
<div><div></div>Query Parameters</div>
<div><div></div>Higher Order Functions</div>

# Higher Order Functions

## Contents

- [Overview](#)
- [Tutorial](#)
- [Exercises](#)

## Overview

A **higher order function** is a function that takes a function as an argument, or returns a function.

## Tutorial

Higher order functions is in contrast to first order functions, which do not take a function as an argument or return a function as output.

The following example of a first-order function filters all 4-letter words from a list:

```
const censor = words => {
  const filtered = [];
  for(let i = 0; i < words.length; i++) {
    const word = words[i];
    if(word.length !== 4) filtered.push(word);
  }
  return filtered;
};

censor(['zunk', 'army', 'shout', 'sun']);
// Output: ['shout', 'sun']
```

Now, what if we want to select all the words that begin with 's'? We could create another function...

```
const startsWithS = words => {
  const filtered = [];
  for( let i = 0; i < words.length; i++ ) {
    const word = words[i];
    if(word.startsWith('s')) filtered.push(word);
  }
  return filtered;
};

startsWithS(['zunk', 'army', 'shout', 'sun']);
// Output: ['shout' , 'sun']
```

However, this results in significant code repetition.

There's a pattern forming here which we can identify and abstract into a more generalised solution.

Luckily, JavaScript has first class functions. Just like numbers, strings, or objects, functions can be:

- Assigned to an identifier (variable) value
- Assigned to object property values
- Passed as arguments
- Returned from functions



```
let grades = [
  {name: 'John', grade: 8, sex: 'M'},
  {name: 'Sarah', grade: 12, sex: 'F'},
  {name: 'Bob', grade: 16, sex: 'M'},
  {name: 'Johnny', grade: 2, sex: 'M'},
  {name: 'Cyrus', grade: 4, sex: 'M'},
  {name: 'Paula', grade: 18, sex: 'F'},
  {name: 'Jeff', grade: 5, sex: 'M'},
  {name: 'Jennifer', grade: 13, sex: 'F'},
  {name: 'Courtney', grade: 15, sex: 'F'},
  {name: 'Jane', grade: 9, sex: 'F'}
]
```

Lets say we want to find out:

- The average grade of the classroom
- The average grade of the boys
- The average grade of the girls
- The higher note among the boys
- The higher note among the girls.

We will try to use higher-order functions to get a program that is simple and easy to read.

```
let isBoy = student => student.sex === "M";
let isGirl = student => student.sex === "F";

let getBoys = grades => (grades.filter(isBoy));
let getGirls = grades => (grades.filter(isGirl));

let average = grades => (grades.reduce((acc,curr) => (acc + curr.grade), 0) /
grades.length);

let maxGrade = grades => (Math.max(...grades.map(student => student.grade)));
let minGrade = grades => (Math.min(...grades.map(student => student.grade)));
```

Here we have 7 functions, and each of them only has one job.  
Now we have what we need to write higher-order functions:

```
let classRoomAverage = average(grades);
let boysAverage = average(getBoys(grades));
let girlsAverage = average(getGirls(grades));
```

## Exercises

1. Following on from the previous example, write the code to calculate - ensuring that higher-order functions are used:

- Highest Grade
- Lowest Grade
- Highest Grade of Boys
- Highest Grade of Girls
- Lowest Grade of Boys
- Lowest Grade of Girls

► Solution