

Professional Skills
Agile Fundamentals
Jira
Git
Databases Introduction <ul style="list-style-type: none">Installing MySQL on WindowsProvision a MySQL Server (Google Cloud Platform)Introduction to Relational DatabasesData DesignData Definition Language (DDL)Entity-Relationship DiagramsData Manipulation Language (DML)Data Query Language using SELECTAggregate FunctionsNested QueriesJoinsData Normalisation
Java Beginner
Maven
Testing (Foundation)
Java Intermediate
HTML
CSS
Javascript
Spring Boot
Selenium
Sonarqube
Advanced Testing (Theory)
Cucumber
MongoDB
Express
NodeJS

Aggregate Functions

Contents

- [Overview](#)
- [COUNT](#)
- [SUM](#)
- [MIN, MAX, and AVG](#)
- [GROUP BY](#)
- [Tutorial](#)
- [Exercises](#)

Overview

An aggregate function or aggregation function is a function where the values of multiple rows are grouped together to form a single summary value. There are a number of aggregate functions supported in MySQL, all of which aim to get a single result from several records:

- COUNT** – counts the number of fields
- SUM** – gets the sum total of a field
- MIN/MAX/AVG** – gets the minimum/maximum/average value from a field

COUNT

The **COUNT()** function returns the number of records that matches a specified criteria:

```
SELECT COUNT(field_name1) FROM table_name;
```

For example, if we wanted to count the number of orders placed:

```
SELECT COUNT(order_id) FROM orders;
```

SUM

The **SUM()** function returns a calculated total from a numeric field:

```
SELECT SUM(field_name1) FROM table_name;
```

For example, if we wanted to count the number of items in the order line:

```
SELECT SUM(quantity) FROM order_line;
```

MIN, MAX, and AVG

The **MIN()** function returns the smallest value in a field:

```
SELECT MIN(price) FROM product;
```

The **MAX()** function returns the largest value in a field:

```
SELECT MAX(price) FROM product;
```

The **AVG()** function returns the average value in a field:

```
SELECT AVG(price) FROM product;
```

React
Express-Testing
Networking
Security
Cloud Fundamentals
AWS Foundations
AWS Intermediate
Linux
DevOps
Jenkins Introduction
Jenkins Pipeline
Markdown
IDE Cheatsheet

GROUP BY

The **GROUP BY** command is often used in conjunction with aggregate functions to bring together sections of data based on common values within a field.

For instance, if you wanted to find the most expensive order made by each customer, we could try something like this:

```
SELECT customer_id, MAX(total) AS max_total FROM orders GROUP BY customer_id;
```

Tutorial

There is no tutorial for this module.

Exercises

Design, write and run **SELECT** queries for your games shop database that will answer typical questions you would ask of a retail database (price of the most expensive item, most common customer, etc.)

(*note: if you have not tested **SELECT** statements yet, refer back to the [Data Query Language](#) module for context*)

► Solution