# COURSEWARE



Profe	ssional Skills
Agile Fundamentals	
Jira	
Git	
Databases Introduction	
Java Beginner	
Maven	
Testing (Foundation)	
Java Intermediate	
HTML	
CSS	
Javascript	
Spring Boot	
Selenium	
Sonarqube	
Advanced Testing (Theory)	
Cucumber	
MongoDB	
Express	
NodeJS	
React	
Express-Testing	
Networking	
0 1	letworking Basics
0 1	letworking Models
O F	Routing and IP Addresses
0 1	letwork Address Translation
O F	HTTP Requests
Security	
	d Fundamentals

Cloud Fundamentals

# **Network Address Translation**

#### Contents

- Overview
- Why use NAT
- Local Area Network
  - Communication
- How NAT works
  - Web Servers
- <u>Tutorial</u>
  - Windows
  - Linux/MacOS
  - External IP
- Exercises

### Overview

Network Address Translation (NAT) is a service which translates between IP address from a private network and ones which can be used to communicate across the Internet.

## Why use NAT

There are a finite number of IPv4 addresses available to be used at a time, and with more and more people connecting to the Internet, we are running out. Originally, NAT was designed to free up some of these addresses so that we don't run out.

#### Local Area Network

A Local Area Network (LAN) is a small group of nodes which are contained within a small geographical area, usually controlled by a single source.

In a LAN, such as your home or work network, each node will have it's own private IP address.


This address is used to communicate with other nodes in the same LAN only, as a result, the same private IP can be used in multiple LANs.

#### Communication

When computer A, with a private IP address of 192.168.1.2, tries to communicate with computer B, which has a private IP address of 192.168.1.73, it sends a packet of data which contains both the source IP and the destination IP.

This packet of data is usually sent via a router; the router knows which node has the destination IP and redirects the packet to the correct place.

AWS Foundations	
AWS Intermediate	
Linux	
DevOps	
Jenkins Introduction	
Jenkins Pipeline	
Markdown	
IDE Cheatsheet	




## **How NAT works**

When computer A tries to communicate with a node via the Internet, it sends a packet which contains the source IP and the destination IP.

When the router received this packet, it recognises that the destination IP is not in the LAN and redirects it to the firewall.

The firewall takes this request, and sends a copy of it to the destination IP address, via the Internet, with its own external IP addresses as the source IP.

When a response is received, it is sent back to the computer inside the LAN with using the private IP.



### Web Servers

As nodes in a private network do not have an external IP address by default, nodes from outside the network cannot instigate a connection to them.

To let other devices connect to a node from via the Internet, we use NAT to assigned a separate external IP to the node.

This way, the firewall knows exactly which machine to redirect packets to when a device tries to connect.

Since the connection must come through the firewall, we can set up further firewall rules to help keep out private network secure.

### **Tutorial**

Using the terminal on our machines, we're going to look at the private IP configurations of our machine.

### Windows

Open up powershell.

This can be done by pressing the windows key and R at the same time, and then typing in powershell.

Once you have opened powershell, type the following and press Enter

#### ipconfig

Make a note of your IPv4 address.

## Linux/MacOS

Open up a terminal.

This can be done by searching your applications for the word terminal.

Once you have opened a terminal, type the following and press Enter

#### ifconfig

Make a note of your IPv4 address, you can find it next to the label inet.

### External IP

Now, we want to compare the private IP of our machine, to the external IP (also known as public IP).

Go to google, and search for

#### what **is my** ip

Compare this to the private IP you found earlier, you should see that these are different.

Since Google is running on another node which must be accessed via the internet, the private IP of your machine has been translated to a public IP, using NAT, when you connected to it.

## **Exercises**

There are no exercises for this module.