

Professional Skills
Agile Fundamentals
Jira
Git
Databases Introduction
Java Beginner
Maven
Testing (Foundation)
Java Intermediate
HTML
CSS
Javascript
Spring Boot
Selenium
Sonarqube
Advanced Testing (Theory)
Cucumber
MongoDB
Express
NodeJS
React
Express-Testing
Networking
Security
Cloud Fundamentals
<div><div></div>Cloud Concepts</div>
<div><div></div>Cloud Benefits</div>
<div><div></div>Cloud Enabling Technologies</div>
<div><div></div>Cloud Security</div>
<div><div></div>Comparing Cloud service models: IaaS, PaaS, SaaS</div>

Regions and Availability zones

Contents

- [Overview](#)
 - [Availability zones](#)
 - [Regions](#)
- [Tutorial](#)
- [Exercises](#)

Overview

Availability zones are tightly coupled (related) to *Regions*, hence this module will cover them both alongside each other.

Availability zones

An **Availability zone (AZ)** is a *unique* physical location within a *region*.

One or more data centres make up one *AZ* and has its own independent power supply, cooling and networking.

AZ are independent so as to maintain **zone redundancy**.

Zone redundancy ensures that a datacentre failure would be recoverable through copying everything over to another datacentre within the same *AZ*.

Zone redundancy provides protection from a single point of failure.

Each Cloud provider will be guaranteeing a certain percentage of uptime for their VMs - in most cases reaching ~99.99%.

This pledge is usually described in the **Service Level Agreement (SLA)**.

An additional benefit of *AZ* is that it has good low latency replication next to high availability, which allows you to make sure that mission-critical applications are running without issues.

One of potential use cases where *AZ* comes into play would be a scenario where you would like to make sure that your database is replicated in another *AZ* for increased resilience.

This would ensure that if one *AZ* goes down due to some accident, you wouldn't lose your data as it would be available within another *AZ*.

Regions

A **region** is made up of multiple *AZ* that are interconnected with a low latency network.

In order to maximise resilience, each *region* has multiple *AZ*.

The number of *AZ* each region contains largely depends on the Cloud provider.

Typically, there are three *AZ* per *region*.


Regions give you the benefit of deploying your application in multiple *regions* to increase resilience and reduce latency.

In a scenario where you have half of your user base in one *region*, and another half in a different *region*, deploying to both would give several benefits:

- reduced latency
- increased resilience

Infrastructure-as-a-Service (IaaS)
Platform-as-a-Service (PaaS)
Software-as-a-Service (SaaS)
Public Cloud
Private Cloud
Hybrid Cloud
Regions and Availability zones
AWS Foundations
AWS Intermediate
Linux
DevOps
Jenkins Introduction
Jenkins Pipeline
Markdown
IDE Cheatsheet

Additionally, scaling could be set up for each region separately so that each region could react to their own specific demands in traffic.



Tutorial

This task is research-based.

Try answering the following questions:

Find out what the typical number of AZ within a region is, for the following Cloud providers:

- Google cloud
- AWS
- Azure

Which Cloud provider currently has the most regions?

Exercises

There are no exercises for this module.