

School mapping in ESRI imagery

Andrija Gorup, Dominik Jambrović, Marin Kačan, Siniša Šegvić

April 30th, 2025



Data problems

- **School coordinates and imagery aren't coupled** – coordinates can be recorded much earlier than the corresponding image (or vice versa)
- During the period between coordinates and image acquisition, the captured locations can exhibit changes (for example, urban growth)
- In other words, our data can be **noisy** (incorrectly labelled satellite imagery)
- Perhaps we could use **algorithms for noisy label learning**

Imprecise label learning (ILL)

- State of the art framework for training a model on various imprecise label configurations: partial labels, **noisy labels**, etc.
- Utilizes the **expectation-maximization (EM) algorithm** for modelling imprecise label information, as well as training the given model
- Can be used on custom datasets and model architectures

Imprecise label learning (ILL), CIFAR10

- Train ResNet18 model on CIFAR10 dataset with noisy labels (varying noise rate)
- Measure **accuracy on clean test data** (no noisy labels)

Noise rate (%)	Test accuracy (%)
0	96.87
20	96.36

Imprecise label learning (ILL), Anditi

- Train ConvNext-small model on Anditi dataset for 30 epochs
- Non-schools sampled from OSM Vietnam using **static Gaussian sampling with 1:1 ratio**
- Measure **results on wide dataset**
- Compare with prior best method

Imprecise label learning (ILL), Anditi

Experiment description	Final threshold (%)	Precision (%)	Recall (%)	F1 score (%)
Imprecise label learning	0.21	42.31	100.00	59.46
Prior best method	8.35	56.08	96.36	70.90

Conclusion & Future work

- Algorithms for noisy label learning help with easy tasks (for example, noisy CIFAR10 classification)
- Our experiments suggest that the noisy label learning algorithms aren't that helpful when dealing with harder tasks (school detection on satellite imagery)
- Experiment with various hyperparameter configurations to confirm or deny our suspicions