

**Rohit Sahu**  
**22BCS13677**  
**IOT -615-B**  
**Day-2**

Q1- Majority Elements

```
#include <iostream>
#include <vector> using
namespace std;

int majorityElement(vector<int>& nums) {
    int count = 0;    int candidate = 0;

    for (int num : nums) {
        if (count == 0) {
            candidate = num;
        }
        count += (num == candidate) ? 1 : -1;
    }

    count = 0;    for (int num
: nums) {        if (num ==
candidate) {
count++;
        }
    }

    if (count > nums.size() / 2) {
        return candidate;
    }

    return -1;
}

int main() {
    int n;
    cout << "Enter the number of elements: ";
    cin >> n;

    vector<int> nums(n);    cout
```

```

<< "Enter the elements: ";
for (int i = 0; i < n; ++i) {
    cin >> nums[i];
}

    cout << "Majority Element: " << majorityElement(nums) << endl;
return 0;
}

```

Output-

```

Enter the number of elements: 3
Enter the elements: 2 2 1
Majority Element: 2

```

Q2- Single Number

```

#include <iostream> #include
<vector> using
namespace std;

int singleNumber(vector<int>& nums) {
    int result = 0;    for
(int num : nums) {
        result ^= num;
    }
    return result;
}

int main() {
    int n;
    cout << "Enter the number of elements: ";
    cin >> n;

    vector<int> nums(n);    cout
    << "Enter the elements: ";
    for (int i = 0; i < n; ++i) {
        cin >> nums[i];
    }

    cout << "Single Number: " << singleNumber(nums) << endl;
    return 0;
}

```

```
}
```

Output-

```
Enter the number of elements: 3
Enter the elements: 2 1 1
Single Number: 2
```

Q3- Convert Sorted Array to Binary Search Tree

```
#include <iostream>
#include <vector> using
namespace std;

struct TreeNode {
    int val;
    TreeNode* left;
    TreeNode* right;
    TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
};

TreeNode* sortedArrayToBST(vector<int>& nums) {
    if (nums.empty()) return nullptr;

    int mid = nums.size() / 2;
    TreeNode* root = new TreeNode(nums[mid]);

    vector<int> leftNums(nums.begin(), nums.begin() + mid);
    vector<int> rightNums(nums.begin() + mid + 1, nums.end());

    root->left = sortedArrayToBST(leftNums);    root-
    >right = sortedArrayToBST(rightNums);

    return root;
}

void printInOrder(TreeNode* root) {
    if (!root) return;
    printInOrder(root->left);    cout << root-
    >val << " ";    printInOrder(root->right);
}
```

```

int main() {
int n;
    cout << "Enter the number of elements: ";
cin >> n;

    vector<int> nums(n);    cout <<
"Enter the sorted elements: ";    for
(int i = 0; i < n; ++i) {
cin >> nums[i];
    }

    TreeNode* root = sortedArrayToBST(nums);
cout << "In-order traversal of the BST: ";
printInOrder(root);    cout << endl;

    return 0;
}

```

Output-

```

Enter the number of elements: 6
Enter the sorted elements: 1 2 5 7 8 9
In-order traversal of the BST: 1 2 5 7 8 9

```

Q4- Merge Two Sorted Lists

```

#include <iostream>
using namespace std;

struct ListNode {
    int val;
    ListNode* next;
    ListNode() : val(0), next(nullptr) {}
    ListNode(int x) : val(x), next(nullptr) {}
    ListNode(int x, ListNode* next) : val(x), next(next) {}
};

ListNode* mergeTwoLists(ListNode* list1, ListNode* list2) {
if (!list1) return list2;    if (!list2) return list1;

    if (list1->val < list2->val) {        list1->next =
mergeTwoLists(list1->next, list2);

```

```

return list1;    } else {
    list2->next = mergeTwoLists(list1, list2->next);
return list2;
    }
}

```

```

void printList(ListNode* head) {
while (head) {
    cout << head->val << " ";
head = head->next;
}
cout << endl;
}

```

```

int main() {
int n1, n2;
    cout << "Enter the number of elements in the first list: ";
cin >> n1;
    ListNode* list1 = nullptr;   ListNode* tail1 =
nullptr;   cout << "Enter the sorted elements for the
first list: ";
    for (int i = 0; i < n1; ++i)
    {        int val;        cin
>> val;
        if (!list1) {            list1 =
new ListNode(val);
            tail1 = list1;
        } else {            tail1->next = new
ListNode(val);            tail1 = tail1-
>next;
        }
    }

    cout << "Enter the number of elements in the second list: ";
cin >> n2;
    ListNode* list2 = nullptr;   ListNode* tail2 = nullptr;
cout << "Enter the sorted elements for the second list: ";
    for (int i = 0; i < n2; ++i) {        int val;        cin >> val;
    if (!list2) {            list2 = new
ListNode(val);
            tail2 = list2;
        } else {            tail2->next = new
ListNode(val);            tail2 = tail2-
>next;
        }
    }
}

```

```

    }

    ListNode* mergedList = mergeTwoLists(list1, list2);
    cout << "Merged sorted list: ";
    printList(mergedList);

    return 0;
}

```

Output-

```

Enter the number of elements in the first list: 3
Enter the sorted elements for the first list: 1 2 4
Enter the number of elements in the second list: 3
Enter the sorted elements for the second list: 1 3 4
Merged sorted list: 1 1 2 3 4 4

```

## Q5- Linked List Cycle

```

#include <iostream> using
namespace std;

struct ListNode {
    int val;
    ListNode* next;
    ListNode() : val(0), next(nullptr) {}
    ListNode(int x) : val(x), next(nullptr) {}
    ListNode(int x, ListNode* next) : val(x), next(next) {}
};

bool hasCycle(ListNode* head) {
    if (!head || !head->next) return false;

    ListNode* slow = head;
    ListNode* fast = head->next;

    while (slow != fast) {
        if (!fast || !fast->next) return false;
        slow = slow->next;
        fast = fast->next->next;
    }

    return true;
}

```

```

int main() {
int n;
    cout << "Enter the number of elements in the list: ";
    cin >> n;

    ListNode* head = nullptr;    ListNode*
tail = nullptr;    cout << "Enter the
elements of the list: ";    for (int i = 0; i <
n; ++i) {
        int val;
    cin >> val;
    if (!head) {
        head = new ListNode(val);
    tail = head;    } else {        tail-
>next = new ListNode(val);
    tail = tail->next;
    }
}

    if (hasCycle(head)) {        cout << "The
list has a cycle." << endl;
    } else {
        cout << "The list does not have a cycle." << endl;
    }

    return 0;
}

```

Output-

```

Enter the number of elements in the list: 2
Enter the elements of the list: 1 2
The list does not have a cycle.

```