


## VERY EASY

### Find Center of Star Graph

There is an undirected star graph consisting of  $n$  nodes labeled from 1 to  $n$ . A star graph is a graph where there is one center node and exactly  $n - 1$  edges that connect the center node with every other node.

You are given a 2D integer array `edges` where each `edges[i] = [ui, vi]` indicates that there is an edge between the nodes `ui` and `vi`. Return the center of the given star graph.

#### Example 1:



**Input:** `edges = [[1,2],[2,3],[4,2]]`

**Output:** 2

**Explanation:** As shown in the figure above, node 2 is connected to every other node, so 2 is the center.

#### Code:

```
#include <iostream>
#include <vector>
using namespace std;

int findCenter(vector<vector<int>>& edges) {
    if (edges[0][0] == edges[1][0] || edges[0][0] == edges[1][1]) {
        return edges[0][0];
    }
    return edges[0][1];
}
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
}

int main() {

    int n;
    cout << "Enter the number of edges: ";
    cin >> n;

    vector<vector<int>> edges(n, vector<int>(2));
    cout << "Enter the edges:" << endl;
    for (int i = 0; i < n; ++i) {
        cin >> edges[i][0] >> edges[i][1];
    }

    int center = findCenter(edges);

    cout << "The center of the star graph is: " << center << endl;

    return 0;
}
```

**Output:**

The screenshot shows a C++ IDE with a dark theme. The left pane displays the code for 'main.cpp', and the right pane shows the 'Output' of the program. The code defines a function 'findCenter' that takes a vector of vectors representing edges and returns the center of a star graph. The 'main' function prompts the user for the number of edges (3) and then for the edges themselves (1 2, 2 3, 4 2). The output shows the input and the resulting center of the star graph, which is 2. A status bar at the bottom of the output pane indicates 'Code Execution Successful'.

```
main.cpp
1  #include <iostream>
2  #include <vector>
3  using namespace std;
4
5  int findCenter(vector<vector<int>>& edges) {
6      if (edges[0][0] == edges[1][0] || edges[0][0] == edges[1][1]) {
7          return edges[0][0];
8      }
9      return edges[0][1];
10 }
11
12 int main() {
13     int n;
14     cout << "Enter the number of edges: ";
15     cin >> n;
16
17     vector<vector<int>> edges(n, vector<int>(2));
18     cout << "Enter the edges:" << endl;
19     for (int i = 0; i < n; ++i) {
20         cin >> edges[i][0] >> edges[i][1];
21     }
22
23     int center = findCenter(edges);
24
25     cout << "The center of the star graph is: " << center << endl;
26
27     return 0;
}
```

Output

```
Enter the number of edges: 3
Enter the edges:
1 2
2 3
4 2
The center of the star graph is: 2

=== Code Execution Successful ===
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Find the Town Judge

In a town, there are  $n$  people labeled from 1 to  $n$ . There is a rumor that one of these people is secretly the town judge.

If the town judge exists, then:

1. The town judge trusts nobody.
2. Everybody (except for the town judge) trusts the town judge.
3. There is exactly one person that satisfies properties 1 and 2.

You are given an array `trust` where `trust[i] = [ai, bi]` representing that the person labeled `ai` trusts the person labeled `bi`. If a trust relationship does not exist in trust array, then such a trust relationship does not exist.

Return the label of the town judge if the town judge exists and can be identified, or return -1 otherwise.

Example 1:

Input:  $n = 2$ , `trust = [[1,2]]`

Output: 2

### Code:

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
int findJudge(int n, vector<vector<int>>& trust) {
```

```
    vector<int> trustCount(n + 1, 0);
```

```
    for (const auto& t : trust) {
```

```
        trustCount[t[0]]--;
```

```
        trustCount[t[1]]++;
```

```
    }
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.


```
    for (int i = 1; i <= n; ++i) {
        if (trustCount[i] == n - 1) {
            return i;
        }
    }

    return -1;
}

int main() {
    int n, m;
    cin >> n;
    cin >> m;

    vector<vector<int>> trust(m, vector<int>(2));
    for (int i = 0; i < m; ++i) {
        cin >> trust[i][0] >> trust[i][1];
    }
    int judge = findJudge(n, trust);
    if (judge == -1) {
        cout << "No town judge found." << endl;
    } else {
        cout << "The town judge is: " << judge << endl;
    }
    return 0;
}
```

## OUTPUT:



```
main.cpp  [Icons] [Share] [Run] [Clear]
1  #include <iostream>
2  #include <vector>
3  using namespace std;
4
5  int findJudge(int n, vector<vector<int>>& trust) {
6      vector<int> trustCount(n + 1, 0);
7
8      for (const auto& t : trust) {
9          trustCount[t[0]]--;
10         trustCount[t[1]]++;
11     }
12
13     for (int i = 1; i <= n; ++i) {
14         if (trustCount[i] == n - 1) {
15             return i;
16         }
17     }
18
19     return -1;
20 }
21
22 int main() {
23     int n, m;
24     cin >> n;
25     cin >> m;
26
27     vector<vector<int>> trust(m, vector<int>(2, 0));
28     for (int i = 0; i < m; ++i) {
29         for (int j = 0; j < 2; ++j) {
30             cin >> trust[i][j];
31         }
32     }
33     int judge = findJudge(n, trust);
34     cout << judge << endl;
35     return 0;
36 }
```

Output

```
2
1
1 2
The town judge is: 2

=== Code Execution Successful ===
```

## Flood Fill - [link](#)

You are given an image represented by an  $m \times n$  grid of integers `image`, where `image[i][j]` represents the pixel value of the image. You are also given three integers `sr`, `sc`, and `color`. Your task is to perform a flood fill on the image starting from the pixel `image[sr][sc]`.

To perform a flood fill:

Begin with the starting pixel and change its color to `color`.

Perform the same process for each pixel that is directly adjacent (pixels that share a side with the original pixel, either horizontally or vertically) and shares the same color as the starting pixel.

Keep repeating this process by checking neighboring pixels of the updated pixels and modifying their color if it matches the original color of the starting pixel.

The process stops when there are no more adjacent pixels of the original color to update.

Return the modified image after performing the flood fill.

### Example 1:

**Input:** `image = [[1,1,1],[1,1,0],[1,0,1]]`, `sr = 1`, `sc = 1`, `color = 2`

**Output:** `[[2,2,2],[2,2,0],[2,0,1]]`



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Code:

```
#include <iostream>

#include <vector>

using namespace std;

void floodFillHelper(vector<vector<int>>& image, int sr, int sc, int color, int originalColor) {

    if (sr < 0 || sr >= image.size() || sc < 0 || sc >= image[0].size()) return;

    if (image[sr][sc] != originalColor) return;

    image[sr][sc] = color;

    floodFillHelper(image, sr + 1, sc, color, originalColor);

    floodFillHelper(image, sr - 1, sc, color, originalColor);

    floodFillHelper(image, sr, sc + 1, color, originalColor);

    floodFillHelper(image, sr, sc - 1, color, originalColor);

}

vector<vector<int>> floodFill(vector<vector<int>>& image, int sr, int sc, int color) {

    int originalColor = image[sr][sc];

    if (originalColor != color) {

        floodFillHelper(image, sr, sc, color, originalColor);

    } return image;

}

int main() {

    int m, n, sr, sc, color;

    cout << "Enter the number of rows and columns of the image: ";

    cin >> m >> n;

    vector<vector<int>> image(m, vector<int>(n));

    cout << "Enter the image pixels:" << endl;

    for (int i = 0; i < m; ++i) {

        for (int j = 0; j < n; ++j) {

            cin >> image[i][j];
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
    } }  
  
    cout << "Enter the starting row, column, and color: ";  
  
    cin >> sr >> sc >> color;  
  
    vector<vector<int>>> result = floodFill(image, sr, sc, color);  
  
    cout << "Modified image:" << endl;  
  
    for (const auto& row : result) {  
        for (int val : row) {  
            cout << val << " ";  
        }  
        cout << endl;  
    }  
  
    return 0;  
}
```

## OUTPUT:

The screenshot shows a C++ IDE with a file named 'main.cpp'. The code implements a flood fill algorithm using a recursive helper function. The output window shows the following sequence of prompts and user inputs:

```
Enter the number of rows and columns of the image: 3 3  
Enter the image pixels:  
1 1 1  
1 1 0  
1 0 1  
Enter the starting row, column, and color: 1 1 2  
Modified image:  
2 2 2  
2 2 0  
2 0 1  
  
=== Code Execution Successful ===
```


Easy:

## Find if Path Exists in Graph

There is a bi-directional graph with  $n$  vertices, where each vertex is labeled from 0 to  $n - 1$  (inclusive). The edges in the graph are represented as a 2D integer array `edges`, where each `edges[i] = [ui, vi]` denotes a bi-directional edge between vertex `ui` and vertex `vi`. Every vertex pair is connected by at most one edge, and no vertex has an edge to itself.

You want to determine if there is a valid path that exists from vertex `source` to vertex `destination`. Given `edges` and the integers `n`, `source`, and `destination`, return `true` if there is a valid path from `source` to `destination`, or `false` otherwise.

Example 1:



Input: `n = 3`, `edges = [[0,1],[1,2],[2,0]]`, `source = 0`, `destination = 2`

Output: `true`

### CODE:

```
#include <iostream>

#include <vector>

#include <queue>

using namespace std;

bool bfs(int n, vector<vector<int>>& adjList, int source, int destination) {

    vector<bool> visited(n, false);

    queue<int> q;

    q.push(source);

    visited[source] = true;

    while (!q.empty()) {
```





# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
int node = q.front();
q.pop();

if (node == destination) {
    return true;
}

for (int neighbor : adjList[node]) {
    if (!visited[neighbor]) {
        visited[neighbor] = true;
        q.push(neighbor);
    }
}
return false;
}

bool validPath(int n, vector<vector<int>>& edges, int source, int destination) {
    vector<vector<int>> adjList(n);

    for (auto& edge : edges) {
        adjList[edge[0]].push_back(edge[1]);
        adjList[edge[1]].push_back(edge[0]);
    }

    return bfs(n, adjList, source, destination);
}
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
int main() {  
    int n, source, destination, e;  
    cout << "Enter the number of vertices (n): ";  
    cin >> n;  
  
    cout << "Enter the number of edges: ";  
    cin >> e;  
  
    vector<vector<int>> edges(e, vector<int>(2));  
    cout << "Enter the edges (u v): " << endl;  
    for (int i = 0; i < e; i++) {  
        cin >> edges[i][0] >> edges[i][1];  
    }  
  
    cout << "Enter the source and destination vertices: ";  
    cin >> source >> destination;  
  
    if (validPath(n, edges, source, destination)) {  
        cout << "Yes, there is a path from source to destination." << endl;  
    } else {  
        cout << "No, there is no path from source to destination." << endl;  
    }  
    return 0;  
}
```

**OUTPUT:**

```
main.cpp  [Icons]  Share  Run  Output  Clear

1 #include <iostream>
2 #include <vector>
3 #include <queue>
4 using namespace std;
5
6 bool bfs(int n, vector<vector<int>>& adjList, int source, int
   destination) {
7     vector<bool> visited(n, false);
8     queue<int> q;
9     q.push(source);
10    visited[source] = true;
11
12    while (!q.empty()) {
13        int node = q.front();
14        q.pop();
15
16        if (node == destination) {
17            return true;
18        }
19
20        for (int neighbor : adjList[node]) {
21            if (!visited[neighbor]) {
22                visited[neighbor] = true;
23                q.push(neighbor);
24            }
25        }
26    }
```

```
Enter the number of vertices (n): 3
Enter the number of edges: 3
Enter the edges (u v):
0 1
1 2
2 0
Enter the source and destination vertices: 0
2
Yes, there is a path from source to destination.

=== Code Execution Successful ===
```

## DFS of Graph

Given a connected undirected graph represented by an adjacency list `adj`, which is a vector of vectors where each `adj[i]` represents the list of vertices connected to vertex `i`. Perform a Depth First Traversal (DFS) starting from vertex 0, visiting vertices from left to right as per the adjacency list, and return a list containing the DFS traversal of the graph.

Note: Do traverse in the same order as they are in the adjacency list.

Example 1:

Input: `adj = [[2,3,1], [0], [0,4], [0], [2]]`

Output: `[0, 2, 4, 3, 1]`

**CODE:**

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
void dfs(int node, vector<vector<int>>& adj, vector<bool>& visited, vector<int>& result) {
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
visited[node] = true;
result.push_back(node);

for (int neighbor : adj[node]) {
    if (!visited[neighbor]) {
        dfs(neighbor, adj, visited, result);
    }
}
}

vector<int> dfsTraversal(int n, vector<vector<int>>& adj) {
    vector<bool> visited(n, false);
    vector<int> result;
    dfs(0, adj, visited, result);
    return result;
}


int main() {
    int n, e;
    cout << "Enter the number of vertices: ";
    cin >> n;
    cout << "Enter the number of edges: ";
    cin >> e;

    vector<vector<int>> adj(n);

    cout << "Enter the edges (u v):" << endl;
    for (int i = 0; i < e; i++) {
```

```
int u, v;  
  
cin >> u >> v;  
  
adj[u].push_back(v);  
adj[v].push_back(u);  
  
}  
  
vector<int> result = dfsTraversal(n, adj);  
  
cout << "DFS Traversal: ";  
  
for (int node : result) {  
    cout << node << " ";  
}  
  
cout << endl;  
  
return 0;  
}
```

## OUTPUT:



The screenshot shows a C++ IDE with a file named 'main.cpp'. The code implements a Depth-First Search (DFS) algorithm on an undirected graph. It takes the number of vertices (n) and edges (e) as input, followed by the edges themselves. The output shows the DFS traversal order of the vertices.

```
main.cpp  [Icons]  Run  Output  Clear  
1 #include <iostream>  
2 #include <vector>  
3 using namespace std;  
4  
5 void dfs(int node, vector<vector<int>>& adj, vector<bool>& visited,  
6         vector<int>& result) {  
7     visited[node] = true;  
8     result.push_back(node);  
9  
10    for (int neighbor : adj[node]) {  
11        if (!visited[neighbor]) {  
12            dfs(neighbor, adj, visited, result);  
13        }  
14    }  
15  
16 vector<int> dfsTraversal(int n, vector<vector<int>>& adj) {  
17     vector<bool> visited(n, false);  
18     vector<int> result;  
19     dfs(0, adj, visited, result);  
20     return result;  
21 }  
22  
23 int main() {  
24     int n, e;  
25     cout << "Enter the number of vertices: ";  
26     cin >> n;
```

Output:

```
Enter the number of vertices: 5  
Enter the number of edges: 8  
Enter the edges (u v):  
0 2  
0 3  
0 1  
1 0  
2 0  
2 4  
3 0  
4 2  
DFS Traversal: 0 2 4 3 1  
  
=== Code Execution Successful ===
```

## BFS of graph [link](#)

Given a connected undirected graph represented by an adjacency list adj, which is a vector of vectors where each adj[i] represents the list of vertices connected to vertex i. Perform a Breadth



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

First Traversal (BFS) starting from vertex 0, visiting vertices from left to right according to the adjacency list, and return a list containing the BFS traversal of the graph.

**Note:** Do traverse in the same order as they are in the adjacency list.

Example 1:

Input: adj = [[2,3,1], [0], [0,4], [0], [2]]

Output: [0, 2, 3, 1, 4]

## CODE:

```
#include <iostream>
#include <vector>
#include <queue>
using namespace std;

vector<int> bfsTraversal(int n, vector<vector<int>>& adj) {
    vector<bool> visited(n, false);
    vector<int> result;
    queue<int> q;

    visited[0] = true;
    q.push(0);

    while (!q.empty()) {
        int node = q.front();
        q.pop();
        result.push_back(node);

        for (int neighbor : adj[node]) {
            if (!visited[neighbor]) {
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        visited[neighbor] = true;
        q.push(neighbor);
    }
}

return result;
}

int main() {
    int n, e;
    cout << "Enter the number of vertices: ";
    cin >> n;
    cout << "Enter the number of edges: ";
    cin >> e;

    vector<vector<int>> adj(n);

    cout << "Enter the edges (u v):" << endl;
    for (int i = 0; i < e; i++) {
        int u, v;
        cin >> u >> v;
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    vector<int> result = bfsTraversal(n, adj);
    cout << "BFS Traversal: ";
    for (int node : result) {
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        cout << node << " ";  
    }  
    cout << endl;  
  
    return 0;  
}
```

## OUTPUT:

The screenshot shows a C++ IDE with a file named `main.cpp`. The code implements a Breadth-First Search (BFS) traversal on an undirected graph. It takes the number of vertices (5) and edges (8) as input, followed by the edges themselves. The output shows the BFS traversal sequence: 0 2 3 1 4.

```
main.cpp  
1  #include <iostream>  
2  #include <vector>  
3  #include <queue>  
4  using namespace std;  
5  
6  vector<int> bfsTraversal(int n, vector<vector<int>>& adj) {  
7      vector<bool> visited(n, false);  
8      vector<int> result;  
9      queue<int> q;  
10  
11     visited[0] = true;  
12     q.push(0);  
13  
14     while (!q.empty()) {  
15         int node = q.front();  
16         q.pop();  
17         result.push_back(node);  
18  
19         for (int neighbor : adj[node]) {  
20             if (!visited[neighbor]) {  
21                 visited[neighbor] = true;  
22                 q.push(neighbor);  
23             }  
24         }  
25     }  
26  
27     return result;  
}
```

Output:

```
Enter the number of vertices: 5  
Enter the number of edges: 8  
Enter the edges (u v):  
0 2  
0 3  
0 1  
1 0  
2 0  
2 4  
3 0  
4 2  
BFS Traversal: 0 2 3 1 4  
=== Code Execution Successful ===
```

## Medium

### 01 Matrix

Given an  $m \times n$  binary matrix `mat`, return the distance of the nearest 0 for each cell.





# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

The distance between two adjacent cells is 1.

Example 1:

Input: mat = [[0,0,0],[0,1,0],[0,0,0]]

Output: [[0,0,0],[0,1,0],[0,0,0]]

## CODE:

```
#include <iostream>

#include <vector>

#include <queue>

using namespace std;

vector<vector<int>> updateMatrix(vector<vector<int>>& mat) {

    int m = mat.size();

    int n = mat[0].size();

    vector<vector<int>> dist(m, vector<int>(n, -1));

    queue<pair<int, int>> q;

    for (int i = 0; i < m; i++) {

        for (int j = 0; j < n; j++) {

            if (mat[i][j] == 0) {

                dist[i][j] = 0;

                q.push({i, j});

            } } }

    vector<pair<int, int>> directions = {{-1, 0}, {1, 0}, {0, -1}, {0, 1}};

    while (!q.empty()) {

        auto [x, y] = q.front();

        q.pop();

        for (auto& dir : directions) {
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
int newX = x + dir.first;
int newY = y + dir.second;

if (newX >= 0 && newX < m && newY >= 0 && newY < n && dist[newX][newY] == -1) {
    dist[newX][newY] = dist[x][y] + 1;
    q.push({newX, newY});
} }

return dist;}

int main() {
    int m, n;
    cout << "Enter the number of rows (m): ";
    cin >> m;
    cout << "Enter the number of columns (n): ";
    cin >> n;
    vector<vector<int>> mat(m, vector<int>(n));
    cout << "Enter the matrix elements (0 or 1):\n";
    for (int i = 0; i < m; i++) {
        for (int j = 0; j < n; j++) {
            cin >> mat[i][j];
        }
    }

    vector<vector<int>> result = updateMatrix(mat);

    cout << "Updated Matrix with distances to nearest 0:\n";
    for (auto& row : result) {
        for (int cell : row) {
            cout << cell << " ";
        }
    }
```


```

        cout << endl;
    }

    return 0;
}

```

## OUTPUT:



The screenshot shows a C++ IDE with a file named 'main.cpp'. The code implements a solution for finding the distance of each cell in a matrix from the nearest 0. It uses a queue for BFS. The output window shows the following text:

```

Enter the number of rows (m): 3
Enter the number of columns (n): 3
Enter the matrix elements (0 or 1):
0 0 0
0 1 0
0 0 0
Updated Matrix with distances to nearest 0:
0 0 0
0 1 0
0 0 0
=== Code Execution Successful ===

```

## Course Schedule II

There are a total of numCourses courses you have to take, labeled from 0 to numCourses - 1. You are given an array prerequisites where prerequisites[i] = [ai, bi] indicates that you must take course bi first if you want to take course ai.

For example, the pair [0, 1], indicates that to take course 0 you have to first take course 1. Return the ordering of courses you should take to finish all courses. If there are many valid answers, return any of them. If it is impossible to finish all courses, return an empty array.

Example 1:

Input: numCourses = 2, prerequisites = [[1,0]]

Output: [0,1]



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## CODE:

```
#include <iostream>

#include <vector>

#include <queue>

using namespace std;

vector<int> findOrder(int numCourses, vector<vector<int>>& prerequisites) {

    vector<int> inDegree(numCourses, 0);

    vector<vector<int>> graph(numCourses);

    vector<int> order;

    for (const auto& prereq : prerequisites) {

        int course = prereq[0], prerequisite = prereq[1];

        graph[prerequisite].push_back(course);

        inDegree[course]++;

    }

    queue<int> q;

    for (int i = 0; i < numCourses; i++) {

        if (inDegree[i] == 0) {

            q.push(i);

        }

    }

    while (!q.empty()) {

        int course = q.front();

        q.pop();

        order.push_back(course);
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        for (int neighbor : graph[course]) {
            inDegree[neighbor]--;
            if (inDegree[neighbor] == 0) {
                q.push(neighbor);
            }
        }
    }

    return order.size() == numCourses ? order : vector<int>();
}

int main() {
    int numCourses;
    cin >> numCourses;

    int numPrerequisites;
    cin >> numPrerequisites;
    vector<vector<int>> prerequisites(numPrerequisites, vector<int>(2));
    for (int i = 0; i < numPrerequisites; i++) {
        cin >> prerequisites[i][0] >> prerequisites[i][1];
    }
    vector<int> result = findOrder(numCourses, prerequisites)
    if (result.empty()) {
        cout << "It is impossible to finish all courses.\n";
    } else {
        for (int course : result) {
            cout << course << " ";
        }
    }
}
```



**OUTPUT:**

## Minimum Height Trees

**CODE:**



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
#include <iostream>

#include <vector>

#include <queue>

using namespace std;

vector<int> findMinHeightTrees(int n, vector<vector<int>>& edges) {

    if (n == 1) {

        return {0};

    }

    vector<vector<int>> graph(n);

    for (const auto& edge : edges) {

        graph[edge[0]].push_back(edge[1]);

        graph[edge[1]].push_back(edge[0]);

    }

    queue<int> leaves;

    vector<int> degree(n, 0);

    for (int i = 0; i < n; ++i) {

        degree[i] = graph[i].size();

        if (degree[i] == 1) {

            leaves.push(i);

        }

    }

    int remainingNodes = n;

    while (remainingNodes > 2) {
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
int leavesSize = leaves.size();
remainingNodes -= leavesSize;

for (int i = 0; i < leavesSize; ++i) {
    int leaf = leaves.front();
    leaves.pop();

    for (int neighbor : graph[leaf]) {
        if (--degree[neighbor] == 1) {
            leaves.push(neighbor);
        }
    }
}

vector<int> result;
while (!leaves.empty()) {
    result.push_back(leaves.front());
    leaves.pop();
}

return result;
}

int main() {
    int n = 4;
    vector<vector<int>> edges = {{1,0}, {1,2}, {1,3}};
    vector<int> result = findMinHeightTrees(n, edges);
    for (int node : result) {
        cout << node << " ";
    }
    cout << endl;
    return 0;
}
```





# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## OUTPUT:

```
main.cpp  [Icons]  Share  Run  Output  Clear

1  #include <iostream>
2  #include <vector>
3  #include <queue>
4  using namespace std;
5
6  vector<int> findMinHeightTrees(int n, vector<vector<int>>& edges) {
7      if (n == 1) {
8          return {0};
9      }
10
11     vector<vector<int>> graph(n);
12     for (const auto& edge : edges) {
13         graph[edge[0]].push_back(edge[1]);
14         graph[edge[1]].push_back(edge[0]);
15     }
16
17     queue<int> leaves;
18     vector<int> degree(n, 0);
19
20     for (int i = 0; i < n; ++i) {
21         degree[i] = graph[i].size();
22         if (degree[i] == 1) {
23             leaves.push(i);
24         }
25     }
26
27     int remainingNodes = n;
```

```
Minimum height is : 1

=== Code Execution Successful ===
```

## HARD

### Accounts Merge

Given a list of accounts where each element `accounts[i]` is a list of strings, where the first element `accounts[i][0]` is a name, and the rest of the elements are emails representing emails of the account.

Now, we would like to merge these accounts. Two accounts definitely belong to the same person if there is some common email to both accounts. Note that even if two accounts have the same name, they may belong to different people as people could have the same name. A person can have any number of accounts initially, but all of their accounts definitely have the same name. After merging the accounts, return the accounts in the following format: the first element of each account is the name, and the rest of the elements are emails in sorted order. The accounts themselves can be returned in any order.

Example 1:



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Input: accounts =

```
[["John", "johnsmith@mail.com", "john_newyork@mail.com"], ["John", "johnsmith@mail.com", "john00@mail.com"], ["Mary", "mary@mail.com"], ["John", "johnnybravo@mail.com"]]
```

Output:

```
[["John", "john00@mail.com", "john_newyork@mail.com", "johnsmith@mail.com"], ["Mary", "mary@mail.com"], ["John", "johnnybravo@mail.com"]]
```

## CODE:

```
#include <iostream>
```

```
#include <vector>
```

```
#include <unordered_map>
```

```
#include <algorithm>
```

```
using namespace std;
```

```
class UnionFind {
```

```
public:
```

```
    unordered_map<string, string> parent;
```

```
    string find(string x) {
```

```
        if (parent.find(x) == parent.end()) {
```

```
            parent[x] = x;
```

```
        }
```

```
        if (parent[x] != x) {
```

```
            parent[x] = find(parent[x]);
```

```
        }
```

```
        return parent[x];
```

```
    }
```

```
    void unionSets(string x, string y) {
```

```
        string rootX = find(x);
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
string rootY = find(y);

if (rootX != rootY) {
    parent[rootX] = rootY;
}
}
};

vector<vector<string>> accountsMerge(vector<vector<string>>& accounts) {
    UnionFind uf;
    unordered_map<string, string> emailToName;

    for (const auto& account : accounts) {
        string name = account[0];
        for (int i = 1; i < account.size(); ++i) {
            string email = account[i];
            emailToName[email] = name;

            if (i == 1) {
                continue;
            }
            uf.unionSets(account[1], email);
        }
    }

    unordered_map<string, vector<string>> mergedAccounts;
    for (const auto& pair : emailToName) {
        string rootEmail = uf.find(pair.first);
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        mergedAccounts[rootEmail].push_back(pair.first);
    }

    vector<vector<string>> result;

    for (auto& pair : mergedAccounts) {
        string name = emailToName[pair.second[0]];
        pair.second.push_back(name);
        sort(pair.second.begin(), pair.second.end());
        reverse(pair.second.begin(), pair.second.end());
        result.push_back(pair.second);}

    return result;
}

int main() {
    vector<vector<string>> accounts = {
        {"John", "johnsmith@mail.com", "john_newyork@mail.com"},
        {"John", "johnsmith@mail.com", "john00@mail.com"},
        {"Mary", "mary@mail.com"},
        {"John", "johnnybravo@mail.com"}
    };

    vector<vector<string>> result = accountsMerge(accounts);

    for (const auto& account : result) {
        for (const auto& email : account) {
            cout << email << " ";
        }
        cout << endl;}

    return 0;
}
```

**OUTPUT:**



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
main.cpp  [Icons]  Share  Run  Output  Clear

1 #include <iostream>
2 #include <vector>
3 #include <unordered_map>
4 #include <algorithm>
5 using namespace std;
6
7 class UnionFind {
8 public:
9     unordered_map<string, string> parent;
10
11     string find(string x) {
12         if (parent.find(x) == parent.end()) {
13             parent[x] = x;
14         }
15         if (parent[x] != x) {
16             parent[x] = find(parent[x]);
17         }
18         return parent[x];
19     }
20
21     void unionSets(string x, string y) {
22         string rootX = find(x);
23         string rootY = find(y);
24
25         if (rootX != rootY) {
26             parent[rootX] = rootY;
27         }
28     }
29 }
```

```
johnsmith@mail.com john_newyork@mail.com john00@mail.com John
mary@mail.com Mary
johnnybravo@mail.com John

=== Code Execution Successful ===
```

## Rotting Oranges

You are given an  $m \times n$  grid where each cell can have one of three values:

- 0 representing an empty cell,
- 1 representing a fresh orange, or
- 2 representing a rotten orange.

Every minute, any fresh orange that is 4-directionally adjacent to a rotten orange becomes rotten.

Return the minimum number of minutes that must elapse until no cell has a fresh orange. If this is impossible, return -1.

Example

Input: grid = [[2,1,1],[1,1,0],[0,1,1]]

Output: 4

### CODE:

```
#include <iostream>

#include <vector>

#include <queue>

using namespace std;
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
struct Point {  
    int x, y;  
};  
  
int orangesRotting(vector<vector<int>>& grid) {  
    int m = grid.size();  
    int n = grid[0].size();  
    queue<Point> q;  
    int freshCount = 0;  
    int minutes = 0;  
    for (int i = 0; i < m; ++i) {  
        for (int j = 0; j < n; ++j) {  
            if (grid[i][j] == 2) {  
                q.push({i, j});  
            } else if (grid[i][j] == 1) {  
                freshCount++;  
            } } }  
    vector<int> directions = {-1, 0, 1, 0, -1, 0};  
    while (!q.empty() && freshCount > 0) {  
        int size = q.size();  
        minutes++;  
  
        for (int i = 0; i < size; ++i) {  
            Point p = q.front();  
            q.pop();  
  
            for (int d = 0; d < 4; ++d) {  
                int newX = p.x + directions[d];  
                int newY = p.y + directions[d + 1];
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
        if (newX >= 0 && newX < m && newY >= 0 && newY < n && grid[newX][newY] == 1) {  
            grid[newX][newY] = 2;  
            freshCount--;  
            q.push({newX, newY});  
        }  
    }  
}  
}  
  
return freshCount == 0 ? minutes : -1;  
}  
  
int main() {  
    vector<vector<int>>> grid = {{2, 1, 1}, {1, 1, 0}, {0, 1, 1}};  
    int result = orangesRotting(grid);  
    cout << "Minimum minutes: " << result << endl;  
    return 0;  
}  
OUTPUT:
```



main.cpp

Run

Clear

```
1 #include <iostream>
2 #include <vector>
3 #include <queue>
4 using namespace std;
5
6 struct Point {
7     int x, y;
8 };
9
10 int orangesRotting(vector<vector<int>>& grid) {
11     int m = grid.size();
12     int n = grid[0].size();
13     queue<Point> q;
14     int freshCount = 0;
15     int minutes = 0;
16
17     for (int i = 0; i < m; ++i) {
18         for (int j = 0; j < n; ++j) {
19             if (grid[i][j] == 2) {
20                 q.push({i, j});
21             } else if (grid[i][j] == 1) {
22                 freshCount++;
23             }
24         }
25     }
26 }
```

Output

Minimum minutes: 4

=== Code Execution Successful ===

## Evaluate Division

You are given an array of variable pairs equations and an array of real numbers values, where equations[i] = [Ai, Bi] and values[i] represent the equation Ai / Bi = values[i]. Each Ai or Bi is a string that represents a single variable.

You are also given some queries, where  $\text{queries}[j] = [C_j, D_j]$  represents the  $j$ th query where you must find the answer for  $C_j / D_j = ?$ .

Return the answers to all queries. If a single answer cannot be determined, return -1.0.

Note: The input is always valid. You may assume that evaluating the queries will not result in division by zero and that there is no contradiction.

Note: The variables that do not occur in the list of equations are undefined, so the answer cannot be determined for them.

Example 1:

Input: equations = [{"a","b"}, {"b","c"}], values = [2.0,3.0], queries = [{"a","c"}, {"b","a"}, {"a","e"}, {"a","a"}, {"x","x"}]

Output: [6.00000,0.50000,-1.00000,1.00000,-1.00000]





# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## CODE:

```
#include <iostream>

#include <vector>

#include <unordered_map>

#include <string>

using namespace std;

class Solution {

public:

    unordered_map<string, unordered_map<string, double>> graph;

    void buildGraph(const vector<vector<string>>& equations, const vector<double>& values) {

        for (int i = 0; i < equations.size(); ++i) {

            const string& a = equations[i][0];

            const string& b = equations[i][1];

            double value = values[i];

            graph[a][b] = value;

            graph[b][a] = 1.0 / value;

        }

    }

    double dfs(const string& start, const string& end, unordered_map<string, bool>& visited) {

        if (graph.find(start) == graph.end() || visited[start]) {

            return -1.0;

        }

        if (start == end) {

            return 1.0;

        }

        visited[start] = true;

        for (const auto& pair : graph[start]) {

            const string& next = pair.first;

            double value = pair.second;

            double result = dfs(next, end, visited);

            if (result != -1.0) {

                return value * result;

            }

        }

        return -1.0;

    }

};
```



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
visited[start] = true;

for (const auto& neighbor : graph[start]) {

    double result = dfs(neighbor.first, end, visited);

    if (result != -1.0) {

        return result * neighbor.second;

    }

}

return -1.0; }

vector<double> calcEquation(const vector<vector<string>>& equations, const vector<double>&
values, const vector<vector<string>>& queries) {

    buildGraph(equations, values);

    vector<double> result;

    for (const auto& query : queries) {

        unordered_map<string, bool> visited;

        result.push_back(dfs(query[0], query[1], visited));

    }

    return result ; } };

int main() {

    Solution solution;

    vector<vector<string>> equations = {{ "a", "b"}, {"b", "c"} };

    vector<double> values = {2.0, 3.0};

    vector<vector<string>> queries = {{ "a", "c"}, {"b", "a"}, {"a", "e"}, {"a", "a"}, {"x", "x"} };

    vector<double> result = solution.calcEquation(equations, values, queries);

    for (double res : result) {

        cout << res << " ";

    }

    cout << endl;

    return 0;
```



**OUTPUT:**

main.cpp

Run

Output

Clear

```
1 #include <iostream>
2 #include <vector>
3 #include <unordered_map>
4 #include <string>
5 using namespace std;
6
7 class Solution {
8 public:
9     unordered_map<string, unordered_map<string, double>> graph;
10
11     void buildGraph(const vector<vector<string>>& equations, const
        vector<double>& values) {
12         for (int i = 0; i < equations.size(); ++i) {
13             const string& a = equations[i][0];
14             const string& b = equations[i][1];
15             double value = values[i];
16             graph[a][b] = value;
17             graph[b][a] = 1.0 / value;
18         }
19     }
20
21     double dfs(const string& start, const string& end, unordered_map
        <string, bool>& visited) {
22         if (graph.find(start) == graph.end() || visited[start]) {
23             return -1.0;
24         }
25         if (start == end) {
26             return 1.0;
27         }
28         visited[start] = true;
29         double res = -1.0;
30         for (const string& neighbor : graph[start]) {
31             double val = dfs(neighbor, end, visited);
32             if (val != -1.0) {
33                 res = val * graph[start][neighbor];
34             }
35         }
36         return res;
37     }
38
39     double calcEquation(vector<vector<string>>& equations, vector<double>&
        values) {
40         buildGraph(equations, values);
41         double res = dfs("a", "c", {});
42         return res;
43     }
44 };
45
46 int main() {
47     vector<vector<string>> equations = {{"a", "b"}, {"b", "c"}, {"a", "c"}
48     };
49     vector<double> values = {2.0, 3.0, 1.0};
50     Solution sol;
51     double res = sol.calcEquation(equations, values);
52     cout << res << endl;
53     return 0;
54 }
```

```
6 0.5 -1 1 -1
=== Code Execution Successful ===
```