

# RASD 1.1 Generated HTML structure

```
<html>
```

```
<head>
```

```
<!-- HEAD script. Read from RASD_CLIENT.getHtmlJSLibrary (table documents - rasd/rasd_jslib.html) - GLOBAL settings -->
```

```
<!-- CUSTOM HEADER ON FORM_UIHEAD TRIGGER >> FORM -> CSS, JS source -> Form CSS, JS -->
```

```
    <style type="text/css">
```

```
<!-- CSS CODE ON FORM_CSS TRIGGER >> FORM -> CSS, JS source -> Form CSS, JS -->
```

```
</style>
```

```
<script type="text/javascript">
```

```
// JS CODE ON FORM_JS TRIGGER >> FORM -> CSS, JS source -> Form CSS, JS
```

```
</script>
```

```
</head>
```

HTML Header

```
<body>
```

```
<div id="DEMO_HTML_STRUCTURE_LAB" class="rasdFormLab">Demo RASD HTML structure
```

```
    <div id="rasdSpinner" class="rasdSpinner" style="display:none;"/>
```

```
</div>
```

FORM name with FORM  
spinner object

**rasdFormLab,**  
**rasdSpinner**

```
<div id="DEMO_HTML_STRUCTURE_MENU" class="rasdFormMenu">
```

```
    <!--Read from RASD_CLIENT.getHtmlMenuList - GLOBAL settings -->
```

```
</div>
```

FORM menu – link to other  
forms ...

**rasdFormMenu**

```
<form name="DEMO_HTML_STRUCTURE" method="post" action="?">
```

```
    <div id="DEMO_HTML_STRUCTURE_DIV" class="rasdForm">
```

FORM HEAD

**rasdFormHead**

```
        <div id="DEMO_HTML_STRUCTURE_HEAD" class="rasdFormHead">
```

```
            <input name="Hidden_FORM_field" id="Hidden_FORM_field_RASD" type="hidden" value=""/>
```

```
        </div>
```

```
<div id="DEMO_HTML_STRUCTURE_BODY" class="rasdFormBody">
```

FORM BODY

rasdFormBody

```
<div id="B01_DIV" class="rasdblock"><div>
```

```
<caption>
```

```
<div id="B01_LAB" class="labelblock">Block with 1 row</div>
```

```
</caption>
```

```
<table border="0" id="B01_TABLE">
```

```
<tr id="B01_BLOCK">
```

```
<span id="" value="1" name="" class="hiddenRowItems">
```

```
<input name="B01FIELDHID1_1" id="B01FIELDHID1_1_RASD" type="hidden" value=""/>
```

```
</span>
```

```
<td class="rasdTxB01FIELD1 rasdTxTypeC" id="rasdTxB01FIELD1_1">
```

```
<span id="B01FIELD1_LAB" class="label">Field 1 - charcter</span>
```

```
</td>
```

```
<td class="rasdTxB01FIELD1 rasdTxTypeC" id="rasdTxB01FIELD1_1">
```

```
<input name="B01FIELD1_1" id="B01FIELD1_1_RASD" type="text" value="" class="rasdTextC"/>
```

```
</td>
```

```
</tr><tr>
```

```
<td class="rasdTxB01FIELD2 rasdTxTypeN" id="rasdTxB01FIELD2_1">
```

```
<span id="B01FIELD2_LAB" class="label">Field 2 - number</span>
```

```
</td>
```

```
<td class="rasdTxB01FIELD2 rasdTxTypeN" id="rasdTxB01FIELD2_1">
```

```
<input name="B01FIELD2_1" id="B01FIELD2_1_RASD" type="text" value="" class="rasdTextN"/>
```

```
</td>
```

```
</tr><tr>
```

```
<td class="rasdTxB01FIELD3 rasdTxTypeD" id="rasdTxB01FIELD3_1">
```

```
<span id="B01FIELD3_LAB" class="label">Field 3 - date</span>
```

```
</td>
```

```
<td class="rasdTxB01FIELD3 rasdTxTypeD" id="rasdTxB01FIELD3_1">
```

```
<span id="B01FIELD3_1_RASD">
```

```
<input id="B01FIELD3_1" name="B01FIELD3_1" type="text" value="" class="rasdTextD"/>
```

```
</span>
```

```
</td>
```

```
</tr><tr>
```

```
<td class="rasdTxB01FIELD4 rasdTxTypeC" id="rasdTxB01FIELD4_1">
```

```
<span id="B01FIELD4_LAB" class="label">Field 4 - select list</span>
```

```
</td>
```

```
<td class="rasdTxB01FIELD4 rasdTxTypeC" id="rasdTxB01FIELD4_1">
```

```
<select name="B01FIELD4_1" ID="B01FIELD4_1_RASD" class="rasdSelect">
```

```
</select>
```

```
</td>
```

```
</tr><tr>
```

```
<td class="rasdTxB01FIELD5 rasdTxTypeC" id="rasdTxB01FIELD5_1">
```

```
<span id="B01FIELD5_LAB" class="label">Field 5 - radio list</span>
```

```
</td>
```

```
<td class="rasdTxB01FIELD5 rasdTxTypeC" id="rasdTxB01FIELD5_1">
```

```
<font id="B01FIELD5_1_RASD" class="rasdRadio">
```

```
</font>
```

```
</td>
```

BLOCK #1 (1 row)

labelblock rasdblock

Field label

rasdTxB01FIELD1 label

Field

rasdTxB01FIELD1 rasdTxTypeC

```
</tr></table></div></div>
```

```
<div id="B10_DIV" class="rasdblock">
```

```
<div>
```

```
<caption>
```

```
<div id="B10_LAB" class="labelblock">Block with many rows</div>
```

```
</caption>
```

```
<table border="1" id="B10_TABLE" class="rasdTableN display">
```

```
<thead>
```

```
<tr>
```

```
<td class="rasdTxB10FIELD1 rasdTxB10FIELD1" id="rasdTxB10FIELD1">
```

```
<span id="B10FIELD1_LAB" class="label">Field 1 text</span>
```

```
</td>
```

```
<td class="rasdTxB10FIELD2 rasdTxB10FIELD2" id="rasdTxB10FIELD2">
```

```
<span id="B10FIELD2_LAB" class="label">Field 2 number</span>
```

```
</td>
```

```
<td class="rasdTxB10FIELD3 rasdTxB10FIELD3" id="rasdTxB10FIELD3">
```

```
<span id="B10FIELD3_LAB" class="label">Field 3 date</span>
```

```
</td>
```

```
<td class="rasdTxB10FIELD4 rasdTxB10FIELD4" id="rasdTxB10FIELD4">
```

```
<span id="B10FIELD4_LAB" class="label">Sample field textarea</span>
```

```
</td>
```

```
<td class="rasdTxB10FIELD5 rasdTxB10FIELD5" id="rasdTxB10FIELD5">
```

```
<span id="B10FIELD5_LAB" class="label">Sample field select list</span>
```

```
</td>
```

```
</tr>
```

```
</thead>
```

```
<tr id="B10_BLOCK">
```

```
<span id="" value="1" name="" class="hiddenRowItems">
```

```
<input name="B10FIELDHID1_1" id="B10FIELDHID1_1_RASD" type="hidden" value=""/>
```

```
</span>
```

```
<td class="rasdTxB10FIELD1 rasdTxB10FIELD1" id="rasdTxB10FIELD1_1">
```

```
<font id="B10FIELD1_1_RASD" class="rasdFont">Sample text</font>
```

```
</td>
```

```
<td class="rasdTxB10FIELD2 rasdTxB10FIELD2" id="rasdTxB10FIELD2_1">
```

```
<font id="B10FIELD2_1_RASD" class="rasdFont">7816.83</font>
```

```
</td>
```

```
<td class="rasdTxB10FIELD3 rasdTxB10FIELD3" id="rasdTxB10FIELD3_1">
```

```
<font id="B10FIELD3_1_RASD" class="rasdFont">26.06.18</font>
```

```
</td>
```

```
<td class="rasdTxB10FIELD4 rasdTxB10FIELD4" id="rasdTxB10FIELD4_1">
```

```
<textarea name="B10FIELD4_1" id="B10FIELD4_1_RASD" class="rasdTextarea"/>
```

```
</td>
```

```
<td class="rasdTxB10FIELD5 rasdTxB10FIELD5" id="rasdTxB10FIELD5_1">
```

```
<select name="B10FIELD5_1" ID="B10FIELD5_1_RASD" class="rasdSelect">
```

```
</select>
```

```
</td>
```

```
</tr></table></div></div>
```

```
</div>
```

BLOCK #2 (many rows)

Labelblock rasdblock

Fields labels

rasdTxB10FIELD1 label

Field

rasdTxB10FIELD1+type ...

```
<div id="DEMO_HTML_STRUCTURE_MESSAGE" class="rasdFormMessage">
  <font id="MESSAGE_RASD" class="rasdFont">Message...</font>
</div>
```

FORM MESSAGE  
**rasdFormMessage**

```
<div id="DEMO_HTML_STRUCTURE_FOOTER" class="rasdFormFooter">
  <!--Read from RASD_CLIENT.getHtmlFooter - GLOBAL settings -->
</div>
```

FORM FOOTER  
**rasdFormFooter**

```
</div>
</form>
</body>
</html>
<div class="debug">LOG text ...<br/>
</div>
```

Preview of the code →

Agenda:

*Form name, block name or filed names  
are shown italic*

Reference class that can be  
used. Can be part of bloc,  
form, field name...

Demo RASD HTML structure

WELCOME

DEMO SAMPLE ▾

Block with 1 row

Field 1 - charcter

Field 2 - number

Field 3 - date

Field 4 - select list

Field 5 - radio list

Feild 6 - checkbox

Block with many rows

Search on table

Field 1 text	Field 2 number	Field 3 date	Sample field textarea	Sample field select list
Sample text	9918.04	26.06.18		N ▾
Sample text	1620.07	26.06.18		N ▾

LOG text ...

v.1.1.20180626132924 DEMO ()

