

Web-Programmierung

Aufgabe 3

Dominik Reimer
Max Michael Weber
Roland Roßkopf

Head/ Datenbank- verbindung

```
<?php
    include("includes/mysql.php");
    include("includes/shoppingcart.php");
    include("includes/sessionHandler.php");
?>

<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="UTF-8">
    <title>Toymodels GmbH</title>

    <link href="https://fonts.googleapis.com/css?family=Roboto" rel="stylesheet">
    <link rel="stylesheet" href="css/style.css" type="text/css" />
    <link rel="stylesheet" href="css/mobile.css" type="text/css" media="(max-width: 1024px)" />
    <link rel="stylesheet" href="css/print.css" type="text/css" media="print" />
    <link rel="shortcut icon" href="favicon.ico">
    <script src="js/script.js"></script>
</head>
```

```
<?php
    $host = 
    $database = 
    $username = 
    $password = 

    $pdo = new PDO("mysql:host=" . $host . ";dbname=" . $database, $username, $password);
?>
```

Session Handler

```
<?php
$session_timeout = 300;

if(!isset($_SESSION['last_visit']))
{
    $_SESSION['last_visit'] = time();
}

if(time()-$_SESSION['last_visit'] > $session_timeout)
{
    unset($_SESSION['shoppingcart']);
}

$_SESSION['last_visit'] = time();
?>
```


nav

```
<!-- Navigation -->
<nav>
  <a href="#">
    
  </a>
  <section id="burgerMenu">
    
  </section>
  <ul>
    <li><a href="#" alt="Home" class="active">Home</a></li>
  <?php
    if(!isset($_SESSION["customerId"])){
  ?>
    <li></li>
    <li><a href="register.php" alt="Register">Register</a></li>
  <?php
    }
  ?>
    <li></li>
    <li><a href="shoppingcart.php" alt="Shoppingcart">Shoppingcart</a></li>
    <li></li>
    <li><a href="impressum.php" alt="Impressum">Impressum</a></li>
  <?php
    if(isset($_SESSION["customerId"])){
  ?>
    <li></li>
    <li><a href="index.php?login=1" alt="Logout">Logout</a></li>
  <?php
    }
  ?>
    </ul>
  </nav>
```

Home | Register | Shoppingcart | Impressum

Home | Shoppingcart | Impressum | Logout

nav
mobile



nav
mobile

```
<section id="mobileNavigation">
  <ul>
    <li><a href="index.php" alt="Home" class="active">Home</a></li>
    <li><a href="register.php" alt="Register">Register</a></li>
    <li><a href="shoppingcart.php" alt="Shoppingcart">Shoppingcart</a></li>
    <li><a href="impressum.php" alt="Impressum">Impressum</a></li>
  </ul>
</section>

<?php
  if(isset($_SESSION["customerId"])){
  ?>
    <li><a href="index.php?login=1" alt="Logout">Logout</a></li>
  </li>
<?php
  }
?>
</ul>
</section>
```

```
function toggleNav() {
  var d = document.getElementById("mobileNavigation");
  var mobileNav = d.classList.contains("moveIn");
  console.log(d);

  if(mobileNav) {
    d.className = "moveOut";
    mobileNav = !mobileNav;
  }
  else {
    d.className = "moveIn";
    mobileNav = !mobileNav;
  }
}
```

nav mobile CSS

```
nav {  
  height: 180px;  
}  
  
nav #brand {  
  margin-top: 25px;  
}  
  
nav ul {  
  display: none;  
}  
  
nav #burgerMenu {  
  display: unset;  
  float: right;  
  height: 100%;  
}  
  
nav #burgerMenu img {  
  margin-top: 35px;  
  height: 100px;  
}  
  
#mobileNavigation {  
  display: unset;  
  top: 179px;  
  right: 100%;  
  width: 100%;  
  position: absolute;  
  height: calc(100% - 180px);  
  background-color: rgba(26, 26, 26, 0.99);  
  font-size: 7rem;  
}
```

```
.moveOut {  
  animation: moveOut 1s;  
}  
  
.moveIn {  
  animation: moveIn 1s;  
  right: 0% !important;  
}  
  
@keyframes moveIn {  
  from { right: 100%; }  
  to { right: 0%; }  
}  
  
@keyframes moveOut {  
  from { right: 0%; }  
  to { right: 100%; }  
}  
  
#mobileNavigation a {  
  color: #fff;  
  text-decoration: none;  
}
```

Login

Customer ID

Login

Hello, Carine Schmitt!

Login

```
<section id="login">
<?php
    if(!isset($_SESSION['username']))
    {
?>
        <form action="?login=0#login" method="post">
            <input type="text" name="customerId" placeholder="Customer ID">
            <input type="submit" value="Login" class="button">
        </form>
    <?php
    }
    else
    {
?>
        <h2>Hello, <?php echo $_SESSION['username']; ?>!</h2>
    <?php
    }

    if(isset($_GET["login"]) && $_GET["login"] == 1 && isset($_SESSION["username"])) {
        unset($_SESSION["customerId"], $_SESSION["username"]);
        header('Location: /toymodels');
    }

    if(isset($_GET["login"]) && $_GET["login"] == 0 && isset($_POST['customerId'])) {
        $statement = $pdo -> prepare("SELECT * FROM Kunden Where KundenNr = ?");
        $statement -> execute(array($_POST['customerId']));

        if($statement->rowCount() != 0) {
            $row = $statement->fetch();
            $_SESSION["username"] = trim($row['Vorname']) . " " . trim($row["Nachname"]);
            $_SESSION["customerId"] = $row["KundenNr"];

            header('Location: /toymodels#login');
        }
        else
        {
?>
            <p class="errorMsgLogin">
                Could not find User! Please Try again!
            </p>
        <?php
        }
    }
?>
</section>
```

Main

Search...

Vintage Cars

search



1969 Harley Davidson
Ultimate Chopper

Price: 95.70\$

Size: 1:10

Art-Num: S10_1678 -
Motorcycles



1970 Chevy Chevelle SS
454

Price: 73.49\$

Size: 1:24

Art-Num: S24_1046 -
Classic Cars



1952 Alpine Renault 1300

Price: 214.30\$

Size: 1:10

Art-Num: S10_1949 -
Classic Cars



1970 Dodge Coronet

Price: 57.80\$

Size: 1:24

Art-Num: S24_1444 -
Classic Cars

Main

```
</section>

<section id="searchfilter">
    <!-- Form for Filters, if selected, it will only show Articels in its section -->
    <form method="get" action="#searchfilter">
        <input type="search" name="search" placeholder="Search...">
        <select name="filter">
            <option value="" selected disabled>Please Select...</option>
            <option value="-1">All</option>
        </select>
        <input type="submit" value="search" class="button">
    </form>
</section>
<main id="articleMain">
    <!-- Placeholder for Articles -->
</main>

<?php
$sql = "SELECT * FROM Warengruppen";

foreach ($pdo -> query($sql) as $row) {
    echo '<option value="' . $row['GruppenNr'] . '">' . $row['GruppenName'] . '</option>';
}

</select>
<input type="submit" value="search" class="button">
</form>
</section>
<main id="articleMain">
    <!-- Placeholder for Articles -->
</main>

<?php
if (isset($_GET['search'], $_GET['filter'])) {
    if($_GET["search"] == "" && $_GET["filter"] != "-1")
    {
        $statement = $pdo -> prepare("SELECT * FROM Artikel LEFT JOIN Warengruppen on Artikel.GruppenNr=Warengruppen.GruppenNr WHERE Artikel.GruppenNr = ?");
        $statement -> execute(array($_GET['filter']));
    }

    if($_GET["search"] != "" && $_GET["filter"] != "-1")
    {
        $statement = $pdo -> prepare("SELECT * FROM Artikel LEFT JOIN Warengruppen on Artikel.GruppenNr=Warengruppen.GruppenNr WHERE Artikel.GruppenNr = ? AND Artikel.ArtikelName LIKE ?");
        $statement -> execute(array($_GET["filter"], '%' . $_GET['search'] . '%'));
    }

    if($_GET["search"] == "" && $_GET["filter"] == "-1")
    {
        $statement = $pdo -> prepare("SELECT * FROM Artikel LEFT JOIN Warengruppen on Artikel.GruppenNr=Warengruppen.GruppenNr");
        $statement -> execute();
    }
}

else {
    if(isset($_GET["search"])){
        $statement = $pdo -> prepare("SELECT * FROM Artikel LEFT JOIN Warengruppen on Artikel.GruppenNr=Warengruppen.GruppenNr WHERE Artikel.ArtikelName LIKE ?");
        $statement -> execute(array('%' . $_GET['search'] . '%'));
    }
    else
    {
        $statement = $pdo -> prepare("SELECT * FROM Artikel LEFT JOIN Warengruppen on Artikel.GruppenNr=Warengruppen.GruppenNr");
        $statement -> execute();
    }
}
```

Main

```
if($statement->rowCount() > 0){
    while($row = $statement->fetch()) {
?>
        <article>

        <section class="article-grid">
            <section class="img">
                
            </section>
            <section class="text" onClick="showDetail(<?php echo $row['ArtikelNr'] ?>_description)">
                <h2><?php echo $row['ArtikelName'] ?></h2>
                <p>Price: <?php echo $row['Listenpreis'] ?>$</p>
                <p>Size: <?php echo $row['Massstab'] ?></p>
                <p>Art-Num: <?php echo $row['ArtikelNr'] ?> - <?php echo $row["GruppenName"] ?></p>
            </section>
        </section>

        <section id="<?php echo $row['ArtikelNr'] ?>_description" class="description" >
            <section class="textDescription">
                <h2>Description</h2>
                <p><?php echo $row['Beschreibung'] ?></p>
            </section>
            <section id="buy">
                <h2>Quantity: <?php echo $row['Bestandsmenge']; ?></h2>

                <input type="number" id="<?php echo $row['ArtikelNr'] ?>" value="1"/>
                <input type="submit" class="button" value="Add to shoppingcart" onClick="buy('<?php echo $row['ArtikelNr'] ?>')">
            </section>
        </section>
    </article>

<?php
    }
} else {
    echo "<h2>Nothing found!</h2>";
}
?>
</main>
```

Artikel



1969 Harley Davidson
Ultimate Chopper

Price: 95.70\$

Size: 1:10

Art-Num: S10_1678 -
Motorcycles

Description

Our motorcycles are state of the art replicas of classic as well as contemporary motorcycle legends such as Harley Davidson, Ducati and Vespa. Models contain stunning details such as official logos, rotating wheels, working kickstand, front suspension, gear-shift lever, footbrake lever, and drive chain. Materials used include diecast and plastic. The models range in size from 1:10 to 1:50 scale and include numerous limited edition and several out-of-production vehicles. All models come fully assembled and ready for display in the home or office. Most include a certificate of authenticity.

Quantity: 7933

Add to shoppingcart



1952 Alpine Renault 1300

Price: 214.30\$

Size: 1:10

Art-Num: S24_1046 -



1970 Chevy Chevelle SS
454

Price: 73.49\$

Size: 1:24

Art-Num: S24_1046 -
Classic Cars



1970 Dodge Coronet

Price: 57.80\$

Size: 1:24

Art-Num: S24_1444 -
Classic Cars



1997 BMW R 1100 S

Price: 112.70\$

Size: 1:24

Art-Num: S24_1578 -
Motorcycles

Artikel

```
<article>

<section class="article-grid">
  <section class="img">
    
  </section>
  <section class="text" onClick="showDetail(<?php echo $row['ArtikelNr'] ?>_description)">
    <h2><?php echo $row['ArtikelName'] ?></h2>
    <p>Price: <?php echo $row['Listenpreis'] ?>$</p>
    <p>Size: <?php echo $row['Massstab'] ?></p>
    <p>Art-Num: <?php echo $row['ArtikelNr'] ?> - <?php echo $row["GruppenName"] ?></p>
  </section>
</section>

<section id="<?php echo $row['ArtikelNr'] ?>_description" class="description" >
  <section class="textDescription">
    <h2>Description</h2>
    <p><?php echo $row['Beschreibung'] ?></p>
  </section>
  <section id="buy">
    <h2>Quantity: <?php echo $row['Bestandsmenge']; ?></h2>

    <input type="number" id="<?php echo $row['ArtikelNr'] ?>" value="1"/>
    <input type="submit" class="button" value="Add to shoppingcart" onClick="buy('<?php echo $row['ArtikelNr'] ?>')">

  </section>
</section>

</article>
```

Artikel

```
function showDetail(b) {  
  var e = document.getElementById(b.id);  
  var detail = e.classList.contains("showDetail")  
  if(detail) {  
    e.className = "hideDetail";  
    detail = !detail;  
  }  
  else {  
    e.className = "showDetail";  
    detail = !detail;  
  }  
}
```

```
.hideDetail {  
  display: none;  
}  
  
.showDetail {  
  display: inherit;  
}
```

Warenkorb

Shopping Cart

Your Shopping Cart is empty.



1962 City of Detroit Streetcar

Amount:

[Change](#)

Preis:
234.32
€



1950's Chicago Surface Lines
Streetcar

Amount:

[Change](#)

Preis:
186.42
€

Gesamtpreis:

420.74

[Proceed to checkout](#)

Ihre Auftrags Nummer: 10451

Geplanter Liefertermin: 2019-06-03

Gesamter Preis: 191.40

Warenkorb

```
<?php
    if(!isset($_GET["checkout"])){

?>
        <h2>Shopping Cart</h2>
        <section id="shoppingcartElement">
<?php
    if(isset($_SESSION["shoppingcart"]) && sizeof($_SESSION["shoppingcart"]) > 0)
    {
        $gesamtPreis = 0;

        //unset($_SESSION["shoppingcart"]);
        foreach($_SESSION["shoppingcart"] as $article => $value) {
            $statement = $pdo -> prepare("SELECT * FROM Artikel WHERE ArtikelNr = ?");
            $statement -> execute(array($article));

            $row = $statement->fetch();

            $gesamtPreis += $row["Listenpreis"] * $value;

?>
        <article id="<?php echo $article; ?>">
            <section class="img">
                
            </section>

            <section class="text">
                <h3><?php echo $row["ArtikelName"]; ?></h3>
            </section>
            <section class="quantity">
                Amount: <input type="number" min="0" name="<?php echo $article; ?>" value="<?php echo $value; ?>" /><br><br>
                <button class="button" onClick="change('<?php echo $article; ?>')">Change</button>
            </section>
            <section class="price">
                <p style="display: none" class="singlePrice"><?php echo $row["Listenpreis"]; ?></p>
                Preis: <p class="sumPrice"><?php echo $row["Listenpreis"] * $value; ?></p>€
            </section>
        </article>
<?php
    }
?>
    <section>
        <p>Gesamtpreis: <p id="endPrice"><?php echo $gesamtPreis; ?></p></p>
    </section>
</section>
```

Warenkorb

```
<?php
    if (isset($_SESSION["customerId"])){
?>
        <section id="checkout">
            <!-- Form for submitting Buy action -->

            <form method="post" action="?checkout=-1">
                <textarea name="comment" placeholder="Comment"></textarea><br>
                <input type="submit" class="button" value="Proceed to checkout">
            </form>
        </section>
    <?php
    }
    }
    else
    {
?>
        <section id="shoppingcartElement">
            <p>Your Shopping Cart is empty.</p>
        </section>
        <?php
        }
        //unset($_SESSION["shoppingcart"]);
    }
    else{
        if($_GET["checkout"] == -1)
        {
            Buy($_POST["comment"]);
        }else {
            $statement = $pdo -> prepare("SELECT * FROM Auftraege WHERE AuftragsNr = ?");
            $statement -> execute(array($_GET["checkout"]));

            $row = $statement->fetch();
?>
            <h3>Ihre Auftrags Nummer: <?php echo $row["AuftragsNr"]; ?></h3>
            <p>Geplanter Liefertermin: <?php echo $row["Plantermin"]; ?></p>
            <p>Gesamter Preis: <?php echo number_format($_GET["price"] / 100, 2); ?></p>
        <?php
        }
    }
?>
</main>
```

```

<script>
function buy(artNr){
    var amount = document.getElementById(artNr).value;
    var xhr = new XMLHttpRequest();
    xhr.open('POST', '/toymodels/includes/shoppingcart.php?buy=1');
    xhr.setRequestHeader('Content-Type', 'application/x-www-form-urlencoded');
    xhr.onload = function() {
    }
    xhr.send(encodeURIComponent('artNr=' + artNr + '&amount=' + amount));
}

function change(artNr){
    var amount = document.getElementsByName(artNr)[0].value;
    var xhr = new XMLHttpRequest();
    xhr.open('POST', '/toymodels/includes/shoppingcart.php?buy=2');
    xhr.setRequestHeader('Content-Type', 'application/x-www-form-urlencoded');
    xhr.onload = function() {
    }
    xhr.send(encodeURIComponent('artNr=' + artNr + '&amount=' + amount));

    let listenpreis =
document.getElementById(artNr).getElementsByClassName("singlePrice")[0].innerText;
    document.getElementById(artNr).getElementsByClassName("sumPrice")[0].innerText =
listenpreis * amount;

    changeSum();
}

function changeSum()
{
    var articles = document.getElementsByTagName("article");
    var sum = 0;
    for(var i = 0; i < articles.length; i++) {
        var price =
parseFloat(articles[i].getElementsByClassName("sumPrice")[0].innerHTML);
        sum += price;
    }

    document.getElementById("endPrice").innerHTML = sum;
}
</script>
<?php
session_start();
function Add($article, $amount)
{
    $found = false;

```

```

    if(isset($_SESSION["shoppingcart"]))
        foreach ($_SESSION["shoppingcart"] as $key => $value)
        {
            if ($key == $article)
            {
                $value = $value + $amount;
                $_SESSION["shoppingcart"][$key] = $value;
                $found = true;
            }
        }

    if(!$found)
    {
        $_SESSION["shoppingcart"][$article] = $amount;
    }

    echo "Done";
}

function Remove($article)
{
    if(isset($_SESSION["shoppingcart"][$article]))
    {
        unset($_SESSION["shoppingcart"][$article]);
    }
}

function SetValue($article, $amount)
{
    if(isset($_SESSION["shoppingcart"]))
        foreach ($_SESSION["shoppingcart"] as $key => $value)
        {
            if ($key == $article)
            {
                $_SESSION["shoppingcart"][$key] = $amount;
            }
        }

    if($amount == 0) {
        Remove($article);
    }
}

```

```

function Buy($info)
{
    $auftragsNr = 0;
    $totalSum = 0;
    if(isset($_SESSION["customerId"]))
    if(isset($_SESSION["shoppingcart"]) && sizeof($_SESSION["shoppingcart"]) > 0)
    {
        require("mysql.php");
        //2015-05-30
        $date = date("Y-m-d");
        $plantermin = date("Y-m-d", strtotime("+12 days"));
        $statement = $pdo -> prepare("INSERT INTO Auftraege (Auftragsdatum, Plantermin,
Status, Bemerkungen, KundenNr) VALUES (?, ?, ?, ?, ?)");
        $statement->execute(array($date, $plantermin, "in Bearbeitung", $info,
$_SESSION["customerId"]));

        $auftragsNr = $pdo ->lastInsertId();

        foreach($_SESSION["shoppingcart"] as $key => $value)
        {
            $row = getInfoArticle($key);

            $statement = $pdo -> prepare("INSERT INTO Auftragspositionen (AuftragsNr,
ArtikelNr, Bestellmenge, Verkaufspreis, PositionsNr) VALUES (?, ?, ?, ?, ?)");
            $statement -> execute(array($auftragsNr, $key, $value, $row["Listenpreis"],
$row["GruppenNr"]));
            $totalSum += $row["Listenpreis"] * $value;

            $statement = $pdo -> prepare("UPDATE Artikel SET Bestandsmenge = Bestandsmenge -
? WHERE ArtikelNr = ?");
            $statement -> execute(array($value, $key));
        }
    }
}

```

```

unset($_SESSION["shoppingcart"]);

$totalSum = number_format($totalSum, 2) * 100;

header("Location: /toymodels/shoppingcart.php?checkout=" . $auftragsNr . "&price=" .
$totalSum);
}

function getInfoArticle($article)
{
    require("mysql.php");

    $statement = $pdo -> prepare("SELECT * FROM Artikel WHERE ArtikelNr = ?");
    $statement -> execute(array($article));

    $row = $statement->fetch();

    return $row;
}

if(isset($_GET["buy"]) && $_GET["buy"] == 1)
{
    Add($_POST["artNr"], $_POST["amount"]);
}
if(isset($_GET["buy"]) && $_GET["buy"] == 2)
{
    SetValue($_POST["artNr"], $_POST["amount"]);
}
?>

```

Registrierung

Register

Firstname:	<input type="text"/>
Surname:	<input type="text"/>
Telefon:	<input type="text"/>
Company:	<input type="text"/>
Address:	<input type="text"/>
Location:	<input type="text"/>
Country:	<input type="text"/>
Postcode:	<input type="text"/>

Registrierung

```
<?php
    if(!isset($_GET["register"]))
    {
?>
        <h1>Register</h1>
        <form method="post" action="?register=0">
            <label for="firstname">Firstname:</label>
            <input onfocusout="checkNotEmpty(this)" onkeypress="updateButton()" type="text" name="firstname" placeholder="Firstname"> <br>

            <label for="surename">Surename:</label>
            <input onfocusout="checkNotEmpty(this)" onkeypress="updateButton()" type="text" name="surename" placeholder="Surename"> <br>

            <label for="telefon">Telefon:</label>
            <input onfocusout="checkIsNumber(this)" onkeypress="updateButton()" type="text" name="telefon" placeholder="Telefon"> <br>

            <label for="company">Company:</label>
            <input onfocusout="checkNotEmpty(this)" onkeypress="updateButton()" type="text" name="company" placeholder="Company"> <br>

            <label for="address">Address:</label>
            <input onfocusout="checkNotEmpty(this)" onkeypress="updateButton()" type="text" name="address" placeholder="Address"> <br>

            <label for="location">Location:</label>
            <input onfocusout="checkNotEmpty(this)" onkeypress="updateButton()" type="text" name="location" placeholder="Location"> <br>

            <label for="country">Country:</label>
            <input onfocusout="checkNotEmpty(this)" onkeypress="updateButton()" type="text" name="country" placeholder="Country"> <br>

            <label for="postcode">Postcode:</label>
            <input onfocusout="checkIsNumber(this)" onkeypress="updateButton()" maxlength="5" name="postcode" placeholder="Postcode"> <br>
            <br>
            <input type="reset" value="Reset">
            <input type="submit" value="Register" name="submitRegister" disabled>
        </form>
    <?php
```

Registrierung updateButton()

```
function updateButton()
{
    var firstname = document.getElementsByName("firstname")[0];
    var lastname = document.getElementsByName("surename")[0];
    var telefon = document.getElementsByName("telefon")[0];
    var company = document.getElementsByName("company")[0];
    var address = document.getElementsByName("address")[0];
    var location = document.getElementsByName("location")[0];
    var country = document.getElementsByName("country")[0];
    var postcode = document.getElementsByName("postcode")[0];

    var inputs = [firstname, lastname, telefon, company, address, location, country, postcode];

    var submit = document.getElementsByName("submitRegister")[0];

    var errorFound = false;

    inputs.forEach(function(item){
        if(item.value == "") {
            errorFound = true;
        }
        if(item.className == "inputError"){
            errorFound = true;
        }
    });

    submit.disabled = errorFound;
}
```

Registrierung
checkNotEmpty()

```
function checkNotEmpty(element)
{
  if(element.value == "")
  {
    element.className = "inputError";
  }
  else
  {
    element.className = "";
  }

  updateButton();
}
```


Registrierung
checkIsNumber()

```
function checkIsNumber(element)
{
    if(element.value == "")
    {
        element.className = "inputError";
    }
    else
    {
        var pattern = new RegExp('^\\d+$');
        if(!pattern.test(element.value))
        {
            element.className = "inputError";
        }
        else
        {
            element.className = "";
        }
    }

    updateButton();
}
```

Registrierung

```
}else
{
    if($_GET["register"] == 0)
    {
        $firstname = trim($_POST["firstname"]);
        $surename = trim($_POST["surename"]);
        $telefon = trim($_POST["telefon"]);
        $company = trim($_POST["company"]);
        $address = trim($_POST["address"]);
        $location = trim($_POST["location"]);
        $country = trim($_POST["country"]);
        $postcode = trim($_POST["postcode"]);

        if($firstname != "" && $surename != "" && $telefon != "" && $company != "" && $address != "" && $location != "" && $country != "" && $postcode != "")
        {
            //GET RANDOM VORGESETZEN
            $statement = $pdo->prepare("SELECT PersonalNr FROM Mitarbeiter ORDER BY RAND() LIMIT 1");
            $statement -> execute();

            $PersonalNr = $statement->fetch()["PersonalNr"];

            $statement = $pdo->prepare("INSERT INTO Kunden (Firma, Nachname, Vorname, Telefon, Strasse, Ort, PLZ, Land, Kundenbetreuer) VALUES (?, ?, ?, ?, ?, ?, ?, ?, ?)");
            $statement -> execute(array($company, $surename, $firstname, $telefon, $address, $location, $postcode, $country, $PersonalNr));

            $newID = $pdo->lastInsertId();
            $_SESSION["customerId"] = $newID;
            $_SESSION["username"] = $firstname . " " . $surename;
            echo "<h1>Registration Successfull! Your ID: " . $newID . ". <a href='index.php'>Main</a></h1>";
        }
        else
        {
            echo "<h1>Error, please try again! <a href='register.php'>HERE</a></h1>";
        }
    }
}

?>
```

Footer

```
<!-- Footer -->
<?php
    include("includes/footer.html");
?>
</body>
```

About

Address:
Toymodels GmbH
Joachimstaler Str. 52
97234 Reichenberg

Telefon:
+49 6771 62 55 99

Links

[Home](#)
[Register](#)
[Shoppingcart](#)
[Impressum](#)

Impressum

[Impressum](#)