INPUT

```cpp
#include <iostream>
using namespace std;

int main () {
    double service, rating;

    cout << "Years of service: ";
    cin >> service;

    if (service >= 10) {
        cout << "RATING: ";
        cin >> rating;

        if (rating >= 4 && rating <= 5 ) {
            cout << "Bonus: ₱20,000";
        }
        else if (rating >= 2 && rating <= 3) {
            cout << "Bonus: ₱15,000";
        }
        else if (rating >= 1 && rating < 2) {
            cout << "Bonus: ₱10,000";
        }

    }
```

```cpp
    else if (service >= 5 && service <= 9) {
        cout << "RATING: ";
        cin >> rating;

        if (rating >= 4 && rating <= 5 ) {
            cout << "Bonus: ₱15,000";
        }
        else if (rating >= 2 && rating <= 3) {
            cout << "Bonus: ₱10,000";
        }
        else if (rating >= 1 && rating < 2) {
            cout << "Bonus: ₱5,000";
        }
```

```cpp
    else if (service < 5) {
        cout << "RATING: ";
        cin >> rating;

        if (rating >= 4 && rating <= 5 ) {
            cout << "Bonus: ₱10,000";
        }
        else if (rating >= 2 && rating <= 3) {
            cout << "Bonus: ₱5,000";
        }
        else if (rating >= 0 && rating < 2) {
            cout << "No Bonus.";
        }
    }
```

OUTPUT

Output

```
Years of service: 10
RATING: 4
Bonus: ₱20,000

=== Code Execution Successful ===
```

Output

```
Years of service: 10.5
RATING: 2.7
Bonus: ₱15,000

=== Code Execution Successful ===
```

Output

```
Years of service: 7.5
RATING: 4.2
Bonus: ₱15,000

=== Code Execution Successful ===
```

Output

```
Years of service: 7
RATING: 3
Bonus: ₱10,000

=== Code Execution Successful ===
```

Output

```
Years of service: 3
RATING: 1
No Bonus.

=== Code Execution Successful ===
```

Output

```
Years of service: 1.8
RATING: 2.9
Bonus: ₱5,000

=== Code Execution Successful ===
```

The program posted on the document follows the given direction of the seatwork where the machine asks the user its years of service and rating that corresponds to a certain bonus. The normal approach for this situation is to use the switch function, since there are a lot of choices to consider, however, I took a tiny step further and decided to make the program also applicable for decimal numbers since the switch function does not have the ability to handle decimal numbers but years of service and ratings are realistically possible to take in decimal values (e. g. 10 years and 5 months is actually 10.5 and a 4.5 rating is also possible). Instead of using switch, the program utilized the if-else if function wherein it first asks the user the service years before asking it again for the ratings and give its corresponding bonuses as the output. To make it possible for decimal numbers to work, I used the data type variable of double since it can take decimal numbers and it is precise. Other pictures are posted to show the validation that whole and decimal numbers work and does not make the program have an error or be ambiguous.