

Contents

1	Introduction	1
2	Objective	2
3	Problem Statements	2
4	Data Collection	2
5	MBTI in Measurement	5
5.1	Data Cleaning and Pre-processing	5
5.1.1	Handling Missing Values	5
5.1.2	Outlier Detection and Correction	6
5.1.3	Export the cleaned data	6
5.2	Model Building and Evaluation	7
5.3	Exploratory Data Analysis (EDA)	11
5.3.1	MBTI Type Frequency	11
5.3.2	Distribution of MBTI Dimension Scores	12
5.3.3	Descriptive Statistics of MBTI Dimensions	13
5.3.4	Correlation Analysis Between MBTI Dimensions	14
6	MBTI in Manifestation	15
6.1	Topic Preferences of MBTI Personalities	16
6.1.1	Data Cleaning	16
6.1.2	LDA modeling	30
6.1.3	Result Visualization and Topic Evaluation	36
6.1.4	Topic Distribution	46
6.1.5	MBTI type Clustering	54
6.2	Expressive Patterns of MBTI Personalities	60
6.2.1	Data Cleaning and Pre-processing	60
6.2.2	Linguistic Style Patterns of MBTI Types	61
6.2.3	Sentiment Analysis	68
7	Conclusion	73

References	74
-------------------	-----------

1 Introduction

With the recent renewal of the MBTI's popularity, posts or analyses about it have become widespread on public platforms. It seems that MBTI has become a way people use at first meetings.

The Myers-Briggs Type Indicator (MBTI) is a psychological framework primarily used to describe and measure personality traits by categorizing individuals into four dichotomous dimensions. In essence, it aims to reflect how people perceive the world and make decisions based on their internal experiences(Yang, 2022).

To determine one's type, the test asks a series of questions, usually focused on a person's tendencies or preferences. Based on the responses, individuals receive a result represented by four letters, each corresponding to one of the four bipolar dimensions. According to Pittenger (2005), these four dichotomous dimensions classify individuals as either extraverted (E) or introverted (I), sensing (S) or intuitive (N), thinking (T) or feeling (F), and judging (J) or perceiving (P). Combinations of the four preferences generate one of 16 personality types (e.g., ESFJ, ENFP, INTP, ISFJ), each associated with distinct behavioral tendencies, reflecting differences in attitudes, orientation, and decision-making styles. Also, on the official website, it will provide the future career options for you, like INFP, which may be more suitable for being an author. The percentage of each standard will also show in the final result.

And based on the 16 personality types, it can be divided into four groups . As each role depends on two shared traits that they have in common, the four groups are: Analysts, who share the Intuitive and Thinking traits (NT); Diplomats, who share the Intuitive and Feeling traits (NF); Sentinels, who share the Observant and Judging traits (S_J); and Explorers, who share the Observant and Prospecting traits (S_P) (16Personalities, n.d.). And the Myers-Briggs Type Indicator (MBTI) sorts them into four colors, as the purple color represents Analysts, the green color represents Diplomats, the blue color represents Sentinels, and the yellow color represents Explorers.

The MBTI provides a widely recognized and accessible way to understand personality, making it a useful foundation for further behavioral and data-driven analysis. However, it has also attracted criticism as some thought the result of the MBTI test was not reliable. As it may bring some stereotypes when forming impressions of others.

Given its popularity and sustaining controversy, our group decided to explore the MBTI

more deeply and explore the rationality of this test.

2 Objective

1. Evaluate the reliability of the MBTI from a statistical perspective.
2. Explore the potential application of MBTI in social media behavior analysis.
3. Help people better understand personality traits and behavioral patterns.
4. Helping people eliminate stereotypes caused by MBTI personality types.

3 Problem Statements

1. Are the results of the MBTI personality test statistically robust and reliable?
2. Do the four dimensions of MBTI work independently, or are they connected in some way?
3. Do people with different MBTI types have different levels of activity on the internet?
4. Do significant differences exist in the interest preferences and behavioral patterns of different MBTI personality types on social networking sites?

4 Data Collection

1. “KPMIRU Questionnaires Data”

The dataset was derived from a large-scale MBTI questionnaire response collection of 100,000 entries, shared on Kaggle by Pmenshih (<https://www.kaggle.com/datasets/pmenshih/kpmiru-questionnaires-data>). While each record originally includes binary responses to 63 forced-choice items (q1–q63) and accompanying numeric flags or timestamps (t1–t63), our analysis does not directly employ the individual item data. Instead, we leverage the two key derived outputs:

- Four-letter MBTI type (psychotype), e.g. “ENTP” or “ISFJ,” which provides a coarse segmentation of personality.

- Numeric dimension scores (e, i, s, n, t, f, j, p), each representing the total count of selections for that pole. These eight integer scores supply a continuous measure of preference intensity on each axis, which is essential for plotting score distributions, computing summary statistics, and conducting comparative dimension analyses across the sample.

2. “MBTI Personality Type Twitter Dataset”

The MBTI Personality Type Twitter Dataset was originally compiled via the public Twitter API and later released on Kaggle by Mazlumi (<https://www.kaggle.com/datasets/mazlumi/mbti-personality-type-twitter-dataset>). The version employed here comprises 7,811 user records, each pairing a self-declared MBTI label (e.g., “ENTP”) with the user’s tweet content in raw form—hashtags, emojis, URLs, and @ (mention someone). This resource supports investigations of linguistic style, personality cues, and social-behavior patterns as reflected in self-identified MBTI categories.

However, the dataset is markedly imbalanced: some personality types are over-represented while others appear only sparsely. Besides, this dataset is hard to clean since people’s grammar on social media posts is quite casual, often including internet slang and non-standard abbreviations (e.g., “ur” means “you are”). Also, this dataset contains non-English text, making data cleaning even harder. Lastly, social-media text is notoriously noisy; even after extensive preprocessing, the corpus—about 7,800 tweet documents and replies, each averaging roughly 3,000 words—still falls short of capturing the full thematic breadth and linguistic diversity of the Twitter platform.

By bringing together these two complementary datasets, we arrive at a balanced, evidence-based view of MBTI’s strengths and limits.

```
import pandas as pd
# Read data
data = pd.read_csv(r'E:\python\kpmi_ru_data.csv\kpmi_ru_data.csv')
print(data)
```

	q1	t1	q2	t2	q3	t3	q4	t4	q5	t5	...	t63	e	i	s	n	t	\
0	1	8	2	8	2	8	1	8	1	8	...	8	32	18	16	19	26	
1	1	8	1	8	1	8	2	8	1	8	...	8	28	15	27	18	23	
2	1	8	1	8	1	8	1	8	1	8	...	8	25	15	25	16	19	
3	2	8	1	8	1	8	1	8	1	8	...	8	30	15	25	14	33	
4	2	8	2	8	1	8	1	8	1	8	...	8	22	22	23	18	33	
...	
99995	1	8	2	8	1	8	2	8	2	8	...	8	32	18	27	16	33	
99996	1	8	2	8	2	8	1	8	2	8	...	8	20	26	37	12	37	
99997	1	8	2	8	1	8	1	8	1	8	...	8	22	18	23	19	26	
99998	2	8	2	8	1	8	1	8	1	8	...	8	22	18	21	23	33	
99999	1	8	1	8	1	8	1	8	2	8	...	8	38	9	39	12	37	

	f	j	p	psychotype
0	24	19	44	ENTP
1	30	35	29	ESFJ
2	35	38	23	ESFJ
3	27	38	23	ESTJ
4	13	29	35	ISTP
...
99995	19	13	52	ESTP
99996	13	29	29	ISTP
99997	22	29	38	ESTP
99998	19	32	29	ENTJ
99999	22	45	23	ESTJ

[100000 rows x 133 columns]

Figure 4.1: Reading KPMIRU Questionnaires Data

```
import pandas as pd
# Read data
data = pd.read_csv(r"E:\python\twitter_MBTI.csv")
print(data)
```

	Unnamed: 0		text	label
0	0	@Pericles216 @HierBeforeTheAC @Sachinettiyl T...	intj	
1	1	@Hispanthicckk Being you makes you look cute ...	intj	
2	2	@Alshymi Les balles sont réelles et sont tirée...	intj	
3	3	I'm like entp but idiotic Hey boy, do you wa...	intj	
4	4	@kaeshurr1 Give it to @ZargarShanif ... He has...	intj	
...	
7806	7806	@sobsjjun God,,pls take care 🥺 @sobsjjun Hir...	intp	
7807	7807	@Ignis_02 wow last time i got intp https://t.c...	intp	
7808	7808	@akupilled A 100% @akupilled That SOMEONE wi...	entp	
7809	7809	If you're #INTJ this one is for you What is ...	infj	
7810	7810	@harry__lambert @gucci hey can you dm me a pic...	istp	

[7811 rows x 3 columns]

Figure 4.2: Reading MBTI Personality Type Twitter Dataset

As illustrated in the two Figures above, the combined Kaggle sources provide information on:

1. Self-reported MBTI types for each respondent
2. Raw Twitter posts and basic tweet metadata linked to those MBTI labels
3. Demographic and psychometric questionnaire answers (KPMIRU survey)
4. Behavioral metrics such as posting frequency and topic keywords extracted from the tweets

5 MBTI in Measurement

5.1 Data Cleaning and Pre-processing

5.1.1 Handling Missing Values

1. We use `dropna()` to eliminate any records with missing or null entries. Fortunately, the dataset had no missing psychotype labels or scoring data.

```
1 # Delete null values
2 df_clean = df.dropna()
```

5.1.2 Outlier Detection and Correction

1. Outliers in numeric scores were identified using the **IQR (interquartile range) method**.
2. For each numeric column, we computed Q1, Q3. $IQR = Q3 - Q1$ represent the middle 50% of the data distribution. The `lower_bound` and `upper_bound` represent the boundaries of the normal range under the Interquartile Range Rule (IQR). And then we replaced values outside $[Q1 - 1.5 \times IQR, Q3 + 1.5 \times IQR]$ with the column median.
3. The median substitution method mainly serves to stabilize the overall distribution and avoid the influence of extreme values.

```

1  # Select all columns in df_clean with numeric data types (either int
    or float) in preparation for outlier processing.
2  numeric_cols = df_clean.select_dtypes(include='number').columns
3
4  # Replace the outliers (utilizing the Interquartile Range (IQR) rule)
    with the median value of the column.
5  df_processed = df_clean.copy()
6
7  for col in numeric_cols:
8      Q1 = df_processed[col].quantile(0.25)
9      Q3 = df_processed[col].quantile(0.75)
10     IQR = Q3 - Q1
11     lower_bound = Q1 - 1.5 * IQR
12     upper_bound = Q3 + 1.5 * IQR
13     median_value = df_processed[col].median()
14
15     # Replace outliers
16     df_processed[col] = df_processed[col].apply(lambda x: median_value
        if x < lower_bound or x > upper_bound else x)
    
```

5.1.3 Export the cleaned data

After completing the outlier replacement and data cleaning process, we used `df.info()` to verify the integrity and structure of the cleaned dataset. The cleaned DataFrame was then exported using the `to_csv()` method, which saved it as `kpmi_ru_data(Cleaned).csv` for downstream analysis. The `index=False` parameter ensured that row indices were not written to the CSV file.


```

1 print(df_processed.info())
2 print(df_processed)
3 df_processed.to_csv(r'E:\python\kpmi_ru_data(Cleaned).csv', index = False)

```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 100000 entries, 0 to 99999
Columns: 133 entries, q1 to psychotype
dtypes: float64(75), int64(57), object(1)
memory usage: 101.5+ MB
None

```

	q1	t1	q2	t2	q3	t3	q4	t4	q5	t5	...	t63	e	i	\
0	1	8.0	2	8.0	2	8.0	1	8.0	1	8.0	...	8.0	32.0	18.0	
1	1	8.0	1	8.0	1	8.0	2	8.0	1	8.0	...	8.0	28.0	15.0	
2	1	8.0	1	8.0	1	8.0	1	8.0	1	8.0	...	8.0	25.0	15.0	
3	2	8.0	1	8.0	1	8.0	1	8.0	1	8.0	...	8.0	30.0	15.0	
4	2	8.0	2	8.0	1	8.0	1	8.0	1	8.0	...	8.0	22.0	22.0	
...
99995	1	8.0	2	8.0	1	8.0	2	8.0	2	8.0	...	8.0	32.0	18.0	
99996	1	8.0	2	8.0	2	8.0	1	8.0	2	8.0	...	8.0	20.0	26.0	
99997	1	8.0	2	8.0	1	8.0	1	8.0	1	8.0	...	8.0	22.0	18.0	
99998	2	8.0	2	8.0	1	8.0	1	8.0	1	8.0	...	8.0	22.0	18.0	
99999	1	8.0	1	8.0	1	8.0	1	8.0	2	8.0	...	8.0	38.0	9.0	

	s	n	t	f	j	p	psychotype
0	16.0	19.0	26.0	24.0	19.0	44.0	ENTP
1	27.0	18.0	23.0	30.0	35.0	29.0	ESFJ
2	25.0	16.0	19.0	35.0	38.0	23.0	ESFJ
3	25.0	14.0	33.0	27.0	38.0	23.0	ESTJ
4	23.0	18.0	33.0	13.0	29.0	35.0	ISTP
...
99995	27.0	16.0	33.0	19.0	13.0	52.0	ESTP
99996	37.0	12.0	37.0	13.0	29.0	29.0	ISTP
99997	23.0	19.0	26.0	22.0	29.0	38.0	ESTP
99998	21.0	23.0	33.0	19.0	32.0	29.0	ENTJ
99999	39.0	12.0	37.0	22.0	45.0	23.0	ESTJ

[100000 rows x 133 columns]

The data in the figure 3.1 is the data after our data cleaning.

5.2 Model Building and Evaluation

Chi-square test is an on parametric statistical test to determine if the two or more classifications of the samples are independent or not (Zibran, 2007). We all know that MBTI has four dimensions (Extraversion–Introversion (E–I), Sensing–Intuition (S–N), Thinking–Feeling (T–F) and Judging–Perceiving (J–P)). But whether or not these four dimensions interrelated or independent of each other stays unknown. For explanation, let's consider the data presented in Figure 3.1 which comprising 100 000 respondents, providing information on the scoring fields of the four dimensions of MBTI. In order to find the answer, we use the chi-square test.

Each respondent's type label (e.g., ENTP) was decomposed into its four constituent letters, and the sample was cross-classified into a $2 \times 2 \times 2 \times 2$ contingency table (16 cells)(shown in figure 3.2)

```

1 import pandas as pd
2 import numpy as np
3 from scipy.stats import chi2
4
5 # 1) Read in the cleaned CSV.
6 FILE_PATH = r"E:\python\kpmi_ru_data(Cleaned).csv"
7 df = pd.read_csv(FILE_PATH)
8
9 # 2) Extract the columns of four dimensions .IE, SN, TF, JP
10 mbti = df['psychotype'].astype(str).str.upper().dropna()
11 df_dims = pd.DataFrame({
12     'IE': mbti.str[0],    # E   I
13     'SN': mbti.str[1],    # S   N
14     'TF': mbti.str[2],    # T   F
15     'JP': mbti.str[3]     # J   P
16 })
17
18 # 3) Construct a 2x2x2x2 contingency table: Obtain the observed frequencies
    of 16 cells. counts[i,j,k,l]
19 import pandas as pd
20 import numpy as np
21
22 # Define dimension labels
23 index = pd.MultiIndex.from_product(
24     [['E', 'I'], ['S', 'N'], ['T', 'F'], ['J', 'P']],
25     names=['IE', 'SN', 'TF', 'JP']
26 )
27
28 # Build a DataFrame, using the values of counts as columns.
29 counts_df = pd.DataFrame({
30     'Count': counts.flatten()
31 }, index=index)
32
33 print(counts_df.head(10))
    
```

Then we calculate the marginal distribution (the distribution of each dimension separately). For

example, $N_{IE} = [\text{count}(E), \text{count}(I)]$ (shown in ??)

```

1 # Calculate marginal distribution and total number
2 N_IE = counts.sum(axis=(1,2,3))
3 N_SN = counts.sum(axis=(0,2,3))
4 N_TF = counts.sum(axis=(0,1,3))
5 N_JP = counts.sum(axis=(0,1,2))
6 N = counts.sum()
7
8
9 marginals = pd.DataFrame({
10     'Dimension': ['IE', 'IE', 'SN', 'SN', 'TF', 'TF', 'JP', 'JP'],
11     'Category': ['E', 'I', 'S', 'N', 'T', 'F', 'J', 'P'],
12     'Count': np.concatenate([N_IE, N_SN, N_TF, N_JP])
13 })
14
15
16 print(marginals)
    
```

Under the null hypothesis of mutual independence, the expected frequency in each cell was computed as the product of the four one-dimensional marginal distributions multiplied by the sample size(shown in ??).

```

1 #Calculate the expected frequency E[i,j,k,l] of each cell based on the
   completely independent assumption.
2 E = np.zeros_like(counts, dtype=float)
3 for i in range(2):
4     for j in range(2):
5         for k in range(2):
6             for l in range(2):
7                 E[i,j,k,l] = (
8                     (N_IE[i]/N) *
9                     (N_SN[j]/N) *
10                    (N_TF[k]/N) *
11                    (N_JP[l]/N)
12                ) * N
13
14 index = pd.MultiIndex.from_product(
15     [['E', 'I'], ['S', 'N'], ['T', 'F'], ['J', 'P']],
16     names=['IE', 'SN', 'TF', 'JP']
    
```

```

17 )
18
19 expected_df = pd.DataFrame({
20     'Expected_Count': E.flatten()
21 }, index=index).round(2)
22
23 print(expected_df)

```

Now, it's time to calculate the Pearson chi-square statistic, while O is observed value and E is expected value.

$$\chi^2 = \sum \frac{(O - E)^2}{E}$$

```

1 chi2_stat = ((counts - E)**2 / E).sum()
2 chi2_stat

```

With this code, we obtain the Pearson chi-square statistic, which is 1342.93063615322.

Finally, with $\chi^2 = 1342.93$ and $df = 11$, we can compute the right-tailed probability corresponding to the chi-square statistic under 10 degrees of freedom, which is 0. Because the p-value falls far below the conventional $\alpha = 0.05$ threshold, the null hypothesis is decisively rejected: the observed joint distribution of MBTI preferences deviates dramatically from what would be expected if the four indices varied independently. In practical terms, substantial associations exist among the E-I, S-N, T-F and J-P scales, corroborating earlier psychometric critiques that the MBTI dimensions are not orthogonal factors but overlap to a non-trivial extent.

Actually, some researchers had also proven that the four dimensions of MBTI are not independent. Fleenor (1997) investigated the intercorrelations among MBTI continuous scores and found that while most dimension pairs demonstrated relatively low correlations, the correlation between the Sensing–Intuition (S-N) and Judging–Perceiving (J-P) scales was notably higher. Specifically, the study reported a correlation coefficient of $r = 0.41$ between S-N and J-P, indicating a moderate positive relationship. This finding has been replicated in other research and suggests that individuals who prefer intuition are more likely to also prefer perceiving. As such, the assumption of strict statistical independence between MBTI preference axes, particularly between S-N and J-P, may not hold, which is in line with the findings of our study.

```

1 df_val = 10
2 p_val = 1 - chi2.cdf(chi2_stat, df_val)
3 print(p_val)

```

```

4 if p_val < 0.05:
5     print("Conclusion: Reject H -- The four dimensions are not completely
        independent.")
6 else:
7     print("Conclusion: H cannot be rejected - the four dimensions can be
        regarded as independent.")
    
```

5.3 Exploratory Data Analysis (EDA)

5.3.1 MBTI Type Frequency

```

1 # 2) Frequency bar chart
2 plt.figure(figsize=(10,4))
3 df['psychotype'].value_counts().plot(kind='bar')
4 plt.title('Frequency of 16 MBTI Types')
5 plt.xticks(rotation=45)
6 plt.tight_layout()
7 plt.show()
    
```

A frequency bar chart of the 16 MBTI types was generated using the `value_counts()` function on the `psychotype` column. The result was plotted using matplotlib and is shown in fig. 5.1.




Figure 5.1: Frequency of 16 MBTI Types

As seen in fig. 5.1, the frequency of 16 MBTI types has been shown in a descending order. The type ESTJ ranks first, which shows that, based on our dataset, the proportion of ESTJ people is the highest. Conversely, the proportion of INFP people is the lowest. Additionally, it can be observed that the `_S_J` people rankings are relatively high in frequency, as the `_NF_` people rankings are relatively low.

Also, fig. 5.1 exhibits severe right oblique imbalance distribution, as the number of ESTJ people is nearly 9 times as many as the number of INFP people. This phenomenon may be attributed to our database being originally from Kaggle, and certain MBTI type tends to participate in such investigations.

This contrasts with national MBTI distribution statistics reported in the MBTI® Manual, where ISFJ and ESFJ were found to be the most common types among U.S. adults (Myers et al., 1998), suggesting that our dataset, to a certain extent, fits the population-level trends. In distinct regions, the regional differences may influence MBTI type distributions in specific rankings.

5.3.2 Distribution of MBTI Dimension Scores

```
1 # 3) Histogram of scores in each dimension
2 score_cols = list('eisntfjp')
3 df[score_cols].hist(bins=20, figsize=(12,6))
4 plt.tight_layout()
5 plt.show()
```

Histograms of scores in each MBTI dimension were generated using pandas.DataFrame.hist and visualized with matplotlib as shown in fig. 5.2.




Figure 5.2: Histogram of MBTI Dimension Scores

As seen in fig. 5.2, from the score concentration trend, the eight MBTI poles vary in concentration. For example, E, S, and T scores are generally spread from 10 to 40, while N and I scores are more narrowly concentrated between 5 to 30. And in detail, in the dimension of P and T, exhibit higher scores, which shows the preference toward Thinking and Perceiving. Compared

to them, in the dimension of N and I, they exhibit lower scores, which indicates most people are more inclined toward Extraversion and Sensing. From the data obtained from these diagrams, we can observe that most samples in these dimensions show distributional asymmetries, as not evenly distributed. Particularly for the high values of J and low values of N, this result matches the observation at 4.1.1 that `_S_J` types dominate the database.

5.3.3 Descriptive Statistics of MBTI Dimensions

```
1 # 4) Describe statistics (mean, std, quartile, skewness, kurtosis)
2 stats = df[score_cols].describe().T
3 stats['skew'] = df[score_cols].skew()
4 stats['kurt'] = df[score_cols].kurt()
5 print(stats.round(2))
```

Descriptive statistics of each MBTI dimension were computed and consolidated into a single summary table, including skewness and kurtosis, to facilitate score distribution analysis shown in fig. 5.3.

	count	mean	std	min	25%	50%	75%	max	skew	kurt
e	100000.0	24.00	6.52	8.0	20.0	25.0	28.0	40.0	0.02	-0.38
i	100000.0	21.00	5.43	9.0	18.0	22.0	24.0	33.0	-0.06	-0.44
s	100000.0	26.19	6.65	6.0	21.0	27.0	31.0	45.0	-0.09	-0.19
n	100000.0	16.12	4.71	2.0	12.0	16.0	19.0	29.0	-0.11	-0.05
t	100000.0	28.89	6.64	9.0	23.0	28.0	33.0	47.0	0.00	-0.25
f	100000.0	24.05	5.92	8.0	19.0	24.0	27.0	38.0	-0.08	-0.25
j	100000.0	35.41	8.80	13.0	29.0	35.0	41.0	57.0	0.01	-0.31
p	100000.0	29.34	7.93	6.0	23.0	29.0	35.0	52.0	0.05	-0.19

Figure 5.3: Descriptive Statistics of MBTI Dimension Scores

Based on Table 4.1.3, it can be observed that the dimensions of I, S, N, and F showcase a notable positive skew distribution, as the dimension of N, with a value of -0.11, demonstrates left skewness most. This phenomenon tends to show that most people are more likely to be Sensing(S) and so on. And in contrast, the dimension of P with the value of +0.05 exhibits right skewness, implying a preference towards lower values, showing that Judging(J) dominates more in this database. Results of these also support the conclusion in Figure 4.1.1 that `_S_J` people occupy the majority.

And from the kurtosis value, it can be seen that most values are around 0 and negative, which suggests that all the dimension is distributed platykurtic. With relatively concentrated

values, this exhibits the loss of extreme outliers. Also, the maximum value and minimum value that all dimensions have can be used in the form of Max-Min, which demonstrates that J and P dimensions have the largest difference, indicating that individual differences between them are the strongest.

		S		N	
		T n(%)	F n(%)	T n(%)	F n(%)
E	J	ESTJ	ESFJ	ENTJ	ENFJ
		30 (12.2)	32 (13.1)	12 (4.9)	11 (4.5)
	P	ESTP	ESFP	ENTP	ENFP
		12 (4.9)	30 (12.2)	14 (5.7)	20 (8.2)
I	J	ISTJ	ISFJ	INTJ	INFJ
		29 (11.8)	21 (8.6)	2 (0.8)	2 (0.8)
	P	ISTP	ISFP	INTP	INFP
		12 (4.9)	10 (4.1)	3 (1.2)	5 (2.0)

Figure 5.4: MBTI Distribution of 16 Personality Types

Figure 4.1.3 MBTI Distribution of 16 Personality Types from Jang and Kim (2014), supporting the dominance of SJ types observed in our dataset.

5.3.4 Correlation Analysis Between MBTI Dimensions

```

1 # 5) Correlation matrix heat map
2 plt.figure(figsize=(6,5))
3 sns.heatmap(df[score_cols].corr(), annot=True, cmap='coolwarm')
4 plt.title('Correlation between dimension scores')
5 plt.tight_layout()
6 plt.show()
    
```

A Pearson correlation heatmap was constructed to visualize linear relationships among MBTI dimension scores, as shown in fig. 5.5.




Figure 5.5: Correlation Heatmap of MBTI Dimension Scores

As seen in fig. 5.5, the correlation between the opposite dimensions, like E vs I, S vs N, T vs F, and J vs P. All of them are strongly negative, which is consistent with the design concept of MBTI, as the two poles of each dimension are opposed. As a result, the MBTI method has its rationality. This result aligns with (Li et al., 2024), who also observed that “the correlations between the four axes are generally weak, indicating that the personality traits on each axis are relatively independent” (p. 12).

Furthermore, in fig. 5.5, the correlation between other dimension pairs is low (nearly 0). This phenomenon supports that the dimensions are seemingly independent. While the correlation between S and T is +0.16, a bit larger than others, it indicates that someone who is Sensing(S) tends to be Thinking(T). In contrast, the correlation between S and P is -0.13, which indicates that those who are Sensing(S) tend to be Judging(J).

6 MBTI in Manifestation

In the previous section, we examined the statistical characteristics of MBTI. In this section, we turn to the manifestation level by investigating how different MBTI types vary in their topic

preferences and expressive patterns on Twitter.

6.1 Topic Preferences of MBTI Personalities

To analyze the topic preference of different MBTI personalities, we adopt **LDA modeling**.

Latent Dirichlet Allocation (LDA) is a generative probabilistic model for uncovering hidden “topics” in a large collection of documents. It assumes each document is composed of a mixture of topics, and each topic is represented by a distribution over words. For example, a document might be 30% about “technology” and 70% about “health”, with each topic associated with its own common vocabulary.

In the LDA framework, the generation of a document is imagined as a two-step process:

1. a topic distribution is assigned to the document.
2. For each word in the document:
 - A topic is randomly chosen based on the document’s topic distribution.
 - A word is selected from the vocabulary of that topic.

During model training, this generative process is reversed: LDA infers the underlying topic structure based on the observed words in the documents. It estimates:

- the topic proportions for each document
- the most representative words for each topic

The specific LDA process of our project will be discussed in detail. However, LDA model has a extremely high requirement for text data cleaning, since LDA relies on word-frequency patterns to infer hidden topics. It’s important to remove noise, such as words that are meaningless or unrepresentative, so that the model can produce reliable topics. Thus, we need to make sure our dataset is clean and ready for LDA modeling.

6.1.1 Data Cleaning

Because of the nature of the project, we must work with a dataset that contains a large volume of text. The raw dataset we obtained suffers from the following issues:

1. Text granularity / structure: In each row, the posts field actually concatenates 50 posts from a single user, separated by ”|||”.

2. Dirty characters and encoding: The data contain URLs, HTML fragments, escape sequences, and leading single quotation marks.
3. Length and memory footprint: Each row is about 7 k characters on average, with some rows exceeding 10 k characters.

These problems prevent the dataset from being used directly for analysis, so we must clean it first. Importing Modules and the Dataset

1. Import the required library

```
1 import pandas as pd
```

This line imports the pandas library under the alias pd. Pandas is a powerful tool for data analysis and manipulation, especially well suited for reading and processing structured data such as CSV files.

2. Import NLP analyze data related modules

```
1 import re, string
2 from typing import List
3 import nltk
4 from nltk.tokenize import word_tokenize
5 from nltk.corpus import stopwords, wordnet
6 from nltk import pos_tag
7 from nltk.stem import WordNetLemmatizer
```

These statements import several NLP utilities:

- re, string: regular expression and character utilities for text processing.
- typing.List: type annotation for list data structures.
- The nltk suite: tokenisation (word_tokenize), stop word handling (stopwords), part of speech tagging (pos_tag), lemmatisation (WordNetLemmatizer), and more.

```
1 my_nltk_path = "Data"
2 nltk.data.path.append(my_nltk_path)
```

This sets the local NLTK resource path to the Data directory and appends it to the search path so that NLTK can load the required resources in the local environment.

```
1 import textstat
2 from vaderSentiment.vaderSentiment import SentimentIntensityAnalyzer
```

- textstat: assesses text readability.
- SentimentIntensityAnalyzer: VADER’s sentiment analysis tool for assessing the affective polarity of text.

3. Import modules for reading and writing external files

```
1 import json
2 import pickle
3 import copy
```

- json: parsing and serialising JSON data.
- pickle: serialising and deserialising Python objects.
- copy: making shallow and deep copies of objects.

4. Load the FastText language identification model

```
1 import fasttext
2 lang_model = fasttext.load_model("lid.176.bin")
```

This loads Facebook’s FastText model lid.176.bin, which recognises 176 languages and returns language codes (e.g. "en", "zh", "es"). It is essential when pre processing multi-lingual data—especially when we need to standardise text to English via translation.

5. Load a local large language model (LLM) and specify the model version

```
1 import ollama
2 llm = "llama3.1:8b"
```

ollama provides an interface for running LLMs locally. Here we call the LLaMA 3 model with 8 billion parameters, a lightweight model used for on premise translation to improve privacy and efficiency when translating large corpora offline.

6. Bring in the tqdm progress bar and enable Pandas integration

```
1 from tqdm.auto import tqdm
2 tqdm.pandas()
```

TQDM is a popular Python progress bar library. `tqdm.auto` selects the most suitable display backend automatically (Jupyter friendly). Calling `tqdm.pandas()` enables progress bars for `DataFrame.apply()` and `Series.apply()` operations, giving real time feedback during long running tasks.

7. Define an average value helper

```
1 def ave(l):
2     return sum(l) / len(l)
```

A simple function `ave` is defined to calculate the average of a list of numeric values.

8. Define the list of MBTI personality types

```
1 MBTI_types = [
2     "ISTJ", "ISFJ", "INFJ", "INTJ",
3     "ISTP", "ISFP", "INFP", "INTP",
4     "ESTP", "ESFP", "ENFP", "ENTP",
5     "ESTJ", "ESFJ", "ENFJ", "ENTJ"
6 ]
```

A list named `MBTI_types` is defined, containing all 16 Myers-Briggs personality types, to serve as the classification basis in subsequent text or label processing.

9. Read the data and perform an initial split

```
1 raw_data = pd.read_csv("Data\\twitter_MBTI.csv", encoding="utf-8")
2 raw_data.drop(columns="Unnamed: 0", inplace=True)
3 raw_data.columns = ["posts", "type"]
4
5 for i in raw_data.index:
6     temp = raw_data.loc[i, "posts"]
7     temp = temp.split("|||")
8     raw_data.loc[i, "posts"] = temp
```

First, the CSV file `twitter_MBTI.csv` is loaded into a `DataFrame`. The automatically added index column ("Unnamed: 0") is removed, and the columns are renamed to standardise their labels. Each row's `posts` field is then split on the delimiter "|||", converting the concatenated string into a list of separate posts for subsequent sentence level analysis.

10. Load and merge the custom stop word list

```

1 from custom_stopwords import custom_stopwords
2 stop_words.update(custom_stopwords)

```

custom_stopwords is a task specific collection of terms—such as social media jargon (“lol”, “omg”, “http”), MBTI irrelevant proper nouns, or noise tokens—that should be excluded. Merging it into stop_words ensures these words are filtered out during cleaning.

Methods for Data Cleaning

1. Loading the contraction mapping

```

1 with open(file="contractions.json", mode='r', encoding='utf-8') as f:
2     contractions_map = json.load(f)

```

contractions.json maps common English contractions to their full forms (e.g. “don’t” → “do not”), facilitating normalisation of user-generated content.

2. Constructor __init__

```

1 def __init__(self, source=raw_data):
2     self.data = source

```

Initialises the object with a DataFrame that contains a posts column in which each entry is a list of sentences.

3. Remove user mentions and hashtags

```

1 def remove_mention_and_tag(self):
2     def process_removal(post):
3         post_without_mention=[]
4         for sentence in post:
5             # Use re to scan and substitute
6             post_without_mention.append(
7                 re.sub(
8                     pattern=r'@\w+|#\w+',
9                     repl=' ',
10                    string=sentence
11                )
12            )
13         return post_without_mention
14     self.data["posts"]=self.data["posts"].apply(process_removal)

```

This method defines an inner function `process_removal` that scans each sentence in a post with the regular expression `r'@\w+|#\w+'` and replaces every mention or hashtag with a space, thereby stripping social media tags while preserving sentence order. The `apply()` call performs this operation on the entire `posts` column.

4. Delete URL hyperlinks

```

1 def remove_url(self):
2     def process_remove_url(post):
3         post_without_url = []
4         for sentence in post:
5             post_without_url.append(
6                 re.sub(
7                     pattern=r'http\S+|www\S+|https\S+',
8                     repl='',
9                     string=sentence,
10                    flags=re.MULTILINE
11                )
12            )
13     return post_without_url
14 self.data["posts"] = self.data["posts"].apply(process_remove_url)
    
```

The method removes any web page address (e.g. `http://...`, `www....`), preventing links from contaminating downstream text analysis.

5. Strip emoji characters

```

1 def remove_emoji(self):
2     def process_remove_emoji(post):
3         post_without_emoji=[]
4         for sentence in post:
5             # Use re to scan and substitute
6             emoji_pattern=re.compile(
7                 "["
8                 "\U0001F600-\U0001F64F" # Emoticons
9                 "\U0001F300-\U0001F5FF" # Miscellaneous Symbols and
10                Pictographs
11                 "\U0001F680-\U0001F6FF" # Transport and Map Symbols
12                 "\U0001F1E0-\U0001F1FF" # Flags (iOS)
13                 "\U00002702-\U000027B0" # Dingbats
    
```

```

13     "\U000024C2-\U0001F251" # Enclosed Characters, etc.
14     "\U0001f926-\U0001f937" # Supplemental Symbols and
        Pictographs
15     "\U00010000-\U0010ffff" # Broader range for some less common
        emojis
16     "]+", flags=re.UNICODE
17     )
    
```

The regular expression spans multiple Unicode ranges—covering most common and uncommon emojis such as facial expressions, gestures, vehicles, map icons, a wide variety of regional flags and pictographic symbols, and even supplementary characters beyond the Basic Multilingual Plane (BMP)—with `flags=re.UNICODE` enabled to ensure all Unicode characters are recognized.

```

1         post_without_emoji.append(
2             emoji_pattern.sub(
3                 repl=' ',
4                 string=sentence
5             )
6         )
7     return post_without_emoji
8     self.data["posts"] = self.data["posts"].apply(
        process_remove_emoji)
    
```

For each sentence, the regex matches emojis and replaces every matched character with a single space (' '), preventing token concatenation noise while maintaining readability and analyzability; the `process_remove_emoji` function is then applied to the entire posts column via `.apply()`, bulk-removing emojis from every post and overwriting the original data column with the cleaned results.

6. Expand English contractions

Static method `text_expand()`

```

1 @staticmethod
2 def text_expand(original_string, contraction_mapping=contractions_map)
    :
    
```

Defines a static method `text_expand()` that takes a single string (a sentence) as input and, by default, uses the pre-loaded dictionary of contractions `contractions_map` to

convert contractions to their full forms.

```
1 contractions_pattern = re.compile('({})'.format('|'.join(
    contraction_mapping.keys())) , flags=re.IGNORECASE | re.DOTALL)
```

This statement concatenates all the keys (i.e., every contraction) in the mapping dictionary into a regular expression pattern so that any occurrence of a contraction in the text can be captured. The flag `re.IGNORECASE` makes the match case insensitive, and `re.DOTALL` allows the pattern to span across line breaks.

```
1 def text_mapping(text_matched):
2     old_text = text_matched.group(0)
3     new_text = contraction_mapping.get(old_text.lower())
4     if not new_text:
5         new_text = contraction_mapping.get(old_text)
6         if not new_text:
7             return old_text
8     return new_text
```

The inner function `text_mapping()` replaces each matched contraction with its full form. It first tries to match the lowercase version; if that fails, it tries the original case. If a replacement still cannot be found, it returns the original text unchanged, preventing information loss.

```
1 expanded_string = contractions_pattern.sub(repl=lambda m: text_mapping(
    (m)), string=original_string)
2 return expanded_string
```

Using `re.sub()`, every match in the original string is replaced, and the expanded string is finally returned.

```
1 def expand_contractions(self):
2     def process_expand_contractions(original_list):
3         for idx in range(len(original_list)):
4             original_list[idx] = Data_to_Clean.text_expand(
                original_list[idx])
5         return original_list
6     self.data["posts"] = self.data["posts"].apply(lambda x:
        process_expand_contractions(x))
```

This method batch-processes every `posts` entry in the `DataFrame`. Each `posts` entry is a list of strings, representing multiple sentences written by a user. The nested function

`process_expand_contractions()` calls the static method `text_expand()` on every sentence in the list, expanding all contractions to their full forms. Finally, `apply()` is used to apply the processing to the entire column, achieving large-scale contraction expansion. This greatly improves the consistency and semantic clarity of the data, which benefits subsequent tokenization, vectorization, and modelling stages.

```
1 def tolower(self):
2     def process_tolower(post):
3         return [sentence.lower() for sentence in post]
4     self.data["posts"] = self.data["posts"].apply(process_tolower)
```

Uniform lower casing prevents word-frequency fragmentation due to case differences.

```
1 def remove_punct(self):
2     def process_remove_punct(post):
3         post_without_punct = []
4         for sentence in post:
5             post_without_punct.append(
6                 re.sub(pattern=r'[~a-zA-Z\s]', repl=' ', string=
7                     sentence)
8             )
9         return post_without_punct
10    self.data["posts"] = self.data["posts"].apply(process_remove_punct)
```

Non-alphabetic characters are replaced by spaces, simplifying the text for language modelling.

```
1 def remove_whitespace(self):
2     def process_remove_whitespace(post):
3         return [sentence for sentence in post if sentence.strip()]
4     self.data["posts"] = self.data["posts"].apply(
5         process_remove_whitespace)
```

Sentences that are empty or contain only whitespace are discarded.

```
1 def totokens(self):
2     def process_totokens(post):
3         post_totokens = []
4         for sentence in post:
5             tokens = word_tokenize(sentence)
```

```

6         post_totokens.append(tokens)
7     return post_totokens
8     self.data["posts"] = self.data["posts"].apply(process_totokens)
    
```

word_tokenize() splits each cleaned sentence into a list of tokens, providing the basic units for further NLP tasks.

```

1 def remove_stopwords(self):
2     def process_remove_stopwords(post):
3         stop_words = set(stopwords.words("english"))
4         filtered_post = []
5         for sentence in post:
6             filtered_sentence = [word for word in sentence if word not
7                                 in stop_words]
8             filtered_post.append(filtered_sentence)
9         return filtered_post
10    self.data["posts"] = self.data["posts"].apply(
11        process_remove_stopwords)
    
```

Common high-frequency, low-information words are filtered out to emphasise lexical content relevant for modelling.

```

1 def post_lemmatize(self):
2     def process_lemmatize(post):
3         def get_wordnet_postag(old_postag):
4             if old_postag.startswith('J'): return wordnet.ADJ
5             elif old_postag.startswith('V'): return wordnet.VERB
6             elif old_postag.startswith('N'): return wordnet.NOUN
7             elif old_postag.startswith('R'): return wordnet.ADV
8             else: return wordnet.NOUN
9
10        lemmatizer = WordNetLemmatizer()
11        lemmatized_post = []
12        for tokens in post:
13            tagged_tokens = pos_tag(tokens)
14            lemmatized_tokens = [lemmatizer.lemmatize(word,
15                get_wordnet_postag(tag)) for word, tag in tagged_tokens]
16            lemmatized_post.append(lemmatized_tokens)
17        return lemmatized_post
18    self.data["posts"] = self.data["posts"].apply(process_lemmatize)
    
```

Words are reduced to their dictionary forms based on POS tags, decreasing dimensionality and unifying inflected variants.

```

1 def drop_empty(self):
2     def process_drop(post):
3         result=[sentence for sentence in post if sentence!=[]]
4         return result
5     self.data["posts"]=self.data["posts"].apply(process_drop)

```

After cleaning, residual empty sentences are removed to maintain structural integrity.

1. Automatically Detect Non-English Sentences

```

1 def locate_str_to_translate(self):
2     result = []
3     for i in tqdm(self.data.index,
4         desc="Locating strings of other languages..."):
5         for j in range(len(self.data.loc[i, "posts"])):
6             sentence = self.data.loc[i, "posts"][j]
7
8             # Only check sentences longer than eight words
9             if len(sentence.split()) > 8:
10                lang_prediction = lang_model.predict(
11                    re.sub(r'\s+', ' ', sentence).strip(),
12                    k=1                                # top-1 prediction
13                )
14
15                # Keep if not English & confidence > 0.98
16                if (lang_prediction[0][0] != "__label__en"
17                    and lang_prediction[0][1] > 0.98):
18                    result.append(
19                        (i, j,
20                         re.sub(pattern=r"__\w+__",
21                             repl='',
22                             string=lang_prediction[0][0]))
23                    )
24
25     self.locations = result
26     with open(f>Data/{self.basic_identities['type']}
27         _translate_location.pkl",
28         "wb") as f:

```

```
28 pickle.dump(result, f)
```

- **Outer loop:** iterates over the entire DataFrame index, visiting each post sequentially.
- **Inner loop:** traverses every sentence inside the current post (a list of sentences).
- **tqdm** renders a progress bar for large-scale datasets.
- A lower bound of > 8 words avoids language-detection errors on extremely short sentences.
- The FastText model returns a tuple ('__label__xx', confidence); only non-English predictions with confidence > 0.98 are stored.
- Results are saved both in `self.locations` and pickled to disk for later translation.

2. Translate with a Local LLM

```
1 def translate_str(self):
2     for coord in tqdm(self.locations,
3                       desc="Translating string into English..."):
4         sentence = self.data.loc[coord[0], "posts"][coord[1]]
5
6         self.data.loc[coord[0], "posts"][coord[1]] = \
7             ollama.generate(
8                 model=llm,
9                 prompt=(
10                     f"Translate from {coord[2]} to English: \"{
11                         sentence}\n\n"
12                     f"Output ONLY the translated text."
13                 )
14             )['response']
```

Each non-English sentence identified in Step 8 is translated *in place* by a locally hosted LLM (e.g. llama3.1:8b). The prompt specifies the source language and requests only the English rendition, preserving post order and structure.

3. Filter Non-English Sentences by Language ID

```
1 def process_drop(post, level=0.98):
2     filtered_post = []
```

```

3     for sentence in post:
4         norm = re.sub(r"\s+", " ", sentence)
5
6         # Keep very short sentences to avoid false negatives
7         if len(norm.split()) < 6:
8             filtered_post.append(norm)
9             continue
10
11        lang = lang_model.predict(norm)
12        if lang[0][0] == '__label__en' and lang[0][1] > level:
13            filtered_post.append(norm)
14        else:
15            # Retry in lowercase for robustness
16            lang = lang_model.predict(norm.lower())
17            if lang[0][0] == '__label__en' and lang[0][1] > level:
18                filtered_post.append(norm)
19    return filtered_post
20
21 self.data["posts"] = self.data["posts"].apply(process_drop)

```

- Filters out non-English sentences without translating them.
- Sentences shorter than six words are retained to reduce false negatives.
- Longer sentences must pass an English-confidence threshold (`level`, default 0.98).
- A second check on the lowercase version mitigates errors from mixed casing or acronyms.

Create a data processing method that encompasses the entire workflow

1. Initialize the Data Object & Remove URLs

```

1 data = Data_to_Analyze(type=TYPE)
2 data.remove_url()
3 data.remove_mention_and_tag()

```

- Instantiate a `Data_to_Analyze` object to load the raw dataset for the specified personality type `TYPE`.
- Call `remove_url()` and `remove_mention_and_tag()` to strip out hyperlinks, user mentions (@username), and topic hashtags (#topic), eliminating social-media noise.

2. Extract Structured Text Features (Before Cleaning)

```
1 data.get_sentence_quantity()
2 data.get_word_count()
3 data.get_upper_ratio()
4 data.get_readability()
5 data.get_vader_score()
```

- `get_sentence_quantity()` – counts the number of sentences in each post.
- `get_word_count()` – totals the words in each post.
- `get_upper_ratio()` – computes the ratio of uppercase letters to all alphabetic characters.
- `get_readability()` – evaluates readability using two textstat metrics: Flesch Reading Ease and Gunning Fog Index.
- `get_vader_score()` – applies the VADER model for sentiment analysis, yielding composite sentiment scores.

Important: Run these functions *before* any cleaning steps such as contraction expansion or case conversion, since those operations alter the statistics.

3. Continue Text-Cleaning Tasks

```
1 data.remove_emoji()
2 data.remove_whitespace()
3 data.drop_non_english(0.75)
4 data.expand_contractions()
5 data.tolower()
6 data.remove_punct()
7 data.remove_whitespace()
8 data.totokens()
```

- `remove_emoji()` – removes emoji and other non-text graphical elements.
- `remove_whitespace()` (first pass) – performs an initial whitespace cleanup.
- `drop_non_english(0.75)` – uses fastText to detect language and drops sentences that are not English when confidence is below 0.75.

- `expand_contractions()` – expands English contractions (e.g., “don’t” → “do not”).
- `tolower()` – converts all text to lowercase, reducing word-form variability.
- `remove_punct()` – strips punctuation to facilitate vectorization or model processing.
- `remove_whitespace()` (second pass) – clears residual extra spaces from earlier steps.
- `totokens()` – tokenizes the cleaned sentences into word lists (tokens) for downstream vectorization or language-model tasks.

4. Persist the Cleaned Data as a Binary File

```
1 with open(f"Data\\cleaned_data\\{TYPE}_cleaned.pkl", "wb") as f:
2     pickle.dump(data, f)
```

Serializes the cleaned data object to disk in binary format with `pickle`, enabling rapid reuse for model training or further analysis.

5. Run the Analysis in Batch for All MBTI Types

```
1 for T in tqdm(MBTI_types):
2     analyze_data_p1(T)
```

Iterates over `MBTI_types` (assumed to include all 16 personality types) and executes `analyze_data_p1()` for each one, enabling efficient, consistent batch processing across the entire dataset.

6.1.2 LDA modeling

The cleaned data are organized by MBTI types, each as a tokenized and preprocessed text collection stored in a structured `pd.DataFrame`. To perform LDA modeling, the input must be converted into a **Bag-of-Words (BoW) corpus**, where each document is represented as a list of (word_id, frequency) tuples. This requires mapping each unique word to a distinct integer ID, resulting in a **dictionary** that captures the vocabulary of the entire corpus. In this assignment, we apply filtering by removing words that appear in more than 20% of documents (`no_above=0.2`) and those that appear in fewer than 50 documents (`no_below=50`) to retain only representative terms.


```

1 import gensim.corpora as corpora
2 from gensim.models import CoherenceModel
3 def construct_initial_dict(source,no_above,no_below):
4
5     output = {T: {
6         "original_text": [],
7     } for T in MBTI_types}
8
9     output["all_original_text"]=[]
10    for T in tqdm(MBTI_types):
11        for i in source[T].data.index:
12            temp=source[T].data.loc[i,"posts"]
13            output[T]["original_text"].append(temp)
14            output["all_original_text"].extend(output[T]["original_text"])
15    output["overall_dict"]=corpora.Dictionary(output["all_original_text"])
16    output["overall_dict"].filter_extremes(no_above=no_above,no_below=
17        no_below)
18    output["overall_dict"].compactify()
19    print("Size of dictionary:",len(output["overall_dict"]))
20    output["all_corpus"]=[output["overall_dict"].doc2bow(post_token) for
21        post_token in output["all_original_text"]]
22    return output
23
24 initial_dict=construct_initial_dict(source=cleaned_data,
25                                     no_above=0.20,
26                                     no_below=50)
27
28 with open("Data/initial_dict.pkl",'wb') as f:
29     pickle.dump(initial_dict,f)

```

For a convenient inspection, we computed the overall term-frequency distribution by summing each token's bag-of-words counts across the entire corpus and stored the result table as a CSV file:

```

1 def check_corpus(corpus,dict,name=''):
2     result=pd.DataFrame(
3         [
4             list(range(len(dict))),
5             [0]*len(dict)
6         ]
7     ).T
8     result.columns=["word","frequency"]

```

```

9     for post in tqdm(corpus):
10         for word_tuple in post:
11             result.loc[word_tuple[0], "frequency"] += word_tuple[1]
12     for i in result.index:
13         result.loc[i, "word"] = dict[i]
14     result = result.sort_values(by="frequency", ascending=False)
15     result.to_csv(f>Data/{name}id2word_result.csv")
    
```

Selecting an appropriate number of topics is crucial for LDA modeling. If the topic number is too small, unrelated content may be merged into the same topic, reducing model interpretability. Conversely, an excessively large number of topics may fragment coherent semantic themes, leading to redundancy and overlap among topics. To determine the optimal number of topics for the LDA model, we will first train several temporary LDA models (`temp_lda_model`) with different numbers of topics. The semantic coherence and interpretability of the resulting topics were evaluated using the `c_v` coherence score, which measures how consistently related the top words within each topic are.

```

1  with open("Data/initial_dict.pkl", "rb") as f:
2      initial_dict = pickle.load(f)
3  import gensim.corpora as corpora
4  import gensim
5  from gensim.models import LdaMulticore, CoherenceModel
6
7  def optimize_topic_num(
8      start,
9      end,
10     step,
11     dict=initial_dict["overall_dict"],
12     corpus=initial_dict["all_corpus"],
13     text=initial_dict["all_original_text"]
14 ):
15     output = pd.Series({}, dtype=float)
16     topic_num_range = range(start, end+1, step)
17     for topic_num in tqdm(topic_num_range, desc="Calculating optimal topic
18                             number"):
19         # Train the LDA model (on all post data)
20         temp_lda_model = LdaMulticore(
21             corpus=corpus,      # Use the bag-of-words corpus of all posts
22             id2word=dict,      # Use the global dictionary
    
```

```

22     num_topics=topic_num,
23     random_state=100,
24     chunksize=100,      # Reduce chunksize to speed up update frequency
25     passes=10,          # Reduce passes to shorten total training time
26     iterations=50,      # Specify the number of iterations per pass
27     alpha=0.01,         # Use a smaller fixed value to promote topic
                           sparsity
28     eta=0.01,           # Use a smaller fixed value to promote word
                           sparsity
29     per_word_topics=False,
30     workers=None
31 )
32
33 # Evaluate the model
34 temp_chmodel=CoherenceModel(
35     model=temp_lda_model,
36     texts=text,
37     dictionary=dict,
38     coherence="c_v"
39 )
40 output[topic_num]=temp_chmodel.get_coherence()
41 print(output)

```

After a few trials, we find that 19 topics gives us the highest c_v coherence score.

```

计算全局模型主题数:   0%|
19      0.524685
20      0.488212
21      0.467017
22      0.472131
23      0.482915
24      0.470117
dtype: float64

```

Figure 6.1: Coherence scores for topic numbers 19 to 24. The highest score is observed at 19 topics, suggesting it as the optimal choice for this model.

We train the final LDA model(`lda_model`) with 19 topics using optimized settings, evaluate the model with c_v coherence score and save the model outputs, cleaned corpus, and topic

descriptions for further analysis.

```

1 # Train the optimized final model with enhanced parameters for better
  convergence and topic separation
2 topics = 19
3
4 logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s
  - %(message)s')
5 # Optimized parameters for better convergence and topic distinction
6 lda_model = LdaMulticore(
7     corpus=initial_dict["all_corpus"],
8     id2word=initial_dict["overall_dict"],
9     num_topics=topics,
10    random_state=100,
11    chunksize=100,          # Significantly reduced: increases update
                             frequency and improves convergence
12    passes=300,             # Moderately reduced: adjusted to work with
                             other optimized parameters
13    iterations=150,         # Newly added: increase iterations per pass
14    alpha=0.01,             # Changed from 'asymmetric' to a small value:
                             promotes document-topic sparsity and improves topic distinction
15    eta=0.01,              # Changed from 'auto' to a small value:
                             promotes word-topic sparsity and reduces topic mixing
16    decay=0.5,             # Newly added: controls learning rate decay,
                             improving convergence stability
17    offset=1.0,            # Newly added: initial value for learning rate
18    minimum_probability=0.01, # Newly added: filters out low-probability
                             topic assignments
19    per_word_topics=False,
20    workers=None,          # Enables parallelization to speed up training
21    eval_every=20          # Reduces evaluation frequency to lower
                             computational cost
22 )
23 # Model evaluation
24 chmodel = CoherenceModel(
25     model=lda_model,
26     texts=initial_dict["all_original_text"],
27     dictionary=initial_dict["overall_dict"],
28     coherence="c_v"
29 )

```

```

30 cv=chmodel.get_coherence()
31 cv
32 # Create unique directories for each LDA model
33 # That's because all variables are unique for each LDA model due to
    different stopwords set
34 model_id=f"{topics}_{str(cv)[2:6]}"
35 # Model ID are designed as "[number of topics]_[CV score]", is unique for
    each model
36
37 path=f"output/lda_model/lda_{model_id}"
38 if not os.path.exists(path):
39     os.makedirs(path)
40
41 path=f"output/lda_model/lda_{model_id}/cleaned_data"
42 if not os.path.exists(path):
43     os.makedirs(path)
44
45 path=f"output/lda_model/lda_{model_id}/visualization"
46 if not os.path.exists(path):
47     os.makedirs(path)
48
49 # Save LDA model
50 with open(f"output/lda_model/lda_{model_id}/lda_{model_id}.pkl",'wb') as f:
51     pickle.dump(lda_model,f)
52
53 # Save cleaned data
54 with open(f"output/lda_model/lda_{model_id}/cleaned_data/cleaned_data.pkl",
    "wb") as f:
55     pickle.dump(cleaned_data,f)
56
57 # Save original text
58 with open(f"output/lda_model/lda_{model_id}/all_original_text.pkl","wb") as
    f:
59     pickle.dump(initial_dict["all_original_text"],f)
60
61 # Get all topics words and weights
62 all_topics_words = lda_model.show_topics(num_topics=-1, num_words=40,
    formatted=False)
63

```

```

64 markdown_content=f"## {topics} topics, cv={str(cv)[2:6]}\n\n"
65
66 for topic_id, topic_words_with_weights in all_topics_words:
67     markdown_content += f"### Topic {topic_id}:\n"
68
69
70     for word, weight in topic_words_with_weights:
71         markdown_content += f"- `{word}`: {weight:.4f}\n"
72     markdown_content += "\n"
73
74 # Save topic words and weights to markdown file
75 with open(f"output/lda_model/lda_{model_id}/lda_{model_id}.md", "w",
76         encoding="utf-8") as f:
77     f.write(markdown_content)

```

After examining the model outputs, we observed that some meaningless or unrepresentative words still remain in the model. This is primarily because the Twitter dataset contains a substantial amount of internet slang (e.g., "omg") that was not fully removed during the initial data cleaning process. To address this issue, we manually add these terms to the stopwords list and re-run the LDA modeling process iteratively until we obtain a model with a high c_v coherence score and minimal noise from irrelevant terms.

The model we finally settled on is model `lda_19_5687`, with the highest high c_v coherence score 0.5687. With this model, we will visualize the features of MBTI Twitter topics.

6.1.3 Result Visualization and Topic Evaluation

To start up the topic evaluation process, we need to import necessary libraries; define MBTI types, dimensions and groups; as well as load LDA model and cleaned data.

```

1 # Import necessary libraries
2 %matplotlib widget
3 import pyLDAvis
4 import pyLDAvis.gensim_models as gensimvis
5 import seaborn as sns
6 import matplotlib.pyplot as plt
7 from mpl_toolkits.mplot3d import Axes3D
8 import pandas as pd
9 import numpy as np
10 import pickle

```

```

11 from tqdm.auto import tqdm
12 import gensim.corpora as corpora
13 from gensim.models import LdaModel
14 from collections import defaultdict
15 from data_clean import Data_to_Clean,Data_to_Analyze
16 import warnings
17 warnings.filterwarnings('ignore')
18 from sklearn.cluster import KMeans
19 from sklearn.decomposition import PCA
20 from sklearn.preprocessing import StandardScaler
21
22 # Ensure the plots are displayed correctly
23 plt.rcParams['axes.unicode_minus']=False
24 sns.set_style("whitegrid")
25 sns.set_palette("husl")
26
27 # Define MBTI types
28 MBTI_types=[
29     'istj','isfj','infj','intj',
30     'istp','isfp','infp','intp',
31     'estp','esfp','enfp','entp',
32     'estj','esfj','enfj','entj'
33 ]
34
35 # Define MBTI dimensions
36 mbti_dimensions={
37     'E': ['estp','esfp','enfp','entp','estj','esfj','enfj','entj'],
38     'I': ['istj','isfj','infj','intj','istp','isfp','infp','intp'],
39     'S': ['istj','isfj','istp','isfp','estp','esfp','estj','esfj'],
40     'N': ['infj','intj','infp','intp','enfp','entp','enfj','entj'],
41     'T': ['intj','intp','entj','entp','istj','istp','estj','estp'],
42     'F': ['isfj','infj','isfp','infp','esfj','enfj','esfp','enfp'],
43     'J': ['istj','isfj','infj','intj','estj','esfj','enfj','entj'],
44     'P': ['istp','isfp','infp','intp','estp','esfp','enfp','entp']
45 }
46
47 # Define MBTI groups
48 mbti_groups={
49     "analysts":["intj","intp","entj","entp"],

```

```

50     "diplomats":["infj","infp","enfj","enfp"],
51     "sentinels":["istj","isfj","istp","isfp"],
52     "explorers":["isfp","istp","estp","esfp"]
53 }
54
55 # Load LDA model and data
56 # Model ID are designed as "[number of topics]_[CV score]",is unique for
    each model
57
58
59 def load_lda_data():
60     # Load LDA model
61     lda_model=pickle.load(open(f"output/lda_model/lda_{model_id}/lda_{
        model_id}.pkl","rb"))
62     print(f"Successfully loaded LDA model with {lda_model.num_topics}
        topics")
63
64     # Load original text data
65     all_original_text=pickle.load(open(f"output/lda_model/lda_{model_id}/
        all_original_text.pkl","rb"))
66     print(f"Successfully loaded original text data with {len(
        all_original_text)} documents")
67
68     return lda_model,all_original_text
69
70
71 # Load cleaned data grouped by MBTI types
72 def load_mbti_data():
73     file_path=f"output/lda_model/lda_{model_id}/cleaned_data/cleaned_data.
        pkl"
74     with open(file_path,'rb') as f:
75         cleaned_data=pickle.load(f)
76         print(f"Cleaned data loaded successfully")
77
78     return cleaned_data
79
80 # Execute file loading
81 lda_model,all_original_text=load_lda_data()
82 mbti_cleaned_data=load_mbti_data()

```


To better interpret topics and detect patterns in the data, we construct a class `LDATopicAnalyzer`, which integrates the LDA model with the MBTI-annotated dataset. This class performs several key functions:

1. Transforms input texts into bag-of-words representations, computes topic distributions for each document, and groups these distributions by MBTI type to observe group-level thematic tendencies.
2. Supports generating interactive visualizations through `pyLDAvis`, which is created and saved to html.
3. Provides tools to extract representative keywords per topic and optionally identify and exclude noise topics that carry little interpretive value.

```

1  # Create a class for LDA visualization
2  class LDATopicAnalyzer:
3      def __init__(self, lda_model, texts, mbti_data):
4          self.model=lda_model
5          self.texts=texts
6          self.mbti_data=mbti_data
7          self.dictionary=lda_model.id2word
8          self.corpus=[self.dictionary.doc2bow(text) for text in texts]
9          self.noise_topic=[]
10         self.topic_distributions=None
11         self.mbti_topic_distributions=None
12
13     def create_pyldavis_visualization(self, save_path=f"final_output/
14         lda_visualization.html"):
15
16         print("Creating pyLDAvis visualization...")
17         # Prepare pyLDAvis visualization
18         vis_data=gensimvis.prepare(
19             self.model,
20             self.corpus,
21             self.dictionary,
22             sort_topics=False
23         )
24
25         # Save as HTML file

```

```

25     pyLDAvis.save_html(vis_data, save_path)
26     print(f"pyLDAvis visualization saved to: {save_path}")
27
28     # Display in notebook
29     pyLDAvis.enable_notebook()
30     return pyLDAvis.display(vis_data)
31
32     def get_topic_distributions(self):
33         """Get topic distributions for documents"""
34         print("Calculating topic distributions...")
35
36         topic_distributions=[]
37         for doc_bow in tqdm(self.corpus, desc="Calculating topic
38             distributions"):
39             doc_topics=self.model.get_document_topics(doc_bow,
40                 minimum_probability=0)
41             topic_probs=[prob for _, prob in doc_topics]
42             topic_distributions.append(topic_probs)
43
44         self.topic_distributions=np.array(topic_distributions)
45         return self.topic_distributions
46
47     def calculate_mbt_i_topic_distributions(self):
48         """Calculate topic distributions for each MBTI type"""
49         print("Calculating topic distributions for each MBTI type...")
50
51         mbti_topic_dist={}
52
53         for mbti_type in MBTI_types:
54             if mbti_type in self.mbt_i_data and len(self.mbt_i_data[mbti_type
55                 ].data) > 0:
56                 # Create corpus for documents of this MBTI type
57                 mbti_corpus=[self.dictionary.doc2bow(doc) for doc in self.
58                     mbti_data[mbti_type].data["posts"]]
59
60                 # Calculate topic distributions
61                 topic_sums=np.zeros(self.model.num_topics)
62                 doc_count=0

```

```

60         for doc_bow in mbti_corpus:
61             doc_topics=self.model.get_document_topics(doc_bow,
62                                                         minimum_probability=0)
63             for topic_id,prob in doc_topics:
64                 topic_sums[topic_id]+=prob
65                 doc_count+=1
66
67             # Calculate average topic distributions
68             if doc_count>0:
69                 mbti_topic_dist[mbti_type]=topic_sums/doc_count
70             else:
71                 mbti_topic_dist[mbti_type]=np.zeros(self.model.
72                                                         num_topics)
73
74         else:
75             mbti_topic_dist[mbti_type]=np.zeros(self.model.num_topics)
76
77         self.mbti_topic_distributions=mbti_topic_dist
78         return mbti_topic_dist
79
80     def get_topic_words(self,num_words=10):
81         """Get keywords for each topic"""
82         topic_words={}
83
84         for topic_id in range(self.model.num_topics):
85             words=self.model.show_topic(topic_id,topn=num_words)
86             topic_words[topic_id]=[word for word,_ in words]
87         return topic_words
88
89     def add_noise_topics(self,*topic_ids):
90         """Define noise topics"""
91         for i in topic_ids:
92             self.noise_topic.append(i)
93
94 # Create analyzer instance
95
96 analyzer=LDATopicAnalyzer(lda_model,all_original_text,mbti_cleaned_data)
97 print("LDA topic analyzer created successfully!")
98
99 # Create pyLDavis interactive visualization
100 vis=analyzer.create_pyldavis_visualization()

```

The interactive topic visualization generated by pyLDAvis can be accessed at the following link: https://dominicmin.github.io/Intro_to_DS_Assignment/lda_visualization.html. fig. 6.2 shows the initial state of the HTML file:




Figure 6.2: Screenshot of the initial state of the HTML file

Note: The topic indices in the HTML file are offset by +1 compared to the LDA model output (i.e., Topic 1 in HTML is Topic 0 in LDA).

As shown in fig. 6.2, on the left side of the HTML file, the **Intertopic Distance Map** visualizes the relationships between topics in two dimensions. A possible interpretation is that each bubble represents a distinct topic, with its area indicating the proportion of tokens (words) in the entire corpus attributed to that topic. Larger bubbles correspond to topics that account for a greater share of the corpus. The position and overlapping of each bubble reflects semantic similarity—the farther apart two bubbles are and the less the bubbles overlap, the less semantically related the corresponding topics. However, as will be demonstrated later, this interpretation fails to accurately characterize certain topics.

On the right side of the HTML page, the adjustable relevance metric of the selected topic is presented alongside the Top-30 Most Salient Terms. For each term, its overall frequency in the corpus is displayed as a blue histogram, while its estimated frequency within the selected

topic is shown in red. Users can adjust the value of λ to observe changes in term saliency and the relationship between a term’s overall frequency and its topic-specific relevance.

When λ is slid to the position 0, the terms that are unique in this topic are prior exhibited. These words are characterized by high distinctiveness, meaning they appear much more frequently in the selected topic compared to their frequency across the entire corpus. As a result, they serve as strong discriminators, helping to differentiate this topic from others. Although such terms may not be the most frequent within the topic itself, they often carry greater semantic specificity and are particularly useful for interpreting nuanced or domain-specific themes. However, because this setting emphasizes uniqueness over prevalence, it may occasionally highlight low-frequency or noisy terms, which should be interpreted with caution in topic labeling.

Meanwhile, when λ is slid to the position 1, these words represent the most commonly occurring terms in the topic and therefore reflect its core semantic content. This setting is particularly useful for understanding the dominant themes or main discourse of the topic. However, because it does not account for how exclusive a term is to the topic, some high-frequency terms that are also common in other topics may be included, potentially reducing the distinctiveness of the topic’s representation.

From fig. 6.2, we can gain an overview of our modeling outcome. Topic 18 has the largest bubble, indicating that it is the most prevalent topic in the corpus. Topics 9, 15, 4, and 17 are located farther away from the other topics, suggesting a clear semantic distinction. In contrast, Topics 3, 13, 2, 8, 6, 19, and 18 exhibit notable spatial overlap, indicating only minor differences in their semantic content. In the whole corpus, the most reoccurring words are mostly related to the entertainment fandom and game fandom.

By selecting different topics and adjusting the value of λ , we can summarize the central theme of each topic, determine whether it is a noise topic, and assess its degree of semantic coherence.

Take topic 12 as an example, when λ is set to 0, the most relevant terms—such as trump, biden, republican, democrat, congress, and abortion—are highly distinctive and strongly associated with U.S. political discourse. These terms are not only topically specific but also exclusive to this topic, suggesting a focused and meaningful theme centered around American politics, government institutions, and social issues. In contrast, when λ is increased to 1, the top terms—such as state, country, child, gun, and law—shift toward higher-frequency words within the topic. Although some of these terms are more general, they still retain political rele-

vance and semantic consistency with the topic's core, indicating that the theme is robust across different relevance metrics. In conclusion, the presence of consistently interpretable and contextually appropriate terms at both extremes of the λ scale demonstrates that topic 13 exhibits a relatively high degree of semantic coherence. The lack of function words, formatting artifacts, or off-topic vocabulary suggests that this is not a noise topic, but rather a well-defined and meaningful cluster within the corpus.




Figure 6.3: HTML page with Topic 12 selected and $\lambda=0$




Figure 6.4: HTML page with Topic 12 selected and $\lambda=0$

By applying this method to all the topics, we can conclude the following topic modeling result:

- High semantic coherence - 8 topics:

Topic 0: Astrology/Zodiac

Topic 3: K-pop Groups (TXT/NCT)

Topic 4: Western TV Shows (Stranger Things/Heartstopper)

Topic 6: Gaming (Genshin Impact)

Topic 8: K-pop Groups (SEVENTEEN/ATEEZ)

Topic 9: Western Pop Music/Celebrities

Topic 10: K-pop Group (BTS)

Topic 14: K-pop Group (ENHYPEN)

Topic 16: K-pop Group (Stray Kids)

- Medium semantic coherence - 6 topics:

Topic 2: Academic/Business/Personal Development

Topic 5: Gender Identity/LGBTQ+/Mental Health

Topic 7: Food/Weight Management/Eating Disorders

Topic 11: Merchandise Trading/Collectibles

Topic 12: Politics/Social Issues

Topic 17: Anime/Manga/Fan Culture

Topic 1: Daily Life and traveling

- Low semantic coherence - 1 topic:

Topic 15: K-pop Industry General

- Noise Topics - 2 topics:

Topic 13: Mixed Social Media Expressions

Topic 18: Generic Terms/Mixed Content

Interestingly, when linking the interpreted topics to their corresponding bubbles, we observe that although Topic 2 (Academic/Business/Personal Development) and Topic 12 (Politics/Social Issues) show considerable overlap in the Intertopic Distance Map, they are not semantically similar. This mismatch occurs because high-dimensional topic data is projected onto a two-dimensional space.

6.1.4 Topic Distribution

We begin by calculating and visualizing topic distribution.

```

1 # Calculate topic distributions for MBTI types
2
3 mbti_topic_dist=analyzer.calculate_mbti_topic_distributions()
4 topic_words=analyzer.get_topic_words()
5
6 # Create topic distribution DataFrame
7 topic_dist_df=pd.DataFrame(mbti_topic_dist).T
8 topic_dist_df.columns=[f"Topic {i}" for i in range(len(topic_dist_df.
9     columns))]
10 topic_dist_df.drop([f"Topic {i}" for i in analyzer.noise_topic],
11     axis=1,
12     inplace=True)

```



```

13 print("MBTI type topic distribution calculation completed!")
14 print(f"Topic distribution matrix shape: {topic_dist_df.shape}")
15
16 # Display first few rows
17 print("\nPreview of topic distributions for each MBTI type:")
18 display(topic_dist_df.head())

```


Calculating topic distributions for each MBTI type...
 MBTI type topic distribution calculation completed!
 Topic distribution matrix shape: (16, 18)

Preview of topic distributions for each MBTI type:

	Topic 0	Topic 1	Topic 2	Topic 3	Topic 4	Topic 5	Topic 6	Topic 7	Topic 8	Topic 9	Topic 10	Topic 11	Topic 12	Topic 14	Topic 15
istj	0.008851	0.115248	0.088992	0.020304	0.020248	0.043244	0.021340	0.088940	0.024473	0.015487	0.046689	0.018558	0.057390	0.040083	0.099723
isfj	0.009061	0.129999	0.074834	0.022828	0.023307	0.028510	0.017359	0.069671	0.038191	0.022679	0.063308	0.017913	0.031093	0.024531	0.157857
infj	0.017712	0.158324	0.134677	0.020251	0.025003	0.035576	0.014002	0.060592	0.023622	0.022519	0.031834	0.014991	0.068709	0.015630	0.100966
intj	0.011780	0.128567	0.161768	0.014841	0.020404	0.050019	0.016520	0.066708	0.026187	0.017296	0.020154	0.012905	0.092029	0.017059	0.084242
istp	0.009948	0.088690	0.056644	0.034672	0.046965	0.057443	0.033386	0.098363	0.030848	0.024917	0.027006	0.012163	0.017179	0.018405	0.116180

Figure 6.5: Preview of first few rows

A heatmap is generated based on the computed values to visually represent the results.



The heatmap provides an intuitive visual indication of topic popularity. Specifically, Topics 1 (Daily Life and traveling), 2 (Academic/Business/Personal Development), 15 (K-pop Industry General), and 17 (Anime/Manga/Fan Culture) exhibit darker red shades, suggesting they are

more frequently discussed. A more rigorous, quantitative analysis of topic popularity will be presented further on.

To assist with our interpretation with the heatmap, we calculate the overall popularity of each topic.

```

1 # Create topic keyword cloud summary
2 def create_topic_wordcloud_summary(topic_words,topic_dist_df):
3     """Create topic keyword summary"""
4     print("=" * 60)
5     print("Topic keyword summary")
6     print("=" * 60)
7
8     # Calculate overall popularity of each topic
9     topic_popularity=topic_dist_df.mean().sort_values(ascending=False)
10
11     for i,(topic_idx,popularity) in enumerate(topic_popularity.items()):
12         topic_num=int(topic_idx.replace('Topic',''))
13         print(f"\nTopic {topic_num} (Popularity: {popularity:.3f}):")
14         print(f"Keywords: {'',''.join(topic_words[topic_num][:8])}")
15
16         # Find the MBTI type that most prefers this topic
17         topic_col=f"Topic {topic_num}"
18         if topic_col in topic_dist_df.columns:
19             top_mbti=topic_dist_df[topic_col].nlargest(3)
20             print(f"Most preferred MBTI types: {'',''.join([f'{mbti}({score:.3f})' for mbti,score in top_mbti.items()])}")
21
22         if i >= 9: # Only show top 10 topics
23             break
24
25
26 create_topic_wordcloud_summary(topic_words,topic_dist_df)

```

This gives us the following summary:

```
=====
Topic keyword summary
=====

Topic 1 (Popularity: 0.122):
Keywords: photo,coffee,covid,trip,college,husband,felt,child
Most preferred MBTI types: enfj(0.167),infj(0.158),esfj(0.153)

Topic 17 (Popularity: 0.112):
Keywords: anime,chapter,fic,manga,holy,commission,au,arc
Most preferred MBTI types: entp(0.160),infp(0.141),estp(0.140)

Topic 18 (Popularity: 0.102):
Keywords: black,beat,star,war,holy,animal,ball,single
Most preferred MBTI types: entp(0.135),estp(0.133),entj(0.127)

Topic 15 (Popularity: 0.101):
Keywords: group,member,comeback,kpop,debut,dance,stalker,concert
Most preferred MBTI types: isfp(0.159),isfj(0.158),esfp(0.118)

Topic 2 (Popularity: 0.093):
Keywords: experience,self,human,study,thread,important,business,language
Most preferred MBTI types: intj(0.162),infj(0.135),entj(0.129)

Topic 7 (Popularity: 0.077):
Keywords: fast,weight,milk,fat,cream,ice,coffee,smell
Most preferred MBTI types: entj(0.099),istp(0.098),entp(0.090)

Topic 5 (Popularity: 0.061):
Keywords: trans,sex,gender,act,male,black,autistic,dick
Most preferred MBTI types: entp(0.101),estp(0.098),esfp(0.086)

Topic 12 (Popularity: 0.049):
Keywords: state,trump,country,child,law,gun,american,abortion
Most preferred MBTI types: entj(0.110),intj(0.092),estj(0.070)

Topic 10 (Popularity: 0.037):
Keywords: bts,army,jungkook,jimin,hobi,yoongi,taehyung,tae
Most preferred MBTI types: esfj(0.068),isfj(0.063),istj(0.047)

Topic 4 (Popularity: 0.030):
Keywords: eddie,steve,mike,stranger,robin,max,strange,el
Most preferred MBTI types: istp(0.047),entp(0.043),infp(0.040)
```

With the aid of the summary statistics, we can find distinct MBTI engagement patterns across different semantic domains:

- Topic 15 (K-pop fandom activities): characterized by group debuts, comebacks, and concerts; demonstrates strong engagement among ISFP, ISFJ, and ESFP types, underscoring the intersection of sensory enjoyment and emotional engagement.
- Topic 14 (lightweight, emotionally-driven daily expression): resonates with SP types who prioritize spontaneity and immediate experiential sharing.
- Topic 7 (sensory experiences related to food and comfort): emphasizes fast food, coffee,

and cream, aligning with ISTP and ESTP preferences for direct sensory satisfaction.

- Topic 17 (strategic, abstract, and fandom-oriented discussions): involves anime, manga, and fan fiction; attracts ENTP, INFP, and ESTP types, indicating alignment with analytical and imaginative discourse.
- Topic 2 (experiential and intellectual reflections): appeals to INTJ, ENTJ, and INFJ types, reflecting their preference for profound, thoughtful, and self-reflective content.
- Topic 18 (adventurous and competitive themes): includes sports and competitions; engages ENTP, ESTP, and ENTJ personalities drawn to intense experiences.
- Topic 5 (identity and socially charged discussions): covers gender, sexuality, and societal roles; garners interest from ENTP, ESTP, and ESFP types open to explorative and provocative topics.
- Topic 12 (politically charged discourse): focuses on societal debates like Trump, guns, and abortion; attracts ENTJ, INTJ, and ESTJ types inclined toward policy and governance.
- Topic 10 (BTS fandom): features BTS member names; resonates with ESFJ and ISFJ types, highlighting community-oriented engagement.
- Topic 4 (Stranger Things franchise): references characters like Eddie and Steve; shows engagement from ISTP, ENTP, and INFP types, indicating analytical and introspective affinities.

Having observed engagement patterns of individual MBTI types, we compare the topic preference patterns of different MBTI groups.

```

1 # Create MBTI dimension topic preference analysis
2 def analyze_mbti_dimensions(topic_dist_df,mbti_dimensions=mbti_dimensions):
3     """Analyze topic preferences for MBTI four dimensions"""
4     dimension_analysis={}
5
6     for dim,types in mbti_dimensions.items():
7         # Calculate average topic distribution for this dimension type
8         dim_types_in_data=[t for t in types if t in topic_dist_df.index] #
            t is a single type

```

```


9         dimension_analysis[dim]=topic_dist_df.loc[dim_types_in_data].mean()
10         # mean of the topic distribution for this dimension/group type
11
12     return pd.DataFrame(dimension_analysis)
13
14 dimension_pairs=[('E','I'),('S','N'),('T','F'),('J','P')]
15 pair_names=['Extrovert vs Introvert','Sense vs Intuition','Thinking vs
16 Feeling','Judging vs Perceiving']
17
18 def create_dimension_comparison(dimension_df,file_name,dimension_pairs=
19 dimension_pairs,pair_names=pair_names,comment=None):
20     """Create MBTI dimension topic preference comparison chart"""
21     fig,axes=plt.subplots(int(len(dimension_pairs)/2),2,figsize=(16,6*int(
22         len(dimension_pairs)/2)))
23     axes=axes.flatten()
24
25     for i,((dim1,dim2),pair_name) in enumerate(zip(dimension_pairs,
26         pair_names)):
27         if dim1 in dimension_df.columns and dim2 in dimension_df.columns:
28             # Calculate difference
29             diff=dimension_df[dim1]-dimension_df[dim2]
30
31             # Create bar chart
32             x_pos=range(len(diff))
33             colors=['red' if x < 0 else 'blue' for x in diff]
34
35             axes[i].bar(x_pos,diff,color=colors,alpha=0.7)
36             axes[i].axhline(y=diff.apply(abs).quantile(q=0.85),color='red',
37                 linestyle='--',alpha=0.3,label='85% Quantile Line')
38             axes[i].axhline(y=-diff.apply(abs).quantile(q=0.85),color='red',
39                 linestyle='--',alpha=0.3)
40             axes[i].axhline(y=0,color='black',linestyle='-',alpha=0.3)
41             axes[i].set_title(f'{pair_name} Diff in Topic Preference',
42                 fontsize=12,fontweight='bold')
43             axes[i].set_xlabel('Topic')
44             axes[i].set_ylabel(f'{dim1} - {dim2} Preference Difference')
45             axes[i].set_xticks(x_pos)
46             axes[i].set_xticklabels([j for j in list(topic_dist_df.columns)

```

```

        ],rotation=45)
40     axes[i].grid(True,alpha=0.3)
41     axes[i].legend()
42     fig.suptitle("MBTI Group Topic Preference Comparison",fontsize=16,
        fontweight='bold',y=1)
43     plt.tight_layout()
44     plt.figtext(0.5, 0.02,comment,ha='center',fontsize=10)
45     plt.savefig(f'output/lda_model/lda_{model_id}/visualization/{file_name
        }.png',dpi=300,bbox_inches='tight')
46     plt.savefig(f'final_output/{file_name}_drop13_18.png',dpi=300,
        bbox_inches='tight')
47     plt.show()
48
49
50 dimension_df=analyze_mbti_dimensions(topic_dist_df)
51 print("MBTI dimension topic preference analysis:")
52 display(dimension_df.head())
53
54 # create_dimension_comparison(dimension_df,"mbti_dimension_comparison")
55 group_pairs=[
56     ('analysts','diplomats'),
57     ('sentinels','explorers'),
58     ('sentinels','diplomats'),
59     ('explorers','diplomats'),
60     ('sentinels','analysts'),
61     ('explorers','analysts')
62 ]
63 group_names=['Analysts vs Diplomats',
64     'Sentinels vs Explorers',
65     'Sentinels vs Diplomats',
66     'Explorers vs Diplomats',
67     'Sentinels vs Analysts',
68     'Explorers vs Analysts'
69 ]
70
71 group_df=analyze_mbti_dimensions(topic_dist_df,mbti_groups)
72 create_dimension_comparison(group_df,"mbti_group_comparison",group_pairs,
    group_names)

```



For a unified comparison, we set the standard of significantly different as any absolute topic-preference gap that surpasses the 85th-percentile threshold, which is indicated by the red dashed line in each subplot.

From these 6 comparisons we can come up with the following conclusions:

1. Analysts show a clear surplus of discussion in the “Gender / Mental-Health” and “Politics / Social Issues” topics, whereas Diplomats contribute markedly less to these threads. This suggests that the NT temperaments are more inclined toward idea-driven or policy-oriented debates, while the NF group devotes its energy to lighter, experience-based con-

versations such as travel logs and casual fandom chatter.

2. When Sentinels are compared with Explorers, the former post more frequently about day-to-day planning, travel itineraries, and the buying or trading of collectibles. Explorers, in contrast, engage less with these logistics-heavy themes and more with personal identity talk. This difference implies that SJ personalities favour order and tangible exchanges, while SP personalities gravitate toward spontaneous self-expression.
3. Sentinels dominate K-pop industry news and merchandise exchange, yet they underperform on topics related to academic or personal growth. Therefore, the data indicate a Sentinel preference for operational or execution-oriented content, whereas Diplomats continue to focus on introspection and self-development narratives.
4. Explorers outpace Diplomats in discussions about ENHYPEN fandom, the game Genshin Impact, and LGBTQ identity issues, but fall behind in travel diaries, study tips, and political conversations. This result reinforces the notion that SP types pursue sensory entertainment and identity exploration, whereas NF types lean toward reflective or civic-minded themes.
5. Sentinels tweet far more about mainstream idols such as ENHYPEN and BTS, while Analysts turn their attention to academically oriented or self-improvement threads. We conclude that SJ users are deeply involved in collective fan activities, whereas NT users remain focused on knowledge and analytical depth.
6. Explorers lead Analysts in anime and manga chatter, yet they post significantly less about academic and political issues. The evidence points to an SP preference for leisure-centred pop-culture content, contrasting with an NT preference for intellectually demanding discussions.

6.1.5 MBTI type Clustering

Using LDA modeling, we have identified the topic preference different of MBTI personality types. To which extent does the estimated or stereotyped topic preference of the official MBTI groups align with their realistic behaviors? We cluster MBTI types to find out.

Reducing high-dimensional topic distributions into a three-dimensional principal component space is necessary for K-means clustering to be preformed. So, PCA dimensionality re-

duction is performed before we perform K-means clustering

```

1 def create_mbt_i_clustering_analysis_3d(n_clusters,topic_dist_df=
  topic_dist_df):
2
3     # Standardize data
4     scaler=StandardScaler()
5     scaled_data=scaler.fit_transform(topic_dist_df)
6
7     # 3D PCA dimensionality reduction
8     pca=PCA(n_components=3)
9     pca_3d_data=pca.fit_transform(scaled_data)
10
11    # K-means clustering (on 3D data)
12    kmeans=KMeans(n_clusters=n_clusters, random_state=42)
13    clusters=kmeans.fit_predict(pca_3d_data) # Note: clustering on 3D data

```

After clustering, we print PCA variance to see if PCA dimensionality reduction is effective.

```

1 # Print variance explained
2 print(f"3D PCA variance explained:")
3 print(f"PC1: {pca.explained_variance_ratio_[0]:.3f}")
4 print(f"PC2: {pca.explained_variance_ratio_[1]:.3f}")
5 print(f"PC3: {pca.explained_variance_ratio_[2]:.3f}")
6 print(f"Total: {pca.explained_variance_ratio_.sum():.3f}")

```

The results are:

PC1: 0.328

PC2: 0.265

PC3: 0.117

Total: 0.709

With a total of 70.9% of information successfully reserved, our dimensionality reduction is successful.


To interpret our clustering results, it is necessary for us to find out what PC1, PC2, PC3 represents respectively. So we print out the main contributing features of the three dimensions respectively and plot out PCA feature weights.

PC1 Main contributing features (sorted by weight):
 Topic 18 0.385
 Topic 8 0.361
 Topic 10 0.331
 Topic 5 0.308
 Topic 15 0.290
 Name: PC1, dtype: float64

PC2 Main contributing features (sorted by weight):
 Topic 12 0.417
 Topic 2 0.411
 Topic 4 0.358
 Topic 17 0.338
 Topic 1 0.334
 Name: PC2, dtype: float64

PC3 Main contributing features (sorted by weight):
 Topic 0 0.587
 Topic 14 0.483
 Topic 7 0.353
 Topic 9 0.303
 Topic 1 0.213
 Name: PC3, dtype: float64

Figure 6.6: Printed Main contributing features



By analyzing the printed features and plotted results, we approximately conclude the meaning of each axis:

1. PC1: Leisure & Fandom vs. Everyday-life.
2. PC2: Politics–Rationality vs. Entertainment–Support.
3. PC3: Fragmented expressions vs. centralized fandom behavior

6 distinctive clusters can be distinguished from our clustering results.

```

1  # Print clustering results
2  print("\nClustering results:")
3  print("=" * 50)
4  for cluster_id in range(n_clusters):

```

```

5     # Get mbti types in the current cluster
6     mbti_in_cluster=[topic_dist_df.index[i] for i in range(len(clusters
    )) if clusters[i] == cluster_id]
7     # Convert to uppercase and sort
8     mbti_in_cluster_upper=sorted([mbti.upper() for mbti in
    mbti_in_cluster])
9     print(f"Cluster {cluster_id + 1}: {'', '.join(mbti_in_cluster_upper)
    }")
10    print("=" * 50)

```

```

Clustering results:
=====
Cluster 1: ISFP, ISTP
Cluster 2: ENTJ, ESTJ, INTJ, ISTJ
Cluster 3: ESFJ, ISFJ
Cluster 4: ENFP, ENTP, ESFP, ESTP, INFP, INTP
Cluster 5: ENFJ, INFJ
=====

```

Figure 6.7: Printed clustering results

A 3-D scatter plot and it's 2-dimensional projection is plotted to visualize the results.

```


1     # 3D visualization
2     fig=plt.figure(figsize=(12, 9))
3     ax=fig.add_subplot(111, projection='3d')
4
5     # 3D scatter plot
6     scatter=ax.scatter(pca_3d_data[:,0], pca_3d_data[:,1], pca_3d_data
   [:,2],
7
8
9
10    c=clusters, cmap='viridis', s=100, alpha=0.7)
11
12
13
14    # Add MBTI labels
15    for i, mbti_type in enumerate(topic_dist_df.index):
16        ax.text(pca_3d_data[i,0], pca_3d_data[i,1], pca_3d_data[i,2],
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2
```

```

20
21
22
23 plt.colorbar(scatter)
24 plt.show()
25
26
27 return pca_3d_data, clusters
28 fig, axes = plt.subplots(1, 3, figsize=(15, 5))
29 axes[0].scatter(cl_analysis[0][:,0], cl_analysis[0][:,1],
30                 c=cl_analysis[1], cmap='viridis', s=100, alpha
31                 =0.7)
32 axes[1].scatter(cl_analysis[0][:,0], cl_analysis[0][:,2],
33                 c=cl_analysis[1], cmap='viridis', s=100, alpha
34                 =0.7)
35 axes[2].scatter(cl_analysis[0][:,1], cl_analysis[0][:,2],
36                 c=cl_analysis[1], cmap='viridis', s=100, alpha
37                 =0.7)
38 axes[0].set_xlabel("PC1")
39 axes[0].set_ylabel("PC2")
40 axes[0].set_title("Projection of MBTI Types onto PC1 and PC2")
41 axes[1].set_xlabel("PC1")
42 axes[1].set_ylabel("PC3")
43 axes[1].set_title("Projection of MBTI Types onto PC1 and PC3")
44 axes[2].set_xlabel("PC2")
45 axes[2].set_ylabel("PC3")
46 axes[2].set_title("Projection of MBTI Types onto PC2 and PC3")
47 for i, mbti_type in enumerate(topic_dist_df.index):
48     axes[0].text(cl_analysis[0][i,0], cl_analysis[0][i,1],
49                 mbti_type.upper(), fontsize=10, fontweight='bold')
50     axes[1].text(cl_analysis[0][i,0], cl_analysis[0][i,2],
51                 mbti_type.upper(), fontsize=10, fontweight='bold')
52     axes[2].text(cl_analysis[0][i,1], cl_analysis[0][i,2],
53                 mbti_type.upper(), fontsize=10, fontweight='bold')
54 fig.suptitle("Projection of MBTI Types onto PC1, PC2, and PC3",
55             fontsize=14, fontweight='bold')
56 plt.tight_layout()
57 plt.savefig(f"output/lda_model/lda_{model_id}/visualization/
58             mbti_clustering_projection.png")

```

```
54 plt.savefig(f"final_output/mbti_clustering_projection.png")
55 plt.show()
```



Using the concluded meaning of each axis, we can come up with the following conclusions:

- Cluster 1: ISFP, ISTP — leisure-oriented, low political talk, fragmented style
- Cluster 2: ENTJ, ESTJ, INTJ, ISTJ — everyday & rational topics, highly centralised
- Cluster 3: ESFJ, ISFJ — life-focused, cooperative support behaviour
- Cluster 4: ENFP, ENTP, ESFP, ESTP, INFP, INTP — strong entertainment preference, fragmented expression

- Cluster 5: ENFJ, INFJ — politics / affect-driven, centralised fandom

This outcome aligns closely to the four MBTI groups, suggesting certain reliability of MBTI grouping.

6.2 Expressive Patterns of MBTI Personalities

6.2.1 Data Cleaning and Pre-processing

Expression pattern analysis shares the same initial steps as LDA modeling: removing URLs, emojis, and tags. Please refer to the LDA data-cleaning section for details. We only need to load the cleaned data for our expressive pattern analysis.

```

1 from data_clean import Data_to_Clean, Data_to_Analyze
2 import pickle
3 import os
4 import pandas as pd
5 import copy
6 import json
7 import logging
8 from tqdm.auto import tqdm
9 import matplotlib.pyplot as plt
10 tqdm.pandas()
11
12 MBTI_types=[
13     'istj', 'isfj', 'infj', 'intj',
14     'istp', 'isfp', 'infp', 'intp',
15     'estp', 'esfp', 'enfp', 'entp',
16     'estj', 'esfj', 'enfj', 'entj'
17 ]
18 cleaned_data={T:None for T in MBTI_types}
19
20 for type in cleaned_data.keys():
21     file_path=f"Data\\cleaned_data\\{type}_cleaned.pkl"
22     try:
23         with open(file_path, 'rb') as f:
24             cleaned_data[type] = pickle.load(f)
25     except FileNotFoundError:
26         print(f"Error: File not found at {file_path}")
27     except pickle.UnpicklingError:

```

```

28     print(f"Error: Could not unpickle the file {file_path}. It might be
        corrupted or not a valid pickle file.")
29 except Exception as e:
30     print(f"An unexpected error occurred: {e}")

```

To check whether we have successfully imported the cleaned dataset, we print out the 0th column, "posts" row of `infp`.

```

1 infp=cleaned_data["infp"]
2 infp.data.loc[0,"posts"]

```

From the output, we can see that there is no URLs, emojis, and tags in our data, which means that we have successfully cleaned and read from the cleaned dataset. Our data is ready for analysis.

```

[50]: ['forest',
        'elizabeth',
        'holly',
        'fuss',
        'seat',
        'pant',
        'best',
        'friend',
        'day',
        'yes',
        'decoration',
        'old',
        'day',
        'change',
        'present',
        'guess',

```

Figure 6.8: Cleaned Data printed out

6.2.2 Linguistic Style Patterns of MBTI Types

We select 4 distinct linguistic dimensions to represent linguistic styles:

1. Sentence Quantity: A larger sentence quantity suggests that the user tends to express themselves in shorter, more frequent statements. This may reflect a conversational, spontaneous communication style, often associated with extraversion or emotional openness.
2. Word Count: Higher word count may indicate a more elaborative or expressive communication habit, suggesting the user tends to provide more context or detail. This could reflect traits such as thoughtfulness, emotional depth, or even analytical thinking.

3. Upper-Case Ratio: A higher ratio of uppercase letters often signifies stronger emotional expression, emphasis, or a more dramatic tone. It may reveal higher emotional arousal or a more assertive communication style, which could be linked to personality traits like enthusiasm or dominance.
4. Reading Ease(reflected by both Flesch and GF index): Higher reading ease scores imply simpler sentence structures and more familiar vocabulary, often seen in casual or informal communication. In contrast, lower scores suggest complexity and abstractness, which could indicate intellectual engagement, formality, or introversion. In our project, we adopted two kinds of rating systems to evaluate the reading ease of a context. The higher the Flesch Reading Ease score is, the easier the context can be understood; the lower the GF index is, the easier the context can be understood.

These values are first computed before further analysis.

1. Class Definition & Constructor

```

1 class Data_to_Analyze(Data_to_Clean):
2     def __init__(self, type, source=raw_data):
3         super().__init__(source)
4         self.data = self.data.loc[self.data["type"] == type].
5             reset_index(drop=True)
6         self.data_to_vec = None
7         self.basic_identities = pd.Series({
8             "type": type,
9             # Number of sentences in a post
10            "sentence_quantity": [],
11            "ave_sentence_quantity": None,
12            # Number of words in a post
13            "word_count": [],
14            "ave_word_count": None,
15            # Ratio of upper case characters in a post
16            "upper_ratio": [],
17            "ave_upper_ratio": None,
18            # Two readability indicators: Flesch Reading Ease and
19            # Gunning Fog Index
20            "reading_ease": [],
21            "ave_reading_ease": None,
22            "GF_index": [],

```



```

21         "ave_GF_index": None,
22         # Overall sentiment indicator (VADER)
23         "overall_vader_score": None
24     })
    
```

Defines a class `Data_to_Analyze` that inherits from `Data_to_Clean`.

- **Data subset** – The constructor calls `super().__init__(source)` to initialize the parent class, then filters the dataset so that only rows whose type column equals the target MBTI type remain (`self.data`).
- **Feature container** – `basic_identities` is a `pd.Series` used to store a collection of text statistics: sentence count, word count, upper case ratio, readability metrics (Flesch Reading Ease and Gunning Fog Index) and an overall VADER sentiment score.

2. Sentence Count

```

1 def get_sentence_quantity(self):
2     for post in self.data["posts"].values:
3         self.basic_identities["sentence_quantity"].append(len(post))
4     self.basic_identities["ave_sentence_quantity"] = ave(self.
        basic_identities["sentence_quantity"])
    
```

Iterates through every post (each post is already a list of sentences). The length of the list gives the number of sentences, which is appended to `sentence_quantity`. Finally, the helper `ave()` computes their mean.

3. Word Count

```

1 def get_word_count(self):
2     for post in self.data["posts"].values:
3         total = 0
4         for sentence in post:
5             total += len(sentence.split(" "))
6         self.basic_identities["word_count"].append(total)
7     self.basic_identities["ave_word_count"] = ave(self.
        basic_identities["word_count"])
    
```

For each post, it splits every sentence on whitespace to count words and sums them into total. The total per post is stored in `word_count`, and the average is calculated afterwards.

4. Upper Case Character Ratio

```

1  def get_upper_ratio(self):
2      for post in self.data["posts"].values:
3          char_count = 0
4          upper_count = 0
5          for sentence in post:
6              for ch in sentence:
7                  if ch.isalpha():
8                      char_count += 1
9                      if ch.isupper():
10                         upper_count += 1
11             if char_count:
12                 self.basic_identities["upper_ratio"].append(upper_count /
13                     char_count)
14         self.basic_identities["ave_upper_ratio"] = ave(self.
15             basic_identities["upper_ratio"])
    
```

Traverses every character of every sentence, counting alphabetic characters (char_count) and, among them, the upper case ones (upper_count). The ratio per post is stored; the overall mean is then computed.

5. Readability Metrics

```

1  def get_readability(self):
2      reading_ease = []
3      GF_idx = []
4      for post in self.data["posts"].values:
5          concatenated = post[0]
6          for idx in range(1, len(post)):
7              concatenated += post[idx]
8          reading_ease.append(textstat.flesch_reading_ease(concatenated)
9              )
10         GF_idx.append(textstat.gunning_fog(concatenated))
11     self.basic_identities["reading_ease"] = reading_ease
12     self.basic_identities["ave_reading_ease"] = ave(reading_ease)
13     self.basic_identities["GF_index"] = GF_idx
14     self.basic_identities["ave_GF_index"] = ave(GF_idx)
    
```

Each post's sentences are concatenated into a single string, after which textstat computes Flesch Reading Ease and Gunning Fog Index. Both per post values and their averages

are stored.

The calculation results are printed and displayed.

```

1 mbti_identities={
2     T.upper():{
3         k:cleaned_data[T].basic_identities[k]
4         for k in [
5             "ave_sentence_quantity",
6             "ave_word_count",
7             "ave_upper_ratio",
8             "ave_reading_ease",
9             "ave_GF_index"
10        ]
11    }
12    for T in MBTI_types
13 }
14 mbti_identities=pd.DataFrame(mbti_identities).T
15 mbti_identities
    
```

	ave_sentence_quantity	ave_word_count	ave_upper_ratio	ave_reading_ease	ave_GF_index
ISTJ	140.922780	1584.861004	0.125113	53.508301	16.561120
ISFJ	139.890110	1542.766484	0.139261	58.487995	14.762555
INFJ	136.120151	1662.837275	0.108945	59.505421	14.098761
INTJ	142.160051	1768.897567	0.111903	55.228515	15.652458
ISTP	142.599388	1439.327217	0.135959	50.868624	18.008930
ISFP	138.239782	1468.850136	0.147333	51.682698	17.722262
INFP	135.311232	1538.657566	0.133015	54.009626	16.649938
INTP	138.747226	1557.081381	0.124319	50.273724	18.050296
ESTP	138.510000	1528.890000	0.144286	54.100900	16.754100
ESFP	147.137931	1500.454023	0.157108	54.208218	16.571782
ENFP	141.171468	1655.497942	0.136338	55.011289	16.238724
ENTP	147.183709	1617.429809	0.125773	48.465754	18.679307
ESTJ	150.148148	1861.827160	0.099657	55.780123	15.963333
ESFJ	139.666667	1571.104762	0.141718	58.292857	15.020381
ENFJ	141.915058	1690.857143	0.119560	56.535425	15.473456
ENTJ	142.960573	1713.476703	0.116676	55.087849	15.837384

Figure 6.9: Table of Linguistic Style Features of MBTI Social Media Posts


In order to better interpret the underlying patterns in the table, we present descending his-

tograms for visual analysis.

```

1 column_mapping={
2     "ave_sentence_quantity":"Sentence Quantity",
3     "ave_word_count":"Word Count",
4     "ave_upper_ratio":"Upper Case Letter Ratio",
5     "ave_reading_ease":"Reading Ease"
6 }
7 fig,axes=plt.subplots(2,2,figsize=(18,10))
8 axes=axes.flatten()
9 for i,col in enumerate(mbti_identities.columns[:4]):
10     axes[i].bar(mbti_identities[col].sort_values(ascending=False).index,
11                mbti_identities[col].sort_values(ascending=False))
12     axes[i].set_ylabel(f"{column_mapping[col]}")
13     axes[i].set_title(f"{column_mapping[col]}")
14 fig.suptitle("Linguistic Features of MBTI Social Media Posts",fontsize=14,
15              fontweight='bold')
16 plt.legend()
17 plt.tight_layout()
18 plt.savefig("final_output/ling_features.png")
19 plt.show()

```



The histograms allow the observation of surface-level patterns in linguistic styles.

1. Sentence Quantity: The top three MBTI types with the highest average sentence counts are ESTJ (150.1), ENTP (147.2), and ESFP (147.1). In contrast, the bottom three are INFP (135.3), INFJ (136.1), and ISFJ (139.9). This may indicate a correlation between the Extroversion/Introversion type and the extent of verbal expression. However, the overall variation in sentence quantity is relatively minor, suggesting limited explanatory significance.
2. Word Count: ESTJ leads with an average of 1,861.8 words per post, followed by INTJ (1,768.9) and ENTJ (1,713.5). On the other end, ISTP (1,439.3), ISFP (1,468.9) and ESFP (1,500.5) write the fewest words. Overall, Thinking-Judging types (TJs) consistently post at greater length than Perceiving-Feeling types (PFs)
3. Upper-Case Ratio: Posts by ESFP (15.7% uppercase), ISFP (14.7%), and ESTP (14.4%) contain the highest proportion of capital letters, whereas ESTJ (10.0%), INFJ (10.9%), and INTJ (11.2%) post the least. Feeling-Perceiving personalities prefer to use uppercase—perhaps as a tool for emphasis or emotional expression—while Thinking-Judging profiles favor a more uniform casing.
4. Reading Ease: On the Flesch scale, INFJ (59.5), ISFJ (58.5), and ESFJ (58.3) write the most readable posts, whereas ENTP (48.5), INTP (50.3), and ISTP (50.9) produce denser, more complex text. Judging-Feeling types tends for simpler, clearer phrasing, while Perceiving-Thinking types trend toward more intricate language.

Three characteristic can also be observed from the standpoint of MBTI types.

1. ESTJ exhibits the greatest information throughput—leading all types in both mean sentence count and mean word count—whereas ENTP, although nearly as verbose in sentence frequency, records the lowest readability and most negative sentiment, underscoring that sheer output does not translate into a warmer tone.
2. ESFP and ISFP personalities stand out for their high upper-case ratios, corresponding to the commonly held view of ‘FP’ types as spontaneous and emotionally guided.
3. INFJ produces the most readable texts. Meanwhile, they are also among the top three most positive in emotional expression(analyzed in the next section). ENTP produces the least readable and positive texts.

6.2.3 Sentiment Analysis

Sentiment analysis, or opinion mining, is an active area of study in the field of natural language processing that analyzes people's opinions, sentiments, evaluations, attitudes, and emotions via the computational treatment of subjectivity in text. There are various approaches to sentimental analysis. In this assignment, we choose VADER (Valence Aware Dictionary for sEntiment Reasoning) as our tool to analyze the difference of different MBTI personalities in emotional expression due to its superiority in social media context (Kiritchenko, Zhu, & Mohammad, 2014).

We do the following steps to acquire VADER scoring:

```
1 analyzer = SentimentIntensityAnalyzer()
2 overall_vader_score = {'neg': 0.0, 'neu': 0.0, 'pos': 0.0, 'compound': 0.0}
```

- Instantiate NLTK's SentimentIntensityAnalyzer to compute sentiment scores.
- Initialize overall_vader_score as an aggregate dictionary with the four sentiment components (neg, neu, pos, compound), which will be used to assess the text's overall emotional state.

```
1 def addup_score_dict(new_dict, base_dict):
2     for key in base_dict.keys():
3         base_dict[key] += new_dict[key]
```

This function adds the sentiment scores of a sentence (or post) to the target dictionary. It iterates over the keys and sums the corresponding values, allowing either local or global sentiment accumulation.

```
1 def process_vader_score(post):
2     post_vader_score = {'neg': 0.0, 'neu': 0.0, 'pos': 0.0, 'compound':
3         0.0}
4     for sentence in post:
5         addup_score_dict(analyzer.polarity_scores(sentence), base_dict=
6             post_vader_score)
7     ave_score_dict(base_dict=post_vader_score, n=len(post))
8     addup_score_dict(new_dict=post_vader_score, base_dict=
9         overall_vader_score)
10    return post_vader_score
```

This nested function analyzes the sentiment of a single post (a list of sentences) through the following steps:

1. Initialize a score container for the post.
2. Traverse each sentence and obtain its sentiment scores with `polarity_scores()`.
3. Accumulate the sentence scores and divide by the number of sentences to compute the post's average sentiment.
4. Add this post's average score to the overall accumulator `overall_vader_score`.
5. Return the post's sentiment score so it can be stored back in the dataset.

```
1 self.data["vader_score"] = self.data["posts"].apply(process_vader_score)
```

This line applies `process_vader_score` to every post in `self.data`. The returned score dictionaries (neg, neu, pos, compound) are stored in a new column named `vader_score`.

```
1 ave_score_dict(overall_vader_score, len(self.data["posts"]))
2 self.basic_identities["overall_vader_score"] = overall_vader_score
```

After accumulating all post-level scores into `overall_vader_score`, divide by the total number of posts to obtain the average sentiment. Finally, record this overall score in the `basic_identities` dictionary under the key "overall_vader_score" as the global emotional characteristic of the personality type.

Having acquired the VADER score, we collect the average sentiment into a chart that is ordered by descending compound score.

```
1 all_vader_scores={T:cleaned_data[T].basic_identities["overall_vader_score"]
    for T in MBTI_types}
2 all_vader_scores=pd.DataFrame(all_vader_scores).T
3 all_vader_scores=all_vader_scores.sort_values(by="compound",ascending=False)
4 all_vader_scores
```

	neg	neu	pos	compound
isfj	0.074714	0.706432	0.179305	0.156459
infj	0.077386	0.706724	0.171925	0.146350
enfj	0.077268	0.706996	0.172352	0.146079
estj	0.075952	0.715335	0.168221	0.135310
esfj	0.079053	0.708754	0.163387	0.126369
enfp	0.081753	0.717179	0.163048	0.125133
intj	0.078297	0.723588	0.157496	0.117230
infp	0.086349	0.708721	0.163746	0.113087
isfp	0.086260	0.709435	0.164908	0.108508
entj	0.082541	0.718532	0.157704	0.106751
istj	0.083894	0.722811	0.153920	0.099382
esfp	0.088280	0.716392	0.156600	0.093912
estp	0.086791	0.719593	0.150472	0.093669
intp	0.086243	0.720133	0.151148	0.090751
istp	0.089930	0.711712	0.150577	0.078989
entp	0.087409	0.723706	0.144536	0.076574

Figure 6.10: Negative, Neutral, Positive and Compound VADER Score arranged in descending compound order

The characteristics of compound VADER score is described.

```
1 all_vader_scores["compound"].describe()
```

```
count    16.000000
mean      0.113410
std       0.024352
min       0.076574
25%      0.093851
50%      0.110797
75%      0.128604
max       0.156459
Name: compound, dtype: float64
```

Figure 6.11: Description of Compound VADER Scores

From the description, we find that the standard deviation is approximately 0.0243, showing a small overall fluctuation. The range between the most and least positive types spans about

3.3σ , indicating a significant but not extreme variation. Additionally, the standard deviation accounts for only about 20% of the mean, implying a compact and smooth distribution.

The fact that mean is slightly greater than the median suggests a longer tail on the higher end of the scale, which indicates that the distribution exhibits a slight right skew, towards a positive emotional expression. This is supported by a having positive mean value(0.113).

We further visualized the compound results of different MBTI by descending order to find the relationship of MBTI personalities and their sentimental expression.

```

1 x=all_vader_scores.index
2 y=all_vader_scores["compound"]
3 plt.figure(figsize=(10, 6))
4 plt.bar(x,y)
5 plt.xlabel("MBTI Types")
6 plt.ylabel("VADER Compound Score")
7 plt.title("VADER Compound Score for All MBTI Types",fontsize=14, fontweight
   = 'bold')
8 plt.tight_layout()
9 plt.savefig("final_output/vader.png")
10 plt.show()
    
```




Figure 6.12:

We find that ISFJ, INFJ, ENFJ has the highest compound score, while ISTP, ENTP has the lowest, suggesting personalities with F and J tend to be more positive in emotional expression.

To verify this point, we first decomposed every personality label into its four constituent letters and collected all VADER-compound scores belonging to the same pole of a dichotomy.

If $D \in \{I/E, S/N, T/F, J/P\}$ and L denotes one pole of D (e.g., $L = F$ within $D = T/F$), the group mean is obtained by

$$\bar{x}_L = \frac{1}{n_L} \sum_{k \in L} x_k,$$

where x_k is the compound score of the k -th MBTI type and n_L is the number of types that contain the letter L . Letting

$$\mu = \frac{1}{16} \sum_{i=1}^{16} x_i$$

denote the grand mean across all sixteen personalities, we express the relative contribution of letter L as

$$\Delta_L = \frac{\bar{x}_L - \mu}{\mu} \times 100\%.$$

Applying these definitions to our data we obtain $\bar{x}_F = 0.126987$, $\bar{x}_T = 0.099832$, $\bar{x}_J = 0.129241$, and $\bar{x}_P = 0.097578$, while the grand mean is $\mu = 0.113410$. Consequently, Feeling exceeds Thinking by $\Delta_{F,T} \approx 23.9\%$ and Judging exceeds Perceiving by $\Delta_{J,P} \approx 31.6\%$, whereas the contrasts for Extraversion–Introversion and Intuition–Sensing remain below 3 %. These magnitudes confirm that the third and fourth MBTI letters (T/F, J/P) play a significantly greater role in shaping positive emotional expression, while first two dimension make relatively small contribution.

To find the relation between the four roles—Diplomats (NF), Sentinels (SJ), Analysts (NT) and Explorers (SP)—we test its relative contribution. Writing $G \in \{NF, SJ, NT, SP\}$ and letting n_G be the number of types in group G ($n_G = 4$), the group score is obtained by

$$\bar{x}_G = \frac{1}{n_G} \sum_{k \in G} x_k, \quad G \in \{NF, SJ, NT, SP\},$$

with the grand mean μ defined in equation above. Substituting the individual compound values yields

$$\bar{x}_{NF} = 0.133, \quad \bar{x}_{SJ} = 0.129, \quad \bar{x}_{NT} = 0.098, \quad \bar{x}_{SP} = 0.094.$$

To place these figures on the common scale used earlier, we again report the relative devi-

ation

$$\Delta_G = \frac{\bar{x}_G - \mu}{\mu} \times 100\%.$$

Hence

$$\Delta_{NF} = +17.3\%, \quad \Delta_{SJ} = +13.7\%, \quad \Delta_{NT} = -13.6\%, \quad \Delta_{SP} = -17.1\%.$$

The ranking $\bar{x}_{NF} > \bar{x}_{SJ} > \bar{x}_{NT} > \bar{x}_{SP}$ mirrors the earlier letter-level findings: Diplomats, combining the affective “F” and the future-oriented “N”, produce the warmest tone; Sentinels follow closely, driven by the strongly positive “J” component; Analysts, dominated by the critical “T”, adopt a noticeably cooler register; and Explorers, whose “P” preference and playful spontaneity encourage criticism and slang, exhibit the lowest positivity.

```

1 def get_sentence_quantity(self):
2     for post in self.data["posts"].values:
3         self.basic_identities["sentence_quantity"].append(len(post))
4     self.basic_identities["ave_sentence_quantity"] = ave(self.
        basic_identities["sentence_quantity"])
    
```

7 Conclusion

Together, these two strands of evidence allow us to adopt a dialectical stance: MBTI’s four dimensions yield reliable behavioral insights, yet its theoretical assumption of strict independence does not fully hold. In other words, MBTI remains a valuable framework—provided its limitations are recognized and its results interpreted with appropriate caution.

On the one hand, according to Pittenger (1993), “*we would expect each factor to be independent of the other factors, inasmuch as the MBTI theory states that each of the four preference dimensions stands alone; questions within one factor should not correlate with questions in the other factors*” (p. 50). However, our empirical tests contradict this assumption: both chi-square analyses and inter-factor correlation matrices reveal that the four MBTI dimensions—E–I, S–N, T–F, and J–P—are not statistically independent, calling into question the theoretical orthogonality upon which MBTI is predicated.

MBTI can play a valuable role in facilitating self-awareness, improving team communication, and guiding career exploration by highlighting broad preference tendencies. It offers a

common language for discussing interpersonal differences and can inform coaching, leadership development, and collaborative problem-solving. However, relying too heavily on MBTI carries risks. First, type labels can become “social tags” that oversimplify complex inner worlds and foster stereotypes—for example, assuming every INTJ is cold and rational ignores their potential for empathy and emotional depth. Second, the reliability of any single test result is limited by mood, stress, social-desirability bias, and the test-taker’s context; using one score to choose friends or partners lacks scientific support. Finally, excessive trust in MBTI can open the door to manipulation, as bad actors may exploit type labels to gain trust or social leverage.

In short, MBTI offers valuable directional insight into broad personality tendencies—serving as a springboard for personal growth, team building, and career conversations—but it should never be the sole yardstick for judging an individual. By recognizing its psychometric limitations, avoiding type-based stereotypes, and remaining alert to potential misuse, we can benefit from MBTI’s strengths while steering clear of the pitfalls of oversimplified personality labelling.

References

- Fleenor, J. W. (1997). The relationship between the mbti and measures of personality and performance in management groups. *Developing leaders: Research and applications in psychological type and leadership development*, 115–138.
- Kiritchenko, S., Zhu, X., & Mohammad, S. (2014, 08). Sentiment analysis of short informal text. *The Journal of Artificial Intelligence Research (JAIR)*, 50. doi: 10.1613/jair.4272
- Yang, Y. (2022). Research on the application of mbti in organization. In *2022 7th international conference on social sciences and economic development (icssed 2022)* (pp. 1751–1754).
- Zibran, M. F. (2007). Chi-squared test of independence. *Department of Computer Science, University of Calgary, Alberta, Canada*, 1(1), 1–7.