Experiment Reproduction Guide for: "Domain-Adaptive Pretraining for Robust Sentiment Classification"

This document outlines the complete setup and reproduction steps for the experiments presented in our paper:
"Domain-Adaptive Pretraining for Robust Sentiment Classification" (ACL 2024 Submission ID #1245).
The code and data are hosted at https://github.com/nlp-lab/dapt-sentiment.
Please follow the instructions below to reproduce the results locally.

---

1. System Requirements

- **OS**: Ubuntu 20.04 / macOS Monterey / Windows 11 (WSL2 recommended)
- **Python**: 3.9
- **CUDA**: 11.7 (required for GPU training)
- **GPU**: NVIDIA RTX 3060 or above (optional but strongly recommended)
- **Disk Space**: Minimum 15 GB
- **RAM**: 16 GB recommended

---

2. Repository Setup

Clone the repository and navigate to the project directory:

bash

```
git clone https://github.com/nlp-lab/dapt-sentiment.git
cd dapt-sentiment
```

Check out the stable version:

bash

```
git checkout v1.0.1
```

3. Environment Configuration

We provide both Conda and pip environments. The recommended method is via Conda:

bash

```
conda create -n dapt_env python=3.9
conda activate dapt_env
pip install -r requirements.txt
```

If you encounter dependency issues, try:

bash

```
pip install -r requirements_gpu.txt
```

5. Pretraining (Domain-Adaptive BERT)

To run domain-adaptive pretraining on the Amazon dataset:

bash

```
python run_pretrain.py \
  --model_name bert-base-uncased \
  --train_file data/amazon/books.json \
  --output_dir checkpoints/dapt-books \
  --num_train_epochs 3 \
  --per_device_train_batch_size 32
```

Expected output:

- Model checkpoints saved to `checkpoints/dapt-books/`
- Training logs saved under `logs/pretrain/`

---

6. Fine-tuning & Evaluation on SST-2

To fine-tune the DAPT model and evaluate:

bash

```
python run_finetune.py \
  --model_path checkpoints/dapt-books \
  --task_name sst2 \
  --train_file data/sst2/train.tsv \
  --eval_file data/sst2/dev.tsv \
  --output_dir checkpoints/sst2-results \
  --num_train_epochs 4
```

Evaluation metrics:

- Accuracy (primary)
- F1 Score (for completeness)

Expected result (reproducible):

- **Accuracy** on SST-2 dev set: 92.1 ± 0.3%

7. Jupyter Notebook for Analysis

For error analysis and visualizations:

bash

```
jupyter notebook
```

Open:

bash

```
notebooks/error_analysis.ipynb
```

Features:

- Confusion matrix plots
- Attention visualization for selected examples
- Domain shift effect visualized with UMAP embeddings

---

8. GPU Usage & Troubleshooting

Check if GPU is available:

python

```
import torch
print(torch.cuda.get_device_name(0) if torch.cuda.is_available() else "No GPU found")
```

Common issues:

- `CUDA out of memory`: Reduce `--per_device_train_batch_size`
- `CUBLAS_STATUS_ALLOC_FAILED`: Reboot GPU runtime or lower parallelism

- `transformers` version mismatch: stick with `transformers==4.28.1`

---

9. Citation

If you use this code or reproduce the experiments, please cite:

bibtex

```
@misc{dapt-sentiment2024,
  author = {Jiang, Rui and Patel, Meera and Chen, Xiaoyu},
  title = {Domain-Adaptive Pretraining for Robust Sentiment Classification},
  year = {2024},
  howpublished = {\url{https://github.com/nlp-lab/dapt-sentiment}},
}
```

---

10. Contact

For questions, bug reports, or clarifications, please reach out via:

- GitHub Issues: https://github.com/nlp-lab/dapt-sentiment/issues
- Email: ruijiang@nlplab.edu