

Package ‘radiant’

March 16, 2016

Title Business Analytics using R and Shiny

Version 0.4.55

Date 2016-3-16

Description A platform-independent browser-based interface for business analytics in R, based on the Shiny package.

Depends R (>= 3.2.0),
magrittr (>= 1.5),
ggplot2 (>= 2.0.0),
lubridate (>= 1.5.0),
tidyr (>= 0.4.1),
dplyr (>= 0.4.3)

Imports DiagrammeR(>= 0.8.2),
car (>= 2.1.1),
MASS (>= 7.3),
gridExtra (>= 2.0.0),
AlgDesign (>= 1.1.7.3),
psych (>= 1.5.8),
GPArotation (>= 2014.11.1),
wordcloud (>= 2.5),
markdown (>= 0.7.7),
knitr (>= 1.10.5),
ggdendro (>= 0.1.17),
broom (>= 0.4.0),
pryr (>= 0.1.2),
shiny (>= 0.13.1),
jsonlite (>= 0.9.17),
shinyAce (>= 0.2.1),
DT (>= 0.1.45),
readr (>= 0.2.2),
data.tree (>= 0.1.9),
yaml (>= 2.1.13),
scales (>= 0.3.0),
curl (>= 0.9.4),
stringr (>= 1.0),
nnet (>= 7.3.11),
NeuralNetTools (>= 1.4.0),
rstudioapi (>= 0.5),
sandwich (>= 2.3.4)

Suggests rmarkdown (>= 0.7),
 devtools (>= 1.8.0),
 testthat (>= 0.10.0),
 covr (>= 1.2.0)

URL <https://github.com/vnijs/radiant>, <http://vnijs.github.io/radiant/>

BugReports <https://github.com/vnijs/radiant/issues>

License AGPL-3 | file LICENSE

LazyData true

RoxygenNote 5.0.1

R topics documented:

ann	7
as_character	8
as_distance	8
as_dmy	9
as_dmy_hm	9
as_dmy_hms	10
as_duration	10
as_factor	11
as_hm	11
as_hms	12
as_integer	12
as_mdy	13
as_mdy_hm	14
as_mdy_hms	14
as_numeric	15
as_ymd	15
as_ymd_hm	16
as_ymd_hms	16
auc	17
avengers	17
center	18
changedata	18
city	19
ci_label	19
ci_perc	20
clean_loadings	20
combinedata	21
compare_means	22
compare_props	23
computer	24
confint_robust	24
conjoint	25
conjoint_profiles	26
copy_all	27
copy_from	27
copy_imported	28
correlation	28

cross_tabs	29
crs	30
cv	31
dfprint	31
dfround	32
diamonds	32
doe	33
does_vary	33
dtree	34
dtree_parser	35
explore	35
factorizer	36
ff_design	37
filterdata	37
find_dropbox	38
find_max	38
find_min	39
flip	39
full_factor	40
getclass	41
getdata	41
getsummary	42
glm_reg	42
goodness	43
hier_clus	44
install_webshot	45
inverse	45
is_empty	45
is_string	46
items	47
kmeans_clus	47
kurtosi	48
launcher	48
level_list	49
lin_launcher	49
ln	50
loadcsv	51
loadcsv_url	51
loadr	52
loadrda_url	52
mac_launcher	53
make_dt	53
make_expl	54
make_funs	55
make_train	56
max_rm	56
mds	57
mean_rm	58
median_rm	58
min_rm	59
mode_rm	59
mp3	60

mutate_each	60
newspaper	61
normalize	61
nrprint	62
n_missing	62
p05	63
p10	63
p25	64
p75	64
p90	65
p95	65
performance	66
pivotr	67
plot.ann	68
plot.compare_means	68
plot.compare_props	69
plot.conjoint	70
plot.correlation_	71
plot.cross_tabs	71
plot.crs	72
plot.dtree	73
plot.full_factor	74
plot.glm_predict	74
plot.glm_reg	76
plot.goodness	77
plot.hier_clus	78
plot.kmeans_clus	79
plot.mds	79
plot.performance	80
plot.pivotr	81
plot.pmap	82
plot.pre_factor	83
plot.prob_binom	83
plot.prob_chisq	84
plot.prob_disc	84
plot.prob_expo	85
plot.prob_fdist	85
plot.prob_norm	86
plot.prob_pois	86
plot.prob_tdist	87
plot.prob_unif	87
plot.regression	88
plot.reg_predict	89
plot.repeater	90
plot.simulator	90
plot.single_mean	91
plot.single_prop	92
pmap	93
predict.ann	94
predict.glm_reg	94
predict.regression	95
pre_factor	96

print.gtable	97
prob_binom	98
prob_chisq	98
prob_disc	99
prob_expo	99
prob_fdist	100
prob_norm	100
prob_pois	101
prob_tdist	101
prob_unif	102
publishers	102
radiant	103
radiant_analytics	103
radiant_base	103
radiant_marketing	104
radiant_quant	104
recode	104
regression	104
repeater	105
rndnames	106
sample_size	107
sampling	108
saver	108
save_factors	109
save_membership	109
sdp_rm	110
sdw	110
sd_rm	111
serr	111
set_class	112
shopping	112
show_duplicated	112
sig_stars	113
simulator	114
sim_cleaner	115
sim_splitter	116
sim_summary	116
single_mean	117
single_prop	118
skew	119
square	119
sshh	119
sshhr	120
standardize	120
store	121
store.kmeans_clus	121
store_ann	122
store_crs	122
store_glm	123
store_reg	123
summary.ann	124
summary.compare_means	125

summary.compare_props	125
summary.conjoint	126
summary.conjoint_profiles	127
summary.correlation_	128
summary.cross_tabs	128
summary.crs	129
summary.doe	130
summary.dtree	130
summary.explore	131
summary.full_factor	132
summary.glm_reg	133
summary.goodness	134
summary.hier_clus	135
summary.kmeans_clus	135
summary.mds	136
summary.performance	137
summary.pivotr	137
summary.pmap	138
summary.pre_factor	139
summary.prob_binom	140
summary.prob_chisq	140
summary.prob_disc	141
summary.prob_expo	141
summary.prob_fdist	142
summary.prob_norm	142
summary.prob_pois	143
summary.prob_tdist	143
summary.prob_unif	144
summary.regression	144
summary.repeater	145
summary.sample_size	146
summary.sampling	146
summary.simulator	147
summary.single_mean	148
summary.single_prop	148
sum_rm	149
superheroes	150
table2data	150
test_specs	151
the_table	151
titanic	152
titanic_pred	152
toothpaste	153
update_radiant	153
varp_rm	153
var_check	154
var_rm	155
viewdata	155
visualize	156
weighted.sd	157
which.pmax	158
which.pmin	158

win_launcher	159
xtile	159

Index	161
--------------	------------

ann	<i>Artificial Neural Networks</i>
-----	-----------------------------------

Description

Artificial Neural Networks

Usage

```
ann(dataset, rvar, evar, lev = "", size = 1, decay = 0.5, wts = "None",
     check = "", dec = 3, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the logit (probit) model
evar	Explanatory variables in the model
lev	The level in the response variable defined as <code>_success_</code>
size	Number of units (nodes) in the hidden layer
decay	Parameter decay
wts	Weights to use in estimation
check	Optional output or estimation parameters. "vif" to show the multicollinearity diagnostics. "confint" to show coefficient confidence interval estimates. "odds" to show odds ratios and confidence interval estimates. "standardize" to output standardized coefficient estimates. "stepwise" to apply step-wise selection of variables
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/analytics/ann.html> for an example in Radiant

Value

A list with all variables defined in `ann` as an object of class `ann`

See Also

[summary.ann](#) to summarize results

[plot.ann](#) to plot results

[predict.ann](#) for prediction

Examples

```
result <- ann("titanic", "survived", c("pclass","sex"), lev = "Yes")
result <- ann("titanic", "survived", c("pclass","sex"))
```

as_character	<i>Wrapper for as.character</i>
--------------	---------------------------------

Description

Wrapper for as.character

Usage

```
as_character(x)
```

Arguments

x	Input vector
---	--------------

as_distance	<i>Distance in kilometers or miles between two locations based on lat-long Function based on http://www.movable-type.co.uk/scripts/latlong.html. Uses the haversine formula</i>
-------------	--

Description

Distance in kilometers or miles between two locations based on lat-long Function based on <http://www.movable-type.co.uk/scripts/latlong.html>. Uses the haversine formula

Usage

```
as_distance(lat1, long1, lat2, long2, unit = "km", R = c(km = 6371, miles = 3959)[[unit]])
```

Arguments

lat1	Latitude of location 1
long1	Longitude of location 1
lat2	Latitude of location 2
long2	Longitude of location 2
unit	Measure kilometers ("km", default) or miles ("miles")
R	Radius of the earth

Value

Distance bewteen two points

Examples

```
as_distance(32.8245525,-117.0951632, 40.7033127,-73.979681, unit = "km")
as_distance(32.8245525,-117.0951632, 40.7033127,-73.979681, unit = "miles")
```

as_dmy*Convert input in day-month-year format to date*

Description

Convert input in day-month-year format to date

Usage

```
as_dmy(x)
```

Arguments

x Input variable

Value

Date variable of class Date

Examples

```
as_dmy("1-2-2014")
```

as_dmy_hm*Convert input in day-month-year-hour-minute format to date-time*

Description

Convert input in day-month-year-hour-minute format to date-time

Usage

```
as_dmy_hm(x)
```

Arguments

x Input variable

Value

Date-time variable of class Date

Examples

```
as_dmy_hm("1-1-2014 12:15")
```

as_dmy_hms	<i>Convert input in day-month-year-hour-minute-second format to date-time</i>
------------	---

Description

Convert input in day-month-year-hour-minute-second format to date-time

Usage

```
as_dmy_hms(x)
```

Arguments

x	Input variable
---	----------------

Value

Date-time variable of class Date

Examples

```
as_dmy_hms("1-1-2014 12:15:01")
```

as_duration	<i>Wrapper for lubridate's as.duration function. Result converted to numeric</i>
-------------	--

Description

Wrapper for lubridate's as.duration function. Result converted to numeric

Usage

```
as_duration(x)
```

Arguments

x	Time difference
---	-----------------

as_factor	<i>Wrapper for as.factor</i>
-----------	------------------------------

Description

Wrapper for as.factor

Usage

```
as_factor(x)
```

Arguments

x	Input vector
---	--------------

as_hm	<i>Convert input in hour-minute format to time</i>
-------	--

Description

Convert input in hour-minute format to time

Usage

```
as_hm(x)
```

Arguments

x	Input variable
---	----------------

Value

Time variable of class Period

Examples

```
as_hm("12:45")  
## Not run:  
as_hm("12:45") %>% minute  
  
## End(Not run)
```

as_hms	<i>Convert input in hour-minute-second format to time</i>
--------	---

Description

Convert input in hour-minute-second format to time

Usage

```
as_hms(x)
```

Arguments

x	Input variable
---	----------------

Value

Time variable of class Period

Examples

```
as_hms("12:45:00")
## Not run:
as_hms("12:45:00") %>% hour
as_hms("12:45:00") %>% second

## End(Not run)
```

as_integer	<i>Convert variable to integer avoiding potential issues with factors</i>
------------	---

Description

Convert variable to integer avoiding potential issues with factors

Usage

```
as_integer(x)
```

Arguments

x	Input variable
---	----------------

Value

Integer

Examples

```
as_integer(rnorm(10))
as_integer(letters)
as_integer(5:10 %>% as.factor)
as.integer(5:10 %>% as.factor)
```

as_mdy*Convert input in month-day-year format to date*

Description

Convert input in month-day-year format to date

Usage

```
as_mdy(x)
```

Arguments

x	Input variable
---	----------------

Details

Use as.character if x is a factor

Value

Date variable of class Date

Examples

```
as_mdy("2-1-2014")
## Not run:
as_mdy("2-1-2014") %>% month(label = TRUE)
as_mdy("2-1-2014") %>% week
as_mdy("2-1-2014") %>% wday(label = TRUE)

## End(Not run)
```

as_mdy_hm	<i>Convert input in month-day-year-hour-minute format to date-time</i>
-----------	--

Description

Convert input in month-day-year-hour-minute format to date-time

Usage

```
as_mdy_hm(x)
```

Arguments

x	Input variable
---	----------------

Value

Date-time variable of class Date

Examples

```
as_mdy_hm("1-1-2014 12:15")
```

as_mdy_hms	<i>Convert input in month-day-year-hour-minute-second format to date-time</i>
------------	---

Description

Convert input in month-day-year-hour-minute-second format to date-time

Usage

```
as_mdy_hms(x)
```

Arguments

x	Input variable
---	----------------

Value

Date-time variable of class Date

Examples

```
as_mdy_hms("1-1-2014 12:15:01")
```

as_numeric	<i>Convert variable to numeric avoiding potential issues with factors</i>
------------	---

Description

Convert variable to numeric avoiding potential issues with factors

Usage

```
as_numeric(x)
```

Arguments

x	Input variable
---	----------------

Value

Numeric

Examples

```
as_numeric(rnorm(10))
as_numeric(letters)
as_numeric(5:10 %>% as.factor)
as.numeric(5:10 %>% as.factor)
as_numeric(c("1", "2"))
```

as_ymd	<i>Convert input in year-month-day format to date</i>
--------	---

Description

Convert input in year-month-day format to date

Usage

```
as_ymd(x)
```

Arguments

x	Input variable
---	----------------

Value

Date variable of class Date

Examples

```
as_ymd("2013-1-1")
```

as_ymd_hm	<i>Convert input in year-month-day-hour-minute format to date-time</i>
-----------	--

Description

Convert input in year-month-day-hour-minute format to date-time

Usage

```
as_ymd_hm(x)
```

Arguments

x	Input variable
---	----------------

Value

Date-time variable of class Date

Examples

```
as_ymd_hm("2014-1-1 12:15")
```

as_ymd_hms	<i>Convert input in year-month-day-hour-minute-second format to date-time</i>
------------	---

Description

Convert input in year-month-day-hour-minute-second format to date-time

Usage

```
as_ymd_hms(x)
```

Arguments

x	Input variable
---	----------------

Value

Date-time variable of class Date

Examples

```
as_ymd_hms("2014-1-1 12:15:01")
## Not run:
as_ymd_hms("2014-1-1 12:15:01") %>% as.Date
as_ymd_hms("2014-1-1 12:15:01") %>% month
as_ymd_hms("2014-1-1 12:15:01") %>% hour

## End(Not run)
```

auc	<i>Area Under the Curve (AUC)</i>
-----	-----------------------------------

Description

Area Under the Curve (AUC)

Usage

```
auc(pred, rvar, lev)
```

Arguments

pred	Prediction or predictor
rvar	Response variable
lev	The level in the response variable defined as <code>_success_</code>

Details

See <http://vnijs.github.io/radiant/analytics/performance.html> for an example in Radiant

Value

AUC statistic

See Also

[performance](#) to calculate results
[summary.performance](#) to summarize results
[plot.performance](#) to plot results

Examples

```
auc(mtcars$mpg, mtcars$vs, 1)
```

avengers	<i>Avengers</i>
----------	-----------------

Description

Avengers

Usage

```
data(avengers)
```

Format

A data frame with 7 rows and 4 variables

Details

List of avengers. The dataset is used to illustrate data merging / joining. Description provided in `attr(avengers,"description")`

center	<i>Center</i>
--------	---------------

Description

Center

Usage

`center(x)`

Arguments

x Input variable

Value

If x is a numeric variable return `x - mean(x)`

changedata	<i>Change data</i>
------------	--------------------

Description

Change data

Usage

`changedata(dataset, vars = c(), var_names = names(vars))`

Arguments

dataset Name of the dataframe to change
vars New variables to add to the data.frame
var_names Names for the new variables to add to the data.frame

Value

None

city	<i>City distances</i>
------	-----------------------

Description

City distances

Usage

```
data(city)
```

Format

A data frame with 45 rows and 3 variables

Details

Distance in miles between nine cities in the USA. The dataset is used to illustrate multi-dimensional scaling (MDS). Description provided in `attr(city,"description")`

ci_label	<i>Labels for confidence intervals</i>
----------	--

Description

Labels for confidence intervals

Usage

```
ci_label(alt = "two.sided", cl = 0.95)
```

Arguments

alt	Type of hypothesis ("two.sided", "less", "greater")
cl	Confidence level

Value

A character vector with labels for a confidence interval

Examples

```
ci_label("less", .95)
ci_label("two.sided", .95)
ci_label("greater", .9)
```

ci_perc	<i>Values at confidence levels</i>
---------	------------------------------------

Description

Values at confidence levels

Usage

```
ci_perc(dat, alt = "two.sided", cl = 0.95)
```

Arguments

dat	Data
alt	Type of hypothesis ("two.sided", "less", "greater")
cl	Confidence level

Value

A vector with values at a confidence level

Examples

```
ci_perc(0:100, "less", .95)
ci_perc(0:100, "greater", .95)
ci_perc(0:100, "two.sided", .80)
```

clean_loadings	<i>Sort and clean loadings</i>
----------------	--------------------------------

Description

Sort and clean loadings

Usage

```
clean_loadings(floadings, cutoff = 0, fsort = FALSE, dec = 8)
```

Arguments

floadings	Data frame with loadings
cutoff	Show only loadings with (absolute) values above cutoff (default = 0)
fsort	Sort factor loadings
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

Examples

```
result <- full_factor("diamonds",c("price","carat","table","x","y"))
clean_loadings(result$floadings, TRUE, .5, 2)
```

combinedata	<i>Combine datasets using dplyr's bind and join functions</i>
-------------	---

Description

Combine datasets using dplyr's bind and join functions

Usage

```
combinedata(dataset, cmb_dataset, by = "", add = "", type = "inner_join",
  name = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
cmb_dataset	Dataset name (string) to combine with 'dataset'. This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
by	Variables used to combine 'dataset' and 'cmb_dataset'
add	Variables to add from 'cmb_dataset'
type	The main bind and join types from the dplyr package are provided. inner_join returns all rows from x with matching values in y, and all columns from x and y. If there are multiple matches between x and y, all match combinations are returned. left_join returns all rows from x, and all columns from x and y. If there are multiple matches between x and y, all match combinations are returned. right_join is equivalent to a left join for datasets y and x. full_join combines two datasets, keeping rows and columns that appear in either. semi_join returns all rows from x with matching values in y, keeping just columns from x. A semi join differs from an inner join because an inner join will return one row of x for each matching row of y, whereas a semi join will never duplicate rows of x. anti_join returns all rows from x without matching values in y, keeping only columns from x. bind_rows and bind_cols are also included, as are intersect , union , and setdiff . See http://vnijs.github.io/radiant/base/combine.html for further details
name	Name for the combined dataset

Details

See <http://vnijs.github.io/radiant/base/combine.html> for an example in Radiant

Value

If list 'r_data' exists the combined dataset is added as 'name'. Else the combined dataset will be returned as 'name'

Examples

```
combinedata("titanic","titanic_pred",c("pclass","sex","age")) %>% head
titanic %>% combinedata("titanic_pred",c("pclass","sex","age")) %>% head
titanic %>% combinedata(titanic_pred,c("pclass","sex","age")) %>% head
avengers %>% combinedata(superheroes, type = "bind_cols")
combinedata("avengers", "superheroes", type = "bind_cols")
avengers %>% combinedata(superheroes, type = "bind_rows")
avengers %>% combinedata(superheroes, add = "publisher", type = "bind_rows")
```

compare_means

Compare means for two or more variables

Description

Compare means for two or more variables

Usage

```
compare_means(dataset, var1, var2, samples = "independent",
  alternative = "two.sided", conf_lev = 0.95, comb = "",
  adjust = "none", test = "t", dec = 3, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var1	A numeric variable or factor selected for comparison
var2	One or more numeric variables for comparison. If var1 is a factor only one variable can be selected and the mean of this variable is compared across (factor) levels of var1
samples	Are samples independent ("independent") or not ("paired")
alternative	The alternative hypothesis ("two.sided", "greater" or "less")
conf_lev	Span of the confidence interval
comb	Combinations to evaluate
adjust	Adjustment for multiple comparisons ("none" or "bonf" for Bonferroni)
test	T-test ("t") or Wilcox ("wilcox")
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/quant/compare_means.html for an example in Radiant

Value

A list of all variables defined in the function as an object of class `compare_means`

See Also

`summary.compare_means` to summarize results

`plot.compare_means` to plot results

Examples

```
result <- compare_means("diamonds", "cut", "price")
result <- diamonds %>% compare_means("cut", "price")
```

compare_props

Compare proportions across groups

Description

Compare proportions across groups

Usage

```
compare_props(dataset, var1, var2, levs = "", alternative = "two.sided",
  conf_lev = 0.95, comb = "", adjust = "none", dec = 3,
  data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var1	A grouping variable to split the data for comparisons
var2	The variable to calculate proportions for
levs	The factor level selected for the proportion comparison
alternative	The alternative hypothesis ("two.sided", "greater" or "less")
conf_lev	Span of the confidence interval
comb	Combinations to evaluate
adjust	Adjustment for multiple comparisons ("none" or "bonf" for Bonferroni)
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/quant/compare_props.html for an example in Radiant

Value

A list of all variables defined in the function as an object of class `compare_props`

See Also

[summary.compare_props](#) to summarize results
[plot.compare_props](#) to plot results

Examples

```
result <- compare_props("titanic", "pclass", "survived")
result <- titanic %>% compare_props("pclass", "survived")
```

computer	<i>Perceptions of computer (re)sellers</i>
----------	--

Description

Perceptions of computer (re)sellers

Usage

```
data(computer)
```

Format

A data frame with 5 rows and 8 variables

Details

Perceptions of computer (re)sellers. The dataset is used to illustrate perceptual maps. Description provided in `attr(computer,"description")`

confint_robust	<i>Confidence interval for robust estimators</i>
----------------	--

Description

Confidence interval for robust estimators

Usage

```
confint_robust(object, parm, level = 0.95, vcov = NULL, ...)
```

Arguments

object	A fitted model object
parm	A specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered
level	The confidence level required
vcov	Covariance matrix generated by, e.g., <code>sandwich::vcovHC</code>
...	Additional argument(s) for methods

Details

Wrapper for `confint.default` with robust standard errors. See <http://stackoverflow.com/a/3820125/1974918>

conjoint	<i>Conjoint analysis</i>
----------	--------------------------

Description

Conjoint analysis

Usage

```
conjoint(dataset, rvar, evar, reverse = FALSE, data_filter = "")
```

Arguments

<code>dataset</code>	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
<code>rvar</code>	The response variable (e.g., profile ratings)
<code>evar</code>	Explanatory variables in the regression
<code>reverse</code>	Reverse the values of the response variable ('rvar')
<code>data_filter</code>	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class `conjoint`

See Also

[summary.conjoint](#) to summarize results

[plot.conjoint](#) to plot results

Examples

```
result <- conjoint("mp3", rvar = "Rating", evar = "Memory:Shape")
result <- mp3 %>% conjoint(rvar = "Rating", evar = "Memory:Shape")
```

conjoint_profiles	<i>Create fractional factorial design for conjoint analysis</i>
-------------------	---

Description

Create fractional factorial design for conjoint analysis

Usage

```
conjoint_profiles(dataset)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
---------	--

Details

See http://vnijs.github.io/radiant/marketing/conjoint_profiles.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class `conjoint_profiles`

See Also

[summary.conjoint_profiles](#) to summarize results

Examples

```
## Not run:
cp <- c("price = c('$10','$13','$16')", "sight = c('Staggered','Not Staggered')",
      "comfort = c('Average no cupholder','Average cupholder','Large cupholder')",
      "audio.visual = c('Small plain','Large plain','Large digital')",
      "food = c('No food','Hot dogs and popcorn','Gourmet food')")
result <- conjoint_profiles("cp")
result <- cp %>% conjoint_profiles
rm(cp, envir = .GlobalEnv)

## End(Not run)
```

copy_all	<i>Source all package functions</i>
----------	-------------------------------------

Description

Source all package functions

Usage

```
copy_all(.from)
```

Arguments

.from	The package to pull the function from
-------	---------------------------------------

Details

Equivalent of source with local=TRUE for all package functions. Adapted from functions by smbache, author of the import package. See <https://github.com/smbache/import/issues/4> for a discussion. This function will be deprecated when (if) it is included in <https://github.com/smbache/import>

Examples

```
copy_all(radiant)
```

copy_from	<i>Source for package functions</i>
-----------	-------------------------------------

Description

Source for package functions

Usage

```
copy_from(.from, ...)
```

Arguments

.from	The package to pull the function from
...	Functions to pull

Details

Equivalent of source with local=TRUE for package functions. Written by smbache, author of the import package. See <https://github.com/smbache/import/issues/4> for a discussion. This function will be deprecated when (if) it is included in <https://github.com/smbache/import>

Examples

```
copy_from(radiant, getdata)
```

copy_imported	<i>Import all functions that a package imports for use with Shiny</i>
---------------	---

Description

Import all functions that a package imports for use with Shiny

Usage

```
copy_imported(.from)
```

Arguments

.from	The package to pull the function from
-------	---------------------------------------

Examples

```
## Not run:
copy_imported(radiant)

## End(Not run)
```

correlation	<i>Calculate correlations for two or more variables</i>
-------------	---

Description

Calculate correlations for two or more variables

Usage

```
correlation(dataset, vars, method = "pearson", dec = 2, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
vars	Variables to include in the analysis
method	Type of correlations to calculate. Options are "pearson", "spearman", and "kendall". "pearson" is the default
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/quant/correlation.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class `compare_means`

See Also

[summary.correlation_](#) to summarize results

[plot.correlation_](#) to plot results

Examples

```
result <- correlation("diamonds", c("price","carat"))
result <- correlation("diamonds", c("price","carat","clarity"))
result <- correlation("diamonds", "price:table")
result <- diamonds %>% correlation("price:table")
```

cross_tabs	<i>Evaluate associations between categorical variables</i>
------------	--

Description

Evaluate associations between categorical variables

Usage

```
cross_tabs(dataset, var1, var2, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var1	A categorical variable
var2	Another categorical variable
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/quant/cross_tabs.html for an example in Radiant

Value

A list of all variables used in `cross_tabs` as an object of class `cross_tabs`

See Also

[summary.cross_tabs](#) to summarize results

[plot.cross_tabs](#) to plot results

Examples

```
result <- cross_tabs("newspaper", "Income", "Newspaper")
result <- newspaper %>% cross_tabs("Income", "Newspaper")
```

crs	<i>Collaborative Filtering</i>
-----	--------------------------------

Description

Collaborative Filtering

Usage

```
crs(dataset, id, prod, pred, rate, name = "pred", data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
id	String with name of the variable containing user ids
prod	String with name of the variable with product ids
pred	Products to predict for
rate	String with name of the variable with product ratings
name	Name for the prediction variable
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/analytics/crs.html> for an example in Radiant

Value

A data.frame with the original data and a new column with predicted ratings

cv	<i>Coefficient of variation</i>
----	---------------------------------

Description

Coefficient of variation

Usage

```
cv(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

Coefficient of variation

Examples

```
cv(runif (100))
```

dfprint	<i>Print a data.frame with a specified number of decimal places</i>
---------	---

Description

Print a data.frame with a specified number of decimal places

Usage

```
dfprint(tbl, dec = 3, perc = FALSE)
```

Arguments

tbl	Data.frame
dec	Number of decimal places
perc	Display numbers as percentages (TRUE or FALSE)

Value

Data.frame for printing

Examples

```
data.frame(x = c("a","b"), y = c(1L, 2L), z = c(-0.0005, 3)) %>%  
  dfprint(dec = 3)
```

dfround	<i>Round double in a data.frame to a specified number of decimal places</i>
---------	---

Description

Round double in a data.frame to a specified number of decimal places

Usage

```
dfround(tbl, dec = 3)
```

Arguments

tbl	Data.frame
dec	Number of decimal places

Value

Data.frame for viewing

Examples

```
data.frame(x = c("a","b"), y = c(1L, 2L), z = c(-0.0005, 3.1)) %>%  
  dfround(dec = 3)
```

diamonds	<i>Diamond prices</i>
----------	-----------------------

Description

Diamond prices

Usage

```
data(diamonds)
```

Format

A data frame with 3000 rows and 10 variables

Details

A sample of 3,000 from the diamonds dataset bundled with ggplot2. Description provided in `attr(diamonds,"description")`

doe	Create (partial) factorial design
-----	-----------------------------------

Description

Create (partial) factorial design

Usage

```
doe(factors, int = "", trials = NA, seed = NA)
```

Arguments

factors	Categorical variables used as input for design
int	Vector of interaction terms to consider when generating design
trials	Number of trial to create. If NA then all feasible designs will be considered until a design with perfect D-efficiency is found
seed	Random seed to use as the starting point

Details

See <http://vnijs.github.io/radiant/analytics/doe.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class `conjoint_profiles`

See Also

[summary.conjoint_profiles](#) to summarize results

Examples

```
"price; $10; $13; $16\nfood; popcorn; gourmet; no food" %>% doe
```

does_vary	Does a vector have non-zero variability?
-----------	--

Description

Does a vector have non-zero variability?

Usage

```
does_vary(x)
```

Arguments

x	Input variable
---	----------------

Value

Logical. TRUE is there is variability

Examples

```
summarise_each(diamonds, funs(does_vary)) %>% as.logical
```

dtree	<i>Create a decision tree</i>
-------	-------------------------------

Description

Create a decision tree

Usage

```
dtree(yl, opt = "max")
```

Arguments

yl	A yaml string or a list (e.g., from <code>yaml::yaml.load_file()</code>)
opt	Find the maximum ("max") or minimum ("min") value for each decision node

Details

See <http://vnijs.github.io/radiant/base/dtree.html> for an example in Radiant

Value

A list with the initial tree and the calculated tree

See Also

[summary.dtree](#) to summarize results

[plot.dtree](#) to plot results

dtree_parser	<i>Parse yaml input for dtree to provide (more) useful error messages</i>
--------------	---

Description

Parse yaml input for dtree to provide (more) useful error messages

Usage

```
dtree_parser(y1)
```

Arguments

y1	A yaml string
----	---------------

Details

See <http://vnijs.github.io/radiant/base/dtree.html> for an example in Radiant

Value

An updated yaml string or a vector messages to return to the users

See Also

[dtree](#) to calculate tree
[summary.dtree](#) to summarize results
[plot.dtree](#) to plot results

explore	<i>Explore data</i>
---------	---------------------

Description

Explore data

Usage

```
explore(dataset, vars = "", byvar = "", fun = c("mean_rm", "sd_rm"),
  tabfilt = "", tabsort = "", data_filter = "", shiny = FALSE)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
vars	(Numerical) variables to summaries
byvar	Variable(s) to group data by before summarizing
fun	Functions to use for summarizing
tabfilt	Expression used to filter the table. This should be a string (e.g., "Total > 10000")
tabsort	Expression used to sort the table (e.g., "-Total")
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
shiny	Logical (TRUE, FALSE) to indicate if the function call originate inside a shiny app

Details

See <http://vnijs.github.io/radiant/base/explore.html> for an example in Radiant

Value

A list of all variables defined in the function as an object of class `explore`

See Also

[summary.explore](#) to show summaries

Examples

```
result <- explore("diamonds", "price:x")
summary(result)
result <- explore("diamonds", c("price", "carat"), byvar = "cut", fun = c("n_missing", "skew"))
summary(result)
diamonds %>% explore("price", byvar = "cut", fun = c("length", "n_distinct"))
```

factorizer

Convert character to factors as needed

Description

Convert character to factors as needed

Usage

```
factorizer(dat, safx = 20)
```

Arguments

dat	Data.frame
safx	Values to levels ratio

Value

Data.frame with factors

ff_design	<i>Function to generate a fractional factorial design</i>
-----------	---

Description

Function to generate a fractional factorial design

Usage

```
ff_design(attr, trial = 0, rseed = 172110)
```

Arguments

attr	Attributes used to generate profiles
trial	Number of trials that have already been run
rseed	Random seed to use

Details

See http://vnijs.github.io/radiant/marketing/conjoint_profiles.html for an example in Radiant

See Also

[conjoint_profiles](#) to calculate results
[summary.conjoint_profiles](#) to summarize results

filterdata	<i>Filter data with user-specified expression</i>
------------	---

Description

Filter data with user-specified expression

Usage

```
filterdata(dat, filt = "")
```

Arguments

dat	Data.frame to filter
filt	Filter expression to apply to the specified dataset (e.g., "price > 10000" if dataset is "diamonds")

Value

Filtered data.frame

find_dropbox	<i>Find a users dropbox directory</i>
--------------	---------------------------------------

Description

Find a users dropbox directory

Usage

```
find_dropbox(folder = 1)
```

Arguments

folder	If multiple folders are present select which one to use. The first folder listed is used by default.
--------	--

Value

Path to users personal dropbox directory

find_max	<i>Find maxium value of a vector</i>
----------	--------------------------------------

Description

Find maxium value of a vector

Usage

```
find_max(var, val = "")
```

Arguments

var	Variable to find the maximum for
val	Variable to find the value for at the maxium of var

Value

Value of val at the maximum of var

find_min	<i>Find minimum value of a vector</i>
----------	---------------------------------------

Description

Find minimum value of a vector

Usage

```
find_min(var, val = "")
```

Arguments

var	Variable to find the minimum for
val	Variable to find the value for at the maximum of var

Value

Value of val at the minimum of var

flip	<i>Flip the DT table to put Function, Variable, or Group by on top</i>
------	--

Description

Flip the DT table to put Function, Variable, or Group by on top

Usage

```
flip(expl, top = "fun")
```

Arguments

expl	Return value from explore
top	The variable (type) to display at the top of the table ("fun" for Function, "var" for Variable, and "byvar" for Group by. "fun" is the default)

Details

See <http://vnijs.github.io/radiant/base/explore.html> for an example in Radiant

See Also

[explore](#) to generate summaries
[make_expl](#) to create the DT table

Examples

```
result <- explore("diamonds", "price:x") %>% flip("var")

result <- explore("diamonds", "price", byvar = "cut", fun = c("length", "skew")) %>%
  flip("byvar")
```

full_factor	<i>Factor analysis (PCA)</i>
-------------	------------------------------

Description

Factor analysis (PCA)

Usage

```
full_factor(dataset, vars, method = "PCA", nr_fact = 2,
  rotation = "varimax", data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
vars	Variables to include in the analysis
method	Factor extraction method to use
nr_fact	Number of factors to extract
rotation	Apply varimax rotation or no rotation ("varimax" or "none")
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class `full_factor`

See Also

`summary.full_factor` to summarize results
`plot.full_factor` to plot results

Examples

```
result <- full_factor("diamonds",c("price","carat","table","x","y"))
result <- full_factor("diamonds",c("price","carat","table","x","y"), method = "maxlik")
result <- diamonds %>% full_factor(c("price","carat","table","x","y"), method = "maxlik")
```

getclass	<i>Get variable class</i>
----------	---------------------------

Description

Get variable class

Usage

```
getclass(dat)
```

Arguments

dat	Dataset to evaluate
-----	---------------------

Details

Get variable class information for each column in a data.frame

Value

Vector with class information for each variable

Examples

```
getclass(mtcars)
```

getdata	<i>Get data for analysis functions</i>
---------	--

Description

Get data for analysis functions

Usage

```
getdata(dataset, vars = "", filt = "", rows = NULL, na.rm = TRUE)
```

Arguments

dataset	Name of the dataframe
vars	Variables to extract from the dataframe
filt	Filter to apply to the specified dataset. For example "price > 10000" if dataset is "diamonds" (default is "")
rows	Select rows in the specified dataset. For example "1:10" for the first 10 rows or "n()-10:n()" for the last 10 rows (default is NULL)
na.rm	Remove rows with missing values (default is TRUE)

Value

Data.frame with specified columns and rows

getsummary	Create data.frame summary
------------	---------------------------

Description

Create data.frame summary

Usage

```
getsummary(dat, dc = getclass(dat))
```

Arguments

dat	Data.frame
dc	Class for each variable

Details

Used in Radiant's Data > Transform tab

glm_reg	Generalized linear models (GLM)
---------	---------------------------------

Description

Generalized linear models (GLM)

Usage

```
glm_reg(dataset, rvar, evar, lev = "", link = "logit", int = "",
        wts = "None", check = "", dec = 3, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the logit (probit) model
evar	Explanatory variables in the model
lev	The level in the response variable defined as <code>_success_</code>
link	Link function for glm ('logit' or 'probit'). 'logit' is the default
int	Interaction term to include in the model
wts	Weights to use in estimation
check	Optional estimation parameters. "standardize" to output standardized coefficient estimates. "stepwise" to apply step-wise selection of variables
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

Value

A list with all variables defined in `glm_reg` as an object of class `glm_reg`

See Also

`summary.glm_reg` to summarize the results
`plot.glm_reg` to plot the results
`predict.glm_reg` to generate predictions
`plot.glm_predict` to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex"), lev = "Yes")
result <- glm_reg("titanic", "survived", c("pclass","sex"))
```

goodness	<i>Evaluate if sample data for a categorical variable is consistent with a hypothesized distribution</i>
----------	--

Description

Evaluate if sample data for a categorical variable is consistent with a hypothesized distribution

Usage

```
goodness(dataset, var, p = c(), data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var	A categorical variable
p	Hypothesized distribution (either a numeric or character vector). If unspecified, defaults to an even distribution
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/quant/goodness.html> for an example in Radiant

Value

A list of all variables used in `cross_tabs` as an object of class `cross_tabs`

See Also

[summary.goodness](#) to summarize results

[plot.goodness](#) to plot results

Examples

```
result <- goodness("newspaper", "Income")
```

hier_clus

Hierarchical cluster analysis

Description

Hierarchical cluster analysis

Usage

```
hier_clus(dataset, vars, distance = "sq.euclidian", method = "ward.D",
  max_cases = 1000, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
vars	Vector of variables to include in the analysis
distance	Distance
method	Method
max_cases	Maximum number of cases allowed (default is 1000)
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/marketing/hier_clus.html for an example in Radiant

Value

A list of all variables used in `hier_clus` as an object of class `hier_clus`

See Also

[summary.hier_clus](#) to summarize results

[plot.hier_clus](#) to plot results

Examples

```
result <- hier_clus("shopping", vars = c("v1:v6"))
```

install_webshot	<i>Install webshot and phantomjs</i>
-----------------	--------------------------------------

Description

Install webshot and phantomjs

Usage

```
install_webshot()
```

inverse	<i>Calculate inverse of a variable</i>
---------	--

Description

Calculate inverse of a variable

Usage

```
inverse(x)
```

Arguments

x	Input variable
---	----------------

Value

1/x

is_empty	<i>Is a character variable defined</i>
----------	--

Description

Is a character variable defined

Usage

```
is_empty(x, empty = "")
```

Arguments

x	Character value to evaluate
empty	Indicate what 'empty' means. Default is empty string (i.e., "")

Details

Is a variable NULL or an empty string

Value

TRUE if empty, else FALSE

Examples

```
is_empty("")
is_empty(NULL)
```

is_string	<i>Is input a string?</i>
-----------	---------------------------

Description

Is input a string?

Usage

```
is_string(x)
```

Arguments

x	Input
---	-------

Details

Is input a string

Value

TRUE if string, else FALSE

Examples

```
is_string("")
is_string("data")
is_string(c("data", "data"))
is_string(NULL)
```

iterms	<i>Create a vector of interaction terms</i>
--------	---

Description

Create a vector of interaction terms

Usage

```
iterms(vars, nway, sep = ":")
```

Arguments

vars	Variables lables to use
nway	2-way (2) or 3-way (3) interactions labels to create
sep	Separator between variable names (default is :)

Value

Character vector of interaction term labels

Examples

```
paste0("var", 1:3) %>% iterms(2)
paste0("var", 1:3) %>% iterms(3)
paste0("var", 1:3) %>% iterms(2, sep = ".")
```

kmeans_clus	<i>K-means cluster analysis</i>
-------------	---------------------------------

Description

K-means cluster analysis

Usage

```
kmeans_clus(dataset, vars, hc_init = TRUE, distance = "sq.euclidian",
  method = "ward.D", seed = 1234, nr_clus = 2, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
vars	Vector of variables to include in the analysis
hc_init	Use centers from hier_clus as the starting point
distance	Distance for hier_clus
method	Method for hier_clus

seed	Random see to use for kmeans if hc_init is FALSE
nr_clus	Number of clusters to extract
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

Value

A list of all variables used in kmeans_clus as an object of class kmeans_clus

See Also

[summary.kmeans_clus](#) to summarize results
[plot.kmeans_clus](#) to plot results
[store.kmeans_clus](#) to add cluster membership to the selected dataset

Examples

```
result <- kmeans_clus("shopping", c("v1:v6"))
```

kurtosi	<i>Exporting the kurtosi function from the psych package</i>
---------	--

Description

Exporting the kurtosi function from the psych package

launcher	<i>Create a launcher on the desktop for Windows (.bat), Mac (.command), or Linux (.sh)</i>
----------	--

Description

Create a launcher on the desktop for Windows (.bat), Mac (.command), or Linux (.sh)

Usage

```
launcher(app = c("analytics", "marketing", "quant", "base"))
```

Arguments

app	App to run when the desktop icon is double-clicked ("analytics", "marketing", "quant", or "base"). Default is "analytics"
-----	---

Details

On Windows/Mac/Linux a file named radiant.bat/radiant.command/radiant.sh will be put on the desktop. Double-click the file to launch the specified Radiant app

See Also

[win_launcher](#) to create a shortcut on Windows

[mac_launcher](#) to create a shortcut on Mac

[lin_launcher](#) to create a shortcut on Linux

level_list	<i>Generate list of levels and unique values</i>
------------	--

Description

Generate list of levels and unique values

Usage

```
level_list(dat, ...)
```

Arguments

dat	A data.frame
...	Unquoted variable names to evaluate

Examples

```
data.frame(a = c(rep("a",5),rep("b",5)), b = c(rep(1,5),6:10)) %>% level_list
level_list(mtcars, mpg, cyl)
```

lin_launcher	<i>Create a launcher and updater for Linux (.sh)</i>
--------------	--

Description

Create a launcher and updater for Linux (.sh)

Usage

```
lin_launcher(app = c("analytics", "marketing", "quant", "base"))
```

Arguments

app	App to run when the desktop icon is double-clicked ("analytics", "marketing", "quant", or "base"). Default is "analytics"
-----	---

Details

On Linux a file named 'radiant.sh' and one named 'update_radiant.sh' will be put on the desktop. Double-click the file to launch the specified Radiant app or update Radiant to the latest version

Examples

```
if (interactive()) {
  if (Sys.info()["sysname"] == "Linux") {
    lin_launcher()
    fn <- paste0("/home/", Sys.getenv("USER"), "/Desktop/radiant.sh")
    if (!file.exists(fn))
      stop("Linux launcher not created")
    else
      unlink(fn)
  }
}
```

ln	Natural log
----	-------------

Description

Natural log

Usage

```
ln(x, na.rm = TRUE)
```

Arguments

- x Input variable
- na.rm Remove missing values (default is TRUE)

Value

Natural log of vector

Examples

```
ln(runif(10,1,2))
```

loadcsv	<i>Load a csv file with read.csv and read_csv</i>
---------	---

Description

Load a csv file with read.csv and read_csv

Usage

```
loadcsv(fn, header = TRUE, sep = ",", dec = ".", saf = TRUE,
        safx = 20)
```

Arguments

fn	File name string
header	Header in file (TRUE, FALSE)
sep	Use , (default) or ; or \t
dec	Decimal symbol. Use . (default) or ,
saf	Convert character variables to factors if (1) there are less than 100 distinct values (2) there are X (see safx) more values than levels
safox	Values to levels ratio

Value

Data.frame with (some) variables converted to factors

loadcsv_url	<i>Load a csv file with from a url</i>
-------------	--

Description

Load a csv file with from a url

Usage

```
loadcsv_url(csv_url, header = TRUE, sep = ",", dec = ".", saf = TRUE,
            safox = 20)
```

Arguments

csv_url	URL for the csv file
header	Header in file (TRUE, FALSE)
sep	Use , (default) or ; or \t
dec	Decimal symbol. Use . (default) or ,
saf	Convert character variables to factors if (1) there are less than 100 distinct values (2) there are X (see safox) more values than levels
safox	Values to levels ratio

Value

Data.frame with (some) variables converted to factors

loadr	<i>Load an rda or rds file and add it to the radiant data list (r_data) if available</i>
-------	--

Description

Load an rda or rds file and add it to the radiant data list (r_data) if available

Usage

```
loadr(fn, objname = "")
```

Arguments

fn	File name and path as a string. Extension must be either rda or rds
objname	Name to use for the data.frame. Defaults to the file name

Value

Data.frame in r_data or in the calling enviroment

loadrda_url	<i>Load an rda file from a url</i>
-------------	------------------------------------

Description

Load an rda file from a url

Usage

```
loadrda_url(rda_url)
```

Arguments

rda_url	URL for the csv file
---------	----------------------

Value

Data.frame

mac_launcher

*Create a launcher and updater for Mac (.command)***Description**

Create a launcher and updater for Mac (.command)

Usage

```
mac_launcher(app = c("analytics", "marketing", "quant", "base"))
```

Arguments

app App to run when the desktop icon is double-clicked ("analytics", "marketing", "quant", or "base"). Default is "analytics"

Details

On Mac a file named 'radiant.command' and one named 'update_radiant.command' will be put on the desktop. Double-click the file to launch the specified Radiant app or update Radiant to the latest version

Examples

```
if (interactive()) {
  if (Sys.info()["sysname"] == "Darwin") {
    mac_launcher()
    fn <- paste0("/Users/", Sys.getenv("USER"), "/Desktop/radiant.command")
    if (!file.exists(fn))
      stop("Mac launcher not created")
    else
      unlink(fn)
  }
}
```

make_dt

*Make a pivot tabel in DT***Description**

Make a pivot tabel in DT

Usage

```
make_dt(pvt, format = "none", perc = FALSE, dec = 3, search = "",
        searchCols = NULL, order = NULL)
```

Arguments

pvt	Return value from pivotr
format	Show Color bar ("color_bar"), Heat map ("heat"), or None ("none")
perc	Display numbers as percentages (TRUE or FALSE)
dec	Number of decimals to show
search	Global search. Used to save and restore state
searchCols	Column search and filter. Used to save and restore state
order	Column sorting. Used to save and restore state

Details

See <http://vnijs.github.io/radiant/base/pivotr.html> for an example in Radiant

See Also

[pivotr](#) to create the pivot-table using dplyr
[summary.pivotr](#) to print a plain text table

Examples

```
pivotr("diamonds", cvars = "cut") %>% make_dt
pivotr("diamonds", cvars = c("cut","clarity")) %>% make_dt(format = "color_bar")
ret <- pivotr("diamonds", cvars = c("cut","clarity"), normalize = "total") %>%
  make_dt(format = "color_bar", perc = TRUE)
```

make_expl

Make a tabel of summary statistics in DT

Description

Make a tabel of summary statistics in DT

Usage

```
make_expl(expl, top = "fun", dec = 3, search = "", searchCols = NULL,
  order = NULL)
```

Arguments

expl	Return value from explore
top	The variable (type) to display at the top of the table ("fun" for Function, "var" for Variable, and "byvar" for Group by)
dec	Number of decimals to show
search	Global search. Used to save and restore state
searchCols	Column search and filter. Used to save and restore state
order	Column sorting. Used to save and restore state

Details

See <http://vnijs.github.io/radiant/base/explore.html> for an example in Radiant

See Also

[pivotr](#) to create the pivot-table using dplyr

[summary.pivotr](#) to print a plain text table

Examples

```
tab <- explore("diamonds", "price:x") %>% make_expl
tab <- explore("diamonds", "price", byvar = "cut", fun = c("length", "skew")) %>%
  make_expl(top = "byvar")
```

make_funs	<i>Make a list of functions-as-formulas to pass to dplyr</i>
-----------	--

Description

Make a list of functions-as-formulas to pass to dplyr

Usage

```
make_funs(x)
```

Arguments

x	List of functions as strings
---	------------------------------

Value

List of functions to pass to dplyr in formula form

Examples

```
make_funs(c("mean", "sum_rm"))
```

make_train	<i>Generate a variable used to selected a training sample</i>
------------	---

Description

Generate a variable used to selected a training sample

Usage

```
make_train(n = 0.7, nr = 100)
```

Arguments

n	Number (or fraction) of observations to label as training
nr	Number of rows in the dataset

Value

0/1 variables for filtering

Examples

```
make_train(.5, 10)
```

max_rm	<i>Max with na.rm = TRUE</i>
--------	------------------------------

Description

Max with na.rm = TRUE

Usage

```
max_rm(x)
```

Arguments

x	Input variable
---	----------------

Value

Maximum value

Examples

```
max_rm(runif (100))
```

mds	(Dis)similarity based brand maps (MDS)
-----	--

Description

(Dis)similarity based brand maps (MDS)

Usage

```
mds(dataset, id1, id2, dis, method = "metric", nr_dim = 2,  
      data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
id1	A character variable or factor with unique entries
id2	A character variable or factor with unique entries
dis	A numeric measure of brand dissimilarity
method	Apply metric or non-metric MDS
nr_dim	Number of dimensions
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/marketing/mds.html> for an example in Radiant

Value

A list of all variables defined in the function as an object of class `mds`

See Also

[summary.mds](#) to summarize results

[plot.mds](#) to plot results

Examples

```
result <- mds("city", "from", "to", "distance")  
summary(result)  
result <- mds("diamonds", "clarity", "cut", "price")  
summary(result)
```

mean_rm	<i>Mean with na.rm = TRUE</i>
---------	-------------------------------

Description

Mean with na.rm = TRUE

Usage

```
mean_rm(x)
```

Arguments

x	Input variable
---	----------------

Value

Mean value

Examples

```
mean_rm(runif (100))
```

median_rm	<i>Median with na.rm = TRUE</i>
-----------	---------------------------------

Description

Median with na.rm = TRUE

Usage

```
median_rm(x)
```

Arguments

x	Input variable
---	----------------

Value

Median value

Examples

```
median_rm(runif (100))
```

min_rm	<i>Min with na.rm = TRUE</i>
--------	------------------------------

Description

Min with na.rm = TRUE

Usage

```
min_rm(x)
```

Arguments

x Input variable

Value

Minimum value

Examples

```
min_rm(runif (100))
```

mode_rm	<i>Mode with na.rm = TRUE</i>
---------	-------------------------------

Description

Mode with na.rm = TRUE

Usage

```
mode_rm(x)
```

Arguments

x Input variable

Value

Mode value

Examples

```
mode_rm(diamonds$cut)
```

mp3	<i>Conjoint data for MP3 players</i>
-----	--------------------------------------

Description

Conjoint data for MP3 players

Usage

```
data(mp3)
```

Format

A data frame with 18 rows and 6 variables

Details

Conjoint data for MP3 players. Description provided in attr(mp3,"description")

mutate_each	<i>Add transformed variables to a data frame (NSE)</i>
-------------	--

Description

Add tranformed variables to a data frame (NSE)

Usage

```
mutate_each(tbl, funs, ..., ext = "")
```

Arguments

tbl	Data frame to add transformed variables to
funs	Function(s) to apply (e.g., funs(log))
...	Variables to transform
ext	Extension to add for each variable

Details

Wrapper for dplyr::mutate_each that allows custom variable name extensions

Examples

```
mutate_each(mtcars, funs(log), mpg, cyl, ext = "_log")
```

newspaper	<i>Newspaper readership</i>
-----------	-----------------------------

Description

Newspaper readership

Usage

```
data(newspaper)
```

Format

A data frame with 580 rows and 2 variables

Details

Newspaper readership data for 580 consumers. Description provided in `attr(newspaper,"description")`

normalize	<i>Normalize a variable x by a variable y</i>
-----------	---

Description

Normalize a variable x by a variable y

Usage

```
normalize(x, y)
```

Arguments

x	Input variable
y	Normalizing variable

Value

x/y

nrprint	<i>Print a number with a specified number of decimal places, thousand sep, and a symbol</i>
---------	---

Description

Print a number with a specified number of decimal places, thousand sep, and a symbol

Usage

```
nrprint(x, sym = "", dec = 2, perc = FALSE)
```

Arguments

x	Number or vector
sym	Symbol to use
dec	Number of decimal places
perc	Display number as a percentage

Value

Character (vector) in the desired format

Examples

```
nrprint(2000, "$")
nrprint(2000, dec = 4)
nrprint(.05, perc = TRUE)
nrprint(c(.1, .99), perc = TRUE)
nrprint(data.frame(a = c(.1, .99)), perc = TRUE)
nrprint(data.frame(a = 1000), sym = "$", dec = 0)
```

n_missing	<i>Number of missing values</i>
-----------	---------------------------------

Description

Number of missing values

Usage

```
n_missing(x)
```

Arguments

x	Input variable
---	----------------

Value

number of missing values

Examples

```
n_missing(c("a", "b", NA))
```

p05

5th percentile

Description

5th percentile

Usage

```
p05(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

5th percentile

Examples

```
p05(rnorm(100))
```

p10

10th percentile

Description

10th percentile

Usage

```
p10(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

10th percentile

Examples

```
p10(rnorm(100))
```

p25	<i>25th percentile</i>
-----	------------------------

Description

25th percentile

Usage

```
p25(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

25th percentile

Examples

```
p25(rnorm(100))
```

p75	<i>75th percentile</i>
-----	------------------------

Description

75th percentile

Usage

```
p75(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

75th percentile

Examples

```
p75(rnorm(100))
```

p90	<i>90th percentile</i>
-----	------------------------

Description

90th percentile

Usage

```
p90(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

90th percentile

Examples

```
p90(rnorm(100))
```

p95	<i>95th percentile</i>
-----	------------------------

Description

95th percentile

Usage

```
p95(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

95th percentile

Examples

```
p95(rnorm(100))
```

performance	<i>Model performance</i>
-------------	--------------------------

Description

Model performance

Usage

```
performance(dataset, pred, rvar, lev = "", qnt = 10, margin = 1,
  cost = 1, train = "", method = "xtile", data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
pred	Prediction or predictor
rvar	Response variable
lev	The level in the response variable defined as <code>_success_</code>
qnt	Number of bins to create
margin	Margin on each customer purchase
cost	Cost for each connection (e.g., email or mailing)
train	Use data from training ("Training"), validation ("Validation"), both ("Both"), or all data ("All") to evaluate model performance
method	Use either <code>ntile</code> or <code>xtile</code> to split the data (default is <code>xtile</code>)
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/analytics/performance.html> for an example in Radiant

Value

A list of results

See Also

[summary.performance](#) to summarize results

[plot.performance](#) to plot results

Examples

```
result <- performance("titanic", c("age", "fare"), "survived")
```

pivotr

*Create a pivot table using dplyr***Description**

Create a pivot table using dplyr

Usage

```
pivotr(dataset, cvars = "", nvar = "None", fun = "mean_rm",
        normalize = "None", tabfilt = "", tabsort = "", data_filter = "",
        shiny = FALSE)
```

Arguments

dataset	Name of the dataframe to change
cvars	Categorical variables
nvar	Numerical variable
fun	Function to apply to numerical variable
normalize	Normalize the table by "row" total, "column" totals, or overall "total"
tabfilt	Expression used to filter the table. This should be a string (e.g., "Total > 10000")
tabsort	Expression used to sort the table (e.g., "-Total")
data_filter	Expression used to filter the dataset. This should be a string (e.g., "price > 10000")
shiny	Logical (TRUE, FALSE) to indicate if the function call originate inside a shiny app

Details

Create a pivot-table. See <http://vnijs.github.io/radiant/base/pivotr.html> for an example in Radiant

Examples

```
result <- pivotr("diamonds", cvars = "cut")$tab
result <- pivotr("diamonds", cvars = c("cut", "clarity", "color"))$tab
result <- pivotr("diamonds", cvars = "cut:clarity", nvar = "price")$tab
result <- pivotr("diamonds", cvars = "cut", normalize = "total")$tab
```

plot.ann	<i>Plot method for the ann function</i>
----------	---

Description

Plot method for the ann function

Usage

```
## S3 method for class 'ann'  
plot(x, shiny = FALSE, ...)
```

Arguments

x	Return value from ann
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/analytics/ann.html> for an example in Radiant

See Also

[ann](#) to generate results
[summary.ann](#) to summarize results
[predict.ann](#) for prediction

Examples

```
result <- ann("titanic", "survived", c("pclass","sex"), lev = "Yes")  
plot(result, plots = c("imp","net"))
```

plot.compare_means	<i>Plot method for the compare_means function</i>
--------------------	---

Description

Plot method for the compare_means function

Usage

```
## S3 method for class 'compare_means'  
plot(x, plots = "scatter", shiny = FALSE, ...)
```

Arguments

x	Return value from compare_means
plots	One or more plots ("bar", "density", "box", or "scatter")
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_means.html for an example in Radiant

See Also

[compare_means](#) to calculate results
[summary.compare_means](#) to summarize results

Examples

```
result <- compare_means("diamonds", "cut", "price")
plot(result, plots = c("bar", "density"))
```

plot.compare_props	<i>Plot method for the compare_props function</i>
--------------------	---

Description

Plot method for the compare_props function

Usage

```
## S3 method for class 'compare_props'
plot(x, plots = "bar", shiny = FALSE, ...)
```

Arguments

x	Return value from compare_props
plots	One or more plots of proportions ("bar" or "dodge")
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_props.html for an example in Radiant

See Also

[compare_props](#) to calculate results
[summary.compare_props](#) to summarize results

Examples

```
result <- compare_props("titanic", "pclass", "survived")
plot(result, plots = c("bar", "dodge"))
```

plot.conjoint

Plot method for the conjoint function

Description

Plot method for the conjoint function

Usage

```
## S3 method for class 'conjoint'
plot(x, plots = "pw", scale_plot = FALSE,
     shiny = FALSE, ...)
```

Arguments

x	Return value from conjoint
plots	Show either the part-worth ("pw") or importance-weights ("iw") plot
scale_plot	Scale the axes of the part-worth plots to the same range
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results
[summary.conjoint](#) to summarize results

Examples

```
result <- conjoint(dataset = "mp3", rvar = "Rating", evar = "Memory:Shape")
plot(result, scale_plot = TRUE)
plot(result, plots = "iw")
```

plot.correlation_	<i>Plot method for the correlation function</i>
-------------------	---

Description

Plot method for the correlation function

Usage

```
## S3 method for class 'correlation_'  
plot(x, ...)
```

Arguments

x	Return value from correlation
...	further arguments passed to or from other methods.

Details

See <http://vnijs.github.io/radiant/quant/correlation.html> for an example in Radiant

See Also

[correlation](#) to calculate results
[summary.correlation_](#) to summarize results

Examples

```
result <- correlation("diamonds",c("price","carat","clarity"))  
plot(result)  
diamonds %>% correlation("price:clarity") %>% plot
```

plot.cross_tabs	<i>Plot method for the cross_tabs function</i>
-----------------	--

Description

Plot method for the cross_tabs function

Usage

```
## S3 method for class 'cross_tabs'  
plot(x, check = "", shiny = FALSE, ...)
```

Arguments

x	Return value from cross_tabs
check	Show plots for variables var1 and var2. "observed" for the observed frequencies table, "expected" for the expected frequencies table (i.e., frequencies that would be expected if the null hypothesis holds), "chi_sq" for the contribution to the overall chi-squared statistic for each cell (i.e., $(o - e)^2 / e$), "dev_std" for the standardized differences between the observed and expected frequencies (i.e., $(o - e) / \sqrt{e}$), and "row_perc", "col_perc", and "perc" for row, column, and table percentages respectively
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/cross_tabs.html for an example in Radiant

See Also

[cross_tabs](#) to calculate results
[summary.cross_tabs](#) to summarize results

Examples

```
result <- cross_tabs("newspaper", "Income", "Newspaper")
plot(result, check = c("observed", "expected", "chi_sq"))
newspaper %>% cross_tabs("Income", "Newspaper") %>% plot(c("observed", "expected"))
```

plot.crs

Plot method for the crs function

Description

Plot method for the crs function

Usage

```
## S3 method for class 'crs'
plot(x, shiny = FALSE, ...)
```

Arguments

x	Return value from crs
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/analytics/crs.html> for an example in Radiant

See Also

[crs](#) to generate results

[summary.crs](#) to summarize results

plot.dtree

Plot method for the dtree function

Description

Plot method for the dtree function

Usage

```
## S3 method for class 'dtree'  
plot(x, symbol = "$", dec = 3, final = FALSE,  
     shiny = FALSE, ...)
```

Arguments

x	Return value from dtree
symbol	Monetary symbol to use (\$ is the default)
dec	Decimal places to round results to
final	If TRUE plot the decision tree solution, else the initial decision tree
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/dtree.html> for an example in Radiant

See Also

[dtree](#) to generate the result

[summary.dtree](#) to summarize results

plot.full_factor	<i>Plot method for the full_factor function</i>
------------------	---

Description

Plot method for the full_factor function

Usage

```
## S3 method for class 'full_factor'
plot(x, shiny = FALSE, ...)
```

Arguments

x	Return value from <code>full_factor</code>
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

See Also

`full_factor` to calculate results
`plot.full_factor` to plot results

Examples

```
result <- full_factor("diamonds", c("price", "carat", "table"))
plot(result)
result <- full_factor("computer", "high_end:business")
summary(result)
```

plot.glm_predict	<i>Plot method for the predict.glm_reg function</i>
------------------	---

Description

Plot method for the predict.glm_reg function

Usage

```
## S3 method for class 'glm_predict'
plot(x, xvar = "", facet_row = ".", facet_col = ".",
     color = "none", conf_lev = 0.95, ...)
```

Arguments

x	Return value from <code>predict.glm_reg</code> .
xvar	Variable to display along the X-axis of the plot
facet_row	Create vertically arranged subplots for each level of the selected factor variable
facet_col	Create horizontally arranged subplots for each level of the selected factor variable
color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different colour
conf_lev	Confidence level to use for prediction intervals (.95 is the default). Note that the error bars for predictions are approximations at this point.
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

`glm_reg` to generate the result

`summary.glm_reg` to summarize results

`plot.glm_reg` to plot results

`predict.glm_reg` to generate predictions

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex","age"), lev = "Yes")
pred <- predict(result, pred_cmd = "pclass = levels(pclass)")
plot(pred, xvar = "pclass")
pred <- predict(result, pred_cmd = "age = 0:100")
plot(pred, xvar = "age")
pred <- predict(result, pred_cmd = "pclass = levels(pclass), sex = levels(sex)")
plot(pred, xvar = "pclass", color = "sex")
pred <- predict(result, pred_cmd = "pclass = levels(pclass), age = seq(0,100,20)")
plot(pred, xvar = "pclass", color = "age")
plot(pred, xvar = "age", color = "pclass")
pred <- predict(result, pred_cmd="pclass=levels(pclass), sex=levels(sex), age=seq(0,100,20)")
plot(pred, xvar = "age", color = "sex", facet_col = "pclass")
plot(pred, xvar = "age", color = "pclass", facet_col = "sex")
pred <- predict(result, pred_cmd="pclass=levels(pclass), sex=levels(sex), age=seq(0,100,5)")
plot(pred, xvar = "age", color = "sex", facet_col = "pclass")
plot(pred, xvar = "age", color = "pclass", facet_col = "sex")
```

plot.glm_reg	<i>Plot method for the glm_reg function</i>
--------------	---

Description

Plot method for the glm_reg function

Usage

```
## S3 method for class 'glm_reg'
plot(x, plots = "", conf_lev = 0.95, intercept = FALSE,
     shiny = FALSE, ...)
```

Arguments

x	Return value from glm_reg
plots	Plots to produce for the specified GLM model. Use "" to avoid showing any plots (default). "hist" shows histograms of all variables in the model. "scatter" shows scatter plots (or box plots for factors) for the response variable with each explanatory variable. "dashboard" is a series of four plots used to visually evaluate model. "coef" provides a coefficient plot
conf_lev	Confidence level to use for coefficient and odds confidence intervals (.95 is the default)
intercept	Include the intercept in the coefficient plot (TRUE or FALSE). FALSE is the default
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

[glm_reg](#) to generate results
[plot.glm_reg](#) to plot results
[predict.glm_reg](#) to generate predictions
[plot.glm_predict](#) to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex"), lev = "Yes")
plot(result, plots = "coef")
```

plot.goodness	<i>Plot method for the goodness function</i>
---------------	--

Description

Plot method for the goodness function

Usage

```
## S3 method for class 'goodness'  
plot(x, check = "", shiny = FALSE, ...)
```

Arguments

x	Return value from goodness
check	Show plots for variable var. "observed" for the observed frequencies table, "expected" for the expected frequencies table (i.e., frequencies that would be expected if the null hypothesis holds), "chi_sq" for the contribution to the overall chi-squared statistic for each cell (i.e., $(o - e)^2 / e$), "dev_std" for the standardized differences between the observed and expected frequencies (i.e., $(o - e) / \sqrt{e}$), and "perc" for percentages
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/goodness> for an example in Radiant

See Also

[goodness](#) to calculate results
[summary.goodness](#) to summarize results

Examples

```
result <- goodness("newspaper", "Income")  
plot(result, check = c("observed", "expected", "chi_sq"))  
newspaper %>% goodness("Income") %>% plot(c("observed", "expected"))
```

plot.hier_clus	<i>Plot method for the hier_clus function</i>
----------------	---

Description

Plot method for the hier_clus function

Usage

```
## S3 method for class 'hier_clus'
plot(x, plots = c("scree", "diff"), cutoff = 0.02,
     shiny = FALSE, ...)
```

Arguments

x	Return value from hier_clus
plots	Plots to return. "diff" shows the percentage change in within-cluster heterogeneity as respondents are group into different number of clusters, "dendro" shows the dendrogram, "scree" shows a scree plot of within-cluster heterogeneity
cutoff	For large datasets plots can take time to render and become hard to interpret. By selection a cutoff point (e.g., 0.05 percent) the initial steps in hierachical cluster analysis are removed from the plot
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/hier_clus.html for an example in Radiant

See Also

[hier_clus](#) to generate results
[summary.hier_clus](#) to summarize results

Examples

```
result <- hier_clus("shopping", vars = c("v1:v6"))
plot(result, plots = c("diff", "scree"), cutoff = .05)
plot(result, plots = "dendro", cutoff = 0)
shopping %>% hier_clus(vars = c("v1:v6")) %>% plot
```

plot.kmeans_clus	<i>Plot method for kmeans_clus</i>
------------------	------------------------------------

Description

Plot method for kmeans_clus

Usage

```
## S3 method for class 'kmeans_clus'  
plot(x, shiny = FALSE, ...)
```

Arguments

x	Return value from kmeans_clus
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

See Also

[kmeans_clus](#) to generate results
[summary.kmeans_clus](#) to summarize results
[store.kmeans_clus](#) to add cluster membership to the selected dataset

Examples

```
result <- kmeans_clus("shopping", vars = c("v1:v6"))  
plot(result)
```

plot.mds	<i>Plot method for the mds function</i>
----------	---

Description

Plot method for the mds function

Usage

```
## S3 method for class 'mds'  
plot(x, rev_dim = "", fontsz = 1.3, ...)
```

Arguments

x	Return value from mds
rev_dim	Flip the axes in plots
fontsz	Font size to use in plots
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/mds.html> for an example in Radiant

See Also

[mds](#) to calculate results

[summary.mds](#) to plot results

Examples

```
result <- mds("city", "from", "to", "distance")
plot(result)
plot(result, rev_dim = 1:2)
plot(result, rev_dim = 1:2, fontsz = 2)
```

plot.performance	<i>Plot method for the performance function</i>
------------------	---

Description

Plot method for the performance function

Usage

```
## S3 method for class 'performance'
plot(x, plots = c("lift", "gains"), shiny = FALSE,
     ...)
```

Arguments

x	Return value from performance
plots	Plots to return
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/analytics/performance.html> for an example in Radiant

See Also

[performance](#) to generate results

[summary.performance](#) to summarize results

Examples

```
performance("titanic", "age", "survived") %>% plot
performance("titanic", c("age", "fare"), "survived") %>% plot
performance("titanic", c("age", "fare"), "survived", method = "xtile") %>% plot
performance("titanic", c("age", "fare"), "survived") %>% summary
```

plot.pivotr

Plot method for the pivotr function

Description

Plot method for the pivotr function

Usage

```
## S3 method for class 'pivotr'
plot(x, type = "dodge", perc = FALSE, flip = FALSE,
     shiny = FALSE, custom = FALSE, ...)
```

Arguments

x	Return value from pivotr
type	Plot type to use ("fill" or "dodge" (default))
perc	Use percentage on the y-axis
flip	Flip the axes in a plot (FALSE or TRUE)
shiny	Did the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/base/pivotr> for an example in Radiant

See Also

[pivotr](#) to generate summaries

[summary.pivotr](#) to show summaries

Examples

```
pivotr("diamonds", cvars = "cut") %>% plot
pivotr("diamonds", cvars = c("cut", "clarity")) %>% plot
pivotr("diamonds", cvars = c("cut", "clarity", "color")) %>% plot
```

plot.pmap

*Plot method for the pmap function***Description**

Plot method for the pmap function

Usage

```
## S3 method for class 'pmap'
plot(x, plots = "", scaling = 2.1, fontsz = 1.3, ...)
```

Arguments

x	Return value from pmap
plots	Components to include in the plot ("brand", "attr"). If data on preferences is available use "pref" to add preference arrows to the plot
scaling	Arrow scaling in the brand map
fontsz	Font size to use in plots
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/pmap.html> for an example in Radiant

See Also

[pmap](#) to calculate results
[summary.pmap](#) to plot results

Examples

```
result <- pmap("computer", "brand", "high_end:business")
plot(result, plots = "brand")
plot(result, plots = c("brand", "attr"))
plot(result, plots = c("brand", "attr"))
plot(result, scaling = 1, plots = c("brand", "attr"))
result <- pmap("computer", "brand", "high_end:dated",
  pref = c("innovative", "business"))
plot(result, plots = c("brand", "attr", "pref"))
```

plot.pre_factor	<i>Plot method for the pre_factor function</i>
-----------------	--

Description

Plot method for the pre_factor function

Usage

```
## S3 method for class 'pre_factor'
plot(x, ...)
```

Arguments

x	Return value from pre_factor
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/pre_factor.html for an example in Radiant

See Also

[pre_factor](#) to calculate results
[summary.pre_factor](#) to summarize results

Examples

```
result <- pre_factor("diamonds", c("price", "carat", "table"))
plot(result)
```

plot.prob_binom	<i>Plot method for the probability calculator function (binomial)</i>
-----------------	---

Description

Plot method for the probability calculator function (binomial)

Usage

```
## S3 method for class 'prob_binom'
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_binom
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.prob_chisq	<i>Plot method for the probability calculator (Chi-squared distribution)</i>
-----------------	--

Description

Plot method for the probability calculator (Chi-squared distribution)

Usage

```
## S3 method for class 'prob_chisq'
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_chisq
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.prob_disc	<i>Plot method for the probability calculator function (discrete)</i>
----------------	---

Description

Plot method for the probability calculator function (discrete)

Usage

```
## S3 method for class 'prob_disc'
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_disc
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

Examples

```
result <- prob_disc(v = "5 6 7 8 9 10 11 ", p = ".1 .2 .3 .15 .1 .1 .05", pub = 0.95)
plot(result, type = "probs")
```

plot.prob_expo	<i>Plot method for the probability calculator (Exponential distribution)</i>
----------------	--

Description

Plot method for the probability calculator (Exponential distribution)

Usage

```
## S3 method for class 'prob_expo'
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_expo
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.prob_fdist	<i>Plot method for the probability calculator (F-distribution)</i>
-----------------	--

Description

Plot method for the probability calculator (F-distribution)

Usage

```
## S3 method for class 'prob_fdist'
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_fdist
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.prob_norm	<i>Plot method for the probability calculator (normal)</i>
----------------	--

Description

Plot method for the probability calculator (normal)

Usage

```
## S3 method for class 'prob_norm'
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_norm
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.prob_pois	<i>Plot method for the probability calculator function (Poisson distribution)</i>
----------------	---

Description

Plot method for the probability calculator function (Poisson distribution)

Usage

```
## S3 method for class 'prob_pois'
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_pois
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.prob_tdist	<i>Plot method for the probability calculator (t-distribution)</i>
-----------------	--

Description

Plot method for the probability calculator (t-distribution)

Usage

```
## S3 method for class 'prob_tdist'  
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_tdist
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.prob_unif	<i>Plot method for the probability calculator (uniform)</i>
----------------	---

Description

Plot method for the probability calculator (uniform)

Usage

```
## S3 method for class 'prob_unif'  
plot(x, type = "values", shiny = FALSE, ...)
```

Arguments

x	Return value from prob_unif
type	Probabilities or values
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

plot.regression	<i>Plot method for the regression function</i>
-----------------	--

Description

Plot method for the regression function

Usage

```
## S3 method for class 'regression'
plot(x, plots = "", lines = "", conf_lev = 0.95,
     intercept = FALSE, shiny = FALSE, ...)
```

Arguments

x	Return value from regression
plots	Regression plots to produce for the specified regression model. Enter "" to avoid showing any plots (default). "hist" to show histograms of all variables in the model. "correlations" for a visual representation of the correlation matrix selected variables. "scatter" to show scatter plots (or box plots for factors) for the response variable with each explanatory variable. "dashboard" for a series of six plots that can be used to evaluate model fit visually. "resid_pred" to plot the explanatory variables against the model residuals. "coef" for a coefficient plot with adjustable confidence intervals. "leverage" to show leverage plots for each explanatory variable
lines	Optional lines to include in the select plot. "line" to include a line through a scatter plot. "loess" to include a polynomial regression fit line. To include both use c("line","loess")
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
intercept	Include the intercept in the coefficient plot (TRUE, FALSE). FALSE is the default
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the results
[summary.regression](#) to summarize results
[predict.regression](#) to generate predictions

Examples

```

result <- regression("diamonds", "price", c("carat","clarity"))
plot(result, plots = "dashboard")
plot(result, plots = "dashboard", lines = c("line","loess"))
plot(result, plots = "coef", intercept = TRUE)
plot(result, plots = "coef", conf_lev = .99, intercept = TRUE)
plot(result, plots = "hist")
plot(result, plots = "scatter", lines = c("line","loess"))
plot(result, plots = "correlations")
plot(result, plots = "leverage")
plot(result, plots = "resid_pred", lines = "line")

```

plot.reg_predict	<i>Plot method for the predict.regression function</i>
------------------	--

Description

Plot method for the predict.regression function

Usage

```

## S3 method for class 'reg_predict'
plot(x, xvar = "", facet_row = ".", facet_col = ".",
     color = "none", conf_lev = 0.95, ...)

```

Arguments

x	Return value from predict.regression .
xvar	Variable to display along the X-axis of the plot
facet_row	Create vertically arranged subplots for each level of the selected factor variable
facet_col	Create horizontally arranged subplots for each level of the selected factor variable
color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different colour
conf_lev	Confidence level to use for prediction intervals (.95 is the default). Note that the error bars for predictions are approximations at this point.
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the result
[summary.regression](#) to summarize results
[plot.regression](#) to plot results
[predict.regression](#) to generate predictions

Examples

```

result <- regression("diamonds", "price", c("carat","clarity"))
pred <- predict(result, pred_cmd = "carat = 1:10")
plot(pred, xvar = "carat")
result <- regression("diamonds", "price", c("carat","clarity"), int = "carat:clarity")
dpred <- getdata("diamonds") %>% slice(1:100)
pred <- predict(result, pred_data = "dpred")
plot(pred, xvar = "carat", color = "clarity")
rm(dpred, envir = .GlobalEnv)

```

plot.repeater	<i>Plot repeated simulation</i>
---------------	---------------------------------

Description

Plot repeated simulation

Usage

```

## S3 method for class 'repeater'
plot(x, sum_vars = "", byvar = "sim", fun = "sum_rm",
     form = "", shiny = FALSE, ...)

```

Arguments

x	Return value from repeater
sum_vars	(Numerical) variables to summaries
byvar	Variable(s) to group data by before summarizing
fun	Functions to use for summarizing
form	A string with the formula to evaluate (e.g., "profit = demand * (price - cost)")
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

plot.simulater	<i>Plot method for the simulater function</i>
----------------	---

Description

Plot method for the simulater function

Usage

```

## S3 method for class 'simulater'
plot(x, shiny = FALSE, ...)

```

Arguments

x	Return value from simulator
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/simulator> for an example in Radiant

See Also

[single_mean](#) to generate the result
[summary.single_mean](#) to summarize results

Examples

```
result <- simulator(const = "cost 3", norm = "demand 2000 1000",
                    discrete = "price 5 .3 8 .7",
                    form = "profit = demand * (price - cost)")
plot(result)
```

plot.single_mean	<i>Plot method for the single_mean function</i>
------------------	---

Description

Plot method for the single_mean function

Usage

```
## S3 method for class 'single_mean'
plot(x, plots = "hist", shiny = FALSE, ...)
```

Arguments

x	Return value from single_mean
plots	Plots to generate. "hist" shows a histogram of the data along with vertical lines that indicate the sample mean and the confidence interval. "simulate" shows the location of the sample mean and the comparison value (comp_value). Simulation is used to demonstrate the sampling variability in the data under the null-hypothesis
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_mean.html for an example in Radiant

See Also

`single_mean` to generate the result
`summary.single_mean` to summarize results

Examples

```
result <- single_mean("diamonds", "price", comp_value = 3500)
plot(result, plots = c("hist", "simulate"))
```

plot.single_prop	<i>Plot method for the single_prop function</i>
------------------	---

Description

Plot method for the single_prop function

Usage

```
## S3 method for class 'single_prop'
plot(x, plots = "bar", shiny = FALSE, ...)
```

Arguments

x	Return value from <code>single_prop</code>
plots	Plots to generate. "bar" shows a bar chart of the data. The "simulate" chart shows the location of the sample proportion and the comparison value (comp_value). Simulation is used to demonstrate the sampling variability in the data under the null-hypothesis
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_prop.html for an example in Radiant

See Also

`single_prop` to generate the result
`summary.single_prop` to summarize the results

Examples

```
result <- single_prop("diamonds", "clarity", lev = "IF", comp_value = 0.05)
plot(result, plots = c("hist", "simulate"))
result <- single_prop("titanic", "pclass", lev = "1st")
plot(result, plots = c("hist", "simulate"))
```

pmap

Attribute based brand maps

Description

Attribute based brand maps

Usage

```
pmap(dataset, brand, attr, pref = "", nr_dim = 2, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
brand	A character variable with brand names
attr	Names of numeric variables
pref	Names of numeric brand preference measures
nr_dim	Number of dimensions
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/marketing/pmap.html> for an example in Radiant

Value

A list of all variables defined in the function as an object of class `pmap`

See Also

`summary.pmap` to summarize results

`plot.pmap` to plot results

Examples

```
result <- pmap("computer", "brand", "high_end:business")
```

predict.ann	<i>Predict method for the ann function</i>
-------------	--

Description

Predict method for the ann function

Usage

```
## S3 method for class 'ann'  
predict(object, dataset, ...)
```

Arguments

object	Return value from ann
dataset	Dataset to use for prediction
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/analytics/ann.html> for an example in Radiant

See Also

[ann](#) to generate results
[summary.ann](#) to summarize results
[plot.ann](#) to plot results

predict.glm_reg	<i>Predict method for the glm_reg function</i>
-----------------	--

Description

Predict method for the glm_reg function

Usage

```
## S3 method for class 'glm_reg'  
predict(object, pred_vars = "", pred_data = "",  
        pred_cmd = "", prn = 100, se = FALSE, ...)
```

Arguments

object	Return value from <code>glm_reg</code>
pred_vars	Variables selected to generate predictions
pred_data	Provide the name of a dataframe to generate predictions (e.g., "titanic"). The dataset must contain all columns used in the estimation
pred_cmd	Generate predictions using a command. For example, 'pclass = levels(pclass)' would produce predictions for the different levels of factor 'pclass'. To add another variable use a ',' (e.g., 'pclass = levels(pclass), age = seq(0,100,20)')
prn	Number of lines of prediction results to print. Nothing is printed if prn is 0. Use -1 to print all lines (default).
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

`glm_reg` to generate the result
`summary.glm_reg` to summarize results
`plot.glm_reg` to plot results
`plot.glm_predict` to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex"), lev = "Yes")
predict(result, pred_cmd = "pclass = levels(pclass)")
glm_reg("titanic", "survived", c("pclass","sex"), lev = "Yes") %>%
  predict(pred_cmd = "sex = c('male','female')")
glm_reg("titanic", "survived", c("pclass","sex"), lev = "Yes") %>%
  predict(pred_data = "titanic")
```

predict.regression	<i>Predict method for the regression function</i>
--------------------	---

Description

Predict method for the regression function

Usage

```
## S3 method for class 'regression'
predict(object, pred_vars = "", pred_data = "",
  pred_cmd = "", conf_lev = 0.95, prn = 100, se = TRUE, ...)
```

Arguments

object	Return value from regression
pred_vars	Variables to use for prediction
pred_data	Name of the dataset to use for prediction
pred_cmd	Command used to generate data for prediction
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
prn	Number of lines of prediction results to print. Nothing is printed if prn is 0. Use -1 to print all lines (default).
se	Logical that indicates if prediction standard errors should be calculated (default = FALSE)
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the result
[summary.regression](#) to summarize results
[plot.regression](#) to plot results

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
predict(result, pred_cmd = "carat = 1:10")
predict(result, pred_cmd = "clarity = levels(clarity)")
result <- regression("diamonds", "price", c("carat","clarity"), int = c("carat:clarity"))
dpred <- getdata("diamonds") %>% slice(1:10)
predict(result, pred_data = "dpred")
rm(dpred, envir = .GlobalEnv)
```

pre_factor

Evaluate if data are appropriate for PCA / Factor analysis

Description

Evaluate if data are appropriate for PCA / Factor analysis

Usage

```
pre_factor(dataset, vars, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
vars	Variables to include in the analysis
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/marketing/pre_factor.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class `pre_factor`

See Also

`summary.pre_factor` to summarize results

`plot.pre_factor` to plot results

Examples

```
result <- pre_factor("diamonds",c("price","carat","table"))
```

`print.gtable`*Print/draw method for grobs produced by gridExtra*

Description

Print/draw method for grobs produced by gridExtra

Usage

```
## S3 method for class 'gtable'  
print(x, ...)
```

Arguments

<code>x</code>	a gtable object
<code>...</code>	further arguments passed to or from other methods

Details

Print method for ggplot grobs created using `arrangeGrob`. Code is based on <https://github.com/baptiste/gridextra/blob/master/inst/testing/shiny.R>

Value

A plot

prob_binom	<i>Probability calculator for the binomial distribution (binomial)</i>
------------	--

Description

Probability calculator for the binomial distribution (binomial)

Usage

```
prob_binom(n, p, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

n	Number of trials
p	Probability
lb	Lower bound on the number of successes
ub	Upper bound on the number of successes
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_chisq	<i>Probability calculator for the chi-squared distribution</i>
------------	--

Description

Probability calculator for the chi-squared distribution

Usage

```
prob_chisq(df, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

df	Degrees of freedom
lb	Lower bound (default is -Inf)
ub	Upper bound (default is Inf)
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_disc	<i>Probability calculator for the discrete distribution (discrete)</i>
-----------	--

Description

Probability calculator for the discrete distribution (discrete)

Usage

```
prob_disc(v, p, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

v	Values
p	Probabilities
lb	Lower bound on the number of successes
ub	Upper bound on the number of successes
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_expo	<i>Probability calculator for the exponential distribution</i>
-----------	--

Description

Probability calculator for the exponential distribution

Usage

```
prob_expo(rate, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

rate	Rate
lb	Lower bound (default is -Inf)
ub	Upper bound (default is Inf)
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_fdist	<i>Probability calculator for the F-distribution</i>
------------	--

Description

Probability calculator for the F-distribution

Usage

```
prob_fdist(df1, df2, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

df1	Degrees of freedom
df2	Degrees of freedom
lb	Lower bound (default is -Inf)
ub	Upper bound (default is Inf)
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_norm	<i>Probability calculator for the normal distribution</i>
-----------	---

Description

Probability calculator for the normal distribution

Usage

```
prob_norm(mean, stdev, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

mean	Mean
stdev	Standard deviation
lb	Lower bound (default is -Inf)
ub	Upper bound (default is Inf)
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_pois	<i>Probability calculator for the poisson distribution</i>
-----------	--

Description

Probability calculator for the poisson distribution

Usage

```
prob_pois(lambda, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

lambda	Rate
lb	Lower bound (default is -Inf)
ub	Upper bound (default is Inf)
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_tdist	<i>Probability calculator for the t distribution</i>
------------	--

Description

Probability calculator for the t distribution

Usage

```
prob_tdist(df, mean = 0, stdev = 1, lb = NA, ub = NA, plb = NA,  
  pub = NA, dec = 3)
```

Arguments

df	Degrees of freedom
mean	Mean
stdev	Standard deviation
lb	Lower bound (default is -Inf)
ub	Upper bound (default is Inf)
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

prob_unif	<i>Probability calculator for the uniform distribution</i>
-----------	--

Description

Probability calculator for the uniform distribution

Usage

```
prob_unif(min, max, lb = NA, ub = NA, plb = NA, pub = NA, dec = 3)
```

Arguments

min	Minmum value
max	Maximum value
lb	Lower bound
ub	Upper bound
plb	Lower probability bound
pub	Upper probability bound
dec	Number of decimals to show

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

publishers	<i>Comic publishers</i>
------------	-------------------------

Description

Comic publishers

Usage

```
data(publishers)
```

Format

A data frame with 3 rows and 2 variables

Details

List of comic publishers from http://stat545-ubc.github.io/bit001_dplyr-cheatsheet.html. The dataset is used to illustrate data merging / joining. Description provided in attr(publishers,"description")

radiant

radiant

Description

radiant

Launch Radiant in the default browser

Usage

```
radiant(app = c("analytics", "marketing", "quant", "base"))
```

Arguments

app

Choose the app to run. One of "base", "quant", "analytics", "marketing". "analytics" is the default

DetailsSee <http://vnijs.github.io/radiant> for documentation and tutorials**Examples**

```
if (interactive()) {
  radiant("base")
  radiant("quant")
  radiant("marketing")
  radiant("analytics")
}
```

radiant_analytics

Launch Radiant - Analytics as an Rstudio addin

Description

Launch Radiant - Analytics as an Rstudio addin

Usage

```
radiant_analytics()
```

radiant_base

Launch Radiant - Base as an Rstudio addin

Description

Launch Radiant - Base as an Rstudio addin

Usage

```
radiant_base()
```

radiant_marketing	<i>Launch Radiant - Marketing as an Rstudio addin</i>
-------------------	---

Description

Launch Radiant - Marketing as an Rstudio addin

Usage

```
radiant_marketing()
```

radiant_quant	<i>Launch Radiant - Quant as an Rstudio addin</i>
---------------	---

Description

Launch Radiant - Quant as an Rstudio addin

Usage

```
radiant_quant()
```

recode	<i>Exporting the recode function from the car package</i>
--------	---

Description

Exporting the recode function from the car package

regression	<i>Linear regression using OLS</i>
------------	------------------------------------

Description

Linear regression using OLS

Usage

```
regression(dataset, rvar, evar, int = "", check = "", dec = 3,  
  data_filter = "")
```


Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
rvar	The response variable in the regression
evvar	Explanatory variables in the regression
int	Interaction terms to include in the model
check	"standardize" to see standardized coefficient estimates. "stepwise" to apply step-wise selection of variables in estimation
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Value

A list of all variables used in regression as an object of class regression

See Also

`summary.regression` to summarize results
`plot.regression` to plot results
`predict.regression` to generate predictions

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
result <- regression("diamonds", "price", c("carat","clarity"), check = "standardize")
```

repeater

Repeat simulation

Description

Repeat simulation

Usage

```
repeater(nr = 12, vars = "", grid = "", seed = "", name = "",
  sim = "")
```

Arguments

nr	Number times to repeat the simulation
vars	Variables to use in repeated simulation
grid	Expression to use in grid search for constants
seed	To repeat a simulation with the same randomly generated values enter a number into Random seed input box.
name	To save the simulated data for further analysis specify a name in the Sim name input box. You can then investigate the simulated data by choosing the specified name from the Datasets dropdown in any of the other Data tabs.
sim	Return value from the simulator function

Examples

```
result <- simulator(const = "cost 3", norm = "demand 2000 1000",
  discrete = "price 5 .3 8 .7",
  form = "profit = demand * (price - cost)")

repeater(sim = result)
```

rndnames	<i>100 random names</i>
----------	-------------------------

Description

100 random names

Usage

```
data(rndnames)
```

Format

A data frame with 100 rows and 2 variables

Details

A list of 100 random names generated by listofrandomnames.com. Description provided in `attr(rndnames,"description")`

sample_size	<i>Sample size calculation</i>
-------------	--------------------------------

Description

Sample size calculation

Usage

```
sample_size(type = "mean", err_mean = 2, sd_mean = 10, err_prop = 0.1,  
            p_prop = 0.5, conf_lev = 1.96, incidence = 1, response = 1,  
            pop_correction = "no", pop_size = 1000000)
```

Arguments

type	Choose "mean" or "proportion"
err_mean	Acceptable Error for Mean
sd_mean	Standard deviation for Mean
err_prop	Acceptable Error for Proportion
p_prop	Initial proportion estimate for Proportion
conf_lev	Confidence level
incidence	Incidence rate (i.e., fraction of valid respondents)
response	Response rate
pop_correction	Apply correction for population size ("yes","no")
pop_size	Population size

Details

See http://vnijs.github.io/radiant/quant/sample_size.html for an example in Radiant

Value

A list of variables defined in sample_size as an object of class sample_size

See Also

[summary.sample_size](#) to summarize results

Examples

```
result <- sample_size(type = "mean", err_mean = 2, sd_mean = 10)
```

sampling	<i>Simple random sampling</i>
----------	-------------------------------

Description

Simple random sampling

Usage

```
sampling(dataset, var, sample_size, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var	The variable to sample from
sample_size	Number of units to select
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <http://vnijs.github.io/radiant/quant/sampling.html> for an example in Radiant

Value

A list of variables defined in sampling as an object of class `sampling`

See Also

[summary.sampling](#) to summarize results

Examples

```
result <- sampling("rndnames", "Names", 10)
```

saver	<i>Save data.frame as an rda or rds file from Radiant</i>
-------	---

Description

Save data.frame as an rda or rds file from Radiant

Usage

```
saver(objname, file)
```

Arguments

objname	Name of the data.frame
file	File name and path as a string. Extension must be either rda or rds

Value

Data.frame in r_data

save_factors	<i>Save factor scores to active dataset</i>
--------------	---

Description

Save factor scores to active dataset

Usage

```
save_factors(object)
```

Arguments

object	Return value from full_factor
--------	---

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

Examples

```
## Not run:
result <- full_factor("diamonds",c("price","carat","table"))
save_factors(result)
head(diamonds)

## End(Not run)
```

save_membership	<i>Deprecated function to store cluster membership</i>
-----------------	--

Description

Deprecated function to store cluster membership

Usage

```
save_membership(object, ..., name = "")
```

Arguments

object	Return value from kmeans_clus
...	Additional arguments
name	Name of cluster membership variable

See Also

Use [store.kmeans_clus](#) instead

sdp_rm	<i>Standard deviation for the population na.rm = TRUE</i>
--------	---

Description

Standard deviation for the population na.rm = TRUE

Usage

```
sdp_rm(x)
```

Arguments

x	Input variable
---	----------------

Value

Standard deviation for the population

Examples

```
sdp_rm(rnorm(100))
```

sdw	<i>Standard deviation of weighted sum of variables</i>
-----	--

Description

Standard deviation of weighted sum of variables

Usage

```
sdw(...)
```

Arguments

...	A matched number of weights and stocks
-----	--

Value

A vector of standard deviation estimates

sd_rm	<i>Standard deviation with na.rm = TRUE</i>
-------	---

Description

Standard deviation with na.rm = TRUE

Usage

```
sd_rm(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	Remove NAs (TRUE or FALSE)

Value

Standard deviation

Examples

```
sd_rm(rnorm(100))
```

serr	<i>Standard error</i>
------	-----------------------

Description

Standard error

Usage

```
serr(x, na.rm = TRUE)
```

Arguments

x	Input variable
na.rm	If TRUE missing values are removed before calculation

Value

Standard error

Examples

```
serr(rnorm(100))
```

set_class	<i>Alias used to set the class for analysis function return</i>
-----------	---

Description

Alias used to set the class for analysis function return

Usage

```
set_class()
```

Examples

```
foo <- function(x) x^2 %>% set_class(c("foo", class(.)))
```

shopping	<i>Shopping attitudes</i>
----------	---------------------------

Description

Shopping attitudes

Usage

```
data(shopping)
```

Format

A data frame with 20 rows and 7 variables

Details

Attitudinal data on shopping for 20 consumers. Description provided in attr(shopping,"description")

show_duplicated	<i>Show all rows with duplicated values (not just the first or last)</i>
-----------------	--

Description

Show all rows with duplicated values (not just the first or last)

Usage

```
show_duplicated(tbl, ...)
```


Arguments

tbl	Data frame to add transformed variables to
...	Variables used to evaluate row uniqueness

Details

If an entire row is duplicated use "duplicated" to show only one of the duplicated rows. When using a subset of variables to establish uniqueness it may be of interest to show all rows that have (some) duplicate elements

Examples

```
bind_rows(mtcars, mtcars[c(1,5,7),]) %>%
  show_duplicated(mpg, cyl)
bind_rows(mtcars, mtcars[c(1,5,7),]) %>%
  show_duplicated
```

sig_stars	<i>Add stars '***' to a data.frame (from broom's 'tidy' function) based on p.values</i>
-----------	---

Description

Add stars '***' to a data.frame (from broom's 'tidy' function) based on p.values

Usage

```
sig_stars(pval)
```

Arguments

pval	Vector of p-values
------	--------------------

Details

Add stars to output from broom's 'tidy' function

Value

A vector of stars

Examples

```
sig_stars(c(.0009, .049, .009, .4, .09))
```

simulater

*Simulate data for decision analysis***Description**

Simulate data for decision analysis

Usage

```
simulater(const = "", lnorm = "", norm = "", unif = "", discrete = "",
  binom = "", sequ = "", grid = "", data = "", form = "", seed = "",
  name = "", nr = 1000, dat = NULL)
```

Arguments

const	A string listing the constants to include in the analysis (e.g., "cost = 3; size = 4")
lnorm	A string listing the log-normally distributed random variables to include in the analysis (e.g., "demand 2000 1000" where the first number is the log-mean and the second is the log-standard deviation)
norm	A string listing the normally distributed random variables to include in the analysis (e.g., "demand 2000 1000" where the first number is the mean and the second is the standard deviation)
unif	A string listing the uniformly distributed random variables to include in the analysis (e.g., "demand 0 1" where the first number is the minimum value and the second is the maximum value)
discrete	A string listing the random variables with a discrete distribution to include in the analysis (e.g., "price 5 .3 8 .7" where for each pair of numbers the first is the value and the second the probability)
binom	A string listing the random variables with a binomial distribution to include in the analysis (e.g., "crash 100 .01") where the first number is the number of trials and the second is the probability of success)
sequ	A string listing the start and end for a sequence to include in the analysis (e.g., "trend 1 100 1"). The number of 'steps' is determined by the number of simulations.
grid	A string listing the start, end, and step for a set of sequences to include in the analysis (e.g., "trend 1 100 1"). The number of rows in the expanded will override the number of simulations
data	Name of a dataset to be used in the calculations
form	A string with the formula to evaluate (e.g., "profit = demand * (price - cost)")
seed	To repeat a simulation with the same randomly generated values enter a number into Random seed input box.
name	To save the simulated data for further analysis specify a name in the Sim name input box. You can then investigate the simulated data by choosing the specified name from the Datasets dropdown in any of the other Data tabs.
nr	Number of simulations
dat	Data list from previous simulation. Used by repeater function

Details

See <http://vnijs.github.io/radiant/quant/simulator.html> for an example in Radiant

Value

A data.frame with the created variables

See Also

[summary.simulator](#) to summarize results

[plot.simulator](#) to plot results

Examples

```
result <- simulator(const = "cost 3", norm = "demand 2000 1000",
  discrete = "price 5 .3 8 .7",
  form = "profit = demand * (price - cost)")
```

sim_cleaner

Clean input command string

Description

Clean input command string

Usage

```
sim_cleaner(x)
```

Arguments

x Input string

Value

Cleaned string

sim_splitter	<i>Split input command string</i>
--------------	-----------------------------------

Description

Split input command string

Usage

```
sim_splitter(x, symbol = " ")
```

Arguments

x	Input string
symbol	Symbol used to split the command string

Value

Split input command string

sim_summary	<i>Print simulation summary</i>
-------------	---------------------------------

Description

Print simulation summary

Usage

```
sim_summary(dat, dc = getclass(dat), fun = "", dec = 4)
```

Arguments

dat	Simulated data
dc	Variable classes
fun	Summary function to apply
dec	Number of decimals to show

single_mean	<i>Compare a sample mean to a population mean</i>
-------------	---

Description

Compare a sample mean to a population mean

Usage

```
single_mean(dataset, var, comp_value = 0, alternative = "two.sided",  
             conf_lev = 0.95, dec = 3, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var	The variable selected for the mean comparison
comp_value	Population value to compare to the sample mean
alternative	The alternative hypothesis ("two.sided", "greater", or "less")
conf_lev	Span for the confidence interval
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/quant/single_mean.html for an example in Radiant

Value

A list of variables defined in `single_mean` as an object of class `single_mean`

See Also

`summary.single_mean` to summarize results

`plot.single_mean` to plot results

Examples

```
single_mean("diamonds", "price")
```

single_prop

Compare a sample proportion to a population proportion

Description

Compare a sample proportion to a population proportion

Usage

```
single_prop(dataset, var, lev = "", comp_value = 0.5,
  alternative = "two.sided", conf_lev = 0.95, dec = 3, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
var	The variable selected for the proportion comparison
lev	The factor level selected for the proportion comparison
comp_value	Population value to compare to the sample proportion
alternative	The alternative hypothesis ("two.sided", "greater", or "less")
conf_lev	Span of the confidence interval
dec	Number of decimals to show
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/quant/single_prop.html for an example in Radiant

Value

A list of variables used in `single_prop` as an object of class `single_prop`

See Also

[summary.single_prop](#) to summarize the results

[plot.single_prop](#) to plot the results

Examples

```
result <- single_prop("diamonds", "cut")
result <- single_prop("diamonds", "clarity", lev = "IF", comp_value = 0.05)
```

skew	<i>Exporting the skew function from the psych package</i>
------	---

Description

Exporting the skew function from the psych package

square	<i>Calculate square of a variable</i>
--------	---------------------------------------

Description

Calculate square of a variable

Usage

```
square(x)
```

Arguments

x	Input variable
---	----------------

Value

x^2

ssh	<i>Hide warnings and messages and return invisible</i>
-----	--

Description

Hide warnings and messages and return invisible

Usage

```
ssh(...)
```

Arguments

...	Inputs to keep quiet
-----	----------------------

Details

Adapted from <http://www.onthelambda.com/2014/09/17/fun-with-rprofile-and-customizing-r-startup/>

Examples

```
ssh( library(dplyr) )
```

`sshhr`*Hide warnings and messages and return result*

Description

Hide warnings and messages and return result

Usage

```
sshhr(...)
```

Arguments

... Inputs to keep quiet

Details

Adapted from <http://www.onthelambda.com/2014/09/17/fun-with-rprofile-and-customizing-r-startup/>

Examples

```
sshhr( library(dplyr) )
```

`standardize`*Standardize*

Description

Standardize

Usage

```
standardize(x)
```

Arguments

x Input variable

Value

If x is a numeric variable return $\text{center}(x) / \text{mean}(x)$

store	<i>Method to store variables a dataset in Radiant</i>
-------	---

Description

Method to store variables a dataset in Radiant

Usage

```
store(object, ...)
```

Arguments

object	Object of relevant class that has required information to store
...	Additional arguments

store.kmeans_clus	<i>Add a cluster membership variable to the active dataset</i>
-------------------	--

Description

Add a cluster membership variable to the active dataset

Usage

```
## S3 method for class 'kmeans_clus'  
store(object, ..., name = "")
```

Arguments

object	Return value from kmeans_clus
...	Additional arguments
name	Name of cluster membership variable

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

See Also

[kmeans_clus](#) to generate results
[summary.kmeans_clus](#) to summarize results
[plot.kmeans_clus](#) to plot results

Examples

```
## Not run:
result <- kmeans_clus("shopping", vars = c("v1:v6"))
store.kmeans_clus(result)
head(shopping)

## End(Not run)
```

store_ann

*Store predicted values generated in the ann function***Description**

Store predicted values generated in the ann function

Usage

```
store_ann(pred, data, name = "predict_ann")
```

Arguments

pred	Return value from predict.nnet
data	Dataset name
name	Variable name assigned to the predicted values

Details

See <http://vnijs.github.io/radiant/analytics/ann.html> for an example in Radiant

store_crs

*Store predicted values generated in the crs function***Description**

Store predicted values generated in the crs function

Usage

```
store_crs(pred, data, name = "pred_crs")
```

Arguments

pred	Return value from predict.nnet
data	Dataset name
name	Variable name assigned to the predicted values

Details

See <http://vnijs.github.io/radiant/analytics/crs.html> for an example in Radiant

store_glm	<i>Store residuals or predicted values generated in the glm_reg function</i>
-----------	--

Description

Store residuals or predicted values generated in the glm_reg function

Usage

```
store_glm(object, data = object$dataset, type = "residuals",  
  name = paste0(type, "_glm"))
```

Arguments

object	Return value from <code>glm_reg</code> or <code>predict.glm_reg</code>
data	Dataset name
type	Residuals ("residuals") or predictions ("predictions"). For predictions the dataset name must be provided
name	Variable name assigned to the residuals or predicted values

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

Examples

```
## Not run:  
result <- glm_reg("titanic", "survived", "pclass", lev = "Yes")  
store_glm(result)  
  
## End(Not run)
```

store_reg	<i>Store residuals or predicted values generated in the regression function</i>
-----------	---

Description

Store residuals or predicted values generated in the regression function

Usage

```
store_reg(object, data = object$dataset, type = "residuals",  
  name = paste0(type, "_reg"))
```

Arguments

object	Return value from regression or predict.regression
data	Dataset name
type	Residuals ("residuals") or predictions ("predictions"). For predictions the dataset name must be provided
name	Variable name assigned to the residuals or predicted values

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Examples

```
## Not run:
result <- regression("diamonds", "price", c("carat","clarity"))
store_reg(result)

## End(Not run)
```

summary.ann

Summary method for the ann function

Description

Summary method for the ann function

Usage

```
## S3 method for class 'ann'
summary(object, ...)
```

Arguments

object	Return value from ann
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/analytics/ann.html> for an example in Radiant

See Also

[ann](#) to generate esults
[plot.ann](#) to plot results
[predict.ann](#) for prediction

Examples

```
result <- ann("titanic", "survived", "pclass", lev = "Yes")
summary(result)
```

summary.compare_means *Summary method for the compare_means function*

Description

Summary method for the compare_means function

Usage

```
## S3 method for class 'compare_means'  
summary(object, show = FALSE, ...)
```

Arguments

object	Return value from compare_means
show	Show additional output (i.e., t.value, df, and confidence interval)
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_means.html for an example in Radiant

See Also

[compare_means](#) to calculate results
[plot.compare_means](#) to plot results

Examples

```
result <- compare_means("diamonds", "cut", "price")  
summary(result)  
result <- diamonds %>% tbl_df %>% compare_means("x", "y")  
summary(result)  
result <- diamonds %>% tbl_df %>% group_by(cut) %>% compare_means("x", c("x", "y"))  
summary(result)
```

summary.compare_props *Summary method for the compare_props function*

Description

Summary method for the compare_props function

Usage

```
## S3 method for class 'compare_props'  
summary(object, show = FALSE, ...)
```

Arguments

object	Return value from compare_props
show	Show additional output (i.e., chisq.value, df, and confidence interval)
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_props.html for an example in Radiant

See Also

[compare_props](#) to calculate results
[plot.compare_props](#) to plot results

Examples

```
result <- compare_props("titanic", "pclass", "survived")
summary(result)
titanic %>% compare_props("pclass", "survived") %>% summary
```

summary.conjoint

Summary method for the conjoint function

Description

Summary method for the conjoint function

Usage

```
## S3 method for class 'conjoint'
summary(object, mc_diag = FALSE, ...)
```

Arguments

object	Return value from conjoint
mc_diag	Shows multicollinearity diagnostics.
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results
[plot.conjoint](#) to plot results

Examples

```
result <- conjoint("mp3", rvar = "Rating", evar = "Memory:Shape")
summary(result, mc_diag = TRUE)
mp3 %>% conjoint(rvar = "Rating", evar = "Memory:Shape") %>% summary(., mc_diag = TRUE)
```

summary.conjoint_profiles

Summary method for the conjoint_profiles function

Description

Summary method for the conjoint_profiles function

Usage

```
## S3 method for class 'conjoint_profiles'
summary(object, ...)
```

Arguments

object	Return value from conjoint_profiles
...	further arguments passed to or from other methods.

Details

See http://vnijs.github.io/radiant/marketing/conjoint_profiles.html for an example in Radiant

See Also

[conjoint_profiles](#) to calculate results

Examples

```
## Not run:
cp <- c("price = c('$10','$13','$16')", "sight = c('Staggered','Not Staggered')",
        "comfort = c('Average no cupholder','Average cupholder','Large cupholder')",
        "audio.visual = c('Small plain','Large plain','Large digital')",
        "food = c('No food','Hot dogs and popcorn','Gourmet food')")
result <- conjoint_profiles("cp")
summary(result)
rm(cp, envir = .GlobalEnv)

## End(Not run)
```

summary.correlation_ *Summary method for the correlation function*

Description

Summary method for the correlation function

Usage

```
## S3 method for class 'correlation_'
summary(object, cutoff = 0, covar = FALSE, ...)
```

Arguments

object	Return value from correlation
cutoff	Show only correlations larger than the cutoff in absolute value. Default is a cutoff of 0
covar	Show the covariance matrix (default is FALSE)
...	further arguments passed to or from other methods.

Details

See <http://vnijs.github.io/radiant/quant/correlation.html> for an example in Radiant

See Also

[correlation](#) to calculate results
[plot.correlation_](#) to plot results

Examples

```
result <- correlation("diamonds",c("price","carat","clarity"))
summary(result, cutoff = .3)
diamonds %>% correlation("price:clarity") %>% summary
```

summary.cross_tabs *Summary method for the cross_tabs function*

Description

Summary method for the cross_tabs function

Usage

```
## S3 method for class 'cross_tabs'
summary(object, check = "", ...)
```


Arguments

object	Return value from cross_tabs
check	Show table(s) for variables var1 and var2. "observed" for the observed frequencies table, "expected" for the expected frequencies table (i.e., frequencies that would be expected if the null hypothesis holds), "chi_sq" for the contribution to the overall chi-squared statistic for each cell (i.e., $(o - e)^2 / e$), "dev_std" for the standardized differences between the observed and expected frequencies (i.e., $(o - e) / \sqrt{e}$), and "dev_perc" for the percentage difference between the observed and expected frequencies (i.e., $(o - e) / e$)
...	further arguments passed to or from other methods.

Details

See http://vnijs.github.io/radiant/quant/cross_tabs.html for an example in Radiant

See Also

[cross_tabs](#) to calculate results
[plot.cross_tabs](#) to plot results

Examples

```
result <- cross_tabs("newspaper", "Income", "Newspaper")
summary(result, check = c("observed", "expected", "chi_sq"))
newspaper %>% cross_tabs("Income", "Newspaper") %>% summary("observed")
```

summary.crs

*Summary method for Collaborative Filter***Description**

Summary method for Collaborative Filter

Usage

```
## S3 method for class 'crs'
summary(object, ...)
```

Arguments

object	Return value from simulator
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/analytics/crs.html> for an example in Radiant

See Also

[crs](#) to generate the results
[plot.crs](#) to plot results

summary.doe	<i>Summary method for doe function</i>
-------------	--

Description

Summary method for doe function

Usage

```
## S3 method for class 'doe'
summary(object, eff = TRUE, part = TRUE, full = TRUE, ...)
```

Arguments

object	Return value from conjoint_profiles
eff	If TRUE print efficiency output
part	If TRUE print partial factorial
full	If TRUE print full factorial
...	further arguments passed to or from other methods.

Details

See <http://vnijs.github.io/radiant/analytics/doe.html> for an example in Radiant

See Also

[doe](#) to calculate results

Examples

```
"price; $10; $13; $16\nfood; popcorn; gourmet; no food" %>% doe %>% summary
```

summary.dtree	<i>Summary method for the dree function</i>
---------------	---

Description

Summary method for the dree function

Usage

```
## S3 method for class 'dtree'
summary(object, ...)
```

Arguments

object	Return value from simulator
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/dtree.html> for an example in Radiant

See Also

[dtree](#) to generate the results

[plot.dtree](#) to plot results

summary.explore

Summary method for the explore function

Description

Summary method for the explore function

Usage

```
## S3 method for class 'explore'
summary(object, top = "fun", dec = 3, ...)
```

Arguments

object	Return value from explore
top	The variable (type) to display at the top of the table
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/base/explore.html> for an example in Radiant

See Also

[explore](#) to generate summaries

Examples

```
result <- explore("diamonds", "price:x")
summary(result)
result <- explore("diamonds", "price", byvar = "cut", fun = c("length", "skew"))
summary(result)
diamonds %>% explore("price:x") %>% summary
diamonds %>% explore("price", byvar = "cut", fun = c("length", "skew")) %>% summary
```

summary.full_factor	<i>Summary method for the full_factor function</i>
---------------------	--

Description

Summary method for the full_factor function

Usage

```
## S3 method for class 'full_factor'
summary(object, cutoff = 0, fsort = FALSE, ...)
```

Arguments

object	Return value from full_factor
cutoff	Show only loadings with (absolute) values above cutoff (default = 0)
fsort	Sort factor loadings
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

See Also

[full_factor](#) to calculate results

[plot.full_factor](#) to plot results

Examples

```
result <- full_factor("diamonds",c("price","carat","depth","table","x"))
summary(result)
summary(result, cutoff = 0, fsort = FALSE)
summary(result, cutoff = 0, fsort = TRUE)
summary(result, cutoff = .5, fsort = TRUE)
diamonds %>% full_factor(c("price","carat","depth","table","x")) %>% summary
diamonds %>% full_factor(c("price","carat","depth","table","x")) %>% summary(cutoff = .5)
```

summary.glm_reg

*Summary method for the glm_reg function***Description**

Summary method for the glm_reg function

Usage

```
## S3 method for class 'glm_reg'
summary(object, sum_check = "", conf_lev = 0.95,
        test_var = "", ...)
```

Arguments

object	Return value from glm_reg
sum_check	Optional output. "vif" to show multicollinearity diagnostics. "confint" to show coefficient confidence interval estimates. "odds" to show odds ratios and confidence interval estimates.
conf_lev	Confidence level to use for coefficient and odds confidence intervals (.95 is the default)
test_var	Variables to evaluate in model comparison (i.e., a competing models Chi-squared test)
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

[glm_reg](#) to generate the results
[plot.glm_reg](#) to plot the results
[predict.glm_reg](#) to generate predictions
[plot.glm_predict](#) to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", "pclass", lev = "Yes")
summary(result, test_var = "pclass")
res <- glm_reg("titanic", "survived", c("pclass","sex"), int="pclass:sex", lev="Yes")
summary(res, sum_check = c("vif","confint","odds"))
titanic %>% glm_reg("survived", c("pclass","sex","age"), lev = "Yes") %>% summary("vif")
```

summary.goodness	<i>Summary method for the goodness function</i>
------------------	---

Description

Summary method for the goodness function

Usage

```
## S3 method for class 'goodness'
summary(object, check = "", ...)
```

Arguments

object	Return value from goodness
check	Show table(s) for the selected variable (var). "observed" for the observed frequencies table, "expected" for the expected frequencies table (i.e., frequencies that would be expected if the null hypothesis holds), "chi_sq" for the contribution to the overall chi-squared statistic for each cell (i.e., $(o - e)^2 / e$), "dev_std" for the standardized differences between the observed and expected frequencies (i.e., $(o - e) / \sqrt{e}$), and "dev_perc" for the percentage difference between the observed and expected frequencies (i.e., $(o - e) / e$)
...	further arguments passed to or from other methods.

Details

See <http://vnijs.github.io/radiant/quant/goodness> for an example in Radiant

See Also

[goodness](#) to calculate results

[plot.goodness](#) to plot results

Examples

```
result <- goodness("newspaper", "Income", c(.3, .7))
summary(result, check = c("observed", "expected", "chi_sq"))
newspaper %>% goodness("Income", c(.3, .7)) %>% summary("observed")
```

summary.hier_clus	<i>Summary method for the hier_clus function</i>
-------------------	--

Description

Summary method for the hier_clus function

Usage

```
## S3 method for class 'hier_clus'  
summary(object, ...)
```

Arguments

object	Return value from hier_clus
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/hier_clus.html for an example in Radiant

See Also

[hier_clus](#) to generate results
[plot.hier_clus](#) to plot results

Examples

```
result <- hier_clus("shopping", vars = c("v1:v6"))  
summary(result)
```

summary.kmeans_clus	<i>Summary method for kmeans_clus</i>
---------------------	---------------------------------------

Description

Summary method for kmeans_clus

Usage

```
## S3 method for class 'kmeans_clus'  
summary(object, ...)
```

Arguments

object	Return value from kmeans_clus
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

See Also

[kmeans_clus](#) to generate results
[plot.kmeans_clus](#) to plot results
[store.kmeans_clus](#) to add cluster membership to the selected dataset

Examples

```
result <- kmeans_clus("shopping", vars = c("v1:v6"))
summary(result)
shopping %>% kmeans_clus(vars = c("v1:v6"), nr_clus = 3) %>% summary
```

summary.mds

*Summary method for the mds function***Description**

Summary method for the mds function

Usage

```
## S3 method for class 'mds'
summary(object, dec = 1, ...)
```

Arguments

object	Return value from mds
dec	Rounding to use for output (default = 0). +1 used for coordinates. +2 used for stress measure. Not currently accessible in Radiant
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/mds.html> for an example in Radiant

See Also

[mds](#) to calculate results
[plot.mds](#) to plot results

Examples

```
result <- mds("city", "from", "to", "distance")
summary(result)
summary(result, dec = 2)
city %>% mds("from", "to", "distance") %>% summary
```

summary.performance	<i>Summary method for the performance function</i>
---------------------	--

Description

Summary method for the performance function

Usage

```
## S3 method for class 'performance'  
summary(object, prn = TRUE, ...)
```

Arguments

object	Return value from performance
prn	Print model performance results (default is TRUE)
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/analytics/performance.html> for an example in Radiant

See Also

[performance](#) to summarize results
[plot.performance](#) to plot results

Examples

```
performance("titanic", "age", "survived") %>% summary  
performance("titanic", c("age", "fare"), "survived") %>% summary
```

summary.pivotr	<i>Summary method for pivotr</i>
----------------	----------------------------------

Description

Summary method for pivotr

Usage

```
## S3 method for class 'pivotr'  
summary(object, perc = FALSE, dec = 3, chi2 = FALSE,  
        shiny = FALSE, ...)
```

Arguments

object	Return value from pivotr
perc	Display numbers as percentages (TRUE or FALSE)
dec	Number of decimals to show
chi2	If TRUE calculate the chi-square statistic for the (pivot) table
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/base/pivotr.html> for an example in Radiant

See Also

[pivotr](#) to create the pivot-table using dplyr

Examples

```
pivotr("diamonds", cvars = "cut") %>% summary
pivotr("diamonds", cvars = "cut", tabsort = "-n") %>% summary
pivotr("diamonds", cvars = "cut", tabfilt = "n > 700") %>% summary
pivotr("diamonds", cvars = "cut:clarity", nvar = "price") %>% summary
```

summary.pmap

Summary method for the pmap function

Description

Summary method for the pmap function

Usage

```
## S3 method for class 'pmap'
summary(object, cutoff = 0, ...)
```

Arguments

object	Return value from pmap
cutoff	Show only loadings with (absolute) values above cutoff (default = 0)
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/pmap.html> for an example in Radiant

See Also

[pmap](#) to calculate results

[plot.pmap](#) to plot results

Examples

```

result <- pmap("computer", "brand", "high_end:business")
summary(result)
summary(result, cutoff = .3)
result <- pmap("computer", "brand", "high_end:dated", pref = c("innovative", "business"))
summary(result)
computer %>% pmap("brand", "high_end:dated", pref = c("innovative", "business")) %>%
  summary

```

summary.pre_factor	<i>Summary method for the pre_factor function</i>
--------------------	---

Description

Summary method for the pre_factor function

Usage

```

## S3 method for class 'pre_factor'
summary(object, ...)

```

Arguments

object	Return value from pre_factor
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/pre_factor.html for an example in Radiant

See Also

[pre_factor](#) to calculate results
[plot.pre_factor](#) to plot results

Examples

```

result <- pre_factor("diamonds", c("price", "carat", "table"))
summary(result)
diamonds %>% pre_factor(c("price", "carat", "table")) %>% summary
result <- pre_factor("computer", "high_end:business")
summary(result)

```

summary.prob_binom	<i>Summary method for the probability calculator function</i>
--------------------	---

Description

Summary method for the probability calculator function

Usage

```
## S3 method for class 'prob_binom'
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_binom
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.prob_chisq	<i>Summary method for the probability calculator function (Chi-squared distribution)</i>
--------------------	--

Description

Summary method for the probability calculator function (Chi-squared distribution)

Usage

```
## S3 method for class 'prob_chisq'
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_chisq
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.prob_disc	<i>Summary method for the probability calculator function (discrete)</i>
-------------------	--

Description

Summary method for the probability calculator function (discrete)

Usage

```
## S3 method for class 'prob_disc'
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_disc
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

Examples

```
result <- prob_disc(v = "5 6 7 8 9 10 11 ", p = ".1 .2 .3 .15 .1 .1 .05", pub = 0.95)
summary(result, type = "probs")
```

summary.prob_expo	<i>Summary method for the probability calculator function (Exponential distribution)</i>
-------------------	--

Description

Summary method for the probability calculator function (Exponential distribution)

Usage

```
## S3 method for class 'prob_expo'
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_expo
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.prob_fdist	<i>Summary method for the probability calculator function (F-distribution)</i>
--------------------	--

Description

Summary method for the probability calculator function (F-distribution)

Usage

```
## S3 method for class 'prob_fdist'
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_fdist
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.prob_norm	<i>Summary method for the probability calculator function (normal)</i>
-------------------	--

Description

Summary method for the probability calculator function (normal)

Usage

```
## S3 method for class 'prob_norm'
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_norm
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.prob_pois	<i>Summary method for the probability calculator function (Poisson distribution)</i>
-------------------	--

Description

Summary method for the probability calculator function (Poisson distribution)

Usage

```
## S3 method for class 'prob_pois'  
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_pois
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.prob_tdist	<i>Summary method for the probability calculator function (t-distribution)</i>
--------------------	--

Description

Summary method for the probability calculator function (t-distribution)

Usage

```
## S3 method for class 'prob_tdist'  
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_tdist
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.prob_unif	<i>Summary method for the probability calculator function (uniform)</i>
-------------------	---

Description

Summary method for the probability calculator function (uniform)

Usage

```
## S3 method for class 'prob_unif'
summary(object, type = "values", ...)
```

Arguments

object	Return value from prob_unif
type	Probabilities or values
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/prob_calc.html for an example in Radiant

summary.regression	<i>Summary method for the regression function</i>
--------------------	---

Description

Summary method for the regression function

Usage

```
## S3 method for class 'regression'
summary(object, sum_check = "", conf_lev = 0.95,
        test_var = "", ...)
```

Arguments

object	Return value from regression
sum_check	Optional output. "rsme" to show the root mean squared error and the standard deviation of the residuals. "sumsquares" to show the sum of squares table. "vif" to show multicollinearity diagnostics. "confint" to show coefficient confidence interval estimates.
conf_lev	Confidence level used to estimate confidence intervals (.95 is the default)
test_var	Variables to evaluate in model comparison (i.e., a competing models F-test)
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the results

[plot.regression](#) to plot results

[predict.regression](#) to generate predictions

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
summary(result, sum_check = c("rmse","sumsquares","vif","confint"), test_var = "clarity")
result <- regression("shopping", "v1", c("v2","v3"))
summary(result, test_var = "v2")
shopping %>% regression("v1", "v2:v6") %>% summary
```

summary.repeater

Summarize repeated simulation

Description

Summarize repeated simulation

Usage

```
## S3 method for class 'repeater'
summary(object, sum_vars = "", byvar = "",
  fun = "sum_rm", form = "", name = "", dec = 4, ...)
```

Arguments

object	Return value from repeater
sum_vars	(Numerical) variables to summaries
byvar	Variable(s) to group data by before summarizing
fun	Functions to use for summarizing
form	A string with the formula to evaluate (e.g., "profit = demand * (price - cost)")
name	To save the simulated data for further analysis specify a name in the Sim name input box. You can then investigate the simulated data by choosing the specified name from the Datasets dropdown in any of the other Data tabs.
dec	Number of decimals to show
...	further arguments passed to or from other methods

summary.sample_size	Summary method for the sample_size function
---------------------	---

Description

Summary method for the sample_size function

Usage

```
## S3 method for class 'sample_size'  
summary(object, ...)
```

Arguments

object	Return value from sample_size
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/sample_size for an example in Radiant

See Also

[sample_size](#) to generate the results

Examples

```
result <- sample_size(type = "mean", err_mean = 2, sd_mean = 10)  
summary(result)
```

summary.sampling	Summary method for the sampling function
------------------	--

Description

Summary method for the sampling function

Usage

```
## S3 method for class 'sampling'  
summary(object, print_sf = TRUE, ...)
```

Arguments

object	Return value from sampling
print_sf	Print full sampling frame. Default is TRUE
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/sampling> for an example in Radiant

See Also

[sampling](#) to generate the results

Examples

```
set.seed(1234)
result <- sampling("rndnames", "Names", 10)
summary(result)
```

summary.simulater

Summary method for the simulater function

Description

Summary method for the simulater function

Usage

```
## S3 method for class 'simulater'
summary(object, dec = 4, ...)
```

Arguments

object	Return value from simulater
dec	Number of decimals to show
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/simulater.html> for an example in Radiant

See Also

[simulater](#) to generate the results

[plot.simulater](#) to plot results

Examples

```
result <- simulater(norm = "demand 2000 1000")
summary(result)
```

summary.single_mean	<i>Summary method for the single_mean function</i>
---------------------	--

Description

Summary method for the single_mean function

Usage

```
## S3 method for class 'single_mean'  
summary(object, ...)
```

Arguments

object	Return value from single_mean
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_mean.html for an example in Radiant

See Also

[single_mean](#) to generate the results
[plot.single_mean](#) to plot results

Examples

```
result <- single_mean("diamonds", "price")  
summary(result)  
diamonds %>% single_mean("price") %>% summary
```

summary.single_prop	<i>Summary method for the single_prop function</i>
---------------------	--

Description

Summary method for the single_prop function

Usage

```
## S3 method for class 'single_prop'  
summary(object, ...)
```

Arguments

object	Return value from single_prop
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_prop.html for an example in Radiant

See Also

[single_prop](#) to generate the results

[plot.single_prop](#) to plot the results

Examples

```
result <- single_prop("diamonds", "clarity", lev = "IF", comp_value = 0.05)
summary(result)
diamonds %>% single_prop("clarity", lev = "IF", comp_value = 0.05) %>% summary
```

sum_rm	<i>Sum with na.rm = TRUE</i>
--------	------------------------------

Description

Sum with na.rm = TRUE

Usage

```
sum_rm(x)
```

Arguments

x	Input variable
---	----------------

Value

Sum of input values

Examples

```
sum_rm(1:200)
```

superheroes

*Super heroes***Description**

Super heroes

Usage

```
data(superheroes)
```

Format

A data frame with 7 rows and 4 variables

Details

List of super heroes from http://stat545-ubc.github.io/bit001_dplyr-cheatsheet.html.

The dataset is used to illustrate data merging / joining. Description provided in attr(superheroes,"description")

table2data

*Create data.frame from a table***Description**

Create data.frame from a table

Usage

```
table2data(dat, freq = tail(colnames(dat), 1))
```

Arguments

dat

Data.frame

freq

Column name with frequency information

Examples

```
data.frame(price = c("$200", "$300"), sale = c(10, 2)) %>% table2data
```

test_specs	<i>Add interaction terms to list of test variables if needed</i>
------------	--

Description

Add interaction terms to list of test variables if needed

Usage

```
test_specs(test_var, int)
```

Arguments

test_var	List of variables to use for testing for regression or glm_reg
int	Interaction terms specified

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Value

A vector of variables names to test

Examples

```
test_specs("a", c("a:b", "b:c"))
```

the_table	<i>Function to calculate the PW and IW table for conjoint</i>
-----------	---

Description

Function to calculate the PW and IW table for conjoint

Usage

```
the_table(model, dat, evar)
```

Arguments

model	Tidied model results (broom) output from conjoint passed on by summary.conjoint
dat	Conjoint data
evar	Explanatory variables used in the conjoint regression

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results
[summary.conjoint](#) to summarize results
[plot.conjoint](#) to plot results

Examples

```
result <- conjoint(dataset = "mp3", rvar = "Rating", evar = "Memory:Shape")
the_table(result$model, result$dat, result$evar)
```

titanic	<i>Survival data for the Titanic</i>
---------	--------------------------------------

Description

Survival data for the Titanic

Usage

```
data(titanic)
```

Format

A data frame with 1043 rows and 10 variables

Details

Survival data for the Titanic. Description provided in attr(titanic,"description")

titanic_pred	<i>Predict survival</i>
--------------	-------------------------

Description

Predict survival

Usage

```
data(titanic_pred)
```

Format

A data frame with 6 rows and 3 variables

Details

Prediction data.frame for glm_reg based on the Titanic dataset

toothpaste	<i>Toothpaste attitudes</i>
------------	-----------------------------

Description

Toothpaste attitudes

Usage

```
data(toothpaste)
```

Format

A data frame with 60 rows and 10 variables

Details

Attitudinal data on toothpaste for 60 consumers. Description provided in attr(toothpaste,"description")

update_radiant	<i>Update Radiant</i>
----------------	-----------------------

Description

Update Radiant

Usage

```
update_radiant()
```

varp_rm	<i>Variance for the population na.rm = TRUE</i>
---------	---

Description

Variance for the population na.rm = TRUE

Usage

```
varp_rm(x)
```

Arguments

x	Input variable
---	----------------

Value

Variance for the population

Examples

```
varp_rm(rnorm(100))
```

var_check	<i>Check if main effects for all interaction effects are included in the model If ':' is used to select a range _evar_ is updated</i>
-----------	---

Description

Check if main effects for all interaction effects are included in the model If ':' is used to select a range _evar_ is updated

Usage

```
var_check(ev, cn, intv = "")
```

Arguments

ev	List of explanatory variables provided to <code>_regression_</code> or <code>_glm_</code>
cn	Column names for all explanatory variables in <code>_dat_</code>
intv	Interaction terms specified

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Value

'vars' is a vector of right-hand side variables, possibly with interactions, 'iv' is the list of explanatory variables, and intv are interaction terms

Examples

```
var_check("a:d", c("a", "b", "c", "d"))
var_check(c("a", "b"), c("a", "b"), "a:c")
```

var_rm	<i>Variance with na.rm = TRUE</i>
--------	-----------------------------------

Description

Variance with na.rm = TRUE

Usage

```
var_rm(x)
```

Arguments

x	Input variable
---	----------------

Value

Variance

Examples

```
var_rm(rnorm(100))
```

viewdata	<i>View data</i>
----------	------------------

Description

View data

Usage

```
viewdata(dataset, vars = "", filt = "", rows = NULL, na.rm = FALSE)
```

Arguments

dataset	Name of the dataframe to change
vars	Variables to show (default is all)
filt	Filter to apply to the specified dataset. For example "price > 10000" if dataset is "diamonds" (default is "")
rows	Select rows in the specified dataset. For example "1:10" for the first 10 rows or "n()-10:n()" for the last 10 rows (default is NULL)
na.rm	Remove rows with missing values (default is FALSE)

Details

View, search, sort, etc. your data

Examples

```
if (interactive()) {
  viewdata(mtcars)
  viewdata("mtcars")
  mtcars %>% viewdata
}
```

visualize

Visualize data using ggplot2 <http://docs.ggplot2.org/current/>

Description

Visualize data using ggplot2 <http://docs.ggplot2.org/current/>

Usage

```
visualize(dataset, xvar, yvar = "", comby = FALSE, combx = FALSE,
  type = "hist", facet_row = ".", facet_col = ".", color = "none",
  fill = "none", bins = 10, smooth = 1, fun = "mean", check = "",
  axes = "", alpha = 0.5, data_filter = "", shiny = FALSE,
  custom = FALSE)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
xvar	One or more variables to display along the X-axis of the plot
yvar	Variable to display along the Y-axis of the plot (default = "none")
comby	Combine yvars in plot (TRUE or FALSE, FALSE is the default)
combx	Combine xvars in plot (TRUE or FALSE, FALSE is the default)
type	Type of plot to create. One of Histogram ('hist'), Density ('density'), Scatter ('scatter'), Line ('line'), Bar ('bar'), or Box-plot ('box')
facet_row	Create vertically arranged subplots for each level of the selected factor variable
facet_col	Create horizontally arranged subplots for each level of the selected factor variable
color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different color
fill	Group bar, histogram, and density plots by group, each with a different color
bins	Number of bins used for a histogram (1 - 50)
smooth	Adjust the flexibility of the loess line for scatter plots
fun	Set the summary measure for line and bar plots when the X-variable is a factor (default is "mean"). Also used to plot an error bar in a scatter plot when the X-variable is a factor. Options are "mean" and/or "median"
check	Add a regression line ("line"), a loess line ("loess"), or jitter ("jitter") to a scatter plot

axes	Flip the axes in a plot ("flip") or apply a log transformation (base e) to the y-axis ("log_y") or the x-axis ("log_x")
alpha	Opacity for plot elements (0 to 1)
data_filter	Expression used to filter the dataset. This should be a string (e.g., "price > 10000")
shiny	Logical (TRUE, FALSE) to indicate if the function call originate inside a shiny app
custom	Logical (TRUE, FALSE) to indicate if ggplot object (or list of ggplot objects) should be returned. This option can be used to customize plots (e.g., add a title, change x and y labels, etc.). See examples and http://docs.ggplot2.org/ for options.

Details

See <http://vnijs.github.io/radiant/base/visualize.html> for an example in Radiant

Value

Generated plots

Examples

```
visualize("diamonds", "carat", "price", type = "scatter", check = "loess")
visualize("diamonds", "price:x", type = "hist")
visualize("diamonds", "carat:x", yvar = "price", type = "scatter")
visualize(dataset = "diamonds", yvar = "price", xvar = c("cut", "clarity"), type = "bar",
  fun = "median")
visualize(dataset = "diamonds", yvar = "price", xvar = "carat", type = "scatter", custom = TRUE) +
  ggtitle("A scatterplot") + xlab("price in $")
visualize(dataset = "diamonds", xvar = "price:carat", custom = TRUE) %>%
  {.[[1]] + ggtitle("A histogram") + xlab("price in $")}
diamonds %>% visualize(c("price", "carat", "depth"), type = "density")
```

weighted.sd	<i>Weighted standard deviation</i>
-------------	------------------------------------

Description

Weighted standard deviation

Usage

```
weighted.sd(x, wt, na.rm = TRUE)
```

Arguments

x	Numeric vector
wt	Numeric vector of weights
na.rm	Remove missing values (default is TRUE)

Details

Calculated a weighted standard deviation

`which.pmax`*Returns the index of the (parallel) maxima of the input values*

Description

Returns the index of the (parallel) maxima of the input values

Usage

```
which.pmax(...)
```

Arguments

... Numeric or character vectors of the same length

Value

Vector of rankings

Examples

```
which.pmax(1:10, 10:1)
which.pmax(2, 10:1)
```

`which.pmin`*Returns the index of the (parallel) minima of the input values*

Description

Returns the index of the (parallel) minima of the input values

Usage

```
which.pmin(...)
```

Arguments

... Numeric or character vectors of the same length

Value

Vector of rankings

Examples

```
which.pmin(1:10, 10:1)
which.pmin(2, 10:1)
```

win_launcher	<i>Create a launcher and updater for Windows (.bat)</i>
--------------	---

Description

Create a launcher and updater for Windows (.bat)

Usage

```
win_launcher(app = c("analytics", "marketing", "quant", "base"))
```

Arguments

app	App to run when the desktop icon is double-clicked ("analytics", "marketing", "quant", or "base"). Default is "analytics"
-----	---

Details

On Windows a file named 'radiant.bat' and one named 'update_radiant.bat' will be put on the desktop. Double-click the file to launch the specified Radiant app or update Radiant to the latest version

Examples

```
if (interactive()) {
  if (Sys.info()["sysname"] == "Windows") {
    win_launcher()
    fn <- paste0(Sys.getenv("USERPROFILE"), "/Desktop/radiant.bat")
    if (!file.exists(fn))
      stop("Windows launcher not created")
    else
      unlink(fn)
  }
}
```

xtile	<i>Create a quintile (or decile) index</i>
-------	--

Description

Create a quintile (or decile) index

Usage

```
xtile(x, n, rev = FALSE)
```

Arguments

x	Numeric variable
n	number of bins to create
rev	Reverse the order of the xtiles

Details

Same as stata

Examples

```
xtile(1:10,5)  
xtile(1:10,5, rev = TRUE)
```


Index

*Topic **datasets**

avengers, [17](#)
city, [19](#)
computer, [24](#)
diamonds, [32](#)
mp3, [60](#)
newspaper, [61](#)
publishers, [102](#)
rndnames, [106](#)
shopping, [112](#)
superheroes, [150](#)
titanic, [152](#)
titanic_pred, [152](#)
toothpaste, [153](#)

ann, [7](#), [68](#), [94](#), [124](#)
as_character, [8](#)
as_distance, [8](#)
as_dmy, [9](#)
as_dmy_hm, [9](#)
as_dmy_hms, [10](#)
as_duration, [10](#)
as_factor, [11](#)
as_hm, [11](#)
as_hms, [12](#)
as_integer, [12](#)
as_mdy, [13](#)
as_mdy_hm, [14](#)
as_mdy_hms, [14](#)
as_numeric, [15](#)
as_ymd, [15](#)
as_ymd_hm, [16](#)
as_ymd_hms, [16](#)
auc, [17](#)
avengers, [17](#)

center, [18](#)
changedata, [18](#)
ci_label, [19](#)
ci_perc, [20](#)
city, [19](#)
clean_loadings, [20](#)
combinedata, [21](#)
compare_means, [22](#), [69](#), [125](#)

compare_props, [23](#), [69](#), [126](#)
computer, [24](#)
confint_robust, [24](#)
conjoint, [25](#), [70](#), [126](#), [151](#), [152](#)
conjoint_profiles, [26](#), [37](#), [127](#), [130](#)
copy_all, [27](#)
copy_from, [27](#)
copy_imported, [28](#)
correlation, [28](#), [71](#), [128](#)
cross_tabs, [29](#), [72](#), [129](#)
crs, [30](#), [72](#), [73](#), [129](#)
cv, [31](#)

dfprint, [31](#)
dfround, [32](#)
diamonds, [32](#)
doe, [33](#), [130](#)
does_vary, [33](#)
dtree, [34](#), [35](#), [73](#), [131](#)
dtree_parser, [35](#)

explore, [35](#), [39](#), [54](#), [131](#)

factorizer, [36](#)
ff_design, [37](#)
filterdata, [37](#)
find_dropbox, [38](#)
find_max, [38](#)
find_min, [39](#)
flip, [39](#)
full_factor, [40](#), [74](#), [109](#), [132](#)

getclass, [41](#)
getdata, [41](#)
getsummary, [42](#)
glm_reg, [42](#), [75](#), [76](#), [95](#), [123](#), [133](#)
goodness, [43](#), [77](#), [134](#)

hier_clus, [44](#), [78](#), [135](#)

install_webshot, [45](#)
inverse, [45](#)
is_empty, [45](#)
is_string, [46](#)
iterms, [47](#)

- kmeans_clus, [47](#), [79](#), [110](#), [121](#), [135](#), [136](#)
- kurtosi, [48](#)
- launcher, [48](#)
- level_list, [49](#)
- lin_launcher, [49](#), [49](#)
- ln, [50](#)
- loadcsv, [51](#)
- loadcsv_url, [51](#)
- loadr, [52](#)
- loadrda_url, [52](#)
- mac_launcher, [49](#), [53](#)
- make_dt, [53](#)
- make_expl, [39](#), [54](#)
- make_funs, [55](#)
- make_train, [56](#)
- max_rm, [56](#)
- mds, [57](#), [80](#), [136](#)
- mean_rm, [58](#)
- median_rm, [58](#)
- min_rm, [59](#)
- mode_rm, [59](#)
- mp3, [60](#)
- mutate_each, [60](#)
- n_missing, [62](#)
- newspaper, [61](#)
- normalize, [61](#)
- nrprint, [62](#)
- p05, [63](#)
- p10, [63](#)
- p25, [64](#)
- p75, [64](#)
- p90, [65](#)
- p95, [65](#)
- performance, [17](#), [66](#), [80](#), [81](#), [137](#)
- pivotr, [54](#), [55](#), [67](#), [81](#), [138](#)
- plot.ann, [7](#), [68](#), [94](#), [124](#)
- plot.compare_means, [23](#), [68](#), [125](#)
- plot.compare_props, [24](#), [69](#), [126](#)
- plot.conjoint, [25](#), [70](#), [126](#), [152](#)
- plot.correlation_, [29](#), [71](#), [128](#)
- plot.cross_tabs, [29](#), [71](#), [129](#)
- plot.crs, [72](#), [129](#)
- plot.dtree, [34](#), [35](#), [73](#), [131](#)
- plot.full_factor, [40](#), [74](#), [74](#), [132](#)
- plot.glm_predict, [43](#), [74](#), [76](#), [95](#), [133](#)
- plot.glm_reg, [43](#), [75](#), [76](#), [76](#), [95](#), [133](#)
- plot.goodness, [44](#), [77](#), [134](#)
- plot.hier_clus, [44](#), [78](#), [135](#)
- plot.kmeans_clus, [48](#), [79](#), [121](#), [136](#)
- plot.mds, [57](#), [79](#), [136](#)
- plot.performance, [17](#), [66](#), [80](#), [137](#)
- plot.pivotr, [81](#)
- plot.pmap, [82](#), [93](#), [138](#)
- plot.pre_factor, [83](#), [97](#), [139](#)
- plot.prob_binom, [83](#)
- plot.prob_chisq, [84](#)
- plot.prob_disc, [84](#)
- plot.prob_expo, [85](#)
- plot.prob_fdist, [85](#)
- plot.prob_norm, [86](#)
- plot.prob_pois, [86](#)
- plot.prob_tdist, [87](#)
- plot.prob_unif, [87](#)
- plot.reg_predict, [89](#)
- plot.regression, [88](#), [89](#), [96](#), [105](#), [145](#)
- plot.repeater, [90](#)
- plot.simulator, [90](#), [115](#), [147](#)
- plot.single_mean, [91](#), [117](#), [148](#)
- plot.single_prop, [92](#), [118](#), [149](#)
- pmap, [82](#), [93](#), [138](#)
- pre_factor, [83](#), [96](#), [139](#)
- predict.ann, [7](#), [68](#), [94](#), [124](#)
- predict.glm_reg, [43](#), [75](#), [76](#), [94](#), [123](#), [133](#)
- predict.regression, [88](#), [89](#), [95](#), [105](#), [124](#), [145](#)
- print.gtable, [97](#)
- prob_binom, [83](#), [98](#), [140](#)
- prob_chisq, [84](#), [98](#), [140](#)
- prob_disc, [84](#), [99](#), [141](#)
- prob_expo, [85](#), [99](#), [141](#)
- prob_fdist, [85](#), [100](#), [142](#)
- prob_norm, [86](#), [100](#), [142](#)
- prob_pois, [86](#), [101](#), [143](#)
- prob_tdist, [87](#), [101](#), [143](#)
- prob_unif, [87](#), [102](#), [144](#)
- publishers, [102](#)
- radiant, [103](#)
- radiant-package (radiant), [103](#)
- radiant_analytics, [103](#)
- radiant_base, [103](#)
- radiant_marketing, [104](#)
- radiant_quant, [104](#)
- recode, [104](#)
- regression, [88](#), [89](#), [96](#), [104](#), [124](#), [144](#), [145](#)
- repeater, [90](#), [105](#), [145](#)
- rndnames, [106](#)
- sample_size, [107](#), [146](#)
- sampling, [108](#), [146](#), [147](#)
- save_factors, [109](#)
- save_membership, [109](#)

saver, 108
 sd_rm, 111
 sdp_rm, 110
 sdw, 110
 serr, 111
 set_class, 112
 shopping, 112
 show_duplicated, 112
 sig_stars, 113
 sim_cleaner, 115
 sim_splitter, 116
 sim_summary, 116
 simulator, 91, 114, 129, 130, 147
 single_mean, 91, 92, 117, 148
 single_prop, 92, 118, 148, 149
 skew, 119
 square, 119
 sshh, 119
 sshhr, 120
 standardize, 120
 store, 121
 store.kmeans_clus, 48, 79, 110, 121, 136
 store_ann, 122
 store_crs, 122
 store_glm, 123
 store_reg, 123
 sum_rm, 149
 summary.ann, 7, 68, 94, 124
 summary.compare_means, 23, 69, 125
 summary.compare_props, 24, 69, 125
 summary.conjoint, 25, 70, 126, 152
 summary.conjoint_profiles, 26, 33, 37, 127
 summary.correlation_, 29, 71, 128
 summary.cross_tabs, 29, 72, 128
 summary.crs, 73, 129
 summary.doe, 130
 summary.dtree, 34, 35, 73, 130
 summary.explore, 36, 131
 summary.full_factor, 40, 132
 summary.glm_reg, 43, 75, 95, 133
 summary.goodness, 44, 77, 134
 summary.hier_clus, 44, 78, 135
 summary.kmeans_clus, 48, 79, 121, 135
 summary.mds, 57, 80, 136
 summary.performance, 17, 66, 81, 137
 summary.pivotr, 54, 55, 81, 137
 summary.pmap, 82, 93, 138
 summary.pre_factor, 83, 97, 139
 summary.prob_binom, 140
 summary.prob_chisq, 140
 summary.prob_disc, 141
 summary.prob_expo, 141
 summary.prob_fdist, 142
 summary.prob_norm, 142
 summary.prob_pois, 143
 summary.prob_tdist, 143
 summary.prob_unif, 144
 summary.regression, 88, 89, 96, 105, 144
 summary.repeater, 145
 summary.sample_size, 107, 146
 summary.sampling, 108, 146
 summary.simulator, 115, 147
 summary.single_mean, 91, 92, 117, 148
 summary.single_prop, 92, 118, 148
 superheroes, 150

 table2data, 150
 test_specs, 151
 the_table, 151
 titanic, 152
 titanic_pred, 152
 toothpaste, 153

 update_radiant, 153

 var_check, 154
 var_rm, 155
 varp_rm, 153
 viewdata, 155
 visualize, 156

 weighted.sd, 157
 which.pmax, 158
 which.pmin, 158
 win_launcher, 49, 159

 xtile, 159