SELECT with various clause – BETWEEN, IN, Aggregate function

```
mysql> CREATE TABLE Student (
    ->     Student_ID INT PRIMARY KEY,
    ->     Name VARCHAR(30),
    ->     Department VARCHAR(20),
    ->     Age INT,
    ->     Marks INT,
    ->     City VARCHAR(20)
    -> );
Query OK, 0 rows affected (0.02 sec)

mysql> INSERT INTO Student VALUES
    -> (101, 'Arun', 'CSE', 20, 85, 'Chennai'),
    -> (102, 'Bala', 'ECE', 21, 75, 'Madurai'),
    -> (103, 'Charan', 'CSE', 19, 90, 'Chennai'),
    -> (104, 'Divya', 'IT', 20, 65, 'Coimbatore'),
    -> (105, 'Eswar', 'ECE', 22, 80, 'Salem'),
    -> (106, 'Farah', 'IT', 21, 95, 'Madurai'),
    -> (107, 'Gokul', 'CSE', 20, 70, 'Salem'),
    -> (108, 'Hari', 'MECH', 23, 60, 'Chennai');
Query OK, 8 rows affected (0.01 sec)
Records: 8  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM Student;
+------------+--------+------------+------+-------+------------+
| Student_ID | Name   | Department | Age  | Marks | City       |
+------------+--------+------------+------+-------+------------+
|        101 | Arun   | CSE        |   20 |    85 | Chennai    |
|        102 | Bala   | ECE        |   21 |    75 | Madurai    |
|        103 | Charan | CSE        |   19 |    90 | Chennai    |
|        104 | Divya  | IT         |   20 |    65 | Coimbatore |
|        105 | Eswar  | ECE        |   22 |    80 | Salem      |
|        106 | Farah  | IT         |   21 |    95 | Madurai    |
|        107 | Gokul  | CSE        |   20 |    70 | Salem      |
|        108 | Hari   | MECH       |   23 |    60 | Chennai    |
+------------+--------+------------+------+-------+------------+
8 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM Student
    -> WHERE Marks BETWEEN 70 AND 90;
+------------+--------+------------+------+-------+---------+
| Student_ID | Name   | Department | Age  | Marks | City    |
+------------+--------+------------+------+-------+---------+
|        101 | Arun   | CSE        |   20 |    85 | Chennai |
|        102 | Bala   | ECE        |   21 |    75 | Madurai |
|        103 | Charan | CSE        |   19 |    90 | Chennai |
|        105 | Eswar  | ECE        |   22 |    80 | Salem   |
|        107 | Gokul  | CSE        |   20 |    70 | Salem   |
+------------+--------+------------+------+-------+---------+
5 rows in set (0.00 sec)

mysql> SELECT * FROM Student
    -> WHERE Department IN ('CSE', 'IT');
+------------+--------+------------+------+-------+------------+
| Student_ID | Name   | Department | Age  | Marks | City       |
+------------+--------+------------+------+-------+------------+
|        101 | Arun   | CSE        |   20 |    85 | Chennai    |
|        103 | Charan | CSE        |   19 |    90 | Chennai    |
|        104 | Divya  | IT         |   20 |    65 | Coimbatore |
|        106 | Farah  | IT         |   21 |    95 | Madurai    |
|        107 | Gokul  | CSE        |   20 |    70 | Salem      |
+------------+--------+------------+------+-------+------------+
5 rows in set (0.00 sec)

mysql> SELECT COUNT(*) AS Total_Students
    -> FROM Student;
+----------------+
| Total_Students |
+----------------+
|              8 |
+----------------+
1 row in set (0.01 sec)
```

```
mysql> SELECT SUM(Marks) AS Total_Marks
    -> FROM Student;
+-------------+
| Total_Marks |
+-------------+
|         620 |
+-------------+
1 row in set (0.00 sec)

mysql> SELECT AVG(Marks) AS Average_Marks
    -> FROM Student;
+---------------+
| Average_Marks |
+---------------+
|       77.5000 |
+---------------+
1 row in set (0.00 sec)

mysql> SELECT MAX(Marks) AS Highest_Marks
    -> FROM Student;
+---------------+
| Highest_Marks |
+---------------+
|            95 |
+---------------+
1 row in set (0.00 sec)

mysql> SELECT MIN(Marks) AS Lowest_Marks
    -> FROM Student;
+--------------+
| Lowest_Marks |
+--------------+
|           60 |
+--------------+
1 row in set (0.00 sec)
```