

see: examples.swing.misc.DialogExample

```
JFrame frame = new JFrame();
JOptionPane.showMessageDialog(frame,
    "Eggs are not supposed to be green.",
    "Inane warning",
    JOptionPane.WARNING_MESSAGE);
```



```
JFrame frame = new JFrame();
JOptionPane.showMessageDialog(frame,

"Eggs are not supposed to be green.",

"Inane warning",

"OptionPane.WARNING_MESSAGE)

JOptionPane.ERROR_MESSAGE

JOptionPane.PLAIN_MESSAGE
```



```
JFrame frame = new JFrame();
JOptionPane.showMessageDialog(frame,
"Eggs are not supposed to be green.",
"Inane warning",
JOptionPane.WARNING_MESSAGE

JOptionPane.ERROR_MESSAGE

JOptionPane.PLAIN_MESSAGE

JOptionPane.PLAIN_MESSAGE
```

```
JFrame frame = new JFrame();
ImageIcon icon = createImageIcon("calvin.jpg");
JOptionPane.showMessageDialog(frame,
    "Eggs are not supposed to be green.",
    "Inane custom dialog",
    JOptionPane.INFORMATION_MESSAGE,
    icon);
```



Pialog - showOptionPialog

```
JFrame frame = new JFrame();
int n = JOptionPane.showOptionDialog(frame,
    "Would you like some green eggs to go with that ham?",
    "A Silly Question",
    JOptionPane.YES_NO_CANCEL_OPTION,
    JOptionPane.QUESTION_MESSAGE,
null,
null,
null);
```



see: examples.swing.misc.DialogExample

Pialog - showOptionPialog

```
JFrame frame = new JFrame();
int n = JOptionPane.showOptionDialog(frame,

"Would you like some green eggs to go with that ham?",

"A Silly Question",


"OptionPane.YES_NO_CANCEL_OPTION,

JOptionPane.QUESTION_MESSAGE,

null,

null,

null);
```





Pialog - showOptionPialog


```
Object[] options1 = { "Yes, please", "No, thanks","No eggs, no ham!" };
JFrame frame = new JFrame();
int n = JOptionPane.showOptionDialog(frame,
        "Would you like some green eggs to go with that ham?",
        "A Silly Question",
        JOptionPane.YES_NO_CANCEL_OPTION,
        JOptionPane.QUESTION_MESSAGE,
    null,
        options,
        options[2]);
```



see: examples.swinq.misc.DialogExample


Pialog - showInputPialog


```
Object[] possibilities = { "ham", "spam", "yam" };
JFrame frame = new JFrame();
String s = (String) JOptionPane.showInputDialog(frame,
   "Complete the sentence:\n" + "\"Green eggs and...\"",
   "Customized Dialog",
   JOptionPane.PLAIN_MESSAGE,
   null,
   possibilities,
   "ham"
   );
```



Pialog - showInputPialog

```
Object[] possibilities = { "ham", "spam", "yam" };
JFrame frame = new JFrame();
String s = (String) JOptionPane.showInputDialog(frame,
   "Complete the sentence:\n" + "\"Green eggs and...\"",
   "Customized Dialog",
   JOptionPane.PLAIN_MESSAGE,
   null,
        null
   possibilities,
   "ham"
   );
```





Example: Confirmar Salida

```
private void initGUI() {
     JButton quit = new JButton("Quit");
quit.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) { quit(); }
      });
     mainPanel.add(quit);
     this.setDefaultCloseOperation(JFrame.DO_NOTHING_ON_CLOSE);
this.addWindowListener(new WindowListener() {
    public void windowClosing(WindowEvent e) { quit(); }
      });
private void quit() {
     int n = JOptionPane.showOptionDialog(new JFrame(),
"Are sure you want to quit?", "Quit",
JOptionPane.YES_NO_OPTION, JOptionPane.QUESTION_MESSAGE, null,
                  null, null);
     if (n == 0) {
            // finalize your app
            System.exit(0);
```

Example: Confirmar Salida

```
private void initGUI() {
                                                                                      Al hacer click sobre el botón
                                                                                      Quit llamamos a 'quit'
     JButton quit = new JButton("Quit");
     quit.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) { quit(); }
     mainPanel.add(quit);
     this.setDefaultCloseOperation(JFrame.DO_NOTHING_ON_CLOSE);
this.addWindowListener(new WindowListener() {
    public void windowClosing(WindowEvent e) { quit(); }
     });
private void quit() {
     int n = JOptionPane.showOptionDialog(new JFrame(),
"Are sure you want to quit?", "Quit",
JOptionPane.YES_NO_OPTION, JOptionPane.QUESTION_MESSAGE, null,
                null, null);
     if (n == 0) {
          // finalize your app
System.exit(0);
```

Example: Confirmar Salida

```
private void initGUI() {
                                                                               Al hacer click sobre el botón
                                                                               Quit llamamos a 'quit'
    JButton quit = new JButton("Quit");
    quit.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) { quit(); }
    mainPanel.add(quit);
    this.setDefaultCloseOperation(JFrame.DO_NOTHING_ON_CLOSE); this.addWindowListener(new WindowListener() { public void windowClosing(WindowEvent e) { quit(); }
     });
                                                               Llamar a 'quit' también al cerrar la
                                                               ventana usando el icono x en la esquina ..
private void quit() {
    int n = JOptionPane.showOptionDialog(new JFrame(),
"Are sure you want to quit?", "Quit",
JOptionPane.YES_NO_OPTION, JOptionPane.QUESTION_MESSAGE, null,
              null, null);
    if (n == 0) {
         // finalize your app
System.exit(0);
```

see: examples.swing.misc.DialogExample_1